

Question 1

```
In [3]: from functionLibrary import gaussj

matrix = open("q1-matrix.txt", "r+")

M = []
N = []

for row in matrix:
    e1 = row.split()
    fe1 = []
    for i in range(len(e1)-1):
        fe1.append(float(e1[i]))
    M.append(fe1)
    e2 = row.split()
    N.append(float(e2[len(e1)-1]))

print("The solution of the given system of equations is:")

gaussj(M,N)

The solution of the given system of equations is:
[2.000000000000001, -1.3322676295501878e-15, 5.999999999999999, 5.0]
```

Question 2

```
In [4]: from functionLibrary import gaussj

matrix = open("q2-matrix.txt", "r+")

M = []
N = []

for row in matrix:
    e1 = row.split()
    fe1 = []
    for i in range(len(e1)-1):
        fe1.append(float(e1[i]))
    M.append(fe1)
    e2 = row.split()
    N.append(float(e2[len(e1)-1]))

print("The solution of the given system of equations is:")

gaussj(M,N)

The solution of the given system of equations is:
[1.0, -2.0, -1.0]
```

Question 3

```
In [5]: from functionLibrary import inverse

matrix = open("q3-matrix.txt", "r+")

M = []
for row in matrix:
    e1 = row.split()
    fe1 = []
    for i in range(len(e1)):
        fe1.append(float(e1[i]))
    M.append(fe1)

print("The inverse of the given matrix is: ")

inverse(M)

The inverse of the given matrix is:
-0.3333333333333333 0.3333333333333333 0.3333333333333333
-0.16666666666666663 0.16666666666666666 0.6666666666666666
1.3333333333333333 -0.3333333333333333 -1.3333333333333333
```

Question 4

```
In [6]: from functionLibrary import determinant

matrix = open("q4-matrix.txt", "r+")

M = []
for row in matrix:
    e1 = row.split()
    fe1 = []
    for i in range(len(e1)):
        fe1.append(float(e1[i]))
    M.append(fe1)

print("The determinant of the given matrix is: ")

determinant(M)

The determinant of the given matrix is:
65.0
```