

Introduction to Operating Systems

Organized By: Vinay Arora
Assistant Professor
CSED, TU

Disclaimer

This is NOT A COPYRIGHT MATERIAL

Content has been taken mainly from the following books:

Operating Systems Concepts By Silberschatz & Galvin,
Operating Systems: Internals and Design Principles By William Stallings

www.os-book.com

www.cs.jhu.edu/~yairamir/cs418/os2/sld001.htm

www.personal.kent.edu/~rmuhamma/OpSystems/os.html


[http://msdn.microsoft.com/en-us/library/ms685096\(VS.85\).aspx](http://msdn.microsoft.com/en-us/library/ms685096(VS.85).aspx)

<http://www.computer.howstuffworks.com/operating-system6.htm>


<http://williamstallings.com/OS/Animations.html>

Etc...

Computer System Organization




Operating System - Layered View




Operating System - Definition

- A Program that acts as an intermediary between a user of a computer and the computer hardware.
- Operating system goals:
 - Execute user programs and make solving user problems easier.
 - Make the computer system convenient to use.
- Use the computer hardware in an efficient manner.

Various OS



Abstract View




Operating System – Def.

- OS is a *RESOURCE ALLOCATOR*
 - Manages all resources
 - Decides between conflicting requests for efficient and fair resource use
- OS is a *CONTROL PROGRAM*
 - Controls execution of programs to prevent errors and improper use of the computer


Operating Systems can be Classified as Follows:

- **Multi-user :** Allows two or more users to run programs at the same time. Some operating systems permit hundreds or even thousands of concurrent (parallel) users.
- **Multiprocessing :** Supports running a program on more than one CPU.
- **Multitasking :** Allows more than one program to run concurrently.
- **Multithreading :** Allows different parts of a single program to run concurrently.
- **Real Time:** Responds to input instantly.

Multiprogramming



Memory Layout for Multiprogramming System



Operating System Structure

Multiprogramming needed for efficiency

- Single user cannot keep CPU and I/O devices busy at all times
- Multiprogramming organizes jobs (code and data) so CPU always has one to execute
- A subset of total jobs in system is kept in memory
- One job selected and run via **job scheduling**
- When it has to wait (for I/O for example), OS switches to another job

Multitasking (or Time Sharing)



Vinay Arora
CSED, TU

Multitasking (or Time Sharing) Conti...



MULTITASKING


Because we needed another word for "unable to focus on the task at hand"

© 2010 by the author
www.vinayarora.com

Time Sharing

- Timesharing (multitasking) is logical extension in which CPU switches jobs so frequently that users can interact with each job while it is running, creating interactive computing
 - Each user has at least one program executing in memory \Rightarrow process
 - If several jobs ready to run at the same time \Rightarrow CPU scheduling
 - If processes don't fit in memory, swapping moves them in and out to run
 - Virtual memory allows execution of processes not completely in memory

Multiprocessing




Job/CPU Scheduling

- *Job Scheduling* – Choosing the job among several jobs are ready to be brought into Memory when there is not enough room for all of them. (Bringing the particular job into ready queue)
- *CPU Scheduling* – Choosing the job among the several when jobs are ready to run at the same time. (Allocation of CPU to particular job)


Caching

- Important principle, performed at many levels in a computer (in hardware, operating system, software)
- Information in use copied from slower to faster storage temporarily
- Faster storage (cache) checked first to determine if information is there
 - If it is, information used directly from the cache (fast)
 - If not, data copied to cache and used there
- Cache smaller than storage being cached
 - Cache management important design problem
 - Cache size and replacement policy


Migration of Integer A from Disk to Register




Transition from User to Kernel Mode



Compiling & Running C Program




Levels for OS Functionality




Types of System Calls

- Process Control
- File Management
- Device Management
- Information Maintenance
- Communications

System Call Interface




Kernel - View



Kernel

- The Central module of an Operating System.
- It is the part of the Operating System that loads first, and it remains in main memory.
- kernel grants device access through System Calls.
- Kernel32.dll is the 32-bit Dynamic Link Library found in the Windows Operating System Kernel.
- It handles Memory Management, Input/Output Operations, and Interrupts.


Kernel - View



Operating-System Operations

- Dual-mode operation allows OS to protect itself and other system components
 - User mode and kernel mode
 - Mode bit provided by hardware
 - Provides ability to distinguish when system is running user code or kernel code
 - Some instructions designated as privileged, only executable in kernel mode
 - System call changes mode to kernel, return from call resets it to user

Transition from User to Kernel Mode



Timer

- Timer to Prevent Infinite Loop / Process hogging resources
 - Set interrupt after specific period
 - Operating system increments / decrements counter
 - Set up before scheduling process to regain control or terminate program that exceeds allotted time

Process Management Activities

- Creating and deleting both user and system processes
- Suspending and resuming processes
- Providing mechanisms for process synchronization
- Providing mechanisms for process communication
- Providing mechanisms for deadlock handling

Memory Management

- All data in memory before and after processing
- All Instructions in memory in order to execute
- Memory Management determines what is in memory when
 - Optimizing CPU utilization and computer response to users
- Memory Management activities
 - Keeping track of which parts of memory are currently being used and by whom
 - Deciding which processes (or parts thereof) and data to move into and out of memory
 - Allocating and deallocating memory space as needed

Mass-Storage Management

- Usually disks used to store data that does not fit in main memory or data that must be kept for a “long” period of time.
- Proper Management is of central importance
- Entire Speed of computer operation hinges on disk subsystem and its algorithms
- OS Activities
 - Free-Space Management
 - Storage Allocation
 - Disk Scheduling


Protection and Security

- Protection – any mechanism for controlling access of processes or users to resources defined by the OS
- Security – defense of the system against internal and external attacks
 - Huge range, including denial-of-service, worms, viruses, identity theft, theft of service
- Systems generally first distinguish among users, to determine who can do what
 - User identities (user IDs, security IDs) Group ID Privilege escalation allows user to change to effective ID with more rights

Computing Environments

- Client-Server Computing

- Compute-server provides an interface to client to request services (i.e. database)
- File-server provides interface for clients to store and retrieve files



Peer-to-Peer Computing

- Another model of distributed system
- P2P does not distinguish clients and servers
 - Instead all nodes are considered peers
 - May each act as client, server or both
- Node must join P2P network
 - Registers its service with central lookup service on network, or
 - Broadcast request for service and respond to requests for service via discovery protocol

Computer Start Up

- **BOOTSTRAP PROGRAM** is loaded at power-up or reboot
 - Typically stored in ROM or EEPROM, generally known as firmware
 - Initialize all aspects of system
 - Loads operating system kernel and starts execution



Thnx...

*Vinay Arora,
CSED, Thapar University, Patiala*

Vinay Arora
CSED, TU