ShopEase API doc (draft v0.9 - DO NOT SHARE externally)

last updated by dev team... some sections pending. base url is api.shopease.example.com/v1 (staging: stg-api.shopease.example.com/v1/ ?)

Note: all apis need token except login & products. Send 'Authorization' header. content-type json. there is also x-request-id which is optional i think.

APIs list

Name	URL	Type
login	/auth/login	post
Users	/users , /users/{id}	GET/POST/PUT/DELETE
product listing	/products	Get
Orders	/orders	POST
order status	/order/{orderId}/status	patch?

1) Login

POST /auth/login - used to login the user and get token. Pass email and password in body (both mandatory). Password should be min 8 char. Returns accessToken (string), tokenType, expiresIn (number of seconds) and user object having id and name.
headers - Content-Type: application/json , Accept: application/json
errors: 400 if something missing, 401 wrong creds

Response:

```
{"accessToken": "eyJhbGciOiJIUzI1NiIs...", "tokenType": "Bearer", "expiresIn": 3600, "user": {
"id": 1024, "name": "Priya Raman"}}
```

2. Create user [POST] /users

admin only!!

Field	dtype	Mandatory?	Req/Resp	Comments
name	String	Y	req	2-100 chars
email	str	Y	req	must be unique
phone		N	req	E.164 format
role	enum	yes	Req	CUSTOMER/ADMIN
isActive	bool		req	default true
id	int	-	resp	
name, email, role	same as above		resp	
createdAt	datetime	-	response	ISO

returns 201. 409 when email exists, 400 validation

```
sample: {"id":1025,"name":"Arjun
Mehta","email":"arjun.mehta@example.com","role":"CUSTOMER","createdAt":"2026-10-23T10:15:30Z"}
```

Get User GET /users/:userId
path param userId (number). headers: Authorization Bearer token, Accept

Response fields -

id	integer	user id
name	string	
email	string	email address of user
Phone		phone no
role	string	CUSTOMER | ADMIN
isActive	Boolean	
address	obj	contains city, pincode (both string)

Status: 200 / 401 / 404

```
{
    "id": 1024,
    "name": "Priya Raman",
    "email": "priya.raman@example.com",
    "phone": "+919876543210",
    "role": "CUSTOMER",
    "isActive": true,
    "address": {
        "city": "Chennai",
        "pincode": "600042"
    }
}
```

Update user (PUT /users/{userId})

Request body:
• name - required
• phone - optional
• address.city
• address.pincode (6 digits)
Response -> id (int), name, updatedAt (timestamp)
`eg response {"id": 1024, "name": "Priya R. Raman", "updatedAt": "2026-10-23T11:02:10Z"}`
TODO: add error codes

DELETE /users/{userId} → soft delete, admin only. returns message + deletedId. 403 if not admin, 404 not found. e.g. {"message":"User deleted successfully","deletedId":1025}

PRODUCTS

Get /products (no auth needed)

Description	Name	Kind	Type
filter by category	category	query	String
min price	minPrice	query	number
max price	maxPrice	query	decimal?
page no, default 1	page	query	int
page size default 20 max 100	size	query	
current page	page	response	int
	size	response	int
total products	totalItems	response	int
list of products - each has productId, name, price(INR), inStock	items	response	array

Sample o/p:


```
{"page": 1, "size": 2, "totalItems": 48, "items": [{"productId": "SKU-1001", "name": "Wireless
Mouse", "price": 799.0, "inStock": true}, {"productId": "SKU-1002", "name": "USB-C Hub",
"price": 1899.5, "inStock": false}]}
```


400 if filters invalid

Orders module

Create Order - post /orders
Headers: same as others + Idempotency-Key (uuid, required to avoid duplicate orders)

REQUEST	
items	array
items.productId	string
items.qty	int 1-10
paymentMode	UPI/CARD/COD
coupon_code	optional

RESPONSE	
orderId	string
status	PLACED
totalAmount	decimal
currency	INR
estimatedDelivery	date

codes - 201 created, 400, 409 (out of stock), 422 bad coupon


```
{"orderId":"ORD-20261023-5521","status":"PLACED","totalAmount":2498.5,"currency":"INR","estimatedDelivery":"2026-10-28"}
```


Get Order Details

GET /orders/{id} - returns order with items. (fields - refer sample, will document later)


```
{
  "orderId": "ORD-20261023-5521",
  "userId": 1024,
  "status": "PLACED",
  "items": [
    {
      "productId": "SKU-1001",
      "quantity": 1,
      "lineTotal": 799.0
    },
    {
      "productId": "SKU-1003",
      "quantity": 1,
      "lineTotal": 1699.5
    }
  ],
  "totalAmount": 2498.5,
  "createdAt": "2026-10-23T12:40:05Z"
}
```


403 if order is of another user, 404 not found

update order status - PATCH /orders/{orderId}/status (ADMIN)
body: status (SHIPPED / DELIVERED / CANCELLED) mandatory, remarks optional max 250. response gives orderId, previousStatus, currentStatus, updatedAt. Invalid transition gives 400. also 403, 404.


```
ex: {"orderId": "ORD-20261023-5521", "previousStatus": "PLACED", "currentStatus": "SHIPPED", "updatedAt": "2026-10-24T09:00:00Z"}
```


-- end of doc -- pls contact backend team for missing info