

# Traffic Sign Detection in Colour Images

Marvin Klaus<sup>1</sup>, Daniela Schacherer<sup>2</sup>

<sup>1</sup>Heidelberg University, M.Sc. Applied Computer Science

<sup>2</sup>Heidelberg University, M.Sc. Applied Computer Science

## Problem Definition

Our project compares two state-of-the-art approaches towards the detection of traffic signs in color images. The first approach uses a linear classifier, more precisely a support vector machine (SVM), based on Histogram of oriented gradients (HOG) features. The second approach employs a region-based convolutional neural network (R-CNN). Our training set was made available by the University of Bochum in the context of a traffic sign detection competition in 2013 [**Houben-IJCNN-2013**]. It comprises 900 images ( $1360 \times 800$  pixels) containing 1206 traffic signs. In addition, the image sections containing only the traffic signs and a CSV file containing ground truth information (location of the traffic signs within the images) are provided.





## Approach 1: SVM based on HOG features

### Data Preprocessing

- Preparation of positive image patches ( $30 \times 30$  pixels) showing traffic signs.
- Preparation of negative image patches ( $30 \times 30$  pixels) showing something that is not a sign.

### Feature extraction

- Extraction of HOG features from the positive and negative image patches using a HOG implementation from scikit [**scikithog**].



### Training

- Fit the SVM to the prepared training data.
- Hard negative mining: apply the trained SVM to some of the training images - obtained with a sliding window of  $30 \times 30$  pixels size and a step size of 10 pixels at different scales. Each falsely detected patch is taken and explicitly added as a negative example to the training set.
- Fit the SVM using the enlarged training data.

### Detection of traffic signs in an image

- Slide a window of  $30 \times 30$  pixels size with a predefined step size (here: 5 pixels) across the image at different scales and obtain a prediction for every image section from the SVM.

## Results SVM

**Performance Measure:** Each predicted bounding box  $P$  is compared against every ground-truth  $G$  using the Jaccard similarity (intersection over union):

$$S(P, G) = \frac{|P \cap G|}{|P \cup G|}$$

When  $S \geq 0.6$ , the ground truth sign is considered as detected. Finally we record the fraction of detected ground truth signs in all images.




**Result:** The amount of correctly found traffic signs on 30 images from the train respectively test set obtained with and without HNM is shown in the following table.

	train acc	test acc
w/o HNM	93.05 %	89.17 %
w HNM	85.56 %	79.17 %

## Approach 2: R-CNN

### Data Preprocessing



- Create negative image patches by taking samples from traffic scenes without signs
- Create train and test dataloader with following partition

### Network



- Loss function: Cross Entropy Loss
- Optimizer: Adam

## Comparison

### Comparison

The network of course is much faster when it comes to classify if something is a traffic sign or not. The downside is that the selective search algorithm takes much time to define interesting regions. From accuracy perspective ...

## Results R-CNN



- Selective Search to find interesting regions
  - parameter: scale=300 and sigma=0.8
- Run network with every region to get signs
- Same measurement as in SVM approach to find positive results