Solstice® 454C

10673042

Version 1.3	Date of first issue 01/22/2025	Revision Date 02/17/2026	Print Date 06/22/2026

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product information

Trade name	:	Solstice® 454C
Number	:	000000026327
Recommended use of the chemical and restrictions on use	:	Refrigerant
Manufacturer or supplier's details	:	Solstice Trading (Shanghai) Co., Ltd. No.69 Xi Ya Rd, Shanghai, 31 200131 China
For further information, please contact:	:	800-522-8001 +1-973-455-6300 (Monday-Friday, 9:00am-5:00pm)
In case of emergency call	:	**Medical: 1 866-479-8788 or +1 303-739-1378**
	:	**Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887** **In Thailand: 1800014808In Thailand: 1800014808**

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification of the substance or mixture	:	Gases under pressure, Liquefied gas Flammable gases, Category 1

GHS Label elements, including precautionary statements

Symbol(s) :



Signal word : Danger

Hazard statements : Extremely flammable gas.
Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Response:
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Eliminate all ignition sources if safe to do so.

Storage:
Protect from sunlight. Store in a well-ventilated place.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
2,3,3,3-Tetrafluoroprop-1-ene 2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	78.50 %
Difluoromethane Difluoromethane	75-10-5	21.50 %

4. FIRST AID MEASURES

General advice : First aider needs to protect himself.

Move out of dangerous area.
Take off all contaminated clothing immediately.

Inhalation : Remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Use oxygen as required, provided a qualified operator is present.
Call a physician.

Skin contact : Rapid evaporation of the liquid may cause frostbite.
If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering.
Wash contaminated clothing before re-use.
Consult a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
In case of frostbite water should be lukewarm, not hot.
Call a physician.

Ingestion : Unlikely route of exposure.
As this product is a gas, refer to the inhalation section.
Do not induce vomiting without medical advice.
If conscious, drink plenty of water.
Never give anything by mouth to an unconscious person.
Call a physician immediately.

Notes to physician : Treat frost-bitten areas as needed.
Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : In case of fire, allow gas to burn if flow cannot be shut off immediately.
Apply water from a safe distance to cool container and protect surrounding area.

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards during firefighting : Flammable gas.
Contents under pressure.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
Fire or intense heat may cause violent rupture of packages.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen fluoride
Carbonyl halides
Carbon monoxide
Carbon dioxide (CO2)

Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

Further information : Evacuate personnel to safe areas.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
Eliminate all ignition sources if safe to do so.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Wear self-contained breathing apparatus and protective suit.
Eliminate all ignition sources if safe to do so.
Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is >= 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.
Discharge into the environment must be avoided.

Methods and materials for containment and cleaning up : Use explosion-proof equipment.
No sparking tools should be used.
Ventilate the area.
Allow to evaporate.

7. HANDLING AND STORAGE

Handling

Precautions for safe handling : Handle with care.
Wear personal protective equipment.
Do not breathe vapor.
Avoid contact with skin, eyes and clothing.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, or expose them to open flame or excessive heat.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion	:	Container hazardous when empty. Vapours may form flammable mixture with air. Keep product and empty container away from heat and sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Take measures to prevent the build up of electrostatic charge. Electrical equipment should be protected to the appropriate standard. Use explosion-proof equipment. No sparking tools should be used. No smoking.

Storage

Conditions for safe storage, including any incompatibilities	:	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Storage rooms must be properly ventilated. Ensure adequate ventilation, especially in confined areas. Protect cylinders from physical damage. Store away from incompatible substances. Store in original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis

2,3,3,3-Tetrafluoroprop-1-ene 2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	TWA : Time weighted average	(500 ppm)	03 15 2010	Solstice:Limit established by Solstice Advanced Materials
		STEL : Short term exposure limit	(1,500 ppm)	03 15 2010	Solstice:Limit established by Solstice Advanced Materials
		TWA : Time weighted average	(500 ppm)	2009	WEEL:US Workplace Environmental Exposure Level
Difluoromethane Difluoromethane	75-10-5	TWA : Time weighted average	(1,000 ppm)	1994	Solstice:Limit established by Solstice Advanced Materials
		TWA : Time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US Workplace Environmental Exposure Level

Appropriate engineering controls

Use with local exhaust ventilation.

Individual protection measures, such as personal protective equipment (PPE)

Respiratory protection	:	No personal respiratory protective equipment normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use NIOSH approved respiratory protection.
Hand protection	:	Protective gloves Gloves must be inspected prior to use. Replace when worn.
Eye protection	:	Safety goggles
Skin and body protection	:	Avoid skin contact with leaking liquid (danger of frostbite). Wear suitable protective equipment.
Protective measures	:	Ensure that eyewash stations and safety showers are close to the workstation location. Do not breathe vapor. Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	Liquefied gas
Colour	:	colourless
Odour	:	slight ether-like
Odour Threshold	:	Note: No data available
pH	:	Note: neutral
Melting point/freezing point	:	Note: No data available
Boiling point/boiling range	:	Note: No data available

Flash point	:	Note: Not applicable
Evaporation rate	:	Note: No data available
Lower flammability limit	:	7.7 %(V)
Upper flammability limit	:	15.7 %(V)
Vapour pressure	:	871.9 kPa at 21 °C(70 °F)
Vapour density	:	Note: No data available
Density	:	Note: No data available
Water solubility	:	Note: No data available
Partition coefficient: n-octanol/water	:	Note: No data available
Ignition temperature	:	444 °C
Viscosity, dynamic	:	Note: No data available
Viscosity, kinematic	:	Note: No data available
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

10. STABILITY AND REACTIVITY

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Keep away from heat and sources of ignition. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. To avoid thermal decomposition, do not overheat. Some risk may be expected of corrosive and toxic decomposition products.
Incompatible materials to avoid	:	Alkali metals Oxidizers (e.g. peroxide residues present in insufficiently cured rubbers) Finely divided metal powders such as aluminum, magnesium, or zinc.
Hazardous decomposition products	:	In case of fire hazardous decomposition products may be produced such as: Hydrogen fluoride Carbonyl halides Carbon monoxide Carbon dioxide (CO2)

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	:	Inhalation, Eye contact, Skin contact
Acute oral toxicity	:	Note: No data available
Acute inhalation toxicity	:	Note: No data available
Acute dermal toxicity	:	Note: No data available

Skin corrosion/irritation	:	Note: No data available
Serious eye damage/eye irritation	:	Note: No data available
Skin sensitisation 2,3,3,3-Tetrafluoroprop-1-ene	:	Note: Not applicable, as this product is a gas. study technically not feasible
Respiratory or skin sensitisation Difluoromethane	:	Cardiac sensitization Species: dogs Note: No-observed-effect level >350 000 ppm
Repeated dose toxicity 2,3,3,3-Tetrafluoroprop-1-ene	:	Species: Rat Application Route: Inhalation Exposure time: (2 Weeks) No-observed-effect level: 50000 ppm Method: OECD Test Guideline 412 Species: Rat Application Route: Inhalation Exposure time: (4 Weeks) NOAEL (No observed adverse effect level): 50000 ppm Method: OECD Test Guideline 412 Species: Rat Application Route: Inhalation Exposure time: (13 Weeks) NOAEL (No observed adverse effect level): 50000 ppm Method: OECD Test Guideline 413 Species: Rabbit, male Application Route: Inhalation Exposure time: (28 d) No-observed-effect level: 500 ppm

Method: OECD Test Guideline 412
There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Rabbit, female
Application Route: Inhalation
Exposure time: (28 d)
No-observed-effect level: 1000 ppm
Method: OECD Test Guideline 412
There are no observed toxicological effects, which result in classification as a specific target organ toxicant.

Species: Mini-pig
Application Route: Inhalation
Exposure time: (28 d)
NOAEL (No observed adverse effect level): 10000 ppm
highest exposure tested

Difluoromethane : Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Germ cell mutagenicity : Note: No data available

Germ cell mutagenicity
2,3,3,3-Tetrafluoroprop-1-ene : Test Method: Unscheduled DNA synthesis
Dose: up to 50,000 ppm (4 weeks)
Method: OECD Test Guideline 486
Result: negative

: Species: Rat
Cell type: Micronucleus
Dose: up to 50,000 ppm (4 weeks)
Method: OECD Test Guideline 474
Result: negative

Difluoromethane	:	Species: Mouse Cell type: Bone marrow Method: Mutagenicity (micronucleus test) Result: negative
Carcinogenicity	:	Note: No data available
Reproductive toxicity 2,3,3,3-Tetrafluoroprop-1-ene	:	Species: Rat Application Route: Inhalation exposure Exposure time: Two-generation reproductive toxicity NOAEL,parent: 50,000 ppm NOAEL,F1: 50,000 ppm NOAEL,F2: 50,000 ppm
Reproductive toxicity	:	Note: No data available
Teratogenicity 2,3,3,3-Tetrafluoroprop-1-ene	:	Species: Rat Dose: NOAEL (No observed adverse effect level) - 50,000 ppm Species: Rabbit Dose: NOAEL (No observed adverse effect level) - 4,000 ppm
Difluoromethane	:	Species: Rat Dose: NOEL - 50,000 ppm Note: Did not show teratogenic effects in animal experiments. Species: Rabbit Dose: NOEL - 50,000 ppm Note: Did not show teratogenic effects in animal experiments.
Specific target organ toxicity	:	Note :No data available

- single exposure

Specific target organ toxicity - repeated exposure : Note :No data available

12. ECOLOGICAL INFORMATION

Aquatic and ecotoxicity

Toxicity to fish : Note: No data available

Toxicity to daphnia and other aquatic invertebrates

2,3,3,3-Tetrafluoroprop-1-ene : EC50: > 83 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

Toxicity to algae : Note: No data available

Toxicity to bacteria : Note: No data available

Persistence and degradability

Biodegradability : Note: No data available

Bioaccumulative potential

Bioaccumulation : Note: No data available

Mobility in soil

Mobility : Note: No data available

Biochemical Oxygen Demand (BOD)	:	Note: No data available
Chemical Oxygen Demand (COD)	:	Note: No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods	:	In accordance with local and national regulations.

14. TRANSPORT INFORMATION

ADR

UN/ID No.	:	UN 3161
Description of the goods	:	LIQUEFIED GAS, FLAMMABLE, N.O.S. (R-1234yf, DIFLUOROMETHANE)
Class	:	2
Classification Code	:	2F
Hazard Identification Number	:	23
Labels	:	2.1

IATA

UN/ID No.	:	UN 3161
Description of the goods	:	Liquefied gas, flammable, n.o.s. (R-1234yf, Difluoromethane)
Class	:	2.1
Labels	:	2.1
Packing instruction (cargo aircraft)	:	200

IATA_P

UN/ID No.	:	UN 3161
Class	:	2.1 Not permitted for transport

IMDG

UN/ID No.	:	UN 3161
Description of the goods	:	LIQUEFIED GAS, FLAMMABLE, N.O.S.

(R-1234yf, DIFLUOROMETHANE)

Class	:	2.1
Labels	:	2.1
EmS Number 1	:	F-D
EmS Number 2	:	S-U
Marine pollutant	:	no

15. REGULATORY INFORMATION

National regulatory information

: No information available.

Other international regulations

Notification status

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended	:	All substances listed as active on the TSCA inventory
Australian Inventory of Industrial Chemicals	:	All components are listed on the inventory, regulatory obligations/restrictions apply
Canada. Domestic Substances List (DSL), as amended	:	All components of this product are on the Canadian DSL
Japan. Kashin-Hou Law List	:	On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)	:	On the inventory, or in compliance with the inventory
Philippines. Inventory of Chemicals and Chemical Substances (PICCS)	:	On the inventory, or in compliance with the inventory
China. Inventory of Existing Chemical Substances (IECSC)	:	On the inventory, or in compliance with the inventory
Thailand. Existing Chemicals Inventory from FDA (TECI List)	:	On the inventory, or in compliance with the inventory
Taiwan Chemical Substance Inventory (TCSI)	:	On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

		HMIS III	NFPA
Health hazard	:	1	2
Flammability	:	4	4
Physical Hazard	:	1	
Instability	:		0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.
Previous Issue Date: 08/24/2025
Revision Date: 02/17/2026
Version 1.3
Issuing date 01/22/2025
Person who prepared the SDS Solstice Product Stewardship Group