

Freelance Job Manager Backend

Bogdan A. Constantin

May 11, 2016

Contents

1	Installing and Running the Server	3
2	Updating the Server	3
3	Method Reference	3
3.1	Session Methods	3
3.1.1	Login	3
3.2	User Methods	4
3.2.1	User Registration	4
3.2.2	Read User	4
3.2.3	List Users	4
3.2.4	Delete User	5
3.3	Freelancer Methods	5
3.3.1	Freelancer Registration	5
3.3.2	Read Freelancer	5
3.3.3	List Freelancers	5
3.3.4	Delete Freelancer	6
3.4	JobType Methods	6
3.4.1	Create Job Type	6
3.4.2	Read Job Type	6
3.4.3	List Job Types	6
3.4.4	Delete Job Type	7
3.5	Location Methods	7
3.5.1	Create Location	7
3.5.2	Read Location	7
3.5.3	List Locations	7
3.5.4	Delete Location	8
3.6	Job Methods	8

3.6.1	Job Statuses	8
3.6.2	Create Job Request	8
3.6.3	Read Job	8
3.6.4	List User Jobs by Status	8
3.6.5	List Freelancer Jobs by Status	9
3.6.6	List Open Jobs by JobType	9
3.6.7	List Open Jobs by JobType and Location Area	9
3.7	Subscription Methods	9
3.7.1	Subscribe Freelancer	9
3.7.2	List Job subscriptions	10
3.7.3	List Freelancer Subscriptions	10

1 Installing and Running the Server

- Unzip the archive (don't create a new folder)
- cd into the FreeJobServer directory
- Run start.bat. java.exe must be installed and on the path. If not, please edit start.bat and use the full java.exe path.

2 Updating the Server

- To stop the server enter **stop 0** on the console and then press ENTER.
- Unpack the update archive into the /bundle directory.
- Delete **felix-cache** directory
- Restart the server

3 Method Reference

The REST servlet is accessible at the following URL: localhost:48080/freejob
Each method URL must be prefixed with this string.

3.1 Session Methods

3.1.1 Login

POST /sessions/login Login as a customer or freelancer. Sample payload for customer login:

```
{
  "role" : "CUSTOMER",
  "email" : "bogdan.constantin@itsix.com",
  "password" : "mypassword"
}
```

RESPONSE Sample for a customer login.

```
{
  "data": {
    "sessionId": "e8599496-7099-41b7-a554-65dfd38e02f2",
  }
}
```

```

    "user": {
      "id": "5a6a7a5b-a66c-4cb8-bc61-14dea633a8ca",
      "firstName": "Bogdan",
      "lastName": "Constantin ITSIX",
      "email": "bogdan.constantin@itsix.com",
      "role": "CUSTOMER",
      "password": null
    },
    "created": 1461337503669
  },
  "success": true,
  "message": null
}

```

3.2 User Methods

3.2.1 User Registration

POST /users/register Register a new user. Sample payload:

```

{
  "firstName" : "Bogdan",
  "lastName" : "Constantin",
  "email" : "bogdan.constantin@itsix.com",
  "password" : "mypassword",
}

```

3.2.2 Read User

GET /users/{userId} Read user.

3.2.3 List Users

GET /users List all users. Sample response:

```

{
  "data": [
    {
      "id": "5fd2124b-3cf9-434a-97df-5b0af469a9f2",
      "firstName": "Bogdan",
      "lastName": "Constantin",
      "email": "bogdan.constantin@itsix.com",
    }
  ]
}

```

```

        "role": "USER",
        "password": null
    }
],
"success": true,
"message": null
}

```

3.2.4 Delete User

DELETE /users/{userId} Delete a user.

3.3 Freelancer Methods

3.3.1 Freelancer Registration

POST /freelancers/register Register a new freelancer. Sample payload:

```

{
    "jobTypeId": "60243132-4316-4400-86aa-7b17c866584b",
    "firstName": "Bogdan",
    "lastName": "Constantin",
    "email": "bogdan.constantin@itsix.com",
    "password": "some password",
}

```

3.3.2 Read Freelancer

GET /freelancers/{freelancerId} Read freelancer.

3.3.3 List Freelancers

GET /freelancers List all freelancers. Sample response:

```

{
    "data": [
        {
            "id": "baf538a8-fbbe-4bdf-bc83-7819f60b0d62",
            "jobTypeId": "60243132-4316-4400-86aa-7b17c866584b",
            "firstName": "Bogdan",
            "lastName": "Constantin",
            "email": "bogdan.constantin@itsix.com",
            "password": null,
        }
    ]
}

```

```

        "address": null,
        "latitude": null,
        "longitude": null,
        "city": null,
        "county": null,
        "avgRating": 0,
        "bankName": null,
        "accountNumber": null
    }
],
"success": true,
"message": null
}

```

3.3.4 Delete Freelancer

DELETE /freelancers/{freelancerId} Delete a freelancer.

3.4 JobType Methods

3.4.1 Create Job Type

POST /jobtypes Create a new job type. Sample payload:

```

{
  "name" : "Baby-Sitter",
  "description" : "Takes care of babies",
  "commission": 2.5
}

```

3.4.2 Read Job Type

GET /jobtypes/{jobTypeId} Read job type.

3.4.3 List Job Types

GET /jobtypes List all job types. Sample response:

```

{
  "data": [
    {
      "id": "60243132-4316-4400-86aa-7b17c866584b",
      "name": "Baby-Sitter",

```

```

        "description": "Takes care of babies",
        "commission" : 2.5
    }
],
"success": true,
"message": null
}

```

3.4.4 Delete Job Type

DELETE /jobtypes/{jobTypeId} Delete a job type.

3.5 Location Methods

3.5.1 Create Location

POST /users/{userId}/locations Create a new location for a user.

Sample payload:

```

{
  "name" : "Home",
  "address" : "Traian Lalescu 25",
  "city" : "Craiova",
  "county" : "Dolj",
  "latitude" : 44.318266,
  "longitude" : 23.825482
}

```

3.5.2 Read Location

GET /users/{userId}/locations/{locationId} Read a location.

3.5.3 List Locations

GET /users/{userId}/locations List all locations of a user. Sample response:

```

{
  "data": [
    {
      "id": "364b5a88-6ebe-43da-8ebb-0035e1305d5a",
      "name" : "Home",
      "userId": "5a6a7a5b-a66c-4cb8-bc61-14dea633a8ca",

```

```

        "address": "Traian Lalescu 25",
        "city": "Craiova",
        "county": "Dolj",
        "latitude": 44.318266,
        "longitude": 23.825482
    }
],
"success": true,
"message": null
}

```

3.5.4 Delete Location

DELETE /users/{userId}/locations/{locationId} Delete a location for a user.

3.6 Job Methods

3.6.1 Job Statuses

Valid Job statuses are OPEN, ACCEPTED, ONGOING, FINISHED, PAYMENT_REQUESTED, BILLED, CANCELLED

3.6.2 Create Job Request

POST /users/{userId}/jobs Create a new job request for a user. Sample payload:

```

{
    "title" : "Baby sitter request",
    "description" : "Need baby sitter for a 5 yr old.",
    "jobTypeId" : "e0d136eb-8e33-426d-aef3-a66ce5c668de",
    "locationId" : "364b5a88-6ebe-43da-8ebb-0035e1305d5a"
}

```

3.6.3 Read Job

GET /users/{userId}/jobs/{jobId} Read job

3.6.4 List User Jobs by Status

GET /users/{userId}/jobs?status={status} List all jobs of a user. Optionally, a status may be specified.

3.6.5 List Freelancer Jobs by Status

GET /freelancers/{freelancerId}/jobs?status={status} List all jobs of a freelancer. Optionally, a status may be specified.

3.6.6 List Open Jobs by JobType

GET /jobtypes/{jobTypeId}/jobs List all open jobs of a specific type.

3.6.7 List Open Jobs by JobType and Location Area

GET /jobtypes/{jobTypeId}/jobs/latitude/{latitude}/

longitude/{longitude}/range/{range} List all open jobs of a specific type by location coordinates and a range in km.

Sample response:

```
{
  "data": [
    {
      "id": "6ec322a1-c190-4386-a17f-5ff9cb87b01c",
      "status": "OPEN",
      "title": "Baby sitter request",
      "description": "",
      "created": 1462883463063,
      "rating": 0,
      "jobTypeId": "e0d136eb-8e33-426d-aef3-a66ce5c668de",
      "freelancerId": null,
      "userId": "5a6a7a5b-a66c-4cb8-bc61-14dea633a8ca",
      "locationId": "364b5a88-6ebe-43da-8ebb-0035e1305d5a"
    }
  ],
  "success": true,
  "message": null
}
```

3.7 Subscription Methods

3.7.1 Subscribe Freelancer

POST /freelancers/{freelancerId}/jobs/{jobId}/subscriptions Subscribe to a job.

Sample payload:

```
{
    "message" : "Some message from the freelancer"
}
```

3.7.2 List Job subscriptions

GET /users/{userId}/jobs/{jobId}/subscriptions List all subscriptions to a job

Sample response:

```
{
  "data": [
    {
      "jobId": "6ec322a1-c190-4386-a17f-5ff9cb87b01c",
      "freelancerId": "e0d136eb-8e33-426d-aef3-a66ce5c668de",
      "message": "Some message from the freelancer"
    }
  ],
  "success": true,
  "message": null
}
```

3.7.3 List Freelancer Subscriptions

GET /freelancers/{freelancerId}/subscriptions List all freelancer subscriptions

```
{
  "data": [
    {
      "jobId": "6ec322a1-c190-4386-a17f-5ff9cb87b01c",
      "freelancerId": "e0d136eb-8e33-426d-aef3-a66ce5c668de",
      "message": "Some message from the freelancer"
    }
  ],
  "success": true,
  "message": null
}
```