



M2000 Controller

The most advanced controller platform for managing DC systems in all types of telecom environments.

Key Features :

- Powerful controller built on RTOS
- 2.2" high resolution color display and easy to use navigation via joystick.
- Site automation and renewable hybrid support.
- Li-ion battery support and advanced battery management features
- Ethernet for local or remote monitoring via secure web browser and optional modem
- User configurable analog and Boolean logic alarms.
- User configurable performance logging, event logging and energy data logging
- USB Interface for configuration file update and log download.
- Multi language support
- Global compliance

Applications :

- Telecom : Base station sites, LTE/WiMax, hub sites, renewable hybrid sites, and central offices.
- Smart Cities : Smart poles, surveillance etc.
- Power utilities : Control & Protection and communication equipment.
- Railways : Signaling, communication equipment and control & protection.

M2000 Controller – Technical Specifications

Operating Voltage	36–60Vdc
Power Consumption	4W (Nominal)
Dimension (h x w x d)	43 x 111 x 130 (mm)
Operating Environment	–20°C to 60°C; humidity : 95% RH, non-condensing
Compliances	+ Safety Standards EN 60950–1, IEC 60950–1 and UL 60950–1 + Environmental ETSI 300 019 –1, –2, –3 + RoHS Compliant, REACH, EMC Certified Conducted Emission as per CISPR 32, Radiated Emission as per CISPR 32 (Class B), ESD, EFT, Radiated immunity, Continuous conducted RF and Surge. UL file number E505627. M2000 is UL & CE marked.

Battery	+ Float, boost and equalise charge modes, configurable battery temperature compensation, manual charge mode. + Low voltage disconnect and under voltage pre-warning. + Back up time and SoC monitoring. + Automatic battery health test, battery isolation for maintenance, symmetry supervision. + Li-ion battery support, settable charge profiles and communication with battery BMS.
System	+ AC Voltage measurement, grid power / phase failure detect + Integrated support for renewable (solar) hybrid system. + Site automation control, DG control and monitoring . + Alarm grouping, alarm output mapping and alarm naming. + User configurable analog alarm engine and boolean logic alarms. + User profile configuration & password protection. + Application and configuration update locally or remotely, offline configuration tool. + Support for up to 5 battery and 4 load LVDs.
Rectifiers	+ Individual rectifier current , temperature and status monitoring + Power limited walk in, configurable power control in case of controller communication loss + Linear or cyclic rectifier sleep mode automatically as well as manually configurable for system efficiency + Active current sharing and system overload monitoring + Support for up to 120 rectifiers.
Number of IO's supported	4
Voltage sensing	Bus Voltage + 5 channels, $\pm 72V$
Current sensing	3 channels, $\pm 50mV$
Temperature sensing	2 channels, $-20^{\circ}C$ to $100^{\circ}C$
LVD control	3 , NO/NC, 10A@60VDC
Digital inputs	8, optoisolated
Relay outputs	8, NO / NC, 1 form C, 1A@48Vdc Up to 10,000 event logs, performance logs on SD card or internal memory based on user configurable parameters 1,000 change logs and energy & run hour logs for grid , battery and DG
System control bus	2x CAN V2.0b for communication with rectifiers and system units
Serial bus	2 x RS 485, modbus RTU master & device modes
Modem interface	1x RS 232, modem interface for remote monitoring over GPRS /GSM and SMS alarms.
Display	2.2" , 320 x 240 resolution, 65k colour TFT, w / intensity control and power save mode , Joystick, multi-language support.
Ethernet	10/100 Base T, MDI / MDI-X, IP protocols, HTTP, HTTPS, SNMP V2c / V3, SNTP, FTP, IPV4, IPV6 (Static, Stateless & State full, DHCPV6
USB	USB 2.0, Type A, USB Flash Drive support
Web Interface	HTML 5, Java script based secure web interface, encrypted w/TLS
SNMP	SNMP V2c / V3, Get / Get Bulk / Set / TRAPS, multiple user profile
E-mail	Severity & time based alarm reporting along with system parameters.
Modem	Alarm SMS for GSM and data monitoring over GPRS
Hardware	Configurable alarm group mapping to PFC
Part Number	HE 513240
Part description	EMA Controller M 2000-2C2 RMSB V 34.10

Mobility Solutions



DC Telecom Solutions



ESS Solutions



INDIA

Plot No 38, Institutional Area, Sector 32, Gurugram, Haryana 122001, India
cpsales.india@exicom.in

AFRICA

Business Center 1, M Floor, The Meydan Hotel, Nad Al Sheba, Dubai, U.A.E.
cpsales.africa@exicom.in

MIDDLE EAST

Business Center 1, M Floor, The Meydan Hotel, Nad Al Sheba, Dubai, U.A.E.
cpsales.mea@exicom.in

SOUTH EAST ASIA COUNTRY

No 23, Jalan Linggis 15/24, Taman Perindustrian Linggis, Seksyen 15, 40200
Shah AlamSelangor, Malaysia
cpsales.sea@exicom.in

SAUDI ARABIA

14181, 8667 King Fahad Road Olaya, Riyadh 12611 , Saudi Arabia
cpsales.sa@exicom.in