

Grade transition legend — elevation to inches, nearest 1/8"

Elevation (ft) × 12 = transition in inches from datum. A leading – means the point is BELOW datum (step down); no sign means ABOVE datum (step up).

Example: pt. 167, –0.650 ft → –0.650 × 12 = –7.8 in. → step DOWN 7 3/4 in.

Pt.	Type	Elev. ft	in.	1/8 in.
3	Shoring	–0.637	7.6	–7 5/8
4	new	0.200	2.4	2 3/8
5	test	0.000	0.0	0
6	new	0.159	1.9	1 7/8
7	new	0.200	2.4	2 3/8
8	new	0.250	3.0	3
9	new	0.000	0.0	0
10	new	0.010	0.1	1/8
11	new	0.245	2.9	3
13	new	0.167	2.0	2
14	new	0.159	1.9	1 7/8
15	new	0.159	1.9	1 7/8
16	new	0.200	2.4	2 3/8
18	new	0.200	2.4	2 3/8
19	new	0.213	2.6	2 1/2
20	new	0.066	0.8	3/4
21	new	0.240	2.9	2 7/8
22	new	0.169	2.0	2
23	TC	0.229	2.7	2 3/4
24	new	0.256	3.1	3 1/8
25	new	0.200	2.4	2 3/8
26	new	0.205	2.5	2 1/2
28	new	0.200	2.4	2 3/8
29	new	0.200	2.4	2 3/8
30	new	0.000	0.0	0
31	new TC	0.279	3.3	3 3/8
?	new	0.250	3.0	3
33	new TC	0.250	3.0	3
34	new	0.090	1.1	1 1/8
100	EP	0.102	1.2	1 1/4
101	EP	0.066	0.8	3/4
102	EP	0.019	0.2	1/4
103	EP	0.087	1.0	1
104	EP	0.169	2.0	2
105	EP	0.166	2.0	2
106	EP	0.121	1.5	1 1/2
107	EP	0.111	1.3	1 3/8
108	EP	0.078	0.9	7/8
109	EP	–0.056	0.7	–5/8
110	EP	–0.145	1.7	–1 3/4
111	EP	–0.110	1.3	–1 3/8

Pt.	Type	Elev. ft	in.	1/8 in.
112	EP	–0.020	0.2	–1/4
113	EP	–0.104	1.2	–1 1/4
114	MS	–0.085	1.0	–1
115	MS	–0.055	0.7	–5/8
116	MS	–0.040	0.5	–1/2
117	MS	0.005	0.1	0
118	MS	0.048	0.6	5/8
119	MS	0.097	1.2	1 1/8
120	MS	0.060	0.7	3/4
121	MS	0.058	0.7	3/4
122	MS	0.027	0.3	3/8
123	MS	0.049	0.6	5/8
124	MS	–0.034	0.4	–3/8
125	TC	0.247	3.0	3
126	TC	0.235	2.8	2 7/8
127	TC	0.239	2.9	2 7/8
128	TC	0.304	3.6	3 5/8
129	TC	0.254	3.0	3
130	TC	0.159	1.9	1 7/8
131	SW	0.056	0.7	5/8
132	SW	0.043	0.5	1/2
133	SW	0.308	3.7	3 3/4
134	SW	0.201	2.4	2 3/8
135	SW	0.194	2.3	2 3/8
136	SW	0.093	1.1	1 1/8
137	SW	0.170	2.0	2
138	SW	0.077	0.9	7/8
139	SW	0.001	0.0	0
140	SW	0.019	0.2	1/4
141	SW	0.106	1.3	1 1/4
142	SW	0.152	1.8	1 7/8
143	SW	0.193	2.3	2 3/8
144	SW	0.124	1.5	1 1/2
145	SW	0.026	0.3	1/4
147	SW	0.007	0.1	1/8
148	SW	0.102	1.2	1 1/4
149	SW	–0.071	0.9	–7/8
150	SW	0.107	1.3	1 1/4
151	AC	0.008	0.1	1/8
152	AC	–0.036	0.4	–3/8
153	AC	0.001	0.0	0

Pt.	Type	Elev. ft	in.	1/8 in.
154	Shoring	–0.448	5.4	–5 3/8
155	Apron	–0.054	0.6	–5/8
156	Shoring	–0.728	8.7	–8 3/4
157	Shoring	–0.629	7.5	–7 1/2
158	Shoring	–0.656	7.9	–7 7/8
159	Shoring	–0.599	7.2	–7 1/4
160	Shoring	–0.682	8.2	–8 1/8
161	Shoring	–0.700	8.4	–8 3/8
162	apron	–0.042	0.5	–1/2
163	Shoring	–0.668	8.0	–8
164	apron	–0.052	0.6	–5/8
165	Shoring	–0.682	8.2	–8 1/8
166	apron	–0.019	0.2	–1/4
167	Shoring	–0.650	7.8	–7 3/4
168	Shoring	–0.676	8.1	–8 1/8
169	Shoring	–0.610	7.3	–7 3/8
170	Shoring	–0.621	7.5	–7 1/2
171	Shoring	–0.602	7.2	–7 1/4
172	Shoring	–0.632	7.6	–7 5/8
173	Shoring	–0.656	7.9	–7 7/8
174	Shoring	–0.604	7.2	–7 1/4
175	Shoring	–0.571	6.9	–6 7/8
176	Shoring	–0.559	6.7	–6 3/4
177	apron	0.020	0.2	1/4
178	Shoring	–0.544	6.5	–6 1/2
179	Shoring	–0.475	5.7	–5 3/4
180	apron	0.147	1.8	1 3/4
181	Shoring	–0.535	6.4	–6 3/8
182	Shoring	–0.612	7.3	–7 3/8
183	Shoring	–0.639	7.7	–7 5/8
184	Shoring	–0.587	7.0	–7
185	Shoring	–0.572	6.9	–6 7/8
186	Shoring	–0.636	7.6	–7 5/8
187	Shoring	–0.558	6.7	–6 3/4
188	Shoring	–0.561	6.7	–6 3/4
189	Shoring	–0.454	5.4	–5 1/2
190	apron	0.114	1.4	1 3/8
191	apron	0.131	1.6	1 5/8
192	apron	0.133	1.6	1 5/8
193	Shoring	–0.468	5.6	–5 5/8
194	Shoring	–0.437	5.2	–5 1/4

Pt.	Type	Elev. ft	in.	1/8 in.
195	Shoring	–0.437	5.2	–5 1/4
196	Shoring	–0.491	5.9	–5 7/8
197	Shoring	–0.461	5.5	–5 1/2
198	Shoring	–0.368	4.4	–4 3/8
199	Shoring	–0.445	5.3	–5 3/8
200	Shoring	–0.414	5.0	–5
201	Shoring	–0.367	4.4	–4 3/8
202	Shoring	–0.378	4.5	–4 1/2
203	Shoring	–0.430	5.2	–5 1/8
204	Shoring	–0.515	6.2	–6 1/8
205	Shoring	–0.462	5.5	–5 1/2
206	Shoring	–0.422	5.1	–5 1/8
207	Shoring	–0.384	4.6	–4 5/8
208	Shoring	–0.380	4.6	–4 1/2
209	Shoring	–0.358	4.3	–4 1/4
210	Shoring	–0.378	4.5	–4 1/2
211	Shoring	–0.402	4.8	–4 7/8
212	Shoring	–0.411	4.9	–4 7/8
213	Shoring	–0.379	4.5	–4 1/2
214	Shoring	–0.317	3.8	–3 3/4
215	apron	0.283	3.4	3 3/8
216	Shoring	–0.322	3.9	–3 7/8
217	Shoring	–0.435	5.2	–5 1/4
218	Shoring	–0.453	5.4	–5 3/8
219	Shoring	–0.440	5.3	–5 1/4
220	Shoring	–0.367	4.4	–4 3/8
221	Shoring	–0.354	4.2	–4 1/4
222	Shoring	–0.409	4.9	–4 7/8
223	Shoring	–0.356	4.3	–4 1/4
224	Shoring	–0.403	4.8	–4 7/8
225	Shoring	–0.612	7.3	–7 3/8
226	Shoring	–0.326	3.9	–3 7/8
227	Shoring	–0.357	4.3	–4 1/4
228	apron	0.366	4.4	4 3/8
229	apron	0.283	3.4	3 3/8
230	Tp found	–0.324	3.9	–3 7/8
231	Tp found	0.295	3.5	3 1/2
232	Tp found	0.348	4.2	4 1/8
233	Tp found	0.343	4.1	4 1/8
234	Apron	0.331	4.0	4

163 points. Red point numbers need confirming on site: pts. 101/102 print on top of each other (read as +0.066 / +0.019); the “?” point at +0.250 has an illegible number (most likely pt. 32). Pts. 1, 2, 12, 17, 27 and 146 do not appear on the sheet.

Source: Dock_B_Survey_Surface_II_a (Model). Fractions rounded to the nearest 1/8 in.; use the decimal inch column where tighter tolerance matters.