



Beijing Blood-wing Technology Development

UMEX 2026 · Abu Dhabi National Exhibition Centre (ADNEC)
Dates: 20 – 22 January · Booth: 05-005

Blood—wing Company Snapshot

Beijing Blood—wing Technology Development Co. , Ltd.



Beijing Blood Wing Technology Development Co.,Ltd.is a high-tech enterprise specializing in artificial intelligence robotics for specialized fields,with R&D in Shanghai, production in Shenzhen,and offices in Chengdu.Core focus:

Military Augmented Reality System(MARS).

By integrating AI robotics and tactical **MESH** networks,we develop specialized embodied intelligent agents and achieve "omnipotent connectivity"in mission execution.

"Blood Wing"symbolizes revolutionary heritage, technology-enabled military strength,and civil-military integration.

We build **the Intelligent Squad Ecosystem(ISE)**:MARS as the soldier's information node,MESH as the neural framework, integrated with intelligent unmanned platforms and smart command-and-control systems.

The Intelligent Soldier System (MARS+Tactical Exoskeleton/EXO) is AI-powered,modular,wearable equipment that enhances information capability and physical capability,reducing fatigue while augmenting combat effectiveness.It elevates situational awareness, command and control,networked communications,and sustained operational endurance.MARS uses binocular array wave-guide AR optics to overlay digital imagery onto the real-world view.

Blood—wing MARS

Military Augmented Reality System

Beijing Blood—wing Technology Development Co., Ltd.



Product Presentation :

The Military Augmented Reality System (MARS) is an augmented reality (AR)-based individual combat AI device, mounted on helmets and body armor. It consists of tactical goggles and a tactical terminal, with external connectivity to individual power supplies, tactical ad-hoc networks, and smart sights.

Features:

1. Integrated Remote Control: Single-device operation for all unmanned equipment, no multiple remotes required.
2. Integrated Display: Quick switches between multi-device, night vision/thermal images; simultaneous access to tactical data and command instructions.
3. Easy Gear Integration: Directly mounts on tactical vests for faster response.
4. Touchscreen Marking & Soldier Monitoring: Smartphone-like map marking for real-time team communication; shares soldier location and goggle feeds with command.

Advantages:

Integrates integrated control and multispectral sensing to streamline individual combat coordination. Enhances situational awareness and response speed via integrated display, gear adaptability, and command linkage, with a lightweight, practical design.



Blood-wing MARS

Military Augmented Reality System

Beijing Blood-wing Technology Development Co. , Ltd.

Hardware specifications:

Eyewear	visual display	Optical Module	Field of view 40 / Display brightness>800 / Contrast>200:1 RAONTEC-RDC200A / Optical Waveguide / 1920x1080
	camera	Night Vison	1600*1200 / Field of view 60.4*47.1
		Infrared (vision/imagery)	384*288
		Long ragne Optical	30-degree view
	IMU	9-axis Sensor	3-axis acceleration, 3-axis gyroscope, 3-axis compass
	P-sensor	MCU	Remove glasses to turn off the display and put on a display.
	L-sensor		Adjust backlight
	connecting line		
Host	CPU	RK3588	
	RAM	8G	
	FLASH	128G	
	Show	CGS LCD	LCD /1080P/16:9/1200nits above
	Touch screen	GT911	
	WLAN	802.11ax	Based on platform parameters
	BT	5.X BLE	
	Fixed position	Big Dipper	
	NET		The aviation connector corresponds to the RJ45 definition with 1.25mm spacing terminals.
	USB		data transmission
	HDMI IN	MIPI-CSI	
	Drones Remote	radio-frequency head	
	Michael Feng	3.5-inch connector	
	earphone		
	cell	Lithium battery	
	charge	12V	
	rocking bar		One on each side
	antenna	Big Dipper	
	key	source	Switching on and Off and Turning on the Screen
		Rolling key	Use the arrow keys to move the selection forward or backward. Press the scroll wheel to select or confirm.
		Custom Key	8
		Expand port	Reserve Stitches
OS	Android	12	Replace with HarmonyOS

Blood—wing

Quadruped Robot CRW 40

Beijing Blood—wing Technology Development Co., Ltd.



Features:

1. High-speed mobility: Adopts a unique coordinated wheel-leg gait design, enabling efficient wheeled sliding on flat roads and flexible gait adaptation on complex terrain, with a movement speed far exceeding conventional legged robot dogs.
2. Super heavy load capacity: As the only heavy-duty wheel-legged robot dog on the market, it has extremely strong load-bearing capacity, capable of stably carrying various equipment and supplies to meet heavy-load operation needs.
3. Strong terrain adaptability: Independently switches between wheeled and legged movement modes, balancing high-speed travel on flat roads and passability on complex terrain for full-scene adaptation.
4. Flexible and efficient movement: Can perform precise actions such as turning and in-place rotation, with lower energy consumption and higher operation efficiency compared to pure wheeled/legged robots.
5. Multi-functional expansion: Reserved modular interfaces, compatible with additional accessories like robotic arms and detection equipment, suitable for inspection, rescue, security and other multi-scene applications.
6. Intelligent autonomous operation: Equipped with environmental perception and path planning systems, realizing autonomous navigation, obstacle avoidance and terrain adaptation without full-time manual control.

Blood-wing

Quadruped Robot CRW 40

Beijing Blood-wing Technology Development Co. , Ltd.



Advantages:

- Heavy-duty quadruped robot with high load capacity.
- Each leg uses 4 axial-flux motors, providing 16 total degrees of freedom. It walks, trots, and adapts to rough terrain.
- Features dual 96-line LiDAR (head/tail) for 360° obstacle avoidance and a wide-angle HD camera for enhanced visual recognition.

Parameter	Specification	Notes
Overall Dimensions (L × W × H)	1180 × 600 × 610 mm	
Speed	5m/s	
Effective Payload	≥ 20 kg	
Weight (incl. battery)	82 kg	
Operating Temperature	− 20 ° C to 55 ° C	
Max Stair/Slope Angle	≤ 45 °	
Endurance (typical)	3 – 8 hours	Mission profile dependent
Ingress Protection	IP66	Dust/Water protection

Blood—wing Powered Exoskeleton System

Beijing Blood—wing Technology Development Co. , Ltd.



BWEXO—PW (Blood—wing Exoskeleton — Powered Waist)



Item	Specification
Dimensions	872mm × (500mm-560mm) × 320mm
Weight	5.6 kg
Power Source	Electric Power Assist Drive
Assist Capacity	15~30 kg (Max support: 40 kg)
Operating Temp	-20℃ ~ 50℃
Operating Time	6~8 hours
Battery	36V Lithium Battery
Degrees of Freedom	4 DoF
Materials	Nylon Engineering Plastic,Aviation Aluminum Alloy, Carbon Fiber

Blood-wing Light Tactical Exoskeleton System

Beijing Blood-wing Technology Development Co. , Ltd.

BWEXO-PU

(Blood-wing Exoskeleton - Powered Upper-Limb)




Item	Parameters
Dimensions	(600mm-680mm) × 572mm × 220mm
Weight	3.75kg
Power Source	Electric Power Assist Drive
Dual-Arm Assist	15~20kg
Operating Temperature	-20℃~50℃
Operating Time	6~8h
Battery	36V Lithium Battery
Degrees of Freedom	8
Materials	Nylon Engineering Plastic, Aviation Aluminum Alloy, Carbon Fiber

BWEXO-PL

(Blood-wing Exoskeleton - Powered Lower-Limb)



46Nm	Specification
Dimensions	400 × 400 × 270mm(folded)
Weight	2.9kg(without battery)
Maximum Assistance	Total 46Nm for both legs
Boosts leg strength	40%
Reduces fatigue	20%
Working Modes	AI Adaptive Mode (supports climbing, walking, running), Impedance Mode (supports descending stairs, downhill, fitness), Cycling Mode
Power Supply Method	Replaceable lithium-ion battery
Operating Temperature	-20 ° C to 65 ° C
Range	Up to 18 km per single battery



Blood-wing Weapon Station

Beijing Blood-wing Technology Development Co. , Ltd.



Product Presentation :

The Weapon Station is a compact, stabilized pan-tilt platform for remote aiming/observation on manned or unmanned ground systems. It integrates a gimbal, drives, and a control terminal with interfaces for external power, secure comms, and smart sights/sensors. (Expo/demo units are non-weaponized for capability display.)

Features:

- 1. Integrated Control: One console for pan/tilt, modes, and status.
- 2. Stabilized, Fast Switching: Smooth traverse/elevation and sensor/reticle swap; smart-sight ready.
- 3. Quick Integration: 10.5 kg module mounts on UGVs, tripods, or vehicle rails.
- 4. Power & Safety: 24 V LiFePO₄ option, standby monitoring, software limits, E-stop tie-in.

Advantages:

360° traverse, ±50° elevation, 60° /s pan, 20° /s tilt in a lightweight aluminum/carbon-fiber build—precise, responsive, and easy to integrate across platforms.

Parameter	Specification
Dimensions (L × W × H)	304 × 326 × 315 mm
Total Weight (Fully Auto/Semi Auto)	10.5 kg
Elevation Angle	± 50 °
Traverse Angle	360 ° (continuous)
Traverse Speed	60 ° /s
Elevation Speed	20 ° /s
Total Power	300 W / 1000 W (typical/peak)
Power Supply	24 V, 12 Ah LiFePO ₄ battery
Standby Time	120 minutes
Body Material	Aluminum alloy / Carbon fiber



Beijing Blood-wing Technology Development

CONTACT US

Booth: 05-005 • ADNEC, Abu Dhabi

Email: JoeyFan@blood-wing.com

Web: www.blood-wing.com