

# Interrater-Reliability\_P3.93.10

Kristen Johnson

2025-03-04

## Load necessary libraries

### read in the two coded transcripts

```
## be sure to change initials for each coder
JB_codes<- read_excel(here("PN_InterraterReliability", "Coded_P3_H10", "P3.93.10_COMPLETE_JB_Final.xls"))

#MCV_codes<- read_excel('~\KristenWorkingDirectory\Play_Narrative\PN_InterraterReliability\Coded_P3_H10')

KJ_codes <- read_excel(here("PN_InterraterReliability", "Coded_P3_H10", "P3.93.10_COMPLETE_KJ_Final.xls"))
```

### if need be, troubleshoot column name discrepancies

```
# rename c_pret to lowercase only
#colnames(JB_codes)[colnames(JB_codes) == "C_pret_JB"] <- "c_pret_JB"
```

### get instances of pretend play (c\_\_pret columns)

### combine datasets into one

```
coded_combined <- cbind(JB_codes, KJ_codes) ## be sure to change initials for each coder!
#coded_combined <- cbind(MCV_codes, KJ_codes)
```

### create columns to assist in calculating IRR

```
# create new columns for "both" and "either"
coded_combined <- coded_combined %>%
  mutate(
    both_ones = ifelse(C_pret_JB == 1 & c_pret_KJ == 1, 1, 0), ## don't forget to change column names a
    either_one = ifelse(C_pret_JB == 1 | c_pret_KJ == 1, 1, 0)
  )
#coded_combined <- coded_combined %>%
# mutate(
#   both_ones = ifelse(c_pret_MCV == 1 & c_pret_KJ == 1, 1, 0),
#   either_one = ifelse(c_pret_MCV == 1 | c_pret_KJ == 1, 1, 0)
#)
```

make sure everything is numerical

```
# change any NA value in both and either columns to 0
coded_combined[, c("both_ones", "either_one")] <- lapply(coded_combined[, c("both_ones", "either_one")]
```

generate interrater reliability score

```
# divide all instances of pretend play by overlap of pp instances
IRR_score <- sum(coded_combined$both_ones)/sum(coded_combined$either_one)

print(IRR_score)
```

```
## [1] 0.9473684
```