

Explicit Context-Driven Development: From Vibe Coding to Verifiable Workflows in AI-Augmented Software Engineering

Murat Karakaya¹

TED University, Ankara, Türkiye
murat.karakaya@tedu.edu.tr,

WWW home page: <https://www.tedu.edu.tr/kasim-murat-karakaya>

Abstract. AI-assisted programming can accelerate delivery, but informal "vibe coding" with large language models (LLMs) often leads to context loss, architectural drift, and weak traceability. We propose Explicit Context-Driven Development (ECDD), a reusable, artifact-centric methodology that externalizes prompts and project state into version-controlled files. ECDD combines (i) Prompt-Driven AI Governance, (ii) Auditable Task & State Management, and (iii) a five-phase workflow (Define, Plan, Elaborate, Scope, Implement) that produces reviewable artifacts (e.g., `project.definition.md`, work packages, and append-only logs) and tool-scoped instructions (e.g., `copilot-instructions.md`). By making intermediate decisions explicit, diffable, and reusable, ECDD aims to reduce context drift and strengthen auditability across planning, specification, and implementation.

Keywords: Explicit Context-Driven Development (ECDD), AI-Assisted Software Engineering, Prompt-Driven AI Governance, Human-AI Collaboration, Auditable Development Workflows, Version-Controlled Context Artifacts

1 Introduction

AI coding tools can accelerate software delivery, but they also introduce coordination and quality risks. Modern large language models (LLMs) can generate substantial code from short prompts, which makes informal "vibe coding" attractive for fast iteration. Empirical studies of AI-assisted programming report perceived productivity impacts and benefits in some settings [2]. Other studies surface code quality concerns [3] and security risks in AI-generated code, including empirical evidence of security weaknesses in Copilot-generated code used in GitHub projects [4] and large-scale comparative analyses across LLMs [12]. As projects grow, this informal style often leads to architectural drift, inconsistent conventions, and weak traceability between intent and implementation.

A practical alternative is to externalize context from transient chat into repository artifacts that can be reviewed, diffed, and maintained with code. In this view, prompts are not ad hoc instructions but durable technical assets that

encode goals, constraints, architecture, and coding rules for both developers and AI tools.

We propose *Explicit Context-Driven Development (ECDD)*, a methodology for AI-assisted development built around a *Five-Phase Workflow* (*Define, Plan, Elaborate, Scope, and Implement*; see Fig. 1). ECDD structures human-AI collaboration through three pillars:

1. **Prompt-Driven AI Governance:** executable prompts and durable governance documents capture project goals, architectural constraints, and coding standards so AI assistance behaves consistently across sessions.
2. **Auditable Task & State Management:** work decomposition and execution history are captured in reviewable artifacts (roadmaps, work package specifications, stepwise checklists, and append-only logs) to preserve traceability from intent to implementation.
3. **Five-Phase Workflow:** each phase reduces uncertainty by transforming free-form intent into template-shaped, reviewable artifacts before coding begins.

This “copilot, not autopilot” stance preserves human oversight while retaining AI speed advantages. ECDD is intended to improve alignment across planning, specification, and implementation, and to help reduce context loss across sessions.

This paper makes three contributions. First, we define ECDD as a concrete methodology grounded in explicit, version-controlled context artifacts. Second, we present reusable workflows and canonical prompt/template assets that operationalize the methodology in practice. Third, we show how the approach decouples project state from any single AI interface, enabling IDE-agnostic adoption (e.g., GitHub Copilot, Cursor, Windsurf).

The remainder of the paper is organized as follows. Section II introduces ECDD and details the prompt-, template-, and artifact-based workflow. Section III provides a brief running example that illustrates the artifact chain end-to-end. Section IV discusses practical lessons, limitations, and threats to validity. Section V concludes and outlines future research directions, including an evaluation agenda.

2 Explicit Context-Driven Development (ECDD)

Explicit Context-Driven Development (ECDD) is a methodology for AI-assisted software development that treats prompts and project context as first-class, version-controlled artifacts. Rather than relying on whichever files are currently visible in an IDE or whatever a model happens to remember from a chat session, ECDD makes context explicit and durable in the repository. Concretely, ECDD is delivered as (i) executable prompts under `.github/prompts/`, (ii) Markdown templates under `templates/` that act as lightweight schemas, and (iii) generated artifacts under `artifacts/` that capture the evolving project state (Fig. 2).

This repository layout given in Fig. 2 is intentional: `‘.github/prompts/’` is the editable governance and workflow entry point (teams adjust prompting and




Fig. 1. ECDD workflow: five phases (Define, Plan, Elaborate, Scope, Implement) and the three supporting pillars with key artifacts.

interview behavior here), ‘templates/’ is the editable contract layer (teams encode project- and company-specific standards in the artifact structure), and ‘artifacts/’ is the persistent project state (generated by agents but explicitly reviewed and edited by developers as the source of truth). When ‘templates/’ or ‘artifacts/’ evolve, teams re-run the Scope prompt to regenerate ‘copilot-instructions.md’ in the ‘.github/’ folder, ensuring downstream coding agents consistently receive the current standards and decisions. This structure operationalizes “contracts over conversation” and supports the traceability chain described below.

In the remainder of this section, we describe ECDD at increasing levels of concreteness: Section 2.1 summarizes the design principles, Section 2.2 specifies the executable prompt contracts, Section 2.4 discusses resource binding, Section 2.5 defines the artifact model and traceability chain, and Section 2.3 walks through the reference workflow end-to-end.

2.1 Design Principles

ECDD is guided by the following design principles: As summarized in Table 1, ECDD replaces ephemeral chat-based context with durable, version-controlled artifacts and schema-constrained outputs.

1. **Repository-as-source-of-truth:** the project definition, plan, specs, and logs live in files that can be diffed, reviewed, and versioned.
2. **Contracts over conversation:** prompts specify what to read and what to produce; templates constrain intermediate artifacts so outputs remain consistent, reviewable, and reusable. Because `templates/` are version-controlled, teams can update them to reflect project requirements or company standards,




Fig. 2. Reference ECDD repository structure (prompts, templates, artifacts) and edit points.

and agents will fill the new structure instead of producing unconstrained free-text documents.

3. **Human-in-the-loop checkpoints:** after each phase, developers review (and may edit) artifacts before moving forward.
4. **Incremental, resumable execution:** implementation is decomposed into checklists; progress is tracked explicitly rather than inferred from chat history.
5. **IDE-agnostic by default, IDE-integrated when available:** the same artifacts can be used in any AI-IDE, while `copilot-instructions.md` in the `.github/` folder provides an integration point for GitHub Copilot in VS Code [1].

Table 1 contrasts these principles with ad hoc ”vibe coding”, highlighting how ECDD systematically addresses the risks of architectural drift and lost context.

2.2 Executable Prompts as Workflow Contracts

The prompts in `.github/prompts/` are designed as small, executable workflow definitions. Each prompt begins with machine-readable metadata (YAML front

Table 1. Comparison of ad hoc “vibe coding” versus Explicit Context-Driven Development (ECDD), showing how persistent artifacts and schemas replace ephemeral chat context.

Feature	Ad hoc “Vibe Coding”	ECDD (Proposed)
Context Source	Ephemeral chat history (lost on reset)	Version-controlled repository artifacts
Governance	None (user-dependent)	Executable prompt contracts & templates
Consistency	High variability (styles drift)	Schema-enforced (strict template adherence)
Traceability	Implicit / nonexistent	Explicit chain (Definition $\rightarrow$ Spec $\rightarrow$ Log)
Collabration Model	Single-player (hard to share context)	Multi-player (Git-reviewable state)

matter) that declares its purpose, role, and I/O contract (e.g., `input_files` and `output_file`). The prompt body then specifies:

1. **Strict template adherence:** the agent must fill the referenced template structure exactly, treating templates as schemas that reduce variability.
2. **Interactive clarification protocol:** when critical information is missing, the agent asks questions one at a time, offers 2–4 options with brief trade-offs and a recommendation, and waits for an answer before continuing.
3. **Explicit completion statements:** each phase ends with a predictable handoff message that points to the created artifact and the next prompt to run.

Template adherence constrains intermediate outputs, reducing drift and enabling lightweight automation. Because templates are version-controlled, they are auditable and can encode evolving standards. This design makes execution auditable: prompts/templates are versioned and artifacts are reviewed like specifications, allowing project state to persist across sessions. Table 2 summarizes the prompts, their inputs/outputs, and the constraints that keep the workflow deterministic.

2.3 Execution Semantics

Beyond I/O, ECDD prompts encode execution semantics that are designed to make interactions predictable and auditable. The first is a clarification protocol: when a prompt detects missing information that would materially affect downstream work, it asks one question at a time, provides a small set of options with trade-offs and a recommended default, and waits for the developer’s response. The developer can then directly revise artifacts before the next prompt consumes them, turning clarification into a version-controlled correction rather than an ephemeral chat detour.

Table 2. ECDD executable prompts (Define–Implement): purpose, inputs/outputs, and constraints for consistency and auditability.

Prompt	Goal	Template	Input File	Outputs
Define	Establish project intent and constraints	project definition	Developer description + clarifications	project definition
Plan	Create dependency-aware roadmap	simple workpackage	project definition	workpackage list
Elaborate	Specify one WP for implementation	complete workpackage	project definition workpackage list + WP ID	workpackage , WP-XXX
Scope	Generate coding-agent guidance	None	Current facts (definition, roadmap, specs)	artificial copilot instructions in .github/
Implement	Execute one WP with audit trail	None	workpackage WP-XXX, log	todos WP-XXX ; append log

Table 3. Prompt front matter fields and their semantics.

Field	Meaning	Example values (from this repo)	Constraints / notes
name	Stable prompt identifier	define-project, plan-roadmap	Should be unique within the prompts folder
description	One-sentence intent	“Generates a high-level roadmap...”	Human readable; should match actual behavior
version	Prompt contract version	1.0.0	Bump when I/O or constraints change materially
role	Agent role framing	“Software Architect”	Should be consistent with expected outputs
input_files	Declared inputs	project_definition.md (artifacts/)	Must include all artifacts/templates the prompt reads
output_file	Single output (legacy)	workpackage_list.md (artifacts/)	Prefer output_files for normalization
output_files	Multiple outputs	todos_WP-XXX.md + append log.md	Useful when a prompt writes more than one file

The second is an explicit completion statement. Each prompt ends by stating which artifact(s) were created or updated and which prompt should be executed next. This acts as a lightweight handoff mechanism that reduces context loss, especially when developers switch tools or resume work later.

2.4 Resource Binding Mechanism

The reference prompts also include a pragmatic binding mechanism for inputs: `#file:` references that point to the relevant templates and artifacts (e.g., `#file:templates/template_project_definition.md`). In IDEs that support file-aware prompts, these directives can be resolved automatically; in simpler chat interfaces, developers can approximate the same behavior by attaching the referenced files or pasting their contents. The key point is not the specific directive syntax, but the contract principle: prompts declare what must be read and what must be produced, so intermediate artifacts remain consistent across tools and sessions.

2.5 Artifact Model and Traceability

Prompt execution produces a small set of human-readable artifacts with clear roles and naming conventions:

1. **Project definition:** `project_definition.md` in the artifacts folder captures MVP scope, architecture, constraints, and risks (generated from project definition template in the templates folder).
2. **Roadmap (work packages):** `workpackage_list.md` in the artifacts folder decomposes the project into Work Packages (WPs) with dependencies and priorities (generated using `template_simple_workpackage.md` in the templates folder). Each WP has a stable identifier such as `WP-001`.
3. **Detailed WP specification:** `workpackage_WP-XXX.md` in the artifacts folder expands a single WP into an executable spec with acceptance criteria, technical contracts, implementation steps, and test requirements (generated from `template_complete_workpackage.md` in the templates folder).
4. **Execution checklist:** `todos_WP-XXX.md` in the artifacts folder tracks step-wise implementation as a Markdown checklist (checked items `[x]` vs. unchecked `[ ]`), enabling resumable work across sessions.
5. **Append-only log:** `log.md` in the artifacts folder records what changed, where, and why, so future agents can avoid rework and maintain continuity when switching work packages.
6. **AI instructions (scoped context):** `copilot-instructions.md` in the `.github/` folder summarizes project context and coding guidelines for coding agents, derived from the current artifacts.

Understood as lightweight schemas for intermediate artifacts, templates standardize outputs and reduce omission risk. For example, the complete work package template requires explicit acceptance criteria, files-to-touch guidance, and verification steps. These fields are deliberately “quality gates” that reduce omission

Table 4. Examples of how template-shaped fields act as lightweight quality controls, reducing variability and omission risk compared to free-form vibe coding artifacts.

Aim	Template	Risk mitigated
In-scope / out-of-scope boundaries	project definition	Prevents scope creep and reduces contradictory implementations
Dependencies and effort/priority fields	workpackage list	Reduces sequencing errors and makes assumptions explicit
Acceptance criteria checklist	workpackage WP-XXX	Prevents under-specification and provides a reviewable definition of done
Files-to-create/modify list	workpackage WP-XXX	Reduces architectural drift and accidental scatter across the codebase
Testing requirements + verification checklist	workpackage WP-XXX	Reduces “done without tests” failure modes; supports repeatable verification
Append-only log structure	change log	Improves post-hoc auditability and continuity across sessions/tools

risk compared to free-form documents produced during vibe coding, and they also make artifact reviews more systematic (e.g., reviewers can scan for missing acceptance criteria or testing requirements).

Template evolution is itself a workflow. Teams can edit templates to encode project- and company-specific standards, re-run the relevant prompt(s) to regenerate artifacts in the updated structure, and review the resulting diffs like code. This operationalizes the **Human-in-the-loop checkpoints** design principle: revisions to templates and artifacts become explicit, auditable changes that deterministically propagate into subsequent planning and implementation steps.

Together, these artifacts form a traceability chain from intent to code: `project_definition.md` → `workpackage_list.md` → `workpackage_WP-XXX.md` → `todos_WP-XXX.md` → `implementation + log.md` (with the chain stored and reviewed under the artifacts folder).

3 Running Example (Walkthrough)

This section provides a brief walkthrough of how the Section II artifacts and prompts interact in practice. Using a small web app example (“AI Concepts Dictionary”), we illustrate the ECDD artifact chain and the human-in-the-loop checkpoints that replace reliance on chat memory.

Define (creates a project definition): After running the Define prompt, the agent produces a first draft of `project_definition.md` in the artifacts folder. The developer reviews and may revise it before planning continues. The excerpt below is illustrative and abridged:

```
# Project Definition (MVP)
```





Fig. 3. Traceability chain and human-in-the-loop revision checkpoints: each phase produces a reviewable artifact, developers can revise it in version control, and subsequent prompts consume the revised state rather than relying on ephemeral chat memory.

Project Essentials

Project Name: AI Concepts Dictionary

What does this project do? A web app that returns structured

→ definitions, examples, and resources for AI concepts.

Who will use it? *arners and practitioners.

Technical Basics

Tech Stack

- Frontend: React + Vite
- Backend: Node.js + Express (API proxy)
- Deployment: local dev + cloud hosting

Constraints & Risks

- Security: do not hard-code API keys; use environment variables
- Known Risks: inconsistent outputs without templates and
- acceptance criteria

Plan (creates a roadmap): Running the Plan prompt converts the (developer-reviewed) project definition into a dependency-aware roadmap saved as `workpackage_list.md` in the artifacts folder:

WP-001 Project scaffold and build system

- Priority: High
- Effort: Small
- Dependencies: None
- Description: Create the repo structure, build scripts, and
- baseline CI/test scaffolding.

WP-002 LLM-backed definition API

- Priority: High
- Effort: Medium
- Dependencies: WP-001
- Description: Implement an API endpoint that queries the
→ configured LLM and returns a structured response.

WP-003 UI: search + results view

- Priority: High
- Effort: Medium
- Dependencies: WP-001, WP-002
- Description: Build the UI input, results layout, and
→ error/loading states.

Elaborate (creates a detailed spec): The developer selects a work package (e.g., WP-002) and runs *Elaborate* to generate `workpackage.WP-002.md`. The artifact is then reviewed and can be revised before any code is written:

WP-002 LLM-backed definition API

Acceptance Criteria

- [] Given a concept string, the API returns a JSON object with
→ fields: definition, examples, resources
- [] API rejects empty input and returns a clear error message
- [] API reads the LLM API key from an environment variable

Technical Specifications

Files to Create/Modify

- `server/src/routes/define.ts`: add POST `/api/define`
- `server/src/llm/client.ts`: wrap LLM calls and retries

Testing Requirements

- Unit tests for input validation and response shape

Scope (generates coding-agent instructions): Once artifacts are reviewed, the developer runs *Scope* to generate `copilot-instructions.md` in the `.github/` folder. This file summarizes the current project context and coding guidelines so coding agents operate from the same explicit state, even when tools or sessions change.

Implement (creates a checklist and append-only log): Finally, the developer runs *Implement* for a selected WP. The agent creates or updates `todos.WP-002.md` (artifacts folder) and appends an entry to `log.md` (artifacts folder). Both artifacts support resumable execution and post-hoc audit:

todos_WP-002.md (excerpt)

- [] Implement request validation and error responses

- [] Implement LLM client wrapper with timeouts and retries
- [] Implement POST /api/define route and response shaping
- [] Add unit tests for validation and response schema
- [] Update log.md with files touched and key decisions

The key methodological feature is the revision loop: after each phase, the developer can correct scope, standards, dependencies, or acceptance criteria directly in version-controlled artifacts, and subsequent prompts consume the revised state as input (Fig. 3). This makes the workflow reproducible across sessions and tools and keeps the developer in control of project intent.

4 Discussion and Limitations

In this paper, we focus on describing the ECDD methodology and workflow; a controlled empirical evaluation is planned as future work. As a result, the discussion below highlights the expected trade-offs: compared to informal vibe coding, ECDD grounds work in reviewable context (prompts, templates, and append-only logs) to reduce drift, but it adds overhead—best justified for longer-lived, multi-contributor, or higher-risk projects.

A second limitation is over-constraint: templates and large governance prompts can reduce omissions but also encourage “checkbox compliance,” miss domain nuance, and obscure the key constraints if they grow unchecked. ECDD therefore relies on treating templates/prompts as living standards—curated like code (refactored and modularized) and validated through human-in-the-loop review—while recognizing that executable prompts also expand the attack surface (e.g., backdoor attacks targeting prompt-engineered code generation) [14].

Finally, ECDD can create a false sense of assurance: plans, logs, and checklists improve auditability but do not guarantee correctness, and storing rich in-repo context can raise confidentiality risks that require access control and redaction. From a tooling perspective, ECDD also assumes teams can manage plain-text artifacts in version control and connect them to AI assistants; while `copilot-instructions.md` is a simple integration point, broader adoption would benefit from IDE support and integrations with CI, issue trackers, and documentation.

5 Related Work

ECDD sits at the intersection of several threads of work on software development practice. From one angle, it can be seen as a pragmatic descendant of specification-driven and model-driven development, but with LLMs in the loop and with a stronger emphasis on treating prompts themselves as artifacts. Like configuration-as-code and infrastructure-as-code approaches [11], it insists that important project knowledge live in version-controlled text files rather than in wikis, tickets, or team folklore. Compared to traditional style guides and architecture decision records (ADRs), ECDD’s governance prompts are more tightly coupled to AI

tools: they are written to be consumed both by developers and by LLMs, and they are referenced explicitly in planning, execution, and verification prompts. This dual audience influences their structure and language, pushing teams toward more precise but still natural-language descriptions of goals, constraints, and patterns. ECDD is also aligned with long-standing concerns in requirements traceability [10], but shifts the traceability chain toward AI-facing, repository-native artifacts that can be consumed directly by prompts and coding agents.

ECDD also connects to a growing body of work on prompting and agentic software engineering. Survey work catalogues prompt patterns and prompting techniques [5, 6], while prompt-based LLM approaches have also been evaluated for requirements engineering tasks such as requirements classification [15]. Agent architectures such as ReAct combine reasoning and tool use to structure multi-step behavior [7]. More recent software engineering agents (e.g., SWE-agent) explicitly separate planning, file reading, editing, and verification steps and are often evaluated on benchmarks such as SWE-bench [8, 9]. ECDD deliberately chooses a different point in this design space: instead of optimizing for autonomy, it assumes human-in-the-loop control and focuses on making collaboration structured, observable, and reviewable by externalizing project state into template-shaped artifacts.

6 Conclusion and Future Work

We introduced Explicit Context-Driven Development (ECDD), a methodology for AI-assisted software development that treats prompts, templates, and project context as first-class, version-controlled artifacts rather than ephemeral chat state. ECDD combines Prompt-Driven AI Governance, Auditable Task & State Management, and a five-phase workflow (Define, Plan, Elaborate, Scope, Implement) into a concrete, repository-based process. Our central claim is that making planning and specification artifacts explicit, template-shaped, and reviewable yields more predictable handoffs while preserving human-in-the-loop control.

Future work includes (i) controlled comparisons against ad hoc AI-assisted development using process/product measures (traceability completeness, rework, defects, and resumability), (ii) richer tool support (IDE/CI/issue-tracker integrations), and (iii) studying how artifact-centric workflows interact with assurance methods and confidentiality constraints.

References

1. GitHub Docs, “Adding repository custom instructions for GitHub Copilot,” 2026. Accessed: 2026-02-15. Available: <https://docs.github.com/en/copilot/customizing-copilot/adding-repository-custom-instructions-for-github-copilot>
2. Ziegler, A., Kalliamvakou, E., Li, X.A., Rice, A., Rifkin, D., Simister, S., Sittampalam, G., Aftandilian, E.: “Measuring GitHub Copilot’s Impact on Productivity,” *Commun. ACM* 67(3), 54–63 (2024). <https://doi.org/10.1145/3633453>
3. Di Penta, M., Panichella, S.: “GitHub Copilot AI pair programmer: Asset or Liability?,” *J. Syst. Softw.* 203, 111734 (2023)

4. Fu, Y., Liang, P., Tahir, A., Li, Z., Shahin, M., Yu, J., Chen, J.: “Security Weaknesses of Copilot-Generated Code in GitHub Projects: An Empirical Study,” *ACM Trans. Softw. Eng. Methodol.* 34(8), Article 218, 1–34 (2025). <https://doi.org/10.1145/3716848>
5. Schulhoff, S., et al.: “The Prompt Report: A Systematic Survey of Prompting Techniques,” *arXiv:2406.06608* (2024)
6. Liu, P., Yuan, W., Fu, J., Jiang, Z., Hayashi, H., Neubig, G.: “Pre-train, Prompt, and Predict: A Systematic Survey of Prompting Methods in Natural Language Processing,” *arXiv:2107.13586* (2021)
7. Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., Cao, Y.: “ReAct: Synergizing Reasoning and Acting in Language Models,” *arXiv:2210.03629* (2022)
8. Yang, J., Jimenez, C.E., Wettig, A., Lieret, K., Yao, S., Narasimhan, K., Press, O.: “SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering,” *arXiv:2405.15793* (2024)
9. Jimenez, C.E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., Narasimhan, K.R.: “SWE-bench: Can Language Models Resolve Real-World GitHub Issues?,” *arXiv:2310.06770* (2023)
10. Gotel, O., Finkelstein, A.: “An analysis of the requirements traceability problem,” in *Proc. 1st Int. Conf. Requirements Engineering*, pp. 94–101 (1994)
11. K. Morris, *Infrastructure as Code*. O’Reilly Media, (2016).
12. Tihanyi, N., Bisztray, T., Ferrag, M.A., Jain, R., Cordeiro, L.C.: “How secure is AI-generated code: a large-scale comparison of large language models,” *Empir. Softw. Eng.* 30(2), Article 47 (2025). <https://doi.org/10.1007/s10664-024-10590-1>
13. Pornprasit, C., Tantithamthavorn, C.: “Fine-tuning and prompt engineering for large language models-based code review automation,” *Inf. Softw. Technol.* 175, 107523 (2024). <https://doi.org/10.1016/j.infsof.2024.107523>
14. Qu, Y., ang, S., Li, Y., Bai, T., Chen, X., Wang, X., Li, L., Yao, Y.: “BadCodePrompt: backdoor attacks against prompt engineering of large language models for code generation,” *Autom. Softw. Eng.* 32(1), Article 17 (2025). <https://doi.org/10.1007/s10515-024-00485-2>
15. Binkhonain, M., Alfayez, R.: “Are prompts all you need? Evaluating prompt-based Large Language Models (LLMs) for software requirements classification,” *Requirements Engineering* 30(4), 423–443 (2025). <https://doi.org/10.1007/s00766-025-00451-8>