

# aiida-aimall: A Python package for automating workflows for AIMAll software

Kevin M. Lefrancois-Gagnon<sup>1\*</sup>, Robert C. Mawhinney<sup>1</sup>, and <sup>1\*</sup>

<sup>1</sup> Lakehead University, Thunder Bay, ON, Canada \* These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Since its introduction by Richard Bader, the Quantum Theory of Atoms in Molecules (QTAIM) has become a useful tool for computational chemists. This Python package provides plugins for a common QTAIM software, AIMAll, for the AiiDA Python infrastructure. aiida-aimall is an essential tool for ensuring reproducible calculations, with full generation history. Workflows are also provided to interface AIMAll software with any quantum chemistry package that can be run through the command line, so long as it generates the input files required by AIMAll.

## Statement of need

aiida-aimall is a Python package based on the AiiDA ([Talirz et al., 2020](#)) infrastructure designed to assist users with generating inputs for AIMAll software ([Keith, 2019](#)). The goal of the AiiDA infrastructure are, in part, to ensure data provenance and calculation reproducibility. While aiida-aimall has been developed primarily for interface with Gaussian software outputs ([Frisch et al., 2016](#)), through modification of classes provided by aiida-gaussian ([Eimre et al., 2023](#)), a versatile workflow enabling interface with other quantum chemistry packages is also made available.

Through a variety of workflows that can start with Cartesian coordinates, or even with a SMILES string of a molecule, aiida-aimall provides a variety of use cases for automating and complex workflows. Additionally tools to ensure that computers are not overloaded through too many simultaneous processes are made available through classes of FromGroupSubmissionControllers from aiida-submission-controller to limit active processes.

## Features

aiida-aimall contains many different classes from aiida tailored to ensure ease of use of AIMAll calculations. Numerous features provided by aiida-aimall are described in full on the [documentation webpage hosted on ReadTheDocs](#). A brief description of main features is provided here.

## Running Simple AIMAll Calculations

The simplest functionality provided by aiida-aimall is running AIMAll calculations. All AIMAll calculations utilize the AimqbParameters Data type provided by aiida-aimall. The AimqbParameters datatype is a validator for AIMAll command line input. Command line parameters are to be provided as a dictionary, then AimqbParameters ensures that the parameters match options available for AIMAll software as [defined on the software website](#), and that the correct data type is provided for each parameter. In this way, AimqbParameters verifies the provided input to AIMAll calculations prior to launch of the calculation. These parameters,

38 along with SinglefileData of a valid AIMAll input file, a Code object for AIMAll software,  
39 and relevant metadata are provided to an AimqbCalculation.

40 This functionality in itself is an overcomplication of the simple process of running the software  
41 normally. However, it does have some benefits. The output is already extracted and stored in  
42 the database in a readily useable manner. Related, it is now simple to see the history of the  
43 calculation.

## 44 Integrations with Computational Chemistry Software

45 aiida-aimall's main draw is that it enables automation to link the outputs of standard  
46 computational chemistry software directly to an AIMAll calculation. A list of provided workflows  
47 is shown in Table COMPLETE. The software with the most robust implementation is Gaussian  
48 software,(Frisch et al., 2016) as Gaussian already has an implemented aiida package.

49 Table 1: Main workflows provided by aiida-aimall, their aiida entry points that can be used  
50 to load them by aiida.plugins.WorkflowFactory, a brief description, and their main inputs.  
51 These workflows all end with the output of an AimqbCalculation as their main output.

Workflow	Entry Point	Purpose	Input
QMTtoAIMWorkchain	aimall.qm-toaim	Run a general computational chemistry software and link it to an AIMAll calculation	Shell Command Line Output File(s) to Get Shell Code
GenerateWFXtoAIMWorkchain	aimall.wfx-toaim	Take non-standard AIMAll input files, and run AIMAll	.cp2k or .molden files
GaussianToAIMWorkChain	aimall.g16toaim	Run a Gaussian calculation and automatically run an AIMAll calculation on its outputs	GaussianCalc inputs wfx file-name

Workflow	Entry Point	Purpose	Input
SubstituentParameterWorkChain	FromGroupSubstParam	Compute substituent properties defined by the authors obtained from multistep calculation automatically	Input structure as .xyz file SinglefileData StructureData or SMILES StrGaussianC in-puts

## Controllers to limit computer burden when running large numbers of jobs

The last main contribution of `aiida-aimall` is through the definition of `FromGroupSubmissionControllers` from the `aiida-submission-controller` package. These controllers limit active processes and can be used together as demonstrated in (the example notebook) to automate the entire `SubstituentParameterWorkChain`. These use a number of Workchains developed just for their use in these controllers. The process flows as `SmilesToGaussianController -> AIMAllReorController -> GaussianController -> AIMAllController`. The latter two controllers can also be seen and used as general use controllers wrapping `GaussianCalculations` and `AimqbCalculations`

## Acknowledgements

We acknowledge NSERC,

## References

- Eimre, K., Yakutovich, A., Zarabadi-Poor, P., Huber, S., AndresOrtegaGuerrero, & Jablonka, K. M. (2023). *Nanotech-empa/aiida-gaussian: v2.1.0* (Version v2.1.0). Zenodo. <https://doi.org/10.5281/zenodo.8304939>
- Frisch, M. J., Trucks, G. W., Schlegel, H. B., Scuseria, G. E., Robb, M. A., Cheeseman, J. R., Scalmani, G., Barone, V., Petersson, G. A., Nakatsuji, H., Li, X., Caricato, M., Marenich, A. V., Bloino, J., Janesko, B. G., Gomperts, R., Mennucci, B., Hratchian, H. P., Ortiz, J. V., ... Fox, D. J. (2016). *Gaussian~16 Revision C.01*.
- Keith, T. A. (2019). (Version 19.10.12). TK Gristmill Software. [aim.tkgristmill.com](http://aim.tkgristmill.com)
- Talirz, L., Kahle, L., Häuselmann, R., Gresch, D., Müller, T., Yakutovich, A. V., Andersen, C. W., Ramirez, F. F., Adorf, C. S., Gargiulo, F., Kumbhar, S., Passaro, E., Johnston, C., Merkys, A., Cepellotti, A., Mounet, N., Marzari, N., Kozinsky, B., & Pizzi, G. (2020). AiiDA 1.0, a scalable computational infrastructure for automated reproducible workflows and data provenance . *Scientific Data*, 7. <https://doi.org/10.1038/s41597-020-00638-4>