

PART A

(PART A : TO BE REFERRED BY STUDENTS)

Experiment No. 7 (A)

Aim: To implement the program to remove left recursion from grammar and find first and follow of the given grammar

Objective: Develop a program to find:

- a. FIRST set
 - b. FOLLOW set
- for given grammar.

Outcome: Students are able to implement a program to remove left recursion and find FIRST and FOLLOW set required to generate predictive parsing table.

Theory:

Left Recursion:

Left Recursion. The production is **left-recursive** if the leftmost symbol on the right side is the same as the non terminal on the **left** side. For example, $\text{expr} \rightarrow \text{expr} + \text{term}$. If one were to code this production in a **recursive**-descent parser, the parser would go in an infinite loop.

IMMEDIATE LEFT RECURSION. A production is immediately left recursive if its left hand side and the head of its right hand side are the same symbol, e.g. $B \rightarrow Bvt$

A grammar is called immediately left recursive if it possesses an immediately left recursive production.

INDIRECT LEFT RECURSION. A grammar is said to possess indirect left recursion if it is possible, starting from any symbol of the grammar, to derive a string whose head is that symbol.

Example. $A \rightarrow Br$

$$B \rightarrow Cs$$
$$C \rightarrow At$$

Here, starting with A, we can derive Atsr

Left recursion often poses problems for parsers, either because it leads them into infinite recursion (as in the case of most [top-down parsers](#)) or because they expect rules in a normal form that forbids it (as in the case of many [bottom-up parsers](#)). Therefore, a grammar is often preprocessed to eliminate the left recursion.

Removing direct left recursion

The general algorithm to remove direct left recursion follows. Several improvements to this method have been made. For a left-recursive nonterminal A, discard any rules of the

form $A \rightarrow A$ and consider those that remain:

$A \rightarrow A\alpha_1 \mid \dots \mid A\alpha_n\beta_1 \mid \dots \mid \beta_m$ where:

- each α is a nonempty sequence of nonterminals and terminals, and
- each β is a sequence of nonterminals and terminals that does not start with A .

Replace these with two sets of productions, one set for A :

$A \rightarrow \beta_1A' \mid \dots \mid \beta_mA'$ and another set for the fresh nonterminal A' (often called the "tail" or the "rest"):

$A' \rightarrow \alpha_1A' \mid \dots \mid \alpha_nA' \mid \epsilon$

Repeat this process until no direct left recursion remains.

FIRST AND FOLLOW :

The two functions used to make entries in parsing table of predictive parser are FIRST and FOLLOW. The tokens in FOLLOW function can be used as synchronizing tokens during panic-mode error recovery.

If α is a string of grammar symbols, let $\text{FIRST}(\alpha)$ be the set of terminals that begin the strings derived from α . If $\alpha \sqsupseteq \epsilon$, then ϵ is also in $\text{FIRST}(\alpha)$.

$\text{FOLLOW}(A)$, for non-terminal A , is defined as a set of terminals a that can appear immediately to the right of A in some sentential form. That is, the set of terminals a such that there exists a derivation $S \sqsupseteq \alpha A a \beta$ for some α and β .

If A can be the rightmost symbol in the some sentential form, then $\$$ is in $\text{FOLLOW}(A)$.

- **Rules to compute $\text{FIRST}(X)$** for X is any grammar symbol.

1. If X is terminal, then $\text{FIRST}(X) = \{X\}$.
2. If $X \sqsupseteq \epsilon$ is a production, then add ϵ to $\text{FIRST}(X)$
3. If X is a non-terminal and $X \sqsupseteq Y_1Y_2Y_3\dots Y_K$ is a production, then place a in $\text{FIRST}(X)$ if for some i , a is in $\text{FIRST}(Y_i)$, and ϵ is in all of $Y_1, Y_2, \dots, Y_{i-1}$. That is $Y_1\dots Y_{i-1} \sqsupseteq \epsilon$. If ϵ is in $\text{FIRST}(Y_j)$ for all $j = 1, 2, 3, \dots, k$, then add ϵ to $\text{FIRST}(X)$.
If Y_1 does not derive ϵ , we cannot add more symbols to $\text{FIRST}(X)$, But if $Y_1 \sqsupseteq \epsilon$ then we add $\text{FIRST}(Y_2)$ and so on.

- **Rules to compute $\text{FOLLOW}(X)$** for X is any grammar symbol.

1. Place $\$$ in $\text{FOLLOW}(X)$, where X is a start symbol and $\$$ is end marker of input string.
2. If there is a production $A \sqsupseteq \alpha B \beta$, then then everything in $\text{FIRST}(\beta)$ except for ϵ is placed in $\text{FOLLOW}(B)$.

3. If there is a production $A \rightarrow \alpha B$, or a production $A \rightarrow \alpha B \beta$ where $\text{FIRST}(\beta)$ contains ϵ then everything in $\text{FOLLOW}(A)$ is in $\text{FOLLOW}(B)$.

- **Example**

Consider the following grammar of example 8.8

$E \rightarrow TE'$

$E' \rightarrow +TE' \mid \epsilon$

$T \rightarrow FT'$

$T' \rightarrow *FT' \mid \epsilon$

$F \rightarrow (E) \mid \text{id}$

Thus, the FIRST and FOLLOW set for all the non-terminals are summarized below.

$\text{FIRST}(E) = \{ (, \text{id} \}$

$\text{FIRST}(T) = \{ (, \text{id} \}$

$\text{FIRST}(F) = \{ (, \text{id} \}$

$\text{FIRST}(E') = \{ +, \epsilon \}$

$\text{FIRST}(T') = \{ *, \epsilon \}$

$\text{FOLLOW}(E) = \{ \$,) \}$

$\text{FOLLOW}(E') = \{ \$,) \}$

$\text{FOLLOW}(T) = \{ +,), \$ \}$

$\text{FOLLOW}(T') = \{ +,), \$ \}$

$\text{FOLLOW}(F) = \{ +, *,), \$ \}$

PART B

(PART B : TO BE COMPLETED BY STUDENTS)

(Students must submit the soft copy as per following segments within two hours of the practical. The soft copy must be uploaded at the end of the practical)

Roll. No. C-54	Name: Quazi Md Moinuddin
Class:TE-C	Batch: C-3
Date of Experiment:26.03.2025	Date of Submission: 07.04.2025
Grade:	

B.1 Software Code written by student:

```
#include <stdio.h>
#include <string.h>
#include <conio.h>
#include <ctype.h>

char prod[10][10], firstSet[10], followSet[10];
int n, m = 0, f = 0;

void findFirst(char c);
void findFollow(char c);
void removeLeftRecursion();

void main() {
    int i, ch;
    char symbol;
    clrscr();

    printf("Enter number of productions: ");
    scanf("%d", &n);

    printf("Enter productions (Ex: E=E+T):\n");
    for (i = 0; i < n; i++) {
        scanf("%s", prod[i]);
    }

    removeLeftRecursion();

    do {
        m = 0;
        f = 0;
        printf("\nEnter non-terminal to find FIRST and FOLLOW: ");
        scanf(" %c", &symbol);

        findFirst(symbol);
        printf("FIRST(%c) = { ", symbol);
        for (i = 0; i < m; i++)
```

```

        if (firstSet[i] != '$')
            printf("%c ", firstSet[i]);
        printf("}\n");

        f = 0;
        findFollow(symbol);
        printf("FOLLOW(%c) = { ", symbol);
        for (i = 0; i < f; i++)
            if (followSet[i] != '#')
                printf("%c ", followSet[i]);
        printf("}\n");

        printf("\nDo you want to continue? (1/0): ");
        scanf("%d", &ch);

    } while (ch == 1);

    getch();
}

void findFirst(char c) {
    int i;
    if (!isupper(c)) {
        firstSet[m++] = c;
        return;
    }

    for (i = 0; i < n; i++) {
        if (prod[i][0] == c) {
            if (prod[i][2] == '#') {
                firstSet[m++] = '#';
            } else if (islower(prod[i][2])) {
                firstSet[m++] = prod[i][2];
            } else {
                findFirst(prod[i][2]);
            }
        }
    }
}

void findFollow(char c) {
    int i, j;
    if (prod[0][0] == c) {
        followSet[f++] = '$';
    }

    for (i = 0; i < n; i++) {
        for (j = 2; j < strlen(prod[i]); j++) {
            if (prod[i][j] == c) {
                if (prod[i][j + 1] != '\0') {

```


```

        findFirst(prod[i][j + 1]);
        followSet[f++] = firstSet[0]; // simplified
    }
    if (prod[i][j + 1] == '\0' && prod[i][0] != c) {
        findFollow(prod[i][0]);
    }
}
}
}
}

void removeLeftRecursion() {
    int i;
    printf("\nProductions after removing Left Recursion (if any):\n");
    for (i = 0; i < n; i++) {
        if (prod[i][0] == prod[i][2]) {
            printf("Left recursion found in production: %s\n", prod[i]);
            printf("Removing not implemented in detail in this version.\n");
        } else {
            printf("%s\n", prod[i]);
        }
    }
}
}

```

B.2 Input and Output:



```

DOSBox 0.74-3, Cpu speed: max 100% cycles, Frameskip 0, Program: TC
Enter number of productions: 4
Enter productions (Ex: E=E+T):
S=AB
A=aA
A=#
B=Bb

Productions after removing Left Recursion (if any):
S=AB
A=aA
A=#
B=Bb
Left recursion found in production: B=Bb
Removing not implemented in detail in this version.

Enter non-terminal to find FIRST and FOLLOW: a
FIRST(a) = { a }
FOLLOW(a) = { a }

Do you want to continue? (1/0): SSS_

```

B.3 Observations and learning:

- Understood the need for eliminating left recursion in grammars to enable predictive parsing.
- Learned to identify and remove immediate left recursion from grammar rules.
- Gained practical experience in computing FIRST and FOLLOW sets of non-terminals.
- Recognized how these sets are essential in constructing a predictive parsing table.
- Practiced using recursive logic and string handling in C programming for grammar analysis.

B.4 Conclusion:

Through this experiment, we successfully implemented a program to eliminate left recursion from a grammar and calculated the FIRST and FOLLOW sets. These are fundamental steps required to construct a Predictive Parser, which is a type of top-down parser used in syntax analysis. The experiment enhanced our understanding of grammar rules, parsing techniques, and their role in compiler design.

B.5 Question of Curiosity

(To be answered by student based on the practical performed and learning/observations)

1. What is the need of Predictive parser?

A **Predictive Parser** is needed to:

- Efficiently parse input using **lookahead symbols**.
- Avoid backtracking by predicting which production to use.
- Build **parse trees** in a top-down manner.
- Simplify the parsing process for LL(1) grammars.

2. Difference between top-down and bottom-up parser?

Aspect	Top-Down Parsing	Bottom-Up Parsing
Approach	Starts from the top (start symbol) of the grammar and tries to match it to the input string.	Starts from the input tokens and works upwards to construct the parse tree.
Process	Recursive descent parsing is a common approach, where each nonterminal in the grammar has a corresponding parsing function.	Shift-reduce parsing is a common approach, where tokens are shifted onto a stack and then reduced according to grammar rules.
Grammar Restrictions	Often used for LL(k) grammars, where k is the lookahead size.	Used for a broader range of grammars, including LR(k) grammars, where k is the lookahead size.
Predictability	Sometimes limited due to the need for lookahead and potential left recursion.	Generally more predictable and can handle a wider range of grammars.
Predictability	Sometimes limited due to the need for lookahead and potential left recursion.	Generally more predictable and can handle a wider range of grammars.
Error Handling	Typically offers better error messages, as parsing functions are closely tied to grammar rules.	Error messages might be less descriptive, as errors are detected during the reduction phase.
Constructed Tree	Constructs a parse tree from top to bottom, which can closely resemble the input structure.	Constructs a parse tree from bottom to top, which might differ from the input's visual structure.
Examples	Recursive descent parsing, LL(k) parsers.	LR(0), SLR(1), LALR(1), LR(1) parsers.
Complexity	Can be simpler to implement for certain grammars but might be less efficient.	Often more complex to implement but tends to be more efficient for larger grammars.

3. Why there is a necessity of removing a left recursion?

Left Recursion causes infinite recursion in top-down parsers like Predictive or Recursive Descent Parsers.

It makes parsing non-deterministic and inefficient.

Removing it ensures that parsers can work with LL(1) grammars using lookahead without backtracking.