



Hash-Based Indexes

Chapter 11



Overview

Topics covered in this chapter:

- ❖ Static hashing
- ❖ Extendable hashing
- ❖ Linear hashing
- ❖ Extendable vs. linear hashing

Introduction




- ❖ As for any index, 3 alternatives for data entries k^* :
 - Data record with key value k
 - $\langle k, \text{rid of data record with search key value } k \rangle$
 - $\langle k, \text{list of rids of data records with search key } k \rangle$
 - Choice orthogonal to the *indexing technique*
- ❖ Hash-based indexes are best for *equality selections*. *Cannot* support range searches.
- ❖ Static and dynamic hashing techniques exist; trade-offs similar to ISAM vs. B+ trees.

Static Hashing



- ❖ # primary pages fixed, allocated sequentially, never de-allocated; overflow pages if needed.
- ❖ $h(k) \bmod N$ = bucket to which data entry with key k belongs. (N = # of buckets)



Static Hashing (Contd.)



- ❖ Buckets contain *data entries*.
- ❖ Hash fn works on *search key* field of record *r*. Must distribute values uniformly over range 0 ... N-1.
 - $h(key) = (a * key + b)$ usually works well.
 - *a* and *b* are constants; lots known about how to tune *h*.
- ❖ **Long overflow chains** can develop and degrade performance.
 - *Extendible* and *Linear Hashing*: Dynamic techniques to fix this problem.


Extendible Hashing



- ❖ Situation: Bucket (primary page) becomes full. Why not re-organize file by *doubling* # of buckets?
 - Reading and writing all pages is expensive!
 - *Idea*: Use directory of pointers to buckets, double # of buckets by doubling the directory, splitting just the bucket that overflowed!
 - Directory much smaller than file, so doubling it is much cheaper. Only one page of data entries is split.
No overflow page!
 - Trick lies in how hash function is adjusted!


Example

- ❖ Directory is array of size 4.
- ❖ To find bucket for r , take last '*global depth*' # bits of $h(r)$; we denote r by $h(r)$.
 - If $h(r) = 5 = \text{binary } 101$, it is in bucket pointed to by 01.



- ❖ **Insert:** If bucket is full, *split* it (allocate new page, re-distribute).
- ❖ If necessary, double the directory. (As we will see, splitting a bucket does not always require doubling; we can tell by comparing *global depth* with *local depth* for the split bucket.)

Insert $h(r)=20$ (Causes Doubling)



Points to Note



- ❖ 20 = binary 10100. Last 2 bits (00) tell us r belongs in A or A2. Last 3 bits needed to tell which.
 - *Global depth of directory*: Max # of bits needed to tell which bucket an entry belongs to.
 - *Local depth of a bucket*: # of bits used to determine if an entry belongs to this bucket.
- ❖ When does bucket split cause directory doubling?
 - Before insert, *local depth* of bucket = *global depth*. Insert causes *local depth* to become > *global depth*; directory is doubled by *copying it over* and 'fixing' pointer to split image page. (Use of least significant bits enables efficient doubling via copying of directory!)

Comments on Extendible Hashing



- ❖ If directory fits in memory, equality search answered with one disk access; else two.
 - 100MB file, 100 bytes/rec, 4KB pages contains 1,000,000 records (as data entries) and 25,000 directory elements; chances are high that directory will fit in memory.
 - Directory grows in spurts, and, if the distribution of *hash values* is skewed, directory can grow large.
 - Multiple entries with same hash value cause problems!
- ❖ **Delete**: If removal of data entry makes bucket empty, can be merged with 'split image'. If each directory element points to same bucket as its split image, can halve directory.

Linear Hashing



- ❖ This is another dynamic hashing scheme, an alternative to Extendible Hashing.
- ❖ LH handles the problem of long overflow chains without using a directory.
- ❖ Idea: Use a family of hash functions h_0, h_1, h_2, \dots
 - $h_i(\text{key}) = h(\text{key}) \bmod(2^i N)$; N = initial # buckets
 - h is some hash function
 - If $N = 2^{d_0}$, for some d_0 , h_i consists of applying h and looking at the last d_i bits, where $d_i = d_0 + i$.
 - h_{i+1} doubles the range of h_i (similar to directory doubling)

Linear Hashing (Contd.)




- ❖ Directory avoided in LH by using overflow pages, and choosing bucket to split round-robin.
 - **Splitting proceeds in 'rounds'**. Round ends when all N_R initial (for round R) buckets are split. Buckets 0 to *Next-1* have been split; *Next* to N_R yet to be split.
 - **Current round number is Level**.
 - **Search**: To find bucket for data entry r , find $h_{\text{Level}}(r)$:
 - If $h_{\text{Level}}(r)$ in range 'Next to N_R ', r belongs here.
 - Else, r could belong to bucket $h_{\text{Level}}(r)$ or bucket $h_{\text{Level}}(r) + N_R$; must apply $h_{\text{Level}+1}(r)$ to find out.

Overview of LH File



❖ In the middle of a round.



Linear Hashing (Contd.)




- ❖ **Insert:** Find bucket by applying $h_{Level} / h_{Level+1}$:
 - If bucket to insert into is full:
 - Add overflow page and insert data entry.
 - Split *Next* bucket and increment *Next*.
- ❖ Can choose any *criterion* to 'trigger' split.
- ❖ Since buckets are split round-robin, **long overflow chains don't develop!**
- ❖ Doubling of directory in Extendible Hashing is similar; switching of hash functions is *implicit* in how the # of bits examined is increased.

Example of Linear Hashing




- ❖ On split, $h_{Level+1}$ is used to re-distribute entries.



15

Example: End of a Round



16

LH Described as a Variant of EH



- ❖ The two schemes are actually quite similar:
 - Begin with an index where directory has N elements.
 - Use overflow pages, split buckets round-robin.
 - First split is at bucket 0. (Imagine directory being doubled at this point.) We only need to add directory element N now. Elements $\langle 1, N+1 \rangle$, $\langle 2, N+2 \rangle$, ... are the same.
 - When bucket 1 splits, create directory element $N+1$, etc.
- ❖ So, directory can double gradually. Also, primary bucket pages are created in order. If they are *allocated* in sequence too (so that finding i 'th is easy), we actually don't need a directory!

Summary



- ❖ Hash-based indexes: best for equality searches, cannot support range searches.
- ❖ Static Hashing can lead to long overflow chains.
- ❖ Extendible Hashing avoids overflow pages by splitting a full bucket when a new data entry is to be added to it. (*Duplicates may require overflow pages.*)
 - Directory to keep track of buckets, doubles periodically.
 - Can get large with skewed data; additional I/O if this does not fit in main memory.

Summary (Contd.)



- ❖ Linear Hashing avoids directory by splitting buckets round-robin, and using overflow pages.
 - Overflow pages not likely to be long.
 - Duplicates handled easily.
 - Space utilization could be lower than Extendible Hashing, since splits not concentrated on 'dense' data areas.
 - Can tune criterion for triggering splits to trade-off slightly longer chains for better space utilization.
- ❖ For hash-based indexes, a *skewed* data distribution is one in which the *hash values* of data entries are not uniformly distributed!