```
package a20_8_21_event;
import java.applet.Applet;
import java.awt.Button;
import java.awt.Color;
import java.awt.TextArea;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
public class ButtonTest extends Applet implements ActionListener{
            Button btn1, btn2, btn3;
            TextArea ta;
            public void init() {
                        this.setLayout(null);
                        btn1=new Button("java");
btn2=new Button("jsp");
btn3=new Button("연습"); //
                        btn1.setBounds(2, 10, 50, 50);
btn2.setBounds(100, 10, 50, 50);
btn3.setBounds(150, 10, 50, 50);//
                        ta=new TextArea(5, 20);
                        ta.setBackground(Color.yellow);
ta.setBounds(2, 100, 200, 100);
                        this.add(btn1);
                        this.add(btn2);
                        this.add(btn3);//
                        this.add(ta);
                        btn1.addActionListener(this): //btn1버튼에 액션추가btn2.addActionListener(this): //btn2버튼에 액션추가btn3.addActionListener(this): //
            @Override
            public void actionPerformed(ActionEvent e) {
                        if(e.getSource()==btn1) {
    ta.append("རདษ¡:");
    ta.append(btn1.getLabel()+"\n");
                        else if(e.getSource()==btn2) {
                                    ta.append("웹:");
ta.append(btn2.getLabel()+"\n");
                        else if(e.getSource()==btn3) {
ta.append("연습\n");
            }
```

```
kmove2 - a20_8_21_event/src/a20_8_21_event/ButtonTest.java - Eclipse IDE
                                                                                    O
File Edit Source Refactor Navigate Search Project Run Window Help
Quick Access
P 🕱 📟 🗖 💹 *ButtonTest.java 🕱
                                                                            - -
B & |
                                                                                 = × %
         37⊜
                  @Override
                                                                                   38
                  public void actionPerformed(ActionEvent e) {
> 620_8_1
                                                                                 (1)
> 120_8_1
                       if(e.getSource()==btn1) {
                                                                                         80
          39
> 12 > a20 8 1
                                                                                 = = -
                            btn1.disable();
          40
> 20_8_1
                                                                                  ₩ +
> 20_8_2
          41
                            btn2.enable();
                                                                                 <terminated> E
> 20_8_2
> 20_8_2
> 20_8_2
                          btn3.enable();
          42
  > 🖹 JRE Sys
                            ta.append("자바:");
          43
 44
                            ta.append(btn1.getLabel()+"\n");
> [] E
          45
> C > Java실실

> C > SwingTo

> C test [kmo)
                       else if(e.getSource()=btn2)
          46
          47
                            btn2.disable();
          48
                           btn1.enable();
                          btn3.enable();
          49
          50
                            ta.append("웹:");
          51
                            ta.append(btn2.getLabel()+"\n");
          52
          53
                       else if(e.getSource()={btn3}
                           btn3.disable();
          54
          55
                           btn1.enable();
                           btn2.enable();
          56
          57
                            ta.append("연습\n");
< >
                                     Writable
                                              Smart Insert
                                                      45 : 1
```