## Cheat Sheet: Build GenAI Application With LangChain

Estimated time needed: 5 minutes

Package/Method	Description	Code Example
mkdir and cd	Create and navigate into a new project directory.	mkdir genai_flask_app cd genai_flask_app
Virtual environment	Set up a Python virtual environment for package management.	python3.11 -m venv venv source venv/bin/activate
pip install ibm- watsonx-ai	Install the IBM watsonx AI library for LLM interactions.	pip install ibm-watsonx-ai
Credentials	Authenticate with IBM watsonx AI using credentials.	<pre>from ibm_watsonx_ai import Credentials  credentials = Credentials(     url = "https://us-south.ml.cloud.ibm.com",     # api_key = "<your_api_key>" )</your_api_key></pre>
Model parameters	Define parameters for model inference.	<pre>from ibm_watsonx_ai.metanames import GenTextParamsMetaNames  params = {     GenTextParamsMetaNames.DECODING_METHOD: "greedy",     GenTextParamsMetaNames.MAX_NEW_TOKENS: 100 }</pre>
Model inference	Initialize an AI model for text generation.	<pre>from ibm_watsonx_ai.foundation_models import ModelInference  model = ModelInference(     model_id="ibm/granite-13b-instruct-v2",     params=params,     credentials=credentials,     project_id="skills-network" )</pre>

		text = """ Only reply with the answer. What is the capital of Canada?
Generating AI response	Use an AI model to generate text based on a prompt.	<pre>print(model.generate(text)['results'][0]['generated_text'])</pre>
		<pre>from langchain.prompts import PromptTemplate  llama3_template = PromptTemplate(     template='''&lt; begin_of_text &gt;&lt; start_header_id &gt;system&lt; end_header_id &gt; {system_prompt}&lt; eot_id &gt;&lt; start_header_id &gt;user&lt; end_header_id &gt;</pre>
LangChain prompt templates	Define reusable prompt templates for different models.	<pre>{user_prompt}</pre> {user_prompt}/eot_id >/estart_header_id >assistant/end_header_id > ''' input_variables=["system_prompt", "user_prompt"] )
LangChain chaining	Pipe a prompt template into an AI model to generate structured output.	<pre>def get_ai_response(model, template, system_prompt, user_prompt):     chain = template   model     return chain.invoke({'system_prompt': system_prompt, 'user_prompt': user_prompt})</pre>
Tokenization and prompt formatting	Specialized token formatting for different AI models.	<pre># Llama 3 formatted prompt text = """ &lt; begin_of_text &gt;&lt; start_header_id &gt;system&lt; end_header_id &gt; You are an expert assistant who provides concise and accurate answers.&lt; eot_id &gt; &lt; start_header_id &gt;user&lt; end_header_id &gt; What is the capital of Canada?&lt; eot_id &gt; &lt; start_header_id &gt;assistant&lt; end_header_id &gt; """</pre>
JSON output parser	Parse and structure AI- generated responses using LangChain.	<pre>from langchain_core.output_parsers import JsonOutputParser from pydantic import BaseModel, Field  class AIResponse(BaseModel):     summary: str = Field(description="Summary of the user's message")     sentiment: int = Field(description="Sentiment score from 0 to 100")     response: str = Field(description="Generated AI response")  json_parser = JsonOutputParser(pydantic_object=AIResponse)</pre>
Enhancing AI outputs	Modify LangChain chaining to ensure	<pre>def get_ai_response(model, template, system_prompt, user_prompt):     chain = template   model   json_parser     return chain.invoke({         'system_prompt': system_prompt,         'user prompt': user prompt,</pre>

	JSON output.	})
		<pre>from flask import Flask, request, jsonify from model import get_model_response  app = Flask(name)  @app.route('/generate', methods=['POST']) def generate():     data = request.json     model_name = data.get('model')</pre>
Flask API integration		<pre>user_message = data.get('message') if not user_message or not model_name:     return jsonify({"error": "Missing message or model selection"}), 400 system_prompt = "You are an AI assistant helping with customer inquiries. Provide a concise response.</pre>
	Create an API endpoint for AI model interactions.	<pre>try:     response = get_model_response(model_name, system_prompt, user_message)     return jsonify(response) except Exception as e:     return jsonify({"error": str(e)}), 500</pre>
		if name == 'main':     app.run(debug=True)

## Author

Hailey Quach

