

How to implement a neural network Intermezzo 2

This page is part of a 5 (+2) parts tutorial on how to implement a simple neural network model. You can find the links to the rest of the tutorial here:

- Part 1: Linear regression (/posts/neural_network_implementation_part01/)
- Intermezzo 1: Logistic classification function (/posts/neural_network_implementation_intermezzo01/)
- Part 2: Logistic regression (classification) (/posts/neural_network_implementation_part02/)
- Part 3: Hidden layer (/posts/neural_network_implementation_part03/)
- Intermezzo 2: Softmax classification function (/posts/neural_network_implementation_intermezzo02/)
- Part 4: Vectorization (/posts/neural_network_implementation_part04/)
- Part 5: Generalization of multiple layers (/posts/neural_network_implementation_part05/)

Softmax classification function

This intermezzo will cover:

- The softmax function (http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/#Softmax-function)
- Cross-entropy (http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/#Cross-entropy-cost-function-for-the-softmax-function) cost function

The previous intermezzo described how to do a classification of 2 classes with the help of the logistic function (http://en.wikipedia.org/wiki/Logistic_function). For multiclass classification there exists an extension of this logistic function called the softmax function (http://en.wikipedia.org/wiki/Softmax_function) which is used in multinomial logistic regression (http://en.wikipedia.org/wiki/Multinomial_logistic_regression). The following section will explain the softmax function and how to derive it.

```
In [1]: # Python imports
```

Softmax function

The logistic output function (http://en.wikipedia.org/wiki/Logistic_function) described in the previous intermezzo can only be used for the classification between two target classes $[Math Processing Error]$ and $[Math Processing Error]$. This logistic function can be generalized to output a multiclass categorical probability distribution by the softmax function (http://en.wikipedia.org/wiki/Softmax_function). This softmax function $[Math Processing Error]$ takes as input a $[Math Processing Error]$ -dimensional vector $[Math Processing Error]$ and outputs a $[Math Processing Error]$ -dimensional vector $[Math Processing Error]$ of real values between $[Math Processing Error]$ and $[Math Processing Error]$. This function is a normalized exponential and is defined as:

$[Math Processing Error]$

The denominator $[Math Processing Error]$ acts as a regularizer to make sure that $[Math Processing Error]$. As the output layer of a neural network, the softmax function can be represented graphically as a layer with $[Math Processing Error]$ neurons.

We can write the probabilities that the class is $[Math Processing Error]$ for $[Math Processing Error]$ given input $[Math Processing Error]$ as:


$[Math Processing Error]$

Where $[Math Processing Error]$ is thus the probability that the class is $[Math Processing Error]$ given the input $[Math Processing Error]$.

These probabilities of the output $[Math Processing Error]$ for an example system with 2 classes ($[Math Processing Error]$, $[Math Processing Error]$) and input $[Math Processing Error]$ is shown in the figure below. The other probability $[Math Processing Error]$ will be complementary.

```
In [2]: # Define the softmax function
def softmax(z):
    return np.exp(z) / np.sum(np.exp(z))
```

```
In [3]: # Plot the softmax output for 2 dimensions for both classes
```



Derivative of the softmax function

To use the softmax function in neural networks, we need to compute its derivative. If we define J so that J , then this derivative of the output of the softmax function with respect to its input can be calculated as:

Note that if this derivative is similar to the derivative of the logistic function.

Cross-entropy cost function for the softmax function

To derive the cost function for the softmax function we start out from the likelihood function (http://en.wikipedia.org/wiki/Likelihood_function) that a given set of parameters of the model can result in prediction of the correct class of each input sample, as in the derivation for the logistic cost function. The maximization of this likelihood can be written as:

The likelihood can be rewritten as the joint probability (http://en.wikipedia.org/wiki/Joint_probability_distribution) of generating given the parameters. Which can be written as a conditional distribution:

Since we are not interested in the probability of we can reduce this to: . Which can be written as for fixed . Since each is dependent on the full , and only 1 class can be activated in the we can write

As was noted during the derivation of the cost function of the logistic function, maximizing this likelihood can also be done by minimizing the negative log-likelihood:

Which is the cross-entropy error function . Note that for a 2 class system output and this results in the same error function as for logistic regression: .

The cross-entropy error function over a batch of multiple samples of size can be calculated as:

Where is 1 if and only if sample belongs to class , and is the output probability that sample belongs to class .



Derivative of the cross-entropy cost function for the softmax function


The derivative of the cost function with respect to the softmax input can be calculated as:



Note that we already derived for and above.

The result that for all is the same as the derivative of the cross-entropy for the logistic function which had only one output node.

This post at peterroelants.github.io (http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/) is generated from an IPython notebook file. Link to the full IPython notebook file (https://github.com/peterroelants/peterroelants.github.io/blob/master/notebooks/neural_net_implementation/neural_network_implementation_intermezzo02.ipynb)

 ([https://twitter.com/intent/tweet?source=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&text=How to implement a neural network Intermezzo](https://twitter.com/intent/tweet?source=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&text=How%20to%20implement%20a%20neural%20network%20Intermezzo%20via%20%40PeterRoelants) 2%20http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/ via %20@PeterRoelants) 

(https://plus.google.com/share?url=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/) 

([http://www.reddit.com/submit?url=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&title=How to implement a neural network Intermezzo 2](http://www.reddit.com/submit?url=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&title=How%20to%20implement%20a%20neural%20network%20Intermezzo%20))  ([http://www.linkedin.com/shareArticle?mini=true&url=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&title=How to implement a neural network Intermezzo 2&source=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/](http://www.linkedin.com/shareArticle?mini=true&url=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/&title=How%20to%20implement%20a%20neural%20network%20Intermezzo%20&source=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/))  (mailto:?subject=How to implement a neural network Intermezzo 2&body=http://peterroelants.github.io/posts/neural_network_implementation_intermezzo02/)