

3. Welcome Message with Styling and ID/Class Scenario:

Display a welcome banner styled uniquely for a logged-in user. Objective:

Practice block/inline tags and differentiate id and class Task:

- Use and apply a blue background via internal CSS
- Use inline styles for a special offer (e.g., color red, bold)
- Apply the .highlight class to certain elements for visual emphasis

Source Code:

```
<!DOCTYPE html>
<html lang="en">

<head>
  <!-- Meta Information -->
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <!-- Page Title -->
  <title>Welcome Banner - Community Portal</title>

  <!-- Internal CSS -->
  <style>

    /* Welcome Banner Styling */
    #welcomeBanner {
      background-color: blue;
      color: white;
      padding: 15px;
    }

    /* Highlight Class */
    .highlight {
      background-color: yellow;
      font-weight: bold;
    }

  </style>
</head>

<body>

  <!-- Welcome Banner Section -->
  <div id="welcomeBanner">

    <h1>Welcome to the Local Community Event Portal</h1>
```

```
<p>
  Residents can register for events and access community services easily.
</p>
```

```
<p class="highlight">
  New events have been added this week.
</p>
```

```
<p>
  <span style="color: red; font-weight: bold;">
    Special Offer:
  </span>
  Register today and get free entry to selected workshops.
</p>
```

```
</div>
```



```
</body>
```

```
</html>
```

4. Image Gallery for Community Events Scenario:

Show images from past events in a table layout. Objective:

- Use a with 2 rows and 3 columns of **Error! Filename not specified.**tags
- Include alt, title, and style each image with borders using a class
- Add a caption to describe each event

Source Code:

```
<!DOCTYPE html>
<html lang="en">

<head>

  <!-- Meta Information -->
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <!-- Page Title -->
  <title>Community Event Gallery</title>
```

```
<!-- Internal CSS -->
```

```
<style>
```

```
body {  
    font-family: Arial, sans-serif;  
    text-align: center;  
    background-color: #f4f4f4;  
}
```

```
h1 {  
    margin-top: 20px;  
    color: #003366;  
}
```

```
table {  
    margin: 20px auto;  
    border-collapse: collapse;  
}
```

```
td {  
    padding: 15px;  
}
```

```
.event-image {  
    width: 250px;  
    height: 180px;  
    border: 3px solid #333;  
    border-radius: 8px;  
    object-fit: cover;  
}
```

```
.caption {  
    margin-top: 8px;  
    font-weight: bold;  
    color: #222;  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<!-- Gallery Heading -->
```

```
<h1>Community Event Gallery</h1>
```

```
<!-- Gallery Table -->
```

```

<table>

<!-- First Row -->
<tr>

  <td>
    

    <p class="caption">
      Cultural Festival 2026
    </p>
  </td>

  <td>
    

    <p class="caption">
      Food Donation Camp
    </p>
  </td>

  <td>
    

    <p class="caption">
      Community Music Concert
    </p>
  </td>

</tr>

<!-- Second Row -->
<tr>

  <td>
    

        <p class="caption">
            Annual Sports Competition
        </p>
    </td>

    <td>
        

        <p class="caption">
            Tree Plantation Drive
        </p>
    </td>

    <td>
        
        <p class="caption">
            Health Awareness Program
        </p>
    </td>
</tr>
</table>
</body>
</html>

```



5.Event Registration Form Scenario: Residents need to register for events.

Objective: Practice input types, validation, placeholder, autofocus, and output

Task:

- Include fields: name (text), email (email), date (date), event type (select), message (textarea)
- Add placeholder, required, and autofocus
- Display a confirmation message using when the form is submitted
- Style the form using CSS 5.

Source Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <!-- Meta Information -->
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <!-- Page Title -->
  <title>Event Registration Form</title>
  <!-- Internal CSS -->
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f4f4f4;
    }
    .form-container {
      width: 400px;
      margin: 40px auto;
      background-color: white;
      padding: 20px;
      border-radius: 8px;
      border: 1px solid #ccc;
    }
    h1 {
      text-align: center;
      color: #003366;
    }

    label {
      font-weight: bold;
    }
  </style>
</head>
```

```
input,
select,
textarea {
    width: 100%;
    padding: 10px;
    margin-top: 5px;
    margin-bottom: 15px;
}
```

```
button {
    width: 100%;
    padding: 10px;
    background-color: #003366;
    color: white;
    border: none;
    cursor: pointer;
}
```

```
button:hover {
    background-color: #0055aa;
}
```

```
output {
    display: block;
    margin-top: 15px;
    color: green;
    font-weight: bold;
    text-align: center;
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
    <!-- Registration Form Container -->
```

```
    <div class="form-container">
```

```
        <h1>Event Registration</h1>
```

```
        <!-- Registration Form -->
```

```
        <form
```

```
            onsubmit="document.getElementById('confirmation').value='Registration Submitted
```

```
Successfully!'; return false;">
```

```
        <!-- Name Field -->
```

```
        <label for="name">Full Name</label>
```

```
        <input type="text"
```

```
            id="name"
```

```
            name="name"
```

```
            placeholder="Enter your full name"
```

```
        required
        autofocus>
<!-- Email Field -->
<label for="email">Email Address</label>
<input type="email"
        id="email"
        name="email"
        placeholder="Enter your email"
        required>
<!-- Date Field -->
<label for="date">Event Date</label>
<input type="date"
        id="date"
        name="date"
        required>
<!-- Event Type -->
<label for="event">Event Type</label>
<select id="event"
        name="event"
        required>
    <option value="">Select Event</option>
    <option value="music">Music Concert</option>
    <option value="sports">Sports Event</option>
    <option value="workshop">Workshop</option>
    <option value="awareness">Awareness Program</option>
</select>
<!-- Message Field -->
<label for="message">Message</label>
<textarea id="message"
        name="message"
        rows="4"
        placeholder="Enter your message">
</textarea>
<!-- Submit Button -->
<button type="submit">
    Register
</button>
<!-- Output Message -->
<output id="confirmation"></output>
</form>
</div>
</body>
</html>
```

7. Video Invite with Media Events Scenario:

Show a short event promo video. Objective: Work with and oncanplay event

Task:

- Insert a element with source and controls
- Use oncanplay to display a message like "Video ready to play"
- Use onbeforeunload to warn users if they try to leave the form page unfinished

Source Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <!-- Meta Information -->
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <!-- Page Title -->
  <title>Event Promo Video</title>
  <!-- Internal CSS -->
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f4f4f4;
    }
    .container {
      width: 600px;
      margin: 30px auto;
      background-color: white;
      padding: 20px;
```

```

        border-radius: 8px;
        border: 1px solid #ccc;
        text-align: center;
    }
    h1 {
        color: #003366;
    }
    video {
        width: 100%;
        border: 3px solid #333;
        border-radius: 5px;
    }

#statusMessage {
    margin-top: 15px;
    font-weight: bold;
    color: green;
}
</style>
<!-- JavaScript -->
<script>
    // Display Video Ready Message
    function videoReady() {
        document.getElementById("statusMessage").innerHTML =
            "Video ready to play";
    }
    // Warn Before Leaving Page
    window.onbeforeunload = function () {
        return "Your form is not completed. Are you sure you want to leave?";
    };
</script>
</head>
<body>
    <!-- Main Container -->
    <div class="container">
        <h1>Community Event Promo</h1>
        <!-- Video Element -->
        <video controls oncanplay="videoReady()">
            <source src="images/event-promo.mp4.mp4" type="video/mp4">
            Your browser does not support the video tag.
        </video>
        <!-- Status Message -->
        <p id="statusMessage"></p>
    </div>
</body>
</html>

```

Geolocation for Event Mapping Scenario:

Practice geolocation.getCurrentPosition, error handling, and options

- Create a button “Find Nearby Events”
- On click, use `getCurrentPosition` to get and display coordinates
- Handle permission denial and timeouts • Use high accuracy options

```
<!DOCTYPE html>
<html lang="en">
<head>
  <!-- Meta Information -->
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <!-- Page Title -->
  <title>Geolocation Event Mapping</title>
  <!-- Internal CSS -->
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color: #f4f4f4;
    }
    .container {
      width: 450px;
      margin: 40px auto;
      background-color: white;
      padding: 20px;
      border-radius: 8px;
      border: 1px solid #ccc;
      text-align: center;
    }
  </style>
</head>
<body>
```

```

}
h1 {
    color: #003366;
}
button {
    width: 100%;
    padding: 10px;
    background-color: #003366;
    color: white;
    border: none;
    cursor: pointer;
    margin-top: 15px;
}
button:hover {
    background-color: #0055aa;
}
#location {
    margin-top: 20px;
    font-weight: bold;
    color: green;
}
</style>
<!-- JavaScript -->
<script>
    // Get User Location
    function findLocation() {
        // Check Browser Support
        if (navigator.geolocation) {
            navigator.geolocation.getCurrentPosition(
                showPosition,
                showError,
                {
                    enableHighAccuracy: true,
                    timeout: 10000,
                    maximumAge: 0
                }
            );
        }
        else {
            document.getElementById("location").innerHTML = "Geolocation is not supported by this browser.";
        }
    }
    // Display Coordinates
    function showPosition(position) {
        let latitude = position.coords.latitude;
        let longitude = position.coords.longitude;
        document.getElementById("location").innerHTML =

```

```

        "Latitude: " + latitude "<br>Longitude: " + longitude;
    }
    // Error Handling
    function showError(error) {
        let message = "";
        switch (error.code) {
            case error.PERMISSION_DENIED:
                message = "Location access denied by user.";
                break;
            case error.POSITION_UNAVAILABLE:
                message = "Location information unavailable.";
                break;
            case error.TIMEOUT:
                message = "Location request timed out.";
                break;
            case error.UNKNOWN_ERROR:
                message = "An unknown error occurred.";
                break;
        }
        document.getElementById("location").innerHTML = message;
    }
</script>
</head>
<body>
    <!-- Main Container -->
    <div class="container">
        <h1>Nearby Event Locator</h1>
        <!-- Find Location Button -->
        <button onclick="findLocation()">
            Find Nearby Events
        </button>
        <!-- Location Output -->
        <p id="location"></p>
    </div>
</body>
</html>

```

Output:

