

# How Can Organisations Innovate?

---

Ambrose Yim, supervised by Stephen Cassidy, Stephen Brewis (BT); Renaud Lambiotte, Andrew Mellor (Oxford)

18 June 2018

InFoMM CDT, Mathematical Institute, University of Oxford

# Motivation

We want to understand the conditions for agents in an organisation to cooperate.

# Motivation

We want to understand the conditions for agents in an organisation to cooperate.

Can a small fraction of 'innovators' in the system influence the entire population to adopt a new idea?

# Motivation

We want to understand the conditions for agents in an organisation to cooperate.

Can a small fraction of 'innovators' in the system influence the entire population to adopt a new idea?

What is the interplay between the population's **willingness** to accept new behaviour and the way they **communicate**?

# Motivation

We want to understand the conditions for agents in an organisation to cooperate.

Can a small fraction of 'innovators' in the system influence the entire population to adopt a new idea?

What is the interplay between the population's **willingness** to accept new behaviour and the way they **communicate**?

What if there are **constraints** that agents are not aware of?

# What we will learn today

Segregating agents into individual teams hinder innovation if new problems come up that require agents across teams to coordinate.

# What we will learn today

Segregating agents into individual teams hinder innovation if new problems come up that require agents across teams to coordinate.

Duh!

# Model

Key modelling assumptions:



# Model

Key modelling assumptions:

- Agents are connected in a **social network** [10] [4]

# Model


Key modelling assumptions:

- Agents are connected in a **social network** [10] [4]
- Each agent receives *information* via its social network

# Model

Key modelling assumptions:

- Agents are connected in a **social network** [10] [4]
- Each agent receives *information* via its social network
- An agent's decision making is *constrained* by the decisions of other agents (**dependency network**)



**Fig. 2.1** **a** Two interdependent networks. A vertex in one network has a mutual dependence, represented by *grey vertical lines*, on zero or one vertex in the other network. **b** This can be reduced to a multiplex network by merging the mutually dependent vertices, and representing the edges of each network by different kinds or *colours* of edges

# Agent behaviour

What is an agent? How do they coordinate? [4]

# Agent behaviour

What is an agent? How do they coordinate? [4]

- Each agent has two states: default (0) or innovate (1)

# Agent behaviour

What is an agent? How do they coordinate? [4]

- Each agent has two states: default (0) or innovate (1)
- All agents start in the default state.

# Agent behaviour

What is an agent? How do they coordinate? [4]

- Each agent has two states: default (0) or innovate (1)
- All agents start in the default state.
- Suppose there is a problem in the organisation that can only be solved if *all* agents coordinate.



# Agent behaviour

# Agent behaviour

- If too few neighbours on the dependency network decide to innovate, then it is not favourable for an agent to innovate

# Agent behaviour

- If too few neighbours on the dependency network decide to innovate, then it is not favourable for an agent to innovate
- Each agent has a **dependency threshold**: number of innovating dependency neighbours for it to 'see' the benefit of innovation

# Agent behaviour

In game theory language, we say the agents play a **coordination game** (a.k.a. **Prisoners' Dilemma**) [9] [5].

# Agent behaviour

In game theory language, we say the agents play a **coordination game** (a.k.a. **Prisoners' Dilemma**) [9] [5].

- **positive pay-off** if it innovates *and* sufficiently many of its dependency neighbours innovate

# Agent behaviour

In game theory language, we say the agents play a **coordination game** (a.k.a. **Prisoners' Dilemma**) [9] [5].

- **positive pay-off** if it innovates *and* sufficiently many of its dependency neighbours innovate
- **negative pay-off** if it innovates *but* not enough agents that constrain you decide with innovate

# Agent behaviour

In game theory language, we say the agents play a **coordination game** (a.k.a. **Prisoners' Dilemma**) [9] [5].

- **positive pay-off** if it innovates *and* sufficiently many of its dependency neighbours innovate
- **negative pay-off** if it innovates *but* not enough agents that constrain you decide with innovate
- **neutral pay-off** if it remains in the default state.

We assume dependency is reflexive; if A influences B then B influences A.

# Agent behaviour



# Agent behaviour

- Agents must first be *aware* of innovation via their social network

# Agent behaviour

- Agents must first be *aware* of innovation via their social network
- Agents have varying 'social awareness': number of 'friends' required to persuade you to adopt new ideas

**Agents must be aware and receive a positive pay-off from innovation to change its state from default to innovation.**

# Network Construction

# Network Construction

- Initially, we assume social network  $\mathcal{S}$  = dependency network  $\mathcal{D}$

# Network Construction

- Initially, we assume social network  $\mathcal{S}$  = dependency network  $\mathcal{D}$
- Over time the business environment changes

# Network Construction

- Initially, we assume social network  $\mathcal{S}$  = dependency network  $\mathcal{D}$
- Over time the business environment changes
- If not updated timely,  $\mathcal{S} \neq \mathcal{D}$

# Network Construction



# Network Construction

We study two modes of ‘information degradation’  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

# Network Construction

We study two modes of ‘information degradation’  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

# Network Construction

We study two modes of ‘information degradation’  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .

# Network Construction

We study two modes of 'information degradation'  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$

# Network Construction

We study two modes of ‘information degradation’  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$
- Network topology (neighbourhood relations) is *altered* (lose memory of neighbours).

# Network Construction

We study two modes of ‘information degradation’  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$
- Network topology (neighbourhood relations) is *altered* (lose memory of neighbours).

2. Random node reshuffle:

# Network Construction

We study two modes of 'information degradation'  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$
- Network topology (neighbourhood relations) is *altered* (lose memory of neighbours).

2. Random node reshuffle:

- Agent degree in  $\mathcal{D} \neq$  degree in  $\mathcal{S}$ .

# Network Construction

We study two modes of 'information degradation'  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$
- Network topology (neighbourhood relations) is *altered* (loose memory of neighbours).

2. Random node reshuffle:

- Agent degree in  $\mathcal{D} \neq$  degree in  $\mathcal{S}$ .
- Network topology is *preserved* (but loose memory of position in network).



# Network Construction

We study two modes of 'information degradation'  $\mathcal{S} \rightarrow \mathcal{D}$  [1]

1. Random edge swap:

- $a - b$  and  $c - d \Rightarrow a - d$  and  $c - b$ .
- Agents preserve their degree (number of neighbours) from  $\mathcal{S} \rightarrow \mathcal{D}$
- Network topology (neighbourhood relations) is *altered* (loose memory of neighbours).

2. Random node reshuffle:

- Agent degree in  $\mathcal{D} \neq$  degree in  $\mathcal{S}$ .
- Network topology is *preserved* (but loose memory of position in network).
- In random degree distribution networks, same as rewiring edges.

## Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

## 2. 'Planted Partition Model'[6]

- Agents are segregated into  $C$  **communities** of equal size  $n$ .

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

## 2. 'Planted Partition Model'[6]

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

## 2. 'Planted Partition Model'[6]

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.

# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

## 2. 'Planted Partition Model'[6]

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.
- Average degree  $z = (n - 1)p_i + (C - 1)np_o$ .



# Random Network Classes

Random graphs with nodes sampled from a degree distribution then randomly connected.

## 1. Erdős-Rényi Graph [2] [8]

- Each pair of nodes has a probability  $p$  of forming an edge.
- Average degree  $z = Np$ . Degree distribution is Binomial.

## 2. 'Planted Partition Model'[6]

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.
- Average degree  $z = (n - 1)p_i + (C - 1)np_o$ .
- We fix  $C = 100$  and  $n = 100$ , with  $(C - 1)np_o = 1/2$ .

# Thresholds

We assume social threshold and dependency thresholds are independent.  
[7]

# Thresholds

We assume social threshold and dependency thresholds are independent.  
[7]

We define the social/dependency threshold = fraction of neighbours above which node becomes aware/susceptible to infection

# Thresholds

We assume social threshold and dependency thresholds are independent.  
[7]

We define the social/dependency threshold = fraction of neighbours above which node becomes aware/susceptible to infection

1. Agent randomly samples both thresholds independently from the same normal distribution (vary mean  $r$  and fix  $\sigma = 0.2$ ) [3]

# Thresholds

We assume social threshold and dependency thresholds are independent.  
[7]

We define the social/dependency threshold = fraction of neighbours above which node becomes aware/susceptible to infection

1. Agent randomly samples both thresholds independently from the same normal distribution (vary mean  $r$  and fix  $\sigma = 0.2$ ) [3]
2. Dependency threshold sampled from normal distribution but social threshold = if one friend is innovating agent is aware.

Agents with a *negative* dependency and social thresholds are *innovators* who would innovate no matter what.

**social network**  $\otimes$  **social threshold**  $\otimes$   
**dependency layer**  $\otimes$  **dependency threshold.**

## Single layer analysis: Watts-Gleeson Theory

Consider social layer = dependency layer and the thresholds are identical for each node.

## Single layer analysis: Watts-Gleeson Theory

Consider social layer = dependency layer and the thresholds are identical for each node.

Watts-Gleeson theory [11] [3] applies to infinite random graphs with negligible clustering (probability of three connected nodes forming a triangle  $\rightarrow 0$  as  $N \rightarrow \infty$ ), or being *locally tree like*.




## Single layer analysis: Watts-Gleeson Theory

Consider social layer = dependency layer and the thresholds are identical for each node.


Watts-Gleeson theory [11] [3] applies to infinite random graphs with negligible clustering (probability of three connected nodes forming a triangle  $\rightarrow 0$  as  $N \rightarrow \infty$ ), or being *locally tree like*.

We can think of this process of synchronously updating the state of nodes as an **infection** from infinitely far away in the network.

## Single layer analysis: Watts-Gleeson Theory




## Single layer analysis: Watts-Gleeson Theory



Initially all nodes are in the 0 state. Infection initiated on level  $n = 0$  at time  $t = 0$ .

## Single layer analysis: Watts-Gleeson Theory




Initially all nodes are in the 0 state. Infection initiated on level  $n = 0$  at time  $t = 0$ .


Probability that a node on layer  $n + 1$  is infected at time  $n + 1$  is dependent on the fraction of nodes infected in layer  $n$ :

$$q_{n+1} = g(q_n ; r) \quad (1)$$

## Single layer analysis: Watts-Gleeson Theory




## Single layer analysis: Watts-Gleeson Theory



Brouwer fixed point theorem: there exists  $q = g(q ; r)$ . Fixed point is either stable or unstable.


## Single layer analysis: Watts-Gleeson Theory



Brouwer fixed point theorem: there exists  $q = g(q ; r)$ . Fixed point is either stable or unstable.

Final layer must be a (stable) fixed point. Let  $q_{\infty} = \Pr(\text{infection on final layer} \mid \text{top node inactive})$ .

## Single layer analysis: Watts-Gleeson Theory



Brouwer fixed point theorem: there exists  $q = g(q ; r)$ . Fixed point is either stable or unstable.

Final layer must be a (stable) fixed point. Let  $q_{\infty} = \Pr(\text{infection on final layer} \mid \text{top node inactive})$ .


Final fraction of infected nodes is

$$\rho = \rho(q_{\infty} ; r) \quad (2)$$




## Single layer analysis: Watts-Gleeson Theory

We look at Erdős-Rényi graphs of varying mean degree.




**Figure 1:**  $g(q) - q$  for parameters  $z = 4$ ; solid is  $r = 0.35$ , dashed is  $r = 0.371$

## Single layer analysis: Watts-Gleeson Theory




**Figure 2:**  $g(q) - q$  for parameters  $z = 4$ ; solid is  $r = 0.35$ , dot-dashed is  $r = 0.3543$ , dashed is  $r = 0.375$

# Single layer analysis: Watts-Gleeson Theory



**Figure 3:** Fixed point plot for increasing  $r$ . Note Goldilocks zone in middle figure.


# Single layer analysis: Watts-Gleeson Theory



**Figure 4:** Fixed point plot for increasing  $z$ .


# Single layer analysis: Watts-Gleeson Theory

Phase transition boundary: discontinuity in  $q_\infty(z, r)$ .




# Double layer analysis: Watts-Gleeson Theory

Technically need two  $q$  probabilities for the two different layers respectively; however agent randomly samples both thresholds independently from the *same* normal distribution, so symmetry reduces the system to one variable.




**Figure 5:** Final fraction size vs  $(z, r)$ ; white curve second order cascade condition

# Double layer analysis: Watts-Gleeson Theory



**Figure 6:** Edge swap: Fixed points cross section across different  $r$  values. Note that the Goldilocks zone disappears.

# Double layer analysis: Watts-Gleeson Theory



**Figure 7:** Node swap: Fixed points cross section across different  $r$  values. Note that the Goldilocks zone disappears.



# Summary of Analytical Results

## Summary of Analytical Results

- The final infection size decreases as  $r$  increases

## Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases

# Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases
- Transition becomes *discontinuous* for values of  $r$  and  $z$  greater than some critical value.

## Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases
- Transition becomes *discontinuous* for values of  $r$  and  $z$  greater than some critical value.
- Discontinuous transition separates two 'phases' where the global cascade is extensive across the population and the other where the infection does not spread.

## Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases
- Transition becomes *discontinuous* for values of  $r$  and  $z$  greater than some critical value.
- Discontinuous transition separates two 'phases' where the global cascade is extensive across the population and the other where the infection does not spread.
- Adding an extra layer lowers the critical value of  $r$  where the discontinuity takes place.

## Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases
- Transition becomes *discontinuous* for values of  $r$  and  $z$  greater than some critical value.
- Discontinuous transition separates two 'phases' where the global cascade is extensive across the population and the other where the infection does not spread.
- Adding an extra layer lowers the critical value of  $r$  where the discontinuity takes place.
- In single layer, there is a competition between the benefits of increasing node degree to increase the chance of exposure vs the increase in a agent's degree of dependency: **Goldilocks zone effect**

# Summary of Analytical Results

- The final infection size decreases as  $r$  increases
- The transition becomes steeper and steeper as  $z$  increases
- Transition becomes *discontinuous* for values of  $r$  and  $z$  greater than some critical value.
- Discontinuous transition separates two 'phases' where the global cascade is extensive across the population and the other where the infection does not spread.
- Adding an extra layer lowers the critical value of  $r$  where the discontinuity takes place.
- In single layer, there is a competition between the benefits of increasing node degree to increase the chance of exposure vs the increase in an agent's degree of dependency: **Goldilocks zone effect**
- In double layer, this zone is missing.



## Simulation: clustering effects

'Planted Partition Model'

- Agents are segregated into  $C$  **communities** of equal size  $n$ .

## Simulation: clustering effects

### 'Planted Partition Model'

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.

## Simulation: clustering effects

### 'Planted Partition Model'

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.

## Simulation: clustering effects

### 'Planted Partition Model'

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.
- Average degree  $z = (n - 1)p_i + (C - 1)np_o$ .


## Simulation: clustering effects

### 'Planted Partition Model'

- Agents are segregated into  $C$  **communities** of equal size  $n$ .
- Between pairs of nodes in the same community there is a probability  $p_i$  of forming an edge.
- Between pairs of nodes in different communities there is a probability  $p_o$  of forming an edge.
- Average degree  $z = (n - 1)p_i + (C - 1)np_o$ .
- We fix  $C = 100$  and  $n = 100$ , with  $(C - 1)np_o = 1/2$ .

## Simulation: clustering effects


'Planted Partition Model'



**Figure 8:** Image due to Preston Engstrom


## Simulation: clustering effects

In our simulations we run the infection on networks of 100 communities, each with 100 members. Average number of edges outside the community is kept at 0.5 per node.



**Figure 9:** Single Layer simulation. Curve overlays are approximate theoretical thresholds of single layer ER graphs.

## Simulation: clustering effects




**Figure 10:** Phase plane with dependency network = edge swap, randomised thresholds.

N.B. in random edge swap, the dependency layer the network loses memory of its community structure and becomes an ER graph.



## Simulation: clustering effects




**Figure 11:** Phase plane with dependency network = node swap, randomised thresholds.

This scenario represents communities of agents trying to solve a *structured* problem which does not correspond to the same social community structure.

## Contact Awareness

If the threshold to be socially aware is for only *one* friend to innovate...


## Contact Awareness: Edge swap ER



**Figure 12:** Phase plane with dependency network = edge swap of ER, contact threshold.

Very similar to situation without social network N.B. no Goldilocks.


## Contact Awareness: Node swap ER



**Figure 13:** Phase plane with dependency network = node swap of ER, contact threshold.

Very similar to situation without social network N.B. no Goldilocks.


## Contact Awareness: ER Dependency, PP Social



**Figure 14:** Dependency = ER, Social = PP, contact threshold.


Very similar to situation without social network N.B. no Goldilocks.

# Contact Awareness: PP Dependency, ER Social



**Figure 15:** Dependency = PP, Social = ER, contact threshold.

## Contact Awareness: node swap, PP Dependency, PP Social



**Figure 16:** Dependency = PP, Social = ER, contact threshold.

Limited extent of infection appears again when PP swaps nodes.

# Summary

- There is a **phase transition** between very little coordination to extensive, population wide coordination at critical values of *social awareness* and *degree of dependency*
- Highly socially aware agents are safe against decoupling of social and dependency network
- Community networks are inflexible against solving structured problems whose dependencies do not correspond to the same community structure. (*Limited horizon of infection*)
- Node swap is more dangerous because it disconnects agents with a high degree of dependency.
- Future extensions: different threshold distributions, different network topologies, adaptive social networks.



**Major thanks to my supervisors Stephen  
Cassidy and Stephen Brewis @BT and Renaud  
Lambiotte and Andrew Mellor @Oxford.**

# References

---



Charles D. Brummitt, Kyu-Min Lee, and K.-I. Goh.  
“Multiplexity-facilitated cascades in networks”. In: *Physical Review E* 85.4 (Apr. 27, 2012), p. 045102. DOI:  
10.1103/PhysRevE.85.045102. URL:  
<https://link.aps.org/doi/10.1103/PhysRevE.85.045102>  
(visited on 05/30/2018).



P Erdős and A Rényi. “On random graphs, I”. In: *Publicationes Mathematicae (Debrecen)* 6 (1959), pp. 290–297. URL:  
[http://www.renyi.hu/~p\\_erdos/Erdos.html#1959-11](http://www.renyi.hu/~p_erdos/Erdos.html#1959-11) (visited  
on 06/17/2018).



James P. Gleeson and Diarmuid J. Cahalane. “Seed size strongly affects cascades on random networks”. In: *Physical Review E* 75.5 (May 3, 2007). ISSN: 1539-3755, 1550-2376. DOI: 10.1103/PhysRevE.75.056103. URL: <https://link.aps.org/doi/10.1103/PhysRevE.75.056103> (visited on 05/30/2018).



Clara Granell, Sergio Gómez, and Alex Arenas. “Dynamical Interplay between Awareness and Epidemic Spreading in Multiplex Networks”. In: *Physical Review Letters* 111.12 (Sept. 17, 2013). ISSN: 0031-9007, 1079-7114. DOI: 10.1103/PhysRevLett.111.128701. URL: <https://link.aps.org/doi/10.1103/PhysRevLett.111.128701> (visited on 06/13/2018).



Matthew O. Jackson and Yves Zenou. *Games on Networks*. SSRN Scholarly Paper ID 2136179. Rochester, NY: Social Science Research Network, Jan. 1, 2014. URL: <https://papers.ssrn.com/abstract=2136179> (visited on 05/09/2018).



Brian Karrer and M. E. J. Newman. "Stochastic blockmodels and community structure in networks". In: *Physical Review E* 83.1 (Jan. 21, 2011). ISSN: 1539-3755, 1550-2376. DOI: 10.1103/PhysRevE.83.016107. arXiv: 1008.3926. URL: <http://arxiv.org/abs/1008.3926> (visited on 05/22/2018).



Kyu-Min Lee, Charles D. Brummitt, and K.-I. Goh. "Threshold cascades with response heterogeneity in multiplex networks". In: *Physical Review E* 90.6 (Dec. 29, 2014), p. 062816. DOI: 10.1103/PhysRevE.90.062816. URL: <https://link.aps.org/doi/10.1103/PhysRevE.90.062816> (visited on 06/17/2018).



M. E. J. Newman, S. H. Strogatz, and D. J. Watts. “Random graphs with arbitrary degree distributions and their applications”. In: *Physical Review E* 64.2 (July 24, 2001). ISSN: 1063-651X, 1095-3787. DOI: 10.1103/PhysRevE.64.026118. arXiv: cond-mat/0007235. URL: <http://arxiv.org/abs/cond-mat/0007235> (visited on 05/18/2018).



Yoav Shoham and Kevin Leyton-Brown. *Multiagent Systems: Algorithmic, Game-Theoretic, and Logical Foundations*. Cambridge: Cambridge University Press, 2008. ISBN: 978-0-511-81165-4. DOI: 10.1017/CB09780511811654. URL: <http://ebooks.cambridge.org/ref/id/CB09780511811654> (visited on 03/29/2018).



Wei Wang, Meng Cai, and Muhua Zheng. “Social contagions on correlated multiplex networks”. In: *Physica A: Statistical Mechanics and its Applications* 499 (June 1, 2018), pp. 121–128. ISSN: 0378-4371. DOI: 10.1016/j.physa.2017.12.081. URL: <http://www.sciencedirect.com/science/article/pii/S0378437117313304> (visited on 05/30/2018).



Duncan J. Watts. “A simple model of global cascades on random networks”. In: *Proceedings of the National Academy of Sciences* 99.9 (Apr. 30, 2002), pp. 5766–5771. ISSN: 0027-8424, 1091-6490. DOI: 10.1073/pnas.082090499. URL: <http://www.pnas.org/content/99/9/5766> (visited on 05/29/2018).