Documentation

search

Search

• rocket launch

Get started

- <u>Installation</u> add
- Fundamentals add
- First steps add
- code

<u>Develop</u>

- Concepts add
- API reference

remove

- PAGE ELEMENTS
- Write and magic

add

■ <u>Text elements</u> add

Data elements

add

• Chart elements

add

• <u>Input widgets</u>

add

Media elements

add

Layouts and containers

• Chat elements add

Status elements

add

- <u>Third-party componentsopen in new</u>
- APPLICATION LOGIC
- Navigation and pages

remove

- st.navigation
- st.Page
- <u>st.page linklink</u>
- st.switch page
- Execution flow

add

Caching and state

add Connections and secrets Custom components Utilities add Configuration add TOOLS App testing add Command line add Tutorials add • Quick reference add web asset <u>Deploy</u> • Concepts add • Streamlit Community Cloud add • Snowflake • Other platforms add school Knowledge base o <u>FAQ</u> • <u>Installing dependencies</u> • <u>Deployment issues</u> Home/ <u>Develop/</u> • API reference/ • Navigation and pages/ • st.Page st.Page

Streamlit Version Version 1.41.0

Configure a page for st.navigation in a multipage app.

Call st.Page to initialize a StreamlitPage object, and pass it to st.navigation to declare a page in your app.

When a user navigates to a page, st.navigation returns the selected StreamlitPage object. Call .run() on the returned StreamlitPage object to execute the page. You can only run the page returned by st.navigation, and you can only run it once per app rerun.

A page can be defined by a Python file or Callable. Python files used as a StreamlitPage source will have name == "__page__". Functions used as a StreamlitPage source will have __name__ corresponding to the module they were imported from. Only the entrypoint file and functions defined within the entrypoint file have name == " main " to adhere to Python convention.

Function signature source

st.Page(page, *, title=None, icon=None, url_path=None, default=False)

Parameters

page (str, Path, or callable)

The page source as a Callable or path to a Python file. If the page source is defined by a Python file, the path can be a string or pathlib. Path object. Paths can be absolute or relative to the entrypoint file. If the page source is defined by a Callable, the Callable can't accept arguments.

The title of the page. If this is None (default), the page title (in the browser tab) and label (in the title (str or None) navigation menu) will be inferred from the filename or callable name in page. For more information, see Overview of multipage apps.

> An optional emoji or icon to display next to the page title and label. If icon is None (default), no icon is displayed next to the page label in the navigation menu, and a Streamlit icon is displayed next to the title (in the browser tab). If icon is a string, the following options are valid:

• A single-character emoji. For example, you can set icon="" "

icon (str or None)

or icon="0". Emoji short codes are not supported.

• An icon from the Material Symbols library (rounded style) in the

format ":material/icon name: " where "icon_name" is the name of the icon in snake case.

For example, icon=":material/thumb up:" will display the Thumb Up icon. Find additional icons in the Material Symbols font library.

url_path (str or None)

The page's URL pathname, which is the path relative to the app's root URL. If this is None (default), the URL pathname will be inferred from the filename or callable name in page. For more information, see Overview of multipage apps.

The default page will have a pathname of "", indicating the root URL of the app. If you set default=True, url path is ignored. url path can't include forward slashes; paths can't include subdirectories.

default (bool)

Whether this page is the default page to be shown when the app is loaded. If default is False (default), the page will have a nonempty URL pathname. However, if no default page is passed to st.navigation and this is the first page, this page will become the default page. If default is True, then the page will have an empty pathname and url path will be ignored.

Returns

(StreamlitPage) The page object associated to the given script.

Example

```
import streamlit as st

def page2():
    st.title("Second page")

pg = st.navigation([
    st.Page("page1.py", title="First page", icon="%"),
    st.Page(page2, title="Second page", icon=":material/favorite:"),
])
pg.run()
```

StreamlitPage



Streamlit Version Version 1.41.0

A page within a multipage Streamlit app.

Use st.Page to initialize a StreamlitPage object.

Class description[source]

StreamlitPage(page, *, title=None, icon=None, url_path=None, default=False)

Methods

<u>run()</u> Execute the page.

Attributes

The icon of the page.

icon (str)

If no icon was declared in st.Page, this property returns "".

The title of the page.

title (str)

Unless declared otherwise in st.Page, the page title is inferred from the filename or callable name. For more information, see <u>Overview of multipage apps</u>.

The page's URL pathname, which is the path relative to the app's root URL.

url_path (str)

Unless declared otherwise in st.Page, the URL pathname is inferred from the filename or callable name. For more information, see <u>Overview of multipage apps</u>.

The default page will always have a url_path of "" to indicate the root URL (e.g. homepage).

StreamlitPage.run



Streamlit Version Version 1.41.0

Execute the page.

When a page is returned by st.navigation, use the .run() method within your entrypoint file to render the page. You can only call this method on the page returned by st.navigation. You can only call this method once per run of your entrypoint file.

Function signature[source]

StreamlitPage.run()

←<u>Previous: st.navigationNext: st.page link</u>→
forum

Still have questions?

Our **forums** are full of helpful information and Streamlit experts.

HomeContact UsCommunity



© 2025 Snowflake Inc. Cookie policy

forum Ask Al