

[Documentation](#)

search

Search

- [rocket launch](#)

[Get started](#)

- [Installation](#)
add
- [Fundamentals](#)
add
- [First steps](#)
add
- [code](#)

[Develop](#)

- [Concepts](#)
add
 - [API reference](#)
remove
 - PAGE ELEMENTS
-
- [Write and magic](#)
add
 - [Text elements](#)
add
 - [Data elements](#)
remove
 - [st.dataframe](#)
 - [st.data_editor](#)
 - [st.column_config](#)
add
 - [st.table](#)
 - [st.metric](#)
 - [st.json](#)
 - [Chart elements](#)
add
 - [Input widgets](#)
add
 - [Media elements](#)
add
 - [Layouts and containers](#)
add
 - [Chat elements](#)
add
 - [Status elements](#)
add
 - [Third-party components](#)*open in new*
 - APPLICATION LOGIC
-
- [Navigation and pages](#)
add

- [Execution flow](#)
add
- [Caching and state](#)
add
- [Connections and secrets](#)
add
- [Custom components](#)
add
- [Utilities](#)
add
- [Configuration](#)
add
- TOOLS

-
- [App testing](#)
add
 - [Command line](#)
add

- [Tutorials](#)
add
- [Quick reference](#)
add
- [web_asset](#)

[Deploy](#)

- [Concepts](#)
add
- [Streamlit Community Cloud](#)
add
- [Snowflake](#)
- [Other platforms](#)
add
- [school](#)

[Knowledge base](#)

- [FAQ](#)
- [Installing dependencies](#)
- [Deployment issues](#)
- [Home/](#)
- [Develop/](#)
- [API reference/](#)
- [Data elements/](#)
- [st.table](#)

star

Tip

Static tables with `st.table` are the most basic way to display dataframes. For the majority of cases, we recommend using [st.dataframe](#) to display interactive dataframes, and [st.data_editor](#) to let users edit dataframes.

st.table



Display a static table.

This differs from `st.dataframe` in that the table in this case is static: its entire contents are laid out directly on the page.

Function signature [\[source\]](#)

`st.table(data=None)`

Parameters


`data` (Anything supported by `st.dataframe`) The table data.


Example

```
import streamlit as st
import pandas as pd
import numpy as np

df = pd.DataFrame(
    np.random.randn(10, 5), columns=("col %d" % i for i in range(5))
)

st.table(df)
```



[Built with Streamlit](#) 
[Fullscreen open in new](#)

element.add_rows



Concatenate a dataframe to the bottom of the current one.

Function signature[\[source\]](#)

element.add_rows(data=None, **kwargs)

Parameters

data (pandas.DataFrame, pandas.Styler, pyarrow.Table, numpy.ndarray, pyspark.sql.DataFrame, snowflake.snowpark.dataframe.DataFrame, Iterable, dict, or None) Table to concat. Optional.

****kwargs** (pandas.DataFrame, numpy.ndarray, Iterable, dict, or None) The named dataset to concat. Optional.
You can only pass in 1 dataset (including the one in the data parameter).

Example

```
import streamlit as st
import pandas as pd
import numpy as np

df1 = pd.DataFrame(
    np.random.randn(50, 20), columns=("col %d" % i for i in range(20))
)

my_table = st.table(df1)

df2 = pd.DataFrame(
    np.random.randn(50, 20), columns=("col %d" % i for i in range(20))
)

my_table.add_rows(df2)
# Now the table shown in the Streamlit app contains the data for
# df1 followed by the data for df2.
```

You can do the same thing with plots. For example, if you want to add more data to a line chart:

```
# Assuming df1 and df2 from the example above still exist...
my_chart = st.line_chart(df1)
my_chart.add_rows(df2)
# Now the chart shown in the Streamlit app contains the data for
# df1 followed by the data for df2.
```

And for plots whose datasets are named, you can pass the data with a keyword argument where the key is the name:

```
my_chart = st.vega_lite_chart(
    {
        "mark": "line",
        "encoding": {"x": "a", "y": "b"},
        "datasets": {
            "some_fancy_name": df1, # <-- named dataset
        },
        "data": {"name": "some_fancy_name"},
    }
)
my_chart.add_rows(some_fancy_name=df2) # <-- name used as keyword
```

Still have questions?

Our [forums](#) are full of helpful information and Streamlit experts.

[Home](#)
[Contact Us](#)
[Community](#)



© 2025 Snowflake Inc.
 [Cookie policy](#)

[forum](#)
[Ask AI](#)