

[Documentation](#)

search

Search

- [rocket launch](#)

[Get started](#)

- [Installation](#)
add
- [Fundamentals](#)
add
- [First steps](#)
add
- [code](#)

[Develop](#)

- [Concepts](#)
add
- [API reference](#)
remove
 - PAGE ELEMENTS

 - [Write and magic](#)
add
 - [Text elements](#)
add
 - [Data elements](#)
add
 - [Chart elements](#)
add
 - [Input widgets](#)
add
 - [Media elements](#)
add
 - [Layouts and containers](#)
add
 - [Chat elements](#)
add
 - [Status elements](#)
add
 - [Third-party components](#)*open in new*
 - APPLICATION LOGIC

 - [Navigation and pages](#)
add
 - [Execution flow](#)
remove
 - [st.dialog](#)
 - [st.form](#)
 - [st.form submit button](#)
 - [st.fragment](#)
 - [st.rerun](#)

- [st.stop](#)
add
 - [Caching and state](#)
add
 - [Connections and secrets](#)
add
 - [Custom components](#)
add
 - [Utilities](#)
add
 - [Configuration](#)
add
 - TOOLS
-
- [App testing](#)
add
 - [Command line](#)
add
 - [Tutorials](#)
add
 - [Quick reference](#)
add
 - [web asset](#)

[Deploy](#)

- [Concepts](#)
add
- [Streamlit Community Cloud](#)
add
- [Snowflake](#)
- [Other platforms](#)
add
- [school](#)

[Knowledge base](#)

- [FAQ](#)
- [Installing dependencies](#)
- [Deployment issues](#)
- [Home/](#)
- [Develop/](#)
- [API reference/](#)
- [Execution flow/](#)
- [st.rerun](#)

st.rerun



Streamlit Version ▼

Rerun the script immediately.

When `st.rerun()` is called, Streamlit halts the current script run and executes no further statements. Streamlit immediately queues the script to rerun.

When using `st.rerun` in a fragment, you can scope the rerun to the fragment. However, if a fragment is running as part of a full-app rerun, a fragment-scoped rerun is not allowed.

`st.rerun(*, scope="app")`

Parameters

	Specifies what part of the app should rerun. If <code>scope</code> is "app" (default), the full app reruns. If <code>scope</code> is "fragment", Streamlit only reruns the fragment from which this command is called.
<code>scope</code> ("app" or "fragment")	Setting <code>scope="fragment"</code> is only valid inside a fragment during a fragment rerun. If <code>st.rerun(scope="fragment")</code> is called during a full-app rerun or outside of a fragment, Streamlit will raise a <code>StreamlitAPIException</code> .

Caveats for `st.rerun`



`st.rerun` is one of the tools to control the logic of your app. While it is great for prototyping, there can be adverse side effects:

- Additional script runs may be inefficient and slower.
- Excessive reruns may complicate your app's logic and be harder to follow.
- If misused, infinite looping may crash your app.

In many cases where `st.rerun` works, [callbacks](#) may be a cleaner alternative. [Containers](#) may also be helpful.

A simple example in three variations



Using `st.rerun` to update an earlier header

```
import streamlit as st
if "value" not in st.session_state:
    st.session_state.value = "Title" #####
Option using st.rerun #####
st.header(st.session_state.value)
if st.button("Foo"):
    st.session_state.value = "Foo"
    st.rerun()
```

Using a callback to update an earlier header

```
##### Option using a callback #####
st.header(st.session_state.value)
def update_value():
    st.session_state.value = "Bar"
st.button("Bar", on_click=update_value)
```

Using containers to update an earlier header

```
##### Option using a container #####
container = st.container()
if st.button("Baz"):
    st.session_state.value = "Baz"
    container.header(st.session_state.value)
```

[←Previous: st.fragment](#)[Next: st.stop→](#)

forum

Still have questions?

Our [forums](#) are full of helpful information and Streamlit experts.

