

[Documentation](#)

search

Search

- [rocket launch](#)

[Get started](#)

- [Installation](#)
add
- [Fundamentals](#)
add
- [First steps](#)
add
- [code](#)

[Develop](#)

- [Concepts](#)
add
- [API reference](#)
remove
 - PAGE ELEMENTS

 - [Write and magic](#)
add
 - [Text elements](#)
remove
 - HEADINGS & BODY

 - [st.title](#)
 - [st.header](#)
 - [st.subheader](#)
 - [st.markdown](#)
 - FORMATTED TEXT

 - [st.caption](#)
 - [st.code](#)
 - [st.divider](#)
 - [st.echo](#)
 - [st.latex](#)
 - [st.text](#)
 - UTILITIES

 - [st.htmllink](#)
- [Data elements](#)
add
- [Chart elements](#)
add
- [Input widgets](#)
add
- [Media elements](#)
add
- [Layouts and containers](#)

add

- [Chat elements](#)
add
 - [Status elements](#)
add
 - [Third-party components](#)*open in new*
 - APPLICATION LOGIC
-

- [Navigation and pages](#)
add
 - [Execution flow](#)
add
 - [Caching and state](#)
add
 - [Connections and secrets](#)
add
 - [Custom components](#)
add
 - [Utilities](#)
add
 - [Configuration](#)
add
 - TOOLS
-

- [App testing](#)
add
- [Command line](#)
add

- [Tutorials](#)
add
- [Quick reference](#)
add

- [web asset](#)

[Deploy](#)

- [Concepts](#)
add
- [Streamlit Community Cloud](#)
add
- [Snowflake](#)
- [Other platforms](#)
add

- [school](#)

[Knowledge base](#)

- [FAQ](#)
- [Installing dependencies](#)
- [Deployment issues](#)

- [Home/](#)
- [Develop/](#)
- [API reference/](#)
- [Text elements/](#)
- [st.echo](#)



Streamlit Version 

Use in a *with* block to draw some code on the app, then execute it.

Function signature[\[source\]](#)

st.echo(code_location="above")

Parameters

code_location ("above" or "below") Whether to show the echoed code before or after the results of the executed code block.

Example

```
import streamlit as st

with st.echo():
    st.write('This code will be printed')
```

Display code



Sometimes you want your Streamlit app to contain *both* your usual Streamlit graphic elements *and* the code that generated those elements. That's where `st.echo()` comes in.

Ok so let's say you have the following file, and you want to make its app a little bit more self-explanatory by making that middle section visible in the Streamlit app:

```
import streamlit as st def get_user_name(): return 'John' # -----
----- # Want people to see this part of the code... def get_punctuation(): return '!!!' greeting =
"Hi there, " user_name = get_user_name() punctuation = get_punctuation() st.write(greeting, user_name,
punctuation) # ...up to here # ----- foo = 'bar'
st.write('Done!')
```

The file above creates a Streamlit app containing the words "Hi there, John", and then "Done!".

Now let's use `st.echo()` to make that middle section of the code visible in the app:

```
import streamlit as st def get_user_name(): return 'John' with st.echo(): # Everything inside this
block will be both printed to the screen # and executed. def get_punctuation(): return '!!!' greeting
= "Hi there, " value = get_user_name() punctuation = get_punctuation() st.write(greeting, value,
punctuation) # And now we're back to _not_ printing to the screen foo = 'bar' st.write('Done!')
```

It's *that* simple!

push_pin

Note

You can have multiple `st.echo()` blocks in the same file. Use it as often as you wish!

[←Previous: st.divider](#)[Next: st.latex→](#)
forum

Still have questions?

Our [forums](#) are full of helpful information and Streamlit experts.

[Home](#)[Contact Us](#)[Community](#)



© 2025 Snowflake Inc. [Cookie policy](#)

[forum](#) [Ask AI](#)