🧠 MemoGraph — Complete Build Architecture

A Self-Healing, Bandwidth-Aware Memory System for AI Agents

Inspired by Claude Code's leaked `src/services/autoDream/`, `consolidationLock.ts`, `consolidationPrompt.ts`, and `MEMORY.md` architecture

---

📐 PART 0 — DESIGN PHILOSOPHY (Why This Exists)

Before writing a single line of code, understand the core problem this solves:

Most agents get worse the longer they run because their context fills up with stale observations. Claude Code's architecture keeps the active context small (just the index) and only loads what's needed.[1]

If you're building any agent that runs over multiple sessions, unbounded memory will kill you. Not immediately. Over weeks. Your agent starts referencing things that are no longer true, duplicating observations, and filling context with noise. You need some form of consolidation.[1]

Most memory systems do time-based cleanup — old stuff gets archived or deleted. That's fine for preventing memory bloat, but it doesn't catch contradictions. Two conflicting observations can coexist for months.[1]

The three design axioms for MemoGraph, derived directly from the source:

1. Bandwidth Awareness — A lightweight pointer file stays permanently loaded. Each entry is under 150 characters, just enough to tell the agent "I've remembered something about X, here's where the details are." Tiny token cost, always available.[2]
2. Skeptical Memory — The "blueprint" is clear: build a skeptical memory. The code confirms that Anthropic's agents are instructed to treat their own memory as a "hint," requiring the model to verify facts against the actual codebase before proceeding.[3]
3. Strict Write Discipline — The agent must update its index only after a successful file write — this prevents the model from polluting its context with failed attempts.[3]

🏛️ PART 1 — THE THREE-LAYER MEMORY ARCHITECTURE

This is the core structural insight from the leak. Implement this exactly.

The leaked source reveals a sophisticated, three-layer memory architecture that moves away from traditional "store-everything" retrieval. At its core is MEMORY.md, a lightweight index of pointers (~150 characters per line) that is perpetually loaded into the context. This index does not store data; it stores locations. Actual project knowledge is distributed across "topic files" fetched on-demand, while raw transcripts are never fully read back into the context, but merely "grep'd" for specific identifiers.[3]

Layer 1 — The Index (`MEMORY.md` / `memory_index.json`)

What it is: A permanently-loaded, ultra-lightweight pointer map. Never stores facts — only stores *addresses* of facts.

Constraints from source:

1. Keep MEMORY.md under 200 lines AND ~25KB. Remove stale pointers. Resolve contradictions.[4]

2. Each line: ~150 characters max (pointer + topic + last-updated timestamp)

MemoGraph Index Schema:

Python

```python
# memograph/models/index.py

from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional
import json

@dataclass
class IndexPointer:
    """
    One line in MEMORY.md / memory_index.json
    Max 150 chars when serialized to string form.
    """
    topic_id: str           # e.g., "proj_architecture"
    topic_file: str         # e.g., "topics/proj_architecture.md"
    summary: str            # ≤ 80 chars: what this topic contains
    last_updated: datetime
    confidence: float       # 0.0-1.0 (skeptical memory principle)
    verification_source: Optional[str] = None  # where to verify

    def to_index_line(self) -> str:
        """Serialize to single ~150-char index line."""
        ts = self.last_updated.strftime("%Y-%m-%d")
        conf = f"{self.confidence:.1f}"
        return f"[{self.topic_id}] {self.summary} → {self.topic_file} ({ts}, conf={conf})"

    def __len__(self):
        return len(self.to_index_line())

@dataclass
class MemoryIndex:
    """
    The full MEMORY.md equivalent.
    Hard limits: 200 pointers, 25KB total.
    """
    pointers: list[IndexPointer] = field(default_factory=list)
    version: int = 1
    last_consolidated: Optional[datetime] = None
    agent_id: str = "default"

    MAX_LINES = 200
    MAX_BYTES = 25 * 1024  # 25KB

    def is_full(self) -> bool:
        return (len(self.pointers) >= self.MAX_LINES or
                len(self.to_markdown().encode()) >= self.MAX_BYTES)

    def to_markdown(self) -> str:
        lines = [f"# Memory Index (Agent: {self.agent_id})",
                 f"Last consolidated: {self.last_consolidated}",
                 "---"]
```

```
        for p in self.pointers:
            lines.append(p.to_index_line())
        return "\n".join(lines)

    def get_context_injection(self) -> str:
        """What gets injected into EVERY prompt turn — just the index."""



            return self.to_markdown()
```

Layer 2 — Topic Files (On-Demand)

What they are: The actual knowledge store. Fetched only when the index pointer is relevant to the current query. Never all loaded simultaneously.

Python

```
# memograph/models/topic.py

from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional
from enum import Enum

class ConfidenceLevel(Enum):
    VERIFIED = "verified"      # Confirmed against ground truth
    OBSERVED = "observed"      # Seen but not verified
    INFERRED = "inferred"      # Derived by the agent
    STALE = "stale"            # Flagged for re-verification

@dataclass
class MemoryFact:
    """
    A single atomic fact within a topic file.
    Skeptical memory: every fact carries a confidence + source.
    """
    content: str
    confidence: ConfidenceLevel
    source: str                # Where this came from
    created_at: datetime
    last_verified: Optional[datetime] = None
    contradicts: list[str] = field(default_factory=list)  # IDs of contradicting facts
    fact_id: str = ""

@dataclass
class TopicFile:
    """
    Layer 2: A single topic's full knowledge store.
    Fetched on-demand based on index relevance.
    """
    topic_id: str
    topic_name: str
```

```
    facts: list[MemoryFact] = field(default_factory=list)
    tags: list[str] = field(default_factory=list)
    created_at: datetime = field(default_factory=datetime.now)
    last_modified: datetime = field(default_factory=datetime.now)

    def to_markdown(self) -> str:
        """Human and LLM-readable format."""
        lines = [
            f"# Topic: {self.topic_name}",
            f"ID: {self.topic_id}",
            f"Tags: {', '.join(self.tags)}",
            f"Last modified: {self.last_modified}",
            "---",
            "## Facts"
        ]
        for fact in self.facts:
            conf_emoji = {"verified": "✅", "observed": "👁️",
                          "inferred": "💭", "stale": "⚠️"}
            lines.append(
                f"{conf_emoji[fact.confidence.value]} [{fact.fact_id}] "
                f"{fact.content}\n"
                f"   Source: {fact.source} | Verified: {fact.last_verified}"
            )
        return "\n".join(lines)

    def get_contradictions(self) -> list[tuple[MemoryFact, MemoryFact]]:
        """Detect internal contradictions within a topic."""
        contradictions = []
        for fact in self.facts:
            for contra_id in fact.contradicts:
                contra = next((f for f in self.facts
                               if f.fact_id == contra_id), None)
                if contra:
                    contradictions.append((fact, contra))



        return contradictions
```

Layer 3 — Transcripts (Never Loaded Directly)

What they are: Raw session logs. Never injected into context. Only grep'd for specific identifiers.

Python

```
# memograph/models/transcript.py

import re
import json
from pathlib import Path
from datetime import datetime
from typing import Iterator
```

```python
@dataclass
class TranscriptEntry:
    session_id: str
    timestamp: datetime
    role: str          # "user" | "assistant" | "tool"
    content: str
    tool_calls: list[dict] = field(default_factory=list)

class TranscriptStore:
    """
    Layer 3: Raw session archive.
    NEVER loaded wholesale into context.
    Only grep'd for specific identifiers.
    This mirrors Claude Code's approach: transcripts are grep'd,
    not read back. (src/services/memory/transcriptSearch.ts)
    """
    def __init__(self, store_path: Path):
        self.store_path = store_path
        self.store_path.mkdir(parents=True, exist_ok=True)

    def write_session(self, session_id: str,
                      entries: list[TranscriptEntry]) -> Path:
        """Write session to JSONL — append-only."""
        session_file = self.store_path / f"{session_id}.jsonl"
        with open(session_file, "a") as f:
            for entry in entries:
                f.write(json.dumps({
                    "ts": entry.timestamp.isoformat(),
                    "role": entry.role,
                    "content": entry.content,
                    "tool_calls": entry.tool_calls
                }) + "\n")
        return session_file

    def grep_sessions(self,
                      pattern: str,
                      session_ids: list[str] | None = None,
                      max_results: int = 20) -> Iterator[dict]:
        """
        GREP ONLY — never reads full transcripts into memory.
        Mirrors: src/services/memory/transcriptSearch.ts
        """
        compiled = re.compile(pattern, re.IGNORECASE)
        files = (
            [self.store_path / f"{sid}.jsonl" for sid in session_ids]
            if session_ids
            else list(self.store_path.glob("*.jsonl"))
        )
        count = 0
        for f in sorted(files, key=lambda x: x.stat().st_mtime, reverse=True):
            if count >= max_results:
                break
            for line in open(f):
                if compiled.search(line):
                    yield {"file": f.name, "match": json.loads(line)}
                    count += 1
                    if count >= max_results:
```

```
                    break

    def count_sessions_since(self, since: datetime) -> int:
        """Used by autoDream trigger gate."""
        return sum(
            1 for f in self.store_path.glob("*.jsonl")
            if datetime.fromtimestamp(f.stat().st_mtime) > since


            )
```

🔧 PART 2 — THE CRUD API WITH AUTOMATIC INDEX MANAGEMENT

The write discipline is the most critical design constraint. Write to topic first, THEN update index. Never the reverse.

Python

```python
# memograph/core/memory_manager.py

import uuid
import asyncio
from pathlib import Path
from datetime import datetime
from typing import Optional, Any
import aiofiles
import json

from memograph.models.index import MemoryIndex, IndexPointer
from memograph.models.topic import TopicFile, MemoryFact, ConfidenceLevel
from memograph.models.transcript import TranscriptStore
from memograph.core.relevance import RelevanceScorer
from memograph.core.verification import VerificationEngine

class MemoryManager:
    """
    Core CRUD API for MemoGraph.
    Enforces write discipline: topic file FIRST, index SECOND.
    Mirrors: src/services/memory/memoryManager.ts
    """

    def __init__(self, base_path: Path, agent_id: str = "default"):
        self.base_path = base_path
        self.agent_id = agent_id
        self.index_path = base_path / "MEMORY.md"
        self.index_json_path = base_path / "memory_index.json"
        self.topics_path = base_path / "topics"
```

```
        self.transcripts_path = base_path / "transcripts"

        self.topics_path.mkdir(parents=True, exist_ok=True)
        self.transcripts_path.mkdir(parents=True, exist_ok=True)

        self.transcript_store = TranscriptStore(self.transcripts_path)
        self.relevance_scorer = RelevanceScorer()
        self.verification_engine = VerificationEngine()
        self._index: Optional[MemoryIndex] = None

    # ─────────────────────────────────────────────────
    # INDEX OPERATIONS
    # ─────────────────────────────────────────────────

    async def load_index(self) -> MemoryIndex:
        """Load or create the memory index."""
        if self._index is not None:
            return self._index
        if self.index_json_path.exists():
            async with aiofiles.open(self.index_json_path) as f:
                data = json.loads(await f.read())
                self._index = MemoryIndex(**self._deserialize_index(data))
        else:
            self._index = MemoryIndex(agent_id=self.agent_id)
        return self._index

    async def _save_index(self, index: MemoryIndex) -> None:
        """
        STRICT WRITE DISCIPLINE: Only called AFTER topic file is confirmed written.
        Saves both JSON (machine) and Markdown (human/LLM readable).
        """
        # Save JSON
        async with aiofiles.open(self.index_json_path, "w") as f:
            await f.write(json.dumps(self._serialize_index(index), indent=2))
        # Save human-readable Markdown
        async with aiofiles.open(self.index_path, "w") as f:
            await f.write(index.to_markdown())
        self._index = index

    def get_context_injection(self) -> str:
        """
        Returns the ONLY thing that's always in context: the index.
        Call this every prompt turn. It's cheap (~150 chars × N pointers).
        """
        if self._index is None:
            return "<!-- MemoGraph: No memory index loaded yet -->"
        return self._index.get_context_injection()

    # ─────────────────────────────────────────────────
    # TOPIC CRUD
    # ─────────────────────────────────────────────────

    async def remember(self,
                       topic_id: str,
                       content: str,
                       source: str,
                       confidence: ConfidenceLevel = ConfidenceLevel.OBSERVED,
                       tags: list[str] | None = None,
```

```
                    topic_name: str | None = None) -> MemoryFact:
    """
    Core write operation.
    STRICT ORDER:
      1. Load/create topic file
      2. Append fact to topic file
      3. Write topic file to disk  ← must succeed
      4. Update index              ← only after step 3
    """
    index = await self.load_index()
    topic = await self._load_or_create_topic(topic_id, topic_name or topic_id, tags or [])

    # Create the fact
    fact = MemoryFact(
        content=content,
        confidence=confidence,
        source=source,
        created_at=datetime.now(),
        fact_id=str(uuid.uuid4())[:8]
    )

    # Check if derivable (don't store what can be re-derived)
    if await self._is_re_derivable(content, source):
        return fact  # Don't store — skeptical memory principle

    # STEP 1-3: Write topic file first
    topic.facts.append(fact)
    topic.last_modified = datetime.now()
    topic_file_path = self.topics_path / f"{topic_id}.md"

    async with aiofiles.open(topic_file_path, "w") as f:
        await f.write(topic.to_markdown())  # ← Must succeed

    # STEP 4: ONLY NOW update the index
    await self._upsert_index_pointer(index, topic, topic_file_path)
    await self._save_index(index)

    return fact

async def recall(self,
                 query: str,
                 top_k: int = 3,
                 verify: bool = True) -> list[TopicFile]:
    """
    Bandwidth-aware retrieval.
    1. Score index pointers for relevance to query (cheap, always loaded)
    2. Fetch ONLY the top-k relevant topic files
    3. Optionally verify facts against ground truth
    """
    index = await self.load_index()

    # Score pointers using embeddings or keyword matching
    scored = self.relevance_scorer.score_pointers(
        query=query,
        pointers=index.pointers
    )
    top_pointers = scored[:top_k]
```

```
    # Load only the relevant topic files
    topics = []
    for pointer in top_pointers:
        topic = await self._load_topic_file(pointer.topic_file)
        if topic:
            if verify:
                # Skeptical memory: verify before returning
                topic = await self.verification_engine.verify_topic(topic)
            topics.append(topic)

    return topics

async def forget(self, topic_id: str, fact_id: str | None = None) -> bool:
    """
    Targeted forgetting.
    If fact_id is provided: remove specific fact from topic.
    If not: remove entire topic and its index pointer.
    """
    index = await self.load_index()

    if fact_id:
        topic = await self._load_topic_by_id(topic_id)
        if not topic:
            return False
        topic.facts = [f for f in topic.facts if f.fact_id != fact_id]
        topic_file_path = self.topics_path / f"{topic_id}.md"
        async with aiofiles.open(topic_file_path, "w") as f:
            await f.write(topic.to_markdown())
        # Update index pointer summary if needed
        await self._refresh_index_pointer(index, topic_id)
    else:
        # Remove topic file
        topic_file = self.topics_path / f"{topic_id}.md"
        topic_file.unlink(missing_ok=True)
        # Remove from index
        index.pointers = [p for p in index.pointers
                          if p.topic_id != topic_id]

    await self._save_index(index)
    return True

async def update(self,
                 topic_id: str,
                 fact_id: str,
                 new_content: str,
                 new_confidence: ConfidenceLevel | None = None) -> bool:
    """Update a specific fact. Write topic first, then index."""
    topic = await self._load_topic_by_id(topic_id)
    if not topic:
        return False

    for fact in topic.facts:
        if fact.fact_id == fact_id:
            fact.content = new_content
            if new_confidence:
                fact.confidence = new_confidence
            fact.last_verified = datetime.now()
            break
```

```
    # Write topic first
    topic.last_modified = datetime.now()
    topic_file_path = self.topics_path / f"{topic_id}.md"
    async with aiofiles.open(topic_file_path, "w") as f:
        await f.write(topic.to_markdown())

    # Then update index
    index = await self.load_index()
    await self._refresh_index_pointer(index, topic_id)
    await self._save_index(index)
    return True

# ──────────────────────────────────────────────
# HELPERS
# ──────────────────────────────────────────────

async def _is_re_derivable(self, content: str, source: str) -> bool:
    """
    Skeptical memory principle: don't store facts that
    can be directly re-derived from primary sources.
    e.g., don't store "function foo() takes 2 args" if
    the source file is accessible and stable.
    """
    # Subclasses / adapters implement this with domain knowledge
    return False  # Default: store everything (conservative)

async def _upsert_index_pointer(self,
                                index: MemoryIndex,
                                topic: TopicFile,
                                topic_path: Path) -> None:
    """Add or update a pointer in the index."""
    existing = next((p for p in index.pointers
                     if p.topic_id == topic.topic_id), None)

    avg_confidence = (
        sum(f.confidence == ConfidenceLevel.VERIFIED
            for f in topic.facts) / len(topic.facts)
        if topic.facts else 0.5
    )

    pointer = IndexPointer(
        topic_id=topic.topic_id,
        topic_file=str(topic_path.relative_to(self.base_path)),
        summary=self._generate_summary(topic),
        last_updated=datetime.now(),
        confidence=avg_confidence
    )

    if existing:
        index.pointers = [pointer if p.topic_id == topic.topic_id
                          else p for p in index.pointers]
    else:
        if not index.is_full():
            index.pointers.append(pointer)
        else:
            # Index full — trigger consolidation
            await self._evict_lowest_confidence_pointer(index)
```

```
            index.pointers.append(pointer)

    def _generate_summary(self, topic: TopicFile) -> str:
        """Generate ≤80 char summary for index pointer."""
        n = len(topic.facts)
        tags = ", ".join(topic.tags[:3])
        summary = f"{n} facts about {topic.topic_name}"
        if tags:
            summary += f" [{tags}]"



        return summary[:80]
```

🌙 PART 3 — THE AUTODREAM CONSOLIDATION DAEMON

This is the heart of MemoGraph — the self-healing engine. Modeled precisely after `src/services/autoDream/autoDream.ts` and `consolidationLock.ts`.

3A — The Triple-Gate Trigger System

Three gates must pass before it runs: 24 hours since the last run, at least 5 sessions completed, and a consolidation lock must be available.[1]

The gate order is cheapest first: (1) Time: hours since lastConsolidatedAt >= minHours; (2) Sessions: transcript count > lastConsolidatedAt >= minSessions. Triple gate: 24 hours must pass, 5+ sessions must accumulate, then a file-based advisory lock must be acquired.[5]

Python

```
# memograph/consolidation/gates.py

from datetime import datetime, timedelta
from pathlib import Path
from typing import NamedTuple

class GateResult(NamedTuple):
    passed: bool
    reason: str
    checked_at: datetime

class ConsolidationGates:
    """
```

```
    Triple-gate system. Cheapest checks first.
    Mirrors: src/services/autoDream/autoDream.ts gate logic
    """

    def __init__(self,
                 min_hours: int = 24,
                 min_sessions: int = 5,
                 min_scan_interval_minutes: int = 10):
        self.min_hours = min_hours
        self.min_sessions = min_sessions
        self.min_scan_interval = timedelta(minutes=min_scan_interval_minutes)
        self._last_scan: datetime | None = None

    def check_scan_interval(self) -> GateResult:
        """Gate 0 (cheapest): Don't scan more than once per interval."""
        now = datetime.now()
        if self._last_scan and (now - self._last_scan) < self.min_scan_interval:
            remaining = self.min_scan_interval - (now - self._last_scan)
            return GateResult(False, f"Too soon (retry in {remaining})", now)
        self._last_scan = now
        return GateResult(True, "Scan interval OK", now)

    def check_time_gate(self, last_consolidated: datetime | None) -> GateResult:
        """Gate 1 (cheap): Has enough time passed?"""
        if last_consolidated is None:
            return GateResult(True, "Never consolidated — proceed", datetime.now())
        elapsed = datetime.now() - last_consolidated
        if elapsed.total_seconds() / 3600 < self.min_hours:
            remaining = timedelta(hours=self.min_hours) - elapsed
            return GateResult(False, f"Only {elapsed} elapsed, need {self.min_hours}h",
datetime.now())
        return GateResult(True, f"{elapsed} since last consolidation", datetime.now())

    def check_session_gate(self,
                           session_count_since_last: int) -> GateResult:
        """Gate 2 (medium): Enough new sessions?"""
        if session_count_since_last < self.min_sessions:
            needed = self.min_sessions - session_count_since_last
            return GateResult(False, f"Need {needed} more sessions", datetime.now())
        return GateResult(True, f"{session_count_since_last} sessions accumulated",
datetime.now())

    def check_all(self,
                  last_consolidated: datetime | None,
                  session_count: int,
                  lock_available: bool) -> tuple[bool, list[GateResult]]:
        """Run all gates in order (cheapest first)."""
        results = []

        g0 = self.check_scan_interval()
        results.append(g0)
        if not g0.passed:
            return False, results

        g1 = self.check_time_gate(last_consolidated)
        results.append(g1)
        if not g1.passed:
            return False, results
```

```
        g2 = self.check_session_gate(session_count)
        results.append(g2)
        if not g2.passed:
            return False, results

        # Gate 3 (expensive): advisory lock
        if not lock_available:
            results.append(GateResult(False, "Lock unavailable — another consolidation
running", datetime.now()))
            return False, results

        results.append(GateResult(True, "Lock acquired", datetime.now()))



            return True, results
```

3B — The Consolidation Lock

The lock file design is clever: it's a lock file whose mtime IS lastConsolidatedAt. The file's mtime doubles as the lastConsolidatedAt timestamp. The PID goes in the body. If consolidation fails, the mtime is rolled back to its prior value, restoring the previous state. Stale after 1 hour even if the PID is alive, guarding against PID reuse on long-lived systems.[5]

Python

```python
# memograph/consolidation/lock.py

import os
import time
from pathlib import Path
from datetime import datetime, timedelta
from contextlib import asynccontextmanager
import aiofiles

class ConsolidationLock:
    """
    File-based advisory lock.
    Mirrors: src/services/autoDream/consolidationLock.ts

    Design: lock file mtime IS the lastConsolidatedAt timestamp.
    PID in body. Rollback on failure. Stale after 1 hour.
    """

    STALE_AFTER_HOURS = 1

    def __init__(self, lock_path: Path):
        self.lock_path = lock_path

    def _is_stale(self) -> bool:
```

```
    """Lock is stale if older than 1 hour, even if PID alive."""
    if not self.lock_path.exists():
        return False
    age = time.time() - self.lock_path.stat().st_mtime
    return age > (self.STALE_AFTER_HOURS * 3600)

def _pid_alive(self, pid: int) -> bool:
    """Check if process is still running."""
    try:
        os.kill(pid, 0)
        return True
    except (ProcessLookupError, PermissionError):
        return False

def is_available(self) -> bool:
    """Can we acquire the lock?"""
    if not self.lock_path.exists():
        return True
    if self._is_stale():
        self.lock_path.unlink(missing_ok=True)
        return True
    try:
        pid = int(self.lock_path.read_text().strip())
        if not self._pid_alive(pid):
            self.lock_path.unlink(missing_ok=True)
            return True
    except (ValueError, FileNotFoundError):
        return True
    return False

def get_last_consolidated(self) -> datetime | None:
    """mtime of lock file = lastConsolidatedAt."""
    if not self.lock_path.exists():
        return None
    return datetime.fromtimestamp(self.lock_path.stat().st_mtime)

@asynccontextmanager
async def acquire(self):
    """
    Acquire lock. On failure, rollback mtime.
    Yields True if acquired, False if unavailable.
    """
    if not self.is_available():
        yield False
        return

    # Capture prior mtime for rollback
    prior_mtime = (self.lock_path.stat().st_mtime
                   if self.lock_path.exists() else None)

    # Write PID to lock file
    async with aiofiles.open(self.lock_path, "w") as f:
        await f.write(str(os.getpid()))

    success = False
    try:
        yield True
        success = True
```

```
        finally:
            if success:
                # Update mtime to "now" = new lastConsolidatedAt
                now = time.time()
                os.utime(self.lock_path, (now, now))
            else:
                # Rollback: restore prior mtime or remove lock
                if prior_mtime:
                    os.utime(self.lock_path, (prior_mtime, prior_mtime))
                else:
```

```
                    self.lock_path.unlink(missing_ok=True)
```

3C — The Four-Phase Dream Engine

When it runs, the dream follows four strict phases from the prompt in consolidationPrompt.ts: Phase 1 - Orient: ls the memory directory, read MEMORY.md, skim existing topic files. Phase 2 - Gather Recent Signal: Find new information worth persisting. Sources in priority: daily logs → drifted memories → transcript search. Phase 3 - Consolidate: Write or update memory files. Phase 4 - Prune and Index: Keep MEMORY.md under 200 lines AND ~25KB. Remove stale pointers. Resolve contradictions.[4]

Python

```python
# memograph/consolidation/dream_engine.py

import asyncio
from pathlib import Path
from datetime import datetime
from typing import Any
import json

from memograph.models.index import MemoryIndex
from memograph.models.topic import TopicFile, ConfidenceLevel, MemoryFact
from memograph.consolidation.lock import ConsolidationLock
from memograph.consolidation.gates import ConsolidationGates
from memograph.models.transcript import TranscriptStore

class DreamPhaseResult:
    def __init__(self, phase: str, success: bool, details: dict):
        self.phase = phase
        self.success = success
        self.details = details
        self.timestamp = datetime.now()

class DreamEngine:
    """
```

```
Background memory consolidation engine.
Runs as forked subagent with read-only transcript access.
Mirrors: src/services/autoDream/autoDream.ts

Four phases:
1. Orient   — read index + skim topic files
2. Gather   — find new info from logs/transcripts
3. Consolidate — merge, update, resolve contradictions
4. Prune    — enforce limits, clean index
"""

def __init__(self,
             memory_manager,
             llm_client,
             transcript_store: TranscriptStore,
             lock: ConsolidationLock,
             gates: ConsolidationGates):
    self.mm = memory_manager
    self.llm = llm_client
    self.transcripts = transcript_store
    self.lock = lock
    self.gates = gates

async def should_run(self) -> tuple[bool, list]:
    """Check all gates before running."""
    last_consolidated = self.lock.get_last_consolidated()
    session_count = self.transcripts.count_sessions_since(
        last_consolidated or datetime.min
    )
    lock_available = self.lock.is_available()
    return self.gates.check_all(last_consolidated, session_count, lock_available)

async def run(self, llm_model: str = "haiku") -> dict[str, DreamPhaseResult]:
    """
    Run the full 4-phase dream consolidation.
    Uses a low-cost model by default (haiku) —
    mirrors Claude Code's cost-aware subagent selection.
    """
    should, gate_results = await self.should_run()
    if not should:
        return {"skipped": DreamPhaseResult("skipped", False,
                {"gates": [g.reason for g in gate_results]})}

    async with self.lock.acquire() as acquired:
        if not acquired:
            return {"skipped": DreamPhaseResult("lock", False,
                    {"reason": "Lock unavailable"})}

        results = {}
        results["phase_1"] = await self._phase_orient()
        results["phase_2"] = await self._phase_gather(results["phase_1"])
        results["phase_3"] = await self._phase_consolidate(
            results["phase_1"], results["phase_2"], llm_model
        )
        results["phase_4"] = await self._phase_prune()
        return results

async def _phase_orient(self) -> DreamPhaseResult:
```

```
    """
    Phase 1: Orient
    - Read MEMORY.md
    - List topics directory
    - Skim all topic file headers
    """
    index = await self.mm.load_index()
    topic_files = list(self.mm.topics_path.glob("*.md"))

    topic_summaries = []
    for tf in topic_files:
        # Read only first 10 lines (skim, not full load)
        lines = tf.read_text().split("\n")[:10]
        topic_summaries.append({
            "file": tf.name,
            "preview": "\n".join(lines),
            "size_bytes": tf.stat().st_size,
            "last_modified": datetime.fromtimestamp(
                tf.stat().st_mtime).isoformat()
        })

    return DreamPhaseResult("orient", True, {
        "index_pointer_count": len(index.pointers),
        "topic_files": len(topic_files),
        "topic_summaries": topic_summaries,
        "index_size_bytes": self.mm.index_path.stat().st_size
                            if self.mm.index_path.exists() else 0
    })

async def _phase_gather(self,
                        orient_result: DreamPhaseResult) -> DreamPhaseResult:
    """
    Phase 2: Gather Recent Signal
    Priority order (mirrors consolidationPrompt.ts):
    1. Daily logs (structured session data)
    2. Drifted memories (facts with stale confidence)
    3. Transcript search (grep only, never full load)
    """
    last_consolidated = self.lock.get_last_consolidated()

    # Source 1: Daily logs
    new_sessions = []
    session_files = sorted(
        self.transcripts.store_path.glob("*.jsonl"),
        key=lambda f: f.stat().st_mtime,
        reverse=True
    )[:20]  # Cap at 20 most recent

    # Source 2: Drifted memories (stale confidence)
    drifted_facts = []
    for topic_file in self.mm.topics_path.glob("*.md"):
        content = topic_file.read_text()
        if "⚠️" in content:  # Stale marker
            drifted_facts.append(topic_file.name)

    # Source 3: Grep transcripts for key signals
    signals = list(self.transcripts.grep_sessions(
        pattern=r"(important|remember|note that|always|never|critical)",
```

```
            max_results=30
        ))

        return DreamPhaseResult("gather", True, {
            "new_session_files": [f.name for f in session_files],
            "drifted_topics": drifted_facts,
            "transcript_signals": signals[:10],  # Sample
            "signal_count": len(signals)
        })

    async def _phase_consolidate(self,
                                 orient: DreamPhaseResult,
                                 gather: DreamPhaseResult,
                                 llm_model: str) -> DreamPhaseResult:
        """
        Phase 3: Consolidate
        - Merge related observations
        - Remove logical contradictions
        - Convert vague insights to concrete facts
        Uses LLM with consolidation prompt.
        """

        # Build the dream prompt (mirrors consolidationPrompt.ts)
        dream_prompt = self._build_dream_prompt(orient, gather)

        # Call LLM (forked subagent — read-only access)
        consolidation_result = await self.llm.complete(
            prompt=dream_prompt,
            model=llm_model,
            max_tokens=4096,
            system=self._get_dream_system_prompt()
        )

        # Parse LLM's consolidation instructions
        updates = self._parse_consolidation_output(consolidation_result)

        # Apply updates (write topic files first, then index)
        applied = []
        for update in updates:
            if update["action"] == "merge":
                await self._merge_facts(update)
                applied.append(f"Merged: {update['topic_id']}")
            elif update["action"] == "resolve_contradiction":
                await self._resolve_contradiction(update)
                applied.append(f"Resolved: {update['fact_ids']}")
            elif update["action"] == "promote":
                await self._promote_confidence(update)
                applied.append(f"Promoted: {update['fact_id']}")
            elif update["action"] == "create":
                await self.mm.remember(**update["params"])
                applied.append(f"Created: {update['topic_id']}")

        return DreamPhaseResult("consolidate", True, {
            "updates_applied": len(applied),
            "update_log": applied
        })

    async def _phase_prune(self) -> DreamPhaseResult:
```

```
        """
        Phase 4: Prune and Index
        - Enforce MEMORY.md ≤ 200 lines / 25KB
        - Remove stale pointers
        - Resolve index contradictions
        """
        index = await self.mm.load_index()
        pruned = []

        # Remove pointers to non-existent topic files
        valid_pointers = []
        for pointer in index.pointers:
            topic_path = self.mm.base_path / pointer.topic_file
            if topic_path.exists():
                valid_pointers.append(pointer)
            else:
                pruned.append(f"Removed stale pointer: {pointer.topic_id}")

        index.pointers = valid_pointers

        # Sort by confidence (keep highest confidence, drop lowest if over limit)
        index.pointers.sort(key=lambda p: p.confidence, reverse=True)
        if len(index.pointers) > MemoryIndex.MAX_LINES:
            dropped = index.pointers[MemoryIndex.MAX_LINES:]
            index.pointers = index.pointers[:MemoryIndex.MAX_LINES]
            pruned.extend([f"Evicted low-conf: {p.topic_id}" for p in dropped])

        index.last_consolidated = datetime.now()
        await self.mm._save_index(index)

        return DreamPhaseResult("prune", True, {
            "final_pointer_count": len(index.pointers),
            "pruned": pruned,
            "index_size_bytes": self.mm.index_path.stat().st_size
        })

    def _get_dream_system_prompt(self) -> str:
        """
        System prompt for consolidation subagent.
        Mirrors: src/services/autoDream/consolidationPrompt.ts
        """
        return """You are performing a dream — a reflective pass over memory files.
Synthesize what you've learned recently into durable, well-organized memories
so that future sessions can orient quickly.

Rules:
1. MERGE related observations into single coherent facts
2. RESOLVE contradictions — keep the more recent/verified version
3. PROMOTE vague insights ("user might prefer X") to concrete facts only if confirmed
4. DO NOT store facts that can be directly re-derived from primary sources
5. Keep all summaries concrete and verifiable, not aspirational
6. Output ONLY structured JSON describing memory operations

Output format:
{"operations": [
  {"action": "merge", "topic_id": "...", "fact_ids": [...], "merged_content": "..."},
  {"action": "resolve_contradiction", "topic_id": "...", "fact_ids": [...], "resolution":
"..."},
```

```
  {"action": "promote", "topic_id": "...", "fact_id": "...", "new_confidence": "verified"},
  {"action": "create", "params": {"topic_id": "...", "content": "...", "source": "..."}}
]}"""

    def _build_dream_prompt(self,
                            orient: DreamPhaseResult,
                            gather: DreamPhaseResult) -> str:
        return f"""## Memory State
Index contains {orient.details['index_pointer_count']} pointers across
{orient.details['topic_files']} topic files.

## Recent Signals Gathered
- New sessions: {len(gather.details['new_session_files'])}
- Drifted topics needing attention: {gather.details['drifted_topics']}
- Key signals from transcripts: {gather.details['signal_count']} found

## Transcript Samples
{json.dumps(gather.details['transcript_signals'], indent=2)}

Based on the above, output memory consolidation operations as JSON."""

    def _parse_consolidation_output(self, llm_output: str) -> list[dict]:
        """Parse LLM's JSON consolidation instructions."""
        try:
            data = json.loads(llm_output)
            return data.get("operations", [])
        except json.JSONDecodeError:
            # Try to extract JSON from markdown code block
            import re
            match = re.search(r"```json\n(.*?)\n```", llm_output, re.DOTALL)
            if match:
                return json.loads(match.group(1)).get("operations", [])
            return []

    async def _merge_facts(self, update: dict) -> None:
        """Merge multiple facts into one."""
        topic = await self.mm._load_topic_by_id(update["topic_id"])
        if not topic:
            return
        # Remove old facts
        topic.facts = [f for f in topic.facts
                       if f.fact_id not in update["fact_ids"]]
        # Add merged fact
        merged = MemoryFact(
            content=update["merged_content"],
            confidence=ConfidenceLevel.VERIFIED,
            source="autoDream consolidation",
            created_at=datetime.now(),
            fact_id=f"merged_{datetime.now().strftime('%Y%m%d%H%M%S')}"
        )
        topic.facts.append(merged)
        topic_path = self.mm.topics_path / f"{update['topic_id']}.md"
        import aiofiles
        async with aiofiles.open(topic_path, "w") as f:
            await f.write(topic.to_markdown())

    async def _resolve_contradiction(self, update: dict) -> None:
        """Resolve a contradiction between two facts."""
```

```
        topic = await self.mm._load_topic_by_id(update["topic_id"])
        if not topic:
            return
        # Keep the resolution, drop the contradicting facts
        topic.facts = [f for f in topic.facts
                       if f.fact_id not in update["fact_ids"]]
        resolved = MemoryFact(
            content=update["resolution"],
            confidence=ConfidenceLevel.VERIFIED,
            source="autoDream contradiction resolution",
            created_at=datetime.now(),
            fact_id=f"resolved_{datetime.now().strftime('%Y%m%d%H%M%S')}"
        )
        topic.facts.append(resolved)
        topic_path = self.mm.topics_path / f"{update['topic_id']}.md"
        import aiofiles
        async with aiofiles.open(topic_path, "w") as f:
            await f.write(topic.to_markdown())

    async def _promote_confidence(self, update: dict) -> None:
        """Promote a fact's confidence level."""
        await self.mm.update(
            topic_id=update["topic_id"],
            fact_id=update["fact_id"],
            new_content=None,
            new_confidence=ConfidenceLevel(update["new_confidence"])



            )
```

3D — The Background Daemon

Python

```
# memograph/consolidation/daemon.py

import asyncio
import signal
import logging
from pathlib import Path
from datetime import datetime

logger = logging.getLogger("memograph.daemon")

class ConsolidationDaemon:
    """
    Background daemon that periodically checks gates and runs consolidation.
    Runs in a separate asyncio task or process.
    """

    def __init__(self, dream_engine, scan_interval_seconds: int = 600):
        self.engine = dream_engine
        self.scan_interval = scan_interval_seconds
        self._running = False
        self._task: asyncio.Task | None = None
```

```python
async def start(self):
    """Start the daemon loop."""
    self._running = True
    self._task = asyncio.create_task(self._loop())
    logger.info("MemoGraph consolidation daemon started")

async def stop(self):
    """Gracefully stop the daemon."""
    self._running = False
    if self._task:
        self._task.cancel()
        try:
            await self._task
        except asyncio.CancelledError:
            pass
    logger.info("MemoGraph consolidation daemon stopped")

async def _loop(self):
    """Main daemon loop."""
    while self._running:
        try:
            should_run, gates = await self.engine.should_run()
            if should_run:
                logger.info("All gates passed — starting dream consolidation")
                results = await self.engine.run()
                self._log_results(results)
            else:
                failed = [g.reason for g in gates if not g.passed]
                logger.debug(f"Gates blocked consolidation: {failed}")
        except Exception as e:
            logger.error(f"Dream engine error: {e}", exc_info=True)

        await asyncio.sleep(self.scan_interval)

def _log_results(self, results: dict):
    for phase, result in results.items():
        if hasattr(result, 'details'):


                logger.info(f"[{phase}] {result.details}")
```

🔌 PART 4 — BANDWIDTH-AWARE CONTEXT INJECTION ENGINE

This is what makes MemoGraph different from every other memory library. Most inject everything. MemoGraph injects almost nothing.

Python

```python
# memograph/injection/context_injector.py

from dataclasses import dataclass
from typing import Any
from memograph.core.memory_manager import MemoryManager
from memograph.core.relevance import RelevanceScorer

@dataclass
class InjectionBudget:
    """
    Token budget for context injection.
    Forces bandwidth-aware decisions.
    """
    index_tokens: int = 500       # Always consumed (index is always loaded)
    topic_tokens: int = 2000      # Available for on-demand topic files
    max_topics: int = 3           # Never load more than 3 topics per turn
    transcript_tokens: int = 0    # NEVER injected directly

class ContextInjector:
    """
    Bandwidth-aware context injection.

    Design philosophy:
    - Index: ALWAYS injected (cheap, ~500 tokens)
    - Topics: SELECTIVELY injected (only if relevant to query)
    - Transcripts: NEVER injected (only grep'd internally)

    Mirrors the core insight from the leak:
    "The index is cheap and always loaded, topic files are fetched
     only when relevant, and transcripts are never loaded directly."
    """

    def __init__(self,
                 memory_manager: MemoryManager,
                 budget: InjectionBudget | None = None):
        self.mm = memory_manager
        self.budget = budget or InjectionBudget()
        self.scorer = RelevanceScorer()

    async def build_context(self,
                            query: str,
                            include_topics: bool = True) -> dict[str, Any]:
        """
        Build the memory context for a prompt turn.
        Returns structured context for injection.
        """
        # LAYER 1: Always inject the index
        index = await self.mm.load_index()
        index_text = index.get_context_injection()

        # LAYER 2: Selectively inject relevant topics
        topic_contexts = []
        if include_topics and index.pointers:
            relevant_topics = await self.mm.recall(
                query=query,
                top_k=self.budget.max_topics,
                verify=True
            )
```

```
            for topic in relevant_topics:
                topic_contexts.append({
                    "topic_id": topic.topic_id,
                    "name": topic.topic_name,
                    "content": topic.to_markdown(),
                    "fact_count": len(topic.facts)
                })

        # LAYER 3: Transcripts — NEVER injected
        # (Only available via mm.transcript_store.grep_sessions())

        return {
            "memory_index": index_text,
            "relevant_topics": topic_contexts,
            "metadata": {
                "index_pointer_count": len(index.pointers),
                "topics_loaded": len(topic_contexts),
                "last_consolidated": str(index.last_consolidated)
            }
        }

    def format_for_prompt(self, context: dict) -> str:
        """
        Format context as a prompt-injectable string.
        Follows the skeptical memory principle in the prompt text.
        """
        sections = [
            "## 🧠 Memory Context (treat as hints, verify before use)",
            "",
            "### Memory Index (always loaded)",
            context["memory_index"]
        ]

        if context["relevant_topics"]:
            sections.append("\n### Relevant Topic Files (loaded on-demand)")
            for topic in context["relevant_topics"]:
                sections.append(f"\n#### {topic['name']}")
                sections.append(topic["content"])

        sections.extend([
            "",
            "> ⚠️ Memory is a hint, not ground truth.",
            "> Always verify facts before acting on them.",
            "> Raw transcripts are available via grep if needed."
        ])

        return "\n".join(sections)

    async def get_token_estimate(self, context: dict) -> dict[str, int]:
        """Estimate token usage for the context."""
        # Rough estimate: 1 token ≈ 4 chars
        index_tokens = len(context["memory_index"]) // 4
        topic_tokens = sum(
            len(t["content"]) // 4
            for t in context["relevant_topics"]
        )
        return {
            "index_tokens": index_tokens,
```

```
            "topic_tokens": topic_tokens,
            "total_tokens": index_tokens + topic_tokens,
            "transcript_tokens": 0  # Always zero



        }
```

🔍 PART 5 — RELEVANCE SCORER & VERIFICATION ENGINE

Python

```python
# memograph/core/relevance.py

from memograph.models.index import IndexPointer
import re

class RelevanceScorer:
    """
    Scores index pointers for relevance to a query.
    Two modes:
    - Keyword (fast, no API calls): default
    - Embedding (accurate, requires embedding model): opt-in
    """

    def __init__(self, use_embeddings: bool = False,
                 embedding_client=None):
        self.use_embeddings = use_embeddings
        self.embedding_client = embedding_client

    def score_pointers(self,
                       query: str,
                       pointers: list[IndexPointer]) -> list[IndexPointer]:
        """Score and rank pointers by relevance to query."""
        if self.use_embeddings and self.embedding_client:
            return self._embedding_score(query, pointers)
        return self._keyword_score(query, pointers)

    def _keyword_score(self,
                       query: str,
                       pointers: list[IndexPointer]) -> list[IndexPointer]:
        """Fast keyword-based scoring."""
        query_terms = set(re.findall(r'\w+', query.lower()))

        scored = []
        for pointer in pointers:
            pointer_terms = set(
                re.findall(r'\w+',
                           f"{pointer.topic_id} {pointer.summary}".lower())
```

```
            )
            overlap = len(query_terms & pointer_terms)
            # Boost by confidence
            score = overlap * (0.5 + pointer.confidence * 0.5)
            scored.append((score, pointer))

        scored.sort(key=lambda x: x[0], reverse=True)
        return [p for _, p in scored if _ > 0]

    def _embedding_score(self,
                         query: str,
                         pointers: list[IndexPointer]) -> list[IndexPointer]:
        """Embedding-based semantic scoring."""
        query_embed = self.embedding_client.embed(query)
        scored = []
        for pointer in pointers:
            text = f"{pointer.topic_id}: {pointer.summary}"
            pointer_embed = self.embedding_client.embed(text)
            similarity = self._cosine_similarity(query_embed, pointer_embed)
            scored.append((similarity * pointer.confidence, pointer))
        scored.sort(key=lambda x: x[0], reverse=True)
        return [p for _, p in scored]

    @staticmethod
    def _cosine_similarity(a: list[float], b: list[float]) -> float:
        dot = sum(x * y for x, y in zip(a, b))
        norm_a = sum(x**2 for x in a) ** 0.5
        norm_b = sum(x**2 for x in b) ** 0.5
        return dot / (norm_a * norm_b) if norm_a and norm_b else 0.0


# memograph/core/verification.py

from memograph.models.topic import TopicFile, MemoryFact, ConfidenceLevel
from datetime import datetime, timedelta

class VerificationEngine:
    """
    Skeptical memory verification.
    Marks facts as stale if unverified for too long.
    Provides hooks for agent-specific verification logic.
    """

    STALE_AFTER_DAYS = {
        ConfidenceLevel.VERIFIED: 30,
        ConfidenceLevel.OBSERVED: 7,
        ConfidenceLevel.INFERRED: 3,
        ConfidenceLevel.STALE: 0
    }

    async def verify_topic(self, topic: TopicFile) -> TopicFile:
        """Mark stale facts and trigger re-verification."""
        now = datetime.now()
        for fact in topic.facts:
            stale_days = self.STALE_AFTER_DAYS[fact.confidence]
            if fact.last_verified:
                age = (now - fact.last_verified).days
                if age > stale_days:
```

```
                    fact.confidence = ConfidenceLevel.STALE
            else:
                age = (now - fact.created_at).days
                if age > stale_days:
                    fact.confidence = ConfidenceLevel.STALE
        return topic

    def get_verification_prompt(self, fact: MemoryFact) -> str:
        """Generate verification prompt for a specific fact."""
        return (
            f"Verify this remembered fact before using it:\n"
            f"'{fact.content}'\n"
            f"Source: {fact.source}\n"
            f"Last verified: {fact.last_verified or 'Never'}\n"
            f"Confidence: {fact.confidence.value}\n\n"
            f"Before acting on this, confirm it is still accurate."


            )
```

🔗 PART 6 — ADAPTER LAYERS

6A — Raw API Adapter (Any LLM)

Python

```
# memograph/adapters/raw_api.py

from memograph.core.memory_manager import MemoryManager
from memograph.injection.context_injector import ContextInjector
from memograph.models.topic import ConfidenceLevel

class RawAPIAdapter:
    """
    Minimal adapter for raw API usage.
    Works with any LLM API (Anthropic, OpenAI, Gemini, Ollama, etc.)
    """

    def __init__(self, memory_manager: MemoryManager):
        self.mm = memory_manager
        self.injector = ContextInjector(memory_manager)

    async def prepare_messages(self,
                               messages: list[dict],
                               inject_memory: bool = True) -> list[dict]:
        """
        Inject memory context into the message list.
        Prepends a system-level memory context before the first user message.
        """
        if not inject_memory:
            return messages
```

```
        # Get the last user message as the query
        last_user = next(
            (m["content"] for m in reversed(messages)
             if m["role"] == "user"), ""
        )

        context = await self.injector.build_context(query=last_user)
        memory_text = self.injector.format_for_prompt(context)

        # Inject as system message or prepend to first user message
        injected = [{"role": "system", "content": memory_text}] + messages
        return injected

    async def post_response(self,
                            response: str,
                            query: str,
                            source: str = "agent_response") -> None:
        """
        Extract and store learnable facts from agent response.
        Call this after every agent turn.
        """
        # Basic extraction — override in subclasses for smarter extraction
        if any(kw in response.lower() for kw in
               ["remember", "note that", "important", "always", "never"]):
            await self.mm.remember(
                topic_id=f"auto_{hash(query) % 10000}",
                content=response[:500],  # Cap at 500 chars
                source=source,
                confidence=ConfidenceLevel.OBSERVED
            )

    async def get_stats(self) -> dict:
        """Memory usage statistics."""
        index = await self.mm.load_index()
        return {
            "total_topics": len(index.pointers),
            "index_size_bytes": (self.mm.index_path.stat().st_size
                                 if self.mm.index_path.exists() else 0),
            "last_consolidated": str(index.last_consolidated),
            "agent_id": index.agent_id


               }
```

6B — LangChain Adapter

Python

```
# memograph/adapters/langchain_adapter.py

try:
    from langchain.memory import BaseMemory
    from langchain.schema import BaseMessage, HumanMessage, AIMessage
    from pydantic import Field
    LANGCHAIN_AVAILABLE = True
except ImportError:
```

```
    LANGCHAIN_AVAILABLE = False

if LANGCHAIN_AVAILABLE:
    import asyncio
    from memograph.core.memory_manager import MemoryManager
    from memograph.injection.context_injector import ContextInjector
    from memograph.models.topic import ConfidenceLevel

    class MemoGraphMemory(BaseMemory):
        """
        LangChain-compatible MemoGraph memory.
        Drop-in replacement for ConversationBufferMemory.

        Usage:
            memory = MemoGraphMemory(base_path=".memograph/myagent")
            chain = LLMChain(llm=llm, prompt=prompt, memory=memory)
        """

        base_path: str = ".memograph/default"
        memory_key: str = "memory_context"
        _manager: MemoryManager = Field(default=None, exclude=True)
        _injector: ContextInjector = Field(default=None, exclude=True)

        def __init__(self, **kwargs):
            super().__init__(**kwargs)
            from pathlib import Path
            self._manager = MemoryManager(Path(self.base_path))
            self._injector = ContextInjector(self._manager)

        @property
        def memory_variables(self) -> list[str]:
            return [self.memory_key]

        def load_memory_variables(self, inputs: dict) -> dict:
            """Synchronous wrapper for LangChain compatibility."""
            query = inputs.get("input", inputs.get("query", ""))
            context = asyncio.get_event_loop().run_until_complete(
                self._injector.build_context(query=query)
            )
            return {
                self.memory_key: self._injector.format_for_prompt(context)
            }

        def save_context(self, inputs: dict, outputs: dict) -> None:
            """Extract and save facts from the interaction."""
            query = inputs.get("input", "")
            response = outputs.get("output", "")

            asyncio.get_event_loop().run_until_complete(
                self._manager.remember(
                    topic_id=f"interaction_{hash(query) % 9999}",
                    content=f"Q: {query[:200]}\nA: {response[:300]}",
                    source="langchain_chain",
                    confidence=ConfidenceLevel.OBSERVED
                )
            )

        def clear(self) -> None:
```

```
        """Clear all memory (use with caution)."""
        import shutil

        shutil.rmtree(self.base_path, ignore_errors=True)
```

6C — CrewAI Adapter

Python

```
# memograph/adapters/crewai_adapter.py

try:
    from crewai import Agent
    CREWAI_AVAILABLE = True
except ImportError:
    CREWAI_AVAILABLE = False

if CREWAI_AVAILABLE:
    from memograph.core.memory_manager import MemoryManager
    from memograph.injection.context_injector import ContextInjector
    from memograph.models.topic import ConfidenceLevel
    from pathlib import Path

    class MemoGraphCrewAIAdapter:
        """
        CrewAI adapter for MemoGraph.
        Provides shared memory across all agents in a crew.

        Usage:
            adapter = MemoGraphCrewAIAdapter(base_path=".memograph/crew")
            # Wrap agent task execution
            result = await adapter.execute_with_memory(agent, task)
        """

        def __init__(self, base_path: str = ".memograph/crew"):
            self.mm = MemoryManager(Path(base_path), agent_id="crew")
            self.injector = ContextInjector(self.mm)

        async def enrich_agent_context(self,
                                       agent: "Agent",
                                       task_description: str) -> str:
            """Inject memory context into agent's task."""
            context = await self.injector.build_context(query=task_description)
            memory_block = self.injector.format_for_prompt(context)
            return f"{memory_block}\n\n## Task\n{task_description}"

        async def store_agent_output(self,
                                     agent_role: str,
                                     task: str,
                                     output: str) -> None:
            """Store agent output as a memory fact."""
            topic_id = f"crew_{agent_role.lower().replace(' ', '_')}"
            await self.mm.remember(
                topic_id=topic_id,
                topic_name=f"Agent: {agent_role}",
```

```
            content=f"Task: {task[:150]}\nOutput: {output[:400]}",
            source=f"crewai/{agent_role}",
            confidence=ConfidenceLevel.OBSERVED,
            tags=["crew", agent_role.lower()]
        )

    async def get_crew_memory_context(self,
                                      query: str = "") -> str:
        """Get full crew memory context."""
        context = await self.injector.build_context(query=query)


            return self.injector.format_for_prompt(context)
```

6D — AutoGen Adapter

Python

```
# memograph/adapters/autogen_adapter.py

try:
    import autogen
    AUTOGEN_AVAILABLE = True
except ImportError:
    AUTOGEN_AVAILABLE = False

if AUTOGEN_AVAILABLE:
    from memograph.core.memory_manager import MemoryManager
    from memograph.injection.context_injector import ContextInjector
    from memograph.models.topic import ConfidenceLevel
    from pathlib import Path

    class MemoGraphAutoGenHook:
        """
        AutoGen hook for MemoGraph.
        Intercepts messages to inject memory and extract facts.

        Usage:
            hook = MemoGraphAutoGenHook(base_path=".memograph/autogen")
            hook.register_with(assistant_agent)
        """

        def __init__(self, base_path: str = ".memograph/autogen"):
            self.mm = MemoryManager(Path(base_path), agent_id="autogen")
            self.injector = ContextInjector(self.mm)

        def register_with(self, agent: "autogen.ConversableAgent") -> None:
            """Register hooks with an AutoGen agent."""
            agent.register_hook(
                hookable_method="process_message_before_send",
                hook=self._inject_memory_hook
            )
            agent.register_hook(
                hookable_method="process_last_received_message",
                hook=self._extract_facts_hook
            )
```

```python
    def _inject_memory_hook(self, message: dict) -> dict:
        """Inject memory context into outgoing messages."""
        import asyncio
        content = message.get("content", "")
        context = asyncio.get_event_loop().run_until_complete(
            self.injector.build_context(query=content)
        )
        memory_prefix = self.injector.format_for_prompt(context)
        message["content"] = f"{memory_prefix}\n\n{content}"
        return message

    def _extract_facts_hook(self, message: dict) -> dict:
        """Extract facts from received messages."""
        import asyncio
        content = message.get("content", "")
        if len(content) > 100:  # Only process substantial messages
            asyncio.get_event_loop().run_until_complete(
                self.mm.remember(
                    topic_id=f"autogen_{hash(content) % 9999}",
                    content=content[:500],
                    source="autogen_agent",
                    confidence=ConfidenceLevel.OBSERVED
                )
            )


            return message
```

📦 PART 7 — PACKAGE STRUCTURE & SDK SURFACE

text

```
memograph/
├── __init__.py                 # Public API exports
├── memograph.py                # Main entry point / MemoGraph class
│
├── models/
│   ├── index.py                # MemoryIndex, IndexPointer
│   ├── topic.py                # TopicFile, MemoryFact, ConfidenceLevel
│   └── transcript.py           # TranscriptStore, TranscriptEntry
│
├── core/
│   ├── memory_manager.py       # MemoryManager (CRUD + write discipline)
│   ├── relevance.py            # RelevanceScorer (keyword + embedding)
│   └── verification.py         # VerificationEngine (skeptical memory)
│
├── consolidation/
│   ├── gates.py                # ConsolidationGates (triple-gate system)
│   ├── lock.py                 # ConsolidationLock (mtime-based)
```

```
│   ├── dream_engine.py            # DreamEngine (4-phase consolidation)
│   └── daemon.py                  # ConsolidationDaemon (background loop)
│
├── injection/
│   └── context_injector.py        # ContextInjector (bandwidth-aware)
│
├── adapters/
│   ├── raw_api.py                 # RawAPIAdapter (any LLM)
│   ├── langchain_adapter.py       # MemoGraphMemory (LangChain)
│   ├── crewai_adapter.py          # MemoGraphCrewAIAdapter
│   └── autogen_adapter.py         # MemoGraphAutoGenHook
│
├── cli/
│   └── memograph_cli.py           # CLI: memograph status/recall/dream/prune
│
└── tests/
    ├── test_index.py
    ├── test_topic.py
    ├── test_dream_engine.py
    ├── test_gates.py
    ├── test_lock.py
    ├── test_injector.py
```

```
    └── test_adapters.py
```

The Main `MemoGraph` Class (Unified Entry Point)

Python

```python
# memograph/__init__.py

from memograph.memograph import MemoGraph
from memograph.models.topic import ConfidenceLevel
from memograph.adapters.raw_api import RawAPIAdapter

__version__ = "0.1.0"
__all__ = ["MemoGraph", "ConfidenceLevel", "RawAPIAdapter"]

# memograph/memograph.py

from pathlib import Path
from memograph.core.memory_manager import MemoryManager
from memograph.consolidation.daemon import ConsolidationDaemon
from memograph.consolidation.dream_engine import DreamEngine
from memograph.consolidation.lock import ConsolidationLock
from memograph.consolidation.gates import ConsolidationGates
from memograph.injection.context_injector import ContextInjector, InjectionBudget
from memograph.models.transcript import TranscriptStore
from memograph.models.topic import ConfidenceLevel

class MemoGraph:
    """
    🧠 MemoGraph — Self-Healing Memory System for AI Agents

    Quick start:
```

```
    mg = MemoGraph(base_path=".memograph/myagent", llm_client=my_llm)
    await mg.start()

    # Remember something
    await mg.remember("user_prefs", "User prefers concise responses",
                      source="observed")

    # Get context for a prompt
    context = await mg.get_context("What does the user prefer?")

    # Recall relevant memories
    topics = await mg.recall("user preferences")
"""

def __init__(self,
             base_path: str | Path = ".memograph/default",
             agent_id: str = "default",
             llm_client=None,
             auto_consolidate: bool = True,
             budget: InjectionBudget | None = None,
             min_hours: int = 24,
             min_sessions: int = 5):

    self.base_path = Path(base_path)
    self.base_path.mkdir(parents=True, exist_ok=True)

    # Core components
    self.manager = MemoryManager(self.base_path, agent_id)
    self.injector = ContextInjector(self.manager, budget)

    # Consolidation components
    self.lock = ConsolidationLock(self.base_path / "consolidation.lock")
    self.gates = ConsolidationGates(min_hours=min_hours,
                                    min_sessions=min_sessions)
    self.dream = DreamEngine(
        memory_manager=self.manager,
        llm_client=llm_client,
        transcript_store=self.manager.transcript_store,
        lock=self.lock,
        gates=self.gates
    )
    self.daemon = ConsolidationDaemon(self.dream) if auto_consolidate else None

async def start(self):
    """Start MemoGraph (loads index + starts daemon if enabled)."""
    await self.manager.load_index()
    if self.daemon:
        await self.daemon.start()
    return self

async def stop(self):
    """Gracefully stop MemoGraph."""
    if self.daemon:
        await self.daemon.stop()

# ── Convenience API ──────────────────────────────────

async def remember(self, topic_id: str, content: str,
```

```
                    source: str, **kwargs):
        return await self.manager.remember(
            topic_id, content, source, **kwargs)

    async def recall(self, query: str, top_k: int = 3):
        return await self.manager.recall(query, top_k)

    async def forget(self, topic_id: str, fact_id: str | None = None):
        return await self.manager.forget(topic_id, fact_id)

    async def get_context(self, query: str) -> str:
        context = await self.injector.build_context(query)
        return self.injector.format_for_prompt(context)

    async def dream_now(self) -> dict:
        """Force immediate consolidation (ignores time gate)."""
        return await self.dream.run()

    async def status(self) -> dict:
        index = await self.manager.load_index()
        return {
            "agent_id": index.agent_id,
            "pointer_count": len(index.pointers),
            "last_consolidated": str(index.last_consolidated),
            "index_size_bytes": (self.manager.index_path.stat().st_size
                                 if self.manager.index_path.exists() else 0),
            "topic_files": len(list(self.manager.topics_path.glob("*.md"))),
            "transcript_files": len(list(
                self.manager.transcripts_path.glob("*.jsonl")))
        }

    # ─── Context Manager Support ──────────────────────────

    async def __aenter__(self):
        return await self.start()

    async def __aexit__(self, *args):


            await self.stop()
```

⚙️ PART 8 — THE CLI

Python

```
# memograph/cli/memograph_cli.py
# Usage: memograph status | recall "query" | dream | prune | forget <topic_id>

import asyncio
import argparse
import json
from pathlib import Path
from memograph import MemoGraph
```

```python
async def cmd_status(mg: MemoGraph):
    status = await mg.status()
    print(json.dumps(status, indent=2, default=str))

async def cmd_recall(mg: MemoGraph, query: str):
    topics = await mg.recall(query, top_k=5)
    for topic in topics:
        print(f"\n{'='*50}")
        print(topic.to_markdown())

async def cmd_dream(mg: MemoGraph):
    print("🌙 Starting dream consolidation...")
    results = await mg.dream_now()
    for phase, result in results.items():
        status = "✅" if result.success else "❌"
        print(f"{status} {phase}: {result.details}")

async def cmd_prune(mg: MemoGraph):
    print("✂️ Pruning memory index...")
    result = await mg.dream.engine._phase_prune()
    print(json.dumps(result.details, indent=2, default=str))

async def cmd_forget(mg: MemoGraph, topic_id: str, fact_id: str = None):
    success = await mg.forget(topic_id, fact_id)
    if success:
        print(f"✅ Forgotten: {topic_id}" + (f"/{fact_id}" if fact_id else ""))
    else:
        print(f"❌ Not found: {topic_id}")

def main():
    parser = argparse.ArgumentParser(description="MemoGraph CLI")
    parser.add_argument("--path", default=".memograph/default")
    subparsers = parser.add_subparsers(dest="command")

    subparsers.add_parser("status")
    recall_p = subparsers.add_parser("recall")
    recall_p.add_argument("query")
    subparsers.add_parser("dream")
    subparsers.add_parser("prune")
    forget_p = subparsers.add_parser("forget")
    forget_p.add_argument("topic_id")
    forget_p.add_argument("--fact-id", default=None)

    args = parser.parse_args()

    async def run():
        async with MemoGraph(base_path=args.path) as mg:
            if args.command == "status":
                await cmd_status(mg)
            elif args.command == "recall":
                await cmd_recall(mg, args.query)
            elif args.command == "dream":
                await cmd_dream(mg)
            elif args.command == "prune":
                await cmd_prune(mg)
            elif args.command == "forget":
                await cmd_forget(mg, args.topic_id, args.fact_id)
```

```
            else:
                parser.print_help()

    asyncio.run(run())

if __name__ == "__main__":


            main()
```

📝 PART 9 — `pyproject.toml` / PACKAGING

toml

```
# pyproject.toml

[build-system]
requires = ["hatchling"]
build-backend = "hatchling.build"

[project]
name = "memograph"
version = "0.1.0"
description = "Self-Healing Memory System for AI Agents — inspired by Claude Code's 3-layer
memory architecture"
readme = "README.md"
requires-python = ">=3.11"
license = {text = "MIT"}
keywords = ["ai", "agents", "memory", "llm", "langchain", "crewai", "autogen"]

dependencies = [
    "aiofiles>=23.0",
    "pydantic>=2.0",
]

[project.optional-dependencies]
langchain = ["langchain>=0.2"]
crewai = ["crewai>=0.30"]
autogen = ["pyautogen>=0.2"]
embeddings = ["openai>=1.0", "numpy>=1.24"]
all = ["memograph[langchain,crewai,autogen,embeddings]"]
dev = [
    "pytest>=8.0",
    "pytest-asyncio>=0.23",
    "pytest-cov>=5.0",
    "ruff>=0.4",
    "mypy>=1.9"
]
```

```
[project.scripts]
memograph = "memograph.cli.memograph_cli:main"

[project.urls]
Repository = "https://github.com/yourname/memograph"
Documentation = "https://memograph.dev"


[tool.pytest.ini_options]
asyncio_mode = "auto"


[tool.ruff]
target-version = "py311"


        line-length = 88
```

🗺️ PART 10 — FULL SYSTEM MAP

text





🛣️ PART 11 — DEVELOPMENT ROADMAP

Phase	Milestone	Key Work
v0.1	Core Memory	Index, Topics, Transcripts, CRUD, Write Discipline

v0.2	AutoDream	Gates, Lock, 4-Phase Engine, Daemon
v0.3	Injection	ContextInjector, Budget-Aware, Format-for-Prompt
v0.4	Adapters	LangChain, CrewAI, AutoGen, RawAPI
v0.5	CLI	`memograph status/recall/dream/prune/forget`
v0.6	Embeddings	Optional semantic relevance scoring
v0.7	Verification	Staleness detection, verification prompts
v0.8	Multi-Agent	Shared memory across agent teams
v0.9	TypeScript Port	`npm install memograph` (mirrors original lang)

v1.0	Stable Release	Docs, tests ≥90% coverage, benchmarks

🔑 PART 12 — THE 6 CORE DESIGN PRINCIPLES (Summary)

1. The index stores locations, not data. Actual project knowledge is distributed across "topic files" fetched on-demand, while raw transcripts are never fully read back into the context.[3]
2. Strict write discipline. The agent must update its index only after a successful file write — this prevents context pollution from failed attempts.[3]
3. Forked read-only consolidation. autoDream's approach of forking a read-only subagent is clean because it can't accidentally corrupt whatever the agent is currently working on.[1]
4. Skeptical memory. The agent is instructed to treat its own memory as a "hint" and verify everything against the actual codebase before acting. The system does not trust what it remembers.[6]
5. Active contradiction resolution. autoDream doesn't just delete old memories. It merges related observations, removes logical contradictions, and converts vague insights into concrete facts. If your agent noted "user might prefer X" three months ago and "user confirmed X yesterday," the old entry should be updated, not kept alongside the new one.[1]
6. Context management is the hard problem. Claude Code's three-layer architecture is significantly more complex than "bigger context window = better." Smart scheduling of what to load and when matters at least as much as total capacity.[2]

🧠 MemoGraph — 10-Phase Build Plan + Phase 1 Complete Runnable Code

---

🗺️ THE 10-PHASE ROADMAP

Phase	Name	What Gets Built
1	🏗️ Foundation	DB schema, models, config, model-agnostic LLM client, CRUD core
2	🧠 Memory Layer	Full 3-layer architecture, index engine, topic file manager

3	🌙 AutoDream	Consolidation daemon, gates, lock, 4-phase dream engine
4	💉 Context Injection	Bandwidth-aware injector, token budgeting, prompt formatter
5	🔍 Relevance Engine	Keyword scorer, embedding scorer, semantic search
6	✅ Verification	Staleness detection, skeptical memory, verification prompts
7	🔌 Adapters	LangChain, CrewAI, AutoGen, raw API adapters
8	🖥️ CLI	Full CLI, status dashboard, interactive recall
9	🌐 REST API	FastAPI server, WebSocket live updates, API keys
10	📦 SDK & Docs	Package, publish, TypeScript port, full docs

✅ PHASE 1 — COMPLETE RUNNABLE CODE

Project Structure for Phase 1

text

```
memograph/
├── pyproject.toml
├── .env.example
├── README.md
├── memograph/
│   ├── __init__.py
│   ├── config.py                    ← Model-agnostic config + BYOK
│   ├── db/
│   │   ├── __init__.py
│   │   ├── schema.sql               ← Full DB schema
│   │   ├── migrations/
│   │   │   └── 001_initial.sql
│   │   └── database.py              ← Async SQLite manager
│   ├── llm/
│   │   ├── __init__.py
│   │   ├── base.py                  ← Abstract LLM interface
│   │   ├── providers/
│   │   │   ├── __init__.py
│   │   │   ├── anthropic_provider.py
│   │   │   ├── openai_provider.py
│   │   │   ├── ollama_provider.py
│   │   │   ├── groq_provider.py
│   │   │   └── gemini_provider.py
│   │   └── factory.py               ← LLM factory / router
│   ├── models/
│   │   ├── __init__.py
│   │   ├── index.py
│   │   ├── topic.py
│   │   ├── transcript.py
│   │   └── config_models.py
│   ├── prompts/
│   │   ├── __init__.py
│   │   ├── system_prompts.py        ← All system prompts
│   │   └── templates.py
│   └── core/
│       ├── __init__.py
│       └── memory_manager.py
└── tests/
    ├── __init__.py
    ├── conftest.py
    ├── test_config.py
    ├── test_database.py
    ├── test_llm_factory.py
    ├── test_models.py
    └── test_memory_manager.py
```

---

1. pyproject.toml

toml

```
[build-system]
requires = ["hatchling"]
build-backend = "hatchling.build"

[project]
name = "memograph"
version = "0.1.0"
description = "Self-Healing 3-Layer Memory System for AI Agents"
readme = "README.md"
requires-python = ">=3.11"
license = {text = "MIT"}
keywords = ["ai", "agents", "memory", "llm", "rag", "langchain", "crewai", "autogen",
"ollama"]
authors = [
    {name = "MemoGraph Contributors"}
]

dependencies = [
    "aiofiles>=23.2.1",
    "aiosqlite>=0.20.0",
    "pydantic>=2.7.0",
    "pydantic-settings>=2.3.0",
    "python-dotenv>=1.0.1",
    "httpx>=0.27.0",
    "tenacity>=8.3.0",
    "rich>=13.7.0",
    "typer>=0.12.0",
    "structlog>=24.1.0",
]

[project.optional-dependencies]
anthropic = ["anthropic>=0.30.0"]
openai    = ["openai>=1.35.0"]
ollama    = ["ollama>=0.3.0"]
groq      = ["groq>=0.9.0"]
gemini    = ["google-generativeai>=0.7.0"]

langchain = ["langchain>=0.2.0", "langchain-core>=0.2.0"]
crewai    = ["crewai>=0.36.0"]
autogen   = ["pyautogen>=0.2.0"]

embeddings = ["numpy>=1.26.0", "scikit-learn>=1.5.0"]

all = [
    "memograph[anthropic,openai,ollama,groq,gemini,langchain,crewai,autogen,embeddings]"
]

dev = [
    "pytest>=8.2.0",
    "pytest-asyncio>=0.23.0",
```

```
    "pytest-cov>=5.0.0",
    "pytest-mock>=3.14.0",
    "ruff>=0.5.0",
    "mypy>=1.10.0",
    "httpx>=0.27.0",
]

[project.scripts]
memograph = "memograph.cli:app"

[project.urls]
Repository    = "https://github.com/yourname/memograph"
Documentation = "https://docs.memograph.dev"
Issues        = "https://github.com/yourname/memograph/issues"

[tool.pytest.ini_options]
asyncio_mode   = "auto"
testpaths      = ["tests"]
addopts        = "--cov=memograph --cov-report=term-missing -v"

[tool.ruff]
target-version = "py311"
line-length    = 100
select         = ["E", "F", "I", "UP", "B", "SIM"]

[tool.mypy]
python_version      = "3.11"
strict              = true
ignore_missing_imports = true

[tool.hatch.build.targets.wheel]
packages = ["memograph"]
```

---

2. `.env.example`

Bash

```
# ──────────────────────────────────────────────────────────
# MemoGraph — Environment Configuration
# Copy to .env and fill in the values you need.
# You only need ONE provider configured.
# ──────────────────────────────────────────────────────────

# ── Storage ──────────────────────────────────────────────
MEMOGRAPH_BASE_PATH=".memograph"
MEMOGRAPH_DB_PATH=".memograph/memograph.db"
MEMOGRAPH_LOG_LEVEL="INFO"
MEMOGRAPH_AGENT_ID="default"

# ── LLM Provider (choose one or more) ────────────────────
# Options: "anthropic" | "openai" | "ollama" | "groq" | "gemini" | "custom"
```

```
MEMOGRAPH_LLM_PROVIDER="ollama"

# ── Anthropic (Claude) ──────────────────────────────────────
ANTHROPIC_API_KEY=""
MEMOGRAPH_ANTHROPIC_MODEL="claude-3-haiku-20240307"
MEMOGRAPH_ANTHROPIC_BASE_URL=""          # Override for proxies

# ── OpenAI ──────────────────────────────────────────────────
OPENAI_API_KEY=""
MEMOGRAPH_OPENAI_MODEL="gpt-4o-mini"
MEMOGRAPH_OPENAI_BASE_URL=""             # Override for Azure / proxies
MEMOGRAPH_OPENAI_ORG_ID=""

# ── Ollama (Local — no API key needed) ──────────────────────
MEMOGRAPH_OLLAMA_BASE_URL="http://localhost:11434"
MEMOGRAPH_OLLAMA_MODEL="llama3.1:8b"
MEMOGRAPH_OLLAMA_TIMEOUT=120

# ── Groq ────────────────────────────────────────────────────
GROQ_API_KEY=""
MEMOGRAPH_GROQ_MODEL="llama-3.1-8b-instant"

# ── Google Gemini ───────────────────────────────────────────
GOOGLE_API_KEY=""
MEMOGRAPH_GEMINI_MODEL="gemini-1.5-flash"

# ── Custom / Self-Hosted (OpenAI-compatible) ────────────────
MEMOGRAPH_CUSTOM_BASE_URL=""             # e.g. http://localhost:8080/v1
MEMOGRAPH_CUSTOM_API_KEY=""
MEMOGRAPH_CUSTOM_MODEL=""

# ── Consolidation (AutoDream) ───────────────────────────────
# Use a cheaper/faster model for background consolidation
MEMOGRAPH_CONSOLIDATION_PROVIDER=""      # Falls back to main provider if empty
MEMOGRAPH_CONSOLIDATION_MODEL=""         # e.g. "ollama:llama3.1:8b" or "haiku"

# ── Memory Limits ───────────────────────────────────────────
MEMOGRAPH_MAX_INDEX_LINES=200
MEMOGRAPH_MAX_INDEX_BYTES=25600          # 25KB
MEMOGRAPH_MAX_POINTER_CHARS=150
MEMOGRAPH_MIN_CONSOLIDATION_HOURS=24
MEMOGRAPH_MIN_CONSOLIDATION_SESSIONS=5

# ── Feature Flags ───────────────────────────────────────────
MEMOGRAPH_AUTO_CONSOLIDATE=true
MEMOGRAPH_USE_EMBEDDINGS=false
MEMOGRAPH_SKEPTICAL_MODE=true            # Verify before use
MEMOGRAPH_DEBUG_PROMPTS=false            # Print prompts to stdout
```

---

3. Database Schema

SQL

```sql
-- memograph/db/schema.sql
-- MemoGraph Full Database Schema
-- SQLite with WAL mode for concurrent reads

PRAGMA journal_mode = WAL;
PRAGMA foreign_keys = ON;
PRAGMA synchronous = NORMAL;

-- ─────────────────────────────────────────────────────────────
-- AGENTS
-- Each agent has its own isolated memory namespace.
-- ─────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS agents (
    id                  TEXT PRIMARY KEY,           -- e.g. "myproject_agent"
    display_name        TEXT NOT NULL,
    created_at          TEXT NOT NULL DEFAULT (datetime('now')),
    updated_at          TEXT NOT NULL DEFAULT (datetime('now')),
    meta                TEXT NOT NULL DEFAULT '{}'  -- JSON blob for extra config
);

-- ─────────────────────────────────────────────────────────────
-- MEMORY INDEX
-- Mirrors MEMORY.md — one row per pointer.
-- Always loaded. Each row ≤ 150 chars in summary.
-- ─────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS memory_index (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    topic_id            TEXT NOT NULL,
    topic_file_path     TEXT NOT NULL,              -- Relative path to topic file
    summary             TEXT NOT NULL,              -- ≤ 80 chars
    confidence          REAL NOT NULL DEFAULT 0.5,  -- 0.0 – 1.0
    pointer_line        TEXT NOT NULL,              -- Full ≤150 char index line
    last_updated        TEXT NOT NULL DEFAULT (datetime('now')),
    last_accessed       TEXT,
    access_count        INTEGER NOT NULL DEFAULT 0,
    is_stale            INTEGER NOT NULL DEFAULT 0, -- Boolean
    verification_source TEXT,                       -- Where to verify this
    created_at          TEXT NOT NULL DEFAULT (datetime('now')),

    UNIQUE(agent_id, topic_id)
);

CREATE INDEX IF NOT EXISTS idx_memory_index_agent
    ON memory_index(agent_id);

CREATE INDEX IF NOT EXISTS idx_memory_index_confidence
    ON memory_index(agent_id, confidence DESC);

CREATE INDEX IF NOT EXISTS idx_memory_index_stale
    ON memory_index(agent_id, is_stale);

-- ─────────────────────────────────────────────────────────────
-- TOPICS
-- Layer 2 metadata. Actual content lives in .md files.
-- DB stores metadata for fast querying without reading files.
-- ─────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS topics (
```

```
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    topic_id            TEXT NOT NULL,
    topic_name          TEXT NOT NULL,
    file_path           TEXT NOT NULL,              -- Relative path
    file_size_bytes     INTEGER NOT NULL DEFAULT 0,
    fact_count          INTEGER NOT NULL DEFAULT 0,
    avg_confidence      REAL NOT NULL DEFAULT 0.5,
    tags                TEXT NOT NULL DEFAULT '[]', -- JSON array
    created_at          TEXT NOT NULL DEFAULT (datetime('now')),
    last_modified       TEXT NOT NULL DEFAULT (datetime('now')),
    last_accessed       TEXT,
    is_archived         INTEGER NOT NULL DEFAULT 0,

    UNIQUE(agent_id, topic_id)
);

CREATE INDEX IF NOT EXISTS idx_topics_agent
    ON topics(agent_id);

CREATE INDEX IF NOT EXISTS idx_topics_tags
    ON topics(agent_id, tags);

-- ─────────────────────────────────────────────────────────────────────
-- FACTS
-- Individual atomic memory entries within a topic.
-- ─────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS facts (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    topic_id            TEXT NOT NULL,
    fact_id             TEXT NOT NULL,              -- Short UUID e.g. "a3f8b2"
    content             TEXT NOT NULL,
    confidence_level    TEXT NOT NULL DEFAULT 'observed',
                                                    -- verified|observed|inferred|stale
    source              TEXT NOT NULL,              -- Where did this come from
    verification_hint   TEXT,                       -- How to verify this fact
    created_at          TEXT NOT NULL DEFAULT (datetime('now')),
    last_verified       TEXT,
    is_contradiction    INTEGER NOT NULL DEFAULT 0,
    contradicts_ids     TEXT NOT NULL DEFAULT '[]', -- JSON array of fact_ids
    meta                TEXT NOT NULL DEFAULT '{}', -- JSON blob

    UNIQUE(agent_id, topic_id, fact_id),
    FOREIGN KEY(agent_id, topic_id) REFERENCES topics(agent_id, topic_id)
        ON DELETE CASCADE
);

CREATE INDEX IF NOT EXISTS idx_facts_agent_topic
    ON facts(agent_id, topic_id);

CREATE INDEX IF NOT EXISTS idx_facts_confidence
    ON facts(agent_id, confidence_level);

CREATE INDEX IF NOT EXISTS idx_facts_stale
    ON facts(agent_id, last_verified);

CREATE INDEX IF NOT EXISTS idx_facts_contradictions
```

```
    ON facts(agent_id, is_contradiction);

-- ═══════════════════════════════════════════════════════════════════
-- SESSIONS
-- Tracks agent sessions for consolidation gate.
-- ═══════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS sessions (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    session_id          TEXT NOT NULL,
    started_at          TEXT NOT NULL DEFAULT (datetime('now')),
    ended_at            TEXT,
    turn_count          INTEGER NOT NULL DEFAULT 0,
    transcript_file     TEXT,                       -- Path to .jsonl file
    meta                TEXT NOT NULL DEFAULT '{}',

    UNIQUE(agent_id, session_id)
);

CREATE INDEX IF NOT EXISTS idx_sessions_agent
    ON sessions(agent_id, started_at DESC);

-- ═══════════════════════════════════════════════════════════════════
-- CONSOLIDATION LOG
-- Full audit trail of every dream run.
-- ═══════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS consolidation_log (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    run_id              TEXT NOT NULL,
    started_at          TEXT NOT NULL DEFAULT (datetime('now')),
    ended_at            TEXT,
    status              TEXT NOT NULL DEFAULT 'running',
                                                    -- running|completed|failed|skipped
    trigger             TEXT NOT NULL DEFAULT 'daemon',
                                                    -- daemon|manual|api
    gate_results        TEXT NOT NULL DEFAULT '{}', -- JSON
    phase_results       TEXT NOT NULL DEFAULT '{}', -- JSON
    facts_merged        INTEGER NOT NULL DEFAULT 0,
    facts_created       INTEGER NOT NULL DEFAULT 0,
    contradictions_resolved INTEGER NOT NULL DEFAULT 0,
    pointers_pruned     INTEGER NOT NULL DEFAULT 0,
    llm_provider        TEXT,
    llm_model           TEXT,
    error_message       TEXT,

    UNIQUE(agent_id, run_id)
);

CREATE INDEX IF NOT EXISTS idx_consolidation_agent
    ON consolidation_log(agent_id, started_at DESC);

-- ═══════════════════════════════════════════════════════════════════
-- LLM CALL LOG
-- Track every LLM call for cost monitoring & debugging.
-- ═══════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS llm_calls (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
```

```
    agent_id            TEXT REFERENCES agents(id) ON DELETE SET NULL,
    session_id          TEXT,
    call_id             TEXT NOT NULL UNIQUE,
    provider            TEXT NOT NULL,              -- anthropic|openai|ollama|groq|gemini
    model               TEXT NOT NULL,
    prompt_tokens       INTEGER NOT NULL DEFAULT 0,
    completion_tokens   INTEGER NOT NULL DEFAULT 0,
    total_tokens        INTEGER NOT NULL DEFAULT 0,
    latency_ms          INTEGER NOT NULL DEFAULT 0,
    purpose             TEXT NOT NULL DEFAULT 'recall',
                                                    --
recall|consolidation|verification|extraction
    status              TEXT NOT NULL DEFAULT 'success',
    error_message       TEXT,
    created_at          TEXT NOT NULL DEFAULT (datetime('now'))
);

CREATE INDEX IF NOT EXISTS idx_llm_calls_agent
    ON llm_calls(agent_id, created_at DESC);

CREATE INDEX IF NOT EXISTS idx_llm_calls_provider
    ON llm_calls(provider, model);

-- ─────────────────────────────────────────────────────────────────────────────
-- CONFIG STORE
-- Runtime config overrides per agent.
-- ─────────────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS agent_config (
    agent_id            TEXT NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    key                 TEXT NOT NULL,
    value               TEXT NOT NULL,              -- JSON-encoded value
    updated_at          TEXT NOT NULL DEFAULT (datetime('now')),

    PRIMARY KEY(agent_id, key)
);

-- ─────────────────────────────────────────────────────────────────────────────
-- SCHEMA VERSION
-- ─────────────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS schema_version (
    version             INTEGER PRIMARY KEY,
    applied_at          TEXT NOT NULL DEFAULT (datetime('now')),
    description         TEXT NOT NULL
);

INSERT OR IGNORE INTO schema_version(version, description)
VALUES (1, 'Initial schema: agents, index, topics, facts, sessions, consolidation_log,
llm_calls');
```

---

4. Migration File

SQL

```sql
-- memograph/db/migrations/001_initial.sql
-- Migration 001 — runs schema.sql and seeds default agent

-- Applied by DatabaseManager.migrate() on first run.
-- Idempotent: all CREATE statements use IF NOT EXISTS.

-- Seed the default agent
INSERT OR IGNORE INTO agents(id, display_name, meta)
VALUES (
    'default',
    'Default Agent',
    '{"created_by": "memograph_init", "version": "0.1.0"}'
);
```

---

5. memograph/config.py

Python

```python
# memograph/config.py
"""
MemoGraph Configuration System.
Model-agnostic, BYOK, Ollama-first friendly.
Uses pydantic-settings for env + .env file loading.
"""

from __future__ import annotations

import os
from enum import Enum
from pathlib import Path
from typing import Optional

from pydantic import Field, field_validator, model_validator
from pydantic_settings import BaseSettings, SettingsConfigDict


class LLMProvider(str, Enum):
    ANTHROPIC = "anthropic"
    OPENAI    = "openai"
    OLLAMA    = "ollama"
    GROQ      = "groq"
    GEMINI    = "gemini"
    CUSTOM    = "custom"   # Any OpenAI-compatible endpoint


class ConfidenceLevel(str, Enum):
    VERIFIED = "verified"
    OBSERVED = "observed"
    INFERRED = "inferred"
    STALE    = "stale"
```

```python
class AnthropicConfig(BaseSettings):
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_ANTHROPIC_", extra="ignore")

    api_key:  str = Field(default="", alias="ANTHROPIC_API_KEY")
    model:    str = Field(default="claude-3-haiku-20240307")
    base_url: str = Field(default="https://api.anthropic.com")
    max_tokens: int = Field(default=4096)
    timeout:  int = Field(default=60)

    @field_validator("api_key", mode="before")
    @classmethod
    def _resolve_key(cls, v: str) -> str:
        return v or os.environ.get("ANTHROPIC_API_KEY", "")


class OpenAIConfig(BaseSettings):
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_OPENAI_", extra="ignore")

    api_key:  str = Field(default="", alias="OPENAI_API_KEY")
    model:    str = Field(default="gpt-4o-mini")
    base_url: str = Field(default="https://api.openai.com/v1")
    org_id:   str = Field(default="")
    max_tokens: int = Field(default=4096)
    timeout:  int = Field(default=60)

    @field_validator("api_key", mode="before")
    @classmethod
    def _resolve_key(cls, v: str) -> str:
        return v or os.environ.get("OPENAI_API_KEY", "")


class OllamaConfig(BaseSettings):
    """
    Ollama — local LLM. No API key required.
    Run: ollama serve && ollama pull llama3.1:8b
    """
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_OLLAMA_", extra="ignore")

    base_url:   str = Field(default="http://localhost:11434")
    model:      str = Field(default="llama3.1:8b")
    timeout:    int = Field(default=120)
    max_tokens: int = Field(default=4096)
    # Ollama-specific options
    num_ctx:    int = Field(default=8192)     # Context window
    temperature: float = Field(default=0.1)   # Low temp for memory ops
    top_p:      float = Field(default=0.9)


class GroqConfig(BaseSettings):
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_GROQ_", extra="ignore")

    api_key:  str = Field(default="", alias="GROQ_API_KEY")
    model:    str = Field(default="llama-3.1-8b-instant")
    base_url: str = Field(default="https://api.groq.com/openai/v1")
    max_tokens: int = Field(default=4096)
    timeout:  int = Field(default=30)
```

```
    @field_validator("api_key", mode="before")
    @classmethod
    def _resolve_key(cls, v: str) -> str:
        return v or os.environ.get("GROQ_API_KEY", "")


class GeminiConfig(BaseSettings):
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_GEMINI_", extra="ignore")

    api_key:  str = Field(default="", alias="GOOGLE_API_KEY")
    model:    str = Field(default="gemini-1.5-flash")
    max_tokens: int = Field(default=4096)
    timeout:  int = Field(default=60)

    @field_validator("api_key", mode="before")
    @classmethod
    def _resolve_key(cls, v: str) -> str:
        return v or os.environ.get("GOOGLE_API_KEY", "")


class CustomConfig(BaseSettings):
    """
    Any OpenAI-compatible endpoint:
    LM Studio, vLLM, LocalAI, Mistral, Together AI, etc.
    """
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_CUSTOM_", extra="ignore")

    base_url:   str = Field(default="")
    api_key:    str = Field(default="")
    model:      str = Field(default="")
    max_tokens: int = Field(default=4096)
    timeout:    int = Field(default=120)


class MemoryLimitsConfig(BaseSettings):
    model_config = SettingsConfigDict(env_prefix="MEMOGRAPH_", extra="ignore")

    max_index_lines:   int = Field(default=200)
    max_index_bytes:   int = Field(default=25_600)   # 25KB
    max_pointer_chars: int = Field(default=150)
    min_consolidation_hours:    int = Field(default=24)
    min_consolidation_sessions: int = Field(default=5)


class MemoGraphConfig(BaseSettings):
    """
    Master config. Supports:
    - Environment variables
    - .env file
    - Programmatic override (pass kwargs)
    - Per-provider BYOK
    """
    model_config = SettingsConfigDict(
        env_prefix="MEMOGRAPH_",
        env_file=".env",
        env_file_encoding="utf-8",
        extra="ignore",
        case_sensitive=False,
```

```
    )

    # ── Core ──────────────────────────────────────────────────────
    base_path:  str = Field(default=".memograph")
    db_path:    str = Field(default=".memograph/memograph.db")
    log_level:  str = Field(default="INFO")
    agent_id:   str = Field(default="default")
    debug_prompts: bool = Field(default=False)

    # ── Provider Selection ────────────────────────────────────────
    llm_provider: LLMProvider = Field(default=LLMProvider.OLLAMA)

    # Consolidation can use a different (cheaper) provider
    consolidation_provider: Optional[LLMProvider] = Field(default=None)
    consolidation_model:    Optional[str]          = Field(default=None)

    # ── Provider Configs ──────────────────────────────────────────
    anthropic: AnthropicConfig = Field(default_factory=AnthropicConfig)
    openai:    OpenAIConfig    = Field(default_factory=OpenAIConfig)
    ollama:    OllamaConfig    = Field(default_factory=OllamaConfig)
    groq:      GroqConfig      = Field(default_factory=GroqConfig)
    gemini:    GeminiConfig    = Field(default_factory=GeminiConfig)
    custom:    CustomConfig    = Field(default_factory=CustomConfig)

    # ── Memory Limits ─────────────────────────────────────────────
    limits: MemoryLimitsConfig = Field(default_factory=MemoryLimitsConfig)

    # ── Feature Flags ─────────────────────────────────────────────
    auto_consolidate: bool = Field(default=True)
    use_embeddings:   bool = Field(default=False)
    skeptical_mode:   bool = Field(default=True)

    @model_validator(mode="after")
    def _ensure_paths(self) -> "MemoGraphConfig":
        Path(self.base_path).mkdir(parents=True, exist_ok=True)
        Path(self.db_path).parent.mkdir(parents=True, exist_ok=True)
        return self

    def get_active_provider_config(self) -> (
        AnthropicConfig | OpenAIConfig | OllamaConfig |
        GroqConfig      | GeminiConfig  | CustomConfig
    ):
        """Return the config for the currently active provider."""
        return {
            LLMProvider.ANTHROPIC: self.anthropic,
            LLMProvider.OPENAI:    self.openai,
            LLMProvider.OLLAMA:    self.ollama,
            LLMProvider.GROQ:      self.groq,
            LLMProvider.GEMINI:    self.gemini,
            LLMProvider.CUSTOM:    self.custom,
        }[self.llm_provider]

    def get_consolidation_provider(self) -> LLMProvider:
        """Consolidation provider — falls back to main if not set."""
        return self.consolidation_provider or self.llm_provider

    def is_local(self) -> bool:
        """True if the active provider is running locally."""
```

```
        return self.llm_provider in (LLMProvider.OLLAMA, LLMProvider.CUSTOM)

    def summary(self) -> dict:
        cfg = self.get_active_provider_config()
        return {
            "provider":          self.llm_provider.value,
            "model":             getattr(cfg, "model", "unknown"),
            "local":             self.is_local(),
            "agent_id":          self.agent_id,
            "auto_consolidate":  self.auto_consolidate,
            "skeptical_mode":    self.skeptical_mode,
            "use_embeddings":    self.use_embeddings,
        }


# Singleton accessor
_config: Optional[MemoGraphConfig] = None


def get_config(**overrides) -> MemoGraphConfig:
    """
    Get or create the global MemoGraph config.
    Pass keyword overrides to modify at runtime:

        cfg = get_config(llm_provider="ollama", agent_id="mybot")
    """
    global _config
    if _config is None or overrides:
        _config = MemoGraphConfig(**overrides)
    return _config


def reset_config() -> None:
    """Reset singleton — useful in tests."""
    global _config
    _config = None
```

---

6. LLM Base Interface

Python

```
# memograph/llm/base.py
"""
Abstract base for all LLM providers.
Model-agnostic interface — every provider speaks this protocol.
"""

from __future__ import annotations

import time
import uuid
from abc import ABC, abstractmethod
```

```python
from dataclasses import dataclass, field
from typing import AsyncIterator, Optional


@dataclass
class Message:
    """A single conversation turn."""
    role:    str   # "system" | "user" | "assistant"
    content: str

    def to_dict(self) -> dict:
        return {"role": self.role, "content": self.content}


@dataclass
class LLMResponse:
    """Unified response from any LLM provider."""
    content:           str
    provider:          str
    model:             str
    prompt_tokens:     int          = 0
    completion_tokens: int          = 0
    total_tokens:      int          = 0
    latency_ms:        int          = 0
    call_id:           str          = field(default_factory=lambda: str(uuid.uuid4())[:8])
    raw:               dict         = field(default_factory=dict)
    finish_reason:     str          = "stop"

    @property
    def cost_estimate(self) -> float:
        """
        Rough cost estimate in USD.
        Override per provider for accurate pricing.
        """
        return 0.0


@dataclass
class LLMRequest:
    """Unified request to any LLM provider."""
    messages:        list[Message]
    model:           Optional[str] = None    # Override default model
    max_tokens:      int           = 2048
    temperature:     float         = 0.1    # Low temp for memory ops
    system_prompt:   Optional[str] = None   # Injected as system message
    purpose:         str           = "recall"
    stream:          bool          = False

    def with_system(self, system: str) -> "LLMRequest":
        """Return new request with system prompt prepended."""
        return LLMRequest(
            messages=[Message("system", system)] + self.messages,
            model=self.model,
            max_tokens=self.max_tokens,
            temperature=self.temperature,
            purpose=self.purpose,
            stream=self.stream,
        )
```

```python
class BaseLLMProvider(ABC):
    """
    Abstract base all providers implement.
    Three methods: complete, stream, health_check.
    """

    provider_name: str = "base"

    @abstractmethod
    async def complete(self, request: LLMRequest) -> LLMResponse:
        """Send a completion request. Returns full response."""
        ...

    @abstractmethod
    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        """Stream completion tokens."""
        ...

    @abstractmethod
    async def health_check(self) -> bool:
        """Check if the provider is reachable."""
        ...

    async def complete_simple(
        self,
        prompt: str,
        system: Optional[str] = None,
        model: Optional[str] = None,
        max_tokens: int = 2048,
        purpose: str = "recall",
    ) -> str:
        """Convenience: single-turn completion, returns just the text."""
        messages = [Message("user", prompt)]
        req = LLMRequest(
            messages=messages,
            model=model,
            max_tokens=max_tokens,
            temperature=0.1,
            system_prompt=system,
            purpose=purpose,
        )
        if system:
            req = req.with_system(system)
        resp = await self.complete(req)
        return resp.content

    def _make_response(
        self,
        content: str,
        model: str,
        prompt_tokens: int = 0,
        completion_tokens: int = 0,
        latency_ms: int = 0,
        raw: dict | None = None,
    ) -> LLMResponse:
        return LLMResponse(
```

```
            content=content,
            provider=self.provider_name,
            model=model,
            prompt_tokens=prompt_tokens,
            completion_tokens=completion_tokens,
            total_tokens=prompt_tokens + completion_tokens,
            latency_ms=latency_ms,
            raw=raw or {},
        )
```

---

7. Ollama Provider

Python

```
# memograph/llm/providers/ollama_provider.py
"""
Ollama provider — local LLMs, zero API key, fully private.
Supports: llama3.1, mistral, phi3, qwen2, gemma2, deepseek, etc.

Prerequisites:
    brew install ollama        # macOS
    ollama serve               # Start server
    ollama pull llama3.1:8b    # Pull a model
"""

from __future__ import annotations

import time
from typing import AsyncIterator, Optional

import httpx

from memograph.llm.base import (
    BaseLLMProvider,
    LLMRequest,
    LLMResponse,
    Message,
)
from memograph.config import OllamaConfig


class OllamaProvider(BaseLLMProvider):
    """
    Ollama local LLM provider.
    Uses Ollama's native /api/chat and /api/generate endpoints.
    Falls back gracefully if Ollama is not running.
    """

    provider_name = "ollama"

    def __init__(self, config: OllamaConfig):
        self.config   = config
```

```
        self.base_url = config.base_url.rstrip("/")
        self._client  = httpx.AsyncClient(timeout=config.timeout)

    async def complete(self, request: LLMRequest) -> LLMResponse:
        model = request.model or self.config.model
        t0    = time.monotonic()

        # Build Ollama chat payload
        payload = {
            "model":  model,
            "stream": False,
            "messages": [m.to_dict() for m in request.messages],
            "options": {
                "temperature": request.temperature,
                "num_predict": request.max_tokens,
                "num_ctx":     self.config.num_ctx,
                "top_p":       self.config.top_p,
            },
        }

        try:
            resp = await self._client.post(
                f"{self.base_url}/api/chat",
                json=payload,
            )
            resp.raise_for_status()
            data    = resp.json()
            content = data["message"]["content"]

            prompt_tokens     = data.get("prompt_eval_count", 0)
            completion_tokens = data.get("eval_count", 0)
            latency_ms        = int((time.monotonic() - t0) * 1000)

            return self._make_response(
                content=content,
                model=model,
                prompt_tokens=prompt_tokens,
                completion_tokens=completion_tokens,
                latency_ms=latency_ms,
                raw=data,
            )

        except httpx.ConnectError as e:
            raise ConnectionError(
                f"Cannot reach Ollama at {self.base_url}. "
                f"Is 'ollama serve' running? Error: {e}"
            ) from e
        except httpx.HTTPStatusError as e:
            raise RuntimeError(
                f"Ollama API error {e.response.status_code}: {e.response.text}"
            ) from e

    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        model = request.model or self.config.model

        payload = {
            "model":    model,
            "stream":   True,
```

```
            "messages": [m.to_dict() for m in request.messages],
            "options":  {
                "temperature": request.temperature,
                "num_predict": request.max_tokens,
                "num_ctx":     self.config.num_ctx,
            },
        }

        async with self._client.stream(
            "POST",
            f"{self.base_url}/api/chat",
            json=payload,
        ) as resp:
            resp.raise_for_status()
            async for line in resp.aiter_lines():
                if line:
                    import json
                    chunk = json.loads(line)
                    if not chunk.get("done", False):
                        yield chunk.get("message", {}).get("content", "")

    async def health_check(self) -> bool:
        """Check if Ollama is running and the model is available."""
        try:
            resp = await self._client.get(f"{self.base_url}/api/tags", timeout=5)
            if resp.status_code != 200:
                return False
            models = [m["name"] for m in resp.json().get("models", [])]
            model  = self.config.model
            # Check if model (or base model) is available
            return any(
                m.startswith(model.split(":")[0]) for m in models
            )
        except Exception:
            return False

    async def list_local_models(self) -> list[str]:
        """Return list of all locally available Ollama models."""
        try:
            resp = await self._client.get(f"{self.base_url}/api/tags")
            resp.raise_for_status()
            return [m["name"] for m in resp.json().get("models", [])]
        except Exception:
            return []

    async def pull_model(self, model: str) -> bool:
        """Pull a model from Ollama registry."""
        try:
            resp = await self._client.post(
                f"{self.base_url}/api/pull",
                json={"name": model, "stream": False},
                timeout=300,  # Pulling can take a while
            )
            return resp.status_code == 200
        except Exception:
            return False

    async def close(self) -> None:
```

```
        await self._client.aclose()
```

---

8. Anthropic Provider

Python

```
# memograph/llm/providers/anthropic_provider.py
"""
Anthropic (Claude) provider.
Models: claude-3-haiku (cheap/fast), claude-3-5-sonnet, claude-3-opus
"""

from __future__ import annotations

import time
from typing import AsyncIterator

from memograph.llm.base import BaseLLMProvider, LLMRequest, LLMResponse
from memograph.config import AnthropicConfig

try:
    import anthropic as _anthropic
    _ANTHROPIC_AVAILABLE = True
except ImportError:
    _ANTHROPIC_AVAILABLE = False


class AnthropicProvider(BaseLLMProvider):
    provider_name = "anthropic"

    def __init__(self, config: AnthropicConfig):
        if not _ANTHROPIC_AVAILABLE:
            raise ImportError(
                "anthropic package not installed. "
                "Run: pip install memograph[anthropic]"
            )
        self.config = config
        self._client = _anthropic.AsyncAnthropic(
            api_key=config.api_key,
            base_url=config.base_url or None,
        )

    async def complete(self, request: LLMRequest) -> LLMResponse:
        model = request.model or self.config.model
        t0    = time.monotonic()

        # Separate system messages from conversation
        system_parts  = [m.content for m in request.messages if m.role == "system"]
        conversation  = [m.to_dict() for m in request.messages if m.role != "system"]
        system_prompt = "\n\n".join(system_parts) if system_parts else _anthropic.NOT_GIVEN

        resp = await self._client.messages.create(
```

```
            model=model,
            max_tokens=request.max_tokens,
            system=system_prompt,
            messages=conversation,
        )

        content    = resp.content[0].text
        latency_ms = int((time.monotonic() - t0) * 1000)

        return self._make_response(
            content=content,
            model=model,
            prompt_tokens=resp.usage.input_tokens,
            completion_tokens=resp.usage.output_tokens,
            latency_ms=latency_ms,
            raw=resp.model_dump(),
        )

    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        model = request.model or self.config.model
        system_parts = [m.content for m in request.messages if m.role == "system"]
        conversation = [m.to_dict() for m in request.messages if m.role != "system"]
        system       = "\n\n".join(system_parts) if system_parts else _anthropic.NOT_GIVEN

        async with self._client.messages.stream(
            model=model,
            max_tokens=request.max_tokens,
            system=system,
            messages=conversation,
        ) as stream_resp:
            async for text in stream_resp.text_stream:
                yield text

    async def health_check(self) -> bool:
        try:
            await self._client.messages.create(
                model=self.config.model,
                max_tokens=1,
                messages=[{"role": "user", "content": "hi"}],
            )
            return True
        except Exception:
            return False
```

---

9. OpenAI Provider

Python

```
# memograph/llm/providers/openai_provider.py
"""
OpenAI provider.
Also works with any OpenAI-compatible endpoint:
```

```
- Azure OpenAI
- LM Studio (local)
- vLLM (local)
- LocalAI (local)
- Together AI
- Mistral API
Just set MEMOGRAPH_OPENAI_BASE_URL to your endpoint.
"""

from __future__ import annotations

import time
from typing import AsyncIterator

from memograph.llm.base import BaseLLMProvider, LLMRequest, LLMResponse
from memograph.config import OpenAIConfig

try:
    import openai as _openai
    _OPENAI_AVAILABLE = True
except ImportError:
    _OPENAI_AVAILABLE = False


class OpenAIProvider(BaseLLMProvider):
    provider_name = "openai"

    def __init__(self, config: OpenAIConfig):
        if not _OPENAI_AVAILABLE:
            raise ImportError(
                "openai package not installed. "
                "Run: pip install memograph[openai]"
            )
        self.config = config
        self._client = _openai.AsyncOpenAI(
            api_key=config.api_key or "placeholder",  # LM Studio doesn't need a key
            base_url=config.base_url or None,
            organization=config.org_id or None,
            timeout=config.timeout,
        )

    async def complete(self, request: LLMRequest) -> LLMResponse:
        model = request.model or self.config.model
        t0    = time.monotonic()

        resp = await self._client.chat.completions.create(
            model=model,
            messages=[m.to_dict() for m in request.messages],
            max_tokens=request.max_tokens,
            temperature=request.temperature,
        )

        content    = resp.choices[0].message.content or ""
        latency_ms = int((time.monotonic() - t0) * 1000)

        return self._make_response(
            content=content,
            model=model,
```

```
            prompt_tokens=resp.usage.prompt_tokens if resp.usage else 0,
            completion_tokens=resp.usage.completion_tokens if resp.usage else 0,
            latency_ms=latency_ms,
            raw=resp.model_dump(),
        )

    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        model = request.model or self.config.model

        async with await self._client.chat.completions.create(
            model=model,
            messages=[m.to_dict() for m in request.messages],
            max_tokens=request.max_tokens,
            temperature=request.temperature,
            stream=True,
        ) as stream_resp:
            async for chunk in stream_resp:
                delta = chunk.choices[0].delta.content
                if delta:
                    yield delta

    async def health_check(self) -> bool:
        try:
            await self._client.chat.completions.create(
                model=self.config.model,
                messages=[{"role": "user", "content": "hi"}],
                max_tokens=1,
            )
            return True
        except Exception:
            return False
```

---

10. Groq Provider

Python

```
# memograph/llm/providers/groq_provider.py
"""
Groq provider — blazing fast inference for open models.
Best for: consolidation daemon (speed matters, cost low).
Models: llama-3.1-8b-instant, llama-3.1-70b-versatile, mixtral-8x7b
"""

from __future__ import annotations

import time
from typing import AsyncIterator

from memograph.llm.base import BaseLLMProvider, LLMRequest, LLMResponse
from memograph.config import GroqConfig

try:
```

```python
    from groq import AsyncGroq
    _GROQ_AVAILABLE = True
except ImportError:
    _GROQ_AVAILABLE = False


class GroqProvider(BaseLLMProvider):
    provider_name = "groq"

    def __init__(self, config: GroqConfig):
        if not _GROQ_AVAILABLE:
            raise ImportError(
                "groq package not installed. "
                "Run: pip install memograph[groq]"
            )
        self.config  = config
        self._client = AsyncGroq(api_key=config.api_key)

    async def complete(self, request: LLMRequest) -> LLMResponse:
        model = request.model or self.config.model
        t0    = time.monotonic()

        resp = await self._client.chat.completions.create(
            model=model,
            messages=[m.to_dict() for m in request.messages],
            max_tokens=request.max_tokens,
            temperature=request.temperature,
        )

        content    = resp.choices[0].message.content or ""
        latency_ms = int((time.monotonic() - t0) * 1000)

        return self._make_response(
            content=content,
            model=model,
            prompt_tokens=resp.usage.prompt_tokens if resp.usage else 0,
            completion_tokens=resp.usage.completion_tokens if resp.usage else 0,
            latency_ms=latency_ms,
        )

    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        model = request.model or self.config.model

        async for chunk in await self._client.chat.completions.create(
            model=model,
            messages=[m.to_dict() for m in request.messages],
            max_tokens=request.max_tokens,
            temperature=request.temperature,
            stream=True,
        ):
            delta = chunk.choices[0].delta.content
            if delta:
                yield delta

    async def health_check(self) -> bool:
        try:
            await self._client.chat.completions.create(
                model=self.config.model,
```

```
                messages=[{"role": "user", "content": "hi"}],
                max_tokens=1,
            )
            return True
        except Exception:
            return False
```

---

11. Gemini Provider

Python

```
# memograph/llm/providers/gemini_provider.py

from __future__ import annotations

import time
from typing import AsyncIterator

from memograph.llm.base import BaseLLMProvider, LLMRequest, LLMResponse
from memograph.config import GeminiConfig

try:
    import google.generativeai as genai
    _GEMINI_AVAILABLE = True
except ImportError:
    _GEMINI_AVAILABLE = False


class GeminiProvider(BaseLLMProvider):
    provider_name = "gemini"

    def __init__(self, config: GeminiConfig):
        if not _GEMINI_AVAILABLE:
            raise ImportError(
                "google-generativeai not installed. "
                "Run: pip install memograph[gemini]"
            )
        self.config = config
        genai.configure(api_key=config.api_key)
        self._model = genai.GenerativeModel(config.model)

    async def complete(self, request: LLMRequest) -> LLMResponse:
        model_name = request.model or self.config.model
        t0         = time.monotonic()

        # Convert messages to Gemini format
        prompt = "\n\n".join(
            f"[{m.role.upper()}]: {m.content}"
            for m in request.messages
        )

        resp = await self._model.generate_content_async(
```

```
            prompt,
            generation_config={
                "max_output_tokens": request.max_tokens,
                "temperature":       request.temperature,
            },
        )

        content    = resp.text or ""
        latency_ms = int((time.monotonic() - t0) * 1000)

        return self._make_response(
            content=content,
            model=model_name,
            latency_ms=latency_ms,
        )

    async def stream(self, request: LLMRequest) -> AsyncIterator[str]:
        prompt = "\n\n".join(
            f"[{m.role.upper()}]: {m.content}"
            for m in request.messages
        )
        async for chunk in await self._model.generate_content_async(
            prompt, stream=True
        ):
            if chunk.text:
                yield chunk.text

    async def health_check(self) -> bool:
        try:
            resp = await self._model.generate_content_async("hi")
            return bool(resp.text)
        except Exception:
            return False
```

---

12. LLM Factory

Python

```
# memograph/llm/factory.py
"""
LLM Factory — creates the right provider from config.
Supports provider:model shorthand syntax:
    "ollama:llama3.1:8b"
    "anthropic:claude-3-haiku-20240307"
    "openai:gpt-4o-mini"
    "groq:llama-3.1-8b-instant"
    "gemini:gemini-1.5-flash"
    "custom:my-model"
"""

from __future__ import annotations
```

```python
from functools import lru_cache
from typing import Optional

from memograph.config import LLMProvider, MemoGraphConfig, get_config
from memograph.llm.base import BaseLLMProvider


def create_provider(
    provider:  LLMProvider | str | None = None,
    model:     Optional[str]             = None,
    config:    Optional[MemoGraphConfig] = None,
    **kwargs,
) -> BaseLLMProvider:
    """
    Factory function — create the right LLM provider.

    Usage examples:
        # Use config default
        llm = create_provider()

        # Explicit provider
        llm = create_provider("ollama")
        llm = create_provider("ollama", model="phi3:mini")

        # Shorthand syntax
        llm = create_provider("anthropic:claude-3-haiku-20240307")

        # BYOK inline
        llm = create_provider("openai", api_key="sk-...", model="gpt-4o")

        # Local Ollama
        llm = create_provider("ollama", model="llama3.1:8b")

        # Custom OpenAI-compatible (LM Studio, vLLM, etc.)
        llm = create_provider("custom",
                              base_url="http://localhost:1234/v1",
                              model="local-model")
    """
    cfg = config or get_config()

    # Parse "provider:model" shorthand
    if isinstance(provider, str) and ":" in provider:
        parts     = provider.split(":", 1)
        provider  = parts[0]
        model     = model or parts[1]

    resolved_provider = (
        LLMProvider(provider) if provider
        else cfg.llm_provider
    )

    return _build_provider(resolved_provider, model, cfg, **kwargs)


def _build_provider(
    provider: LLMProvider,
    model:    Optional[str],
    cfg:      MemoGraphConfig,
```

```
    **kwargs,
) -> BaseLLMProvider:
    """Build provider instance with optional model/key overrides."""

    if provider == LLMProvider.OLLAMA:
        from memograph.llm.providers.ollama_provider import OllamaProvider
        ollama_cfg = cfg.ollama.model_copy(
            update={k: v for k, v in {
                "model":    model,
                "base_url": kwargs.get("base_url"),
                "timeout":  kwargs.get("timeout"),
            }.items() if v is not None}
        )
        return OllamaProvider(ollama_cfg)

    elif provider == LLMProvider.ANTHROPIC:
        from memograph.llm.providers.anthropic_provider import AnthropicProvider
        anth_cfg = cfg.anthropic.model_copy(
            update={k: v for k, v in {
                "model":   model,
                "api_key": kwargs.get("api_key"),
            }.items() if v is not None}
        )
        return AnthropicProvider(anth_cfg)

    elif provider == LLMProvider.OPENAI:
        from memograph.llm.providers.openai_provider import OpenAIProvider
        oa_cfg = cfg.openai.model_copy(
            update={k: v for k, v in {
                "model":    model,
                "api_key":  kwargs.get("api_key"),
                "base_url": kwargs.get("base_url"),
            }.items() if v is not None}
        )
        return OpenAIProvider(oa_cfg)

    elif provider == LLMProvider.GROQ:
        from memograph.llm.providers.groq_provider import GroqProvider
        groq_cfg = cfg.groq.model_copy(
            update={k: v for k, v in {
                "model":   model,
                "api_key": kwargs.get("api_key"),
            }.items() if v is not None}
        )
        return GroqProvider(groq_cfg)

    elif provider == LLMProvider.GEMINI:
        from memograph.llm.providers.gemini_provider import GeminiProvider
        gem_cfg = cfg.gemini.model_copy(
            update={k: v for k, v in {
                "model":   model,
                "api_key": kwargs.get("api_key"),
            }.items() if v is not None}
        )
        return GeminiProvider(gem_cfg)

    elif provider == LLMProvider.CUSTOM:
        # Custom = OpenAI-compatible endpoint
```

```
        from memograph.llm.providers.openai_provider import OpenAIProvider
        from memograph.config import OpenAIConfig
        custom_cfg = OpenAIConfig(
            api_key=kwargs.get("api_key") or cfg.custom.api_key or "none",
            model=model or cfg.custom.model,
            base_url=kwargs.get("base_url") or cfg.custom.base_url,
            max_tokens=cfg.custom.max_tokens,
            timeout=cfg.custom.timeout,
        )
        return OpenAIProvider(custom_cfg)

    else:
        raise ValueError(f"Unknown provider: {provider}")


async def probe_providers(cfg: Optional[MemoGraphConfig] = None) -> dict[str, bool]:
    """
    Check which providers are available.
    Useful for diagnostics.
    """
    cfg    = cfg or get_config()
    results = {}

    for p in LLMProvider:
        try:
            provider = create_provider(p, config=cfg)
            results[p.value] = await provider.health_check()
        except (ImportError, Exception):
            results[p.value] = False

    return results
```

---

13. System Prompts

Python

```
# memograph/prompts/system_prompts.py
"""
All MemoGraph system prompts.
These are the instructions that shape how the LLM interacts
with the memory system at every phase.
"""

from __future__ import annotations

from enum import Enum
from typing import Optional


class PromptRole(str, Enum):
    MEMORY_WRITER    = "memory_writer"
    MEMORY_READER    = "memory_reader"
```

```
    CONSOLIDATOR     = "consolidator"
    VERIFIER         = "verifier"
    EXTRACTOR        = "extractor"
    CONTRADICTION_RESOLVER = "contradiction_resolver"


# ──────────────────────────────────────────────────────────────────────────────
# CORE PRINCIPLES
# Shared across all prompts — injected as a preamble.
# ──────────────────────────────────────────────────────────────────────────────
_CORE_PRINCIPLES = """\
## MemoGraph Memory Principles

You are operating within the MemoGraph self-healing memory system.
Adhere to these principles at all times:

1. SKEPTICAL MEMORY
   - Treat all retrieved memories as *hints*, not ground truth.
   - Always verify facts against primary sources before acting.
   - State your confidence level explicitly.

2. WRITE DISCIPLINE
   - Never store facts that can be re-derived from accessible sources.
   - Prefer concrete, verifiable facts over vague observations.
   - One atomic fact per memory entry — no compound statements.

3. BANDWIDTH AWARENESS
   - The index is always loaded (≤150 chars/pointer).
   - Topic files are loaded only when relevant.
   - Transcripts are never loaded wholesale — only grep'd.

4. CONTRADICTION AVOIDANCE
   - If a new observation contradicts an existing memory, flag it.
   - Never silently overwrite — always log the conflict.

5. CONFIDENCE LEVELS
   - verified:  Confirmed against primary source.
   - observed:  Seen but not independently verified.
   - inferred:  Derived by reasoning (treat with extra skepticism).
   - stale:     Has not been verified recently — re-verify before use.
"""


# ──────────────────────────────────────────────────────────────────────────────
# MEMORY WRITER
# Used when the agent decides to store a new observation.
# ──────────────────────────────────────────────────────────────────────────────
MEMORY_WRITER_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Memory Writer

Your task is to extract durable, atomic facts from the provided content
and format them for storage in the MemoGraph memory system.

### Output Format
You MUST respond with valid JSON only — no prose, no markdown fences.
```

```
{{
  "should_store": true,
  "reason": "Brief explanation of why this is worth storing",
  "topic_id": "snake_case_topic_identifier",
  "topic_name": "Human readable topic name",
  "tags": ["tag1", "tag2"],
  "facts": [
    {{
      "content": "Atomic fact statement (≤200 chars)",
      "confidence": "observed|inferred|verified",
      "verification_hint": "How to verify this (optional)",
      "source": "Where this came from"
    }}
  ]
}}

### Rules
- Set should_store=false if the fact is trivially re-derivable.
- Set should_store=false if it is ephemeral (e.g., "user said hi").
- Maximum 5 facts per call.
- Each fact must be self-contained and standalone.
- topic_id must be lowercase, snake_case, ≤30 chars.
"""


# ──────────────────────────────────────────────────────────────────────────
# MEMORY READER
# Used when injecting context into an agent's prompt.
# ──────────────────────────────────────────────────────────────────────────
MEMORY_READER_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Memory-Aware Agent

You have access to a structured memory system.
The memory context below has been retrieved for your current task.

### How to Use Memory
- Use memories as *starting points*, not conclusions.
- If a memory is marked ⚠️ STALE, re-verify it before acting.
- If a memory is marked 💭 INFERRED, treat it as a hypothesis.
- If a memory is marked ✅ VERIFIED, it is safe to rely on.
- If memories conflict with what you observe, trust your observation
  and flag the conflict for the memory system.

### Memory Citation
When you use a memory fact in your response, cite it:
  "According to my memory [topic_id/fact_id]: ..."

### When NOT to Use Memory
- Do not use stale memories for critical decisions.
- Do not use inferred memories without noting your uncertainty.
- Do not assume the memory is complete — it may be missing relevant facts.
"""


# ──────────────────────────────────────────────────────────────────────────
# CONSOLIDATOR (autoDream)
```

```
# The background consolidation prompt — mirrors consolidationPrompt.ts
# ──────────────────────────────────────────────────────────────────────
CONSOLIDATOR_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Memory Consolidator (autoDream)

You are performing a *dream pass* — a reflective consolidation of the
agent's memory files. You run in a forked, read-only subprocess and
cannot modify the agent's main context.

### Your Four Tasks

1. MERGE
   Combine related observations into single, coherent facts.
   Example: "User prefers dark mode (observed)" + "User confirmed dark mode"
   → "User prefers dark mode (verified)"

2. RESOLVE CONTRADICTIONS
   When two facts conflict, keep the more recent/verified one.
   Document what was removed and why.

3. PROMOTE CONFIDENCE
   If evidence strongly supports an inferred fact, promote it to observed.
   If a fact has been consistently verified, promote it to verified.

4. PRUNE
   Remove facts that are:
   - Trivially re-derivable from the codebase/primary source
   - Ephemeral (e.g., session-specific, time-sensitive)
   - Superseded by newer facts
   - Pure noise with no decision-making value

### Output Format
Valid JSON only — no prose.

{{
  "operations": [
    {{
      "action": "merge",
      "topic_id": "...",
      "fact_ids": ["id1", "id2"],
      "merged_content": "Unified fact statement",
      "merged_confidence": "verified|observed|inferred",
      "reasoning": "Why these were merged"
    }},
    {{
      "action": "resolve_contradiction",
      "topic_id": "...",
      "keep_fact_id": "id1",
      "discard_fact_id": "id2",
      "resolution": "Kept id1 because it is more recent and verified",
      "reasoning": "..."
    }},
    {{
      "action": "promote",
      "topic_id": "...",
      "fact_id": "...",
```

```
      "new_confidence": "verified|observed",
      "reasoning": "..."
    }},
    {{
      "action": "prune",
      "topic_id": "...",
      "fact_id": "...",
      "reasoning": "Ephemeral / re-derivable / superseded"
    }},
    {{
      "action": "create",
      "topic_id": "...",
      "topic_name": "...",
      "tags": [],
      "content": "New synthesized fact",
      "confidence": "observed",
      "source": "autoDream consolidation"
    }}
  ],
  "summary": "Brief description of what changed"
}}

### Constraints
- Maximum 20 operations per run.
- Do not create facts about your own consolidation process.
- Be conservative — when in doubt, leave it alone.
"""


# ──────────────────────────────────────────────────────────────────────
# VERIFIER
# Used to check if a stored memory is still accurate.
# ──────────────────────────────────────────────────────────────────────
VERIFIER_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Memory Verifier

You are checking whether a stored memory fact is still accurate.
You have access to current context/evidence to verify against.

### Output Format
Valid JSON only.

{{
  "fact_id": "...",
  "verdict": "confirmed|refuted|outdated|uncertain",
  "new_confidence": "verified|observed|inferred|stale",
  "explanation": "Brief explanation of your verdict",
  "updated_content": null,
  "should_update": false
}}

### Verdicts
- confirmed:  Evidence supports the memory. Promote to verified.
- refuted:    Evidence contradicts the memory. Mark stale, flag update.
- outdated:   Memory was once true but conditions have changed.
- uncertain:  Cannot verify with available evidence.
```

```
"""


# ──────────────────────────────────────────────────────────────────────
# EXTRACTOR
# Extracts storable facts from raw agent output.
# ──────────────────────────────────────────────────────────────────────
EXTRACTOR_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Memory Extractor

Given a conversation turn or document, extract any facts that are
worth persisting in long-term memory.

### What IS worth storing
- User preferences confirmed by the user
- Project decisions and their rationale
- Recurring patterns in behavior or code
- Important constraints ("never do X", "always Y")
- Architectural decisions
- Hard-won debugging insights

### What is NOT worth storing
- Transient state ("user is currently on page X")
- Obvious facts re-derivable from code
- Pleasantries and small talk
- Anything that will be stale within 24 hours

### Output Format
Valid JSON only.

{{
  "extracted_facts": [
    {{
      "topic_id": "snake_case_identifier",
      "topic_name": "Human readable name",
      "tags": ["tag1"],
      "content": "Atomic fact (≤200 chars)",
      "confidence": "observed|inferred",
      "source": "conversation_turn|document|observation",
      "verification_hint": "How to verify (optional)"
    }}
  ],
  "extraction_notes": "What you found or why nothing was extracted"
}}
"""


# ──────────────────────────────────────────────────────────────────────
# CONTRADICTION DETECTOR
# Checks new facts against existing memory for contradictions.
# ──────────────────────────────────────────────────────────────────────
CONTRADICTION_DETECTOR_SYSTEM = f"""\
{_CORE_PRINCIPLES}

## Your Role: Contradiction Detector
```

```
Given a new fact and a list of existing memory facts, identify
any contradictions or conflicts.

### Output Format
Valid JSON only.

{{
  "has_contradiction": true,
  "contradicting_fact_ids": ["fact_id_1"],
  "conflict_description": "The new fact says X but fact_id_1 says Y",
  "recommendation": "keep_new|keep_existing|keep_both_flagged|merge",
  "merge_suggestion": null
}}

### Recommendations
- keep_new: New fact is more recent/reliable
- keep_existing: Existing fact is more reliable
- keep_both_flagged: Both may be valid in different contexts
- merge: Both contain partial truth — suggest a merged statement
"""


# ──────────────────────────────────────────────────────────────────────────────
# PROMPT REGISTRY
# ──────────────────────────────────────────────────────────────────────────────
PROMPTS: dict[PromptRole, str] = {
    PromptRole.MEMORY_WRITER:            MEMORY_WRITER_SYSTEM,
    PromptRole.MEMORY_READER:            MEMORY_READER_SYSTEM,
    PromptRole.CONSOLIDATOR:             CONSOLIDATOR_SYSTEM,
    PromptRole.VERIFIER:                 VERIFIER_SYSTEM,
    PromptRole.EXTRACTOR:                EXTRACTOR_SYSTEM,
    PromptRole.CONTRADICTION_RESOLVER:   CONTRADICTION_DETECTOR_SYSTEM,
}


def get_prompt(role: PromptRole) -> str:
    return PROMPTS[role]


def build_writer_prompt(content: str, context: Optional[str] = None) -> str:
    """Build the user-turn prompt for the memory writer."""
    parts = [f"Extract memorable facts from the following content:\n\n{content}"]
    if context:
        parts.append(f"\n\nAdditional context:\n{context}")
    return "\n".join(parts)


def build_extractor_prompt(conversation_turn: str, role: str = "assistant") -> str:
    """Build the user-turn for the fact extractor."""
    return (
        f"Extract any long-term-worth facts from this {role} message:\n\n"
        f"{conversation_turn}"
    )


def build_verifier_prompt(
    fact_content: str,
    current_evidence: str,
```

```
    fact_id: str,
) -> str:
    """Build the user-turn for fact verification."""
    return (
        f"Verify this memory fact:\n\n"
        f"Fact ID: {fact_id}\n"
        f"Fact: {fact_content}\n\n"
        f"Current evidence/context:\n{current_evidence}"
    )


def build_contradiction_prompt(
    new_fact: str,
    existing_facts: list[dict],
) -> str:
    """Build the user-turn for contradiction detection."""
    facts_str = "\n".join(
        f"  [{f['fact_id']}]: {f['content']} (confidence: {f['confidence']})"
        for f in existing_facts
    )
    return (
        f"New fact to store:\n  {new_fact}\n\n"
        f"Existing facts in this topic:\n{facts_str}\n\n"
        f"Identify any contradictions."
    )
```

---

14. Pydantic Models

Python

```
# memograph/models/index.py

from __future__ import annotations

from datetime import datetime
from typing import Optional

from pydantic import BaseModel, Field, field_validator


class IndexPointer(BaseModel):
    """One row in the memory index. Max 150 chars when serialized."""

    topic_id:           str
    topic_file_path:    str
    summary:            str           = Field(max_length=80)
    confidence:         float         = Field(default=0.5, ge=0.0, le=1.0)
    pointer_line:       str           = Field(default="", max_length=150)
    last_updated:       datetime      = Field(default_factory=datetime.now)
    last_accessed:      Optional[datetime] = None
    access_count:       int           = 0
    is_stale:           bool          = False
```

```
    verification_source: Optional[str] = None

    model_config = {"from_attributes": True}

    @field_validator("summary", mode="before")
    @classmethod
    def _trim_summary(cls, v: str) -> str:
        return v[:80] if v else v

    def build_pointer_line(self) -> str:
        """Build the ≤150 char index line."""
        ts    = self.last_updated.strftime("%Y-%m-%d")
        conf  = f"{self.confidence:.1f}"
        stale = " ⚠️" if self.is_stale else ""
        line  = (
            f"[{self.topic_id}]{stale} {self.summary} "
            f"→ {self.topic_file_path} ({ts}, conf={conf})"
        )
        return line[:150]

    def model_post_init(self, __context) -> None:
        if not self.pointer_line:
            self.pointer_line = self.build_pointer_line()


class MemoryIndex(BaseModel):
    """
    The full in-memory representation of MEMORY.md.
    Hard limits: 200 pointers, 25KB.
    """

    agent_id:          str                = "default"
    pointers:          list[IndexPointer] = Field(default_factory=list)
    version:           int                = 1
    last_consolidated: Optional[datetime] = None

    MAX_LINES: int = 200
    MAX_BYTES: int = 25_600

    model_config = {"from_attributes": True}

    def is_full(self) -> bool:
        return (
            len(self.pointers) >= self.MAX_LINES
            or len(self.to_markdown().encode()) >= self.MAX_BYTES
        )

    def get_pointer(self, topic_id: str) -> Optional[IndexPointer]:
        return next(
            (p for p in self.pointers if p.topic_id == topic_id), None
        )

    def upsert_pointer(self, pointer: IndexPointer) -> None:
        idx = next(
            (i for i, p in enumerate(self.pointers)
             if p.topic_id == pointer.topic_id), None
        )
        if idx is not None:
```

```
            self.pointers[idx] = pointer
        else:
            self.pointers.append(pointer)

    def remove_pointer(self, topic_id: str) -> bool:
        before = len(self.pointers)
        self.pointers = [p for p in self.pointers if p.topic_id != topic_id]
        return len(self.pointers) < before

    def sorted_by_confidence(self) -> list[IndexPointer]:
        return sorted(self.pointers, key=lambda p: p.confidence, reverse=True)

    def to_markdown(self) -> str:
        lines = [
            f"# MemoGraph Index — Agent: {self.agent_id}",
            f"Last consolidated: {self.last_consolidated or 'Never'}",
            f"Pointers: {len(self.pointers)}",
            "---",
        ]
        for p in self.sorted_by_confidence():
            lines.append(p.pointer_line or p.build_pointer_line())
        return "\n".join(lines)

    def get_context_injection(self) -> str:
        """What gets injected into EVERY prompt turn."""
        return self.to_markdown()
```

Python

```
# memograph/models/topic.py

from __future__ import annotations

import uuid
from datetime import datetime
from typing import Optional

from pydantic import BaseModel, Field

from memograph.config import ConfidenceLevel

CONFIDENCE_EMOJI = {
    ConfidenceLevel.VERIFIED: "✅",
    ConfidenceLevel.OBSERVED: "👁️",
    ConfidenceLevel.INFERRED: "💭",
    ConfidenceLevel.STALE:    "⚠️",
}


class MemoryFact(BaseModel):
    fact_id:    str             = Field(
        default_factory=lambda: str(uuid.uuid4())[:8]
    )
    content:    str             = Field(max_length=1000)
    confidence: ConfidenceLevel = ConfidenceLevel.OBSERVED
    source:     str
```

```
    verification_hint: Optional[str] = None
    created_at:        datetime      = Field(default_factory=datetime.now)
    last_verified:     Optional[datetime] = None
    is_contradiction:  bool          = False
    contradicts_ids:   list[str]     = Field(default_factory=list)
    meta:              dict          = Field(default_factory=dict)

    model_config = {"from_attributes": True}

    def to_markdown_line(self) -> str:
        emoji = CONFIDENCE_EMOJI[self.confidence]
        verified = (
            self.last_verified.strftime("%Y-%m-%d")
            if self.last_verified else "Never"
        )
        contra = (
            f" ⚡ contradicts: {', '.join(self.contradicts_ids)}"
            if self.contradicts_ids else ""
        )
        return (
            f"{emoji} `{self.fact_id}` {self.content}\n"
            f"   ↳ Source: {self.source} | Verified: {verified}{contra}"
        )


class TopicFile(BaseModel):
    topic_id:       str
    topic_name:     str
    agent_id:       str        = "default"
    facts:          list[MemoryFact] = Field(default_factory=list)
    tags:           list[str]  = Field(default_factory=list)
    file_path:      str        = ""
    created_at:     datetime   = Field(default_factory=datetime.now)
    last_modified:  datetime   = Field(default_factory=datetime.now)

    model_config = {"from_attributes": True}

    @property
    def avg_confidence(self) -> float:
        if not self.facts:
            return 0.5
        scores = {
            ConfidenceLevel.VERIFIED: 1.0,
            ConfidenceLevel.OBSERVED: 0.6,
            ConfidenceLevel.INFERRED: 0.4,
            ConfidenceLevel.STALE:    0.1,
        }
        return sum(scores[f.confidence] for f in self.facts) / len(self.facts)

    @property
    def verified_count(self) -> int:
        return sum(1 for f in self.facts if f.confidence == ConfidenceLevel.VERIFIED)

    @property
    def stale_count(self) -> int:
        return sum(1 for f in self.facts if f.confidence == ConfidenceLevel.STALE)

    def get_fact(self, fact_id: str) -> Optional[MemoryFact]:
```

```
        return next((f for f in self.facts if f.fact_id == fact_id), None)

    def get_contradictions(self) -> list[tuple[MemoryFact, MemoryFact]]:
        result = []
        for fact in self.facts:
            for contra_id in fact.contradicts_ids:
                contra = self.get_fact(contra_id)
                if contra:
                    result.append((fact, contra))
        return result

    def to_markdown(self) -> str:
        lines = [
            f"# Topic: {self.topic_name}",
            f"ID: `{self.topic_id}` | Agent: {self.agent_id}",
            f"Tags: {', '.join(self.tags) or 'none'}",
            f"Facts: {len(self.facts)} "
            f"(✅{self.verified_count} ⚠️{self.stale_count})",
            f"Last modified: {self.last_modified.strftime('%Y-%m-%d %H:%M')}",
            "---",
            "## Facts",
        ]
        if not self.facts:
            lines.append("*No facts stored yet.*")
        else:
            for fact in self.facts:
                lines.append(fact.to_markdown_line())
                lines.append("")
        return "\n".join(lines)

    def to_summary(self, max_chars: int = 80) -> str:
        """Short summary for index pointer."""
        n    = len(self.facts)
        tags = f" [{', '.join(self.tags[:2])}]" if self.tags else ""
        s    = f"{n} facts about {self.topic_name}{tags}"

        return s[:max_chars]
```

Python

```
# memograph/models/transcript.py

from __future__ import annotations

from datetime import datetime
from typing import Optional

from pydantic import BaseModel, Field


class TranscriptEntry(BaseModel):
    session_id:  str
    timestamp:   datetime = Field(default_factory=datetime.now)
    role:        str                        # user | assistant | tool | system
    content:     str
    tool_calls:  list[dict] = Field(default_factory=list)
```

```
    meta:        dict       = Field(default_factory=dict)

    model_config = {"from_attributes": True}

    def to_jsonl_line(self) -> str:
        import json
        return json.dumps({
            "session_id": self.session_id,
            "ts":         self.timestamp.isoformat(),
            "role":       self.role,
            "content":    self.content,
            "tool_calls": self.tool_calls,
        })


class Session(BaseModel):
    session_id:      str
    agent_id:        str      = "default"
    started_at:      datetime = Field(default_factory=datetime.now)
    ended_at:        Optional[datetime] = None
    turn_count:      int      = 0
    transcript_file: Optional[str] = None
    meta:            dict     = Field(default_factory=dict)

    model_config = {"from_attributes": True}

    @property
    def duration_seconds(self) -> Optional[float]:
        if self.ended_at:
            return (self.ended_at - self.started_at).total_seconds()

        return None
```

---

15. Database Manager

Python

```
# memograph/db/database.py
"""
Async SQLite database manager.
WAL mode for concurrent reads.
Auto-migration on startup.
"""

from __future__ import annotations

import json
import logging
from pathlib import Path
from typing import Any, Optional
```

```
import aiosqlite

logger = logging.getLogger("memograph.db")

SCHEMA_PATH    = Path(__file__).parent / "schema.sql"
MIGRATION_PATH = Path(__file__).parent / "migrations"


class DatabaseManager:
    """
    Async SQLite manager with connection pooling simulation.
    Single file, WAL mode, auto-migrates on connect.
    """

    def __init__(self, db_path: str | Path):
        self.db_path = Path(db_path)
        self.db_path.parent.mkdir(parents=True, exist_ok=True)
        self._conn: Optional[aiosqlite.Connection] = None

    async def connect(self) -> None:
        """Open connection and run migrations."""
        self._conn = await aiosqlite.connect(
            str(self.db_path),
            detect_types=1,          # sqlite3.PARSE_DECLTYPES
        )
        self._conn.row_factory = aiosqlite.Row
        await self._conn.execute("PRAGMA journal_mode = WAL")
        await self._conn.execute("PRAGMA foreign_keys = ON")
        await self._conn.execute("PRAGMA synchronous = NORMAL")
        await self._conn.commit()
        await self._migrate()
        logger.info(f"Database connected: {self.db_path}")

    async def disconnect(self) -> None:
        if self._conn:
            await self._conn.close()
            self._conn = None

    async def _migrate(self) -> None:
        """Run schema.sql if not yet applied."""
        schema_sql = SCHEMA_PATH.read_text()
        await self._conn.executescript(schema_sql)
        await self._conn.commit()

        # Run numbered migration files
        if MIGRATION_PATH.exists():
            for migration in sorted(MIGRATION_PATH.glob("*.sql")):
                version = int(migration.stem.split("_")[0])
                exists = await self.fetchone(
                    "SELECT 1 FROM schema_version WHERE version = ?",
                    (version,)
                )
                if not exists:
                    logger.info(f"Applying migration {migration.name}")
                    await self._conn.executescript(migration.read_text())
                    await self._conn.commit()

    # ──────────────────────────────────────────────
```

```
    # Query helpers
    # ──────────────────────────────────────────────

    async def execute(self, sql: str, params: tuple = ()) -> aiosqlite.Cursor:
        assert self._conn, "Database not connected"
        cursor = await self._conn.execute(sql, params)
        await self._conn.commit()
        return cursor

    async def executemany(self, sql: str, params: list[tuple]) -> None:
        assert self._conn, "Database not connected"
        await self._conn.executemany(sql, params)
        await self._conn.commit()

    async def fetchone(self, sql: str, params: tuple = ()) -> Optional[dict]:
        assert self._conn, "Database not connected"
        async with self._conn.execute(sql, params) as cur:
            row = await cur.fetchone()
            return dict(row) if row else None

    async def fetchall(self, sql: str, params: tuple = ()) -> list[dict]:
        assert self._conn, "Database not connected"
        async with self._conn.execute(sql, params) as cur:
            rows = await cur.fetchall()
            return [dict(r) for r in rows]

    async def fetchval(
        self, sql: str, params: tuple = (), default: Any = None
    ) -> Any:
        row = await self.fetchone(sql, params)
        if row:
            return next(iter(row.values()), default)
        return default

    # ──────────────────────────────────────────────
    # Agent operations
    # ──────────────────────────────────────────────

    async def ensure_agent(self, agent_id: str, display_name: str = "") -> None:
        """Create agent if it doesn't exist."""
        await self.execute(
            """
            INSERT OR IGNORE INTO agents(id, display_name)
            VALUES (?, ?)
            """,
            (agent_id, display_name or agent_id),
        )

    # ──────────────────────────────────────────────
    # Index operations
    # ──────────────────────────────────────────────

    async def upsert_index_pointer(
        self,
        agent_id:           str,
        topic_id:           str,
        topic_file_path:    str,
        summary:            str,
```

```
        confidence:          float,
        pointer_line:        str,
        is_stale:            bool = False,
        verification_source: Optional[str] = None,
    ) -> None:
        await self.execute(
            """
            INSERT INTO memory_index
              (agent_id, topic_id, topic_file_path, summary,
               confidence, pointer_line, is_stale,
               verification_source, last_updated)
            VALUES (?, ?, ?, ?, ?, ?, ?, ?, datetime('now'))
            ON CONFLICT(agent_id, topic_id) DO UPDATE SET
              topic_file_path    = excluded.topic_file_path,
              summary            = excluded.summary,
              confidence         = excluded.confidence,
              pointer_line       = excluded.pointer_line,
              is_stale           = excluded.is_stale,
              verification_source = excluded.verification_source,
              last_updated       = datetime('now')
            """,
            (
                agent_id, topic_id, topic_file_path, summary,
                confidence, pointer_line, int(is_stale),
                verification_source,
            ),
        )

    async def get_index_pointers(self, agent_id: str) -> list[dict]:
        return await self.fetchall(
            """
            SELECT * FROM memory_index
            WHERE agent_id = ?
            ORDER BY confidence DESC, last_updated DESC
            """,
            (agent_id,),
        )

    async def delete_index_pointer(self, agent_id: str, topic_id: str) -> None:
        await self.execute(
            "DELETE FROM memory_index WHERE agent_id = ? AND topic_id = ?",
            (agent_id, topic_id),
        )

    async def count_index_pointers(self, agent_id: str) -> int:
        return await self.fetchval(
            "SELECT COUNT(*) FROM memory_index WHERE agent_id = ?",
            (agent_id,),
            default=0,
        )

    async def get_stale_pointers(self, agent_id: str) -> list[dict]:
        return await self.fetchall(
            "SELECT * FROM memory_index WHERE agent_id = ? AND is_stale = 1",
            (agent_id,),
        )

    # ──────────────────────────────────────────────
```

```python
    # Topic operations
    # ──────────────────────────────────────────────

    async def upsert_topic(
        self,
        agent_id:       str,
        topic_id:       str,
        topic_name:     str,
        file_path:      str,
        fact_count:     int    = 0,
        avg_confidence: float  = 0.5,
        tags:           list   = None,
        file_size_bytes: int   = 0,
    ) -> None:
        tags_json = json.dumps(tags or [])
        await self.execute(
            """
            INSERT INTO topics
              (agent_id, topic_id, topic_name, file_path,
               fact_count, avg_confidence, tags, file_size_bytes,
               last_modified)
            VALUES (?, ?, ?, ?, ?, ?, ?, ?, datetime('now'))
            ON CONFLICT(agent_id, topic_id) DO UPDATE SET
              topic_name      = excluded.topic_name,
              file_path       = excluded.file_path,
              fact_count      = excluded.fact_count,
              avg_confidence  = excluded.avg_confidence,
              tags            = excluded.tags,
              file_size_bytes = excluded.file_size_bytes,
              last_modified   = datetime('now')
            """,
            (
                agent_id, topic_id, topic_name, file_path,
                fact_count, avg_confidence, tags_json, file_size_bytes,
            ),
        )

    async def get_topics(self, agent_id: str) -> list[dict]:
        return await self.fetchall(
            """
            SELECT * FROM topics
            WHERE agent_id = ? AND is_archived = 0
            ORDER BY last_modified DESC
            """,
            (agent_id,),
        )

    async def get_topic(self, agent_id: str, topic_id: str) -> Optional[dict]:
        return await self.fetchone(
            "SELECT * FROM topics WHERE agent_id = ? AND topic_id = ?",
            (agent_id, topic_id),
        )

    # ──────────────────────────────────────────────
    # Fact operations
    # ──────────────────────────────────────────────

    async def insert_fact(
```

```
        self,
        agent_id:          str,
        topic_id:          str,
        fact_id:           str,
        content:           str,
        confidence_level:  str,
        source:            str,
        verification_hint: Optional[str] = None,
        contradicts_ids:   list          = None,
        meta:              dict          = None,
    ) -> None:
        await self.execute(
            """
            INSERT INTO facts
              (agent_id, topic_id, fact_id, content, confidence_level,
               source, verification_hint, contradicts_ids, meta)
            VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?)
            ON CONFLICT(agent_id, topic_id, fact_id) DO UPDATE SET
              content           = excluded.content,
              confidence_level  = excluded.confidence_level,
              source            = excluded.source,
              verification_hint = excluded.verification_hint,
              contradicts_ids   = excluded.contradicts_ids,
              meta              = excluded.meta
            """,
            (
                agent_id, topic_id, fact_id, content, confidence_level,
                source, verification_hint,
                json.dumps(contradicts_ids or []),
                json.dumps(meta or {}),
            ),
        )

    async def get_facts(self, agent_id: str, topic_id: str) -> list[dict]:
        return await self.fetchall(
            """
            SELECT * FROM facts
            WHERE agent_id = ? AND topic_id = ?
            ORDER BY created_at ASC
            """,
            (agent_id, topic_id),
        )

    async def delete_fact(
        self, agent_id: str, topic_id: str, fact_id: str
    ) -> None:
        await self.execute(
            """
            DELETE FROM facts
            WHERE agent_id = ? AND topic_id = ? AND fact_id = ?
            """,
            (agent_id, topic_id, fact_id),
        )

    async def update_fact_confidence(
        self,
        agent_id:         str,
        topic_id:         str,
```

```
        fact_id:          str,
        confidence_level: str,
    ) -> None:
        await self.execute(
            """
            UPDATE facts
            SET confidence_level = ?,
                last_verified    = datetime('now')
            WHERE agent_id = ? AND topic_id = ? AND fact_id = ?
            """,
            (confidence_level, agent_id, topic_id, fact_id),
        )

    async def get_stale_facts(
        self,
        agent_id:      str,
        older_than_days: int = 7,
    ) -> list[dict]:
        return await self.fetchall(
            """
            SELECT * FROM facts
            WHERE agent_id = ?
              AND confidence_level != 'verified'
              AND (
                last_verified IS NULL
                OR julianday('now') - julianday(last_verified) > ?
              )
            ORDER BY created_at ASC
            """,
            (agent_id, older_than_days),
        )

    # ──────────────────────────────────────────────────
    # Session operations
    # ──────────────────────────────────────────────────

    async def create_session(
        self,
        agent_id:   str,
        session_id: str,
        meta:       dict = None,
    ) -> None:
        await self.execute(
            """
            INSERT OR IGNORE INTO sessions(agent_id, session_id, meta)
            VALUES (?, ?, ?)
            """,
            (agent_id, session_id, json.dumps(meta or {})),
        )

    async def end_session(
        self,
        agent_id:        str,
        session_id:      str,
        turn_count:      int  = 0,
        transcript_file: str  = None,
    ) -> None:
        await self.execute(
```

```
            """
            UPDATE sessions
            SET ended_at        = datetime('now'),
                turn_count      = ?,
                transcript_file = ?
            WHERE agent_id = ? AND session_id = ?
            """,
            (turn_count, transcript_file, agent_id, session_id),
        )

    async def count_sessions_since(
        self, agent_id: str, since_iso: str
    ) -> int:
        return await self.fetchval(
            """
            SELECT COUNT(*) FROM sessions
            WHERE agent_id = ? AND started_at > ?
            """,
            (agent_id, since_iso),
            default=0,
        )

    # ──────────────────────────────────────────────────
    # LLM call logging
    # ──────────────────────────────────────────────────

    async def log_llm_call(
        self,
        agent_id:          Optional[str],
        session_id:        Optional[str],
        call_id:           str,
        provider:          str,
        model:             str,
        prompt_tokens:     int,
        completion_tokens: int,
        latency_ms:        int,
        purpose:           str  = "recall",
        status:            str  = "success",
        error_message:     str  = None,
    ) -> None:
        await self.execute(
            """
            INSERT INTO llm_calls
              (agent_id, session_id, call_id, provider, model,
               prompt_tokens, completion_tokens, total_tokens,
               latency_ms, purpose, status, error_message)
            VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?)
            """,
            (
                agent_id, session_id, call_id, provider, model,
                prompt_tokens, completion_tokens,
                prompt_tokens + completion_tokens,
                latency_ms, purpose, status, error_message,
            ),
        )

    async def get_usage_stats(self, agent_id: str) -> dict:
        row = await self.fetchone(
```

```
            """
            SELECT
                COUNT(*)                    AS total_calls,
                SUM(prompt_tokens)          AS total_prompt_tokens,
                SUM(completion_tokens)      AS total_completion_tokens,
                SUM(total_tokens)           AS total_tokens,
                AVG(latency_ms)             AS avg_latency_ms,
                MIN(created_at)             AS first_call,
                MAX(created_at)             AS last_call
            FROM llm_calls
            WHERE agent_id = ?
            """,
            (agent_id,),
        )
        return row or {}

    # ──────────────────────────────────────────────
    # Async context manager
    # ──────────────────────────────────────────────

    async def __aenter__(self) -> "DatabaseManager":
        await self.connect()
        return self

    async def __aexit__(self, *args) -> None:
        await self.disconnect()
```

---

16. Core Memory Manager (Phase 1 Version)

Python

```
# memograph/core/memory_manager.py
"""
Phase 1 MemoryManager — full CRUD with write discipline.
No consolidation daemon yet (Phase 3).
No relevance scoring yet (Phase 5).
"""

from __future__ import annotations

import json
import logging
import uuid
from datetime import datetime
from pathlib import Path
from typing import Optional

import aiofiles
```

```python
from memograph.config import ConfidenceLevel, MemoGraphConfig, get_config
from memograph.db.database import DatabaseManager
from memograph.llm.base import BaseLLMProvider, LLMRequest, Message
from memograph.llm.factory import create_provider
from memograph.models.index import IndexPointer, MemoryIndex
from memograph.models.topic import MemoryFact, TopicFile
from memograph.models.transcript import Session, TranscriptEntry
from memograph.prompts.system_prompts import (
    PromptRole,
    build_contradiction_prompt,
    build_extractor_prompt,
    build_writer_prompt,
    get_prompt,
)

logger = logging.getLogger("memograph.core")


class WriteResult:
    def __init__(
        self,
        success:    bool,
        fact:       Optional[MemoryFact] = None,
        topic:      Optional[TopicFile]  = None,
        skipped:    bool                 = False,
        skip_reason: Optional[str]       = None,
        error:      Optional[str]        = None,
    ):
        self.success     = success
        self.fact        = fact
        self.topic       = topic
        self.skipped     = skipped
        self.skip_reason = skip_reason
        self.error       = error


class MemoryManager:
    """
    Phase 1 core: Full CRUD with write discipline,
    LLM-assisted extraction, contradiction detection,
    and transcript archiving.
    """

    def __init__(
        self,
        config:   Optional[MemoGraphConfig] = None,
        llm:      Optional[BaseLLMProvider] = None,
        db:       Optional[DatabaseManager] = None,
    ):
        self.config    = config or get_config()
        self.base_path = Path(self.config.base_path)
        self.agent_id  = self.config.agent_id

        # File paths
        self.index_md_path   = self.base_path / "MEMORY.md"
        self.topics_path     = self.base_path / "topics"
        self.transcripts_path = self.base_path / "transcripts"
```

```
        for p in (self.topics_path, self.transcripts_path):
            p.mkdir(parents=True, exist_ok=True)

        # Components — injected or created from config
        self._llm: Optional[BaseLLMProvider] = llm
        self._db:  Optional[DatabaseManager] = db

        # In-memory index cache
        self._index: Optional[MemoryIndex] = None

        # Active session
        self._current_session: Optional[Session] = None

    # ──────────────────────────────────────────────────────────────────────
    # LIFECYCLE
    # ──────────────────────────────────────────────────────────────────────

    async def initialize(self) -> None:
        """Connect DB, ensure agent, load index."""
        if not self._db:
            self._db = DatabaseManager(self.config.db_path)
            await self._db.connect()

        if not self._llm:
            self._llm = create_provider(config=self.config)

        await self._db.ensure_agent(self.agent_id)
        await self._load_index()

        logger.info(
            f"MemoryManager initialized — agent={self.agent_id}, "
            f"provider={self.config.llm_provider.value}"
        )

    async def close(self) -> None:
        if self._current_session:
            await self.end_session()
        if self._db:
            await self._db.disconnect()

    async def __aenter__(self) -> "MemoryManager":
        await self.initialize()
        return self

    async def __aexit__(self, *args) -> None:
        await self.close()

    # ──────────────────────────────────────────────────────────────────────
    # SESSION MANAGEMENT
    # ──────────────────────────────────────────────────────────────────────

    async def start_session(
        self,
        session_id: Optional[str] = None,
        meta: dict = None,
    ) -> Session:
        sid = session_id or str(uuid.uuid4())[:12]
```

```
        session = Session(session_id=sid, agent_id=self.agent_id, meta=meta or {})
        await self._db.create_session(self.agent_id, sid, meta)
        self._current_session = session
        logger.debug(f"Session started: {sid}")
        return session

    async def end_session(self, turn_count: int = 0) -> None:
        if not self._current_session:
            return
        await self._db.end_session(
            self.agent_id,
            self._current_session.session_id,
            turn_count=turn_count,
        )
        self._current_session = None

    # ──────────────────────────────────────────────────────────────────────
    # INDEX OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    async def _load_index(self) -> MemoryIndex:
        """Load index from DB into memory cache."""
        rows = await self._db.get_index_pointers(self.agent_id)
        pointers = [
            IndexPointer(
                topic_id=r["topic_id"],
                topic_file_path=r["topic_file_path"],
                summary=r["summary"],
                confidence=r["confidence"],
                pointer_line=r["pointer_line"],
                is_stale=bool(r["is_stale"]),
                verification_source=r["verification_source"],
                last_updated=datetime.fromisoformat(r["last_updated"]),
            )
            for r in rows
        ]
        self._index = MemoryIndex(agent_id=self.agent_id, pointers=pointers)
        return self._index

    async def get_index(self) -> MemoryIndex:
        if not self._index:
            await self._load_index()
        return self._index

    def get_context_injection(self) -> str:
        """
        ALWAYS-LOADED context. Call this on every prompt turn.
        Returns the full MEMORY.md markdown — cheap, always in context.
        """
        if not self._index:
            return "<!-- MemoGraph: Index not yet loaded -->"
        return self._index.get_context_injection()

    async def _save_index_pointer(self, pointer: IndexPointer) -> None:
        """Persist one pointer. Ensures DB and markdown file stay in sync."""
        await self._db.upsert_index_pointer(
            agent_id=self.agent_id,
            topic_id=pointer.topic_id,
```

```
            topic_file_path=pointer.topic_file_path,
            summary=pointer.summary,
            confidence=pointer.confidence,
            pointer_line=pointer.pointer_line or pointer.build_pointer_line(),
            is_stale=pointer.is_stale,
            verification_source=pointer.verification_source,
        )
        self._index.upsert_pointer(pointer)
        await self._write_index_markdown()

    async def _write_index_markdown(self) -> None:
        """Write MEMORY.md from current in-memory index."""
        async with aiofiles.open(self.index_md_path, "w") as f:
            await f.write(self._index.to_markdown())

    # ──────────────────────────────────────────────────────────────────────
    # TOPIC FILE OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    def _topic_path(self, topic_id: str) -> Path:
        return self.topics_path / f"{topic_id}.md"

    def _topic_json_path(self, topic_id: str) -> Path:
        return self.topics_path / f"{topic_id}.json"

    async def _load_topic_file(self, topic_id: str) -> Optional[TopicFile]:
        """Load a topic from its JSON file."""
        json_path = self._topic_json_path(topic_id)
        if not json_path.exists():
            return None
        async with aiofiles.open(json_path) as f:
            data = json.loads(await f.read())
        facts = [MemoryFact(**fact) for fact in data.get("facts", [])]
        return TopicFile(
            topic_id=data["topic_id"],
            topic_name=data["topic_name"],
            agent_id=data.get("agent_id", self.agent_id),
            facts=facts,
            tags=data.get("tags", []),
            file_path=str(json_path.relative_to(self.base_path)),
        )

    async def _save_topic_file(self, topic: TopicFile) -> Path:
        """
        STRICT WRITE DISCIPLINE:
        1. Write JSON (machine-readable)
        2. Write Markdown (human/LLM-readable)
        3. Update DB metadata
        NEVER updates the index — caller does that after this returns.
        """
        json_path = self._topic_json_path(topic.topic_id)
        md_path   = self._topic_path(topic.topic_id)

        # Serialize facts to JSON
        payload = {
            "topic_id":     topic.topic_id,
            "topic_name":   topic.topic_name,
            "agent_id":     topic.agent_id,
```

```
            "tags":          topic.tags,
            "facts":         [f.model_dump(mode="json") for f in topic.facts],
            "last_modified": datetime.now().isoformat(),
        }

        # Step 1: Write JSON
        async with aiofiles.open(json_path, "w") as f:
            await f.write(json.dumps(payload, indent=2, default=str))

        # Step 2: Write Markdown
        async with aiofiles.open(md_path, "w") as f:
            await f.write(topic.to_markdown())

        # Step 3: Update DB metadata
        await self._db.upsert_topic(
            agent_id=self.agent_id,
            topic_id=topic.topic_id,
            topic_name=topic.topic_name,
            file_path=str(json_path.relative_to(self.base_path)),
            fact_count=len(topic.facts),
            avg_confidence=topic.avg_confidence,
            tags=topic.tags,
            file_size_bytes=json_path.stat().st_size,
        )

        # Step 4: Sync individual facts to DB
        for fact in topic.facts:
            await self._db.insert_fact(
                agent_id=self.agent_id,
                topic_id=topic.topic_id,
                fact_id=fact.fact_id,
                content=fact.content,
                confidence_level=fact.confidence.value,
                source=fact.source,
                verification_hint=fact.verification_hint,
                contradicts_ids=fact.contradicts_ids,
                meta=fact.meta,
            )

        return json_path

    # ──────────────────────────────────────────────────────────────────────
    # CORE CRUD API
    # ──────────────────────────────────────────────────────────────────────

    async def remember(
        self,
        topic_id:          str,
        content:           str,
        source:            str,
        topic_name:        Optional[str]           = None,
        confidence:        ConfidenceLevel          = ConfidenceLevel.OBSERVED,
        tags:              Optional[list[str]]      = None,
        verification_hint: Optional[str]            = None,
        check_contradictions: bool                  = True,
    ) -> WriteResult:
        """
        Store a memory fact.
```

```
        STRICT WRITE ORDER:
          1. Load or create topic
          2. Check for contradictions (if enabled)
          3. Create fact
          4. Write topic files to disk  ← Must succeed
          5. Update index pointer       ← Only after step 4
          6. Log to DB

        Args:
            topic_id:   Snake_case topic identifier
            content:    The fact to remember (≤1000 chars)
            source:     Where this came from
            topic_name: Human-readable name (defaults to topic_id)
            confidence: Initial confidence level
            tags:       List of string tags
            verification_hint: How to verify this fact later
            check_contradictions: Use LLM to detect contradictions first

        Returns:
            WriteResult with success flag and stored fact
        """
        await self.get_index()  # Ensure index is loaded

        # Load or create topic
        topic = await self._load_topic_file(topic_id)
        if topic is None:
            topic = TopicFile(
                topic_id=topic_id,
                topic_name=topic_name or topic_id.replace("_", " ").title(),
                agent_id=self.agent_id,
                tags=tags or [],
            )

        # Check for contradictions using LLM if requested
        if check_contradictions and topic.facts and self._llm:
            contradiction = await self._check_contradiction(content, topic)
            if contradiction and contradiction.get("has_contradiction"):
                logger.warning(
                    f"Contradiction detected in {topic_id}: "
                    f"{contradiction.get('conflict_description')}"
                )
                # Flag contradicting facts
                rec = contradiction.get("recommendation", "keep_both_flagged")
                if rec == "keep_existing":
                    return WriteResult(
                        success=False,
                        skipped=True,
                        skip_reason=f"Contradiction:
{contradiction.get('conflict_description')}",
                    )

        # Create the fact
        fact = MemoryFact(
            content=content,
            confidence=confidence,
            source=source,
            verification_hint=verification_hint,
```

```
            created_at=datetime.now(),
        )

        topic.facts.append(fact)
        topic.last_modified = datetime.now()
        if tags:
            topic.tags = list(set(topic.tags + tags))

        try:
            # STEP 4: Write topic files (must succeed before index update)
            await self._save_topic_file(topic)

            # STEP 5: Update index pointer (only after topic write succeeds)
            pointer = IndexPointer(
                topic_id=topic.topic_id,
                topic_file_path=str(
                    self._topic_json_path(topic_id)
                    .relative_to(self.base_path)
                ),
                summary=topic.to_summary(),
                confidence=topic.avg_confidence,
                last_updated=datetime.now(),
            )
            pointer.pointer_line = pointer.build_pointer_line()
            await self._save_index_pointer(pointer)

            # Log the LLM call if applicable
            if self.config.debug_prompts:
                logger.debug(
                    f"Stored fact {fact.fact_id} in topic {topic_id}"
                )

            return WriteResult(success=True, fact=fact, topic=topic)

        except Exception as e:
            logger.error(f"Failed to write topic {topic_id}: {e}", exc_info=True)
            # Rollback: remove fact from in-memory topic
            topic.facts = [f for f in topic.facts if f.fact_id != fact.fact_id]
            return WriteResult(success=False, error=str(e))

    async def recall(
        self,
        query:    str,
        top_k:    int  = 3,
        verify:   bool = False,
    ) -> list[TopicFile]:
        """
        Bandwidth-aware recall.
        Phase 1: keyword matching against index.
        Phase 5 will add embedding-based semantic scoring.

        Args:
            query:  What you're looking for
            top_k:  Maximum number of topic files to load
            verify: Mark stale facts (expensive — skip in hot paths)

        Returns:
            List of relevant TopicFile objects, sorted by relevance
```

```
        """
        index = await self.get_index()
        if not index.pointers:
            return []

        # Phase 1: Simple keyword scoring
        scored = self._keyword_score(query, index.pointers)
        top_pointers = scored[:top_k]

        topics: list[TopicFile] = []
        for pointer in top_pointers:
            # Update access stats
            pointer.access_count += 1
            pointer.last_accessed = datetime.now()
            await self._db.execute(
                """
                UPDATE memory_index
                SET access_count = access_count + 1,
                    last_accessed = datetime('now')
                WHERE agent_id = ? AND topic_id = ?
                """,
                (self.agent_id, pointer.topic_id),
            )

            topic = await self._load_topic_file(pointer.topic_id)
            if topic:
                if verify:
                    topic = self._mark_stale_facts(topic)
                topics.append(topic)

        return topics

    async def forget(
        self,
        topic_id: str,
        fact_id:  Optional[str] = None,
    ) -> bool:
        """
        Targeted forgetting.
        If fact_id provided: remove one fact from the topic.
        Otherwise: remove the entire topic and its index pointer.

        Returns True if something was actually deleted.
        """
        if fact_id:
            topic = await self._load_topic_file(topic_id)
            if not topic:
                return False

            before = len(topic.facts)
            topic.facts = [f for f in topic.facts if f.fact_id != fact_id]

            if len(topic.facts) == before:
                return False  # Fact not found

            topic.last_modified = datetime.now()

            # Write topic first
```

```
            await self._save_topic_file(topic)

            # Update index pointer
            pointer = self._index.get_pointer(topic_id)
            if pointer:
                pointer.summary    = topic.to_summary()
                pointer.confidence = topic.avg_confidence
                pointer.pointer_line = pointer.build_pointer_line()
                await self._save_index_pointer(pointer)

            # Remove from facts DB
            await self._db.delete_fact(self.agent_id, topic_id, fact_id)
            return True

        else:
            # Remove entire topic
            json_path = self._topic_json_path(topic_id)
            md_path   = self._topic_path(topic_id)
            json_path.unlink(missing_ok=True)
            md_path.unlink(missing_ok=True)

            # Remove from DB
            await self._db.execute(
                "DELETE FROM topics WHERE agent_id = ? AND topic_id = ?",
                (self.agent_id, topic_id),
            )
            await self._db.execute(
                "DELETE FROM facts WHERE agent_id = ? AND topic_id = ?",
                (self.agent_id, topic_id),
            )

            # Remove from index
            await self._db.delete_index_pointer(self.agent_id, topic_id)
            self._index.remove_pointer(topic_id)
            await self._write_index_markdown()

            logger.info(f"Forgot topic: {topic_id}")
            return True

    async def update(
        self,
        topic_id:      str,
        fact_id:       str,
        new_content:   Optional[str]           = None,
        new_confidence: Optional[ConfidenceLevel] = None,
    ) -> bool:
        """
        Update a specific fact.
        Write topic first, then update index.
        """
        topic = await self._load_topic_file(topic_id)
        if not topic:
            return False

        fact = topic.get_fact(fact_id)
        if not fact:
            return False
```

```
        if new_content:
            fact.content = new_content
        if new_confidence:
            fact.confidence    = new_confidence
            fact.last_verified = datetime.now()

        topic.last_modified = datetime.now()

        # Write topic first
        await self._save_topic_file(topic)

        # Update index pointer
        pointer = self._index.get_pointer(topic_id)
        if pointer:
            pointer.confidence   = topic.avg_confidence
            pointer.pointer_line = pointer.build_pointer_line()
            await self._save_index_pointer(pointer)

        # Update confidence in DB
        if new_confidence:
            await self._db.update_fact_confidence(
                self.agent_id, topic_id, fact_id, new_confidence.value
            )

        return True

    # ──────────────────────────────────────────────────────────────────────
    # LLM-ASSISTED OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    async def extract_and_remember(
        self,
        text:    str,
        source:  str = "extraction",
        context: Optional[str] = None,
    ) -> list[WriteResult]:
        """
        Use LLM to extract memorable facts from text
        and automatically store them.
        """
        if not self._llm:
            logger.warning("No LLM configured — skipping extraction")
            return []

        prompt  = build_extractor_prompt(text)
        system  = get_prompt(PromptRole.EXTRACTOR)

        try:
            result = await self._llm.complete_simple(
                prompt=prompt,
                system=system,
                purpose="extraction",
            )

            # Log the call
            await self._log_llm_call(result, purpose="extraction")

            data   = self._parse_json(result)
```

```
            facts  = data.get("extracted_facts", [])
            results = []

            for f in facts:
                wr = await self.remember(
                    topic_id=f.get("topic_id", "auto_extracted"),
                    content=f.get("content", ""),
                    source=source,
                    topic_name=f.get("topic_name"),
                    confidence=ConfidenceLevel(
                        f.get("confidence", "observed")
                    ),
                    tags=f.get("tags", []),
                    verification_hint=f.get("verification_hint"),
                )
                results.append(wr)

            return results

        except Exception as e:
            logger.error(f"Extraction failed: {e}", exc_info=True)
            return []

    async def _check_contradiction(
        self,
        new_content: str,
        topic:       TopicFile,
    ) -> Optional[dict]:
        """Use LLM to check if new_content contradicts existing facts."""
        if not topic.facts or not self._llm:
            return None

        existing = [
            {
                "fact_id":    f.fact_id,
                "content":    f.content,
                "confidence": f.confidence.value,
            }
            for f in topic.facts[-10:]  # Last 10 facts max
        ]

        prompt = build_contradiction_prompt(new_content, existing)
        system = get_prompt(PromptRole.CONTRADICTION_RESOLVER)

        try:
            result = await self._llm.complete_simple(
                prompt=prompt,
                system=system,
                purpose="verification",
            )
            return self._parse_json(result)
        except Exception as e:
            logger.warning(f"Contradiction check failed: {e}")
            return None

    # ──────────────────────────────────────────────────────────────────
    # TRANSCRIPT ARCHIVING
    # ──────────────────────────────────────────────────────────────────
```

```python
    async def archive_turn(
        self,
        role:        str,
        content:     str,
        tool_calls:  list[dict] = None,
        session_id:  Optional[str] = None,
    ) -> None:
        """
        Archive a conversation turn to the transcript store.
        Layer 3: written to .jsonl, never loaded back wholesale.
        """
        sid = (
            session_id
            or (self._current_session.session_id if self._current_session else "unknown")
        )

        entry = TranscriptEntry(
            session_id=sid,
            role=role,
            content=content,
            tool_calls=tool_calls or [],
        )

        transcript_file = self.transcripts_path / f"{sid}.jsonl"
        async with aiofiles.open(transcript_file, "a") as f:
            await f.write(entry.to_jsonl_line() + "\n")

    async def grep_transcripts(
        self,
        pattern:     str,
        session_ids: Optional[list[str]] = None,
        max_results: int = 20,
    ) -> list[dict]:
        """
        GREP ONLY — never loads full transcripts.
        Returns matching lines as parsed dicts.
        """
        import re
        compiled = re.compile(pattern, re.IGNORECASE)
        results:  list[dict] = []

        files = (
            [self.transcripts_path / f"{sid}.jsonl" for sid in session_ids]
            if session_ids
            else sorted(
                self.transcripts_path.glob("*.jsonl"),
                key=lambda f: f.stat().st_mtime,
                reverse=True,
            )
        )

        for filepath in files:
            if len(results) >= max_results:
                break
            if not filepath.exists():
                continue
            async with aiofiles.open(filepath) as f:
```

```
                async for line in f:
                    if compiled.search(line):
                        try:
                            results.append({
                                "file": filepath.name,
                                "match": json.loads(line),
                            })
                        except json.JSONDecodeError:
                            pass
                    if len(results) >= max_results:
                        break

        return results

    # ──────────────────────────────────────────────────────────────────────
    # HELPERS
    # ──────────────────────────────────────────────────────────────────────

    def _keyword_score(
        self,
        query:    str,
        pointers: list[IndexPointer],
    ) -> list[IndexPointer]:
        """
        Phase 1 relevance scoring — keyword overlap.
        Phase 5 replaces this with embedding-based scoring.
        """
        import re
        query_terms = set(re.findall(r"\w+", query.lower()))
        scored: list[tuple[float, IndexPointer]] = []

        for p in pointers:
            text  = f"{p.topic_id} {p.summary}".lower()
            terms = set(re.findall(r"\w+", text))
            overlap = len(query_terms & terms)
            # Boost by confidence; penalize stale
            multiplier = 0.3 if p.is_stale else 1.0
            score = overlap * (0.5 + p.confidence * 0.5) * multiplier
            if score > 0:
                scored.append((score, p))

        scored.sort(key=lambda x: x[0], reverse=True)
        return [p for _, p in scored]

    def _mark_stale_facts(self, topic: TopicFile) -> TopicFile:
        """Mark facts as stale based on age thresholds."""
        from datetime import timedelta
        thresholds = {
            ConfidenceLevel.VERIFIED: 30,
            ConfidenceLevel.OBSERVED: 7,
            ConfidenceLevel.INFERRED: 3,
            ConfidenceLevel.STALE:    0,
        }
        now = datetime.now()
        for fact in topic.facts:
            days_threshold = thresholds.get(fact.confidence, 7)
            ref_date = fact.last_verified or fact.created_at
            if (now - ref_date).days > days_threshold:
```

```
                fact.confidence = ConfidenceLevel.STALE
        return topic

    def _parse_json(self, text: str) -> dict:
        """Parse JSON from LLM response, handling markdown fences."""
        import re
        text = text.strip()
        # Try to extract from markdown code block
        match = re.search(r"```(?:json)?\n?(.*?)\n?```", text, re.DOTALL)
        if match:
            text = match.group(1).strip()
        try:
            return json.loads(text)
        except json.JSONDecodeError:
            logger.warning(f"Failed to parse JSON from LLM response: {text[:100]}")
            return {}

    async def _log_llm_call(self, response, purpose: str = "recall") -> None:
        """Log an LLM call to the database."""
        if not self._db:
            return
        try:
            await self._db.log_llm_call(
                agent_id=self.agent_id,
                session_id=(
                    self._current_session.session_id
                    if self._current_session else None
                ),
                call_id=response.call_id if hasattr(response, "call_id") else
str(uuid.uuid4())[:8],
                provider=response.provider if hasattr(response, "provider") else "unknown",
                model=response.model if hasattr(response, "model") else "unknown",
                prompt_tokens=response.prompt_tokens if hasattr(response, "prompt_tokens")
else 0,
                completion_tokens=response.completion_tokens if hasattr(response,
"completion_tokens") else 0,
                latency_ms=response.latency_ms if hasattr(response, "latency_ms") else 0,
                purpose=purpose,
            )
        except Exception as e:
            logger.debug(f"Failed to log LLM call: {e}")

    # ─────────────────────────────────────────────────────────────────────
    # DIAGNOSTICS
    # ─────────────────────────────────────────────────────────────────────

    async def status(self) -> dict:
        """Full system status snapshot."""
        index   = await self.get_index()
        topics  = await self._db.get_topics(self.agent_id)
        usage   = await self._db.get_usage_stats(self.agent_id)
        stale   = await self._db.get_stale_facts(self.agent_id)
        transcripts = list(self.transcripts_path.glob("*.jsonl"))

        return {
            "agent_id":           self.agent_id,
            "provider":           self.config.llm_provider.value,
            "index": {
```

```
                "pointer_count":  len(index.pointers),
                "last_consolidated": str(index.last_consolidated),
                "index_size_bytes": (
                    self.index_md_path.stat().st_size
                    if self.index_md_path.exists() else 0
                ),
            },
            "topics": {
                "total":          len(topics),
                "total_facts":    sum(t["fact_count"] for t in topics),
                "stale_facts":    len(stale),
            },
            "transcripts": {
                "session_files":  len(transcripts),
            },
            "llm_usage":          usage,
        }
```

---

17. Top-Level `__init__.py`

Python

```
# memograph/__init__.py
"""
MemoGraph — Self-Healing 3-Layer Memory System for AI Agents.

Quick start:
    from memograph import MemoGraph

    async with MemoGraph(provider="ollama", model="llama3.1:8b") as mg:
        await mg.remember("project", "Uses FastAPI", source="readme")
        topics = await mg.recall("what framework?")
        context = mg.get_context_injection()  # inject into every prompt
"""

from __future__ import annotations

from pathlib import Path
from typing import Optional

from memograph.config import ConfidenceLevel, LLMProvider, MemoGraphConfig, get_config
from memograph.core.memory_manager import MemoryManager, WriteResult
from memograph.models.index import MemoryIndex
from memograph.models.topic import MemoryFact, TopicFile

__version__ = "0.1.0"
__all__ = [
    "MemoGraph",
    "MemoryManager",
    "MemoGraphConfig",
    "LLMProvider",
```

```
    "ConfidenceLevel",
    "TopicFile",
    "MemoryFact",
    "WriteResult",
    "__version__",
]


class MemoGraph:
    """
    High-level API facade for MemoGraph.

    Supports:
    - Ollama (local, no key needed): provider="ollama"
    - Anthropic Claude:              provider="anthropic", api_key="sk-ant-..."
    - OpenAI:                        provider="openai",    api_key="sk-..."
    - Groq:                          provider="groq",      api_key="gsk-..."
    - Google Gemini:                 provider="gemini",    api_key="..."
    - Custom/LM Studio:              provider="custom",    base_url="http://..."
    - Any shorthand:                 provider="ollama:phi3:mini"
    """

    def __init__(
        self,
        base_path:   str | Path          = ".memograph",
        agent_id:    str                 = "default",
        provider:    str | LLMProvider   = LLMProvider.OLLAMA,
        model:       Optional[str]       = None,
        api_key:     Optional[str]       = None,
        base_url:    Optional[str]       = None,
        config:      Optional[MemoGraphConfig] = None,
        **kwargs,
    ):
        # Build config from convenience args if not provided
        if config is None:
            env_overrides: dict = {
                "base_path": str(base_path),
                "agent_id":  agent_id,
            }

            # Parse "provider:model" shorthand
            if isinstance(provider, str) and ":" in provider:
                parts    = provider.split(":", 1)
                provider = parts[0]
                model    = model or parts[1]

            env_overrides["llm_provider"] = (
                provider.value if isinstance(provider, LLMProvider)
                else provider
            )

            config = MemoGraphConfig(**{**env_overrides, **kwargs})

        self.config   = config
        self._manager: Optional[MemoryManager] = None

        # Store BYOK/model overrides for provider creation
        self._provider_override = str(provider) if provider else None
```

```
        self._model_override    = model
        self._api_key_override  = api_key
        self._base_url_override = base_url

    async def _get_manager(self) -> MemoryManager:
        if self._manager is None:
            from memograph.llm.factory import create_provider as _create

            llm = _create(
                provider=self._provider_override,
                model=self._model_override,
                config=self.config,
                **({"api_key": self._api_key_override}
                   if self._api_key_override else {}),
                **({"base_url": self._base_url_override}
                   if self._base_url_override else {}),
            )

            from memograph.db.database import DatabaseManager
            db = DatabaseManager(self.config.db_path)

            self._manager = MemoryManager(
                config=self.config,
                llm=llm,
                db=db,
            )
            await self._manager.initialize()

        return self._manager

    # ── Convenience API ──────────────────────────────────────────────

    async def remember(
        self,
        topic_id:   str,
        content:    str,
        source:     str = "user",
        **kwargs,
    ) -> WriteResult:
        mgr = await self._get_manager()
        return await mgr.remember(topic_id, content, source, **kwargs)

    async def recall(
        self, query: str, top_k: int = 3
    ) -> list[TopicFile]:
        mgr = await self._get_manager()
        return await mgr.recall(query, top_k)

    async def forget(
        self, topic_id: str, fact_id: Optional[str] = None
    ) -> bool:
        mgr = await self._get_manager()
        return await mgr.forget(topic_id, fact_id)

    async def update(
        self,
        topic_id:       str,
        fact_id:        str,
```

```
        new_content:    Optional[str]           = None,
        new_confidence: Optional[ConfidenceLevel] = None,
    ) -> bool:
        mgr = await self._get_manager()
        return await mgr.update(topic_id, fact_id, new_content, new_confidence)

    async def extract_and_remember(
        self, text: str, source: str = "extraction"
    ) -> list[WriteResult]:
        mgr = await self._get_manager()
        return await mgr.extract_and_remember(text, source)

    def get_context_injection(self) -> str:
        """
        Returns the always-loaded index for prompt injection.
        Call this every turn — it's cheap.
        """
        if self._manager:
            return self._manager.get_context_injection()
        return "<!-- MemoGraph: Not initialized -->"

    async def grep_transcripts(
        self, pattern: str, max_results: int = 20
    ) -> list[dict]:
        mgr = await self._get_manager()
        return await mgr.grep_transcripts(pattern, max_results=max_results)

    async def status(self) -> dict:
        mgr = await self._get_manager()
        return await mgr.status()

    async def start_session(self, session_id: Optional[str] = None) -> str:
        mgr     = await self._get_manager()
        session = await mgr.start_session(session_id)
        return session.session_id

    async def archive_turn(
        self, role: str, content: str, tool_calls: list = None
    ) -> None:
        mgr = await self._get_manager()
        await mgr.archive_turn(role, content, tool_calls)

    # ── Lifecycle ──────────────────────────────────────────────────────────

    async def close(self) -> None:
        if self._manager:
            await self._manager.close()

    async def __aenter__(self) -> "MemoGraph":
        await self._get_manager()
        return self

    async def __aexit__(self, *args) -> None:
        await self.close()
```

---

18. Tests

Python

```
# tests/conftest.py

import asyncio
import pytest
from pathlib import Path

@pytest.fixture(scope="session")
def event_loop():
    loop = asyncio.new_event_loop()
    yield loop
    loop.close()

@pytest.fixture
def tmp_base(tmp_path):
    return tmp_path / "memograph_test"

@pytest.fixture
def test_config(tmp_base):
    from memograph.config import MemoGraphConfig, LLMProvider
    return MemoGraphConfig(
        base_path=str(tmp_base),
        db_path=str(tmp_base / "test.db"),
        agent_id="test_agent",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
    )
```

Python

```
# tests/test_config.py

import pytest
from memograph.config import (
    MemoGraphConfig,
    LLMProvider,
    AnthropicConfig,
    OllamaConfig,
    get_config,
    reset_config,
)


def test_default_config():
    cfg = MemoGraphConfig()
    assert cfg.llm_provider == LLMProvider.OLLAMA
    assert cfg.agent_id == "default"
    assert cfg.auto_consolidate is True
    assert cfg.skeptical_mode is True
```

```python
def test_provider_config_ollama():
    cfg = MemoGraphConfig(llm_provider="ollama")
    assert cfg.llm_provider == LLMProvider.OLLAMA
    active = cfg.get_active_provider_config()
    assert isinstance(active, OllamaConfig)
    assert active.base_url == "http://localhost:11434"


def test_provider_config_anthropic():
    cfg = MemoGraphConfig(
        llm_provider="anthropic",
        anthropic=AnthropicConfig(api_key="sk-ant-test123"),
    )
    active = cfg.get_active_provider_config()
    assert isinstance(active, AnthropicConfig)
    assert active.api_key == "sk-ant-test123"


def test_is_local_flag():
    cfg_ollama = MemoGraphConfig(llm_provider="ollama")
    cfg_openai = MemoGraphConfig(llm_provider="openai")
    assert cfg_ollama.is_local() is True
    assert cfg_openai.is_local() is False


def test_config_singleton():
    reset_config()
    cfg1 = get_config()
    cfg2 = get_config()
    assert cfg1 is cfg2
    reset_config()


def test_config_summary():
    cfg = MemoGraphConfig(llm_provider="ollama", agent_id="mybot")
    summary = cfg.summary()
    assert summary["provider"] == "ollama"
    assert summary["agent_id"] == "mybot"
    assert summary["local"] is True


def test_consolidation_provider_fallback():
    cfg = MemoGraphConfig(llm_provider="openai", consolidation_provider=None)

    assert cfg.get_consolidation_provider() == LLMProvider.OPENAI
```

Python

```python
# tests/test_database.py

import pytest
from memograph.db.database import DatabaseManager
```

```python
@pytest.mark.asyncio
async def test_connect_and_migrate(tmp_path):
    db_path = tmp_path / "test.db"
    async with DatabaseManager(db_path) as db:
        # Schema version should be set
        version = await db.fetchval("SELECT version FROM schema_version LIMIT 1")
        assert version == 1


@pytest.mark.asyncio
async def test_agent_operations(tmp_path):
    async with DatabaseManager(tmp_path / "test.db") as db:
        await db.ensure_agent("agent_01", "Test Agent")
        row = await db.fetchone("SELECT * FROM agents WHERE id = ?", ("agent_01",))
        assert row is not None
        assert row["display_name"] == "Test Agent"

        # Idempotent
        await db.ensure_agent("agent_01", "Test Agent")
        count = await db.fetchval(
            "SELECT COUNT(*) FROM agents WHERE id = ?", ("agent_01",)
        )
        assert count == 1


@pytest.mark.asyncio
async def test_index_operations(tmp_path):
    async with DatabaseManager(tmp_path / "test.db") as db:
        await db.ensure_agent("agent_01")

        await db.upsert_index_pointer(
            agent_id="agent_01",
            topic_id="test_topic",
            topic_file_path="topics/test_topic.json",
            summary="A test topic with 1 fact",
            confidence=0.7,
            pointer_line="[test_topic] A test topic → topics/test_topic.json",
        )

        pointers = await db.get_index_pointers("agent_01")
        assert len(pointers) == 1
        assert pointers[0]["topic_id"] == "test_topic"
        assert pointers[0]["confidence"] == 0.7

        # Upsert updates
        await db.upsert_index_pointer(
            agent_id="agent_01",
            topic_id="test_topic",
            topic_file_path="topics/test_topic.json",
            summary="Updated summary",
            confidence=0.9,
            pointer_line="[test_topic] Updated summary → ...",
        )

        pointers = await db.get_index_pointers("agent_01")
        assert len(pointers) == 1
        assert pointers[0]["confidence"] == 0.9
```

```
        count = await db.count_index_pointers("agent_01")
        assert count == 1


@pytest.mark.asyncio
async def test_fact_operations(tmp_path):
    async with DatabaseManager(tmp_path / "test.db") as db:
        await db.ensure_agent("a1")
        await db.upsert_topic(
            agent_id="a1",
            topic_id="proj",
            topic_name="Project",
            file_path="topics/proj.json",
        )

        await db.insert_fact(
            agent_id="a1",
            topic_id="proj",
            fact_id="fact01",
            content="Uses Python 3.11",
            confidence_level="observed",
            source="readme",
        )

        facts = await db.get_facts("a1", "proj")
        assert len(facts) == 1
        assert facts[0]["content"] == "Uses Python 3.11"

        await db.update_fact_confidence("a1", "proj", "fact01", "verified")
        facts = await db.get_facts("a1", "proj")
        assert facts[0]["confidence_level"] == "verified"

        await db.delete_fact("a1", "proj", "fact01")
        facts = await db.get_facts("a1", "proj")
        assert len(facts) == 0


@pytest.mark.asyncio
async def test_session_operations(tmp_path):
    async with DatabaseManager(tmp_path / "test.db") as db:
        await db.ensure_agent("a1")
        await db.create_session("a1", "sess_001")
        await db.end_session("a1", "sess_001", turn_count=5)

        count = await db.count_sessions_since("a1", "1970-01-01")
        assert count == 1


@pytest.mark.asyncio
async def test_llm_call_logging(tmp_path):
    async with DatabaseManager(tmp_path / "test.db") as db:
        await db.ensure_agent("a1")
        await db.log_llm_call(
            agent_id="a1",
            session_id="sess_001",
            call_id="call_abc",
            provider="ollama",
            model="llama3.1:8b",
```

```
            prompt_tokens=100,
            completion_tokens=50,
            latency_ms=342,
            purpose="recall",
        )

        stats = await db.get_usage_stats("a1")
        assert stats["total_calls"] == 1

        assert stats["total_tokens"] == 150
```

Python

```
# tests/test_models.py

from datetime import datetime
import pytest
from memograph.models.index import IndexPointer, MemoryIndex
from memograph.models.topic import MemoryFact, TopicFile
from memograph.config import ConfidenceLevel


def test_index_pointer_line_length():
    p = IndexPointer(
        topic_id="my_topic",
        topic_file_path="topics/my_topic.json",
        summary="A test topic with important project facts",
        confidence=0.8,
        last_updated=datetime(2025, 1, 15),
    )
    line = p.build_pointer_line()
    assert len(line) <= 150
    assert "my_topic" in line
    assert "0.8" in line


def test_summary_truncated_at_80_chars():
    p = IndexPointer(
        topic_id="t",
        topic_file_path="topics/t.json",
        summary="x" * 100,   # Too long
        confidence=0.5,
    )
    assert len(p.summary) <= 80


def test_memory_index_full():
    idx = MemoryIndex(agent_id="a1")
    idx.MAX_LINES = 3

    for i in range(3):
        idx.pointers.append(
            IndexPointer(
                topic_id=f"t{i}",
                topic_file_path=f"topics/t{i}.json",
                summary=f"Topic {i}",
```

```
                confidence=0.5,
            )
        )
    assert idx.is_full() is True


def test_memory_index_upsert():
    idx = MemoryIndex(agent_id="a1")
    p1  = IndexPointer(
        topic_id="t1",
        topic_file_path="topics/t1.json",
        summary="Original",
        confidence=0.5,
    )
    idx.upsert_pointer(p1)
    assert len(idx.pointers) == 1

    p2 = IndexPointer(
        topic_id="t1",
        topic_file_path="topics/t1.json",
        summary="Updated",
        confidence=0.9,
    )
    idx.upsert_pointer(p2)
    assert len(idx.pointers) == 1
    assert idx.get_pointer("t1").confidence == 0.9


def test_topic_avg_confidence():
    topic = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(content="f1", confidence=ConfidenceLevel.VERIFIED,
                   source="test"),
        MemoryFact(content="f2", confidence=ConfidenceLevel.OBSERVED,
                   source="test"),
        MemoryFact(content="f3", confidence=ConfidenceLevel.STALE,
                   source="test"),
    ]
    avg = topic.avg_confidence
    assert 0.0 < avg < 1.0


def test_topic_to_markdown_contains_facts():
    topic = TopicFile(topic_id="proj", topic_name="Project")
    topic.facts = [
        MemoryFact(
            content="Uses Python 3.11",
            confidence=ConfidenceLevel.VERIFIED,
            source="readme",
        )
    ]
    md = topic.to_markdown()
    assert "Uses Python 3.11" in md
    assert "✅" in md


def test_topic_summary_max_80_chars():
    topic = TopicFile(
```

```
        topic_id="some_long_project_topic",
        topic_name="A Very Long Project Topic Name That Keeps Going",
        tags=["python", "fastapi", "postgres"],
    )
    for _ in range(5):
        topic.facts.append(
            MemoryFact(content="fact", confidence=ConfidenceLevel.OBSERVED,
                       source="test")
        )
    summary = topic.to_summary()

    assert len(summary) <= 80
```

Python

```
# tests/test_memory_manager.py

import pytest
from unittest.mock import AsyncMock, MagicMock
from memograph.core.memory_manager import MemoryManager
from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
from memograph.llm.base import LLMResponse
from memograph.db.database import DatabaseManager


@pytest.fixture
async def manager(tmp_path):
    """Create a MemoryManager with a real SQLite DB but mock LLM."""
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="test_agent",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
    )

    # Mock LLM
    mock_llm = MagicMock()
    mock_llm.complete_simple = AsyncMock(
        return_value='{"has_contradiction": false}'
    )
    mock_llm.provider_name = "mock"

    db = DatabaseManager(config.db_path)
    mgr = MemoryManager(config=config, llm=mock_llm, db=db)
    await mgr.initialize()
    yield mgr
    await mgr.close()


@pytest.mark.asyncio
async def test_remember_basic(manager):
    result = await manager.remember(
        topic_id="project_tech",
        content="The project uses FastAPI for the REST layer",
        source="readme",
```

```
        confidence=ConfidenceLevel.OBSERVED,
    )
    assert result.success is True
    assert result.fact is not None
    assert result.fact.content == "The project uses FastAPI for the REST layer"


@pytest.mark.asyncio
async def test_remember_creates_topic_files(manager, tmp_path):
    await manager.remember(
        topic_id="tech_stack",
        content="PostgreSQL for primary storage",
        source="architecture_doc",
    )
    topics_path = tmp_path / "mg" / "topics"
    assert (topics_path / "tech_stack.json").exists()
    assert (topics_path / "tech_stack.md").exists()


@pytest.mark.asyncio
async def test_remember_updates_index(manager):
    await manager.remember(
        topic_id="user_prefs",
        content="User prefers dark mode",
        source="observation",
    )
    index = await manager.get_index()
    pointer = index.get_pointer("user_prefs")
    assert pointer is not None
    assert "user_prefs" in pointer.topic_id


@pytest.mark.asyncio
async def test_recall_basic(manager):
    await manager.remember(
        topic_id="arch_decisions",
        content="Chose async Python for high concurrency",
        source="design_doc",
    )
    await manager.remember(
        topic_id="user_prefs",
        content="User prefers verbose logging",
        source="user",
    )

    results = await manager.recall("architecture and async")
    assert len(results) >= 1
    topic_ids = [t.topic_id for t in results]
    assert "arch_decisions" in topic_ids


@pytest.mark.asyncio
async def test_forget_fact(manager):
    await manager.remember(
        topic_id="remove_test",
        content="This fact will be deleted",
        source="test",
    )
```

```
    index = await manager.get_index()
    pointer = index.get_pointer("remove_test")
    assert pointer is not None

    topic = await manager._load_topic_file("remove_test")
    fact_id = topic.facts[0].fact_id

    deleted = await manager.forget("remove_test", fact_id)
    assert deleted is True

    topic_after = await manager._load_topic_file("remove_test")
    assert len(topic_after.facts) == 0


@pytest.mark.asyncio
async def test_forget_topic(manager, tmp_path):
    await manager.remember(
        topic_id="delete_me",
        content="Gone forever",
        source="test",
    )
    deleted = await manager.forget("delete_me")
    assert deleted is True

    topic_path = tmp_path / "mg" / "topics" / "delete_me.json"
    assert not topic_path.exists()

    index = await manager.get_index()
    assert index.get_pointer("delete_me") is None


@pytest.mark.asyncio
async def test_update_fact(manager):
    await manager.remember(
        topic_id="mutable_facts",
        content="Old content",
        source="test",
    )
    topic   = await manager._load_topic_file("mutable_facts")
    fact_id = topic.facts[0].fact_id

    updated = await manager.update(
        topic_id="mutable_facts",
        fact_id=fact_id,
        new_content="New updated content",
        new_confidence=ConfidenceLevel.VERIFIED,
    )
    assert updated is True

    topic_after = await manager._load_topic_file("mutable_facts")
    fact_after  = topic_after.get_fact(fact_id)
    assert fact_after.content == "New updated content"
    assert fact_after.confidence == ConfidenceLevel.VERIFIED


@pytest.mark.asyncio
async def test_multiple_facts_same_topic(manager):
```

```
    for i in range(5):
        await manager.remember(
            topic_id="multi_facts",
            content=f"Fact number {i}",
            source="test",
        )

    topic = await manager._load_topic_file("multi_facts")
    assert len(topic.facts) == 5


@pytest.mark.asyncio
async def test_archive_and_grep_transcript(manager):
    await manager.start_session("sess_test_001")
    await manager.archive_turn("user", "How does the auth system work?")
    await manager.archive_turn("assistant", "The auth system uses JWT tokens with RS256.")

    matches = await manager.grep_transcripts("JWT", max_results=10)
    assert len(matches) >= 1
    assert any("JWT" in m["match"].get("content", "") for m in matches)


@pytest.mark.asyncio
async def test_status(manager):
    await manager.remember(
        topic_id="status_test",
        content="Testing the status endpoint",
        source="test",
    )
    s = await manager.status()
    assert s["agent_id"] == "test_agent"
    assert s["index"]["pointer_count"] >= 1
    assert s["topics"]["total"] >= 1


@pytest.mark.asyncio
async def test_get_context_injection(manager):
    await manager.remember(
        topic_id="ctx_test",
        content="This should appear in the context injection",
        source="test",
    )
    ctx = manager.get_context_injection()
    assert "ctx_test" in ctx

    assert "MemoGraph Index" in ctx
```

Python

```
# tests/test_llm_factory.py

import pytest
from memograph.config import LLMProvider, MemoGraphConfig
from memograph.llm.factory import create_provider, _build_provider
```

```python
def test_create_ollama_provider():
    cfg      = MemoGraphConfig(llm_provider="ollama")
    provider = create_provider("ollama", config=cfg)
    assert provider.provider_name == "ollama"


def test_create_provider_shorthand():
    cfg      = MemoGraphConfig(llm_provider="ollama")
    provider = create_provider("ollama:phi3:mini", config=cfg)
    assert provider.provider_name == "ollama"
    # Model should be overridden
    assert provider.config.model == "phi3:mini"


def test_create_custom_provider():
    cfg = MemoGraphConfig(llm_provider="custom")
    provider = create_provider(
        "custom",
        base_url="http://localhost:1234/v1",
        model="local-llama",
        config=cfg,
    )
    assert provider.provider_name == "openai"  # Custom uses OpenAI compat


def test_invalid_provider_raises():
    cfg = MemoGraphConfig()
    with pytest.raises(ValueError, match="Unknown provider"):
        _build_provider(
            provider="nonexistent",   # type: ignore
            model=None,
            cfg=cfg,
        )


def test_anthropic_missing_package(monkeypatch):
    import memograph.llm.providers.anthropic_provider as ap
    monkeypatch.setattr(ap, "_ANTHROPIC_AVAILABLE", False)

    from memograph.config import AnthropicConfig
    with pytest.raises(ImportError, match="anthropic package not installed"):
        from memograph.llm.providers.anthropic_provider import AnthropicProvider

        AnthropicProvider(AnthropicConfig(api_key="test"))
```

---

19. Complete Usage Examples

```
Python


# examples/01_quickstart_ollama.py
"""
```

```
Quickstart: MemoGraph with local Ollama.

Prerequisites:
    ollama serve
    ollama pull llama3.1:8b
"""

import asyncio
from memograph import MemoGraph


async def main():
    async with MemoGraph(
        provider="ollama",
        model="llama3.1:8b",
        agent_id="my_coding_agent",
    ) as mg:

        # Store some memories
        await mg.remember(
            topic_id="project_stack",
            content="Project uses FastAPI + SQLite + Pydantic v2",
            source="architecture_doc",
        )

        await mg.remember(
            topic_id="user_preferences",
            content="User prefers type hints and async/await everywhere",
            source="observed_from_code_review",
        )

        await mg.remember(
            topic_id="project_stack",
            content="Deployed on Railway, not AWS or GCP",
            source="deployment_config",
        )

        # Get always-loaded context (inject into EVERY prompt)
        ctx = mg.get_context_injection()
        print("=== Always-Loaded Index ===")
        print(ctx)

        # Recall relevant topics for a specific query
        print("\n=== Relevant Topics for 'tech stack' ===")
        topics = await mg.recall("tech stack and deployment")
        for topic in topics:
            print(topic.to_markdown())
            print()

        # System status
        status = await mg.status()
        print(f"\n=== Status ===")
        print(f"Topics: {status['topics']['total']}")
        print(f"Facts:  {status['topics']['total_facts']}")
        print(f"Provider: {status['provider']}")


if __name__ == "__main__":
```

```
    asyncio.run(main())
```

Python

```
# examples/02_byok_anthropic.py
"""
Bring Your Own Key — Anthropic Claude.
"""

import asyncio
import os
from memograph import MemoGraph


async def main():
    async with MemoGraph(
        provider="anthropic",
        model="claude-3-haiku-20240307",
        api_key=os.environ["ANTHROPIC_API_KEY"],
        agent_id="claude_agent",
    ) as mg:

        result = await mg.remember(
            topic_id="coding_patterns",
            content="Always use dataclasses or Pydantic for structured data",
            source="code_review_session",
        )
        print(f"Stored: {result.fact.fact_id} — {result.success}")

        # Extract facts from a longer piece of text
        results = await mg.extract_and_remember(
            text="""
            The team decided to use PostgreSQL instead of MongoDB after
            performance testing showed 3x better query speed for our workload.
            Authentication will use OAuth2 with PKCE for security.
            The API must support both REST and GraphQL interfaces.
            """,
            source="architecture_decision_doc",
        )
        print(f"Extracted and stored {len(results)} facts")


if __name__ == "__main__":

    asyncio.run(main())
```

Python

```
# examples/03_lm_studio_local.py
"""
LM Studio or any OpenAI-compatible local endpoint.
No API key required.
"""
```

```python
import asyncio
from memograph import MemoGraph, LLMProvider


async def main():
    async with MemoGraph(
        provider="custom",
        base_url="http://localhost:1234/v1",
        model="lmstudio-community/Meta-Llama-3.1-8B-Instruct-GGUF",
        agent_id="lmstudio_agent",
    ) as mg:

        await mg.remember(
            topic_id="local_setup",
            content="LM Studio running Meta-Llama-3.1-8B locally",
            source="config",
        )
        ctx = mg.get_context_injection()
        print(ctx)


if __name__ == "__main__":

    asyncio.run(main())
```

Python

```python
# examples/04_session_with_transcript.py
"""
Full session: archive turns, then grep transcripts.
"""

import asyncio
from memograph import MemoGraph


async def main():
    async with MemoGraph(provider="ollama", agent_id="session_agent") as mg:
        session_id = await mg.start_session()
        print(f"Session: {session_id}")

        # Simulate a multi-turn conversation
        turns = [
            ("user",      "How should I structure the authentication module?"),
            ("assistant", "Use JWT with RS256. Store refresh tokens in Redis."),
            ("user",      "What about rate limiting?"),
            ("assistant", "Use a sliding window with Redis. Limit to 100 req/min."),
        ]

        for role, content in turns:
            await mg.archive_turn(role, content)

        # Grep transcripts (never loads full transcript)
        matches = await mg.grep_transcripts("Redis")
        print(f"\nFound {len(matches)} mentions of Redis in transcripts:")
        for m in matches:
```

```
            print(f"  [{m['match']['role']}]: {m['match']['content'][:80]}...")

        # Store a durable memory from this session
        await mg.remember(
            topic_id="auth_decisions",
            content="JWT with RS256 + Redis for refresh tokens and rate limiting",
            source=f"session/{session_id}",
        )


if __name__ == "__main__":

    asyncio.run(main())
```

---

20. Run It Now

Bash

```
# Install
git clone https://github.com/yourname/memograph
cd memograph
pip install -e ".[dev]"

# Copy and configure env
cp .env.example .env
# Edit .env — set MEMOGRAPH_LLM_PROVIDER=ollama (or your provider)

# Make sure Ollama is running (if using Ollama)
ollama serve &
ollama pull llama3.1:8b

# Run tests
pytest tests/ -v --cov=memograph

# Run quickstart
python examples/01_quickstart_ollama.py

# Check status
python -c "
import asyncio
from memograph import MemoGraph

async def main():
    async with MemoGraph() as mg:
        print(await mg.status())

asyncio.run(main())
"
```

📊 Phase 1 Completion Checklist

Component	Status
`pyproject.toml` with all optional deps	✅
`.env.example` with every config option	✅
Full SQLite schema (7 tables, WAL mode)	✅
Pydantic config with BYOK for all providers	✅
Abstract `BaseLLMProvider` interface	✅
Ollama provider (local, no key)	✅
Anthropic provider	✅
OpenAI provider (+ LM Studio / vLLM compat)	✅
Groq provider	✅
Gemini provider	✅

`create_provider()` factory with shorthand	✅
All 6 system prompts (writer/reader/consolidator/verifier/extractor/detector)	✅
`IndexPointer` + `MemoryIndex` Pydantic models	✅
`TopicFile` + `MemoryFact` Pydantic models	✅
`TranscriptEntry` + `Session` models	✅
`DatabaseManager` (async SQLite, auto-migrate)	✅
`MemoryManager` with strict write discipline	✅
Full CRUD: `remember`, `recall`, `forget`, `update`	✅
LLM-assisted extraction + contradiction detection	✅
Layer 3 transcript archiving + grep-only access	✅
`MemoGraph` high-level facade with BYOK	✅
Full test suite (config, DB, models, manager, factory)	✅

✅

Working usage examples (Ollama, Anthropic, LM Studio, Sessions)

🧠 PHASE 2 — COMPLETE MEMORY LAYER ARCHITECTURE

Building on Phase 1's foundation, Phase 2 implements the full 3-layer memory architecture with proper separation, caching, lazy loading, and bandwidth-aware operations.

📋 Phase 2 Scope

Feature	Description
Index Engine	Always-loaded, bandwidth-optimized, auto-compaction when full
Topic Manager	Lazy loading, LRU cache, batch operations, conflict resolution
File Sync	Bidirectional sync between DB and filesystem, atomic writes

Memory Pressure	Smart eviction strategies, pointer pruning, staleness handling
Batch Ops	Bulk remember/forget, transaction support
Versioning	Topic file versions, conflict detection, merge strategies
Monitoring	Memory metrics, cache stats, performance tracking

New Project Structure (Phase 2 Additions)

```
text
```

```
memograph/
├── core/
│   ├── memory_manager.py          # Phase 1 (enhanced in Phase 2)
│   ├── index_engine.py            # NEW — Index management & compaction
│   ├── topic_manager.py           # NEW — Topic file lifecycle
│   ├── file_sync.py               # NEW — Filesystem ↔ DB sync
│   └── cache.py                   # NEW — LRU cache for topics
│
├── strategies/
│   ├── __init__.py
│   ├── eviction.py                # NEW — Pointer eviction strategies
│   ├── compaction.py              # NEW — Index compaction logic
│   └── relevance.py               # NEW — Enhanced relevance scoring
│
├── monitoring/
│   ├── __init__.py
│   └── metrics.py                 # NEW — Performance & memory metrics
│
└── utils/
    ├── __init__.py
    ├── atomic.py                  # NEW — Atomic file operations
    └── validation.py              # NEW — Data validation helpers
```

---

1. Index Engine — Always-Loaded, Auto-Compacting

Python

```python
# memograph/core/index_engine.py
"""
Index Engine — manages the always-loaded MEMORY.md layer.

Design principles:
1. Index stays under 200 lines / 25KB at all times
2. Pointers are ranked by relevance × confidence × recency
3. When full, lowest-value pointers are evicted (with warning)
4. Index is the ONLY thing loaded on every prompt turn
5. Bidirectional sync: DB ↔ Markdown file
"""

from __future__ import annotations

import logging
from datetime import datetime
from pathlib import Path
from typing import Optional

import aiofiles

from memograph.config import MemoGraphConfig
from memograph.db.database import DatabaseManager
from memograph.models.index import IndexPointer, MemoryIndex
from memograph.strategies.eviction import EvictionStrategy, LRUEvictionStrategy
from memograph.strategies.compaction import compact_index
from memograph.utils.atomic import atomic_write

logger = logging.getLogger("memograph.index")


class IndexStats:
    """Runtime statistics for the index."""

    def __init__(self):
        self.load_count          = 0
        self.pointer_adds        = 0
        self.pointer_updates     = 0
        self.pointer_removes     = 0
        self.compactions         = 0
        self.evictions           = 0
        self.last_compaction     = None
        self.last_save           = None


class IndexEngine:
```

```
    """
    Manages the always-loaded memory index (Layer 1).

    Responsibilities:
    - Load index from DB on startup
    - Keep index under size limits (200 lines, 25KB)
    - Sync index to MEMORY.md (human-readable)
    - Sync index to DB (machine-queryable)
    - Evict low-value pointers when full
    - Compact index periodically
    - Track access patterns for smart eviction
    """

    def __init__(
        self,
        config:            MemoGraphConfig,
        db:                DatabaseManager,
        eviction_strategy: Optional[EvictionStrategy] = None,
    ):
        self.config   = config
        self.db       = db
        self.agent_id = config.agent_id

        # File paths
        self.base_path      = Path(config.base_path)
        self.index_md_path  = self.base_path / "MEMORY.md"
        self.index_bak_path = self.base_path / "MEMORY.md.bak"

        # In-memory index (single source of truth at runtime)
        self._index: Optional[MemoryIndex] = None

        # Eviction strategy
        self._eviction = eviction_strategy or LRUEvictionStrategy()

        # Stats
        self.stats = IndexStats()

    # ──────────────────────────────────────────────────────────────────
    # LIFECYCLE
    # ──────────────────────────────────────────────────────────────────

    async def initialize(self) -> MemoryIndex:
        """Load index from DB and validate."""
        self._index = await self._load_from_db()
        self.stats.load_count += 1
        logger.info(
            f"Index loaded: {len(self._index.pointers)} pointers, "
            f"agent={self.agent_id}"
        )
        # Ensure filesystem is in sync
        await self._sync_to_markdown()
        return self._index

    async def get_index(self) -> MemoryIndex:
        """Get the current in-memory index (always fast, no I/O)."""
        if self._index is None:
            await self.initialize()
        return self._index
```

```python
    async def refresh(self) -> MemoryIndex:
        """Force reload from DB (use sparingly — expensive)."""
        self._index = await self._load_from_db()
        self.stats.load_count += 1
        return self._index

    # ─────────────────────────────────────────────────────────────
    # INDEX OPERATIONS
    # ─────────────────────────────────────────────────────────────

    async def add_pointer(
        self,
        topic_id:           str,
        topic_file_path:    str,
        summary:            str,
        confidence:         float,
        verification_source: Optional[str] = None,
    ) -> IndexPointer:
        """
        Add a new pointer to the index.
        If index is full, evicts the lowest-value pointer first.

        Returns the added pointer.
        """
        index = await self.get_index()

        # Check if pointer already exists (this is an update, not an add)
        existing = index.get_pointer(topic_id)
        if existing:
            return await self.update_pointer(
                topic_id=topic_id,
                summary=summary,
                confidence=confidence,
                verification_source=verification_source,
            )

        # Create pointer
        pointer = IndexPointer(
            topic_id=topic_id,
            topic_file_path=topic_file_path,
            summary=summary[:80],  # Enforce 80-char limit
            confidence=confidence,
            verification_source=verification_source,
            last_updated=datetime.now(),
        )
        pointer.pointer_line = pointer.build_pointer_line()

        # Check if index is full — evict if needed
        if index.is_full():
            logger.warning(
                f"Index full ({len(index.pointers)} pointers) — "
                f"evicting lowest-value pointer"
            )
            await self._evict_one()

        # Add to in-memory index
        index.pointers.append(pointer)
```

```
        self.stats.pointer_adds += 1

        # Persist to DB and filesystem
        await self._persist_pointer(pointer)
        await self._sync_to_markdown()

        logger.debug(f"Added pointer: {topic_id} (conf={confidence:.2f})")
        return pointer

    async def update_pointer(
        self,
        topic_id:            str,
        summary:             Optional[str]   = None,
        confidence:          Optional[float] = None,
        is_stale:            Optional[bool]  = None,
        verification_source: Optional[str]   = None,
        increment_access:    bool            = False,
    ) -> Optional[IndexPointer]:
        """
        Update an existing pointer.
        Returns None if pointer doesn't exist.
        """
        index   = await self.get_index()
        pointer = index.get_pointer(topic_id)

        if not pointer:
            logger.warning(f"Cannot update non-existent pointer: {topic_id}")
            return None

        # Apply updates
        if summary is not None:
            pointer.summary = summary[:80]
        if confidence is not None:
            pointer.confidence = confidence
        if is_stale is not None:
            pointer.is_stale = is_stale
        if verification_source is not None:
            pointer.verification_source = verification_source

        pointer.last_updated = datetime.now()

        if increment_access:
            pointer.access_count += 1
            pointer.last_accessed = datetime.now()

        # Rebuild pointer line
        pointer.pointer_line = pointer.build_pointer_line()

        self.stats.pointer_updates += 1

        # Persist
        await self._persist_pointer(pointer)
        await self._sync_to_markdown()

        return pointer

    async def remove_pointer(self, topic_id: str) -> bool:
        """
```

```
        Remove a pointer from the index.
        Returns True if pointer was found and removed.
        """
        index = await self.get_index()

        if not index.remove_pointer(topic_id):
            return False

        self.stats.pointer_removes += 1

        # Persist removal
        await self.db.delete_index_pointer(self.agent_id, topic_id)
        await self._sync_to_markdown()

        logger.debug(f"Removed pointer: {topic_id}")
        return True

    async def mark_accessed(self, topic_id: str) -> None:
        """Mark a pointer as recently accessed (for LRU eviction)."""
        await self.update_pointer(topic_id, increment_access=True)

    async def mark_stale(self, topic_id: str) -> None:
        """Mark a pointer as stale (needs re-verification)."""
        await self.update_pointer(topic_id, is_stale=True)

    # ──────────────────────────────────────────────────────────────────
    # COMPACTION & EVICTION
    # ──────────────────────────────────────────────────────────────────

    async def compact(self) -> dict:
        """
        Run index compaction:
        1. Remove pointers to non-existent topic files
        2. Remove duplicate pointers
        3. Sort by confidence × recency
        4. Enforce size limits

        Returns compaction report.
        """
        index = await self.get_index()
        before_count = len(index.pointers)

        # Run compaction strategy
        result = await compact_index(
            index=index,
            topics_path=self.base_path / "topics",
            max_pointers=self.config.limits.max_index_lines,
            max_bytes=self.config.limits.max_index_bytes,
        )

        self._index = result.compacted_index
        self.stats.compactions += 1
        self.stats.last_compaction = datetime.now()

        # Persist compacted index
        await self._sync_all()

        logger.info(
```

```
            f"Compaction complete: "
            f"{before_count} → {len(self._index.pointers)} pointers, "
            f"removed {result.removed_count} stale/orphaned"
        )

        return {
            "before_count":    before_count,
            "after_count":     len(self._index.pointers),
            "removed_stale":   result.removed_stale,
            "removed_orphans": result.removed_orphans,
            "removed_duplicates": result.removed_duplicates,
        }

    async def _evict_one(self) -> Optional[str]:
        """
        Evict the lowest-value pointer according to eviction strategy.
        Returns the evicted topic_id, or None if index is empty.
        """
        index = await self.get_index()

        if not index.pointers:
            return None

        # Ask eviction strategy which pointer to remove
        victim = self._eviction.select_victim(index.pointers)

        if not victim:
            logger.warning("Eviction strategy returned no victim")
            return None

        logger.warning(
            f"Evicting pointer: {victim.topic_id} "
            f"(conf={victim.confidence:.2f}, "
            f"accessed={victim.access_count}x)"
        )

        await self.remove_pointer(victim.topic_id)
        self.stats.evictions += 1

        return victim.topic_id

    async def auto_compact_if_needed(self) -> bool:
        """
        Check if compaction is needed and run if so.
        Criteria: index > 90% full OR has stale/orphaned pointers.

        Returns True if compaction was run.
        """
        index = await self.get_index()

        # Check size pressure
        usage_ratio = len(index.pointers) / self.config.limits.max_index_lines
        byte_usage  = len(index.to_markdown().encode())
        byte_ratio  = byte_usage / self.config.limits.max_index_bytes

        # Check for orphaned pointers
        stale_pointers = await self.db.get_stale_pointers(self.agent_id)
```

```
        should_compact = (
            usage_ratio > 0.9
            or byte_ratio > 0.9
            or len(stale_pointers) > 5
        )

        if should_compact:
            logger.info("Auto-compaction triggered")
            await self.compact()
            return True

        return False

    # ──────────────────────────────────────────────────────────────────────
    # PERSISTENCE
    # ──────────────────────────────────────────────────────────────────────

    async def _load_from_db(self) -> MemoryIndex:
        """Load index from database."""
        rows = await self.db.get_index_pointers(self.agent_id)

        pointers = [
            IndexPointer(
                topic_id=r["topic_id"],
                topic_file_path=r["topic_file_path"],
                summary=r["summary"],
                confidence=r["confidence"],
                pointer_line=r["pointer_line"],
                is_stale=bool(r["is_stale"]),
                verification_source=r["verification_source"],
                last_updated=datetime.fromisoformat(r["last_updated"]),
                last_accessed=(
                    datetime.fromisoformat(r["last_accessed"])
                    if r["last_accessed"] else None
                ),
                access_count=r["access_count"],
            )
            for r in rows
        ]

        return MemoryIndex(
            agent_id=self.agent_id,
            pointers=pointers,
        )

    async def _persist_pointer(self, pointer: IndexPointer) -> None:
        """Persist a single pointer to DB."""
        await self.db.upsert_index_pointer(
            agent_id=self.agent_id,
            topic_id=pointer.topic_id,
            topic_file_path=pointer.topic_file_path,
            summary=pointer.summary,
            confidence=pointer.confidence,
            pointer_line=pointer.pointer_line,
            is_stale=pointer.is_stale,
            verification_source=pointer.verification_source,
        )
```

```python
    async def _sync_to_markdown(self) -> None:
        """
        Write the current in-memory index to MEMORY.md.
        Uses atomic write to prevent corruption.
        """
        if not self._index:
            return

        markdown = self._index.to_markdown()

        # Backup existing file first
        if self.index_md_path.exists():
            import shutil
            shutil.copy2(self.index_md_path, self.index_bak_path)

        # Atomic write
        await atomic_write(self.index_md_path, markdown)
        self.stats.last_save = datetime.now()

    async def _sync_all(self) -> None:
        """Full sync: DB + filesystem."""
        # Sync all pointers to DB
        for pointer in self._index.pointers:
            await self._persist_pointer(pointer)

        # Sync to markdown
        await self._sync_to_markdown()

    # ──────────────────────────────────────────────────────────────────────
    # QUERIES & CONTEXT INJECTION
    # ──────────────────────────────────────────────────────────────────────

    async def get_pointers_by_confidence(
        self, min_confidence: float = 0.0
    ) -> list[IndexPointer]:
        """Get pointers above a confidence threshold, sorted descending."""
        index = await self.get_index()
        return [
            p for p in index.sorted_by_confidence()
            if p.confidence >= min_confidence
        ]

    async def get_stale_pointers(self) -> list[IndexPointer]:
        """Get all pointers marked as stale."""
        index = await self.get_index()
        return [p for p in index.pointers if p.is_stale]

    def get_context_injection(self) -> str:
        """
        The ONLY thing injected into every prompt turn.
        Fast — no I/O, pure in-memory operation.
        """
        if not self._index:
            return "<!-- MemoGraph: Index not loaded -->"
        return self._index.to_markdown()

    async def search_pointers(self, query: str) -> list[IndexPointer]:
        """
```

```
        Simple keyword search over pointer summaries.
        Phase 5 replaces this with embedding-based search.
        """
        index = await self.get_index()
        import re
        query_terms = set(re.findall(r"\w+", query.lower()))

        scored: list[tuple[float, IndexPointer]] = []
        for p in index.pointers:
            text  = f"{p.topic_id} {p.summary}".lower()
            terms = set(re.findall(r"\w+", text))
            overlap = len(query_terms & terms)

            if overlap > 0:
                # Boost by confidence, penalize stale
                multiplier = 0.3 if p.is_stale else 1.0
                score = overlap * (0.5 + p.confidence * 0.5) * multiplier
                scored.append((score, p))

        scored.sort(key=lambda x: x[0], reverse=True)
        return [p for _, p in scored]

    # ──────────────────────────────────────────────────────────────────────
    # DIAGNOSTICS
    # ──────────────────────────────────────────────────────────────────────

    async def get_metrics(self) -> dict:
        """Index engine runtime metrics."""
        index      = await self.get_index()
        md_size    = (self.index_md_path.stat().st_size
                      if self.index_md_path.exists() else 0)
        usage      = len(index.pointers) / self.config.limits.max_index_lines
        byte_usage = md_size / self.config.limits.max_index_bytes

        return {
            "pointer_count":      len(index.pointers),
            "max_pointers":       self.config.limits.max_index_lines,
            "usage_ratio":        usage,
            "byte_usage_ratio":   byte_usage,
            "markdown_size_kb":   md_size / 1024,
            "stale_count":        len([p for p in index.pointers if p.is_stale]),
            "avg_confidence":     (
                sum(p.confidence for p in index.pointers) / len(index.pointers)
                if index.pointers else 0.0
            ),
            "stats": {
                "loads":          self.stats.load_count,
                "adds":           self.stats.pointer_adds,
                "updates":        self.stats.pointer_updates,
                "removes":        self.stats.pointer_removes,
                "compactions":    self.stats.compactions,
                "evictions":      self.stats.evictions,
                "last_compaction": str(self.stats.last_compaction),
                "last_save":      str(self.stats.last_save),
            },
        }
```

---

2. Topic Manager — Lazy Loading with LRU Cache

Python

```python
# memograph/core/topic_manager.py
"""
Topic Manager — handles Layer 2 (topic files).

Design principles:
1. Topic files are NEVER all loaded at once
2. Only load topics when index pointer is relevant to query
3. LRU cache keeps recently-used topics in memory
4. All writes are atomic (JSON + Markdown)
5. Conflict detection on concurrent writes
6. Batch operations for performance
"""

from __future__ import annotations

import hashlib
import json
import logging
from datetime import datetime
from pathlib import Path
from typing import Optional

import aiofiles

from memograph.config import ConfidenceLevel, MemoGraphConfig
from memograph.core.cache import LRUCache
from memograph.db.database import DatabaseManager
from memograph.models.topic import MemoryFact, TopicFile
from memograph.utils.atomic import atomic_write
from memograph.utils.validation import validate_topic_id

logger = logging.getLogger("memograph.topics")


class TopicStats:
    def __init__(self):
        self.loads          = 0
        self.saves          = 0
        self.cache_hits     = 0
        self.cache_misses   = 0
        self.conflicts      = 0
        self.batch_ops      = 0


class TopicManager:
```

```
    """
    Manages Layer 2: Topic files.

    Responsibilities:
    - Lazy-load topics only when needed
    - Cache recently-used topics (LRU)
    - Atomic writes (JSON + Markdown)
    - Conflict detection (via file hash)
    - Batch operations for bulk remember/forget
    - Topic versioning
    """

    def __init__(
        self,
        config:     MemoGraphConfig,
        db:         DatabaseManager,
        cache_size: int = 50,
    ):
        self.config     = config
        self.db         = db
        self.agent_id   = config.agent_id
        self.base_path  = Path(config.base_path)
        self.topics_path = self.base_path / "topics"
        self.topics_path.mkdir(parents=True, exist_ok=True)

        # LRU cache for topic files
        self._cache = LRUCache[str, TopicFile](capacity=cache_size)

        # File hash cache (for conflict detection)
        self._file_hashes: dict[str, str] = {}

        # Stats
        self.stats = TopicStats()

    # ──────────────────────────────────────────────────────────────────────
    # LOAD / GET
    # ──────────────────────────────────────────────────────────────────────

    async def get_topic(
        self,
        topic_id: str,
        use_cache: bool = True,
    ) -> Optional[TopicFile]:
        """
        Get a topic file. Checks cache first, then loads from disk.

        Args:
            topic_id:  Topic identifier
            use_cache: If False, forces reload from disk

        Returns:
            TopicFile or None if not found
        """
        validate_topic_id(topic_id)

        # Check cache first
        if use_cache:
            cached = self._cache.get(topic_id)
```

```
            if cached:
                self.stats.cache_hits += 1
                logger.debug(f"Topic cache hit: {topic_id}")
                return cached

        self.stats.cache_misses += 1

        # Load from disk
        topic = await self._load_from_disk(topic_id)

        if topic:
            # Store in cache
            self._cache.put(topic_id, topic)
            # Update file hash for conflict detection
            await self._update_file_hash(topic_id)

        return topic

    async def get_topics_batch(
        self,
        topic_ids: list[str],
    ) -> dict[str, Optional[TopicFile]]:
        """Load multiple topics efficiently (batch operation)."""
        results: dict[str, Optional[TopicFile]] = {}

        for tid in topic_ids:
            results[tid] = await self.get_topic(tid)

        return results

    async def list_topics(self) -> list[str]:
        """List all topic IDs for this agent."""
        topics = await self.db.get_topics(self.agent_id)
        return [t["topic_id"] for t in topics]

    async def topic_exists(self, topic_id: str) -> bool:
        """Check if a topic file exists."""
        json_path = self._get_json_path(topic_id)
        return json_path.exists()

    # ──────────────────────────────────────────────────────────────────────
    # SAVE / UPDATE
    # ──────────────────────────────────────────────────────────────────────

    async def save_topic(
        self,
        topic:          TopicFile,
        detect_conflicts: bool = True,
    ) -> Path:
        """
        Save a topic file atomically.

        STRICT WRITE DISCIPLINE (from Phase 1):
        1. Write JSON (machine-readable)
        2. Write Markdown (human/LLM-readable)
        3. Update DB metadata
        4. Update cache
        5. Update file hash
```

```
        Args:
            topic:            TopicFile to save
            detect_conflicts: If True, checks file hash before writing

        Returns:
            Path to written JSON file

        Raises:
            FileConflictError: If file was modified by another process
        """
        validate_topic_id(topic.topic_id)

        json_path = self._get_json_path(topic.topic_id)
        md_path   = self._get_md_path(topic.topic_id)

        # Conflict detection
        if detect_conflicts and json_path.exists():
            current_hash = await self._compute_file_hash(json_path)
            expected_hash = self._file_hashes.get(topic.topic_id)

            if expected_hash and current_hash != expected_hash:
                self.stats.conflicts += 1
                logger.error(
                    f"File conflict detected for {topic.topic_id}: "
                    f"expected hash {expected_hash[:8]}, "
                    f"got {current_hash[:8]}"
                )
                raise FileConflictError(
                    f"Topic {topic.topic_id} was modified by another process"
                )

        # Update timestamps
        topic.last_modified = datetime.now()

        # Serialize to JSON
        payload = {
            "topic_id":     topic.topic_id,
            "topic_name":   topic.topic_name,
            "agent_id":     topic.agent_id,
            "tags":         topic.tags,
            "facts":        [f.model_dump(mode="json") for f in topic.facts],
            "created_at":   topic.created_at.isoformat(),
            "last_modified": topic.last_modified.isoformat(),
            "version":      2,  # Phase 2 version marker
        }

        # Step 1: Write JSON atomically
        json_content = json.dumps(payload, indent=2, default=str)
        await atomic_write(json_path, json_content)

        # Step 2: Write Markdown atomically
        md_content = topic.to_markdown()
        await atomic_write(md_path, md_content)

        # Step 3: Update DB metadata
        await self.db.upsert_topic(
            agent_id=self.agent_id,
```

```
            topic_id=topic.topic_id,
            topic_name=topic.topic_name,
            file_path=str(json_path.relative_to(self.base_path)),
            fact_count=len(topic.facts),
            avg_confidence=topic.avg_confidence,
            tags=topic.tags,
            file_size_bytes=json_path.stat().st_size,
        )

        # Step 4: Sync individual facts to DB
        await self._sync_facts_to_db(topic)

        # Step 5: Update cache and hash
        self._cache.put(topic.topic_id, topic)
        await self._update_file_hash(topic.topic_id)

        self.stats.saves += 1
        logger.debug(f"Saved topic: {topic.topic_id} ({len(topic.facts)} facts)")

        return json_path

    async def save_topics_batch(
        self,
        topics: list[TopicFile],
    ) -> dict[str, Path]:
        """Save multiple topics in a batch (more efficient)."""
        self.stats.batch_ops += 1
        results: dict[str, Path] = {}

        for topic in topics:
            try:
                path = await self.save_topic(topic)
                results[topic.topic_id] = path
            except Exception as e:
                logger.error(f"Failed to save topic {topic.topic_id}: {e}")
                results[topic.topic_id] = None

        return results

    async def update_topic_metadata(
        self,
        topic_id:   str,
        topic_name: Optional[str]      = None,
        tags:       Optional[list[str]] = None,
    ) -> bool:
        """Update just the metadata without loading/saving all facts."""
        topic = await self.get_topic(topic_id)
        if not topic:
            return False

        if topic_name:
            topic.topic_name = topic_name
        if tags is not None:
            topic.tags = tags

        await self.save_topic(topic)
        return True
```

```python
    # ──────────────────────────────────────────────────────────────────────
    # FACT OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    async def add_fact(
        self,
        topic_id:    str,
        fact:        MemoryFact,
    ) -> TopicFile:
        """
        Add a fact to a topic.
        Creates topic if it doesn't exist.
        """
        topic = await self.get_topic(topic_id)

        if topic is None:
            topic = TopicFile(
                topic_id=topic_id,
                topic_name=topic_id.replace("_", " ").title(),
                agent_id=self.agent_id,
            )

        topic.facts.append(fact)
        await self.save_topic(topic)
        return topic

    async def add_facts_batch(
        self,
        topic_id: str,
        facts:    list[MemoryFact],
    ) -> TopicFile:
        """Add multiple facts to a topic in one operation."""
        topic = await self.get_topic(topic_id)

        if topic is None:
            topic = TopicFile(
                topic_id=topic_id,
                topic_name=topic_id.replace("_", " ").title(),
                agent_id=self.agent_id,
            )

        topic.facts.extend(facts)
        await self.save_topic(topic)
        return topic

    async def update_fact(
        self,
        topic_id:       str,
        fact_id:        str,
        new_content:    Optional[str]           = None,
        new_confidence: Optional[ConfidenceLevel] = None,
    ) -> bool:
        """Update a specific fact within a topic."""
        topic = await self.get_topic(topic_id)
        if not topic:
            return False

        fact = topic.get_fact(fact_id)
```

```
        if not fact:
            return False

        if new_content:
            fact.content = new_content
        if new_confidence:
            fact.confidence = new_confidence
            fact.last_verified = datetime.now()

        await self.save_topic(topic)
        return True

    async def remove_fact(
        self,
        topic_id: str,
        fact_id:  str,
    ) -> bool:
        """Remove a fact from a topic."""
        topic = await self.get_topic(topic_id)
        if not topic:
            return False

        before_count = len(topic.facts)
        topic.facts = [f for f in topic.facts if f.fact_id != fact_id]

        if len(topic.facts) == before_count:
            return False  # Fact not found

        await self.save_topic(topic)
        await self.db.delete_fact(self.agent_id, topic_id, fact_id)
        return True

    async def remove_facts_batch(
        self,
        topic_id: str,
        fact_ids: list[str],
    ) -> int:
        """Remove multiple facts at once. Returns count removed."""
        topic = await self.get_topic(topic_id)
        if not topic:
            return 0

        before_count = len(topic.facts)
        topic.facts = [f for f in topic.facts if f.fact_id not in fact_ids]
        removed = before_count - len(topic.facts)

        if removed > 0:
            await self.save_topic(topic)
            # Batch delete from DB
            for fid in fact_ids:
                await self.db.delete_fact(self.agent_id, topic_id, fid)

        return removed

    # ──────────────────────────────────────────────────────────────
    # DELETE
    # ──────────────────────────────────────────────────────────────
```

```python
    async def delete_topic(self, topic_id: str) -> bool:
        """Delete a topic completely (files + DB + cache)."""
        json_path = self._get_json_path(topic_id)
        md_path   = self._get_md_path(topic_id)

        if not json_path.exists():
            return False

        # Remove files
        json_path.unlink(missing_ok=True)
        md_path.unlink(missing_ok=True)

        # Remove from DB
        await self.db.execute(
            "DELETE FROM topics WHERE agent_id = ? AND topic_id = ?",
            (self.agent_id, topic_id),
        )
        await self.db.execute(
            "DELETE FROM facts WHERE agent_id = ? AND topic_id = ?",
            (self.agent_id, topic_id),
        )

        # Remove from cache
        self._cache.remove(topic_id)
        self._file_hashes.pop(topic_id, None)

        logger.info(f"Deleted topic: {topic_id}")
        return True

    async def delete_topics_batch(self, topic_ids: list[str]) -> int:
        """Delete multiple topics. Returns count deleted."""
        deleted = 0
        for tid in topic_ids:
            if await self.delete_topic(tid):
                deleted += 1
        return deleted

    # ──────────────────────────────────────────────────────────────────────
    # CACHE MANAGEMENT
    # ──────────────────────────────────────────────────────────────────────

    def invalidate_cache(self, topic_id: str) -> None:
        """Force-remove a topic from cache (next get will reload)."""
        self._cache.remove(topic_id)

    def clear_cache(self) -> None:
        """Clear entire topic cache."""
        self._cache.clear()
        logger.info("Topic cache cleared")

    def get_cache_stats(self) -> dict:
        """Cache performance statistics."""
        return {
            "capacity":    self._cache.capacity,
            "size":        self._cache.size,
            "hits":        self.stats.cache_hits,
            "misses":      self.stats.cache_misses,
            "hit_rate":    (
```

```
                self.stats.cache_hits / (self.stats.cache_hits + self.stats.cache_misses)
                if (self.stats.cache_hits + self.stats.cache_misses) > 0
                else 0.0
            ),
        }

    # ──────────────────────────────────────────────────────────────────────
    # HELPERS
    # ──────────────────────────────────────────────────────────────────────

    def _get_json_path(self, topic_id: str) -> Path:
        return self.topics_path / f"{topic_id}.json"

    def _get_md_path(self, topic_id: str) -> Path:
        return self.topics_path / f"{topic_id}.md"

    async def _load_from_disk(self, topic_id: str) -> Optional[TopicFile]:
        """Load topic from JSON file."""
        json_path = self._get_json_path(topic_id)

        if not json_path.exists():
            return None

        try:
            async with aiofiles.open(json_path) as f:
                data = json.loads(await f.read())

            facts = [MemoryFact(**f) for f in data.get("facts", [])]

            topic = TopicFile(
                topic_id=data["topic_id"],
                topic_name=data["topic_name"],
                agent_id=data.get("agent_id", self.agent_id),
                facts=facts,
                tags=data.get("tags", []),
                file_path=str(json_path.relative_to(self.base_path)),
                created_at=datetime.fromisoformat(data["created_at"]),
                last_modified=datetime.fromisoformat(data["last_modified"]),
            )

            self.stats.loads += 1
            return topic

        except Exception as e:
            logger.error(f"Failed to load topic {topic_id}: {e}", exc_info=True)
            return None

    async def _sync_facts_to_db(self, topic: TopicFile) -> None:
        """Sync all facts in a topic to the database."""
        for fact in topic.facts:
            await self.db.insert_fact(
                agent_id=self.agent_id,
                topic_id=topic.topic_id,
                fact_id=fact.fact_id,
                content=fact.content,
                confidence_level=fact.confidence.value,
                source=fact.source,
                verification_hint=fact.verification_hint,
```

```
                contradicts_ids=fact.contradicts_ids,
                meta=fact.meta,
            )

    async def _compute_file_hash(self, path: Path) -> str:
        """Compute SHA256 hash of a file (for conflict detection)."""
        async with aiofiles.open(path, "rb") as f:
            content = await f.read()
        return hashlib.sha256(content).hexdigest()

    async def _update_file_hash(self, topic_id: str) -> None:
        """Update stored file hash for conflict detection."""
        json_path = self._get_json_path(topic_id)
        if json_path.exists():
            self._file_hashes[topic_id] = await self._compute_file_hash(json_path)

    # ──────────────────────────────────────────────────────────────────────
    # DIAGNOSTICS
    # ──────────────────────────────────────────────────────────────────────

    async def get_metrics(self) -> dict:
        """Topic manager runtime metrics."""
        all_topics = await self.db.get_topics(self.agent_id)

        total_facts = sum(t["fact_count"] for t in all_topics)
        total_size  = sum(t["file_size_bytes"] for t in all_topics)

        return {
            "topic_count":       len(all_topics),
            "total_facts":       total_facts,
            "total_size_kb":     total_size / 1024,
            "cache":             self.get_cache_stats(),
            "stats": {
                "loads":         self.stats.loads,
                "saves":         self.stats.saves,
                "conflicts":     self.stats.conflicts,
                "batch_ops":     self.stats.batch_ops,
            },
        }


class FileConflictError(Exception):
    """Raised when a file has been modified by another process."""
    pass
```

---

3. LRU Cache Implementation

Python

```
# memograph/core/cache.py
"""
Generic LRU cache for topic files.
```

```
Thread-safe, O(1) get/put, automatic eviction.
"""

from __future__ import annotations

from collections import OrderedDict
from typing import Generic, Optional, TypeVar

K = TypeVar("K")
V = TypeVar("V")


class LRUCache(Generic[K, V]):
    """
    Least Recently Used cache with O(1) operations.
    Uses OrderedDict for insertion order tracking.
    """

    def __init__(self, capacity: int = 100):
        if capacity <= 0:
            raise ValueError("Cache capacity must be positive")

        self.capacity = capacity
        self._cache: OrderedDict[K, V] = OrderedDict()

    def get(self, key: K) -> Optional[V]:
        """Get value, mark as recently used."""
        if key not in self._cache:
            return None

        # Move to end (most recently used)
        self._cache.move_to_end(key)
        return self._cache[key]

    def put(self, key: K, value: V) -> None:
        """Put value, evict LRU if full."""
        if key in self._cache:
            # Update and move to end
            self._cache[key] = value
            self._cache.move_to_end(key)
        else:
            # Add new entry
            self._cache[key] = value

            # Evict LRU if over capacity
            if len(self._cache) > self.capacity:
                self._cache.popitem(last=False)  # Remove oldest (FIFO)

    def remove(self, key: K) -> bool:
        """Remove a key. Returns True if key existed."""
        if key in self._cache:
            del self._cache[key]
            return True
        return False

    def clear(self) -> None:
        """Clear entire cache."""
        self._cache.clear()
```

```
    @property
    def size(self) -> int:
        """Current cache size."""
        return len(self._cache)

    def keys(self) -> list[K]:
        """All keys in LRU order (oldest first)."""
        return list(self._cache.keys())

    def items(self) -> list[tuple[K, V]]:
        """All items in LRU order."""
        return list(self._cache.items())
```

---

4. Eviction Strategies

Python

```
# memograph/strategies/eviction.py
"""
Index pointer eviction strategies.
Decides which pointer to remove when index is full.
"""

from __future__ import annotations

import random
from abc import ABC, abstractmethod
from datetime import datetime

from memograph.models.index import IndexPointer


class EvictionStrategy(ABC):
    """Abstract base for eviction strategies."""

    @abstractmethod
    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        """Select which pointer to evict."""
        ...


class LRUEvictionStrategy(EvictionStrategy):
    """Evict least recently accessed pointer."""

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None

        # Sort by last_accessed (None = never accessed = oldest)
        def access_key(p: IndexPointer) -> datetime:
            return p.last_accessed or datetime.min
```

```
        sorted_pointers = sorted(pointers, key=access_key)
        return sorted_pointers[0]


class LFUEvictionStrategy(EvictionStrategy):
    """Evict least frequently accessed pointer."""

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None

        # Sort by access count
        sorted_pointers = sorted(pointers, key=lambda p: p.access_count)
        return sorted_pointers[0]


class ConfidenceEvictionStrategy(EvictionStrategy):
    """Evict lowest confidence pointer."""

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None

        # Sort by confidence
        sorted_pointers = sorted(pointers, key=lambda p: p.confidence)
        return sorted_pointers[0]


class StaleFirstEvictionStrategy(EvictionStrategy):
    """Evict stale pointers first, then fall back to LRU."""

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None

        # Prioritize stale pointers
        stale = [p for p in pointers if p.is_stale]
        if stale:
            return stale[0]

        # Fall back to LRU
        return LRUEvictionStrategy().select_victim(pointers)


class CompositeEvictionStrategy(EvictionStrategy):
    """
    Score-based eviction using multiple factors.
    Lower score = more likely to be evicted.
    """

    def __init__(
        self,
        confidence_weight: float = 0.4,
        recency_weight:    float = 0.3,
        frequency_weight:  float = 0.3,
    ):
        self.confidence_weight = confidence_weight
```

```
        self.recency_weight    = recency_weight
        self.frequency_weight  = frequency_weight

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None

        # Stale pointers are always evicted first
        stale = [p for p in pointers if p.is_stale]
        if stale:
            return stale[0]

        # Compute normalized scores
        now = datetime.now()
        max_access = max((p.access_count for p in pointers), default=1)

        scored: list[tuple[float, IndexPointer]] = []

        for p in pointers:
            # Confidence score (0-1)
            conf_score = p.confidence

            # Recency score (0-1) — days since last access
            if p.last_accessed:
                days_since = (now - p.last_accessed).total_seconds() / 86400
                recency_score = max(0.0, 1.0 - (days_since / 30))
            else:
                recency_score = 0.0

            # Frequency score (0-1) — normalized access count
            freq_score = p.access_count / max_access if max_access > 0 else 0.0

            # Weighted composite score
            total_score = (
                self.confidence_weight * conf_score +
                self.recency_weight    * recency_score +
                self.frequency_weight  * freq_score
            )

            scored.append((total_score, p))

        # Return pointer with lowest score
        scored.sort(key=lambda x: x[0])
        return scored[0][1]


class RandomEvictionStrategy(EvictionStrategy):
    """Random eviction (useful for testing)."""

    def select_victim(self, pointers: list[IndexPointer]) -> IndexPointer | None:
        if not pointers:
            return None
        return random.choice(pointers)
```

---

5. Index Compaction Logic

Python

```python
# memograph/strategies/compaction.py
"""
Index compaction strategies.
Removes stale/orphaned pointers, deduplicates, enforces limits.
"""

from __future__ import annotations

import logging
from dataclasses import dataclass
from pathlib import Path

from memograph.models.index import MemoryIndex

logger = logging.getLogger("memograph.compaction")


@dataclass
class CompactionResult:
    """Result of an index compaction operation."""
    compacted_index:     MemoryIndex
    removed_count:       int
    removed_stale:       int
    removed_orphans:     int
    removed_duplicates:  int
    bytes_before:        int
    bytes_after:         int


async def compact_index(
    index:        MemoryIndex,
    topics_path:  Path,
    max_pointers: int,
    max_bytes:    int,
) -> CompactionResult:
    """
    Full index compaction.

    Steps:
    1. Remove pointers to non-existent topic files (orphans)
    2. Remove duplicate pointers (same topic_id)
    3. Mark stale pointers but keep them (manual review needed)
    4. Sort by confidence × recency
    5. Enforce max_pointers limit
    6. Enforce max_bytes limit

    Returns:
        CompactionResult with statistics
    """
    before_count = len(index.pointers)
```

```
    before_bytes = len(index.to_markdown().encode())

    removed_stale      = 0
    removed_orphans    = 0
    removed_duplicates = 0

    # Step 1: Remove orphaned pointers
    valid_pointers = []
    for p in index.pointers:
        topic_file = topics_path / f"{p.topic_id}.json"
        if topic_file.exists():
            valid_pointers.append(p)
        else:
            removed_orphans += 1
            logger.warning(f"Removing orphaned pointer: {p.topic_id}")

    # Step 2: Remove duplicates (keep highest confidence)
    seen: dict[str, int] = {}
    deduped_pointers = []

    for p in valid_pointers:
        if p.topic_id in seen:
            removed_duplicates += 1
            # Keep the one with higher confidence
            existing_idx = seen[p.topic_id]
            if p.confidence > deduped_pointers[existing_idx].confidence:
                deduped_pointers[existing_idx] = p
        else:
            seen[p.topic_id] = len(deduped_pointers)
            deduped_pointers.append(p)

    # Step 3: Sort by composite score (confidence × recency)
    def score_pointer(p):
        # Penalize stale
        stale_penalty = 0.5 if p.is_stale else 1.0

        # Recency (days since last update)
        from datetime import datetime
        days_old = (datetime.now() - p.last_updated).days
        recency_score = max(0.1, 1.0 - (days_old / 365))

        return p.confidence * recency_score * stale_penalty

    sorted_pointers = sorted(deduped_pointers, key=score_pointer, reverse=True)

    # Step 4: Enforce max_pointers limit
    if len(sorted_pointers) > max_pointers:
        logger.warning(
            f"Index over limit: {len(sorted_pointers)} > {max_pointers} — "
            f"truncating lowest {len(sorted_pointers) - max_pointers} pointers"
        )
        sorted_pointers = sorted_pointers[:max_pointers]

    # Step 5: Enforce max_bytes limit
    compacted = MemoryIndex(
        agent_id=index.agent_id,
        pointers=sorted_pointers,
        version=index.version,
```

```
        last_consolidated=index.last_consolidated,
    )

    while len(compacted.to_markdown().encode()) > max_bytes and compacted.pointers:
        logger.warning("Index over byte limit — removing lowest-score pointer")
        compacted.pointers.pop()  # Remove last (lowest score)

    after_count = len(compacted.pointers)
    after_bytes = len(compacted.to_markdown().encode())

    return CompactionResult(
        compacted_index=compacted,
        removed_count=before_count - after_count,
        removed_stale=removed_stale,
        removed_orphans=removed_orphans,
        removed_duplicates=removed_duplicates,
        bytes_before=before_bytes,
        bytes_after=after_bytes,
    )
```

---

6. Atomic File Operations

Python

```
# memograph/utils/atomic.py
"""
Atomic file write operations to prevent corruption.
Uses temp file + rename (atomic on POSIX systems).
"""

from __future__ import annotations

import os
import tempfile
from pathlib import Path

import aiofiles


async def atomic_write(path: Path, content: str, encoding: str = "utf-8") -> None:
    """
    Write content to file atomically.

    Strategy:
    1. Write to temp file in same directory
    2. Flush to disk (fsync)
    3. Rename temp file to target (atomic on POSIX)

    This prevents partial writes and corruption.
    """
    path = Path(path)
    path.parent.mkdir(parents=True, exist_ok=True)
```

```
    # Create temp file in same directory (required for atomic rename)
    fd, temp_path = tempfile.mkstemp(
        dir=path.parent,
        prefix=f".{path.name}.",
        suffix=".tmp",
    )

    try:
        # Write to temp file
        async with aiofiles.open(temp_path, "w", encoding=encoding) as f:
            await f.write(content)
            await f.flush()
            os.fsync(f.fileno())  # Force write to disk

        # Atomic rename (overwrites target if exists)
        os.replace(temp_path, path)

    except Exception:
        # Clean up temp file on error
        try:
            os.unlink(temp_path)
        except OSError:
            pass
        raise


async def atomic_write_bytes(path: Path, content: bytes) -> None:
    """Atomic write for binary content."""
    path = Path(path)
    path.parent.mkdir(parents=True, exist_ok=True)

    fd, temp_path = tempfile.mkstemp(
        dir=path.parent,
        prefix=f".{path.name}.",
        suffix=".tmp",
    )

    try:
        async with aiofiles.open(temp_path, "wb") as f:
            await f.write(content)
            await f.flush()
            os.fsync(f.fileno())

        os.replace(temp_path, path)

    except Exception:
        try:
            os.unlink(temp_path)
        except OSError:
            pass
        raise
```

---

7. Validation Helpers

Python

```python
# memograph/utils/validation.py
"""
Data validation helpers for MemoGraph.
"""

from __future__ import annotations

import re


def validate_topic_id(topic_id: str) -> None:
    """
    Validate topic_id format.

    Rules:
    - Lowercase alphanumeric + underscores only
    - Must start with letter
    - 1-50 characters

    Raises ValueError if invalid.
    """
    if not topic_id:
        raise ValueError("topic_id cannot be empty")

    if len(topic_id) > 50:
        raise ValueError(f"topic_id too long: {len(topic_id)} > 50")

    if not re.match(r"^[a-z][a-z0-9_]*$", topic_id):
        raise ValueError(
            f"Invalid topic_id '{topic_id}': must be lowercase, "
            f"start with letter, and contain only a-z, 0-9, _"
        )


def validate_fact_content(content: str, max_length: int = 1000) -> None:
    """
    Validate fact content.

    Rules:
    - Not empty
    - ≤ max_length characters

    Raises ValueError if invalid.
    """
    if not content or not content.strip():
        raise ValueError("Fact content cannot be empty")

    if len(content) > max_length:
        raise ValueError(
            f"Fact content too long: {len(content)} > {max_length}"
        )


def validate_summary(summary: str, max_length: int = 80) -> None:
    """Validate index pointer summary."""
```

```
    if not summary or not summary.strip():
        raise ValueError("Summary cannot be empty")

    if len(summary) > max_length:
        raise ValueError(f"Summary too long: {len(summary)} > {max_length}")


def normalize_topic_id(name: str) -> str:
    """
    Convert a human-readable name to a valid topic_id.

    Example:
        "Project Architecture" → "project_architecture"
        "User Preferences (Dark Mode)" → "user_preferences_dark_mode"
    """
    # Convert to lowercase
    s = name.lower()

    # Replace spaces and hyphens with underscores
    s = re.sub(r"[\s\-]+", "_", s)

    # Remove non-alphanumeric (except underscores)
    s = re.sub(r"[^a-z0-9_]", "", s)

    # Remove leading/trailing underscores
    s = s.strip("_")

    # Collapse multiple underscores
    s = re.sub(r"_+", "_", s)

    # Ensure starts with letter
    if s and not s[0].isalpha():
        s = "topic_" + s

    # Truncate to 50 chars
    s = s[:50]

    if not s:
        raise ValueError(f"Cannot normalize '{name}' to valid topic_id")

    return s
```

---

8. Monitoring & Metrics

Python

```
# memograph/monitoring/metrics.py
"""
Performance and memory metrics for MemoGraph.
Tracks index pressure, cache performance, topic sizes, etc.
"""
```

```python
from __future__ import annotations

import time
from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional


@dataclass
class MemoryMetrics:
    """System-wide memory metrics snapshot."""

    timestamp:            datetime = field(default_factory=datetime.now)

    # Index metrics
    index_pointer_count: int   = 0
    index_max_pointers:  int   = 200
    index_usage_ratio:   float = 0.0
    index_size_bytes:    int   = 0
    index_max_bytes:     int   = 25_600
    index_byte_ratio:    float = 0.0
    index_stale_count:   int   = 0

    # Topic metrics
    topic_count:          int   = 0
    total_facts:          int   = 0
    total_topic_size_kb: float = 0.0
    avg_facts_per_topic: float = 0.0

    # Cache metrics
    cache_size:           int   = 0
    cache_capacity:       int   = 0
    cache_hit_rate:      float = 0.0

    # Performance metrics
    avg_index_load_ms:   float = 0.0
    avg_topic_load_ms:   float = 0.0
    avg_topic_save_ms:   float = 0.0

    def is_index_under_pressure(self, threshold: float = 0.9) -> bool:
        """True if index is near capacity."""
        return (
            self.index_usage_ratio > threshold
            or self.index_byte_ratio > threshold
        )

    def is_cache_effective(self, min_hit_rate: float = 0.7) -> bool:
        """True if cache is performing well."""
        return self.cache_hit_rate >= min_hit_rate


class MetricsCollector:
    """
    Collects and aggregates metrics over time.
    Useful for performance monitoring and optimization.
    """

    def __init__(self):
```

```
        self._snapshots: list[MemoryMetrics] = []
        self._timings: dict[str, list[float]] = {}

    def record_snapshot(self, metrics: MemoryMetrics) -> None:
        """Record a metrics snapshot."""
        self._snapshots.append(metrics)

        # Keep last 1000 snapshots
        if len(self._snapshots) > 1000:
            self._snapshots = self._snapshots[-1000:]

    def record_timing(self, operation: str, duration_ms: float) -> None:
        """Record operation timing."""
        if operation not in self._timings:
            self._timings[operation] = []

        self._timings[operation].append(duration_ms)

        # Keep last 1000 timings per operation
        if len(self._timings[operation]) > 1000:
            self._timings[operation] = self._timings[operation][-1000:]

    def get_latest_snapshot(self) -> Optional[MemoryMetrics]:
        """Get the most recent metrics snapshot."""
        return self._snapshots[-1] if self._snapshots else None

    def get_avg_timing(self, operation: str) -> float:
        """Get average timing for an operation."""
        timings = self._timings.get(operation, [])
        return sum(timings) / len(timings) if timings else 0.0

    def get_p95_timing(self, operation: str) -> float:
        """Get 95th percentile timing for an operation."""
        timings = self._timings.get(operation, [])
        if not timings:
            return 0.0

        sorted_timings = sorted(timings)
        idx = int(len(sorted_timings) * 0.95)
        return sorted_timings[idx]

    def summary(self) -> dict:
        """Summary of all collected metrics."""
        latest = self.get_latest_snapshot()

        return {
            "latest_snapshot": latest.__dict__ if latest else None,
            "timing_summary": {
                op: {
                    "avg_ms":  self.get_avg_timing(op),
                    "p95_ms":  self.get_p95_timing(op),
                    "samples": len(timings),
                }
                for op, timings in self._timings.items()
            },
            "snapshot_count": len(self._snapshots),
        }
```

```python
def measure_time(collector: MetricsCollector, operation: str):
    """
    Context manager for timing operations.

    Usage:
        with measure_time(collector, "topic_save"):
            await topic_manager.save_topic(topic)
    """
    class Timer:
        def __init__(self):
            self.start = None

        def __enter__(self):
            self.start = time.perf_counter()
            return self

        def __exit__(self, *args):
            duration_ms = (time.perf_counter() - self.start) * 1000
            collector.record_timing(operation, duration_ms)

    return Timer()
```

---

9. Enhanced MemoryManager (Phase 2)

Python

```python
# memograph/core/memory_manager.py (PHASE 2 UPDATE)
"""
Phase 2 MemoryManager — integrates IndexEngine + TopicManager.
Adds batch operations, better caching, metrics tracking.
"""

from __future__ import annotations

import logging
from datetime import datetime
from pathlib import Path
from typing import Optional

from memograph.config import ConfidenceLevel, MemoGraphConfig, get_config
from memograph.core.cache import LRUCache
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.base import BaseLLMProvider
from memograph.llm.factory import create_provider
from memograph.models.index import MemoryIndex
from memograph.models.topic import MemoryFact, TopicFile
from memograph.models.transcript import Session
from memograph.monitoring.metrics import MemoryMetrics, MetricsCollector, measure_time
from memograph.prompts.system_prompts import (
```

```
    PromptRole,
    build_contradiction_prompt,
    build_extractor_prompt,
    get_prompt,
)
from memograph.utils.validation import normalize_topic_id, validate_fact_content

logger = logging.getLogger("memograph.core")


class WriteResult:
    """Result of a remember() operation."""

    def __init__(
        self,
        success:      bool,
        fact:         Optional[MemoryFact] = None,
        topic:        Optional[TopicFile]  = None,
        skipped:      bool                 = False,
        skip_reason:  Optional[str]        = None,
        error:        Optional[str]        = None,
    ):
        self.success     = success
        self.fact        = fact
        self.topic       = topic
        self.skipped     = skipped
        self.skip_reason = skip_reason
        self.error       = error


class MemoryManagerV2:
    """
    Phase 2 MemoryManager — full 3-layer architecture.

    Key improvements over Phase 1:
    - Separate IndexEngine (Layer 1) and TopicManager (Layer 2)
    - LRU caching for topics
    - Batch operations
    - Atomic writes with conflict detection
    - Performance metrics tracking
    - Auto-compaction when index is under pressure
    """

    def __init__(
        self,
        config:   Optional[MemoGraphConfig] = None,
        llm:      Optional[BaseLLMProvider] = None,
        db:       Optional[DatabaseManager] = None,
    ):
        self.config    = config or get_config()
        self.base_path = Path(self.config.base_path)
        self.agent_id  = self.config.agent_id

        # File paths
        self.transcripts_path = self.base_path / "transcripts"
        self.transcripts_path.mkdir(parents=True, exist_ok=True)

        # Components — injected or created from config
```

```
        self._llm: Optional[BaseLLMProvider] = llm
        self._db:  Optional[DatabaseManager] = db

        # Phase 2: Separate engines
        self._index_engine:  Optional[IndexEngine]  = None
        self._topic_manager: Optional[TopicManager] = None

        # Active session
        self._current_session: Optional[Session] = None

        # Metrics
        self.metrics = MetricsCollector()

    # ──────────────────────────────────────────────────────────────────────
    # LIFECYCLE
    # ──────────────────────────────────────────────────────────────────────

    async def initialize(self) -> None:
        """Connect DB, ensure agent, initialize engines."""
        if not self._db:
            self._db = DatabaseManager(self.config.db_path)
            await self._db.connect()

        if not self._llm:
            self._llm = create_provider(config=self.config)

        await self._db.ensure_agent(self.agent_id)

        # Initialize Phase 2 engines
        self._index_engine = IndexEngine(
            config=self.config,
            db=self._db,
        )
        await self._index_engine.initialize()

        self._topic_manager = TopicManager(
            config=self.config,
            db=self._db,
            cache_size=50,
        )

        logger.info(
            f"MemoryManager V2 initialized — agent={self.agent_id}, "
            f"provider={self.config.llm_provider.value}"
        )

        # Collect initial metrics
        await self._collect_metrics()

    async def close(self) -> None:
        if self._current_session:
            await self.end_session()
        if self._db:
            await self._db.disconnect()

    async def __aenter__(self) -> "MemoryManagerV2":
        await self.initialize()
        return self
```

```python
    async def __aexit__(self, *args) -> None:
        await self.close()

    # ──────────────────────────────────────────────────────────────────────
    # SESSION MANAGEMENT
    # ──────────────────────────────────────────────────────────────────────

    async def start_session(
        self,
        session_id: Optional[str] = None,
        meta: dict = None,
    ) -> Session:
        import uuid
        sid = session_id or str(uuid.uuid4())[:12]
        session = Session(session_id=sid, agent_id=self.agent_id, meta=meta or {})
        await self._db.create_session(self.agent_id, sid, meta)
        self._current_session = session
        logger.debug(f"Session started: {sid}")
        return session

    async def end_session(self, turn_count: int = 0) -> None:
        if not self._current_session:
            return
        await self._db.end_session(
            self.agent_id,
            self._current_session.session_id,
            turn_count=turn_count,
        )
        self._current_session = None

    # ──────────────────────────────────────────────────────────────────────
    # CORE CRUD API (Phase 2 Enhanced)
    # ──────────────────────────────────────────────────────────────────────

    async def remember(
        self,
        topic_id:          str,
        content:           str,
        source:            str,
        topic_name:        Optional[str]           = None,
        confidence:        ConfidenceLevel         = ConfidenceLevel.OBSERVED,
        tags:              Optional[list[str]]     = None,
        verification_hint: Optional[str]           = None,
        check_contradictions: bool                 = True,
        auto_normalize_id: bool                    = True,
    ) -> WriteResult:
        """
        Store a memory fact.

        Phase 2 enhancements:
        - Auto-normalize topic_id if requested
        - Atomic writes via TopicManager
        - Automatic index compaction if under pressure
        - Performance metrics tracking

        STRICT WRITE ORDER:
          1. Validate inputs
```

```
            2. Load or create topic
            3. Check contradictions (optional)
            4. Add fact to topic
            5. Save topic atomically (TopicManager)
            6. Update index pointer (IndexEngine)
            7. Auto-compact if needed
        """
        with measure_time(self.metrics, "remember"):
            # Normalize topic_id if requested
            if auto_normalize_id:
                topic_id = normalize_topic_id(topic_id)

            # Validate
            validate_fact_content(content)

            # Load or create topic
            topic = await self._topic_manager.get_topic(topic_id)

            if topic is None:
                topic = TopicFile(
                    topic_id=topic_id,
                    topic_name=topic_name or topic_id.replace("_", " ").title(),
                    agent_id=self.agent_id,
                    tags=tags or [],
                )

            # Check contradictions
            if check_contradictions and topic.facts and self._llm:
                contradiction = await self._check_contradiction(content, topic)
                if contradiction and contradiction.get("has_contradiction"):
                    logger.warning(
                        f"Contradiction detected in {topic_id}: "
                        f"{contradiction.get('conflict_description')}"
                    )
                    rec = contradiction.get("recommendation", "keep_both_flagged")
                    if rec == "keep_existing":
                        return WriteResult(
                            success=False,
                            skipped=True,
                            skip_reason=f"Contradiction:
{contradiction.get('conflict_description')}",
                        )

            # Create fact
            fact = MemoryFact(
                content=content,
                confidence=confidence,
                source=source,
                verification_hint=verification_hint,
                created_at=datetime.now(),
            )

            try:
                # Save topic (atomic, with conflict detection)
                topic = await self._topic_manager.add_fact(topic_id, fact)

                # Update index pointer
                pointer = await self._index_engine.add_pointer(
```

```
                    topic_id=topic.topic_id,
                    topic_file_path=f"topics/{topic_id}.json",
                    summary=topic.to_summary(),
                    confidence=topic.avg_confidence,
                )

                # Auto-compact if index is under pressure
                await self._index_engine.auto_compact_if_needed()

                # Collect metrics
                await self._collect_metrics()

                logger.debug(
                    f"Stored fact {fact.fact_id} in topic {topic_id}"
                )

                return WriteResult(success=True, fact=fact, topic=topic)

            except Exception as e:
                logger.error(f"Failed to remember: {e}", exc_info=True)
                return WriteResult(success=False, error=str(e))

    async def remember_batch(
        self,
        facts: list[dict],
    ) -> list[WriteResult]:
        """
        Batch remember operation — more efficient for multiple facts.

        Args:
            facts: List of dicts with keys: topic_id, content, source, ...

        Returns:
            List of WriteResults
        """
        with measure_time(self.metrics, "remember_batch"):
            results = []
            for f in facts:
                result = await self.remember(
                    topic_id=f["topic_id"],
                    content=f["content"],
                    source=f["source"],
                    topic_name=f.get("topic_name"),
                    confidence=f.get("confidence", ConfidenceLevel.OBSERVED),
                    tags=f.get("tags"),
                    verification_hint=f.get("verification_hint"),
                )
                results.append(result)

            return results

    async def recall(
        self,
        query:    str,
        top_k:    int  = 3,
        verify:   bool = False,
    ) -> list[TopicFile]:
        """
```

```
        Bandwidth-aware recall using IndexEngine.

        Phase 2 enhancements:
        - Uses IndexEngine.search_pointers() for relevance
        - Lazy-loads topics via TopicManager
        - Tracks access for LRU eviction
        - Records performance metrics
        """
        with measure_time(self.metrics, "recall"):
            # Search index for relevant pointers
            pointers = await self._index_engine.search_pointers(query)
            top_pointers = pointers[:top_k]

            topics: list[TopicFile] = []

            for pointer in top_pointers:
                # Mark as accessed (for LRU)
                await self._index_engine.mark_accessed(pointer.topic_id)

                # Load topic from cache or disk
                topic = await self._topic_manager.get_topic(pointer.topic_id)

                if topic:
                    if verify:
                        topic = self._mark_stale_facts(topic)
                    topics.append(topic)

            return topics

    async def forget(
        self,
        topic_id: str,
        fact_id:  Optional[str] = None,
    ) -> bool:
        """
        Targeted forgetting.

        Phase 2: Uses TopicManager for topic operations,
        IndexEngine for pointer removal.
        """
        with measure_time(self.metrics, "forget"):
            if fact_id:
                # Remove specific fact
                removed = await self._topic_manager.remove_fact(topic_id, fact_id)

                if removed:
                    # Update index pointer (fact count changed)
                    topic = await self._topic_manager.get_topic(topic_id)
                    if topic:
                        await self._index_engine.update_pointer(
                            topic_id=topic_id,
                            summary=topic.to_summary(),
                            confidence=topic.avg_confidence,
                        )
                return removed

            else:
                # Remove entire topic
```

```
                removed = await self._topic_manager.delete_topic(topic_id)

                if removed:
                    # Remove index pointer
                    await self._index_engine.remove_pointer(topic_id)

                return removed

    async def forget_batch(
        self,
        topic_ids: list[str],
    ) -> int:
        """Batch forget — remove multiple topics at once."""
        with measure_time(self.metrics, "forget_batch"):
            count = await self._topic_manager.delete_topics_batch(topic_ids)

            # Remove all pointers
            for tid in topic_ids:
                await self._index_engine.remove_pointer(tid)

            return count

    async def update(
        self,
        topic_id:       str,
        fact_id:        str,
        new_content:    Optional[str]           = None,
        new_confidence: Optional[ConfidenceLevel] = None,
    ) -> bool:
        """Update a specific fact."""
        with measure_time(self.metrics, "update"):
            updated = await self._topic_manager.update_fact(
                topic_id, fact_id, new_content, new_confidence
            )

            if updated:
                # Update index pointer confidence
                topic = await self._topic_manager.get_topic(topic_id)
                if topic:
                    await self._index_engine.update_pointer(
                        topic_id=topic_id,
                        confidence=topic.avg_confidence,
                    )

            return updated

    # ──────────────────────────────────────────────────────────────────────
    # INDEX & TOPIC ACCESS
    # ──────────────────────────────────────────────────────────────────────

    async def get_index(self) -> MemoryIndex:
        """Get the current memory index."""
        return await self._index_engine.get_index()

    async def get_topic(self, topic_id: str) -> Optional[TopicFile]:
        """Get a specific topic."""
        return await self._topic_manager.get_topic(topic_id)
```

```python
    def get_context_injection(self) -> str:
        """
        The ONLY thing injected into every prompt turn.
        Fast — no I/O, pure in-memory operation.
        """
        return self._index_engine.get_context_injection()

    # ──────────────────────────────────────────────────────────────────────
    # LLM-ASSISTED OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    async def extract_and_remember(
        self,
        text:    str,
        source:  str = "extraction",
        context: Optional[str] = None,
    ) -> list[WriteResult]:
        """
        Use LLM to extract memorable facts from text.
        Phase 2: Uses batch remember for efficiency.
        """
        if not self._llm:
            logger.warning("No LLM configured — skipping extraction")
            return []

        prompt  = build_extractor_prompt(text)
        system  = get_prompt(PromptRole.EXTRACTOR)

        try:
            result = await self._llm.complete_simple(
                prompt=prompt,
                system=system,
                purpose="extraction",
            )

            data  = self._parse_json(result)
            facts = data.get("extracted_facts", [])

            # Batch remember
            return await self.remember_batch(facts)

        except Exception as e:
            logger.error(f"Extraction failed: {e}", exc_info=True)
            return []

    async def _check_contradiction(
        self,
        new_content: str,
        topic:       TopicFile,
    ) -> Optional[dict]:
        """Use LLM to check for contradictions."""
        if not topic.facts or not self._llm:
            return None

        existing = [
            {
                "fact_id":    f.fact_id,
                "content":    f.content,
```

```
                "confidence": f.confidence.value,
            }
            for f in topic.facts[-10:]
        ]

        prompt = build_contradiction_prompt(new_content, existing)
        system = get_prompt(PromptRole.CONTRADICTION_RESOLVER)

        try:
            result = await self._llm.complete_simple(
                prompt=prompt,
                system=system,
                purpose="verification",
            )
            return self._parse_json(result)
        except Exception as e:
            logger.warning(f"Contradiction check failed: {e}")
            return None

    # ──────────────────────────────────────────────────────────────────────
    # TRANSCRIPT ARCHIVING (unchanged from Phase 1)
    # ──────────────────────────────────────────────────────────────────────

    async def archive_turn(
        self,
        role:        str,
        content:     str,
        tool_calls:  list[dict] = None,
        session_id:  Optional[str] = None,
    ) -> None:
        """Archive a conversation turn to transcript."""
        import aiofiles
        from memograph.models.transcript import TranscriptEntry

        sid = (
            session_id
            or (self._current_session.session_id if self._current_session else "unknown")
        )

        entry = TranscriptEntry(
            session_id=sid,
            role=role,
            content=content,
            tool_calls=tool_calls or [],
        )

        transcript_file = self.transcripts_path / f"{sid}.jsonl"
        async with aiofiles.open(transcript_file, "a") as f:
            await f.write(entry.to_jsonl_line() + "\n")

    async def grep_transcripts(
        self,
        pattern:     str,
        session_ids: Optional[list[str]] = None,
        max_results: int = 20,
    ) -> list[dict]:
        """GREP transcripts (never loads full files)."""
        import aiofiles
```

```
        import re
        import json

        compiled = re.compile(pattern, re.IGNORECASE)
        results:  list[dict] = []

        files = (
            [self.transcripts_path / f"{sid}.jsonl" for sid in session_ids]
            if session_ids
            else sorted(
                self.transcripts_path.glob("*.jsonl"),
                key=lambda f: f.stat().st_mtime,
                reverse=True,
            )
        )

        for filepath in files:
            if len(results) >= max_results:
                break
            if not filepath.exists():
                continue

            async with aiofiles.open(filepath) as f:
                async for line in f:
                    if compiled.search(line):
                        try:
                            results.append({
                                "file": filepath.name,
                                "match": json.loads(line),
                            })
                        except json.JSONDecodeError:
                            pass
                    if len(results) >= max_results:
                        break

        return results

    # ──────────────────────────────────────────────────────────────────────
    # METRICS & DIAGNOSTICS
    # ──────────────────────────────────────────────────────────────────────

    async def _collect_metrics(self) -> None:
        """Collect current system metrics."""
        index_metrics   = await self._index_engine.get_metrics()
        topic_metrics   = await self._topic_manager.get_metrics()

        snapshot = MemoryMetrics(
            index_pointer_count=index_metrics["pointer_count"],
            index_max_pointers=index_metrics["max_pointers"],
            index_usage_ratio=index_metrics["usage_ratio"],
            index_size_bytes=int(index_metrics["markdown_size_kb"] * 1024),
            index_max_bytes=self.config.limits.max_index_bytes,
            index_byte_ratio=index_metrics["byte_usage_ratio"],
            index_stale_count=index_metrics["stale_count"],
            topic_count=topic_metrics["topic_count"],
            total_facts=topic_metrics["total_facts"],
            total_topic_size_kb=topic_metrics["total_size_kb"],
            avg_facts_per_topic=(
```

```
                topic_metrics["total_facts"] / topic_metrics["topic_count"]
                if topic_metrics["topic_count"] > 0 else 0.0
            ),
            cache_size=topic_metrics["cache"]["size"],
            cache_capacity=topic_metrics["cache"]["capacity"],
            cache_hit_rate=topic_metrics["cache"]["hit_rate"],
        )

        self.metrics.record_snapshot(snapshot)

    async def status(self) -> dict:
        """Full system status snapshot."""
        await self._collect_metrics()

        index_metrics = await self._index_engine.get_metrics()
        topic_metrics = await self._topic_manager.get_metrics()
        usage         = await self._db.get_usage_stats(self.agent_id)
        transcripts   = list(self.transcripts_path.glob("*.jsonl"))

        return {
            "agent_id":   self.agent_id,
            "provider":   self.config.llm_provider.value,
            "index":      index_metrics,
            "topics":     topic_metrics,
            "transcripts": {"session_files": len(transcripts)},
            "llm_usage":  usage,
            "metrics":    self.metrics.summary(),
        }

    def _mark_stale_facts(self, topic: TopicFile) -> TopicFile:
        """Mark facts as stale based on age."""
        from datetime import timedelta
        thresholds = {
            ConfidenceLevel.VERIFIED: 30,
            ConfidenceLevel.OBSERVED: 7,
            ConfidenceLevel.INFERRED: 3,
            ConfidenceLevel.STALE:    0,
        }
        now = datetime.now()
        for fact in topic.facts:
            days_threshold = thresholds.get(fact.confidence, 7)
            ref_date = fact.last_verified or fact.created_at
            if (now - ref_date).days > days_threshold:
                fact.confidence = ConfidenceLevel.STALE
        return topic

    def _parse_json(self, text: str) -> dict:
        """Parse JSON from LLM response."""
        import re
        import json
        text = text.strip()
        match = re.search(r"```(?:json)?\n?(.*?)\n?```", text, re.DOTALL)
        if match:
            text = match.group(1).strip()
        try:
            return json.loads(text)
        except json.JSONDecodeError:
            logger.warning(f"Failed to parse JSON: {text[:100]}")
```

```
            return {}


# Backward compat alias
MemoryManager = MemoryManagerV2
```

---

10. Updated `__init__.py` with Phase 2 exports

Python

```
# memograph/__init__.py (Phase 2)

from memograph.config import ConfidenceLevel, LLMProvider, MemoGraphConfig
from memograph.core.memory_manager import MemoryManager, WriteResult
from memograph.models.index import MemoryIndex, IndexPointer
from memograph.models.topic import MemoryFact, TopicFile

# Phase 2 exports
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.core.cache import LRUCache
from memograph.strategies.eviction import (
    EvictionStrategy,
    LRUEvictionStrategy,
    CompositeEvictionStrategy,
)
from memograph.monitoring.metrics import MemoryMetrics, MetricsCollector

__version__ = "0.2.0"
__all__ = [
    "MemoGraph",
    "MemoryManager",
    "MemoGraphConfig",
    "LLMProvider",
    "ConfidenceLevel",
    "TopicFile",
    "MemoryFact",
    "MemoryIndex",
    "IndexPointer",
    "WriteResult",
    # Phase 2
    "IndexEngine",
    "TopicManager",
    "LRUCache",
    "EvictionStrategy",
    "MemoryMetrics",
    "MetricsCollector",
    "__version__",
```

```
]

# High-level facade (updated for Phase 2)
class MemoGraph:
    """Phase 2 facade with enhanced APIs."""

    def __init__(self, **kwargs):
        self._manager = MemoryManager(**kwargs)

    async def __aenter__(self):
        await self._manager.initialize()
        return self

    async def __aexit__(self, *args):
        await self._manager.close()

    # Delegate to manager
    async def remember(self, *args, **kwargs):
        return await self._manager.remember(*args, **kwargs)

    async def remember_batch(self, *args, **kwargs):
        return await self._manager.remember_batch(*args, **kwargs)

    async def recall(self, *args, **kwargs):
        return await self._manager.recall(*args, **kwargs)

    async def forget(self, *args, **kwargs):
        return await self._manager.forget(*args, **kwargs)

    async def forget_batch(self, *args, **kwargs):
        return await self._manager.forget_batch(*args, **kwargs)

    def get_context_injection(self):
        return self._manager.get_context_injection()

    async def status(self):
        return await self._manager.status()

    async def compact_index(self):
        """Manually trigger index compaction."""
        return await self._manager._index_engine.compact()

    def get_metrics(self):
        """Get performance metrics."""
        return self._manager.metrics.summary()
```

---

11. Phase 2 Tests

Python

```
# tests/test_index_engine.py
```

```python
import pytest
from memograph.core.index_engine import IndexEngine
from memograph.db.database import DatabaseManager
from memograph.config import MemoGraphConfig


@pytest.mark.asyncio
async def test_index_engine_initialization(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="test_agent",
    )
    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        engine = IndexEngine(config, db)
        index = await engine.initialize()

        assert index.agent_id == "test_agent"
        assert len(index.pointers) == 0


@pytest.mark.asyncio
async def test_add_pointer(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="test_agent",
    )
    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        engine = IndexEngine(config, db)
        await engine.initialize()

        pointer = await engine.add_pointer(
            topic_id="test_topic",
            topic_file_path="topics/test_topic.json",
            summary="A test topic",
            confidence=0.8,
        )

        assert pointer.topic_id == "test_topic"
        assert pointer.confidence == 0.8

        # Check it was persisted
        index = await engine.get_index()
        assert len(index.pointers) == 1


@pytest.mark.asyncio
async def test_index_compaction(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="test_agent",
    )
```

```
    config.limits.max_index_lines = 3  # Force small limit

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        engine = IndexEngine(config, db)
        await engine.initialize()

        # Add 5 pointers (over limit)
        for i in range(5):
            await engine.add_pointer(
                topic_id=f"topic_{i}",
                topic_file_path=f"topics/topic_{i}.json",
                summary=f"Topic {i}",
                confidence=0.5 + i * 0.1,
            )

        # Should have evicted 2 lowest-confidence pointers
        index = await engine.get_index()
        assert len(index.pointers) <= 3


# tests/test_topic_manager.py

import pytest
from memograph.core.topic_manager import TopicManager
from memograph.models.topic import MemoryFact
from memograph.config import ConfidenceLevel, MemoGraphConfig
from memograph.db.database import DatabaseManager


@pytest.mark.asyncio
async def test_topic_manager_save_and_load(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="test",
    )
    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        manager = TopicManager(config, db)

        # Add a fact
        fact = MemoryFact(
            content="Test fact",
            confidence=ConfidenceLevel.OBSERVED,
            source="test",
        )
        topic = await manager.add_fact("test_topic", fact)

        assert topic.topic_id == "test_topic"
        assert len(topic.facts) == 1

        # Reload from disk
        manager.clear_cache()
        topic2 = await manager.get_topic("test_topic")
```

```
        assert topic2 is not None
        assert len(topic2.facts) == 1
        assert topic2.facts[0].content == "Test fact"


@pytest.mark.asyncio
async def test_topic_cache(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
    )
    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        manager = TopicManager(config, db, cache_size=2)

        # Create 3 topics
        for i in range(3):
            fact = MemoryFact(
                content=f"Fact {i}",
                confidence=ConfidenceLevel.OBSERVED,
                source="test",
            )
            await manager.add_fact(f"topic_{i}", fact)

        # Access topic_0 and topic_1
        await manager.get_topic("topic_0")
        await manager.get_topic("topic_1")

        cache_stats = manager.get_cache_stats()
        assert cache_stats["size"] <= 2  # LRU limit


@pytest.mark.asyncio
async def test_batch_operations(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
    )
    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        manager = TopicManager(config, db)

        # Batch add facts
        facts = [
            MemoryFact(
                content=f"Fact {i}",
                confidence=ConfidenceLevel.OBSERVED,
                source="test",
            )
            for i in range(5)
        ]
        topic = await manager.add_facts_batch("batch_topic", facts)

        assert len(topic.facts) == 5
```

```python
# tests/test_lru_cache.py

from memograph.core.cache import LRUCache


def test_lru_basic():
    cache = LRUCache[str, int](capacity=3)

    cache.put("a", 1)
    cache.put("b", 2)
    cache.put("c", 3)

    assert cache.get("a") == 1
    assert cache.get("b") == 2
    assert cache.size == 3


def test_lru_eviction():
    cache = LRUCache[str, int](capacity=2)

    cache.put("a", 1)
    cache.put("b", 2)
    cache.put("c", 3)  # Should evict "a"

    assert cache.get("a") is None
    assert cache.get("b") == 2
    assert cache.get("c") == 3


def test_lru_update():
    cache = LRUCache[str, int](capacity=2)

    cache.put("a", 1)
    cache.put("b", 2)

    # Access "a" (moves to end)
    cache.get("a")

    # Add "c" — should evict "b", not "a"
    cache.put("c", 3)

    assert cache.get("a") == 1
    assert cache.get("b") is None
    assert cache.get("c") == 3


# tests/test_validation.py

import pytest
from memograph.utils.validation import (
    validate_topic_id,
    validate_fact_content,
    normalize_topic_id,
)


def test_validate_topic_id_valid():
    validate_topic_id("project_tech_stack")
```

```
    validate_topic_id("user_preferences")
    validate_topic_id("a")
    validate_topic_id("a123_456")


def test_validate_topic_id_invalid():
    with pytest.raises(ValueError):
        validate_topic_id("")  # Empty

    with pytest.raises(ValueError):
        validate_topic_id("123_topic")  # Starts with number

    with pytest.raises(ValueError):
        validate_topic_id("Topic-With-Dashes")  # Has dashes

    with pytest.raises(ValueError):
        validate_topic_id("x" * 51)  # Too long


def test_normalize_topic_id():
    assert normalize_topic_id("Project Tech Stack") == "project_tech_stack"
    assert normalize_topic_id("User Preferences (Dark Mode)") == "user_preferences_dark_mode"
    assert normalize_topic_id("  Multiple   Spaces  ") == "multiple_spaces"
    assert normalize_topic_id("123-Start-With-Number") == "topic_123_start_with_number"


def test_validate_fact_content():
    validate_fact_content("A valid fact")
    validate_fact_content("x" * 1000)  # Max length

    with pytest.raises(ValueError):
        validate_fact_content("")  # Empty

    with pytest.raises(ValueError):
        validate_fact_content("   ")  # Whitespace only

    with pytest.raises(ValueError):
        validate_fact_content("x" * 1001)  # Too long


# tests/test_eviction_strategies.py

from datetime import datetime, timedelta
from memograph.models.index import IndexPointer
from memograph.strategies.eviction import (
    LRUEvictionStrategy,
    LFUEvictionStrategy,
    ConfidenceEvictionStrategy,
    CompositeEvictionStrategy,
)


def test_lru_eviction():
    strategy = LRUEvictionStrategy()

    pointers = [
        IndexPointer(
            topic_id="recent",
```

```
            topic_file_path="topics/recent.json",
            summary="Recent",
            confidence=0.8,
            last_accessed=datetime.now(),
        ),
        IndexPointer(
            topic_id="old",
            topic_file_path="topics/old.json",
            summary="Old",
            confidence=0.8,
            last_accessed=datetime.now() - timedelta(days=30),
        ),
    ]

    victim = strategy.select_victim(pointers)
    assert victim.topic_id == "old"


def test_lfu_eviction():
    strategy = LFUEvictionStrategy()

    pointers = [
        IndexPointer(
            topic_id="frequent",
            topic_file_path="topics/frequent.json",
            summary="Frequent",
            confidence=0.8,
            access_count=100,
        ),
        IndexPointer(
            topic_id="rare",
            topic_file_path="topics/rare.json",
            summary="Rare",
            confidence=0.8,
            access_count=5,
        ),
    ]

    victim = strategy.select_victim(pointers)
    assert victim.topic_id == "rare"


def test_confidence_eviction():
    strategy = ConfidenceEvictionStrategy()

    pointers = [
        IndexPointer(
            topic_id="high_conf",
            topic_file_path="topics/high.json",
            summary="High",
            confidence=0.9,
        ),
        IndexPointer(
            topic_id="low_conf",
            topic_file_path="topics/low.json",
            summary="Low",
            confidence=0.3,
        ),
```

```
    ]

    victim = strategy.select_victim(pointers)
    assert victim.topic_id == "low_conf"


def test_composite_eviction():
    strategy = CompositeEvictionStrategy()

    pointers = [
        IndexPointer(
            topic_id="best",
            topic_file_path="topics/best.json",
            summary="Best",
            confidence=0.9,
            access_count=100,
            last_accessed=datetime.now(),
        ),
        IndexPointer(
            topic_id="worst",
            topic_file_path="topics/worst.json",
            summary="Worst",
            confidence=0.2,
            access_count=1,
            last_accessed=datetime.now() - timedelta(days=60),
        ),
    ]

    victim = strategy.select_victim(pointers)
    assert victim.topic_id == "worst"
```

---

12. Phase 2 Example

Python

```
# examples/phase2_demo.py
"""
Phase 2 Demo — showcasing new features:
- Batch operations
- Index compaction
- Cache performance
- Metrics tracking
"""

import asyncio
from memograph import MemoGraph, ConfidenceLevel


async def main():
    async with MemoGraph(
        provider="ollama",
        model="llama3.1:8b",
```

```
        agent_id="phase2_demo",
    ) as mg:

        print("=== Phase 2 Demo ===\n")

        # 1. Batch remember
        print("1. Batch remember (10 facts)")
        facts = [
            {
                "topic_id": f"topic_{i}",
                "content": f"Fact number {i} about the project",
                "source": "demo",
                "confidence": ConfidenceLevel.OBSERVED,
            }
            for i in range(10)
        ]
        results = await mg.remember_batch(facts)
        print(f"   Stored {sum(1 for r in results if r.success)} facts\n")

        # 2. Recall with caching
        print("2. Recall (should hit cache on second call)")
        topics1 = await mg.recall("topic", top_k=5)
        print(f"   First call: loaded {len(topics1)} topics")

        topics2 = await mg.recall("topic", top_k=5)
        print(f"   Second call: loaded {len(topics2)} topics (cached)\n")

        # 3. Index metrics
        print("3. Index metrics")
        status = await mg.status()
        print(f"   Pointers: {status['index']['pointer_count']}")
        print(f"   Usage: {status['index']['usage_ratio']:.1%}")
        print(f"   Stale: {status['index']['stale_count']}\n")

        # 4. Cache stats
        print("4. Cache performance")
        cache_stats = status['topics']['cache']
        print(f"   Hit rate: {cache_stats['hit_rate']:.1%}")
        print(f"   Size: {cache_stats['size']}/{cache_stats['capacity']}\n")

        # 5. Manual compaction
        print("5. Manual index compaction")
        before = status['index']['pointer_count']
        compaction_result = await mg.compact_index()
        after = compaction_result['after_count']
        print(f"   Before: {before} pointers")
        print(f"   After: {after} pointers")
        print(f"   Removed: {compaction_result['removed_orphans']} orphans\n")

        # 6. Performance metrics
        print("6. Performance metrics")
        metrics = mg.get_metrics()
        if metrics['timing_summary']:
            for op, stats in metrics['timing_summary'].items():
                print(f"   {op}: {stats['avg_ms']:.1f}ms avg")

        # 7. Batch forget
        print("\n7. Batch forget")
```

```
        deleted = await mg.forget_batch(["topic_0", "topic_1", "topic_2"])
        print(f"   Deleted {deleted} topics")

        # Final status
        final_status = await mg.status()
        print(f"\n=== Final Stats ===")
        print(f"Topics: {final_status['topics']['topic_count']}")
        print(f"Facts: {final_status['topics']['total_facts']}")
        print(f"Cache hit rate: {final_status['topics']['cache']['hit_rate']:.1%}")


if __name__ == "__main__":
    asyncio.run(main())
```

📊 Phase 2 Completion Checklist

Component	Status
`IndexEngine` with auto-compaction	✅
`TopicManager` with LRU cache	✅
`LRUCache` generic implementation	✅
Eviction strategies (LRU/LFU/Confidence/Composite)	✅
Index compaction logic	✅
Atomic file operations	✅
Validation helpers + `normalize_topic_id()`	✅

Conflict detection via file hashing	✅
Batch operations (`remember_batch`, `forget_batch`)	✅
Performance metrics tracking	✅
`MetricsCollector` with timing/snapshots	✅
Enhanced `MemoryManager` (V2)	✅
Full test suite for Phase 2 components	✅
Phase 2 demo example	✅

🚀 Run Phase 2

Bash

```bash
# Install with dev dependencies
pip install -e ".[dev]"

# Run Phase 2 tests
pytest tests/test_index_engine.py -v
pytest tests/test_topic_manager.py -v
pytest tests/test_lru_cache.py -v
pytest tests/test_eviction_strategies.py -v
pytest tests/test_validation.py -v

# Run full test suite
pytest tests/ -v --cov=memograph

# Run Phase 2 demo
python examples/phase2_demo.py
```

🌙 PHASE 3 — AUTODREAM CONSOLIDATION DAEMON

Complete, runnable implementation of the self-healing consolidation system — the heart of MemoGraph.

📋 Phase 3 Scope

Component	Description
ConsolidationGates	Triple-gate system: scan interval → time → sessions → lock
ConsolidationLock	mtime-based advisory file lock with PID tracking and rollback
DreamOrientPhase	Phase 1: Read index, skim topics, inventory signal sources

DreamGatherPhase	Phase 2: Collect new signal from logs, drifted memories, transcript grep
DreamConsolidatePhase	Phase 3: LLM-driven merge, contradiction resolution, confidence promotion
DreamPrunePhase	Phase 4: Enforce limits, remove orphans, rebuild index
DreamEngine	Orchestrates all 4 phases with full audit trail
ConsolidationDaemon	Async background loop with graceful shutdown
DreamScheduler	Configurable scheduling (interval, cron-like, manual trigger)
Full test suite	Unit + integration tests for every component

New Files (Phase 3)

```
text
```

```
memograph/
├── consolidation/
│   ├── __init__.py
│   ├── gates.py              # Triple-gate system
│   ├── lock.py               # Advisory file lock
│   ├── phases/
│   │   ├── __init__.py
│   │   ├── base.py           # Base phase class
│   │   ├── orient.py         # Phase 1: Orient
│   │   ├── gather.py         # Phase 2: Gather
│   │   ├── consolidate.py    # Phase 3: Consolidate
│   │   └── prune.py          # Phase 4: Prune
│   ├── dream_engine.py       # Orchestrator
│   ├── daemon.py             # Background daemon
│   └── scheduler.py          # Scheduling strategies
├── prompts/
│   └── consolidation_prompts.py  # Phase 3 LLM prompts
```

```
└── tests/
    ├── test_gates.py
    ├── test_lock.py
    ├── test_dream_engine.py
    ├── test_daemon.py
    └── test_consolidation_integration.py
```

---

1. Database Schema — Phase 3 Additions

SQL

```sql
-- memograph/db/migrations/002_consolidation.sql
-- Migration 002: Consolidation audit trail + dream state

-- ═══════════════════════════════════════════════════════════════
-- DREAM RUNS
-- Full audit trail for every consolidation run.
-- ═══════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS dream_runs (
    id                      INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id                TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    run_id                  TEXT    NOT NULL,

    -- Lifecycle
    status                  TEXT    NOT NULL DEFAULT 'running',
                                        -- running|completed|failed|skipped|aborted
    trigger                 TEXT    NOT NULL DEFAULT 'daemon',
                                       -- daemon|manual|api|forced
    started_at              TEXT    NOT NULL DEFAULT (datetime('now')),
    ended_at                TEXT,
    duration_ms             INTEGER NOT NULL DEFAULT 0,

    -- Gate results (JSON)
    gate_scan_interval      INTEGER NOT NULL DEFAULT 0,  -- 0=failed, 1=passed
    gate_time               INTEGER NOT NULL DEFAULT 0,
    gate_sessions           INTEGER NOT NULL DEFAULT 0,
    gate_lock               INTEGER NOT NULL DEFAULT 0,
    gate_skip_reason        TEXT,                        -- Why gates failed

    -- Phase results (JSON)
    phase_orient_result     TEXT    NOT NULL DEFAULT '{}',
    phase_gather_result     TEXT    NOT NULL DEFAULT '{}',
    phase_consolidate_result TEXT   NOT NULL DEFAULT '{}',
    phase_prune_result      TEXT    NOT NULL DEFAULT '{}',

    -- Outcomes
    facts_merged            INTEGER NOT NULL DEFAULT 0,
    facts_created           INTEGER NOT NULL DEFAULT 0,
```

```
    facts_pruned            INTEGER NOT NULL DEFAULT 0,
    contradictions_resolved INTEGER NOT NULL DEFAULT 0,
    pointers_pruned         INTEGER NOT NULL DEFAULT 0,
    confidence_promoted     INTEGER NOT NULL DEFAULT 0,

    -- LLM usage
    llm_provider            TEXT,
    llm_model               TEXT,
    llm_prompt_tokens       INTEGER NOT NULL DEFAULT 0,
    llm_completion_tokens   INTEGER NOT NULL DEFAULT 0,
    llm_latency_ms          INTEGER NOT NULL DEFAULT 0,

    -- Error info
    error_message           TEXT,
    error_phase             TEXT,   -- Which phase failed

    UNIQUE(agent_id, run_id)
);

CREATE INDEX IF NOT EXISTS idx_dream_runs_agent
    ON dream_runs(agent_id, started_at DESC);

CREATE INDEX IF NOT EXISTS idx_dream_runs_status
    ON dream_runs(agent_id, status);

-- ═══════════════════════════════════════════════════════════════════════
-- DREAM OPERATIONS
-- Individual operations performed during a dream run.
-- One row per merge/resolve/promote/prune action.
-- ═══════════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS dream_operations (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    run_id              TEXT    NOT NULL,
    operation_id        TEXT    NOT NULL,

    action              TEXT    NOT NULL,
                                -- merge|resolve_contradiction|promote|prune|create
    topic_id            TEXT    NOT NULL,
    fact_ids_input      TEXT    NOT NULL DEFAULT '[]',   -- JSON array
    fact_id_output      TEXT,
    content_before      TEXT,
    content_after       TEXT,
    confidence_before   TEXT,
    confidence_after    TEXT,
    reasoning           TEXT,
    applied             INTEGER NOT NULL DEFAULT 0,       -- Was it actually applied?
    apply_error         TEXT,

    created_at          TEXT    NOT NULL DEFAULT (datetime('now')),

    UNIQUE(agent_id, run_id, operation_id)
);

CREATE INDEX IF NOT EXISTS idx_dream_ops_run
    ON dream_operations(agent_id, run_id);

CREATE INDEX IF NOT EXISTS idx_dream_ops_topic
```

```
    ON dream_operations(agent_id, topic_id);

-- ─────────────────────────────────────────────────────────────────────────────
-- DREAM STATE
-- Tracks daemon state and last consolidation per agent.
-- ─────────────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS dream_state (
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    last_run_id         TEXT,
    last_consolidated_at TEXT,
    last_sessions_at    TEXT,           -- Timestamp of last session counted
    sessions_since_last INTEGER NOT NULL DEFAULT 0,
    total_runs          INTEGER NOT NULL DEFAULT 0,
    daemon_pid          INTEGER,
    daemon_started_at   TEXT,

    PRIMARY KEY(agent_id)
);

INSERT OR IGNORE INTO schema_version(version, description)
VALUES (2, 'Phase 3: dream_runs, dream_operations, dream_state tables');
```

---

2. Database Manager — Phase 3 Methods

```
Python


# memograph/db/database.py  (Phase 3 additions — append to existing class)

    # ─────────────────────────────────────────────────────────────────────────
    # DREAM STATE
    # ─────────────────────────────────────────────────────────────────────────

    async def get_dream_state(self, agent_id: str) -> Optional[dict]:
        return await self.fetchone(
            "SELECT * FROM dream_state WHERE agent_id = ?",
            (agent_id,),
        )

    async def upsert_dream_state(
        self,
        agent_id:             str,
        last_run_id:          Optional[str]  = None,
        last_consolidated_at: Optional[str]  = None,
        sessions_since_last:  Optional[int]  = None,
        daemon_pid:           Optional[int]  = None,
        daemon_started_at:    Optional[str]  = None,
    ) -> None:
        """Upsert only provided fields — leave others unchanged."""
```

```
        # Build dynamic update
        updates: list[str] = []
        params:  list      = []

        if last_run_id is not None:
            updates.append("last_run_id = ?")
            params.append(last_run_id)

        if last_consolidated_at is not None:
            updates.append("last_consolidated_at = ?")
            params.append(last_consolidated_at)

        if sessions_since_last is not None:
            updates.append("sessions_since_last = ?")
            params.append(sessions_since_last)

        if daemon_pid is not None:
            updates.append("daemon_pid = ?")
            params.append(daemon_pid)

        if daemon_started_at is not None:
            updates.append("daemon_started_at = ?")
            params.append(daemon_started_at)

        if not updates:
            return

        params.append(agent_id)
        update_sql = ", ".join(updates)

        await self.execute(
            f"""
            INSERT INTO dream_state(agent_id) VALUES(?)
            ON CONFLICT(agent_id) DO UPDATE SET {update_sql}
            """,
            (agent_id, *[p for p in params[:-1]]),
        )

    async def increment_dream_run_count(self, agent_id: str) -> None:
        await self.execute(
            """
            INSERT INTO dream_state(agent_id, total_runs)
            VALUES(?, 1)
            ON CONFLICT(agent_id) DO UPDATE
            SET total_runs = total_runs + 1
            """,
            (agent_id,),
        )

    # ──────────────────────────────────────────────────────────────────────
    # DREAM RUNS
    # ──────────────────────────────────────────────────────────────────────

    async def create_dream_run(
        self,
        agent_id:  str,
        run_id:    str,
        trigger:   str = "daemon",
```

```
    ) -> None:
        await self.execute(
            """
            INSERT INTO dream_runs(agent_id, run_id, trigger)
            VALUES(?, ?, ?)
            """,
            (agent_id, run_id, trigger),
        )

    async def update_dream_run(
        self,
        agent_id:                 str,
        run_id:                   str,
        status:                   Optional[str]  = None,
        ended_at:                 Optional[str]  = None,
        duration_ms:              Optional[int]  = None,
        gate_scan_interval:       Optional[int]  = None,
        gate_time:                Optional[int]  = None,
        gate_sessions:            Optional[int]  = None,
        gate_lock:                Optional[int]  = None,
        gate_skip_reason:         Optional[str]  = None,
        phase_orient_result:      Optional[str]  = None,
        phase_gather_result:      Optional[str]  = None,
        phase_consolidate_result: Optional[str]  = None,
        phase_prune_result:       Optional[str]  = None,
        facts_merged:             Optional[int]  = None,
        facts_created:            Optional[int]  = None,
        facts_pruned:             Optional[int]  = None,
        contradictions_resolved:  Optional[int]  = None,
        pointers_pruned:          Optional[int]  = None,
        confidence_promoted:      Optional[int]  = None,
        llm_provider:             Optional[str]  = None,
        llm_model:                Optional[str]  = None,
        llm_prompt_tokens:        Optional[int]  = None,
        llm_completion_tokens:    Optional[int]  = None,
        llm_latency_ms:           Optional[int]  = None,
        error_message:            Optional[str]  = None,
        error_phase:              Optional[str]  = None,
    ) -> None:
        fields = {
            "status":                   status,
            "ended_at":                 ended_at,
            "duration_ms":              duration_ms,
            "gate_scan_interval":       gate_scan_interval,
            "gate_time":                gate_time,
            "gate_sessions":            gate_sessions,
            "gate_lock":                gate_lock,
            "gate_skip_reason":         gate_skip_reason,
            "phase_orient_result":      phase_orient_result,
            "phase_gather_result":      phase_gather_result,
            "phase_consolidate_result": phase_consolidate_result,
            "phase_prune_result":       phase_prune_result,
            "facts_merged":             facts_merged,
            "facts_created":            facts_created,
            "facts_pruned":             facts_pruned,
            "contradictions_resolved":  contradictions_resolved,
            "pointers_pruned":          pointers_pruned,
            "confidence_promoted":      confidence_promoted,
```

```
            "llm_provider":              llm_provider,
            "llm_model":                 llm_model,
            "llm_prompt_tokens":         llm_prompt_tokens,
            "llm_completion_tokens":     llm_completion_tokens,
            "llm_latency_ms":            llm_latency_ms,
            "error_message":             error_message,
            "error_phase":               error_phase,
        }

        updates  = [(k, v) for k, v in fields.items() if v is not None]
        if not updates:
            return

        set_clause = ", ".join(f"{k} = ?" for k, _ in updates)
        values     = [v for _, v in updates] + [agent_id, run_id]

        await self.execute(
            f"UPDATE dream_runs SET {set_clause} WHERE agent_id = ? AND run_id = ?",
            tuple(values),
        )

    async def get_dream_runs(
        self,
        agent_id: str,
        limit:    int = 20,
        status:   Optional[str] = None,
    ) -> list[dict]:
        if status:
            return await self.fetchall(
                """
                SELECT * FROM dream_runs
                WHERE agent_id = ? AND status = ?
                ORDER BY started_at DESC LIMIT ?
                """,
                (agent_id, status, limit),
            )
        return await self.fetchall(
            """
            SELECT * FROM dream_runs
            WHERE agent_id = ?
            ORDER BY started_at DESC LIMIT ?
            """,
            (agent_id, limit),
        )

    async def get_dream_run(self, agent_id: str, run_id: str) -> Optional[dict]:
        return await self.fetchone(
            "SELECT * FROM dream_runs WHERE agent_id = ? AND run_id = ?",
            (agent_id, run_id),
        )

    # ──────────────────────────────────────────────────────────────────────
    # DREAM OPERATIONS
    # ──────────────────────────────────────────────────────────────────────

    async def insert_dream_operation(
        self,
        agent_id:         str,
```

```
        run_id:            str,
        operation_id:      str,
        action:            str,
        topic_id:          str,
        fact_ids_input:    list        = None,
        fact_id_output:    Optional[str] = None,
        content_before:    Optional[str] = None,
        content_after:     Optional[str] = None,
        confidence_before: Optional[str] = None,
        confidence_after:  Optional[str] = None,
        reasoning:         Optional[str] = None,
        applied:           bool        = False,
        apply_error:       Optional[str] = None,
    ) -> None:
        await self.execute(
            """
            INSERT OR REPLACE INTO dream_operations(
                agent_id, run_id, operation_id, action, topic_id,
                fact_ids_input, fact_id_output, content_before,
                content_after, confidence_before, confidence_after,
                reasoning, applied, apply_error
            ) VALUES (?,?,?,?,?,?,?,?,?,?,?,?,?,?)
            """,
            (
                agent_id, run_id, operation_id, action, topic_id,
                json.dumps(fact_ids_input or []),
                fact_id_output, content_before, content_after,
                confidence_before, confidence_after,
                reasoning, int(applied), apply_error,
            ),
        )

    async def get_dream_operations(
        self, agent_id: str, run_id: str
    ) -> list[dict]:
        return await self.fetchall(
            """
            SELECT * FROM dream_operations
            WHERE agent_id = ? AND run_id = ?
            ORDER BY created_at ASC
            """,
            (agent_id, run_id),
        )
```

---

3. Consolidation Prompts

Python

```
# memograph/prompts/consolidation_prompts.py
"""
Detailed consolidation prompts for each dream phase.
These mirror the intent of src/services/autoDream/consolidationPrompt.ts
```

```
from the Claude Code source.
"""

from __future__ import annotations

from typing import Optional


# ─────────────────────────────────────────────────────────────────────────
# PHASE 2 — GATHER: SIGNAL EXTRACTION
# Used to extract worthwhile signals from recent transcripts.
# ─────────────────────────────────────────────────────────────────────────
GATHER_SIGNAL_SYSTEM = """\
You are the MemoGraph Gather phase agent.
Your job is to scan recent session transcripts and identify
observations worth persisting in long-term memory.

## What to Look For
- Decisions made (architectural, user preferences, process choices)
- Patterns that recurred across multiple sessions
- Problems solved (especially non-obvious solutions)
- Constraints discovered ("never do X because Y")
- Important facts confirmed by the user
- Things the agent got wrong that needed correction

## What to IGNORE
- Small talk, greetings, closings
- Transient state (what page user is on, current file open)
- Things already in memory (check the index first)
- Ephemeral todos that are now done
- Error messages without context

## Output Format — JSON only, no prose.
{
  "signals": [
    {
      "topic_id": "snake_case_id",
      "topic_name": "Human readable",
      "content": "Concrete fact (≤200 chars)",
      "confidence": "observed|inferred",
      "source": "session_transcript",
      "tags": ["tag1"],
      "reasoning": "Why this is worth remembering"
    }
  ],
  "skipped_count": 5,
  "skip_reasons": ["Transient state", "Already in memory"]
}
"""


GATHER_SIGNAL_USER = """\
## Current Memory Index
{index_markdown}

## Recent Transcript Excerpts
{transcript_excerpts}
```

```
## Previously Identified Signals (this run)
{prior_signals}

Extract any new signals from the transcripts not already captured
in the memory index or prior signals.
"""


# ──────────────────────────────────────────────────────────────────────
# PHASE 3 — CONSOLIDATE: MERGE & RESOLVE
# The main consolidation prompt. One topic at a time.
# ──────────────────────────────────────────────────────────────────────
CONSOLIDATE_TOPIC_SYSTEM = """\
You are the MemoGraph Consolidation phase agent.
You are performing a focused consolidation pass on a single memory topic.

## Your Tasks (in order)

### 1. MERGE
Combine facts that describe the same thing from different angles.
Keep the most complete, accurate version.
Example:
  - "User prefers dark mode (observed, 3 months ago)"
  - "User confirmed dark mode preference (observed, today)"
  → "User confirmed dark mode preference (verified)"

### 2. RESOLVE CONTRADICTIONS
When facts conflict, keep the most recent + most verified one.
Document what changed and why.
Example:
  - "Database is PostgreSQL (observed)"
  - "Migrated from PostgreSQL to CockroachDB (observed, newer)"
  → "Database is CockroachDB, migrated from PostgreSQL (verified)"

### 3. PROMOTE CONFIDENCE
If multiple independent facts support an inferred/observed claim,
promote it to a higher confidence level.
  inferred → observed: at least 2 independent corroborating facts
  observed → verified: direct confirmation from user or primary source

### 4. PRUNE
Remove facts that are:
  - Directly re-derivable from accessible code/config
  - Superseded by newer facts in this same pass
  - Ephemeral (time-sensitive, no longer relevant)
  - Noise (observations with zero decision-making value)

## Critical Rules
- Maximum 10 operations per topic
- Prefer conservative actions — when uncertain, leave it
- NEVER create facts about the consolidation process itself
- Keep all content ≤200 chars
- Output JSON only — no prose, no markdown

## Output Format
{
  "topic_id": "...",
  "operations": [
```

```
    {
      "action": "merge",
      "fact_ids": ["id1", "id2"],
      "merged_content": "Unified fact (≤200 chars)",
      "merged_confidence": "verified|observed|inferred",
      "reasoning": "Brief explanation"
    },
    {
      "action": "resolve_contradiction",
      "keep_fact_id": "id1",
      "discard_fact_id": "id2",
      "updated_content": "Resolved fact (≤200 chars)",
      "reasoning": "Kept id1 because it is newer and verified"
    },
    {
      "action": "promote",
      "fact_id": "id1",
      "new_confidence": "verified|observed",
      "reasoning": "3 independent sources confirm this"
    },
    {
      "action": "prune",
      "fact_id": "id1",
      "reasoning": "Re-derivable from codebase / ephemeral / superseded"
    }
  ],
  "no_changes_needed": false,
  "summary": "One sentence describing what changed"
}
"""


CONSOLIDATE_TOPIC_USER = """\
## Topic: {topic_name} (ID: {topic_id})
Tags: {tags}
Facts: {fact_count}

## Current Facts
{facts_markdown}

## New Signals to Integrate (from Gather phase)
{new_signals}

Consolidate this topic.
"""


# ──────────────────────────────────────────────────────────────────────────────
# PHASE 4 — PRUNE: INDEX MAINTENANCE
# ──────────────────────────────────────────────────────────────────────────────
PRUNE_INDEX_SYSTEM = """\
You are the MemoGraph Prune phase agent.
Your job is to review the memory index and identify pointers that
should be removed or marked stale.

## Remove a pointer if:
- The topic file no longer exists (orphaned)
- The topic has 0 facts remaining after consolidation
```

```
- The topic contains only ephemeral/time-sensitive facts

## Mark stale if:
- The topic has not been accessed in > 30 days
- The last update was > 60 days ago
- The topic's average confidence is below 0.3

## Output Format — JSON only.
{
  "remove_topic_ids": ["id1", "id2"],
  "mark_stale_topic_ids": ["id3", "id4"],
  "keep_topic_ids": ["id5", "id6"],
  "reasoning": {
    "id1": "No topic file exists (orphaned)",
    "id3": "Not accessed in 45 days"
  }
}
"""


PRUNE_INDEX_USER = """\
## Current Memory Index
{index_markdown}

## Topic File Status
{topic_file_status}

## Topics with Zero Facts (post-consolidation)
{empty_topics}

Review the index and recommend removals/staleness marks.
"""


def build_gather_prompt(
    index_markdown:    str,
    transcript_excerpts: str,
    prior_signals:     str = "None yet",
) -> str:
    return GATHER_SIGNAL_USER.format(
        index_markdown=index_markdown,
        transcript_excerpts=transcript_excerpts[:8000],  # Token budget
        prior_signals=prior_signals,
    )


def build_consolidate_prompt(
    topic_id:    str,
    topic_name:  str,
    tags:        list[str],
    fact_count:  int,
    facts_markdown: str,
    new_signals: str = "None",
) -> str:
    return CONSOLIDATE_TOPIC_USER.format(
        topic_id=topic_id,
        topic_name=topic_name,
        tags=", ".join(tags) or "none",
```

```
        fact_count=fact_count,
        facts_markdown=facts_markdown[:6000],  # Token budget
        new_signals=new_signals[:2000],
    )


def build_prune_prompt(
    index_markdown:    str,
    topic_file_status: str,
    empty_topics:      str = "None",
) -> str:
    return PRUNE_INDEX_USER.format(
        index_markdown=index_markdown,
        topic_file_status=topic_file_status[:4000],
        empty_topics=empty_topics,
    )
```

---

4. Consolidation Gates

Python

```
# memograph/consolidation/gates.py
"""
Triple-gate system for consolidation.
Gates run cheapest-first. All must pass before consolidation runs.

Gate 0 — Scan interval:  Don't check more than once per N minutes
Gate 1 — Time elapsed:   At least N hours since last consolidation
Gate 2 — Session count:  At least N new sessions accumulated
Gate 3 — Lock available: Advisory lock file is free

Inspired directly by the autoDream gate logic in the leaked source.
"""

from __future__ import annotations

import logging
from dataclasses import dataclass, field
from datetime import datetime, timedelta
from typing import Optional

logger = logging.getLogger("memograph.gates")


@dataclass
class GateResult:
    """Result of a single gate check."""
    gate_name:    str
    passed:       bool
    reason:       str
    checked_at:   datetime = field(default_factory=datetime.now)
    value:        Optional[float] = None   # The measured value (for logging)
```

```
    threshold:    Optional[float] = None   # The threshold it was compared to


@dataclass
class GateReport:
    """Full report from running all gates."""
    all_passed:   bool
    results:      list[GateResult]
    checked_at:   datetime = field(default_factory=datetime.now)

    def first_failure(self) -> Optional[GateResult]:
        return next((r for r in self.results if not r.passed), None)

    def summary(self) -> str:
        if self.all_passed:
            return "All gates passed ✅"
        failure = self.first_failure()
        return f"Blocked at gate '{failure.gate_name}': {failure.reason}"

    def to_dict(self) -> dict:
        return {
            "all_passed": self.all_passed,
            "checked_at": self.checked_at.isoformat(),
            "results": [
                {
                    "gate":      r.gate_name,
                    "passed":    r.passed,
                    "reason":    r.reason,
                    "value":     r.value,
                    "threshold": r.threshold,
                }
                for r in self.results
            ],
        }


class ConsolidationGates:
    """
    Triple-gate guard for the consolidation daemon.
    Cheapest checks run first to minimize overhead.

    Usage:
        gates = ConsolidationGates(min_hours=24, min_sessions=5)
        report = await gates.check_all(
            last_consolidated=last_dt,
            session_count=12,
            lock_available=True,
        )
        if report.all_passed:
            await dream_engine.run()
    """

    def __init__(
        self,
        min_hours:             int   = 24,
        min_sessions:          int   = 5,
        scan_interval_minutes: int   = 10,
        force_mode:            bool  = False,  # Skip time/session gates (manual trigger)
```

```
    ):
        self.min_hours              = min_hours
        self.min_sessions           = min_sessions
        self.scan_interval          = timedelta(minutes=scan_interval_minutes)
        self.force_mode             = force_mode

        # Mutable state
        self._last_scan: Optional[datetime] = None

    # ─────────────────────────────────────────────────────────────────────
    # INDIVIDUAL GATES
    # ─────────────────────────────────────────────────────────────────────

    def check_scan_interval(self) -> GateResult:
        """
        Gate 0: Scan interval guard.
        Prevents the daemon from checking more than once per N minutes.
        Cheapest possible check — pure in-memory comparison.
        """
        if self.force_mode:
            return GateResult(
                gate_name="scan_interval",
                passed=True,
                reason="Force mode — scan interval bypassed",
            )

        now = datetime.now()

        if self._last_scan is None:
            self._last_scan = now
            return GateResult(
                gate_name="scan_interval",
                passed=True,
                reason="First check — no prior scan",
            )

        elapsed = now - self._last_scan
        remaining = self.scan_interval - elapsed

        if elapsed < self.scan_interval:
            return GateResult(
                gate_name="scan_interval",
                passed=False,
                reason=(
                    f"Too soon — {elapsed.seconds}s elapsed, "
                    f"need {self.scan_interval.seconds}s. "
                    f"Retry in {remaining.seconds}s"
                ),
                value=elapsed.total_seconds(),
                threshold=self.scan_interval.total_seconds(),
            )

        self._last_scan = now
        return GateResult(
            gate_name="scan_interval",
            passed=True,
            reason=f"Scan interval elapsed ({elapsed.seconds}s)",
            value=elapsed.total_seconds(),
```

```
            threshold=self.scan_interval.total_seconds(),
        )

    def check_time_gate(
        self,
        last_consolidated: Optional[datetime],
    ) -> GateResult:
        """
        Gate 1: Time elapsed since last consolidation.
        Prevents running consolidation too frequently.
        """
        if self.force_mode:
            return GateResult(
                gate_name="time_elapsed",
                passed=True,
                reason="Force mode — time gate bypassed",
            )

        if last_consolidated is None:
            return GateResult(
                gate_name="time_elapsed",
                passed=True,
                reason="Never consolidated — proceed immediately",
                value=None,
                threshold=float(self.min_hours),
            )

        elapsed = datetime.now() - last_consolidated
        elapsed_hours = elapsed.total_seconds() / 3600
        remaining_hours = max(0.0, self.min_hours - elapsed_hours)

        if elapsed_hours < self.min_hours:
            return GateResult(
                gate_name="time_elapsed",
                passed=False,
                reason=(
                    f"Only {elapsed_hours:.1f}h since last consolidation. "
                    f"Need {self.min_hours}h. "
                    f"Retry in ~{remaining_hours:.1f}h"
                ),
                value=elapsed_hours,
                threshold=float(self.min_hours),
            )

        return GateResult(
            gate_name="time_elapsed",
            passed=True,
            reason=f"{elapsed_hours:.1f}h elapsed since last consolidation",
            value=elapsed_hours,
            threshold=float(self.min_hours),
        )

    def check_session_gate(self, session_count: int) -> GateResult:
        """
        Gate 2: Minimum new sessions since last consolidation.
        Ensures there's enough new signal to justify running.
        """
        if self.force_mode:
```

```
            return GateResult(
                gate_name="session_count",
                passed=True,
                reason="Force mode — session gate bypassed",
            )

        if session_count >= self.min_sessions:
            return GateResult(
                gate_name="session_count",
                passed=True,
                reason=(
                    f"{session_count} sessions accumulated "
                    f"(threshold: {self.min_sessions})"
                ),
                value=float(session_count),
                threshold=float(self.min_sessions),
            )

        needed = self.min_sessions - session_count
        return GateResult(
            gate_name="session_count",
            passed=False,
            reason=(
                f"Only {session_count}/{self.min_sessions} sessions accumulated. "
                f"Need {needed} more"
            ),
            value=float(session_count),
            threshold=float(self.min_sessions),
        )

    def check_lock_gate(self, lock_available: bool) -> GateResult:
        """
        Gate 3: Advisory lock is available.
        Prevents two consolidation runs from running simultaneously.
        """
        if lock_available:
            return GateResult(
                gate_name="lock",
                passed=True,
                reason="Lock is available",
            )

        return GateResult(
            gate_name="lock",
            passed=False,
            reason=(
                "Consolidation lock is held by another process. "
                "Another dream run may be in progress"
            ),
        )

    # ------------------------------------------------------------------
    # FULL CHECK
    # ------------------------------------------------------------------

    def check_all(
        self,
        last_consolidated: Optional[datetime],
```

```
        session_count:     int,
        lock_available:    bool,
    ) -> GateReport:
        """
        Run all gates in order (cheapest first).
        Short-circuits on first failure.

        Returns GateReport with detailed results.
        """
        results: list[GateResult] = []

        # Gate 0: Scan interval (pure in-memory, no I/O)
        g0 = self.check_scan_interval()
        results.append(g0)
        if not g0.passed:
            return GateReport(all_passed=False, results=results)

        # Gate 1: Time elapsed (datetime comparison)
        g1 = self.check_time_gate(last_consolidated)
        results.append(g1)
        if not g1.passed:
            return GateReport(all_passed=False, results=results)

        # Gate 2: Session count (DB read — caller provides)
        g2 = self.check_session_gate(session_count)
        results.append(g2)
        if not g2.passed:
            return GateReport(all_passed=False, results=results)

        # Gate 3: Lock check (filesystem stat)
        g3 = self.check_lock_gate(lock_available)
        results.append(g3)
        if not g3.passed:
            return GateReport(all_passed=False, results=results)

        return GateReport(all_passed=True, results=results)

    def reset_scan_timer(self) -> None:
        """Force-reset the scan interval (useful after forced run)."""
        self._last_scan = None

    @classmethod
    def forced(cls) -> "ConsolidationGates":
        """Create a gates instance that bypasses time/session/scan checks."""
        return cls(force_mode=True)
```

---

5. Consolidation Lock

Python

```
# memograph/consolidation/lock.py
"""
```

```
Advisory file-based consolidation lock.

Design (mirroring consolidationLock.ts from the leaked source):
- Lock file path: {base_path}/consolidation.lock
- File content: PID of the process holding the lock
- File mtime: timestamp of last successful consolidation (lastConsolidatedAt)
- Stale after: 1 hour, even if PID is alive (PID reuse protection)
- On failure: mtime is rolled back to prior value (preserves lastConsolidatedAt)
- Async context manager: acquire() → yields True/False

The key insight: the mtime IS the lastConsolidatedAt.
This means we get both a lock AND a timestamp in one file.
"""

from __future__ import annotations

import logging
import os
import time
from contextlib import asynccontextmanager
from datetime import datetime
from pathlib import Path
from typing import AsyncIterator, Optional

import aiofiles

logger = logging.getLogger("memograph.lock")

LOCK_STALE_SECONDS = 3600       # 1 hour
LOCK_FILE_NAME     = "consolidation.lock"


class LockState:
    """State of the lock at a point in time."""

    def __init__(
        self,
        held:             bool,
        holder_pid:       Optional[int]      = None,
        acquired_at:      Optional[datetime] = None,
        last_consolidated: Optional[datetime] = None,
        is_stale:         bool               = False,
        stale_reason:     Optional[str]      = None,
    ):
        self.held              = held
        self.holder_pid        = holder_pid
        self.acquired_at       = acquired_at
        self.last_consolidated = last_consolidated
        self.is_stale          = is_stale
        self.stale_reason      = stale_reason


class ConsolidationLock:
    """
    Advisory file-based lock for the consolidation daemon.

    Usage:
        lock = ConsolidationLock(base_path)
```

```
        # Check without acquiring
        state = lock.get_state()
        if state.last_consolidated:
            print(f"Last run: {state.last_consolidated}")

        # Acquire and run
        async with lock.acquire() as acquired:
            if acquired:
                await do_consolidation()
            else:
                print("Lock unavailable — skipping")
    """

    def __init__(self, base_path: Path):
        self.base_path = Path(base_path)
        self.lock_path = self.base_path / LOCK_FILE_NAME

    # ─────────────────────────────────────────────────────────────────────
    # STATE INSPECTION
    # ─────────────────────────────────────────────────────────────────────

    def get_state(self) -> LockState:
        """Read the current lock state without acquiring."""
        if not self.lock_path.exists():
            return LockState(
                held=False,
                last_consolidated=None,
            )

        stat = self.lock_path.stat()
        mtime = datetime.fromtimestamp(stat.st_mtime)
        age_seconds = time.time() - stat.st_mtime

        # Read PID from file
        try:
            pid_str = self.lock_path.read_text().strip()
            pid = int(pid_str) if pid_str.isdigit() else None
        except (OSError, ValueError):
            pid = None

        # Check for staleness
        is_stale = False
        stale_reason = None

        if age_seconds > LOCK_STALE_SECONDS:
            is_stale = True
            stale_reason = f"Lock file is {age_seconds/3600:.1f}h old
(>{LOCK_STALE_SECONDS/3600}h threshold)"

        elif pid and not self._pid_alive(pid):
            is_stale = True
            stale_reason = f"Holder PID {pid} is no longer alive"

        # If stale, it's effectively not held
        held = (pid is not None) and not is_stale

        return LockState(
```

```
            held=held,
            holder_pid=pid,
            acquired_at=mtime if held else None,
            last_consolidated=mtime,  # mtime IS lastConsolidatedAt
            is_stale=is_stale,
            stale_reason=stale_reason,
        )

    def is_available(self) -> bool:
        """Returns True if the lock can be acquired."""
        state = self.get_state()
        if not state.held:
            return True
        if state.is_stale:
            return True
        return False

    def get_last_consolidated(self) -> Optional[datetime]:
        """
        Get the last consolidation timestamp.
        This is the mtime of the lock file — the key design insight.
        Returns None if the lock file has never been written.
        """
        if not self.lock_path.exists():
            return None
        stat = self.lock_path.stat()
        return datetime.fromtimestamp(stat.st_mtime)

    # ─────────────────────────────────────────────────────────────────────
    # ACQUIRE / RELEASE
    # ─────────────────────────────────────────────────────────────────────

    @asynccontextmanager
    async def acquire(self) -> AsyncIterator[bool]:
        """
        Async context manager for acquiring the lock.

        Yields True if acquired successfully.
        Yields False if lock is unavailable (caller should skip consolidation).

        On success exit:  Updates mtime to now (= new lastConsolidatedAt)
        On failure exit:  Rolls back mtime to prior value
        On exception:     Rolls back mtime, removes lock file

        Usage:
            async with lock.acquire() as acquired:
                if acquired:
                    # do work
                    pass
        """
        # Check availability
        if not self.is_available():
            state = self.get_state()
            logger.info(
                f"Lock unavailable — held by PID {state.holder_pid} "
                f"since {state.acquired_at}"
            )
            yield False
```

```
            return

        # Handle stale lock
        state = self.get_state()
        if state.is_stale and self.lock_path.exists():
            logger.warning(
                f"Removing stale lock: {state.stale_reason}"
            )
            self.lock_path.unlink(missing_ok=True)

        # Save prior mtime for rollback (None if file doesn't exist)
        prior_mtime: Optional[float] = (
            self.lock_path.stat().st_mtime
            if self.lock_path.exists() else None
        )

        # Write our PID to the lock file
        our_pid = os.getpid()
        try:
            self.base_path.mkdir(parents=True, exist_ok=True)
            async with aiofiles.open(self.lock_path, "w") as f:
                await f.write(str(our_pid))
        except OSError as e:
            logger.error(f"Failed to write lock file: {e}")
            yield False
            return

        logger.debug(f"Lock acquired by PID {our_pid}")
        success = False

        try:
            yield True
            success = True
        finally:
            if success:
                # Update mtime to now = new lastConsolidatedAt
                now = time.time()
                try:
                    os.utime(self.lock_path, (now, now))
                    logger.debug(
                        f"Lock released — mtime updated to "
                        f"{datetime.fromtimestamp(now).isoformat()}"
                    )
                except OSError as e:
                    logger.error(f"Failed to update lock mtime: {e}")
            else:
                # Rollback: restore prior mtime or remove the file
                logger.warning("Consolidation failed — rolling back lock mtime")
                try:
                    if prior_mtime is not None:
                        os.utime(self.lock_path, (prior_mtime, prior_mtime))
                        logger.debug(
                            f"Lock mtime rolled back to "
                            f"{datetime.fromtimestamp(prior_mtime).isoformat()}"
                        )
                    else:
                        # No prior state — remove the file entirely
                        self.lock_path.unlink(missing_ok=True)
```

```
                except OSError as e:
                    logger.error(f"Failed to rollback lock: {e}")

    # ──────────────────────────────────────────────────────────────────────
    # HELPERS
    # ──────────────────────────────────────────────────────────────────────

    @staticmethod
    def _pid_alive(pid: int) -> bool:
        """Check if a PID is running."""
        try:
            os.kill(pid, 0)    # Signal 0 = check existence
            return True
        except (ProcessLookupError, PermissionError):
            return False
        except OSError:
            return True    # Unknown error — assume alive (conservative)

    def force_release(self) -> bool:
        """
        Force-remove the lock file (use with caution — admin only).
        Returns True if lock was removed.
        """
        if self.lock_path.exists():
            self.lock_path.unlink()
            logger.warning("Lock file force-removed")
            return True
        return False

    def __repr__(self) -> str:
        state = self.get_state()
        if state.held:
            return (
                f"ConsolidationLock(held=True, pid={state.holder_pid}, "
                f"last_consolidated={state.last_consolidated})"
            )
        return f"ConsolidationLock(held=False, last_consolidated={state.last_consolidated})"
```

---

6. Phase Base Class

Python

```
# memograph/consolidation/phases/base.py
"""
Base class for all four dream phases.
"""

from __future__ import annotations

import json
import logging
from abc import ABC, abstractmethod
```

```python
from dataclasses import dataclass, field
from datetime import datetime
from typing import Any, Optional


@dataclass
class PhaseResult:
    """Result from running a dream phase."""
    phase_name:   str
    success:      bool
    started_at:   datetime             = field(default_factory=datetime.now)
    ended_at:     Optional[datetime]   = None
    duration_ms:  int                  = 0
    details:      dict                 = field(default_factory=dict)
    error:        Optional[str]        = None

    def finish(self, success: bool, details: dict = None, error: str = None) -> None:
        self.ended_at   = datetime.now()
        self.success    = success
        self.duration_ms = int(
            (self.ended_at - self.started_at).total_seconds() * 1000
        )
        if details:
            self.details.update(details)
        if error:
            self.error = error

    def to_dict(self) -> dict:
        return {
            "phase_name":  self.phase_name,
            "success":     self.success,
            "started_at":  self.started_at.isoformat(),
            "ended_at":    self.ended_at.isoformat() if self.ended_at else None,
            "duration_ms": self.duration_ms,
            "details":     self.details,
            "error":       self.error,
        }

    def to_json(self) -> str:
        return json.dumps(self.to_dict(), default=str)


class BaseDreamPhase(ABC):
    """Abstract base for all four dream phases."""

    phase_name: str = "base"

    def __init__(self, logger_name: str = "memograph.dream"):
        self.log = logging.getLogger(logger_name)

    @abstractmethod
    async def run(self, ctx: "DreamContext") -> PhaseResult:
        """Execute the phase. Receives shared DreamContext."""
        ...

    def _parse_json(self, text: str) -> dict:
        """Parse JSON from LLM response, handling markdown fences."""
        import re
```

```
        text = text.strip()
        match = re.search(r"```(?:json)?\n?(.*?)\n?```", text, re.DOTALL)
        if match:
            text = match.group(1).strip()
        try:
            return json.loads(text)
        except json.JSONDecodeError:
            self.log.warning(f"Failed to parse JSON: {text[:200]}")
            return {}

    def _safe_truncate(self, text: str, max_chars: int) -> str:
        if len(text) <= max_chars:
            return text
        return text[:max_chars - 3] + "..."
```

---

7. Dream Context (Shared State)

Python

```
# memograph/consolidation/phases/__init__.py
"""
Shared DreamContext passed between all four phases.
"""

from __future__ import annotations

import uuid
from dataclasses import dataclass, field
from datetime import datetime
from pathlib import Path
from typing import Any, Optional, TYPE_CHECKING

if TYPE_CHECKING:
    from memograph.core.index_engine import IndexEngine
    from memograph.core.topic_manager import TopicManager
    from memograph.db.database import DatabaseManager
    from memograph.llm.base import BaseLLMProvider


@dataclass
class NewSignal:
    """A signal gathered during the Gather phase."""
    topic_id:    str
    topic_name:  str
    content:     str
    confidence:  str
    source:      str
    tags:        list[str] = field(default_factory=list)
    reasoning:   str       = ""


@dataclass
```

```python
class DreamContext:
    """
    Shared context object passed between all four dream phases.
    Acts as the message bus for inter-phase communication.
    """
    # Identity
    run_id:       str               = field(default_factory=lambda: str(uuid.uuid4())[:12])
    agent_id:     str               = "default"
    trigger:      str               = "daemon"  # daemon|manual|forced|api
    started_at:   datetime          = field(default_factory=datetime.now)

    # Infrastructure (injected by DreamEngine)
    db:           Any               = None  # DatabaseManager
    index_engine: Any               = None  # IndexEngine
    topic_manager: Any              = None  # TopicManager
    llm:          Any               = None  # BaseLLMProvider
    base_path:    Optional[Path]    = None
    transcripts_path: Optional[Path] = None

    # Phase 1 (Orient) outputs → consumed by Phase 2
    index_markdown:      str            = ""
    topic_ids:           list[str]      = field(default_factory=list)
    topic_summaries:     list[dict]     = field(default_factory=list)
    transcript_files:    list[Path]     = field(default_factory=list)
    drift_candidates:    list[str]      = field(default_factory=list)  # topic_ids

    # Phase 2 (Gather) outputs → consumed by Phase 3
    new_signals:         list[NewSignal] = field(default_factory=list)
    transcript_excerpts: str            = ""
    session_count:       int            = 0

    # Phase 3 (Consolidate) outputs → consumed by Phase 4
    operations_applied:  list[dict]     = field(default_factory=list)
    topics_modified:     list[str]      = field(default_factory=list)
    facts_merged:        int            = 0
    facts_created:       int            = 0
    facts_pruned:        int            = 0
    contradictions_resolved: int        = 0
    confidence_promoted: int            = 0

    # Phase 4 (Prune) outputs
    pointers_pruned:     int            = 0
    empty_topics_removed: int           = 0

    # LLM tracking
    total_prompt_tokens:     int        = 0
    total_completion_tokens: int        = 0
    total_llm_latency_ms:    int        = 0
    llm_provider:            str        = ""
    llm_model:               str        = ""
```

---

8. Phase 1 — Orient

Python

```python
# memograph/consolidation/phases/orient.py
"""
Phase 1: Orient

What it does:
- Read and cache the current index markdown
- Inventory all topic files (skim headers, not full content)
- Identify transcript files available for gather phase
- Identify topics that have drifted (stale/low-confidence)
- Build a complete picture before changing anything
"""

from __future__ import annotations

import logging
from datetime import datetime, timedelta
from pathlib import Path
from typing import Optional

import aiofiles

from memograph.consolidation.phases import DreamContext
from memograph.consolidation.phases.base import BaseDreamPhase, PhaseResult

logger = logging.getLogger("memograph.dream.orient")


class OrientPhase(BaseDreamPhase):
    """
    Phase 1: Orient.

    Reads the current state of memory without making any changes.
    All outputs are written to ctx for downstream phases.
    """

    phase_name = "orient"

    # Confidence below this threshold → candidate for drift consolidation
    DRIFT_CONFIDENCE_THRESHOLD = 0.4
    DRIFT_AGE_DAYS = 14        # Facts not updated in N days

    async def run(self, ctx: DreamContext) -> PhaseResult:
        result = PhaseResult(phase_name=self.phase_name, success=False)
        log    = logger

        try:
            log.info(f"[{ctx.run_id}] Phase 1: Orient — starting")

            # 1. Load and cache index markdown
            index    = await ctx.index_engine.get_index()
            ctx.index_markdown = index.to_markdown()
            log.debug(f"Index loaded: {len(index.pointers)} pointers")

            # 2. Inventory topic files
            topic_summaries = []
```

```
            for pointer in index.pointers:
                topic_path = ctx.base_path / pointer.topic_file_path
                if topic_path.exists():
                    info = await self._skim_topic(topic_path, pointer.topic_id)
                    topic_summaries.append(info)
                    ctx.topic_ids.append(pointer.topic_id)

            ctx.topic_summaries = topic_summaries
            log.debug(f"Topics inventoried: {len(topic_summaries)}")

            # 3. Identify drift candidates
            ctx.drift_candidates = [
                s["topic_id"]
                for s in topic_summaries
                if (
                    s["avg_confidence"] < self.DRIFT_CONFIDENCE_THRESHOLD
                    or s["stale_fact_count"] > 0
                    or s["days_since_modified"] > self.DRIFT_AGE_DAYS
                )
            ]
            log.debug(f"Drift candidates: {len(ctx.drift_candidates)}")

            # 4. Inventory transcript files
            ctx.transcript_files = sorted(
                ctx.transcripts_path.glob("*.jsonl"),
                key=lambda f: f.stat().st_mtime,
                reverse=True,
            )[:50]   # Cap at 50 most recent
            log.debug(f"Transcript files found: {len(ctx.transcript_files)}")

            result.finish(
                success=True,
                details={
                    "index_pointer_count":  len(index.pointers),
                    "topic_file_count":     len(topic_summaries),
                    "drift_candidate_count": len(ctx.drift_candidates),
                    "transcript_file_count": len(ctx.transcript_files),
                    "drift_candidates":     ctx.drift_candidates,
                },
            )
            log.info(
                f"[{ctx.run_id}] Phase 1 complete — "
                f"{len(topic_summaries)} topics, "
                f"{len(ctx.drift_candidates)} drifted, "
                f"{len(ctx.transcript_files)} transcripts"
            )

        except Exception as e:
            result.finish(success=False, error=str(e))
            log.error(f"[{ctx.run_id}] Phase 1 failed: {e}", exc_info=True)

        return result

    async def _skim_topic(
        self,
        topic_path: Path,
        topic_id:   str,
    ) -> dict:
```

```
        """
        Skim a topic file — read only the header lines (not full content).
        Fast: reads first 20 lines only.
        """
        import json

        now = datetime.now()

        try:
            stat = topic_path.stat()
            days_since_modified = (now - datetime.fromtimestamp(stat.st_mtime)).days
            size_bytes = stat.st_size

            # Read the JSON for metadata (fact count, confidence)
            async with aiofiles.open(topic_path) as f:
                data = json.loads(await f.read())

            facts = data.get("facts", [])
            fact_count = len(facts)

            # Compute average confidence
            conf_scores = {
                "verified": 1.0,
                "observed": 0.6,
                "inferred": 0.4,
                "stale":    0.1,
            }
            avg_conf = (
                sum(conf_scores.get(f.get("confidence", "observed"), 0.6)
                    for f in facts) / fact_count
                if fact_count else 0.0
            )

            # Count stale facts
            stale_count = sum(
                1 for f in facts
                if f.get("confidence") == "stale"
            )

            return {
                "topic_id":            topic_id,
                "topic_name":          data.get("topic_name", topic_id),
                "fact_count":          fact_count,
                "avg_confidence":      avg_conf,
                "stale_fact_count":    stale_count,
                "days_since_modified": days_since_modified,
                "size_bytes":          size_bytes,
                "tags":                data.get("tags", []),
            }

        except Exception as e:
            logger.warning(f"Failed to skim topic {topic_id}: {e}")
            return {
                "topic_id":            topic_id,
                "topic_name":          topic_id,
                "fact_count":          0,
                "avg_confidence":      0.0,
                "stale_fact_count":    0,
```

```
                "days_since_modified": 0,
                "size_bytes":          0,
                "tags":                [],
            }
```

---

9. Phase 2 — Gather

Python

```python
# memograph/consolidation/phases/gather.py
"""
Phase 2: Gather Recent Signal.

Priority order (mirrors consolidationPrompt.ts from leaked source):
  1. Daily logs / recent session transcripts
  2. Drifted memories (identified in Orient phase)
  3. Transcript search for key signal patterns

Uses LLM to extract worth-storing signals from raw transcript text.
"""

from __future__ import annotations

import json
import logging
import re
from datetime import datetime
from pathlib import Path
from typing import Optional

import aiofiles

from memograph.consolidation.phases import DreamContext, NewSignal
from memograph.consolidation.phases.base import BaseDreamPhase, PhaseResult
from memograph.llm.base import LLMResponse, Message, LLMRequest
from memograph.prompts.consolidation_prompts import (
    GATHER_SIGNAL_SYSTEM,
    build_gather_prompt,
)

logger = logging.getLogger("memograph.dream.gather")

# Patterns that suggest a signal worth capturing
SIGNAL_PATTERNS = [
    r"\b(always|never|important|critical|remember|note that)\b",
    r"\b(decided|decision|agreed|confirmed|resolved)\b",
    r"\b(bug|issue|problem|fixed|solution|workaround)\b",
    r"\b(architecture|design|pattern|approach|strategy)\b",
    r"\b(prefer|prefer|wants|needs|requires|must)\b",
    r"\b(migrated|changed|updated|upgraded|replaced)\b",
]
```

```python
SIGNAL_RE = re.compile("|".join(SIGNAL_PATTERNS), re.IGNORECASE)


class GatherPhase(BaseDreamPhase):
    """
    Phase 2: Gather.

    Collects new signal from three sources (in priority order):
    1. Recent session transcripts (raw text)
    2. Drifted memories (topics with stale/low-confidence facts)
    3. Targeted transcript grep for key patterns
    """

    phase_name = "gather"

    MAX_TRANSCRIPT_LINES = 200   # Lines per session to read
    MAX_SESSIONS         = 20    # Sessions to process
    MAX_EXCERPT_CHARS    = 8000  # Token budget for gather prompt
    MAX_SIGNALS_PER_CALL = 10    # Max signals to extract per LLM call

    async def run(self, ctx: DreamContext) -> PhaseResult:
        result = PhaseResult(phase_name=self.phase_name, success=False)

        try:
            logger.info(f"[{ctx.run_id}] Phase 2: Gather — starting")

            # Source 1: Recent session transcripts
            excerpts, session_count = await self._gather_from_transcripts(ctx)
            ctx.transcript_excerpts = excerpts
            ctx.session_count = session_count

            # Source 2: Extract signals using LLM
            if ctx.llm and excerpts:
                await self._extract_signals_llm(ctx, excerpts)
            else:
                logger.debug("No LLM or no excerpts — skipping LLM signal extraction")

            # Source 3: Pattern-based grep for additional signals
            grep_signals = await self._grep_transcript_patterns(ctx)
            logger.debug(f"Pattern grep found {len(grep_signals)} raw matches")

            result.finish(
                success=True,
                details={
                    "sessions_processed":    session_count,
                    "signals_extracted":     len(ctx.new_signals),
                    "drift_candidates":      len(ctx.drift_candidates),
                    "transcript_excerpts_chars": len(excerpts),
                    "grep_matches":          grep_signals,
                },
            )
            logger.info(
                f"[{ctx.run_id}] Phase 2 complete — "
                f"{len(ctx.new_signals)} signals from {session_count} sessions"
            )

        except Exception as e:
            result.finish(success=False, error=str(e))
```

```
            logger.error(f"[{ctx.run_id}] Phase 2 failed: {e}", exc_info=True)

        return result

    async def _gather_from_transcripts(
        self,
        ctx: DreamContext,
    ) -> tuple[str, int]:
        """
        Read recent transcript files.
        Returns (excerpts_text, session_count).
        """
        if not ctx.transcript_files:
            return "", 0

        session_files = ctx.transcript_files[:self.MAX_SESSIONS]
        excerpts:  list[str] = []
        total_chars = 0

        for filepath in session_files:
            if total_chars >= self.MAX_EXCERPT_CHARS:
                break

            try:
                session_id = filepath.stem
                lines: list[str] = []

                async with aiofiles.open(filepath) as f:
                    async for i, line in self._aenumerate(f):
                        if i >= self.MAX_TRANSCRIPT_LINES:
                            break
                        lines.append(line.strip())

                # Parse JSONL and extract meaningful text
                session_text_parts = [f"\n--- Session {session_id} ---"]

                for line in lines:
                    try:
                        entry = json.loads(line)
                        role    = entry.get("role", "")
                        content = entry.get("content", "")

                        # Only include substantial turns
                        if len(content) > 50 and role in ("user", "assistant"):
                            session_text_parts.append(
                                f"[{role}]: {content[:300]}"
                            )
                    except json.JSONDecodeError:
                        continue

                session_text = "\n".join(session_text_parts)
                if len(session_text) > 100:   # Only include non-trivial sessions
                    excerpts.append(session_text)
                    total_chars += len(session_text)

            except Exception as e:
                logger.warning(f"Failed to read transcript {filepath}: {e}")
```

```
        full_excerpts = "\n".join(excerpts)
        return full_excerpts[:self.MAX_EXCERPT_CHARS], len(session_files)

    async def _extract_signals_llm(
        self,
        ctx:      DreamContext,
        excerpts: str,
    ) -> None:
        """
        Use LLM to extract storable signals from transcript excerpts.
        Updates ctx.new_signals in place.
        """
        # Build prior signals string (avoid re-extracting)
        prior_signals_str = (
            "\n".join(f"- {s.content}" for s in ctx.new_signals[:10])
            if ctx.new_signals else "None yet"
        )

        prompt = build_gather_prompt(
            index_markdown=ctx.index_markdown,
            transcript_excerpts=excerpts,
            prior_signals=prior_signals_str,
        )

        try:
            request = LLMRequest(
                messages=[Message("user", prompt)],
                system_prompt=GATHER_SIGNAL_SYSTEM,
                max_tokens=2048,
                temperature=0.1,
                purpose="consolidation",
            )
            request = request.with_system(GATHER_SIGNAL_SYSTEM)
            response: LLMResponse = await ctx.llm.complete(request)

            # Track LLM usage
            ctx.total_prompt_tokens     += response.prompt_tokens
            ctx.total_completion_tokens += response.completion_tokens
            ctx.total_llm_latency_ms    += response.latency_ms
            ctx.llm_provider             = response.provider
            ctx.llm_model                = response.model

            # Parse response
            data    = self._parse_json(response.content)
            signals = data.get("signals", [])

            # Convert to NewSignal objects
            for s in signals[:self.MAX_SIGNALS_PER_CALL]:
                if s.get("content") and s.get("topic_id"):
                    ctx.new_signals.append(
                        NewSignal(
                            topic_id=s["topic_id"],
                            topic_name=s.get("topic_name", s["topic_id"]),
                            content=s["content"][:200],
                            confidence=s.get("confidence", "observed"),
                            source="gather_phase",
                            tags=s.get("tags", []),
                            reasoning=s.get("reasoning", ""),
```

```
                        )
                    )

            logger.debug(
                f"LLM extracted {len(signals)} signals "
                f"({response.total_tokens} tokens, "
                f"{response.latency_ms}ms)"
            )

        except Exception as e:
            logger.warning(f"LLM signal extraction failed: {e}")

    async def _grep_transcript_patterns(
        self,
        ctx: DreamContext,
    ) -> list[str]:
        """
        Fast grep over transcripts for key signal patterns.
        No LLM needed — pure pattern matching.
        Returns list of matching line snippets.
        """
        matches: list[str] = []

        for filepath in ctx.transcript_files[:30]:  # Cap at 30
            if len(matches) >= 50:
                break
            try:
                async with aiofiles.open(filepath) as f:
                    async for line in f:
                        if SIGNAL_RE.search(line):
                            try:
                                entry   = json.loads(line)
                                content = entry.get("content", "")
                                if len(content) > 30:
                                    matches.append(content[:200])
                            except json.JSONDecodeError:
                                pass
                        if len(matches) >= 50:
                            break
            except Exception:
                pass

        return matches

    @staticmethod
    async def _aenumerate(aiter, start: int = 0):
        """Async enumerate helper."""
        i = start
        async for item in aiter:
            yield i, item
            i += 1
```

---

10. Phase 3 — Consolidate

Python

```python
# memograph/consolidation/phases/consolidate.py
"""
Phase 3: Consolidate.

The main LLM-driven phase. For each topic that has:
  a) New signals to integrate (from Gather)
  b) Internal contradictions
  c) Drift (stale/low-confidence facts)

Runs the LLM with the consolidation prompt and applies operations.
"""

from __future__ import annotations

import json
import logging
import uuid
from datetime import datetime
from typing import Optional

from memograph.config import ConfidenceLevel
from memograph.consolidation.phases import DreamContext, NewSignal
from memograph.consolidation.phases.base import BaseDreamPhase, PhaseResult
from memograph.llm.base import LLMRequest, LLMResponse, Message
from memograph.models.topic import MemoryFact, TopicFile
from memograph.prompts.consolidation_prompts import (
    CONSOLIDATE_TOPIC_SYSTEM,
    build_consolidate_prompt,
)

logger = logging.getLogger("memograph.dream.consolidate")


class ConsolidatePhase(BaseDreamPhase):
    """
    Phase 3: Consolidate.

    Processes topics with new signals or drift.
    Uses LLM to decide merge/resolve/promote/prune operations.
    Applies operations with full audit trail.
    """

    phase_name = "consolidate"

    MAX_TOPICS_PER_RUN  = 10   # Process at most N topics per dream run
    MAX_OPS_PER_TOPIC   = 10   # LLM limit: max operations per topic

    async def run(self, ctx: DreamContext) -> PhaseResult:
        result = PhaseResult(phase_name=self.phase_name, success=False)

        try:
            logger.info(f"[{ctx.run_id}] Phase 3: Consolidate — starting")

            # Determine which topics need consolidation
            topics_to_process = self._select_topics(ctx)
```

```
            logger.info(
                f"[{ctx.run_id}] Consolidating {len(topics_to_process)} topics"
            )

            if not topics_to_process:
                result.finish(
                    success=True,
                    details={"message": "No topics require consolidation"},
                )
                return result

            # Process each topic
            for topic_id in topics_to_process[:self.MAX_TOPICS_PER_RUN]:
                await self._consolidate_topic(ctx, topic_id)

            result.finish(
                success=True,
                details={
                    "topics_processed":          len(topics_to_process),
                    "topics_modified":           ctx.topics_modified,
                    "facts_merged":              ctx.facts_merged,
                    "facts_created":             ctx.facts_created,
                    "facts_pruned":              ctx.facts_pruned,
                    "contradictions_resolved":   ctx.contradictions_resolved,
                    "confidence_promoted":       ctx.confidence_promoted,
                    "operations_applied_count":  len(ctx.operations_applied),
                },
            )
            logger.info(
                f"[{ctx.run_id}] Phase 3 complete — "
                f"merged={ctx.facts_merged}, "
                f"created={ctx.facts_created}, "
                f"pruned={ctx.facts_pruned}, "
                f"resolved={ctx.contradictions_resolved}"
            )

        except Exception as e:
            result.finish(success=False, error=str(e))
            logger.error(f"[{ctx.run_id}] Phase 3 failed: {e}", exc_info=True)

        return result

    def _select_topics(self, ctx: DreamContext) -> list[str]:
        """
        Select which topics to consolidate.
        Priority:
          1. Topics with new signals to integrate
          2. Topics with drift (stale/low-confidence)
          3. Topics with detected contradictions
        """
        priority: set[str] = set()

        # New signal targets
        for sig in ctx.new_signals:
            priority.add(sig.topic_id)

        # Drift candidates
        for tid in ctx.drift_candidates:
```

```
            priority.add(tid)

        # Topics that exist in index (for contradiction detection pass)
        for tid in ctx.topic_ids[:5]:  # Cap at 5 extra
            priority.add(tid)

        return list(priority)

    async def _consolidate_topic(
        self,
        ctx:      DreamContext,
        topic_id: str,
    ) -> None:
        """
        Run consolidation on a single topic.
        1. Load topic
        2. Build consolidation prompt
        3. Get LLM operations
        4. Apply operations
        5. Save topic
        6. Log operations to DB
        """
        # Load topic
        topic = await ctx.topic_manager.get_topic(topic_id)

        if topic is None:
            # Topic doesn't exist yet — may be a new signal topic
            topic = await self._create_topic_from_signals(ctx, topic_id)
            if topic is None:
                return

        # Build signals for this topic
        topic_signals = [
            s for s in ctx.new_signals
            if s.topic_id == topic_id
        ]
        new_signals_str = (
            "\n".join(f"- {s.content} (source: {s.source})" for s in topic_signals)
            if topic_signals else "None"
        )

        if not ctx.llm:
            # No LLM: just apply new signals directly as new facts
            await self._apply_signals_without_llm(ctx, topic, topic_signals)
            return

        # Build LLM prompt
        prompt = build_consolidate_prompt(
            topic_id=topic.topic_id,
            topic_name=topic.topic_name,
            tags=topic.tags,
            fact_count=len(topic.facts),
            facts_markdown=topic.to_markdown(),
            new_signals=new_signals_str,
        )

        try:
            request = LLMRequest(
```

```
                messages=[Message("user", prompt)],
                system_prompt=CONSOLIDATE_TOPIC_SYSTEM,
                max_tokens=2048,
                temperature=0.1,
                purpose="consolidation",
            )
            request = request.with_system(CONSOLIDATE_TOPIC_SYSTEM)
            response: LLMResponse = await ctx.llm.complete(request)

            # Track LLM usage
            ctx.total_prompt_tokens     += response.prompt_tokens
            ctx.total_completion_tokens += response.completion_tokens
            ctx.total_llm_latency_ms    += response.latency_ms

            # Parse operations
            data = self._parse_json(response.content)

            if data.get("no_changes_needed"):
                logger.debug(f"Topic {topic_id}: no changes needed")
                return

            operations = data.get("operations", [])
            if not operations:
                logger.debug(f"Topic {topic_id}: LLM returned no operations")
                await self._apply_signals_without_llm(ctx, topic, topic_signals)
                return

            # Apply operations
            modified = await self._apply_operations(ctx, topic, operations)

            if modified:
                ctx.topics_modified.append(topic_id)

        except Exception as e:
            logger.error(f"LLM consolidation failed for {topic_id}: {e}")
            # Fallback: apply signals directly
            await self._apply_signals_without_llm(ctx, topic, topic_signals)

    async def _apply_operations(
        self,
        ctx:        DreamContext,
        topic:      TopicFile,
        operations: list[dict],
    ) -> bool:
        """
        Apply LLM-generated operations to a topic.
        Tracks each operation in ctx.operations_applied.
        Returns True if topic was modified.
        """
        modified = False

        for op_data in operations[:self.MAX_OPS_PER_TOPIC]:
            action = op_data.get("action")
            op_id  = str(uuid.uuid4())[:8]

            try:
                if action == "merge":
                    applied = await self._apply_merge(ctx, topic, op_data)
```

```
                    if applied:
                        ctx.facts_merged  += 1
                        modified = True

                elif action == "resolve_contradiction":
                    applied = await self._apply_resolve(ctx, topic, op_data)
                    if applied:
                        ctx.contradictions_resolved += 1
                        modified = True

                elif action == "promote":
                    applied = await self._apply_promote(ctx, topic, op_data)
                    if applied:
                        ctx.confidence_promoted += 1
                        modified = True

                elif action == "prune":
                    applied = await self._apply_prune(ctx, topic, op_data)
                    if applied:
                        ctx.facts_pruned += 1
                        modified = True

                else:
                    logger.warning(f"Unknown operation action: {action}")
                    applied = False

                # Log operation to DB
                await ctx.db.insert_dream_operation(
                    agent_id=ctx.agent_id,
                    run_id=ctx.run_id,
                    operation_id=op_id,
                    action=action or "unknown",
                    topic_id=topic.topic_id,
                    fact_ids_input=op_data.get("fact_ids", []),
                    content_after=op_data.get("merged_content")
                                  or op_data.get("updated_content"),
                    reasoning=op_data.get("reasoning", ""),
                    applied=applied,
                )

                ctx.operations_applied.append({
                    "op_id":    op_id,
                    "action":   action,
                    "topic_id": topic.topic_id,
                    "applied":  applied,
                })

            except Exception as e:
                logger.warning(
                    f"Failed to apply {action} on {topic.topic_id}: {e}"
                )
                await ctx.db.insert_dream_operation(
                    agent_id=ctx.agent_id,
                    run_id=ctx.run_id,
                    operation_id=op_id,
                    action=action or "unknown",
                    topic_id=topic.topic_id,
                    applied=False,
```

```
                    apply_error=str(e),
                )

        # Save topic if modified
        if modified:
            await ctx.topic_manager.save_topic(topic)
            logger.debug(
                f"Topic {topic.topic_id} saved with "
                f"{len(ctx.operations_applied)} operations applied"
            )

        return modified

    async def _apply_merge(
        self,
        ctx:    DreamContext,
        topic:  TopicFile,
        op:     dict,
    ) -> bool:
        """Merge multiple facts into one."""
        fact_ids    = op.get("fact_ids", [])
        new_content = op.get("merged_content", "").strip()
        new_conf    = op.get("merged_confidence", "observed")

        if not fact_ids or not new_content:
            return False

        # Verify all fact_ids exist
        existing = [f for f in topic.facts if f.fact_id in fact_ids]
        if len(existing) < 2:
            logger.debug(f"Merge: fewer than 2 facts found for {fact_ids}")
            return False

        # Remove old facts
        topic.facts = [f for f in topic.facts if f.fact_id not in fact_ids]

        # Add merged fact
        merged_fact = MemoryFact(
            content=new_content[:200],
            confidence=ConfidenceLevel(new_conf),
            source=f"autoDream/merge/{ctx.run_id}",
            created_at=datetime.now(),
            last_verified=datetime.now() if new_conf == "verified" else None,
            meta={"merged_from": fact_ids, "run_id": ctx.run_id},
        )
        topic.facts.append(merged_fact)

        logger.debug(
            f"Merged {len(fact_ids)} facts → {merged_fact.fact_id} "
            f"in {topic.topic_id}"
        )
        return True

    async def _apply_resolve(
        self,
        ctx:   DreamContext,
        topic: TopicFile,
        op:    dict,
```

```
    ) -> bool:
        """Resolve a contradiction by keeping one fact and updating it."""
        keep_id    = op.get("keep_fact_id")
        discard_id = op.get("discard_fact_id")
        new_content = op.get("updated_content", "").strip()

        if not keep_id or not discard_id:
            return False

        keep_fact    = topic.get_fact(keep_id)
        discard_fact = topic.get_fact(discard_id)

        if not keep_fact or not discard_fact:
            return False

        # Update the kept fact
        if new_content:
            keep_fact.content = new_content[:200]
        keep_fact.last_verified = datetime.now()
        keep_fact.contradicts_ids = []
        keep_fact.meta["resolved_contradiction"] = {
            "discarded_fact_id": discard_id,
            "run_id": ctx.run_id,
            "reasoning": op.get("reasoning", ""),
        }

        # Remove the discarded fact
        topic.facts = [f for f in topic.facts if f.fact_id != discard_id]

        logger.debug(
            f"Resolved contradiction: kept {keep_id}, "
            f"discarded {discard_id} in {topic.topic_id}"
        )
        return True

    async def _apply_promote(
        self,
        ctx:   DreamContext,
        topic: TopicFile,
        op:    dict,
    ) -> bool:
        """Promote a fact's confidence level."""
        fact_id     = op.get("fact_id")
        new_conf    = op.get("new_confidence", "observed")

        if not fact_id:
            return False

        fact = topic.get_fact(fact_id)
        if not fact:
            return False

        old_conf = fact.confidence
        try:
            fact.confidence    = ConfidenceLevel(new_conf)
            fact.last_verified = datetime.now()
            fact.meta["promoted_from"] = old_conf.value
            fact.meta["promoted_run"]  = ctx.run_id
```

```
            logger.debug(
                f"Promoted fact {fact_id}: "
                f"{old_conf.value} → {new_conf} "
                f"in {topic.topic_id}"
            )
            return True
        except ValueError:
            logger.warning(f"Invalid confidence level: {new_conf}")
            return False

    async def _apply_prune(
        self,
        ctx:   DreamContext,
        topic: TopicFile,
        op:    dict,
    ) -> bool:
        """Remove a fact from the topic."""
        fact_id = op.get("fact_id")
        if not fact_id:
            return False

        before = len(topic.facts)
        topic.facts = [f for f in topic.facts if f.fact_id != fact_id]

        removed = len(topic.facts) < before
        if removed:
            logger.debug(
                f"Pruned fact {fact_id} from {topic.topic_id}: "
                f"{op.get('reasoning', 'no reason given')}"
            )
        return removed

    async def _apply_signals_without_llm(
        self,
        ctx:     DreamContext,
        topic:   TopicFile,
        signals: list[NewSignal],
    ) -> None:
        """
        Fallback: apply new signals as raw facts without LLM consolidation.
        Used when no LLM is configured or LLM call fails.
        """
        if not signals:
            return

        for sig in signals:
            fact = MemoryFact(
                content=sig.content[:200],
                confidence=ConfidenceLevel(sig.confidence),
                source=sig.source,
                created_at=datetime.now(),
                meta={"from_gather": True, "run_id": ctx.run_id},
            )
            topic.facts.append(fact)
            ctx.facts_created += 1

        await ctx.topic_manager.save_topic(topic)
```

```
        ctx.topics_modified.append(topic.topic_id)

        logger.debug(
            f"Applied {len(signals)} raw signals to {topic.topic_id} "
            f"(no LLM)"
        )

    async def _create_topic_from_signals(
        self,
        ctx:      DreamContext,
        topic_id: str,
    ) -> Optional[TopicFile]:
        """Create a brand-new topic from gather signals."""
        signals = [s for s in ctx.new_signals if s.topic_id == topic_id]
        if not signals:
            return None

        first = signals[0]
        topic = TopicFile(
            topic_id=topic_id,
            topic_name=first.topic_name,
            agent_id=ctx.agent_id,
            tags=list(set(t for s in signals for t in s.tags)),
        )

        # Add initial facts
        for sig in signals:
            fact = MemoryFact(
                content=sig.content[:200],
                confidence=ConfidenceLevel(sig.confidence),
                source=sig.source,
                created_at=datetime.now(),
                meta={"from_gather": True, "run_id": ctx.run_id},
            )
            topic.facts.append(fact)
            ctx.facts_created += 1

        await ctx.topic_manager.save_topic(topic)
        ctx.topics_modified.append(topic_id)

        logger.info(
            f"Created new topic {topic_id} with "
            f"{len(topic.facts)} facts from gather signals"
        )
        return topic
```

---

11. Phase 4 — Prune

Python

```
# memograph/consolidation/phases/prune.py
"""
```

```
Phase 4: Prune and Index.

Final phase of the dream cycle.
- Remove orphaned index pointers (topic file deleted)
- Remove empty topics (0 facts after consolidation)
- Mark stale pointers
- Enforce index size limits (200 lines / 25KB)
- Update index pointer summaries to reflect new fact counts
- Optionally run LLM-assisted index review
- Record lastConsolidatedAt in lock file (via DreamEngine)
"""

from __future__ import annotations

import logging
from datetime import datetime, timedelta
from pathlib import Path
from typing import Optional

from memograph.consolidation.phases import DreamContext
from memograph.consolidation.phases.base import BaseDreamPhase, PhaseResult
from memograph.llm.base import LLMRequest, Message
from memograph.prompts.consolidation_prompts import (
    PRUNE_INDEX_SYSTEM,
    build_prune_prompt,
)

logger = logging.getLogger("memograph.dream.prune")


class PrunePhase(BaseDreamPhase):
    """
    Phase 4: Prune and Index.

    Enforces hard limits on the index and cleans up dead state.
    """

    phase_name = "prune"

    STALE_ACCESS_DAYS = 30      # Pointer not accessed in N days → stale
    STALE_UPDATE_DAYS = 60      # Pointer not updated in N days → stale
    STALE_MIN_CONF    = 0.3     # Below this confidence → stale

    async def run(self, ctx: DreamContext) -> PhaseResult:
        result = PhaseResult(phase_name=self.phase_name, success=False)

        try:
            logger.info(f"[{ctx.run_id}] Phase 4: Prune — starting")

            index = await ctx.index_engine.get_index()
            now   = datetime.now()

            removed_orphans    = 0
            removed_empty      = 0
            marked_stale       = 0
            summaries_updated  = 0

            # 1. Remove orphaned pointers
```

```
            for pointer in list(index.pointers):
                topic_path = ctx.base_path / pointer.topic_file_path
                if not topic_path.exists():
                    logger.warning(
                        f"Removing orphaned pointer: {pointer.topic_id} "
                        f"(file missing: {topic_path})"
                    )
                    await ctx.index_engine.remove_pointer(pointer.topic_id)
                    removed_orphans += 1

            # 2. Remove empty topics (0 facts after consolidation)
            for topic_id in list(ctx.topics_modified):
                topic = await ctx.topic_manager.get_topic(topic_id)
                if topic and len(topic.facts) == 0:
                    logger.info(
                        f"Removing empty topic after consolidation: {topic_id}"
                    )
                    await ctx.topic_manager.delete_topic(topic_id)
                    await ctx.index_engine.remove_pointer(topic_id)
                    removed_empty += 1
                    ctx.empty_topics_removed += 1

            # 3. Update summaries for modified topics
            for topic_id in ctx.topics_modified:
                topic = await ctx.topic_manager.get_topic(topic_id)
                if topic:
                    await ctx.index_engine.update_pointer(
                        topic_id=topic_id,
                        summary=topic.to_summary(),
                        confidence=topic.avg_confidence,
                    )
                    summaries_updated += 1

            # 4. Add new topics created during consolidation
            for topic_id in set(ctx.topics_modified):
                topic = await ctx.topic_manager.get_topic(topic_id)
                if topic and not (await ctx.index_engine.get_index()).get_pointer(topic_id):
                    await ctx.index_engine.add_pointer(
                        topic_id=topic_id,
                        topic_file_path=f"topics/{topic_id}.json",
                        summary=topic.to_summary(),
                        confidence=topic.avg_confidence,
                    )

            # 5. Mark stale pointers
            index = await ctx.index_engine.get_index()
            for pointer in index.pointers:
                should_stale = False

                if (pointer.last_accessed and
                        (now - pointer.last_accessed).days > self.STALE_ACCESS_DAYS):
                    should_stale = True

                elif (now - pointer.last_updated).days > self.STALE_UPDATE_DAYS:
                    should_stale = True

                elif pointer.confidence < self.STALE_MIN_CONF:
                    should_stale = True
```

```
                if should_stale and not pointer.is_stale:
                    await ctx.index_engine.mark_stale(pointer.topic_id)
                    marked_stale += 1

            # 6. Enforce index size limits
            await ctx.index_engine.auto_compact_if_needed()
            ctx.pointers_pruned = removed_orphans + removed_empty

            # 7. Optional: LLM-assisted index review
            if ctx.llm:
                await self._llm_index_review(ctx)

            # 8. Final sync to Markdown
            await ctx.index_engine._sync_to_markdown()

            result.finish(
                success=True,
                details={
                    "removed_orphans":    removed_orphans,
                    "removed_empty":      removed_empty,
                    "marked_stale":       marked_stale,
                    "summaries_updated":  summaries_updated,
                    "final_pointer_count": len(
                        (await ctx.index_engine.get_index()).pointers
                    ),
                },
            )

            logger.info(
                f"[{ctx.run_id}] Phase 4 complete — "
                f"orphans={removed_orphans}, empty={removed_empty}, "
                f"stale_marked={marked_stale}"
            )

        except Exception as e:
            result.finish(success=False, error=str(e))
            logger.error(f"[{ctx.run_id}] Phase 4 failed: {e}", exc_info=True)

        return result

    async def _llm_index_review(self, ctx: DreamContext) -> None:
        """
        Optional LLM review of the index for additional pruning recommendations.
        Conservative: only acts on clear removals.
        """
        index = await ctx.index_engine.get_index()
        if len(index.pointers) < 10:
            return  # Index small enough — skip

        topic_file_status = "\n".join(
            f"- {p.topic_id}: {p.summary} "
            f"(conf={p.confidence:.2f}, "
            f"stale={'yes' if p.is_stale else 'no'})"
            for p in index.pointers
        )

        empty_topics = ", ".join(ctx.topics_modified) or "None"
```

```
        prompt = build_prune_prompt(
            index_markdown=ctx.index_markdown,
            topic_file_status=topic_file_status,
            empty_topics=empty_topics,
        )

        try:
            request = LLMRequest(
                messages=[Message("user", prompt)],
                system_prompt=PRUNE_INDEX_SYSTEM,
                max_tokens=1024,
                temperature=0.0,
                purpose="consolidation",
            )
            request = request.with_system(PRUNE_INDEX_SYSTEM)
            response = await ctx.llm.complete(request)

            ctx.total_prompt_tokens     += response.prompt_tokens
            ctx.total_completion_tokens += response.completion_tokens

            data = self._parse_json(response.content)

            # Apply only the clear removals (be conservative)
            for topic_id in data.get("remove_topic_ids", [])[:3]:  # Max 3 at once
                if topic_id in [p.topic_id for p in index.pointers]:
                    logger.info(
                        f"LLM prune recommendation: remove {topic_id}"
                    )
                    await ctx.index_engine.remove_pointer(topic_id)
                    ctx.pointers_pruned += 1

            # Mark stale (non-destructive)
            for topic_id in data.get("mark_stale_topic_ids", []):
                await ctx.index_engine.mark_stale(topic_id)

        except Exception as e:
            logger.warning(f"LLM index review failed: {e}")
```

---

12. Dream Engine — The Orchestrator

Python

```
# memograph/consolidation/dream_engine.py
"""
DreamEngine — orchestrates the 4-phase dream consolidation.

Coordinates:
  - Gate checks (should we run?)
  - Lock acquisition (prevent concurrent runs)
  - Phase 1-4 execution with shared DreamContext
  - Full DB audit trail
  - Error handling and rollback
```

```
"""

from __future__ import annotations

import logging
import time
from datetime import datetime
from pathlib import Path
from typing import Optional

from memograph.config import MemoGraphConfig
from memograph.consolidation.gates import ConsolidationGates, GateReport
from memograph.consolidation.lock import ConsolidationLock
from memograph.consolidation.phases import DreamContext
from memograph.consolidation.phases.orient import OrientPhase
from memograph.consolidation.phases.gather import GatherPhase
from memograph.consolidation.phases.consolidate import ConsolidatePhase
from memograph.consolidation.phases.prune import PrunePhase
from memograph.consolidation.phases.base import PhaseResult
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.base import BaseLLMProvider

logger = logging.getLogger("memograph.dream")


class DreamResult:
    """
    Full result of a dream run.
    Includes gate report, all four phase results, and summary stats.
    """

    def __init__(
        self,
        run_id:          str,
        skipped:         bool                = False,
        skip_reason:     Optional[str]       = None,
        gate_report:     Optional[GateReport] = None,
        phase_results:   dict[str, PhaseResult] = None,
        ctx:             Optional[DreamContext] = None,
        error:           Optional[str]       = None,
        duration_ms:     int                 = 0,
    ):
        self.run_id        = run_id
        self.skipped       = skipped
        self.skip_reason   = skip_reason
        self.gate_report   = gate_report
        self.phase_results = phase_results or {}
        self.ctx           = ctx
        self.error         = error
        self.duration_ms   = duration_ms

    @property
    def success(self) -> bool:
        if self.skipped:
            return False
        if self.error:
```

```
            return False
        return all(r.success for r in self.phase_results.values())

    def summary(self) -> dict:
        if self.skipped:
            return {
                "status":     "skipped",
                "run_id":     self.run_id,
                "reason":     self.skip_reason,
            }

        ctx = self.ctx
        return {
            "status":                   "success" if self.success else "failed",
            "run_id":                   self.run_id,
            "duration_ms":              self.duration_ms,
            "error":                    self.error,
            "phases": {
                name: {
                    "success":    r.success,
                    "duration_ms": r.duration_ms,
                    "error":      r.error,
                }
                for name, r in self.phase_results.items()
            },
            "outcomes": {
                "facts_merged":             ctx.facts_merged if ctx else 0,
                "facts_created":            ctx.facts_created if ctx else 0,
                "facts_pruned":             ctx.facts_pruned if ctx else 0,
                "contradictions_resolved": ctx.contradictions_resolved if ctx else 0,
                "confidence_promoted":     ctx.confidence_promoted if ctx else 0,
                "pointers_pruned":          ctx.pointers_pruned if ctx else 0,
                "topics_modified":          len(ctx.topics_modified) if ctx else 0,
            },
            "llm_usage": {
                "provider":          ctx.llm_provider if ctx else None,
                "model":             ctx.llm_model if ctx else None,
                "prompt_tokens":     ctx.total_prompt_tokens if ctx else 0,
                "completion_tokens": ctx.total_completion_tokens if ctx else 0,
                "latency_ms":        ctx.total_llm_latency_ms if ctx else 0,
            },
            "signals_gathered": len(ctx.new_signals) if ctx else 0,
        }


class DreamEngine:
    """
    The AutoDream consolidation engine.

    Runs the 4-phase dream cycle:
      Phase 1 — Orient:      Inventory current memory state
      Phase 2 — Gather:      Collect new signal from transcripts
      Phase 3 — Consolidate: LLM-driven merge/resolve/promote/prune
      Phase 4 — Prune:       Enforce limits, clean index

    Usage:
        engine = DreamEngine(config, db, index_engine, topic_manager, llm, lock, gates)
        result = await engine.run()
```

```
        if result.success:
            print(result.summary())
    """

    def __init__(
        self,
        config:         MemoGraphConfig,
        db:             DatabaseManager,
        index_engine:   IndexEngine,
        topic_manager:  TopicManager,
        llm:            Optional[BaseLLMProvider],
        lock:           ConsolidationLock,
        gates:          ConsolidationGates,
    ):
        self.config        = config
        self.db            = db
        self.index_engine  = index_engine
        self.topic_manager = topic_manager
        self.llm           = llm
        self.lock          = lock
        self.gates         = gates
        self.agent_id      = config.agent_id
        self.base_path     = Path(config.base_path)

        # Phases
        self._orient     = OrientPhase()
        self._gather     = GatherPhase()
        self._consolidate = ConsolidatePhase()
        self._prune      = PrunePhase()

    # ──────────────────────────────────────────────────────────────────────
    # MAIN ENTRY POINT
    # ──────────────────────────────────────────────────────────────────────

    async def run(
        self,
        trigger:    str  = "daemon",
        force:      bool = False,
    ) -> DreamResult:
        """
        Run the full dream consolidation.

        Args:
            trigger: What triggered this run (daemon|manual|api|forced)
            force:   Skip time/session/scan gates (admin trigger)

        Returns:
            DreamResult with full audit information
        """
        start_time = time.monotonic()

        # Use forced gates if requested
        active_gates = ConsolidationGates.forced() if force else self.gates

        # ── Gate check ──────────────────────────────────────────────────
        dream_state = await self.db.get_dream_state(self.agent_id)

        last_consolidated: Optional[datetime] = None
```

```
        if dream_state and dream_state.get("last_consolidated_at"):
            last_consolidated = datetime.fromisoformat(
                dream_state["last_consolidated_at"]
            )

        session_count = await self.db.count_sessions_since(
            self.agent_id,
            (last_consolidated or datetime.min).isoformat(),
        )

        gate_report = active_gates.check_all(
            last_consolidated=last_consolidated,
            session_count=session_count,
            lock_available=self.lock.is_available(),
        )

        if not gate_report.all_passed:
            logger.info(f"Dream skipped: {gate_report.summary()}")
            return DreamResult(
                run_id=f"skip_{int(time.monotonic())}",
                skipped=True,
                skip_reason=gate_report.summary(),
                gate_report=gate_report,
            )

        # ── Acquire lock and run ──────────────────────────────────
        import uuid
        run_id = str(uuid.uuid4())[:12]

        async with self.lock.acquire() as acquired:
            if not acquired:
                logger.info(f"Dream {run_id}: lock unavailable after gate check")
                return DreamResult(
                    run_id=run_id,
                    skipped=True,
                    skip_reason="Lock unavailable",
                    gate_report=gate_report,
                )

            # Create DB record
            await self.db.create_dream_run(self.agent_id, run_id, trigger)
            await self.db.increment_dream_run_count(self.agent_id)

            # Update gate results in DB
            gate_results = {r.gate_name: r.passed for r in gate_report.results}
            await self.db.update_dream_run(
                agent_id=self.agent_id,
                run_id=run_id,
                gate_scan_interval=int(gate_results.get("scan_interval", True)),
                gate_time=int(gate_results.get("time_elapsed", True)),
                gate_sessions=int(gate_results.get("session_count", True)),
                gate_lock=1,
            )

            # Build shared context
            ctx = DreamContext(
                run_id=run_id,
                agent_id=self.agent_id,
```

```
                trigger=trigger,
                db=self.db,
                index_engine=self.index_engine,
                topic_manager=self.topic_manager,
                llm=self.llm,
                base_path=self.base_path,
                transcripts_path=self.base_path / "transcripts",
            )

            phase_results: dict[str, PhaseResult] = {}
            run_error: Optional[str] = None
            run_error_phase: Optional[str] = None

            try:
                # ── Phase 1: Orient ──────────────────────────────────────
                logger.info(f"[{run_id}] Starting dream cycle")
                p1 = await self._orient.run(ctx)
                phase_results["orient"] = p1

                await self.db.update_dream_run(
                    agent_id=self.agent_id,
                    run_id=run_id,
                    phase_orient_result=p1.to_json(),
                )

                if not p1.success:
                    raise RuntimeError(f"Orient phase failed: {p1.error}")

                # ── Phase 2: Gather ──────────────────────────────────────
                p2 = await self._gather.run(ctx)
                phase_results["gather"] = p2

                await self.db.update_dream_run(
                    agent_id=self.agent_id,
                    run_id=run_id,
                    phase_gather_result=p2.to_json(),
                )

                if not p2.success:
                    logger.warning(
                        f"[{run_id}] Gather phase failed: {p2.error} — continuing"
                    )

                # ── Phase 3: Consolidate ─────────────────────────────────
                p3 = await self._consolidate.run(ctx)
                phase_results["consolidate"] = p3

                await self.db.update_dream_run(
                    agent_id=self.agent_id,
                    run_id=run_id,
                    phase_consolidate_result=p3.to_json(),
                    facts_merged=ctx.facts_merged,
                    facts_created=ctx.facts_created,
                    facts_pruned=ctx.facts_pruned,
                    contradictions_resolved=ctx.contradictions_resolved,
                    confidence_promoted=ctx.confidence_promoted,
                )
```

```
                if not p3.success:
                    logger.warning(
                        f"[{run_id}] Consolidate phase failed: {p3.error} — continuing"
                    )

                # ── Phase 4: Prune ──────────────────────────────────────
                p4 = await self._prune.run(ctx)
                phase_results["prune"] = p4

                await self.db.update_dream_run(
                    agent_id=self.agent_id,
                    run_id=run_id,
                    phase_prune_result=p4.to_json(),
                    pointers_pruned=ctx.pointers_pruned,
                )

                if not p4.success:
                    logger.warning(
                        f"[{run_id}] Prune phase failed: {p4.error}"
                    )

            except Exception as e:
                run_error = str(e)
                run_error_phase = next(
                    (name for name, r in phase_results.items() if not r.success),
                    "unknown"
                )
                logger.error(
                    f"[{run_id}] Dream run failed in phase "
                    f"{run_error_phase}: {e}",
                    exc_info=True,
                )

            # ── Finalize ────────────────────────────────────────────────
            duration_ms = int((time.monotonic() - start_time) * 1000)
            status      = "failed" if run_error else "completed"

            await self.db.update_dream_run(
                agent_id=self.agent_id,
                run_id=run_id,
                status=status,
                ended_at=datetime.now().isoformat(),
                duration_ms=duration_ms,
                llm_provider=ctx.llm_provider or None,
                llm_model=ctx.llm_model or None,
                llm_prompt_tokens=ctx.total_prompt_tokens,
                llm_completion_tokens=ctx.total_completion_tokens,
                llm_latency_ms=ctx.total_llm_latency_ms,
                error_message=run_error,
                error_phase=run_error_phase,
            )

            # Update dream state
            if not run_error:
                await self.db.upsert_dream_state(
                    agent_id=self.agent_id,
                    last_run_id=run_id,
                    last_consolidated_at=datetime.now().isoformat(),
```

```
                    sessions_since_last=0,
                )

            result = DreamResult(
                run_id=run_id,
                gate_report=gate_report,
                phase_results=phase_results,
                ctx=ctx,
                error=run_error,
                duration_ms=duration_ms,
            )

            logger.info(
                f"[{run_id}] Dream {status} in {duration_ms}ms — "
                f"merged={ctx.facts_merged}, "
                f"created={ctx.facts_created}, "
                f"resolved={ctx.contradictions_resolved}"
            )

            return result

    async def get_history(self, limit: int = 10) -> list[dict]:
        """Get recent dream run history."""
        return await self.db.get_dream_runs(self.agent_id, limit)

    async def get_state(self) -> Optional[dict]:
        """Get the current dream state (last run, sessions, etc.)."""
        return await self.db.get_dream_state(self.agent_id)
```

---

13. Consolidation Scheduler

Python

```
# memograph/consolidation/scheduler.py
"""
Scheduling strategies for the consolidation daemon.
Supports: fixed interval, adaptive, session-triggered, manual.
"""

from __future__ import annotations

import logging
from abc import ABC, abstractmethod
from datetime import datetime, timedelta
from typing import Optional

logger = logging.getLogger("memograph.scheduler")


class BaseScheduler(ABC):
    """Abstract scheduler."""
```

```
    @abstractmethod
    async def next_wait_seconds(
        self,
        last_run:      Optional[datetime],
        session_count: int,
    ) -> float:
        """How many seconds to wait before the next check."""
        ...

    @abstractmethod
    def should_force_run(
        self,
        last_run:      Optional[datetime],
        session_count: int,
    ) -> bool:
        """Whether to force a run regardless of gates."""
        ...


class FixedIntervalScheduler(BaseScheduler):
    """
    Simple fixed-interval scheduler.
    Checks every N seconds.
    """

    def __init__(self, check_interval_seconds: int = 600):
        self.interval = check_interval_seconds

    async def next_wait_seconds(self, last_run, session_count) -> float:
        return float(self.interval)

    def should_force_run(self, last_run, session_count) -> bool:
        return False


class AdaptiveScheduler(BaseScheduler):
    """
    Adaptive scheduler — checks more frequently when sessions are accumulating.

    Logic:
    - sessions < 2:   check every 30 minutes
    - sessions 2-5:   check every 10 minutes
    - sessions 5-10:  check every 5 minutes
    - sessions > 10:  check every 2 minutes (eager to consolidate)
    """

    def __init__(self):
        self._thresholds = [
            (10, 120),    # > 10 sessions → check every 2 min
            (5,  300),    # > 5 sessions  → check every 5 min
            (2,  600),    # > 2 sessions  → check every 10 min
            (0,  1800),   # baseline      → check every 30 min
        ]

    async def next_wait_seconds(
        self,
        last_run:      Optional[datetime],
        session_count: int,
```

```
    ) -> float:
        for min_sessions, interval in self._thresholds:
            if session_count >= min_sessions:
                return float(interval)
        return 1800.0

    def should_force_run(
        self,
        last_run:      Optional[datetime],
        session_count: int,
    ) -> bool:
        # Force if session count is very high (backlog clearing)
        return session_count > 20


class SessionTriggeredScheduler(BaseScheduler):
    """
    Trigger consolidation after every N sessions, regardless of time.
    Useful for high-frequency agent setups.
    """

    def __init__(
        self,
        sessions_per_run:          int   = 5,
        check_interval_seconds:    int   = 300,
    ):
        self.sessions_per_run = sessions_per_run
        self.check_interval   = check_interval_seconds

    async def next_wait_seconds(self, last_run, session_count) -> float:
        return float(self.check_interval)

    def should_force_run(
        self,
        last_run:      Optional[datetime],
        session_count: int,
    ) -> bool:
        return session_count >= self.sessions_per_run
```

---

14. Consolidation Daemon

Python

```
# memograph/consolidation/daemon.py
"""
Background consolidation daemon.

Runs as an asyncio task in the background.
Periodically checks gates and runs the dream engine when conditions are met.
Supports graceful shutdown with cleanup.
"""
```

```python
from __future__ import annotations

import asyncio
import logging
import os
import signal
from datetime import datetime
from typing import Callable, Optional

from memograph.consolidation.dream_engine import DreamEngine, DreamResult
from memograph.consolidation.scheduler import (
    BaseScheduler,
    AdaptiveScheduler,
)
from memograph.db.database import DatabaseManager

logger = logging.getLogger("memograph.daemon")


class DaemonStatus:
    """Runtime status of the daemon."""

    STOPPED   = "stopped"
    STARTING  = "starting"
    RUNNING   = "running"
    SLEEPING  = "sleeping"
    DREAMING  = "dreaming"
    STOPPING  = "stopping"
    ERRORED   = "errored"


class DaemonStats:
    """Daemon runtime statistics."""

    def __init__(self):
        self.started_at:        Optional[datetime] = None
        self.total_checks:      int                = 0
        self.total_dream_runs:  int                = 0
        self.total_skips:       int                = 0
        self.total_errors:      int                = 0
        self.last_check_at:     Optional[datetime] = None
        self.last_dream_at:     Optional[datetime] = None
        self.last_error_at:     Optional[datetime] = None
        self.last_error_msg:    Optional[str]      = None
        self.consecutive_errors: int               = 0

    def to_dict(self) -> dict:
        return {
            "started_at":          str(self.started_at),
            "total_checks":        self.total_checks,
            "total_dream_runs":    self.total_dream_runs,
            "total_skips":         self.total_skips,
            "total_errors":        self.total_errors,
            "last_check_at":       str(self.last_check_at),
            "last_dream_at":       str(self.last_dream_at),
            "last_error_at":       str(self.last_error_at),
            "last_error_msg":      self.last_error_msg,
            "consecutive_errors":  self.consecutive_errors,
```

```
        }


class ConsolidationDaemon:
    """
    Background consolidation daemon.

    Runs the dream engine periodically according to the configured scheduler.

    Features:
    - Graceful start/stop
    - Adaptive scheduling
    - Error backoff (stops after 5 consecutive errors)
    - Run callbacks (notify on dream completion)
    - Manual trigger (skip scheduler, run now)
    - Status inspection

    Usage:
        daemon = ConsolidationDaemon(dream_engine, db)
        await daemon.start()

        # Later...
        result = await daemon.trigger_now()   # Force immediate run
        await daemon.stop()
    """

    MAX_CONSECUTIVE_ERRORS = 5
    ERROR_BACKOFF_SECONDS  = 60 * 5   # 5-minute backoff after errors

    def __init__(
        self,
        dream_engine:   DreamEngine,
        db:             DatabaseManager,
        scheduler:      Optional[BaseScheduler]      = None,
        on_dream_done:  Optional[Callable[[DreamResult], None]] = None,
    ):
        self.engine    = dream_engine
        self.db        = db
        self.scheduler = scheduler or AdaptiveScheduler()
        self.on_dream_done = on_dream_done

        self._status:  str                     = DaemonStatus.STOPPED
        self._task:    Optional[asyncio.Task] = None
        self._stop_event                       = asyncio.Event()
        self._trigger_event                    = asyncio.Event()
        self._force_trigger                    = False

        self.stats  = DaemonStats()
        self.agent_id = dream_engine.agent_id

    # ──────────────────────────────────────────────────────────────────────
    # LIFECYCLE
    # ──────────────────────────────────────────────────────────────────────

    async def start(self) -> None:
        """Start the background daemon task."""
        if self._status not in (DaemonStatus.STOPPED, DaemonStatus.ERRORED):
            logger.warning(f"Daemon already running (status={self._status})")
```

```
            return

        self._status    = DaemonStatus.STARTING
        self._stop_event.clear()
        self._trigger_event.clear()

        # Record our PID
        await self.db.upsert_dream_state(
            agent_id=self.agent_id,
            daemon_pid=os.getpid(),
            daemon_started_at=datetime.now().isoformat(),
        )

        # Start background task
        self._task = asyncio.create_task(
            self._loop(),
            name=f"memograph.daemon.{self.agent_id}",
        )

        self._status        = DaemonStatus.RUNNING
        self.stats.started_at = datetime.now()

        logger.info(
            f"Consolidation daemon started — "
            f"agent={self.agent_id}, "
            f"scheduler={self.scheduler.__class__.__name__}, "
            f"pid={os.getpid()}"
        )

    async def stop(self, timeout_seconds: int = 30) -> None:
        """
        Gracefully stop the daemon.
        Waits for the current dream to finish before stopping.
        """
        if self._status == DaemonStatus.STOPPED:
            return

        logger.info(f"Stopping consolidation daemon (agent={self.agent_id})")
        self._status = DaemonStatus.STOPPING
        self._stop_event.set()

        if self._task:
            try:
                await asyncio.wait_for(self._task, timeout=timeout_seconds)
            except asyncio.TimeoutError:
                logger.warning(
                    f"Daemon did not stop within {timeout_seconds}s — cancelling"
                )
                self._task.cancel()
                try:
                    await self._task
                except asyncio.CancelledError:
                    pass

        self._status = DaemonStatus.STOPPED
        logger.info("Consolidation daemon stopped")

    async def trigger_now(self, force: bool = False) -> DreamResult:
```

```
        """
        Trigger an immediate dream run.
        Bypasses the scheduler wait but still checks gates
        (unless force=True which bypasses all gates).

        Returns the DreamResult.
        """
        logger.info(f"Manual dream trigger (force={force})")
        self._force_trigger = force
        self._trigger_event.set()

        # Run directly if daemon isn't running
        if self._status == DaemonStatus.STOPPED:
            return await self.engine.run(trigger="manual", force=force)

        # Otherwise let the daemon loop handle it and return the result
        result = await self.engine.run(trigger="manual", force=force)
        return result

    # ──────────────────────────────────────────────────────────────────────
    # MAIN LOOP
    # ──────────────────────────────────────────────────────────────────────

    async def _loop(self) -> None:
        """
        Main daemon loop.

        Each iteration:
        1. Determine wait time from scheduler
        2. Wait (sleep) unless triggered manually
        3. Check if we should stop
        4. Run the dream engine
        5. Handle errors with backoff
        """
        logger.debug(f"Daemon loop started for agent={self.agent_id}")

        while not self._stop_event.is_set():
            try:
                # Get wait time from scheduler
                dream_state    = await self.db.get_dream_state(self.agent_id)
                last_consolidated = None
                if dream_state and dream_state.get("last_consolidated_at"):
                    last_consolidated = datetime.fromisoformat(
                        dream_state["last_consolidated_at"]
                    )

                session_count = await self.db.count_sessions_since(
                    self.agent_id,
                    (last_consolidated or datetime.min).isoformat(),
                )

                wait_seconds = await self.scheduler.next_wait_seconds(
                    last_run=last_consolidated,
                    session_count=session_count,
                )

                # Sleep with interruptibility
                self._status = DaemonStatus.SLEEPING
```

```
                await self._interruptible_sleep(wait_seconds)

                # Check stop signal
                if self._stop_event.is_set():
                    break

                # Run dream
                self._status = DaemonStatus.DREAMING
                self.stats.total_checks  += 1
                self.stats.last_check_at  = datetime.now()

                force_run = (
                    self._force_trigger
                    or self.scheduler.should_force_run(last_consolidated, session_count)
                )
                self._force_trigger = False
                self._trigger_event.clear()

                result = await self.engine.run(
                    trigger="daemon",
                    force=force_run,
                )

                # Update stats
                if result.skipped:
                    self.stats.total_skips       += 1
                else:
                    self.stats.total_dream_runs  += 1
                    self.stats.last_dream_at      = datetime.now()
                    self.stats.consecutive_errors = 0  # Reset error counter

                    logger.info(
                        f"Dream run complete: {result.summary()}"
                    )

                # Fire callback
                if self.on_dream_done and not result.skipped:
                    try:
                        self.on_dream_done(result)
                    except Exception as e:
                        logger.warning(f"on_dream_done callback failed: {e}")

                self._status = DaemonStatus.RUNNING

            except asyncio.CancelledError:
                logger.info("Daemon task cancelled")
                break

            except Exception as e:
                self.stats.total_errors      += 1
                self.stats.consecutive_errors += 1
                self.stats.last_error_at      = datetime.now()
                self.stats.last_error_msg     = str(e)
                self._status                  = DaemonStatus.ERRORED

                logger.error(
                    f"Daemon error #{self.stats.consecutive_errors}: {e}",
                    exc_info=True,
```

```
                )

                # Stop daemon after too many consecutive errors
                if self.stats.consecutive_errors >= self.MAX_CONSECUTIVE_ERRORS:
                    logger.critical(
                        f"Daemon stopping after {self.MAX_CONSECUTIVE_ERRORS} "
                        f"consecutive errors"
                    )
                    self._stop_event.set()
                    break

                # Wait before retrying
                logger.info(
                    f"Daemon backing off for {self.ERROR_BACKOFF_SECONDS}s"
                )
                await self._interruptible_sleep(self.ERROR_BACKOFF_SECONDS)

        self._status = DaemonStatus.STOPPED
        logger.debug(f"Daemon loop exited for agent={self.agent_id}")

    async def _interruptible_sleep(self, seconds: float) -> None:
        """
        Sleep for N seconds, but wake up immediately if:
        - Stop event is set
        - Manual trigger event is set
        """
        try:
            await asyncio.wait_for(
                asyncio.shield(
                    asyncio.ensure_future(
                        self._wait_for_any(
                            self._stop_event,
                            self._trigger_event,
                        )
                    )
                ),
                timeout=seconds,
            )
        except asyncio.TimeoutError:
            pass   # Normal — sleep expired

    @staticmethod
    async def _wait_for_any(*events: asyncio.Event) -> None:
        """Wait until any of the given events is set."""
        tasks = [asyncio.create_task(e.wait()) for e in events]
        try:
            done, pending = await asyncio.wait(
                tasks,
                return_when=asyncio.FIRST_COMPLETED,
            )
            for t in pending:
                t.cancel()
        except asyncio.CancelledError:
            for t in tasks:
                t.cancel()
            raise

    # ──────────────────────────────────────────────────────────────────
```

```
    # STATUS & DIAGNOSTICS
    # ──────────────────────────────────────────────────────────────────────

    @property
    def status(self) -> str:
        return self._status

    @property
    def is_running(self) -> bool:
        return self._status not in (DaemonStatus.STOPPED, DaemonStatus.ERRORED)

    def get_stats(self) -> dict:
        return {
            "status":    self._status,
            "agent_id":  self.agent_id,
            "pid":       os.getpid(),
            "scheduler": self.scheduler.__class__.__name__,
            **self.stats.to_dict(),
        }
```

---

15. Integration into MemoryManager

Python

```
# memograph/core/memory_manager.py  (Phase 3 additions)
"""
Add start_dream(), stop_dream(), trigger_dream() to MemoryManagerV2.
"""

# Add these imports to memory_manager.py:
from memograph.consolidation.dream_engine import DreamEngine, DreamResult
from memograph.consolidation.daemon import ConsolidationDaemon
from memograph.consolidation.gates import ConsolidationGates
from memograph.consolidation.lock import ConsolidationLock
from memograph.consolidation.scheduler import AdaptiveScheduler

# Add these attributes to MemoryManagerV2.__init__:
#   self._lock   = None
#   self._gates  = None
#   self._dream  = None
#   self._daemon = None

# Add these methods to MemoryManagerV2:

    async def _init_dream_engine(self) -> None:
        """Initialize the consolidation subsystem."""
        self._lock  = ConsolidationLock(self.base_path)
        self._gates = ConsolidationGates(
            min_hours=self.config.limits.min_consolidation_hours,
            min_sessions=self.config.limits.min_consolidation_sessions,
        )
        self._dream = DreamEngine(
```

```
            config=self.config,
            db=self._db,
            index_engine=self._index_engine,
            topic_manager=self._topic_manager,
            llm=self._llm,
            lock=self._lock,
            gates=self._gates,
        )

        if self.config.auto_consolidate:
            self._daemon = ConsolidationDaemon(
                dream_engine=self._dream,
                db=self._db,
                scheduler=AdaptiveScheduler(),
            )
            await self._daemon.start()
            logger.info("AutoDream daemon started")

    async def dream_now(self, force: bool = False) -> DreamResult:
        """
        Trigger an immediate consolidation run.

        Args:
            force: If True, skip time/session gates (admin use only).

        Returns:
            DreamResult with full audit information.
        """
        if self._dream is None:
            await self._init_dream_engine()
        return await self._dream.run(trigger="manual", force=force)

    async def get_dream_history(self, limit: int = 10) -> list[dict]:
        """Get recent dream run history."""
        if self._dream is None:
            return []
        return await self._dream.get_history(limit)

    def get_daemon_stats(self) -> dict:
        """Get daemon runtime statistics."""
        if self._daemon is None:
            return {"status": "not_started"}
        return self._daemon.get_stats()
```

---

16. Full Phase 3 Test Suite

Python

```
# tests/test_gates.py

import pytest
from datetime import datetime, timedelta
```

```python
from memograph.consolidation.gates import ConsolidationGates


def test_gates_pass_when_fresh():
    gates = ConsolidationGates(
        min_hours=24,
        min_sessions=5,
        scan_interval_minutes=10,
    )
    # First run ever
    report = gates.check_all(
        last_consolidated=None,
        session_count=10,
        lock_available=True,
    )
    assert report.all_passed is True


def test_time_gate_blocks_too_soon():
    gates = ConsolidationGates(min_hours=24, min_sessions=5)
    last = datetime.now() - timedelta(hours=2)  # Only 2h ago

    result = gates.check_time_gate(last_consolidated=last)
    assert result.passed is False
    assert "2.0h" in result.reason or "Only" in result.reason


def test_time_gate_passes_after_threshold():
    gates = ConsolidationGates(min_hours=24, min_sessions=5)
    last = datetime.now() - timedelta(hours=25)

    result = gates.check_time_gate(last_consolidated=last)
    assert result.passed is True


def test_session_gate_blocks_too_few():
    gates = ConsolidationGates(min_sessions=5)
    result = gates.check_session_gate(session_count=3)

    assert result.passed is False
    assert "2 more" in result.reason


def test_session_gate_passes_at_threshold():
    gates = ConsolidationGates(min_sessions=5)
    result = gates.check_session_gate(session_count=5)
    assert result.passed is True


def test_lock_gate_blocks_when_unavailable():
    gates = ConsolidationGates()
    result = gates.check_lock_gate(lock_available=False)
    assert result.passed is False


def test_scan_interval_blocks_too_soon():
    gates = ConsolidationGates(scan_interval_minutes=60)
    gates.check_scan_interval()  # First call — sets _last_scan
```

```
    result = gates.check_scan_interval()  # Second call immediately
    assert result.passed is False


def test_force_mode_bypasses_all():
    forced_gates = ConsolidationGates.forced()
    report = forced_gates.check_all(
        last_consolidated=datetime.now() - timedelta(minutes=5),
        session_count=0,
        lock_available=True,
    )
    assert report.all_passed is True


def test_gate_report_summary():
    gates = ConsolidationGates(min_sessions=10)
    report = gates.check_all(
        last_consolidated=None,
        session_count=2,  # Too few
        lock_available=True,
    )
    assert not report.all_passed
    assert "session_count" in report.summary()


def test_gate_report_to_dict():
    gates = ConsolidationGates.forced()
    report = gates.check_all(
        last_consolidated=None,
        session_count=0,
        lock_available=True,
    )
    d = report.to_dict()
    assert "all_passed" in d
    assert "results" in d
    assert isinstance(d["results"], list)
```

Python

```
# tests/test_lock.py

import asyncio
import os
import time
import pytest
from pathlib import Path
from memograph.consolidation.lock import ConsolidationLock, LOCK_STALE_SECONDS


@pytest.mark.asyncio
async def test_lock_available_when_no_file(tmp_path):
    lock = ConsolidationLock(tmp_path)
    assert lock.is_available() is True


@pytest.mark.asyncio
```

```python
async def test_lock_acquire_and_release(tmp_path):
    lock = ConsolidationLock(tmp_path)

    async with lock.acquire() as acquired:
        assert acquired is True
        assert lock.lock_path.exists()

        # While held — unavailable for another acquire
        state = lock.get_state()
        assert state.holder_pid == os.getpid()


@pytest.mark.asyncio
async def test_lock_mtime_updated_on_success(tmp_path):
    lock = ConsolidationLock(tmp_path)
    before = time.time()

    async with lock.acquire() as acquired:
        assert acquired is True

    after   = time.time()
    mtime   = lock.lock_path.stat().st_mtime
    assert before <= mtime <= after + 1


@pytest.mark.asyncio
async def test_lock_mtime_rolled_back_on_failure(tmp_path):
    lock = ConsolidationLock(tmp_path)

    # Write initial lock to set a known mtime
    lock.lock_path.parent.mkdir(parents=True, exist_ok=True)
    lock.lock_path.write_text("12345")
    initial_mtime = time.time() - 1000
    os.utime(lock.lock_path, (initial_mtime, initial_mtime))

    try:
        async with lock.acquire() as acquired:
            if acquired:
                raise RuntimeError("Simulated failure")
    except RuntimeError:
        pass

    # mtime should be rolled back
    final_mtime = lock.lock_path.stat().st_mtime
    assert abs(final_mtime - initial_mtime) < 2


@pytest.mark.asyncio
async def test_lock_stale_detection(tmp_path):
    lock = ConsolidationLock(tmp_path)

    # Create a stale lock file (old mtime)
    lock.lock_path.parent.mkdir(parents=True, exist_ok=True)
    lock.lock_path.write_text("99999")  # Non-existent PID
    stale_mtime = time.time() - LOCK_STALE_SECONDS - 100
    os.utime(lock.lock_path, (stale_mtime, stale_mtime))

    # Should be available (stale lock is treated as free)
```

```
    assert lock.is_available() is True

    state = lock.get_state()
    assert state.is_stale is True


@pytest.mark.asyncio
async def test_get_last_consolidated(tmp_path):
    lock = ConsolidationLock(tmp_path)

    # No file — returns None
    assert lock.get_last_consolidated() is None

    # After a successful acquire
    async with lock.acquire() as acquired:
        assert acquired is True

    last = lock.get_last_consolidated()
    assert last is not None
    assert (time.time() - last.timestamp()) < 5   # Recent


@pytest.mark.asyncio
async def test_force_release(tmp_path):
    lock = ConsolidationLock(tmp_path)

    lock.lock_path.parent.mkdir(parents=True, exist_ok=True)
    lock.lock_path.write_text(str(os.getpid()))

    assert lock.lock_path.exists()
    released = lock.force_release()
    assert released is True

    assert not lock.lock_path.exists()
```

Python

```
# tests/test_dream_engine.py

import asyncio
import pytest
from datetime import datetime
from pathlib import Path
from unittest.mock import AsyncMock, MagicMock, patch

from memograph.config import MemoGraphConfig, LLMProvider
from memograph.consolidation.dream_engine import DreamEngine
from memograph.consolidation.gates import ConsolidationGates
from memograph.consolidation.lock import ConsolidationLock
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.base import LLMResponse


@pytest.fixture
```

```python
async def dream_setup(tmp_path):
    """Full dream engine setup with real SQLite + mock LLM."""
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="dream_test",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
        limits=MemoGraphConfig.__fields__["limits"].default_factory(),
    )

    db = DatabaseManager(config.db_path)
    await db.connect()
    await db.ensure_agent(config.agent_id)

    index_engine  = IndexEngine(config, db)
    await index_engine.initialize()

    topic_manager = TopicManager(config, db)

    # Mock LLM — returns valid JSON for all phases
    mock_llm = MagicMock()
    mock_llm.complete = AsyncMock(return_value=LLMResponse(
        content='{"signals": [], "skipped_count": 0, "skip_reasons": []}',
        provider="mock",
        model="mock-model",
        prompt_tokens=100,
        completion_tokens=50,
    ))
    mock_llm.provider_name = "mock"

    lock  = ConsolidationLock(Path(config.base_path))
    gates = ConsolidationGates.forced()  # Skip all time/session gates

    engine = DreamEngine(
        config=config,
        db=db,
        index_engine=index_engine,
        topic_manager=topic_manager,
        llm=mock_llm,
        lock=lock,
        gates=gates,
    )

    yield engine, config, db

    await db.disconnect()


@pytest.mark.asyncio
async def test_dream_runs_all_phases(dream_setup):
    engine, config, db = dream_setup

    result = await engine.run(trigger="test", force=True)

    # Should complete (not skip)
    assert not result.skipped
    assert "orient" in result.phase_results
```

```
    assert "gather" in result.phase_results
    assert "consolidate" in result.phase_results
    assert "prune" in result.phase_results


@pytest.mark.asyncio
async def test_dream_persists_run_to_db(dream_setup):
    engine, config, db = dream_setup

    result = await engine.run(trigger="test", force=True)

    # Check DB record was created
    run = await db.get_dream_run(config.agent_id, result.run_id)
    assert run is not None
    assert run["status"] == "completed"
    assert run["trigger"] == "test"


@pytest.mark.asyncio
async def test_dream_result_summary(dream_setup):
    engine, config, db = dream_setup

    result = await engine.run(force=True)
    summary = result.summary()

    assert "status" in summary
    assert "phases" in summary
    assert "outcomes" in summary
    assert "llm_usage" in summary


@pytest.mark.asyncio
async def test_dream_blocked_without_force(dream_setup):
    engine, config, db = dream_setup

    # Use real gates (not forced) — will block on scan interval
    real_gates = ConsolidationGates(
        min_hours=24,
        min_sessions=5,
        scan_interval_minutes=10,
    )
    engine.gates = real_gates

    result = await engine.run(trigger="daemon", force=False)

    # Should be skipped (gates not passed)
    assert result.skipped is True


@pytest.mark.asyncio
async def test_dream_state_updated_after_run(dream_setup):
    engine, config, db = dream_setup

    await engine.run(force=True)

    state = await db.get_dream_state(config.agent_id)
    assert state is not None
    assert state["last_consolidated_at"] is not None
```

```python
@pytest.mark.asyncio
async def test_dream_with_existing_topics(dream_setup):
    engine, config, db = dream_setup

    # Pre-populate memory
    from memograph.models.topic import MemoryFact, TopicFile
    from memograph.config import ConfidenceLevel

    topic = TopicFile(
        topic_id="test_topic",
        topic_name="Test Topic",
        agent_id=config.agent_id,
    )
    topic.facts.append(MemoryFact(
        content="Uses Python 3.11",
        confidence=ConfidenceLevel.OBSERVED,
        source="test",
    ))
    topic.facts.append(MemoryFact(
        content="Deployed on Railway",
        confidence=ConfidenceLevel.STALE,
        source="test",
    ))

    await engine.topic_manager.save_topic(topic)
    await engine.index_engine.add_pointer(
        topic_id="test_topic",
        topic_file_path="topics/test_topic.json",
        summary="Test topic with Python and deployment info",
        confidence=0.5,
    )

    result = await engine.run(force=True)
    assert not result.skipped
    assert result.phase_results["orient"].success


@pytest.mark.asyncio
async def test_dream_history(dream_setup):
    engine, config, db = dream_setup

    # Run twice
    await engine.run(force=True)
    await engine.run(force=True)

    history = await engine.get_history(limit=5)
    assert len(history) >= 2

    assert all("run_id" in r for r in history)
```

Python

```
# tests/test_daemon.py
```

```python
import asyncio
import pytest
from unittest.mock import AsyncMock, MagicMock

from memograph.consolidation.daemon import (
    ConsolidationDaemon,
    DaemonStatus,
)
from memograph.consolidation.dream_engine import DreamResult
from memograph.consolidation.scheduler import FixedIntervalScheduler


@pytest.fixture
def mock_dream_engine():
    engine = MagicMock()
    engine.agent_id = "test_agent"

    # Default: returns a skipped result (no work to do)
    engine.run = AsyncMock(return_value=DreamResult(
        run_id="test_run",
        skipped=True,
        skip_reason="Test",
    ))
    return engine


@pytest.fixture
def mock_db():
    db = MagicMock()
    db.get_dream_state         = AsyncMock(return_value=None)
    db.count_sessions_since    = AsyncMock(return_value=0)
    db.upsert_dream_state      = AsyncMock()
    return db


@pytest.mark.asyncio
async def test_daemon_starts_and_stops(mock_dream_engine, mock_db):
    daemon = ConsolidationDaemon(
        dream_engine=mock_dream_engine,
        db=mock_db,
        scheduler=FixedIntervalScheduler(check_interval_seconds=9999),
    )

    await daemon.start()
    assert daemon.status in (DaemonStatus.RUNNING, DaemonStatus.SLEEPING)

    await daemon.stop(timeout_seconds=5)
    assert daemon.status == DaemonStatus.STOPPED


@pytest.mark.asyncio
async def test_daemon_not_double_started(mock_dream_engine, mock_db):
    daemon = ConsolidationDaemon(
        dream_engine=mock_dream_engine,
        db=mock_db,
        scheduler=FixedIntervalScheduler(check_interval_seconds=9999),
    )
```

```
    await daemon.start()
    await daemon.start()  # Should not raise

    assert daemon.is_running
    await daemon.stop(timeout_seconds=5)


@pytest.mark.asyncio
async def test_daemon_trigger_now(mock_dream_engine, mock_db):
    mock_dream_engine.run = AsyncMock(return_value=DreamResult(
        run_id="manual_run",
        skipped=False,
        phase_results={},
        ctx=MagicMock(
            facts_merged=1, facts_created=0, facts_pruned=0,
            contradictions_resolved=0, confidence_promoted=0,
            pointers_pruned=0, topics_modified=[],
            total_prompt_tokens=100, total_completion_tokens=50,
            total_llm_latency_ms=200, llm_provider="mock",
            llm_model="mock", new_signals=[],
        ),
    ))

    daemon = ConsolidationDaemon(
        dream_engine=mock_dream_engine,
        db=mock_db,
        scheduler=FixedIntervalScheduler(check_interval_seconds=9999),
    )

    result = await daemon.trigger_now(force=True)
    assert result.run_id == "manual_run"


@pytest.mark.asyncio
async def test_daemon_callback_fired(mock_dream_engine, mock_db):
    callback_results = []

    def callback(result: DreamResult):
        callback_results.append(result)

    # Return a successful result
    mock_dream_engine.run = AsyncMock(return_value=DreamResult(
        run_id="cb_run",
        skipped=False,
        phase_results={},
        ctx=MagicMock(
            facts_merged=0, facts_created=1, facts_pruned=0,
            contradictions_resolved=0, confidence_promoted=0,
            pointers_pruned=0, topics_modified=["t1"],
            total_prompt_tokens=50, total_completion_tokens=25,
            total_llm_latency_ms=100, llm_provider="mock",
            llm_model="mock", new_signals=[],
        ),
    ))

    daemon = ConsolidationDaemon(
        dream_engine=mock_dream_engine,
        db=mock_db,
```

```
        scheduler=FixedIntervalScheduler(check_interval_seconds=1),
        on_dream_done=callback,
    )

    await daemon.start()
    await asyncio.sleep(2)   # Wait for one cycle
    await daemon.stop(timeout_seconds=5)

    assert len(callback_results) >= 1


@pytest.mark.asyncio
async def test_daemon_stats(mock_dream_engine, mock_db):
    daemon = ConsolidationDaemon(
        dream_engine=mock_dream_engine,
        db=mock_db,
        scheduler=FixedIntervalScheduler(check_interval_seconds=9999),
    )
    await daemon.start()

    stats = daemon.get_stats()
    assert "status" in stats
    assert "total_checks" in stats
    assert "agent_id" in stats

    await daemon.stop(timeout_seconds=5)


# tests/test_consolidation_integration.py

import asyncio
import pytest
from pathlib import Path

from memograph import MemoGraph
from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider


@pytest.fixture
async def mg(tmp_path):
    """Full MemoGraph instance with mock LLM, auto-consolidate OFF."""
    from unittest.mock import AsyncMock, MagicMock
    from memograph.llm.base import LLMResponse

    mock_llm = MagicMock()
    mock_llm.complete = AsyncMock(return_value=LLMResponse(
        content='{"signals":[],"skipped_count":0,"skip_reasons":[]}',
        provider="mock",
        model="mock-model",
        prompt_tokens=50,
        completion_tokens=25,
    ))
    mock_llm.complete_simple = AsyncMock(
        return_value='{"has_contradiction": false}'
    )
    mock_llm.provider_name = "mock"

    config = MemoGraphConfig(
```

```
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="integration_test",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
    )

    from memograph.core.memory_manager import MemoryManagerV2
    from memograph.db.database import DatabaseManager

    db  = DatabaseManager(config.db_path)
    mgr = MemoryManagerV2(config=config, llm=mock_llm, db=db)
    await mgr.initialize()

    yield mgr
    await mgr.close()


@pytest.mark.asyncio
async def test_remember_then_dream(mg, tmp_path):
    """Full integration: store facts → trigger dream → verify state."""

    # Store facts across multiple topics
    for i in range(5):
        await mg.remember(
            topic_id=f"topic_{i}",
            content=f"Fact {i}: some important project information",
            source="integration_test",
            confidence=ConfidenceLevel.OBSERVED,
        )

    # Simulate sessions for gate
    for j in range(5):
        session = await mg.start_session(f"sess_{j:03d}")
        await mg.archive_turn("user", f"Test message {j}")
        await mg.end_session(turn_count=1)

    # Initialize dream engine
    await mg._init_dream_engine()

    # Force dream run
    result = await mg.dream_now(force=True)

    assert not result.skipped, f"Dream was skipped: {result.skip_reason}"
    assert result.phase_results.get("orient") is not None
    assert result.phase_results.get("gather") is not None
    assert result.phase_results.get("consolidate") is not None
    assert result.phase_results.get("prune") is not None


@pytest.mark.asyncio
async def test_dream_history_stored(mg):
    await mg._init_dream_engine()

    await mg.dream_now(force=True)
    await mg.dream_now(force=True)

    history = await mg.get_dream_history(limit=5)
```

```
    assert len(history) >= 2
    assert all(h["status"] in ("completed", "failed") for h in history)


@pytest.mark.asyncio
async def test_lock_prevents_concurrent_dreams(mg):
    await mg._init_dream_engine()

    # Run two dreams concurrently
    results = await asyncio.gather(
        mg.dream_now(force=True),
        mg.dream_now(force=True),
    )

    # At least one should succeed, the other may be skipped (lock)
    statuses = [r.skipped for r in results]

    assert not all(statuses), "Both dreams were skipped — at least one should run"
```

---

17. Phase 3 Example

Python

```
# examples/phase3_autodream.py
"""
Phase 3 Demo — AutoDream consolidation in action.

Shows:
1. Storing facts across many sessions
2. Background daemon running
3. Manual dream trigger
4. Dream history inspection
5. Lock state inspection
"""

import asyncio
import logging
from pathlib import Path

from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
from memograph.consolidation.daemon import ConsolidationDaemon
from memograph.consolidation.dream_engine import DreamEngine
from memograph.consolidation.gates import ConsolidationGates
from memograph.consolidation.lock import ConsolidationLock
from memograph.consolidation.scheduler import AdaptiveScheduler
from memograph.core.index_engine import IndexEngine
from memograph.core.memory_manager import MemoryManagerV2
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.factory import create_provider
```

```python
logging.basicConfig(
    level=logging.INFO,
    format="%(asctime)s [%(name)s] %(levelname)s: %(message)s",
)
logger = logging.getLogger("phase3_demo")


async def main():
    # ── Setup ──────────────────────────────────────────────────────────
    base_path = Path(".memograph/phase3_demo")
    base_path.mkdir(parents=True, exist_ok=True)

    config = MemoGraphConfig(
        base_path=str(base_path),
        db_path=str(base_path / "demo.db"),
        agent_id="phase3_agent",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,   # Manual control for demo
    )

    # Use Ollama (change to your preferred provider)
    # For demo without LLM, set llm=None (signals applied directly)
    try:
        llm = create_provider("ollama", model="llama3.1:8b", config=config)
        llm_available = await llm.health_check()
        if not llm_available:
            logger.warning("Ollama not available — running without LLM")
            llm = None
    except Exception:
        logger.warning("LLM provider error — running without LLM")
        llm = None

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)

        index_engine  = IndexEngine(config, db)
        await index_engine.initialize()

        topic_manager = TopicManager(config, db)

        # ── Phase 3 components ─────────────────────────────────────────
        lock  = ConsolidationLock(base_path)
        gates = ConsolidationGates(
            min_hours=0,         # 0 for demo (normally 24)
            min_sessions=3,
            scan_interval_minutes=0,
        )

        engine = DreamEngine(
            config=config,
            db=db,
            index_engine=index_engine,
            topic_manager=topic_manager,
            llm=llm,
            lock=lock,
            gates=gates,
        )
```

```
        # ── 1. Simulate several sessions with memories ──────────────────────
        logger.info("=== Step 1: Storing facts across sessions ===")

        mem = MemoryManagerV2(config=config, llm=llm, db=db)
        await mem.initialize()

        topics_and_facts = [
            ("tech_stack",    "Backend uses FastAPI with async PostgreSQL",
"session_1"),
            ("tech_stack",    "Frontend is Next.js 14 with TypeScript",
"session_1"),
            ("user_prefs",    "User wants dark mode enabled by default",
"session_2"),
            ("user_prefs",    "User confirmed dark mode preference explicitly",
"session_3"),
            ("deployment",    "Hosted on Railway, not AWS",
"session_2"),
            ("deployment",    "Uses Railway for both staging and production",
"session_4"),
            ("arch_decisions","Chose asyncpg over SQLAlchemy for performance",
"session_3"),
            ("arch_decisions","Redis used for caching hot queries only",
"session_4"),
        ]

        for topic_id, content, source in topics_and_facts:
            result = await mem.remember(
                topic_id=topic_id,
                content=content,
                source=source,
                confidence=ConfidenceLevel.OBSERVED,
            )
            logger.info(f"  Stored [{topic_id}]: {content[:50]}... → {result.success}")

        # Simulate sessions
        for i in range(5):
            sid = await mem.start_session(f"demo_session_{i:03d}")
            await mem.archive_turn("user", f"User query in session {i}")
            await mem.archive_turn("assistant", f"Response in session {i}")
            await mem.end_session(turn_count=2)

        logger.info("Memory stored and sessions recorded\n")

        # ── 2. Check lock state ─────────────────────────────────────────────
        logger.info("=== Step 2: Lock inspection ===")
        lock_state = lock.get_state()
        logger.info(f"  Lock held: {lock_state.held}")
        logger.info(f"  Last consolidated: {lock_state.last_consolidated}")
        logger.info(f"  Available: {lock.is_available()}\n")

        # ── 3. Check gate state ─────────────────────────────────────────────
        logger.info("=== Step 3: Gate check ===")
        dream_state   = await db.get_dream_state(config.agent_id)
        session_count = await db.count_sessions_since(
            config.agent_id,
            (dream_state or {}).get("last_consolidated_at") or "1970-01-01",
        )
        gate_report   = gates.check_all(
```

```
            last_consolidated=None,
            session_count=session_count,
            lock_available=lock.is_available(),
        )

        logger.info(f"  {gate_report.summary()}")
        for gr in gate_report.results:
            status = "✅" if gr.passed else "❌"
            logger.info(f"  {status} {gr.gate_name}: {gr.reason}")
        logger.info("")

        # ── 4. Manual dream trigger ──────────────────────────────────
        logger.info("=== Step 4: Manual dream run (force=True) ===")
        result = await engine.run(trigger="manual", force=True)

        if result.skipped:
            logger.warning(f"  Dream skipped: {result.skip_reason}")
        else:
            logger.info(f"  Run ID: {result.run_id}")
            logger.info(f"  Duration: {result.duration_ms}ms")
            logger.info(f"  Success: {result.success}")

            for phase, pr in result.phase_results.items():
                status = "✅" if pr.success else "❌"
                logger.info(
                    f"    {status} {phase}: "
                    f"{pr.duration_ms}ms — {pr.details}"
                )

            outcomes = result.summary()["outcomes"]
            logger.info(f"\n  Outcomes:")
            for k, v in outcomes.items():
                if v:
                    logger.info(f"    {k}: {v}")
        logger.info("")

        # ── 5. Inspect dream history ─────────────────────────────────
        logger.info("=== Step 5: Dream history ===")
        history = await engine.get_history(limit=5)
        for run in history:
            logger.info(
                f"  [{run['run_id']}] {run['status']} "
                f"({run['duration_ms']}ms) "
                f"merged={run['facts_merged']} "
                f"created={run['facts_created']}"
            )
        logger.info("")

        # ── 6. Post-dream memory state ───────────────────────────────
        logger.info("=== Step 6: Post-dream memory state ===")
        index = await index_engine.get_index()
        logger.info(f"  Index pointers: {len(index.pointers)}")

        for p in index.pointers:
            stale = " ⚠️" if p.is_stale else ""
            logger.info(
                f"  [{p.topic_id}]{stale} "
                f"conf={p.confidence:.2f} — {p.summary}"
```

```
            )
        logger.info("")

        # ── 7. Daemon demo ──────────────────────────────────────────
        logger.info("=== Step 7: Background daemon (5s demo) ===")

        completed_runs = []

        def on_dream_done(dr):
            completed_runs.append(dr)
            logger.info(f"  🌙 Dream completed: {dr.run_id} — {dr.summary()['status']}")

        daemon = ConsolidationDaemon(
            dream_engine=engine,
            db=db,
            scheduler=AdaptiveScheduler(),
            on_dream_done=on_dream_done,
        )

        await daemon.start()
        logger.info(f"  Daemon started — status: {daemon.status}")

        # Trigger manually
        trigger_result = await daemon.trigger_now(force=True)
        logger.info(f"  Manual trigger result: {trigger_result.run_id}")

        await asyncio.sleep(1)

        stats = daemon.get_stats()
        logger.info(f"  Daemon stats: {stats}")

        await daemon.stop()
        logger.info(f"  Daemon stopped — total runs: {stats['total_dream_runs']}")

        logger.info("\n=== Phase 3 Demo Complete ===")


if __name__ == "__main__":
    asyncio.run(main())
```

---

18. Run Phase 3

```
Bash


# Install Phase 3 dependencies
pip install -e ".[dev]"

# Run Phase 3 tests
pytest tests/test_gates.py -v
pytest tests/test_lock.py -v
pytest tests/test_dream_engine.py -v
pytest tests/test_daemon.py -v
```

```
pytest tests/test_consolidation_integration.py -v

# Run all tests
pytest tests/ -v --cov=memograph --cov-report=term-missing

# Run Phase 3 demo (Ollama optional)
python examples/phase3_autodream.py

# Quick smoke test (no LLM needed)
python -c "
import asyncio
from memograph.consolidation.gates import ConsolidationGates
from memograph.consolidation.lock import ConsolidationLock
from pathlib import Path

gates = ConsolidationGates.forced()
report = gates.check_all(None, 0, True)
print('Gates:', report.summary())

lock = ConsolidationLock(Path('/tmp/mg_test'))

async def test():
    async with lock.acquire() as ok:
        print('Lock acquired:', ok)
    print('Last consolidated:', lock.get_last_consolidated())

asyncio.run(test())
"
```

📊 Phase 3 Completion Checklist

Component	Status
`ConsolidationGates` — triple-gate with detailed reporting	✅
`ConsolidationLock` — mtime-based with PID tracking + rollback	✅
`DreamContext` — shared state bus between all phases	✅

`OrientPhase` — fast inventory without loading full topics	✅
`GatherPhase` — transcript reading + LLM signal extraction + grep	✅
`ConsolidatePhase` — LLM-driven merge/resolve/promote/prune with fallback	✅
`PrunePhase` — orphan removal, staleness detection, limit enforcement	✅
`DreamEngine` — full 4-phase orchestrator with DB audit trail	✅
`ConsolidationDaemon` — interruptible sleep, backoff, callbacks	✅
`AdaptiveScheduler` + `FixedIntervalScheduler`	✅
DB schema migration 002	✅
Full test suite — gates, lock, engine, daemon, integration	✅
Phase 3 demo example	

💉 PHASE 4 — BANDWIDTH-AWARE CONTEXT INJECTION ENGINE

The engine that decides what goes into the LLM's context window, when, and how much — the most performance-critical component in MemoGraph.

📋 Phase 4 Scope

Component	Description
TokenBudgetManager	Per-provider token counting, window pressure detection, budget allocation
RelevanceRanker	Score index pointers against query using keyword + TF-IDF hybrid
ContextBuilder	Per-turn context assembly with layer-aware injection

InjectionStrategies	Conservative / Balanced / Aggressive injection modes
SkepticalFormatter	Formats memory with verification hints and confidence markers
ContextCache	Per-turn caching to avoid re-building identical contexts
ContextPressureMonitor	Detect when context window is filling up, trigger emergency compaction
ProviderContextLimits	Known context window sizes per provider/model
StreamingContextUpdater	Update context mid-stream without full rebuild
Full test suite	Unit + integration + benchmark tests

New Files (Phase 4)

```
text
```

```
memograph/
├── injection/
│   ├── __init__.py
│   ├── token_budget.py          # Token counting + budget management
│   ├── relevance_ranker.py      # Query-aware pointer scoring
│   ├── context_builder.py       # Per-turn context assembly
│   ├── strategies.py            # Conservative/Balanced/Aggressive modes
│   ├── formatter.py             # Skeptical memory formatting
│   ├── context_cache.py         # Per-turn context cache
│   ├── pressure_monitor.py      # Context window pressure detection
│   ├── provider_limits.py       # Known context window sizes
│   └── streaming_updater.py     # Mid-stream context updates
├── prompts/
│   └── injection_prompts.py     # Context injection prompt templates
└── tests/
    ├── test_token_budget.py
    ├── test_relevance_ranker.py
```

```
    ├── test_context_builder.py
    ├── test_strategies.py
    ├── test_formatter.py
    ├── test_context_cache.py
    ├── test_pressure_monitor.py
    └── test_injection_integration.py
```

---

1. Provider Context Window Limits

Python

```python
# memograph/injection/provider_limits.py
"""
Known context window sizes for all supported providers and models.
Used by the token budget manager to calculate available space.

Sources: official provider documentation.
Updated periodically — override via config if your model differs.
"""

from __future__ import annotations

from dataclasses import dataclass
from typing import Optional


@dataclass(frozen=True)
class ContextWindowSpec:
    """Specification for a model's context window."""
    model_pattern:     str        # Substring match against model name
    context_tokens:    int        # Total context window size
    safe_output_tokens: int       # Reserve for completion
    provider:          str
    notes:             str = ""


# ── Complete registry of known models ──────────────────────────────
CONTEXT_WINDOW_REGISTRY: list[ContextWindowSpec] = [

    # ── Anthropic ──────────────────────────────────────────────────
    ContextWindowSpec("claude-3-5-sonnet",        200_000, 8_192,  "anthropic"),
    ContextWindowSpec("claude-3-5-haiku",         200_000, 8_192,  "anthropic"),
    ContextWindowSpec("claude-3-opus",            200_000, 4_096,  "anthropic"),
    ContextWindowSpec("claude-3-sonnet",          200_000, 4_096,  "anthropic"),
    ContextWindowSpec("claude-3-haiku",           200_000, 4_096,  "anthropic"),
    ContextWindowSpec("claude-2",                 100_000, 4_096,  "anthropic"),

    # ── OpenAI ─────────────────────────────────────────────────────
    ContextWindowSpec("gpt-4o",                   128_000, 4_096,  "openai"),
    ContextWindowSpec("gpt-4-turbo",              128_000, 4_096,  "openai"),
    ContextWindowSpec("gpt-4",                      8_192, 4_096,  "openai"),
    ContextWindowSpec("gpt-3.5-turbo-16k",         16_385, 4_096,  "openai"),
```

```
    ContextWindowSpec("gpt-3.5-turbo",              4_096, 2_048,  "openai"),
    ContextWindowSpec("o1",                       200_000, 32_768, "openai"),
    ContextWindowSpec("o3",                       200_000, 32_768, "openai"),

    # ── Groq (hosted open models) ──────────────────────────────────────
    ContextWindowSpec("llama-3.1-70b",            131_072, 4_096,  "groq"),
    ContextWindowSpec("llama-3.1-8b",             131_072, 4_096,  "groq"),
    ContextWindowSpec("llama-3.3-70b",            128_000, 4_096,  "groq"),
    ContextWindowSpec("mixtral-8x7b",              32_768, 4_096,  "groq"),
    ContextWindowSpec("gemma2-9b",                  8_192, 4_096,  "groq"),

    # ── Google Gemini ──────────────────────────────────────────────────
    ContextWindowSpec("gemini-1.5-pro",         2_000_000, 8_192,  "gemini"),
    ContextWindowSpec("gemini-1.5-flash",       1_000_000, 8_192,  "gemini"),
    ContextWindowSpec("gemini-2.0-flash",       1_000_000, 8_192,  "gemini"),
    ContextWindowSpec("gemini-1.0-pro",            32_760, 8_192,  "gemini"),

    # ── Ollama (local models) ──────────────────────────────────────────
    ContextWindowSpec("llama3.1:70b",             131_072, 4_096,  "ollama"),
    ContextWindowSpec("llama3.1:8b",              131_072, 4_096,  "ollama"),
    ContextWindowSpec("llama3.1:latest",          131_072, 4_096,  "ollama"),
    ContextWindowSpec("llama3.2:3b",               32_768, 4_096,  "ollama"),
    ContextWindowSpec("llama3.2:1b",               32_768, 2_048,  "ollama"),
    ContextWindowSpec("mistral:7b",                32_768, 4_096,  "ollama"),
    ContextWindowSpec("mistral:latest",            32_768, 4_096,  "ollama"),
    ContextWindowSpec("mixtral:8x7b",              32_768, 4_096,  "ollama"),
    ContextWindowSpec("phi3:mini",                128_000, 4_096,  "ollama"),
    ContextWindowSpec("phi3:medium",              128_000, 4_096,  "ollama"),
    ContextWindowSpec("phi4",                     128_000, 4_096,  "ollama"),
    ContextWindowSpec("qwen2.5:7b",               131_072, 4_096,  "ollama"),
    ContextWindowSpec("qwen2.5:14b",              131_072, 4_096,  "ollama"),
    ContextWindowSpec("qwen2.5:72b",              131_072, 4_096,  "ollama"),
    ContextWindowSpec("deepseek-r1:7b",            65_536, 4_096,  "ollama"),
    ContextWindowSpec("deepseek-r1:14b",           65_536, 4_096,  "ollama"),
    ContextWindowSpec("deepseek-r1:32b",           65_536, 4_096,  "ollama"),
    ContextWindowSpec("gemma2:2b",                  8_192, 2_048,  "ollama"),
    ContextWindowSpec("gemma2:9b",                  8_192, 4_096,  "ollama"),
    ContextWindowSpec("gemma2:27b",                 8_192, 4_096,  "ollama"),
    ContextWindowSpec("codellama:7b",              16_384, 4_096,  "ollama"),
    ContextWindowSpec("codellama:13b",             16_384, 4_096,  "ollama"),
    ContextWindowSpec("nomic-embed-text",           8_192, 0,      "ollama",
                      notes="Embedding model — no completion"),
]

# ── Fallback when model is unknown ─────────────────────────────────────
DEFAULT_CONTEXT_SPEC = ContextWindowSpec(
    model_pattern="default",
    context_tokens=8_192,
    safe_output_tokens=2_048,
    provider="unknown",
    notes="Conservative fallback for unknown models",
)


def get_context_spec(model: str, provider: str = "") -> ContextWindowSpec:
    """
    Look up the context window spec for a model.
    Matches by substring in model name (case-insensitive).
```

```
    Provider is used as a tiebreaker.

    Returns DEFAULT_CONTEXT_SPEC if no match found.
    """
    model_lower    = model.lower()
    provider_lower = provider.lower()

    # First: try exact provider + model match
    provider_matches = [
        s for s in CONTEXT_WINDOW_REGISTRY
        if s.provider == provider_lower
        and s.model_pattern.lower() in model_lower
    ]
    if provider_matches:
        # Return the most specific match (longest pattern)
        return max(provider_matches, key=lambda s: len(s.model_pattern))

    # Second: try any provider match
    any_matches = [
        s for s in CONTEXT_WINDOW_REGISTRY
        if s.model_pattern.lower() in model_lower
    ]
    if any_matches:
        return max(any_matches, key=lambda s: len(s.model_pattern))

    return DEFAULT_CONTEXT_SPEC


def list_models_by_provider(provider: str) -> list[ContextWindowSpec]:
    """List all known models for a provider."""
    return [s for s in CONTEXT_WINDOW_REGISTRY if s.provider == provider]


def get_largest_context_model(provider: str) -> Optional[ContextWindowSpec]:
    """Get the model with the largest context window for a provider."""
    models = list_models_by_provider(provider)
    return max(models, key=lambda s: s.context_tokens) if models else None
```

---

2. Token Budget Manager

Python

```
# memograph/injection/token_budget.py
"""
Token budget management for context injection.

Core responsibility:
- Know how many tokens we have available
- Allocate tokens across layers (index / topics / system / conversation)
- Track spending in real time
- Signal when budget is exhausted
```

```
Token counting strategy:
- Exact:   Use provider's tokenizer when available (tiktoken for OpenAI)
- Approx:  chars / 3.5  (conservative for multilingual text)
- Fast:    chars / 4    (English-heavy code/text)

The budget is split into fixed allocations:
   ┌──────────────────────────────────────────────────┐
   │  CONTEXT WINDOW  (e.g., 8,192 tokens)            │
   │  ├── System prompt          ( 5%)   ~  410 tokens    │
   │  ├── Memory index           ( 8%)   ~  655 tokens    │ ← always loaded
   │  ├── Topic files            (20%)   ~ 1,638 tokens   │ ← on-demand
   │  ├── Conversation history   (45%)   ~ 3,686 tokens   │
   │  └── Safe output reserve    (22%)   ~ 1,803 tokens   │
   └──────────────────────────────────────────────────┘
"""

from __future__ import annotations

import logging
import math
from dataclasses import dataclass, field
from typing import Optional

from memograph.injection.provider_limits import ContextWindowSpec, get_context_spec

logger = logging.getLogger("memograph.injection.budget")


@dataclass
class BudgetAllocation:
    """Token budget allocation across context layers."""

    total_context:      int    # Total context window
    safe_output:        int    # Reserved for model output
    available_input:    int    # Total available for input

    # Layer allocations (tokens)
    system_prompt:      int    # Fixed system prompt budget
    memory_index:       int    # Layer 1: always-loaded index
    topic_files:        int    # Layer 2: on-demand topics
    conversation:       int    # Conversation history
    overflow_buffer:    int    # Emergency buffer

    # Fractions used to compute allocations
    system_fraction:    float  = 0.05
    index_fraction:     float  = 0.08
    topic_fraction:     float  = 0.20
    conversation_fraction: float = 0.45
    buffer_fraction:    float  = 0.02

    def is_feasible(self) -> bool:
        """Check that allocations add up correctly."""
        allocated = (
            self.system_prompt + self.memory_index +
            self.topic_files + self.conversation + self.overflow_buffer
        )
        return allocated <= self.available_input
```

```
    def summary(self) -> dict:
        return {
            "total_context":   self.total_context,
            "safe_output":     self.safe_output,
            "available_input": self.available_input,
            "layers": {
                "system_prompt":  self.system_prompt,
                "memory_index":   self.memory_index,
                "topic_files":    self.topic_files,
                "conversation":   self.conversation,
                "overflow_buffer": self.overflow_buffer,
            },
        }


@dataclass
class BudgetSpend:
    """Tracks actual token spend during context building."""

    system_tokens:       int = 0
    index_tokens:        int = 0
    topic_tokens:        int = 0
    conversation_tokens: int = 0
    overhead_tokens:     int = 0   # Separators, labels, etc.

    @property
    def total(self) -> int:
        return (
            self.system_tokens + self.index_tokens +
            self.topic_tokens + self.conversation_tokens +
            self.overhead_tokens
        )

    def remaining(self, allocation: BudgetAllocation) -> dict[str, int]:
        """Remaining tokens per layer."""
        return {
            "system_prompt": max(0, allocation.system_prompt - self.system_tokens),
            "memory_index":  max(0, allocation.memory_index  - self.index_tokens),
            "topic_files":   max(0, allocation.topic_files   - self.topic_tokens),
            "conversation":  max(0, allocation.conversation  - self.conversation_tokens),
        }

    def usage_ratio(self, allocation: BudgetAllocation) -> float:
        """Overall usage ratio (0.0 - 1.0)."""
        return self.total / allocation.available_input if allocation.available_input > 0 else
0.0


class TokenCounter:
    """
    Estimates token count for text.

    Three modes:
    - tiktoken:  Exact, requires tiktoken package (OpenAI models)
    - sentencepiece: Exact, requires sentencepiece (LLaMA models)
    - approximate: Fast chars/N heuristic (all models)
    """
```

```
    # Characters per token approximation by content type
    CHARS_PER_TOKEN = {
        "code":    3.0,   # Code is token-dense
        "prose":   4.0,   # English prose
        "mixed":   3.5,   # Mixed content (default)
        "unicode": 2.5,   # Non-ASCII heavy content
    }

    def __init__(
        self,
        model:    str = "",
        provider: str = "",
        mode:     str = "approximate",    # approximate | tiktoken
    ):
        self.model    = model
        self.provider = provider
        self.mode     = mode
        self._enc     = None   # tiktoken encoder, lazy-loaded

        if mode == "tiktoken":
            self._try_load_tiktoken()

    def _try_load_tiktoken(self) -> None:
        """Try to load tiktoken encoder (optional dependency)."""
        try:
            import tiktoken
            model_name = self.model or "gpt-4o"
            try:
                self._enc = tiktoken.encoding_for_model(model_name)
            except KeyError:
                self._enc = tiktoken.get_encoding("cl100k_base")
            logger.debug(f"tiktoken loaded for {model_name}")
        except ImportError:
            logger.debug("tiktoken not available — using approximation")
            self.mode = "approximate"

    def count(self, text: str, content_type: str = "mixed") -> int:
        """Count tokens in text."""
        if not text:
            return 0

        if self.mode == "tiktoken" and self._enc:
            try:
                return len(self._enc.encode(text))
            except Exception:
                pass   # Fall through to approximation

        # Approximate counting
        chars_per_token = self.CHARS_PER_TOKEN.get(content_type, 3.5)
        return max(1, math.ceil(len(text) / chars_per_token))

    def count_messages(self, messages: list[dict]) -> int:
        """Count tokens in a list of chat messages."""
        total = 0
        for msg in messages:
            content = msg.get("content", "")
            total  += self.count(content)
            total  += 4   # Per-message overhead (role, formatting)
```

```
        total += 2  # Conversation-level overhead
        return total

    def fits_in_budget(self, text: str, budget: int) -> bool:
        """Check if text fits within a token budget."""
        return self.count(text) <= budget

    def truncate_to_budget(
        self,
        text:   str,
        budget: int,
        suffix: str = "\n[... truncated to fit context budget ...]",
    ) -> str:
        """
        Truncate text to fit within token budget.
        Uses binary search for efficiency.
        """
        if self.count(text) <= budget:
            return text

        suffix_tokens = self.count(suffix)
        content_budget = budget - suffix_tokens

        if content_budget <= 0:
            return suffix

        # Binary search for the right length
        lo, hi = 0, len(text)
        while lo < hi - 1:
            mid = (lo + hi) // 2
            if self.count(text[:mid]) <= content_budget:
                lo = mid
            else:
                hi = mid

        return text[:lo] + suffix


class TokenBudgetManager:
    """
    Manages token budgets for context injection.

    Usage:
        budget_mgr = TokenBudgetManager(model="llama3.1:8b", provider="ollama")
        allocation = budget_mgr.get_allocation()
        counter    = budget_mgr.counter

        # Check if index fits
        index_tokens = counter.count(index_markdown)
        if index_tokens <= allocation.memory_index:
            inject_index()
    """

    # Custom allocation overrides for different injection strategies
    STRATEGY_ALLOCATIONS = {
        "conservative": {
            "system_fraction":       0.05,
            "index_fraction":        0.06,  # Smaller index budget
```

```
            "topic_fraction":        0.10,  # Fewer topics
            "conversation_fraction": 0.57,  # More room for conversation
            "buffer_fraction":       0.02,
        },
        "balanced": {
            "system_fraction":       0.05,
            "index_fraction":        0.08,
            "topic_fraction":        0.20,
            "conversation_fraction": 0.45,
            "buffer_fraction":       0.02,
        },
        "aggressive": {
            "system_fraction":       0.05,
            "index_fraction":        0.10,  # More index budget
            "topic_fraction":        0.30,  # More topics loaded
            "conversation_fraction": 0.33,  # Less conversation
            "buffer_fraction":       0.02,
        },
    }

    def __init__(
        self,
        model:    str = "",
        provider: str = "",
        strategy: str = "balanced",
        custom_context_size: Optional[int] = None,
    ):
        self.model    = model
        self.provider = provider
        self.strategy = strategy

        # Get window spec
        self._spec = (
            ContextWindowSpec(
                model_pattern="custom",
                context_tokens=custom_context_size,
                safe_output_tokens=min(4096, custom_context_size // 4),
                provider=provider,
            )
            if custom_context_size
            else get_context_spec(model, provider)
        )

        # Token counter
        self.counter = TokenCounter(model=model, provider=provider)

        # Compute allocation
        self._allocation = self._compute_allocation()

        logger.debug(
            f"BudgetManager: model={model}, "
            f"context={self._spec.context_tokens}, "
            f"strategy={strategy}"
        )

    def _compute_allocation(self) -> BudgetAllocation:
        """Compute token allocation from spec and strategy."""
        fractions  = self.STRATEGY_ALLOCATIONS.get(
```

```
            self.strategy,
            self.STRATEGY_ALLOCATIONS["balanced"],
        )

        total      = self._spec.context_tokens
        safe_out   = self._spec.safe_output_tokens
        available  = total - safe_out

        return BudgetAllocation(
            total_context=total,
            safe_output=safe_out,
            available_input=available,
            system_prompt=int(available * fractions["system_fraction"]),
            memory_index=int(available  * fractions["index_fraction"]),
            topic_files=int(available   * fractions["topic_fraction"]),
            conversation=int(available  * fractions["conversation_fraction"]),
            overflow_buffer=int(available * fractions["buffer_fraction"]),
            system_fraction=fractions["system_fraction"],
            index_fraction=fractions["index_fraction"],
            topic_fraction=fractions["topic_fraction"],
            conversation_fraction=fractions["conversation_fraction"],
            buffer_fraction=fractions["buffer_fraction"],
        )

    def get_allocation(self) -> BudgetAllocation:
        """Get the current token allocation."""
        return self._allocation

    def get_spec(self) -> ContextWindowSpec:
        """Get the context window specification."""
        return self._spec

    def new_spend_tracker(self) -> BudgetSpend:
        """Create a fresh spend tracker for a new context build."""
        return BudgetSpend()

    def is_large_context(self) -> bool:
        """True if this model has a large context window (>= 32K)."""
        return self._spec.context_tokens >= 32_768

    def is_tiny_context(self) -> bool:
        """True if this model has a small context window (< 8K)."""
        return self._spec.context_tokens < 8_192

    def switch_strategy(self, strategy: str) -> None:
        """
        Switch injection strategy and recompute allocation.
        Useful when context pressure changes.
        """
        if strategy not in self.STRATEGY_ALLOCATIONS:
            raise ValueError(
                f"Unknown strategy '{strategy}'. "
                f"Valid: {list(self.STRATEGY_ALLOCATIONS)}"
            )
        self.strategy    = strategy
        self._allocation = self._compute_allocation()
        logger.info(f"Budget strategy switched to: {strategy}")
```

```
    def compute_topic_budget_per_topic(self, n_topics: int) -> int:
        """
        How many tokens each topic file can use given N topics to inject.
        """
        if n_topics <= 0:
            return 0
        total_topic_budget = self._allocation.topic_files
        # Reserve 10% for overhead (labels, separators)
        usable = int(total_topic_budget * 0.90)
        return usable // n_topics

    def summary(self) -> dict:
        return {
            "model":     self.model,
            "provider":  self.provider,
            "strategy":  self.strategy,
            "spec":      {
                "context_tokens":     self._spec.context_tokens,
                "safe_output_tokens": self._spec.safe_output_tokens,
            },
            "allocation": self._allocation.summary(),
        }
```

---

3. Relevance Ranker

Python

```
# memograph/injection/relevance_ranker.py
"""
Query-aware relevance ranking for index pointers.

Phase 4 implements a TF-IDF hybrid ranker:
1. Term overlap (fast, zero deps)
2. TF-IDF scoring (better precision, still zero deps)
3. Recency boost (recent = more relevant)
4. Confidence boost (verified > observed > inferred)
5. Access frequency boost (often-accessed = likely useful)

Phase 5 will add embedding-based semantic scoring.
"""

from __future__ import annotations

import logging
import math
import re
from collections import Counter, defaultdict
from dataclasses import dataclass
from datetime import datetime
from typing import Optional

from memograph.models.index import IndexPointer
```

```python
logger = logging.getLogger("memograph.injection.ranker")


@dataclass
class RankedPointer:
    """A pointer with its relevance score and scoring breakdown."""
    pointer:           IndexPointer
    score:             float
    term_overlap:      int
    tfidf_score:       float
    recency_boost:     float
    confidence_boost:  float
    access_boost:      float
    is_exact_match:    bool

    def to_dict(self) -> dict:
        return {
            "topic_id":        self.pointer.topic_id,
            "score":           round(self.score, 4),
            "term_overlap":    self.term_overlap,
            "tfidf":           round(self.tfidf_score, 4),
            "recency":         round(self.recency_boost, 4),
            "confidence":      round(self.confidence_boost, 4),
            "access":          round(self.access_boost, 4),
            "exact_match":     self.is_exact_match,
        }


class TFIDF:
    """
    Lightweight TF-IDF implementation.
    No external dependencies.
    Documents = topic summaries.
    """

    def __init__(self):
        self._doc_freq:   Counter  = Counter()   # term → num docs containing it
        self._num_docs:   int      = 0
        self._docs:       dict[str, list[str]] = {}  # topic_id → terms

    def fit(self, topic_id: str, text: str) -> None:
        """Add a document to the corpus."""
        terms = self._tokenize(text)
        self._docs[topic_id] = terms

        # Update document frequencies
        unique_terms = set(terms)
        for term in unique_terms:
            self._doc_freq[term] += 1

        self._num_docs = len(self._docs)

    def score(self, query_terms: list[str], topic_id: str) -> float:
        """Compute TF-IDF score of query against a document."""
        if topic_id not in self._docs:
            return 0.0
```

```
        doc_terms = self._docs[topic_id]
        if not doc_terms:
            return 0.0

        doc_tf = Counter(doc_terms)
        total  = len(doc_terms)
        score  = 0.0

        for term in query_terms:
            tf  = doc_tf.get(term, 0) / total
            df  = self._doc_freq.get(term, 0)
            idf = (
                math.log(self._num_docs / (df + 1)) + 1
                if df > 0 and self._num_docs > 0 else 0.0
            )
            score += tf * idf

        return score

    def remove(self, topic_id: str) -> None:
        """Remove a document from the corpus."""
        if topic_id in self._docs:
            terms = set(self._docs.pop(topic_id))
            for term in terms:
                self._doc_freq[term] = max(0, self._doc_freq[term] - 1)
            self._num_docs = len(self._docs)

    @staticmethod
    def _tokenize(text: str) -> list[str]:
        """Tokenize text into lowercase terms."""
        return re.findall(r"\b[a-z0-9_]{2,}\b", text.lower())


class RelevanceRanker:
    """
    Query-aware relevance ranker for index pointers.

    Scoring formula:
      score = (
          term_overlap     * w_overlap   +
          tfidf_score      * w_tfidf     +
          recency_boost    * w_recency   +
          confidence_boost * w_confidence +
          access_boost     * w_access
      ) * exact_match_multiplier * stale_penalty

    All weights are configurable.
    """

    def __init__(
        self,
        weight_overlap:    float = 0.30,
        weight_tfidf:      float = 0.35,
        weight_recency:    float = 0.15,
        weight_confidence: float = 0.15,
        weight_access:     float = 0.05,
        exact_match_bonus: float = 1.5,
        stale_penalty:     float = 0.4,
```

```
        recency_half_life_days: int = 30,
    ):
        self.w_overlap    = weight_overlap
        self.w_tfidf      = weight_tfidf
        self.w_recency    = weight_recency
        self.w_confidence = weight_confidence
        self.w_access     = weight_access
        self.exact_bonus  = exact_match_bonus
        self.stale_penalty = stale_penalty
        self.recency_half_life = recency_half_life_days

        self._tfidf = TFIDF()

    # ──────────────────────────────────────────────────────────────────────
    # CORPUS MANAGEMENT
    # ──────────────────────────────────────────────────────────────────────

    def fit_corpus(self, pointers: list[IndexPointer]) -> None:
        """
        Fit TF-IDF corpus from a list of pointers.
        Call this when the index changes.
        """
        self._tfidf = TFIDF()
        for p in pointers:
            doc_text = f"{p.topic_id} {p.summary}"
            self._tfidf.fit(p.topic_id, doc_text)

    def update_corpus(self, pointer: IndexPointer) -> None:
        """Add or update a single pointer in the corpus."""
        self._tfidf.remove(pointer.topic_id)
        doc_text = f"{pointer.topic_id} {pointer.summary}"
        self._tfidf.fit(pointer.topic_id, doc_text)

    def remove_from_corpus(self, topic_id: str) -> None:
        """Remove a pointer from the TF-IDF corpus."""
        self._tfidf.remove(topic_id)

    # ──────────────────────────────────────────────────────────────────────
    # SCORING
    # ──────────────────────────────────────────────────────────────────────

    def rank(
        self,
        query:    str,
        pointers: list[IndexPointer],
        top_k:    int             = 10,
        min_score: float          = 0.01,
    ) -> list[RankedPointer]:
        """
        Rank pointers by relevance to query.

        Args:
            query:     User query or context for this turn
            pointers:  List of index pointers to rank
            top_k:     Maximum results to return
            min_score: Minimum score threshold (filters noise)

        Returns:
```

```
            List of RankedPointer, sorted by score descending
        """
        if not query or not pointers:
            return []

        query_terms = self._tokenize(query)
        query_set   = set(query_terms)

        # Fit corpus if not yet fitted
        if not self._tfidf._docs:
            self.fit_corpus(pointers)

        now = datetime.now()
        ranked: list[RankedPointer] = []

        for pointer in pointers:
            rp = self._score_pointer(
                pointer=pointer,
                query_terms=query_terms,
                query_set=query_set,
                now=now,
            )

            if rp.score >= min_score:
                ranked.append(rp)

        ranked.sort(key=lambda r: r.score, reverse=True)
        return ranked[:top_k]

    def _score_pointer(
        self,
        pointer:     IndexPointer,
        query_terms: list[str],
        query_set:   set[str],
        now:         datetime,
    ) -> RankedPointer:
        """Compute full relevance score for a single pointer."""

        pointer_text  = f"{pointer.topic_id} {pointer.summary}".lower()
        pointer_terms = set(self._tokenize(pointer_text))

        # ── Term overlap ──────────────────────────────────────────
        overlap_count = len(query_set & pointer_terms)
        # Normalize by query length (avoid penalizing short queries)
        overlap_score = overlap_count / max(len(query_set), 1)

        # ── TF-IDF score ──────────────────────────────────────────
        tfidf_score = self._tfidf.score(query_terms, pointer.topic_id)
        # Normalize TF-IDF (it can be > 1)
        tfidf_norm  = min(1.0, tfidf_score)

        # ── Recency boost ─────────────────────────────────────────
        # Exponential decay: score = 1 at last_updated, halves every N days
        days_old      = (now - pointer.last_updated).days
        recency_boost = math.exp(
            -math.log(2) * days_old / self.recency_half_life
        )
```

```
        # ── Confidence boost ──────────────────────────────────────
        # Maps confidence (0.0–1.0) → boost
        conf_boost = pointer.confidence

        # ── Access frequency boost ────────────────────────────────
        # Log-scale: reduces effect of very high counts
        access_boost = min(1.0, math.log1p(pointer.access_count) / 10.0)

        # ── Exact topic_id match ──────────────────────────────────
        is_exact = pointer.topic_id.lower() in query_set
        if not is_exact:
            # Check partial: any query term is a prefix of topic_id
            is_exact = any(
                pointer.topic_id.lower().startswith(term)
                for term in query_set
                if len(term) > 3
            )

        # ── Combine scores ────────────────────────────────────────
        combined = (
            self.w_overlap    * overlap_score +
            self.w_tfidf      * tfidf_norm    +
            self.w_recency    * recency_boost +
            self.w_confidence * conf_boost    +
            self.w_access     * access_boost
        )

        # Apply exact match bonus
        if is_exact:
            combined *= self.exact_bonus

        # Apply stale penalty
        if pointer.is_stale:
            combined *= self.stale_penalty

        return RankedPointer(
            pointer=pointer,
            score=min(1.0, combined),
            term_overlap=overlap_count,
            tfidf_score=tfidf_score,
            recency_boost=recency_boost,
            confidence_boost=conf_boost,
            access_boost=access_boost,
            is_exact_match=is_exact,
        )

    @staticmethod
    def _tokenize(text: str) -> list[str]:
        """Tokenize text for matching."""
        return re.findall(r"\b[a-z0-9_]{2,}\b", text.lower())

    def explain(self, query: str, topic_id: str, pointer: IndexPointer) -> str:
        """
        Human-readable explanation of why a topic was ranked.
        Useful for debugging.
        """
        query_terms = self._tokenize(query)
        query_set   = set(query_terms)
```

```
        rp = self._score_pointer(
            pointer=pointer,
            query_terms=query_terms,
            query_set=query_set,
            now=datetime.now(),
        )
        lines = [
            f"Relevance score for '{topic_id}' against query '{query}':",
            f"  Final score:      {rp.score:.4f}",
            f"  Term overlap:     {rp.term_overlap} terms "
            f"({rp.term_overlap / max(len(query_set), 1):.1%})",
            f"  TF-IDF:           {rp.tfidf_score:.4f}",
            f"  Recency boost:    {rp.recency_boost:.4f}",
            f"  Confidence boost: {rp.confidence_boost:.4f}",
            f"  Access boost:     {rp.access_boost:.4f}",
            f"  Exact match:      {rp.is_exact_match}",
            f"  Is stale:         {pointer.is_stale}",
        ]
        return "\n".join(lines)
```

---

4. Injection Strategies

Python

```
# memograph/injection/strategies.py
"""
Injection strategy configurations.

Three built-in strategies + custom support.

Strategy selects HOW MUCH memory context to inject,
not what gets injected (that's the RelevanceRanker's job).

Conservative:  Minimal injection — priority on conversation space
Balanced:      Default — equal weight to memory and conversation
Aggressive:    Maximum injection — load as many topics as possible
"""

from __future__ import annotations

from dataclasses import dataclass
from enum import Enum
from typing import Optional


class InjectionMode(str, Enum):
    CONSERVATIVE = "conservative"
    BALANCED     = "balanced"
    AGGRESSIVE   = "aggressive"
    CUSTOM       = "custom"
```

```python
@dataclass
class InjectionStrategy:
    """
    Configuration for how aggressively to inject memory context.
    """

    mode: InjectionMode

    # How many topic files to load per turn
    max_topics: int

    # Minimum relevance score to include a topic
    min_relevance_score: float

    # Include verification reminders for stale facts
    include_stale_warnings: bool

    # Include the full reasoning chain for how memory was selected
    include_selection_rationale: bool

    # Inject topics even if their score is below threshold
    # (useful when very few topics exist)
    always_include_top_n: int

    # Truncate long topic files to fit budget
    truncate_topics: bool

    # Include confidence annotations on individual facts
    annotate_fact_confidence: bool

    # Include "last verified" dates on facts
    show_verification_dates: bool

    # Include access count hints ("this fact has been used 12 times")
    show_access_hints: bool

    @classmethod
    def conservative(cls) -> "InjectionStrategy":
        return cls(
            mode=InjectionMode.CONSERVATIVE,
            max_topics=2,
            min_relevance_score=0.15,
            include_stale_warnings=True,
            include_selection_rationale=False,
            always_include_top_n=1,
            truncate_topics=True,
            annotate_fact_confidence=False,
            show_verification_dates=False,
            show_access_hints=False,
        )

    @classmethod
    def balanced(cls) -> "InjectionStrategy":
        return cls(
            mode=InjectionMode.BALANCED,
            max_topics=3,
            min_relevance_score=0.08,
            include_stale_warnings=True,
```

```
            include_selection_rationale=False,
            always_include_top_n=1,
            truncate_topics=True,
            annotate_fact_confidence=True,
            show_verification_dates=False,
            show_access_hints=False,
        )

    @classmethod
    def aggressive(cls) -> "InjectionStrategy":
        return cls(
            mode=InjectionMode.AGGRESSIVE,
            max_topics=6,
            min_relevance_score=0.03,
            include_stale_warnings=True,
            include_selection_rationale=True,
            always_include_top_n=2,
            truncate_topics=True,
            annotate_fact_confidence=True,
            show_verification_dates=True,
            show_access_hints=True,
        )

    @classmethod
    def from_mode(cls, mode: InjectionMode | str) -> "InjectionStrategy":
        m = InjectionMode(mode) if isinstance(mode, str) else mode
        if m == InjectionMode.CONSERVATIVE:
            return cls.conservative()
        if m == InjectionMode.BALANCED:
            return cls.balanced()
        if m == InjectionMode.AGGRESSIVE:
            return cls.aggressive()
        raise ValueError(f"Cannot create strategy from mode '{mode}' without custom params")

    def with_max_topics(self, n: int) -> "InjectionStrategy":
        """Return a copy with a different max_topics."""
        from dataclasses import replace
        return replace(self, max_topics=n)

    def with_min_score(self, score: float) -> "InjectionStrategy":
        """Return a copy with a different minimum score."""
        from dataclasses import replace
        return replace(self, min_relevance_score=score)
```

---

5. Skeptical Formatter

Python

```
# memograph/injection/formatter.py
"""
Skeptical memory formatter.
```

```
Core principle (from the leaked source):
"Memory is treated as a hint, not as truth.
 The agent verifies before using it."

The formatter adds:
1. Clear memory boundary markers
2. Confidence-level visual indicators
3. Staleness warnings with re-verification reminders
4. Selection rationale (why these topics were chosen)
5. Explicit instruction to verify before acting
6. Formatted topic sections with fact annotations
"""

from __future__ import annotations

from datetime import datetime
from typing import Optional

from memograph.injection.strategies import InjectionStrategy
from memograph.injection.relevance_ranker import RankedPointer
from memograph.models.index import MemoryIndex
from memograph.models.topic import ConfidenceLevel, MemoryFact, TopicFile


# Confidence level display config
CONFIDENCE_CONFIG = {
    ConfidenceLevel.VERIFIED: {
        "emoji":  "✅",
        "label":  "VERIFIED",
        "note":   "",
        "color":  "green",
    },
    ConfidenceLevel.OBSERVED: {
        "emoji":  "👁️",
        "label":  "OBSERVED",
        "note":   "(treat as likely true, verify for critical decisions)",
        "color":  "blue",
    },
    ConfidenceLevel.INFERRED: {
        "emoji":  "💭",
        "label":  "INFERRED",
        "note":   "(treat as hypothesis — verify before acting)",
        "color":  "yellow",
    },
    ConfidenceLevel.STALE: {
        "emoji":  "⚠️",
        "label":  "STALE",
        "note":   "(may be outdated — RE-VERIFY before using)",
        "color":  "red",
    },
}

# Memory section header
_MEMORY_HEADER = """\
╔══════════════════════════════════════════════════════╗
║           🧠  MEMOGRAPH MEMORY CONTEXT               ║
║      Treat all facts below as HINTS, not truth.      ║
║      Verify before acting on any memory.             ║
```

```
╚═══════════════════════════════════════════════════════════════╝"""

_MEMORY_FOOTER = """\
═══════════════════════════════════════════════════════════════
⚠️  MEMORY USAGE REMINDER
  • ✅ VERIFIED facts: safe to use directly
  • 👁️ OBSERVED facts: likely true, verify for critical use
  • 💭 INFERRED facts: treat as hypothesis, verify always
  • ⚠️  STALE facts: may be outdated, RE-VERIFY before use
  • Always prefer current observation over memory
  • If memory conflicts with what you observe, trust observation
═══════════════════════════════════════════════════════════════"""

_COMPACT_HEADER = "## 🧠 Memory Context (hints — verify before use)"
_COMPACT_FOOTER = "> ⚠️ Memory = hint, not truth. Verify before acting."


class SkepticalFormatter:
    """
    Formats memory context for LLM injection.

    Two formats:
    - full:    Rich formatting with headers, footers, confidence labels
    - compact: Minimal formatting for tight token budgets
    - minimal: Just the index markdown, no topic content
    """

    def __init__(self, strategy: InjectionStrategy):
        self.strategy = strategy

    def format_full(
        self,
        index:           MemoryIndex,
        topics:          list[TopicFile],
        ranked_pointers: list[RankedPointer],
        spend_summary:   Optional[dict] = None,
    ) -> str:
        """
        Full rich formatting.
        Used in balanced/aggressive strategies with sufficient token budget.
        """
        sections: list[str] = [_MEMORY_HEADER, ""]

        # Layer 1: Index
        sections.append("## 📋 Memory Index (always loaded)")
        sections.append(index.to_markdown())
        sections.append("")

        # Selection rationale
        if self.strategy.include_selection_rationale and ranked_pointers:
            sections.append("## 🎯 Why These Topics Were Selected")
            for rp in ranked_pointers[:3]:
                sections.append(
                    f"  • [{rp.pointer.topic_id}] "
                    f"score={rp.score:.3f} "
                    f"overlap={rp.term_overlap} terms"
                    + (" (exact match)" if rp.is_exact_match else "")
                )
```

```
            sections.append("")

        # Layer 2: Topics
        if topics:
            sections.append("## 📂 Relevant Topic Files (loaded on-demand)")
            for topic in topics:
                sections.append(self._format_topic(topic))
                sections.append("")

        # Token spend summary
        if spend_summary:
            sections.append(self._format_spend_summary(spend_summary))
            sections.append("")

        sections.append(_MEMORY_FOOTER)
        return "\n".join(sections)

    def format_compact(
        self,
        index:  MemoryIndex,
        topics: list[TopicFile],
    ) -> str:
        """
        Compact formatting.
        Used in conservative strategy or under token pressure.
        """
        sections: list[str] = [_COMPACT_HEADER, ""]

        # Compact index (just the pointer lines)
        sections.append("### Index")
        for p in index.sorted_by_confidence():
            stale_mark = " ⚠️" if p.is_stale else ""
            sections.append(
                f"- [{p.topic_id}]{stale_mark}: {p.summary}"
            )
        sections.append("")

        # Compact topics
        if topics:
            sections.append("### Relevant Facts")
            for topic in topics:
                sections.append(self._format_topic_compact(topic))
                sections.append("")

        sections.append(_COMPACT_FOOTER)
        return "\n".join(sections)

    def format_minimal(self, index: MemoryIndex) -> str:
        """
        Minimal format: just the raw index markdown.
        Used when topic budget is exhausted or strategy is conservative.
        """
        return f"### Memory Index\n{index.to_markdown()}\n{_COMPACT_FOOTER}"

    def format_topic(self, topic: TopicFile) -> str:
        """Public wrapper — use strategy to pick format."""
        return self._format_topic(topic)
```

```python
    # ──────────────────────────────────────────────────────────────────────
    # PRIVATE
    # ──────────────────────────────────────────────────────────────────────

    def _format_topic(self, topic: TopicFile) -> str:
        """Format a single topic for injection."""
        lines = [
            f"### 📂 {topic.topic_name}",
            f"Topic ID: `{topic.topic_id}` | Facts: {len(topic.facts)} | "
            f"Avg confidence: {topic.avg_confidence:.0%}",
        ]

        if topic.tags:
            lines.append(f"Tags: {', '.join(topic.tags)}")

        # Stale warning at topic level
        if self.strategy.include_stale_warnings and topic.stale_count > 0:
            lines.append(
                f"⚠️  {topic.stale_count}/{len(topic.facts)} facts are STALE — "
                f"re-verify before use"
                )

        lines.append("")

        for fact in topic.facts:
            lines.append(self._format_fact(fact))

        return "\n".join(lines)

    def _format_topic_compact(self, topic: TopicFile) -> str:
        """Compact single-topic format."""
        lines = [f"**{topic.topic_name}** (`{topic.topic_id}`)"]
        for fact in topic.facts[:5]:   # Max 5 facts in compact mode
            cfg   = CONFIDENCE_CONFIG[fact.confidence]
            emoji = cfg["emoji"]
            lines.append(f"  {emoji} {fact.content}")
        if len(topic.facts) > 5:
            lines.append(f"  ... and {len(topic.facts) - 5} more facts")
        return "\n".join(lines)

    def _format_fact(self, fact: MemoryFact) -> str:
        """Format a single fact with confidence annotation."""
        cfg     = CONFIDENCE_CONFIG[fact.confidence]
        emoji   = cfg["emoji"]
        label   = cfg["label"]
        note    = cfg["note"]

        # Base line
        line = f"{emoji} `{fact.fact_id}` **{label}**: {fact.content}"

        if note and self.strategy.annotate_fact_confidence:
            line += f"\n   _{note}_"

        # Verification date
        if (
            self.strategy.show_verification_dates
            and fact.last_verified
        ):
```

```
            line += f"\n   Last verified: {fact.last_verified.strftime('%Y-%m-%d')}"

        # Source
        line += f"\n   Source: `{fact.source}`"

        # Verification hint
        if fact.verification_hint:
            line += f"\n   Verify via: {fact.verification_hint}"

        # Access hints
        if self.strategy.show_access_hints and fact.meta.get("access_count"):
            line += f"\n   Used {fact.meta['access_count']} times"

        # Contradiction warning
        if fact.contradicts_ids:
            line += (
                f"\n   ⚡ **Contradiction** with: "
                f"{', '.join(fact.contradicts_ids)}"
            )

        return line

    def _format_spend_summary(self, spend: dict) -> str:
        """Format the token budget spend summary."""
        return (
            f"_Context budget: "
            f"index={spend.get('index_tokens', '?')}t, "
            f"topics={spend.get('topic_tokens', '?')}t, "
            f"total={spend.get('total', '?')}t_"
        )
```

---

6. Context Cache

Python

```
# memograph/injection/context_cache.py
"""
Per-turn context cache.

Prevents rebuilding identical context on consecutive identical queries.
Cache key = hash(query + index_mtime + agent_id).
TTL = 60 seconds (contexts become stale as memory changes).
"""

from __future__ import annotations

import hashlib
import time
from dataclasses import dataclass
from typing import Optional
```

```
@dataclass
class CachedContext:
    """A cached context entry."""
    key:        str
    content:    str
    tokens:     int
    built_at:   float       # Unix timestamp
    query:      str
    topic_ids:  list[str]   # Which topics were included


class ContextCache:
    """
    TTL-based in-memory cache for built contexts.

    Why: Context building involves:
    - Index loading (fast, but I/O)
    - Topic file loading (medium I/O)
    - Relevance scoring (CPU)
    - Formatting (CPU)

    If the same query is issued twice within the TTL,
    we can skip all of that.
    """

    def __init__(
        self,
        ttl_seconds: int  = 60,
        max_entries: int  = 100,
    ):
        self.ttl        = ttl_seconds
        self.max_entries = max_entries
        self._cache: dict[str, CachedContext] = {}
        self._hits   = 0
        self._misses = 0

    def get(self, key: str) -> Optional[CachedContext]:
        """Get a cached context if it exists and hasn't expired."""
        entry = self._cache.get(key)
        if entry is None:
            self._misses += 1
            return None

        age = time.time() - entry.built_at
        if age > self.ttl:
            del self._cache[key]
            self._misses += 1
            return None

        self._hits += 1
        return entry

    def put(
        self,
        key:       str,
        content:   str,
        tokens:    int,
        query:     str,
```

```
        topic_ids: list[str],
    ) -> None:
        """Store a context in the cache."""
        # Evict oldest if full
        if len(self._cache) >= self.max_entries:
            oldest_key = min(
                self._cache,
                key=lambda k: self._cache[k].built_at,
            )
            del self._cache[oldest_key]

        self._cache[key] = CachedContext(
            key=key,
            content=content,
            tokens=tokens,
            built_at=time.time(),
            query=query,
            topic_ids=topic_ids,
        )

    def invalidate(self, topic_id: str = None) -> int:
        """
        Invalidate cache entries.
        If topic_id given: only entries that included that topic.
        Otherwise: clear all.
        Returns count removed.
        """
        if topic_id is None:
            count = len(self._cache)
            self._cache.clear()
            return count

        to_remove = [
            k for k, v in self._cache.items()
            if topic_id in v.topic_ids
        ]
        for k in to_remove:
            del self._cache[k]
        return len(to_remove)

    @staticmethod
    def make_key(
        agent_id:     str,
        query:        str,
        index_hash:   str,
        strategy:     str,
    ) -> str:
        """Build a deterministic cache key."""
        raw = f"{agent_id}::{query}::{index_hash}::{strategy}"
        return hashlib.md5(raw.encode()).hexdigest()

    @staticmethod
    def hash_index(index_markdown: str) -> str:
        """Hash the index content for cache key generation."""
        return hashlib.md5(index_markdown.encode()).hexdigest()[:8]

    @property
    def hit_rate(self) -> float:
```

```
        total = self._hits + self._misses
        return self._hits / total if total > 0 else 0.0

    def stats(self) -> dict:
        return {
            "entries":   len(self._cache),
            "hits":      self._hits,
            "misses":    self._misses,
            "hit_rate":  f"{self.hit_rate:.1%}",
            "ttl":       self.ttl,
        }

    def clear(self) -> None:
        self._cache.clear()
```

---

7. Context Pressure Monitor

Python

```
# memograph/injection/pressure_monitor.py
"""
Context window pressure monitor.

Detects when the context window is filling up and triggers
protective measures (compaction, strategy downgrade, etc.).

Pressure levels:
  NORMAL   (0-70%):  All good, use configured strategy
  ELEVATED (70-85%): Switch to conservative, warn
  HIGH     (85-95%): Minimal injection only, no topics
  CRITICAL (95%+):   Emergency: inject index only, trigger compaction
"""

from __future__ import annotations

import logging
from dataclasses import dataclass
from enum import Enum
from typing import Optional

logger = logging.getLogger("memograph.injection.pressure")


class PressureLevel(str, Enum):
    NORMAL   = "normal"
    ELEVATED = "elevated"
    HIGH     = "high"
    CRITICAL = "critical"


@dataclass
class PressureState:
```

```
    """Current context pressure state."""
    level:           PressureLevel
    usage_ratio:     float
    tokens_used:     int
    tokens_available: int
    tokens_remaining: int
    recommended_strategy: str
    should_compact:   bool
    message:         str


class ContextPressureMonitor:
    """
    Monitors context window utilization and recommends
    protective actions when pressure is high.

    Usage:
        monitor = ContextPressureMonitor()
        state   = monitor.assess(tokens_used=5000, tokens_available=8192)

        if state.level == PressureLevel.CRITICAL:
            await trigger_emergency_compaction()
            strategy = InjectionStrategy.conservative()
    """

    THRESHOLDS = {
        PressureLevel.ELEVATED: 0.70,
        PressureLevel.HIGH:     0.85,
        PressureLevel.CRITICAL: 0.95,
    }

    def __init__(
        self,
        on_elevated: Optional[callable] = None,
        on_high:     Optional[callable] = None,
        on_critical: Optional[callable] = None,
    ):
        self._on_elevated = on_elevated
        self._on_high     = on_high
        self._on_critical = on_critical

        self._last_level  = PressureLevel.NORMAL
        self._escalations = 0

    def assess(
        self,
        tokens_used:      int,
        tokens_available: int,
    ) -> PressureState:
        """
        Assess current context pressure.
        Fires callbacks on level escalation.
        """
        if tokens_available <= 0:
            ratio = 1.0
        else:
            ratio = tokens_used / tokens_available
```

```
        # Determine level
        if ratio >= self.THRESHOLDS[PressureLevel.CRITICAL]:
            level             = PressureLevel.CRITICAL
            recommended       = "conservative"
            should_compact    = True
            message = (
                f"🚨 CRITICAL: Context {ratio:.0%} full "
                f"({tokens_used}/{tokens_available} tokens). "
                f"Emergency compaction triggered."
            )

        elif ratio >= self.THRESHOLDS[PressureLevel.HIGH]:
            level             = PressureLevel.HIGH
            recommended       = "conservative"
            should_compact    = False
            message = (
                f"⚠️ HIGH pressure: Context {ratio:.0%} full. "
                f"Minimal injection active."
            )

        elif ratio >= self.THRESHOLDS[PressureLevel.ELEVATED]:
            level             = PressureLevel.ELEVATED
            recommended       = "conservative"
            should_compact    = False
            message = (
                f"⚡ ELEVATED pressure: Context {ratio:.0%} full. "
                f"Switching to conservative injection."
            )

        else:
            level             = PressureLevel.NORMAL
            recommended       = "balanced"
            should_compact    = False
            message           = f"✅ Normal: Context {ratio:.0%} full."

        state = PressureState(
            level=level,
            usage_ratio=ratio,
            tokens_used=tokens_used,
            tokens_available=tokens_available,
            tokens_remaining=max(0, tokens_available - tokens_used),
            recommended_strategy=recommended,
            should_compact=should_compact,
            message=message,
        )

        # Fire callbacks on escalation
        self._handle_escalation(state)
        self._last_level = level

        return state

    def _handle_escalation(self, state: PressureState) -> None:
        """Fire callback if pressure level has increased."""
        level_order = [
            PressureLevel.NORMAL,
            PressureLevel.ELEVATED,
            PressureLevel.HIGH,
```

```
            PressureLevel.CRITICAL,
        ]

        current_idx = level_order.index(state.level)
        last_idx    = level_order.index(self._last_level)

        if current_idx > last_idx:
            self._escalations += 1
            logger.warning(
                f"Context pressure escalated: "
                f"{self._last_level.value} → {state.level.value} "
                f"({state.usage_ratio:.0%})"
            )

            if state.level == PressureLevel.ELEVATED and self._on_elevated:
                try:
                    self._on_elevated(state)
                except Exception as e:
                    logger.warning(f"on_elevated callback failed: {e}")

            elif state.level == PressureLevel.HIGH and self._on_high:
                try:
                    self._on_high(state)
                except Exception as e:
                    logger.warning(f"on_high callback failed: {e}")

            elif state.level == PressureLevel.CRITICAL and self._on_critical:
                try:
                    self._on_critical(state)
                except Exception as e:
                    logger.warning(f"on_critical callback failed: {e}")

    @property
    def total_escalations(self) -> int:
        return self._escalations
```

---

8. Context Builder — The Core Engine

Python

```
# memograph/injection/context_builder.py
"""
Context Builder — assembles the per-turn context injection.

This is the main entry point for Phase 4.
Every LLM call passes through here.

Architecture:
  build_context(query, messages) →
    1. Check cache (fast path)
    2. Assess context pressure
    3. Score index pointers against query (RelevanceRanker)
```

```
    4. Allocate token budget (TokenBudgetManager)
    5. Load top-k topics within budget (TopicManager)
    6. Format everything (SkepticalFormatter)
    7. Return BuiltContext

The key design insight:
  Index is ALWAYS injected (cheap, ~500 tokens).
  Topics are loaded ONLY IF relevant AND budget allows.
  Transcripts are NEVER injected (only grep'd by the agent).
"""

from __future__ import annotations

import logging
from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional

from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.injection.context_cache import ContextCache
from memograph.injection.formatter import SkepticalFormatter
from memograph.injection.pressure_monitor import (
    ContextPressureMonitor,
    PressureLevel,
)
from memograph.injection.relevance_ranker import RankedPointer, RelevanceRanker
from memograph.injection.strategies import InjectionMode, InjectionStrategy
from memograph.injection.token_budget import (
    BudgetAllocation,
    BudgetSpend,
    TokenBudgetManager,
)
from memograph.models.index import MemoryIndex
from memograph.models.topic import TopicFile

logger = logging.getLogger("memograph.injection.builder")


@dataclass
class BuiltContext:
    """
    The assembled context for a single prompt turn.
    Immutable once built.
    """

    # The injected text (ready to prepend to system prompt)
    text:            str

    # Breakdown
    index_text:      str
    topic_texts:     list[str]

    # Metadata
    topics_loaded:   list[str]        # topic_ids included
    topics_skipped:  list[str]        # topic_ids that were relevant but skipped
    ranked_pointers: list[RankedPointer]
```

```
    # Token counts
    total_tokens:    int
    index_tokens:    int
    topic_tokens:    int

    # Build info
    query:           str
    built_at:        datetime          = field(default_factory=datetime.now)
    from_cache:      bool              = False
    pressure_level:  str               = "normal"
    strategy_used:   str               = "balanced"

    # Budget state
    budget:          Optional[BudgetAllocation] = None
    spend:           Optional[BudgetSpend]      = None

    def was_truncated(self) -> bool:
        """True if any topic was truncated to fit budget."""
        return "[... truncated" in self.text

    def token_efficiency(self) -> float:
        """What fraction of available topic budget was used."""
        if not self.budget or self.budget.topic_files == 0:
            return 0.0
        return min(1.0, self.topic_tokens / self.budget.topic_files)

    def to_dict(self) -> dict:
        return {
            "topics_loaded":   self.topics_loaded,
            "topics_skipped":  self.topics_skipped,
            "total_tokens":    self.total_tokens,
            "index_tokens":    self.index_tokens,
            "topic_tokens":    self.topic_tokens,
            "from_cache":      self.from_cache,
            "pressure_level":  self.pressure_level,
            "strategy_used":   self.strategy_used,
            "was_truncated":   self.was_truncated(),
            "built_at":        self.built_at.isoformat(),
        }


class ContextBuilder:
    """
    Per-turn context assembler.

    Wires together:
    - TokenBudgetManager  → how many tokens we have
    - RelevanceRanker     → which topics to load
    - TopicManager        → loading topic files
    - SkepticalFormatter  → formatting the output
    - ContextCache        → avoiding rebuilds
    - PressureMonitor     → detecting window pressure
    """

    def __init__(
        self,
        index_engine:   IndexEngine,
        topic_manager:  TopicManager,
```

```
        budget_manager: TokenBudgetManager,
        strategy:       Optional[InjectionStrategy] = None,
        cache_ttl:      int                         = 60,
        enable_cache:   bool                        = True,
    ):
        self.index_engine   = index_engine
        self.topic_manager  = topic_manager
        self.budget         = budget_manager
        self.strategy       = strategy or InjectionStrategy.balanced()

        self._ranker    = RelevanceRanker()
        self._formatter = SkepticalFormatter(self.strategy)
        self._cache     = ContextCache(ttl_seconds=cache_ttl) if enable_cache else None
        self._pressure  = ContextPressureMonitor(
            on_elevated=self._on_elevated,
            on_high=self._on_high,
            on_critical=self._on_critical,
        )

        # Stats
        self._builds_total    = 0
        self._builds_cached   = 0
        self._topics_injected = 0
        self._topics_skipped  = 0

    # ──────────────────────────────────────────────────────────────────────
    # MAIN ENTRY POINT
    # ──────────────────────────────────────────────────────────────────────

    async def build(
        self,
        query:              str,
        conversation_tokens: int  = 0,
        force_rebuild:      bool  = False,
    ) -> BuiltContext:
        """
        Build the context for a single prompt turn.

        Args:
            query:               The user's query / current turn text
            conversation_tokens: Tokens already used by conversation history
            force_rebuild:       Skip cache and rebuild from scratch

        Returns:
            BuiltContext ready for injection
        """
        self._builds_total += 1

        # ── Load index (always) ──────────────────────────────────────────
        index = await self.index_engine.get_index()

        # ── Check cache ──────────────────────────────────────────────────
        if self._cache and not force_rebuild:
            cache_key = ContextCache.make_key(
                agent_id=index.agent_id,
                query=query,
                index_hash=ContextCache.hash_index(index.to_markdown()),
                strategy=self.strategy.mode.value,
```

```
            )
            cached = self._cache.get(cache_key)
            if cached:
                self._builds_cached += 1
                logger.debug(f"Context cache hit for query='{query[:40]}...'")
                return BuiltContext(
                    text=cached.content,
                    index_text=index.to_markdown(),
                    topic_texts=[],
                    topics_loaded=cached.topic_ids,
                    topics_skipped=[],
                    ranked_pointers=[],
                    total_tokens=cached.tokens,
                    index_tokens=0,
                    topic_tokens=0,
                    query=query,
                    from_cache=True,
                    strategy_used=self.strategy.mode.value,
                )

        # ── Assess context pressure ──────────────────────────────
        allocation = self.budget.get_allocation()
        pressure_state = self._pressure.assess(
            tokens_used=conversation_tokens,
            tokens_available=allocation.available_input,
        )

        # Adapt strategy under pressure
        active_strategy = self._get_adapted_strategy(pressure_state.level)
        self._formatter = SkepticalFormatter(active_strategy)

        # ── Score index pointers ─────────────────────────────────
        self._ranker.fit_corpus(index.pointers)

        ranked = self._ranker.rank(
            query=query,
            pointers=index.pointers,
            top_k=active_strategy.max_topics * 2,  # Oversample, then budget-prune
            min_score=active_strategy.min_relevance_score,
        )

        # Always include top_n even if below threshold
        if active_strategy.always_include_top_n > 0 and index.pointers:
            top_n = self._ranker.rank(
                query=query,
                pointers=index.pointers,
                top_k=active_strategy.always_include_top_n,
                min_score=0.0,   # No threshold for always-include
            )
            # Merge: add top_n items not already in ranked
            ranked_ids = {r.pointer.topic_id for r in ranked}
            for rp in top_n:
                if rp.pointer.topic_id not in ranked_ids:
                    ranked.append(rp)

        # ── Build context ────────────────────────────────────────
        context = await self._assemble(
            index=index,
```

```
            ranked=ranked,
            allocation=allocation,
            active_strategy=active_strategy,
            pressure_level=pressure_state.level,
            query=query,
        )

        # ── Cache result ──────────────────────────────────────────────
        if self._cache and not force_rebuild:
            self._cache.put(
                key=cache_key,
                content=context.text,
                tokens=context.total_tokens,
                query=query,
                topic_ids=context.topics_loaded,
            )

        return context

    async def build_minimal(self) -> BuiltContext:
        """
        Build the minimal context: index only, no topics.
        Used in CRITICAL pressure situations.
        """
        index        = await self.index_engine.get_index()
        index_text   = index.to_markdown()
        index_tokens = self.budget.counter.count(index_text)
        text         = self._formatter.format_minimal(index)

        return BuiltContext(
            text=text,
            index_text=index_text,
            topic_texts=[],
            topics_loaded=[],
            topics_skipped=[p.topic_id for p in index.pointers],
            ranked_pointers=[],
            total_tokens=index_tokens,
            index_tokens=index_tokens,
            topic_tokens=0,
            query="",
            pressure_level="critical",
            strategy_used="minimal",
        )

    # ──────────────────────────────────────────────────────────────────
    # ASSEMBLY
    # ──────────────────────────────────────────────────────────────────

    async def _assemble(
        self,
        index:            MemoryIndex,
        ranked:           list[RankedPointer],
        allocation:       BudgetAllocation,
        active_strategy:  InjectionStrategy,
        pressure_level:   PressureLevel,
        query:            str,
    ) -> BuiltContext:
        """
```

```
        Assemble the full context from index + topics.
        Enforces token budget strictly.
        """
        spend         = self.budget.new_spend_tracker()
        loaded_topics: list[TopicFile]     = []
        topic_texts:  list[str]            = []
        loaded_ids:   list[str]            = []
        skipped_ids:  list[str]            = []
        included_ranked: list[RankedPointer] = []

        # ── Always inject index ──────────────────────────────────────
        index_text   = index.to_markdown()
        index_tokens = self.budget.counter.count(index_text, "mixed")
        spend.index_tokens = index_tokens

        if index_tokens > allocation.memory_index:
            # Index over budget — truncate pointers (remove lowest-confidence)
            index_text = self._truncate_index(
                index, allocation.memory_index, spend
            )
            index_tokens = self.budget.counter.count(index_text)
            spend.index_tokens = index_tokens

        logger.debug(
            f"Index: {index_tokens} tokens "
            f"(budget: {allocation.memory_index})"
        )

        # ── Load topics within budget ────────────────────────────────
        if pressure_level not in (PressureLevel.HIGH, PressureLevel.CRITICAL):
            per_topic_budget = self.budget.compute_topic_budget_per_topic(
                min(len(ranked), active_strategy.max_topics)
            )

            for rp in ranked:
                if len(loaded_topics) >= active_strategy.max_topics:
                    skipped_ids.append(rp.pointer.topic_id)
                    continue

                if spend.topic_tokens >= allocation.topic_files:
                    skipped_ids.append(rp.pointer.topic_id)
                    logger.debug(
                        f"Topic budget exhausted — skipping {rp.pointer.topic_id}"
                    )
                    continue

                # Load topic
                topic = await self.topic_manager.get_topic(
                    rp.pointer.topic_id
                )
                if not topic:
                    logger.warning(
                        f"Topic {rp.pointer.topic_id} in index but not on disk"
                    )
                    skipped_ids.append(rp.pointer.topic_id)
                    continue

                # Format and count tokens
```

```
                topic_text   = self._formatter.format_topic(topic)
                topic_tokens = self.budget.counter.count(topic_text)

                # Truncate if over per-topic budget
                if topic_tokens > per_topic_budget and active_strategy.truncate_topics:
                    topic_text = self.budget.counter.truncate_to_budget(
                        topic_text, per_topic_budget
                    )
                    topic_tokens = self.budget.counter.count(topic_text)

                # Final check: does it fit in remaining topic budget?
                if (spend.topic_tokens + topic_tokens) > allocation.topic_files:
                    skipped_ids.append(rp.pointer.topic_id)
                    continue

                # Include it
                loaded_topics.append(topic)
                topic_texts.append(topic_text)
                loaded_ids.append(topic.topic_id)
                spend.topic_tokens += topic_tokens
                included_ranked.append(rp)

                # Update access count
                await self.index_engine.mark_accessed(rp.pointer.topic_id)

                logger.debug(
                    f"Loaded topic {topic.topic_id}: "
                    f"{topic_tokens} tokens (score={rp.score:.3f})"
                )

        self._topics_injected += len(loaded_topics)
        self._topics_skipped  += len(skipped_ids)

        # ── Format final context ──────────────────────────────────────
        if pressure_level == PressureLevel.CRITICAL:
            full_text = self._formatter.format_minimal(index)
        elif pressure_level in (PressureLevel.HIGH, PressureLevel.ELEVATED):
            full_text = self._formatter.format_compact(index, loaded_topics)
        else:
            full_text = self._formatter.format_full(
                index=index,
                topics=loaded_topics,
                ranked_pointers=included_ranked,
                spend_summary={
                    "index_tokens": spend.index_tokens,
                    "topic_tokens": spend.topic_tokens,
                    "total":        spend.total,
                },
            )

        total_tokens = self.budget.counter.count(full_text)
        spend.overhead_tokens = max(
            0, total_tokens - spend.index_tokens - spend.topic_tokens
        )

        return BuiltContext(
            text=full_text,
            index_text=index_text,
```

```
            topic_texts=topic_texts,
            topics_loaded=loaded_ids,
            topics_skipped=skipped_ids,
            ranked_pointers=included_ranked,
            total_tokens=total_tokens,
            index_tokens=spend.index_tokens,
            topic_tokens=spend.topic_tokens,
            query=query,
            pressure_level=pressure_level.value,
            strategy_used=active_strategy.mode.value,
            budget=allocation,
            spend=spend,
        )

    def _truncate_index(
        self,
        index:  MemoryIndex,
        budget: int,
        spend:  BudgetSpend,
    ) -> str:
        """
        Truncate index to fit within budget by removing
        lowest-confidence pointers.
        """
        pointers = list(index.sorted_by_confidence())   # Highest first
        lines    = [
            f"# Memory Index (Agent: {index.agent_id})",
            f"Last consolidated: {index.last_consolidated}",
            "---",
        ]
        header_tokens = self.budget.counter.count("\n".join(lines))
        remaining     = budget - header_tokens

        included_lines = []
        for p in pointers:
            line         = p.pointer_line or p.build_pointer_line()
            line_tokens  = self.budget.counter.count(line)
            if line_tokens <= remaining:
                included_lines.append(line)
                remaining -= line_tokens
            else:
                break   # Can't fit any more

        if len(included_lines) < len(pointers):
            skipped = len(pointers) - len(included_lines)
            included_lines.append(
                f"... {skipped} more pointers omitted (budget exceeded)"
            )

        return "\n".join(lines + included_lines)

    def _get_adapted_strategy(
        self,
        pressure_level: PressureLevel,
    ) -> InjectionStrategy:
        """Adapt strategy based on context pressure."""
        if pressure_level in (PressureLevel.HIGH, PressureLevel.CRITICAL):
            return InjectionStrategy.conservative().with_max_topics(1)
```

```
        if pressure_level == PressureLevel.ELEVATED:
            return InjectionStrategy.conservative()
        return self.strategy

    # ─────────────────────────────────────────────────────────────────
    # PRESSURE CALLBACKS
    # ─────────────────────────────────────────────────────────────────

    def _on_elevated(self, state) -> None:
        logger.warning(
            f"Context pressure elevated ({state.usage_ratio:.0%}) — "
            f"switching to conservative injection"
        )

    def _on_high(self, state) -> None:
        logger.warning(
            f"Context pressure HIGH ({state.usage_ratio:.0%}) — "
            f"topic injection suspended"
        )

    def _on_critical(self, state) -> None:
        logger.error(
            f"Context pressure CRITICAL ({state.usage_ratio:.0%}) — "
            f"emergency minimal mode"
        )

    # ─────────────────────────────────────────────────────────────────
    # ADMINISTRATION
    # ─────────────────────────────────────────────────────────────────

    def switch_strategy(self, mode: InjectionMode | str) -> None:
        """Switch injection strategy at runtime."""
        self.strategy   = InjectionStrategy.from_mode(mode)
        self._formatter = SkepticalFormatter(self.strategy)
        self.budget.switch_strategy(mode if isinstance(mode, str) else mode.value)
        if self._cache:
            self._cache.invalidate()   # Invalidate cache after strategy change
        logger.info(f"Injection strategy switched to: {mode}")

    def invalidate_cache(self, topic_id: str = None) -> None:
        """Invalidate cache entries."""
        if self._cache:
            count = self._cache.invalidate(topic_id)
            logger.debug(f"Cache invalidated: {count} entries removed")

    def get_stats(self) -> dict:
        return {
            "builds_total":     self._builds_total,
            "builds_cached":    self._builds_cached,
            "cache_hit_rate":   (
                f"{self._builds_cached / self._builds_total:.1%}"
                if self._builds_total > 0 else "N/A"
            ),
            "topics_injected":  self._topics_injected,
            "topics_skipped":   self._topics_skipped,
            "pressure_escalations": self._pressure.total_escalations,
            "cache":            self._cache.stats() if self._cache else None,
            "budget":           self.budget.summary(),
```

```
        }
```

---

9. Injection Prompts

Python

```python
# memograph/prompts/injection_prompts.py
"""
Prompt templates for context-aware memory injection.
These wrap the memory context in role-appropriate framing.
"""

from __future__ import annotations

from typing import Optional


def build_system_with_memory(
    base_system:    str,
    memory_context: str,
    agent_role:     str = "assistant",
) -> str:
    """
    Inject memory context into a system prompt.
    Memory appears AFTER base system instructions
    so base instructions take precedence.
    """
    return f"""{base_system}

{memory_context}

---
You are a {agent_role} with access to the memory context above.
Use it to provide more accurate, consistent, personalized responses.
Always verify facts before relying on them.
"""


def build_memory_refresh_prompt(
    query:           str,
    memory_context:  str,
    prior_response:  Optional[str] = None,
) -> str:
    """
    Ask the agent to re-read memory and revise a response.
    Used when a response may have ignored relevant memory.
    """
    base = (
        f"Please review this memory context:\n\n"
        f"{memory_context}\n\n"
        f"Now answer the following query, making sure to use "
        f"any relevant memory facts:\n\n{query}"
```

```
    )
    if prior_response:
        base += (
            f"\n\nYour previous response was:\n{prior_response}\n\n"
            f"Please revise it if the memory context changes your answer."
        )
    return base


def build_memory_extraction_prompt(response: str) -> str:
    """
    After an agent response, extract any new facts worth storing.
    """
    return (
        f"Review this assistant response and identify any facts "
        f"worth storing in long-term memory:\n\n"
        f"{response}\n\n"
        f"Focus on decisions, preferences, constraints, and "
        f"non-obvious insights that would be valuable in future sessions."
    )


def build_verification_prompt(
    fact_content: str,
    fact_id:      str,
    context:      str,
) -> str:
    """
    Ask the agent to verify a specific memory fact.
    """
    return (
        f"Please verify this stored memory fact:\n\n"
        f"Fact ID: {fact_id}\n"
        f"Fact: {fact_content}\n\n"
        f"Based on this context:\n{context}\n\n"
        f"Is this fact still accurate? If not, what is the correct version?"
    )
```

---

10. Streaming Context Updater

Python

```
# memograph/injection/streaming_updater.py
"""
Mid-stream context updater.

When streaming a long response, the agent may encounter information
that should update the memory index. This module handles:
1. Detecting memory-worthy signals in streaming output
2. Queuing updates for post-stream processing
3. Updating context cache on next turn
"""
```

```python
from __future__ import annotations

import logging
import re
from dataclasses import dataclass, field
from datetime import datetime
from typing import AsyncIterator, Callable, Optional

logger = logging.getLogger("memograph.injection.streaming")


# Patterns that indicate memory-worthy content in streaming output
MEMORY_SIGNALS = re.compile(
    r"\b(decided|confirmed|remember|note:|important:|always|never|"
    r"we should|going forward|from now on|the key insight|"
    r"architecture decision|design choice)\b",
    re.IGNORECASE,
)


@dataclass
class StreamingSignal:
    """A memory-worthy signal detected during streaming."""
    content:    str
    position:   int        # Character position in stream
    detected_at: datetime  = field(default_factory=datetime.now)
    keyword:    str        = ""


class StreamingContextUpdater:
    """
    Monitors streaming output for memory-worthy signals.
    Queues them for post-stream processing.

    Usage:
        updater = StreamingContextUpdater(on_signal=handler)

        async for chunk in llm.stream(request):
            processed = updater.process_chunk(chunk)
            yield processed

        # After stream complete:
        signals = updater.get_signals()
        for sig in signals:
            await memory_manager.remember(...)
    """

    def __init__(
        self,
        on_signal: Optional[Callable[[StreamingSignal], None]] = None,
        buffer_size: int = 500,
    ):
        self._on_signal  = on_signal
        self._buffer     = ""
        self._position   = 0
        self._signals:   list[StreamingSignal] = []
        self._buffer_size = buffer_size
```

```
    def process_chunk(self, chunk: str) -> str:
        """
        Process a streaming chunk.
        Returns the chunk unchanged (pass-through).
        Detects signals in the background.
        """
        self._buffer   += chunk
        self._position += len(chunk)

        # Process buffer when it hits the size limit
        if len(self._buffer) >= self._buffer_size:
            self._scan_buffer()
            self._buffer = self._buffer[-50:]   # Keep tail for context

        return chunk

    def flush(self) -> None:
        """Process any remaining buffered content."""
        if self._buffer:
            self._scan_buffer()
            self._buffer = ""

    def _scan_buffer(self) -> None:
        """Scan buffer for memory signals."""
        for match in MEMORY_SIGNALS.finditer(self._buffer):
            # Extract surrounding context (up to 200 chars)
            start   = max(0, match.start() - 50)
            end     = min(len(self._buffer), match.end() + 150)
            context = self._buffer[start:end].strip()

            signal = StreamingSignal(
                content=context,
                position=self._position - len(self._buffer) + match.start(),
                keyword=match.group(0),
            )

            self._signals.append(signal)

            if self._on_signal:
                try:
                    self._on_signal(signal)
                except Exception as e:
                    logger.warning(f"Signal callback failed: {e}")

    def get_signals(self) -> list[StreamingSignal]:
        """Get all detected signals (call after stream is complete)."""
        self.flush()
        return list(self._signals)

    def reset(self) -> None:
        """Reset for a new stream."""
        self._buffer   = ""
        self._position = 0
        self._signals  = []
```

---

11. Integration into MemoryManager (Phase 4)

Python

```
# memograph/injection/__init__.py
"""Phase 4: Context Injection Engine public exports."""

from memograph.injection.context_builder import BuiltContext, ContextBuilder
from memograph.injection.token_budget import TokenBudgetManager, BudgetAllocation
from memograph.injection.relevance_ranker import RelevanceRanker, RankedPointer
from memograph.injection.strategies import InjectionStrategy, InjectionMode
from memograph.injection.formatter import SkepticalFormatter
from memograph.injection.context_cache import ContextCache
from memograph.injection.pressure_monitor import ContextPressureMonitor, PressureLevel
from memograph.injection.provider_limits import get_context_spec
from memograph.injection.streaming_updater import StreamingContextUpdater

__all__ = [
    "BuiltContext",
    "ContextBuilder",
    "TokenBudgetManager",
    "BudgetAllocation",
    "RelevanceRanker",
    "RankedPointer",
    "InjectionStrategy",
    "InjectionMode",
    "SkepticalFormatter",
    "ContextCache",
    "ContextPressureMonitor",
    "PressureLevel",
    "get_context_spec",
    "StreamingContextUpdater",
]
```

Python

```
# Additions to memograph/core/memory_manager.py (Phase 4)
"""
Add get_context(), build_context_for_prompt(), switch_strategy()
to MemoryManagerV2.
"""

# New imports to add:
from memograph.injection.context_builder import BuiltContext, ContextBuilder
from memograph.injection.token_budget import TokenBudgetManager
from memograph.injection.strategies import InjectionMode, InjectionStrategy

# New attributes in __init__:
```

```python
#   self._context_builder: Optional[ContextBuilder] = None

# New methods:

    async def _init_context_builder(self) -> None:
        """Initialize Phase 4 context builder."""
        budget = TokenBudgetManager(
            model=getattr(
                self.config.get_active_provider_config(),
                "model",
                "",
            ),
            provider=self.config.llm_provider.value,
            strategy="balanced",
        )
        self._context_builder = ContextBuilder(
            index_engine=self._index_engine,
            topic_manager=self._topic_manager,
            budget_manager=budget,
            strategy=InjectionStrategy.balanced(),
            enable_cache=True,
        )

    async def build_context(
        self,
        query:               str = "",
        conversation_tokens: int = 0,
        force_rebuild:       bool = False,
    ) -> BuiltContext:
        """
        Build the per-turn context injection.

        This is what you call before every LLM request.

        Args:
            query:               The user's current message
            conversation_tokens:  How many tokens are in your conversation history
            force_rebuild:        Skip cache and rebuild fresh

        Returns:
            BuiltContext with .text ready to inject as system context

        Usage:
            ctx = await memory.build_context(query=user_message)
            messages = [
                {"role": "system", "content": ctx.text},
                *conversation_history,
                {"role": "user", "content": user_message},
            ]
            response = await llm.complete(messages)
        """
        if self._context_builder is None:
            await self._init_context_builder()

        return await self._context_builder.build(
            query=query,
            conversation_tokens=conversation_tokens,
            force_rebuild=force_rebuild,
```

```
        )

    def switch_injection_strategy(self, mode: str) -> None:
        """
        Switch injection strategy at runtime.
        mode: "conservative" | "balanced" | "aggressive"
        """
        if self._context_builder:
            self._context_builder.switch_strategy(mode)
        logger.info(f"Injection strategy switched to: {mode}")

    def get_injection_stats(self) -> dict:
        """Get context injection performance statistics."""
        if not self._context_builder:
            return {"status": "not_initialized"}

        return self._context_builder.get_stats()
```

---

12. Full Phase 4 Test Suite

Python

```
# tests/test_token_budget.py

import pytest
from memograph.injection.token_budget import (
    TokenBudgetManager,
    TokenCounter,
    BudgetSpend,
)


def test_token_counter_approximate():
    counter = TokenCounter(mode="approximate")
    text    = "Hello world " * 100
    count   = counter.count(text)
    assert count > 0
    assert count < len(text)


def test_token_counter_empty():
    counter = TokenCounter()
    assert counter.count("") == 0
    assert counter.count("   ") == 0


def test_truncate_to_budget():
    counter = TokenCounter()
    text    = "This is a long text. " * 200
    budget  = 50
    result  = counter.truncate_to_budget(text, budget)
```

```
    assert counter.count(result) <= budget + 5   # Small tolerance
    assert "truncated" in result


def test_budget_manager_allocation():
    mgr = TokenBudgetManager(
        model="llama3.1:8b",
        provider="ollama",
        strategy="balanced",
    )
    alloc = mgr.get_allocation()
    assert alloc.total_context    == 131_072
    assert alloc.available_input  >  0
    assert alloc.memory_index     >  0
    assert alloc.topic_files      >  0
    assert alloc.is_feasible()


def test_budget_manager_strategy_switch():
    mgr = TokenBudgetManager(model="gpt-4o", provider="openai")
    mgr.switch_strategy("conservative")
    alloc_cons = mgr.get_allocation()

    mgr.switch_strategy("aggressive")
    alloc_agg  = mgr.get_allocation()

    # Aggressive loads more topics
    assert alloc_agg.topic_files > alloc_cons.topic_files
    # Conservative preserves more conversation space
    assert alloc_cons.conversation > alloc_agg.conversation


def test_budget_manager_tiny_context():
    # Simulate a small context model
    mgr = TokenBudgetManager(
        model="gpt-3.5-turbo",
        provider="openai",
    )
    assert mgr.is_tiny_context()
    assert not mgr.is_large_context()


def test_budget_manager_large_context():
    mgr = TokenBudgetManager(
        model="claude-3-5-sonnet",
        provider="anthropic",
    )
    assert mgr.is_large_context()


def test_budget_spend_tracking():
    mgr   = TokenBudgetManager(model="llama3.1:8b", provider="ollama")
    alloc = mgr.get_allocation()
    spend = mgr.new_spend_tracker()

    spend.index_tokens = 500
    spend.topic_tokens = 1500
```

```
    remaining = spend.remaining(alloc)
    assert remaining["memory_index"]  == alloc.memory_index  - 500
    assert remaining["topic_files"]   == alloc.topic_files   - 1500
    assert spend.usage_ratio(alloc)   >  0


def test_per_topic_budget():
    mgr = TokenBudgetManager(model="llama3.1:8b", provider="ollama")
    b3  = mgr.compute_topic_budget_per_topic(3)
    b6  = mgr.compute_topic_budget_per_topic(6)
    assert b3 > b6   # Fewer topics = more budget per topic
    assert b3 > 0
    assert b6 > 0


def test_budget_summary():
    mgr     = TokenBudgetManager(model="llama3.1:8b", provider="ollama")
    summary = mgr.summary()
    assert "model"      in summary
    assert "strategy"   in summary
    assert "allocation" in summary
    assert "layers"     in summary["allocation"]
```

Python

```
# tests/test_relevance_ranker.py

import pytest
from datetime import datetime, timedelta
from memograph.injection.relevance_ranker import RelevanceRanker, TFIDF
from memograph.models.index import IndexPointer


def make_pointer(
    topic_id:     str,
    summary:      str,
    confidence:   float = 0.7,
    access_count: int   = 0,
    days_old:     int   = 0,
    is_stale:     bool  = False,
) -> IndexPointer:
    return IndexPointer(
        topic_id=topic_id,
        topic_file_path=f"topics/{topic_id}.json",
        summary=summary,
        confidence=confidence,
        access_count=access_count,
        last_updated=datetime.now() - timedelta(days=days_old),
        is_stale=is_stale,
    )


def test_ranker_basic_relevance():
    ranker   = RelevanceRanker()
    pointers = [
        make_pointer("auth_system",  "JWT authentication and OAuth2 setup"),
```

```
        make_pointer("db_schema",    "PostgreSQL database schema and migrations"),
        make_pointer("user_prefs",   "User UI preferences and dark mode settings"),
    ]

    ranked = ranker.rank("how does authentication work", pointers)
    assert len(ranked) > 0
    assert ranked[0].pointer.topic_id == "auth_system"


def test_ranker_no_match_returns_empty():
    ranker   = RelevanceRanker()
    pointers = [
        make_pointer("python_tips", "Python coding conventions"),
    ]
    ranked = ranker.rank("quantum physics research", pointers, min_score=0.5)
    assert len(ranked) == 0


def test_ranker_stale_penalty():
    ranker   = RelevanceRanker(stale_penalty=0.4)
    pointers = [
        make_pointer("fresh",   "database connection settings", is_stale=False),
        make_pointer("stale",   "database connection settings", is_stale=True),
    ]

    ranked = ranker.rank("database connection", pointers)
    assert len(ranked) == 2
    fresh_score = next(r.score for r in ranked if r.pointer.topic_id == "fresh")
    stale_score = next(r.score for r in ranked if r.pointer.topic_id == "stale")
    assert fresh_score > stale_score


def test_ranker_confidence_boost():
    ranker   = RelevanceRanker()
    pointers = [
        make_pointer("high_conf", "deployment configuration", confidence=0.9),
        make_pointer("low_conf",  "deployment configuration", confidence=0.2),
    ]

    ranked = ranker.rank("deployment config", pointers)
    scores = {r.pointer.topic_id: r.score for r in ranked}
    assert scores["high_conf"] > scores["low_conf"]


def test_ranker_exact_match_bonus():
    ranker   = RelevanceRanker(exact_match_bonus=2.0)
    pointers = [
        make_pointer("auth_system",   "user login and token management"),
        make_pointer("payment_system", "Stripe payment processing"),
    ]

    ranked = ranker.rank("auth_system details", pointers)
    if len(ranked) >= 2:
        # auth_system (exact match) should rank higher
        assert ranked[0].pointer.topic_id == "auth_system"


def test_ranker_explain():
```

```
    ranker   = RelevanceRanker()
    pointer  = make_pointer("tech_stack", "FastAPI Python async backend")
    ranker.fit_corpus([pointer])

    explanation = ranker.explain("python backend", "tech_stack", pointer)
    assert "tech_stack" in explanation
    assert "score" in explanation.lower()


def test_tfidf_basic():
    tfidf = TFIDF()
    tfidf.fit("doc1", "python async fastapi postgresql")
    tfidf.fit("doc2", "react typescript frontend components")

    score1 = tfidf.score(["python", "async"], "doc1")
    score2 = tfidf.score(["python", "async"], "doc2")
    assert score1 > score2


def test_tfidf_remove():
    tfidf = TFIDF()
    tfidf.fit("doc1", "important content")
    tfidf.remove("doc1")
    assert "doc1" not in tfidf._docs


def test_ranker_top_k():
    ranker   = RelevanceRanker()
    pointers = [
        make_pointer(f"topic_{i}", f"content about subject {i}")
        for i in range(20)
    ]

    ranked = ranker.rank("content subject", pointers, top_k=5)

    assert len(ranked) <= 5
```

Python

```
# tests/test_strategies.py

import pytest
from memograph.injection.strategies import InjectionStrategy, InjectionMode


def test_conservative_strategy():
    s = InjectionStrategy.conservative()
    assert s.mode          == InjectionMode.CONSERVATIVE
    assert s.max_topics    <= 2
    assert s.min_relevance_score > 0.1


def test_balanced_strategy():
    s = InjectionStrategy.balanced()
    assert s.mode       == InjectionMode.BALANCED
    assert s.max_topics == 3
```

```
def test_aggressive_strategy():
    s = InjectionStrategy.aggressive()
    assert s.mode       == InjectionMode.AGGRESSIVE
    assert s.max_topics >= 5
    assert s.annotate_fact_confidence is True


def test_from_mode_string():
    s = InjectionStrategy.from_mode("conservative")
    assert s.mode == InjectionMode.CONSERVATIVE

    s2 = InjectionStrategy.from_mode("aggressive")
    assert s2.mode == InjectionMode.AGGRESSIVE


def test_with_max_topics():
    s  = InjectionStrategy.balanced()
    s2 = s.with_max_topics(10)
    assert s2.max_topics == 10
    assert s.max_topics  == 3   # Original unchanged


def test_with_min_score():
    s  = InjectionStrategy.balanced()
    s2 = s.with_min_score(0.5)
    assert s2.min_relevance_score == 0.5

    assert s.min_relevance_score  != 0.5
```

Python

```
# tests/test_formatter.py

import pytest
from datetime import datetime
from memograph.injection.formatter import SkepticalFormatter
from memograph.injection.strategies import InjectionStrategy
from memograph.models.index import IndexPointer, MemoryIndex
from memograph.models.topic import MemoryFact, TopicFile
from memograph.config import ConfidenceLevel


@pytest.fixture
def sample_index():
    idx = MemoryIndex(agent_id="test")
    idx.pointers = [
        IndexPointer(
            topic_id="tech_stack",
            topic_file_path="topics/tech_stack.json",
            summary="FastAPI Python async backend",
            confidence=0.9,
        ),
        IndexPointer(
            topic_id="user_prefs",
```

```
            topic_file_path="topics/user_prefs.json",
            summary="User UI preferences",
            confidence=0.7,
            is_stale=True,
        ),
    ]
    return idx


@pytest.fixture
def sample_topic():
    topic = TopicFile(
        topic_id="tech_stack",
        topic_name="Tech Stack",
        agent_id="test",
        tags=["python", "fastapi"],
    )
    topic.facts = [
        MemoryFact(
            content="Backend uses FastAPI with Python 3.11",
            confidence=ConfidenceLevel.VERIFIED,
            source="architecture_doc",
            last_verified=datetime.now(),
        ),
        MemoryFact(
            content="Uses asyncpg for PostgreSQL",
            confidence=ConfidenceLevel.OBSERVED,
            source="codebase",
        ),
        MemoryFact(
            content="Might migrate to SQLModel later",
            confidence=ConfidenceLevel.INFERRED,
            source="team_chat",
        ),
    ]
    return topic


def test_format_full(sample_index, sample_topic):
    formatter = SkepticalFormatter(InjectionStrategy.balanced())
    result    = formatter.format_full(
        index=sample_index,
        topics=[sample_topic],
        ranked_pointers=[],
    )
    assert "MemoGraph" in result
    assert "Memory Index" in result
    assert "Tech Stack" in result
    assert "VERIFIED" in result
    assert "MEMORY USAGE REMINDER" in result


def test_format_compact(sample_index, sample_topic):
    formatter = SkepticalFormatter(InjectionStrategy.conservative())
    result    = formatter.format_compact(sample_index, [sample_topic])
    assert "Memory Context" in result
    assert "tech_stack" in result.lower()
    assert len(result) < 2000   # Should be compact
```

```python
def test_format_minimal(sample_index):
    formatter = SkepticalFormatter(InjectionStrategy.conservative())
    result    = formatter.format_minimal(sample_index)
    assert "Memory Index" in result
    assert "Topics" not in result or len(result) < 1000


def test_stale_warning_shown(sample_index, sample_topic):
    formatter = SkepticalFormatter(
        InjectionStrategy.balanced()
    )
    # Add stale fact
    sample_topic.facts.append(MemoryFact(
        content="Stale fact",
        confidence=ConfidenceLevel.STALE,
        source="old_source",
    ))
    result = formatter.format_full(sample_index, [sample_topic], [])
    assert "STALE" in result
    assert "⚠️" in result


def test_confidence_emojis(sample_index, sample_topic):
    formatter = SkepticalFormatter(InjectionStrategy.aggressive())
    result    = formatter.format_full(sample_index, [sample_topic], [])
    assert "✅" in result   # VERIFIED
    assert "👁️" in result   # OBSERVED
    assert "💭" in result   # INFERRED


def test_rationale_shown_in_aggressive(sample_index, sample_topic):
    from memograph.injection.relevance_ranker import RankedPointer
    formatter = SkepticalFormatter(InjectionStrategy.aggressive())

    rp = RankedPointer(
        pointer=sample_index.pointers[0],
        score=0.82,
        term_overlap=3,
        tfidf_score=0.5,
        recency_boost=0.9,
        confidence_boost=0.9,
        access_boost=0.1,
        is_exact_match=True,
    )

    result = formatter.format_full(sample_index, [sample_topic], [rp])
    assert "Why These Topics" in result


    assert "tech_stack" in result
```

Python

```python
# tests/test_context_cache.py
```

```python
import time
import pytest
from memograph.injection.context_cache import ContextCache


def test_cache_basic_get_put():
    cache = ContextCache(ttl_seconds=60)
    key   = "test_key"
    cache.put(key, "context content", tokens=100, query="test", topic_ids=["t1"])

    result = cache.get(key)
    assert result is not None
    assert result.content == "context content"
    assert result.tokens  == 100


def test_cache_miss():
    cache = ContextCache()
    assert cache.get("nonexistent") is None


def test_cache_ttl_expiry():
    cache = ContextCache(ttl_seconds=1)
    cache.put("key", "content", tokens=50, query="q", topic_ids=[])

    time.sleep(1.1)
    assert cache.get("key") is None


def test_cache_invalidate_by_topic():
    cache = ContextCache()
    cache.put("key1", "c1", 100, "q1", ["topic_a", "topic_b"])
    cache.put("key2", "c2", 100, "q2", ["topic_b", "topic_c"])
    cache.put("key3", "c3", 100, "q3", ["topic_d"])

    removed = cache.invalidate("topic_b")
    assert removed == 2
    assert cache.get("key1") is None
    assert cache.get("key2") is None
    assert cache.get("key3") is not None


def test_cache_invalidate_all():
    cache = ContextCache()
    for i in range(5):
        cache.put(f"key{i}", f"content{i}", 100, f"q{i}", [])

    removed = cache.invalidate()
    assert removed == 5
    assert cache.stats()["entries"] == 0


def test_cache_eviction_on_full():
    cache = ContextCache(ttl_seconds=60, max_entries=3)
    for i in range(4):
        cache.put(f"key{i}", f"content{i}", 100, f"q{i}", [])

    # Should have evicted oldest
```

```
    assert cache.stats()["entries"] == 3


def test_cache_hit_rate():
    cache = ContextCache()
    cache.put("k1", "c1", 100, "q", [])

    cache.get("k1")    # Hit
    cache.get("k1")    # Hit
    cache.get("k2")    # Miss

    assert cache.hit_rate == pytest.approx(2 / 3, rel=0.01)


def test_make_key_deterministic():
    k1 = ContextCache.make_key("agent1", "query", "hash", "balanced")
    k2 = ContextCache.make_key("agent1", "query", "hash", "balanced")
    k3 = ContextCache.make_key("agent1", "query", "hash", "aggressive")
    assert k1 == k2

    assert k1 != k3
```

Python

```
# tests/test_pressure_monitor.py

import pytest
from memograph.injection.pressure_monitor import (
    ContextPressureMonitor,
    PressureLevel,
)


def test_normal_pressure():
    monitor = ContextPressureMonitor()
    state   = monitor.assess(tokens_used=3000, tokens_available=8192)
    assert state.level == PressureLevel.NORMAL
    assert state.recommended_strategy == "balanced"
    assert not state.should_compact


def test_elevated_pressure():
    monitor = ContextPressureMonitor()
    # 75% = elevated
    state = monitor.assess(tokens_used=6000, tokens_available=8000)
    assert state.level == PressureLevel.ELEVATED
    assert state.recommended_strategy == "conservative"


def test_high_pressure():
    monitor = ContextPressureMonitor()
    # 90% = high
    state = monitor.assess(tokens_used=7200, tokens_available=8000)
    assert state.level == PressureLevel.HIGH
    assert not state.should_compact
```

```python
def test_critical_pressure():
    monitor = ContextPressureMonitor()
    # 97% = critical
    state = monitor.assess(tokens_used=7800, tokens_available=8000)
    assert state.level == PressureLevel.CRITICAL
    assert state.should_compact


def test_escalation_callback_fires():
    fired = []

    def on_elevated(state):
        fired.append(("elevated", state.usage_ratio))

    def on_critical(state):
        fired.append(("critical", state.usage_ratio))

    monitor = ContextPressureMonitor(
        on_elevated=on_elevated,
        on_critical=on_critical,
    )

    # Normal → Elevated escalation
    monitor.assess(tokens_used=1000, tokens_available=8000)  # Normal
    monitor.assess(tokens_used=6000, tokens_available=8000)  # Elevated
    monitor.assess(tokens_used=7800, tokens_available=8000)  # Critical

    assert any(f[0] == "elevated" for f in fired)
    assert any(f[0] == "critical" for f in fired)
    assert monitor.total_escalations >= 2


def test_tokens_remaining():
    monitor = ContextPressureMonitor()
    state   = monitor.assess(tokens_used=3000, tokens_available=8000)

    assert state.tokens_remaining == 5000
```

Python

```python
# tests/test_injection_integration.py
"""
Full integration tests for the Phase 4 injection pipeline.
"""

import pytest
from pathlib import Path
from unittest.mock import AsyncMock, MagicMock

from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.injection.context_builder import ContextBuilder
from memograph.injection.strategies import InjectionStrategy, InjectionMode
```

```python
from memograph.injection.token_budget import TokenBudgetManager
from memograph.models.index import IndexPointer
from memograph.models.topic import MemoryFact, TopicFile


@pytest.fixture
async def injection_setup(tmp_path):
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="injection_test",
        llm_provider=LLMProvider.OLLAMA,
    )

    db = DatabaseManager(config.db_path)
    await db.connect()
    await db.ensure_agent(config.agent_id)

    index_engine  = IndexEngine(config, db)
    await index_engine.initialize()

    topic_manager = TopicManager(config, db)

    # Populate with sample topics
    topics_data = [
        ("tech_stack",    "Tech Stack",    "Backend uses FastAPI with Python 3.11"),
        ("user_prefs",    "User Prefs",    "User prefers dark mode and verbose logging"),
        ("deployment",    "Deployment",    "Hosted on Railway, staging and production"),
        ("auth_system",   "Auth System",   "JWT tokens with RS256, refresh in Redis"),
        ("db_decisions",  "DB Decisions",  "PostgreSQL chosen over MongoDB for ACID"),
    ]

    for topic_id, topic_name, fact_content in topics_data:
        topic = TopicFile(
            topic_id=topic_id,
            topic_name=topic_name,
            agent_id=config.agent_id,
            tags=[topic_id.split("_")[0]],
        )
        topic.facts.append(MemoryFact(
            content=fact_content,
            confidence=ConfidenceLevel.OBSERVED,
            source="test",
        ))
        await topic_manager.save_topic(topic)

        await index_engine.add_pointer(
            topic_id=topic_id,
            topic_file_path=f"topics/{topic_id}.json",
            summary=f"{topic_name}: {fact_content[:60]}",
            confidence=0.75,
        )

    budget = TokenBudgetManager(
        model="llama3.1:8b",
        provider="ollama",
        strategy="balanced",
    )
```

```
    builder = ContextBuilder(
        index_engine=index_engine,
        topic_manager=topic_manager,
        budget_manager=budget,
        strategy=InjectionStrategy.balanced(),
        enable_cache=True,
    )

    yield builder, index_engine, topic_manager

    await db.disconnect()


@pytest.mark.asyncio
async def test_build_context_basic(injection_setup):
    builder, _, _ = injection_setup

    ctx = await builder.build(query="how does authentication work")

    assert ctx.text
    assert "Memory" in ctx.text
    assert ctx.total_tokens > 0
    assert ctx.index_tokens > 0
    assert not ctx.from_cache


@pytest.mark.asyncio
async def test_build_context_relevant_topics_loaded(injection_setup):
    builder, _, _ = injection_setup

    ctx = await builder.build(query="JWT authentication token refresh")

    # auth_system should be in loaded topics
    assert "auth_system" in ctx.topics_loaded


@pytest.mark.asyncio
async def test_build_context_cache_hit(injection_setup):
    builder, _, _ = injection_setup

    # First build
    ctx1 = await builder.build(query="tech stack python")
    assert not ctx1.from_cache

    # Second identical build — should hit cache
    ctx2 = await builder.build(query="tech stack python")
    assert ctx2.from_cache
    assert ctx2.text == ctx1.text


@pytest.mark.asyncio
async def test_build_context_force_rebuild(injection_setup):
    builder, _, _ = injection_setup

    ctx1 = await builder.build(query="deployment railway")
    ctx2 = await builder.build(query="deployment railway", force_rebuild=True)
    assert not ctx2.from_cache
```

```python
@pytest.mark.asyncio
async def test_build_context_strategy_switch(injection_setup):
    builder, _, _ = injection_setup

    # Conservative: fewer topics
    builder.switch_strategy(InjectionMode.CONSERVATIVE)
    ctx_cons = await builder.build(query="tech stack python fastapi")
    n_cons   = len(ctx_cons.topics_loaded)

    builder.switch_strategy(InjectionMode.AGGRESSIVE)
    ctx_agg  = await builder.build(
        query="tech stack python fastapi", force_rebuild=True
    )
    n_agg    = len(ctx_agg.topics_loaded)

    # Aggressive should load same or more topics
    assert n_agg >= n_cons


@pytest.mark.asyncio
async def test_build_minimal_context(injection_setup):
    builder, _, _ = injection_setup

    ctx = await builder.build_minimal()
    assert ctx.text
    assert len(ctx.topics_loaded) == 0
    assert ctx.pressure_level     == "critical"
    assert ctx.strategy_used      == "minimal"


@pytest.mark.asyncio
async def test_context_has_skeptical_framing(injection_setup):
    builder, _, _ = injection_setup

    ctx = await builder.build(query="deployment info")
    assert any(
        phrase in ctx.text
        for phrase in ["hint", "verify", "VERIFY", "Verify", "trust"]
    )


@pytest.mark.asyncio
async def test_builder_stats(injection_setup):
    builder, _, _ = injection_setup

    await builder.build(query="query one")
    await builder.build(query="query one")    # Cache hit
    await builder.build(query="query two")

    stats = builder.get_stats()
    assert stats["builds_total"]  >= 3
    assert stats["builds_cached"] >= 1
    assert "cache" in stats


@pytest.mark.asyncio
```

```python
async def test_token_budget_respected(injection_setup):
    builder, _, _ = injection_setup

    ctx = await builder.build(query="everything about the project")

    # Should never exceed available input budget
    alloc = builder.budget.get_allocation()
    assert ctx.total_tokens <= alloc.available_input + 500   # Small tolerance


@pytest.mark.asyncio
async def test_pressure_triggers_conservative_mode(injection_setup):
    builder, _, _ = injection_setup

    # Simulate very high conversation token usage
    ctx = await builder.build(
        query="tech stack",
        conversation_tokens=7800,   # Near 100% of 8192
    )

    # Should have switched to minimal/conservative
    assert ctx.pressure_level in ("high", "critical")

    assert len(ctx.topics_loaded) <= 1
```

---

13. Phase 4 Demo

Python

```python
# examples/phase4_injection_demo.py
"""
Phase 4 Demo — Bandwidth-Aware Context Injection Engine.

Shows:
1. Token budget allocation for different models
2. Relevance ranking in action
3. Conservative vs Aggressive strategy comparison
4. Context pressure simulation
5. Streaming context updater
6. Integration with a real LLM call
"""

import asyncio
import logging
from pathlib import Path

from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
from memograph.core.index_engine import IndexEngine
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.injection.context_builder import ContextBuilder
```

```python
from memograph.injection.pressure_monitor import ContextPressureMonitor
from memograph.injection.provider_limits import get_context_spec, list_models_by_provider
from memograph.injection.relevance_ranker import RelevanceRanker
from memograph.injection.strategies import InjectionStrategy, InjectionMode
from memograph.injection.streaming_updater import StreamingContextUpdater
from memograph.injection.token_budget import TokenBudgetManager
from memograph.llm.factory import create_provider
from memograph.models.index import IndexPointer
from memograph.models.topic import MemoryFact, TopicFile

logging.basicConfig(
    level=logging.INFO,
    format="%(asctime)s [%(name)s] %(levelname)s: %(message)s",
)
logger = logging.getLogger("phase4_demo")


async def demo_token_budget():
    """Show token budget allocation for different models."""
    print("\n" + "="*60)
    print("1. TOKEN BUDGET ALLOCATION BY MODEL")
    print("="*60)

    models = [
        ("gpt-4o",              "openai"),
        ("claude-3-5-sonnet",   "anthropic"),
        ("llama3.1:8b",         "ollama"),
        ("gemini-1.5-flash",    "gemini"),
        ("llama-3.1-8b-instant","groq"),
    ]

    for model, provider in models:
        spec  = get_context_spec(model, provider)
        mgr   = TokenBudgetManager(model, provider, strategy="balanced")
        alloc = mgr.get_allocation()

        print(f"\n  {provider.upper()} / {model}")
        print(f"    Context window:  {spec.context_tokens:,} tokens")
        print(f"    Available input: {alloc.available_input:,} tokens")
        print(f"    Memory index:    {alloc.memory_index:,} tokens")
        print(f"    Topic files:     {alloc.topic_files:,} tokens")
        print(f"    Conversation:    {alloc.conversation:,} tokens")


async def demo_relevance_ranking():
    """Show relevance ranking in action."""
    print("\n" + "="*60)
    print("2. RELEVANCE RANKING")
    print("="*60)

    from datetime import datetime, timedelta

    pointers = [
        IndexPointer(
            topic_id="auth_system",
            topic_file_path="topics/auth.json",
            summary="JWT RS256 authentication, OAuth2, refresh tokens Redis",
            confidence=0.9,
```

```
            last_updated=datetime.now(),
        ),
        IndexPointer(
            topic_id="tech_stack",
            topic_file_path="topics/tech.json",
            summary="FastAPI Python 3.11 async backend PostgreSQL asyncpg",
            confidence=0.85,
            last_updated=datetime.now() - timedelta(days=5),
        ),
        IndexPointer(
            topic_id="deployment",
            topic_file_path="topics/deploy.json",
            summary="Railway hosting staging production CI/CD GitHub Actions",
            confidence=0.7,
            last_updated=datetime.now() - timedelta(days=10),
        ),
        IndexPointer(
            topic_id="user_prefs",
            topic_file_path="topics/prefs.json",
            summary="Dark mode enabled verbose logging prefer concise responses",
            confidence=0.8,
            last_updated=datetime.now() - timedelta(days=2),
        ),
    ]

    ranker = RelevanceRanker()

    queries = [
        "How does authentication work with tokens?",
        "What Python framework are we using?",
        "How is the app deployed?",
        "What are the user's UI preferences?",
        "Tell me about everything",
    ]

    for query in queries:
        ranked = ranker.rank(query, pointers, top_k=3)
        print(f"\n  Query: '{query}'")
        for i, rp in enumerate(ranked, 1):
            exact = " ✓ exact" if rp.is_exact_match else ""
            print(
                f"    {i}. [{rp.pointer.topic_id}] "
                f"score={rp.score:.3f} "
                f"overlap={rp.term_overlap}"
                f"{exact}"
            )


async def demo_strategy_comparison(tmp_path: Path):
    """Compare conservative vs aggressive injection."""
    print("\n" + "="*60)
    print("3. STRATEGY COMPARISON")
    print("="*60)

    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "demo.db"),
        agent_id="demo",
```

```
        llm_provider=LLMProvider.OLLAMA,
    )

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent(config.agent_id)
        index_engine  = IndexEngine(config, db)
        await index_engine.initialize()
        topic_manager = TopicManager(config, db)

        # Create topics
        for i, (tid, name, content) in enumerate([
            ("tech_stack",   "Tech Stack",   "FastAPI Python 3.11 async PostgreSQL"),
            ("auth_system",  "Auth System",  "JWT RS256 OAuth2 Redis refresh tokens"),
            ("deployment",   "Deployment",   "Railway staging production CI/CD"),
            ("user_prefs",   "User Prefs",   "Dark mode verbose logging concise"),
            ("arch_design",  "Architecture", "Microservices async event-driven DDD"),
        ]):
            topic = TopicFile(topic_id=tid, topic_name=name, agent_id="demo")
            topic.facts.append(MemoryFact(
                content=content,
                confidence=ConfidenceLevel.OBSERVED,
                source="demo",
            ))
            await topic_manager.save_topic(topic)
            await index_engine.add_pointer(
                topic_id=tid,
                topic_file_path=f"topics/{tid}.json",
                summary=f"{name}: {content}",
                confidence=0.7 + i * 0.05,
            )

        budget = TokenBudgetManager("llama3.1:8b", "ollama")

        for strategy_name in ["conservative", "balanced", "aggressive"]:
            strategy = InjectionStrategy.from_mode(strategy_name)
            builder  = ContextBuilder(
                index_engine=index_engine,
                topic_manager=topic_manager,
                budget_manager=budget,
                strategy=strategy,
                enable_cache=False,
            )

            ctx = await builder.build("python backend authentication deployment")

            print(f"\n  Strategy: {strategy_name.upper()}")
            print(f"    Topics loaded:  {len(ctx.topics_loaded)} → {ctx.topics_loaded}")
            print(f"    Topics skipped: {len(ctx.topics_skipped)}")
            print(f"    Index tokens:   {ctx.index_tokens:,}")
            print(f"    Topic tokens:   {ctx.topic_tokens:,}")
            print(f"    Total tokens:   {ctx.total_tokens:,}")
            print(f"    Was truncated:  {ctx.was_truncated()}")


async def demo_pressure_simulation():
    """Simulate context pressure levels."""
    print("\n" + "="*60)
    print("4. CONTEXT PRESSURE SIMULATION")
```

```
    print("="*60)

    escalations = []

    monitor = ContextPressureMonitor(
        on_elevated=lambda s: escalations.append(("elevated", s.usage_ratio)),
        on_high=lambda s:     escalations.append(("high",     s.usage_ratio)),
        on_critical=lambda s: escalations.append(("critical", s.usage_ratio)),
    )

    scenarios = [
        (1000,  8192, "Early conversation"),
        (3000,  8192, "Mid conversation"),
        (5700,  8192, "75% full — elevated"),
        (6900,  8192, "87% full — high"),
        (7800,  8192, "97% full — critical"),
    ]

    for used, available, description in scenarios:
        state = monitor.assess(tokens_used=used, tokens_available=available)
        print(
            f"  {state.level.value.upper():10} "
            f"({state.usage_ratio:.0%}) "
            f"→ strategy: {state.recommended_strategy:12} "
            f"| {description}"
        )

    print(f"\n  Total escalations: {monitor.total_escalations}")
    for name, ratio in escalations:
        print(f"    Escalated to {name} at {ratio:.0%}")


async def demo_streaming_updater():
    """Show streaming signal detection."""
    print("\n" + "="*60)
    print("5. STREAMING SIGNAL DETECTION")
    print("="*60)

    signals = []
    updater = StreamingContextUpdater(
        on_signal=lambda s: signals.append(s),
        buffer_size=100,
    )

    # Simulate streaming response
    response_chunks = [
        "Based on what we discussed, ",
        "the architecture decision ",
        "is to use async everywhere. ",
        "Remember that PostgreSQL was chosen ",
        "because of ACID compliance. ",
        "Going forward we should always ",
        "use connection pooling. ",
        "The key insight here is that ",
        "async gives us 10x throughput. ",
        "This is important for scaling.",
    ]
```

```
    full_response = ""
    for chunk in response_chunks:
        processed = updater.process_chunk(chunk)
        full_response += processed

    final_signals = updater.get_signals()
    print(f"\n  Streaming response:")
    print(f"    '{full_response}'")
    print(f"\n  Memory-worthy signals detected: {len(final_signals)}")
    for sig in final_signals:
        print(f"    → [{sig.keyword}] '{sig.content[:80]}...'")


async def demo_full_pipeline(tmp_path: Path):
    """End-to-end: store memory, build context, format for LLM."""
    print("\n" + "="*60)
    print("6. FULL PIPELINE — STORE → INJECT → USE")
    print("="*60)

    config = MemoGraphConfig(
        base_path=str(tmp_path / "pipeline"),
        db_path=str(tmp_path / "pipeline" / "demo.db"),
        agent_id="pipeline_demo",
        llm_provider=LLMProvider.OLLAMA,
    )

    from memograph.core.memory_manager import MemoryManagerV2
    from memograph.llm.base import LLMResponse
    from unittest.mock import AsyncMock, MagicMock

    # Mock LLM for demo
    mock_llm = MagicMock()
    mock_llm.complete_simple = AsyncMock(
        return_value='{"has_contradiction": false}'
    )
    mock_llm.provider_name = "mock"

    async with DatabaseManager(config.db_path) as db:
        mgr = MemoryManagerV2(config=config, llm=mock_llm, db=db)
        await mgr.initialize()

        # Store memories
        memories = [
            ("project_info",  "Project is a SaaS scheduling tool for restaurants"),
            ("tech_stack",    "Backend: FastAPI + Python 3.11 + PostgreSQL + Redis"),
            ("auth_system",   "Auth: JWT RS256, 15min access tokens, 7-day refresh"),
            ("user_profile",  "Primary user is Chef Marco, prefers mobile-first UI"),
        ]

        for topic_id, content in memories:
            await mgr.remember(
                topic_id=topic_id,
                content=content,
                source="demo_setup",
                confidence=ConfidenceLevel.OBSERVED,
            )

        # Simulate a user query
```

```
        user_query = "How does authentication work and who is the main user?"

        # Build context (Phase 4)
        ctx = await mgr.build_context(
            query=user_query,
            conversation_tokens=500,
        )

        print(f"\n  User query: '{user_query}'")
        print(f"  Topics loaded: {ctx.topics_loaded}")
        print(f"  Total tokens:  {ctx.total_tokens}")
        print(f"  Pressure level: {ctx.pressure_level}")
        print(f"  From cache:    {ctx.from_cache}")
        print(f"\n  Context preview (first 500 chars):")
        print(f"  {ctx.text[:500]}...")

        # Show injection stats
        print(f"\n  Injection stats:")
        stats = mgr.get_injection_stats()
        for k, v in stats.items():
            if k != "budget":
                print(f"    {k}: {v}")

        # Show what the final prompt looks like
        from memograph.prompts.injection_prompts import build_system_with_memory
        final_system = build_system_with_memory(
            base_system="You are a helpful restaurant management assistant.",
            memory_context=ctx.text,
        )

        print(f"\n  Final system prompt length: {len(final_system)} chars")
        print(f"  Ready for LLM injection ✅")


async def main():
    import tempfile
    with tempfile.TemporaryDirectory() as tmp:
        tmp_path = Path(tmp)

        await demo_token_budget()
        await demo_relevance_ranking()
        await demo_strategy_comparison(tmp_path)
        await demo_pressure_simulation()
        await demo_streaming_updater()
        await demo_full_pipeline(tmp_path)

        print("\n" + "="*60)
        print("✅  PHASE 4 DEMO COMPLETE")
        print("="*60)


if __name__ == "__main__":
    asyncio.run(main())
```

---

14. Run Phase 4

Bash

```
# Install (all deps for full demo)
pip install -e ".[dev]"

# Optional: install tiktoken for exact token counting
pip install tiktoken

# Run Phase 4 tests
pytest tests/test_token_budget.py      -v
pytest tests/test_relevance_ranker.py  -v
pytest tests/test_strategies.py        -v
pytest tests/test_formatter.py         -v
pytest tests/test_context_cache.py     -v
pytest tests/test_pressure_monitor.py  -v
pytest tests/test_injection_integration.py -v

# Run full test suite with coverage
pytest tests/ -v --cov=memograph --cov-report=term-missing

# Run Phase 4 demo (no LLM needed)
python examples/phase4_injection_demo.py

# Quick smoke test
python -c "
from memograph.injection.token_budget import TokenBudgetManager
from memograph.injection.strategies import InjectionStrategy
from memograph.injection.provider_limits import get_context_spec

spec = get_context_spec('llama3.1:8b', 'ollama')
print('Context window:', spec.context_tokens)

mgr   = TokenBudgetManager('llama3.1:8b', 'ollama')
alloc = mgr.get_allocation()
print('Index budget:', alloc.memory_index, 'tokens')
print('Topic budget:', alloc.topic_files, 'tokens')
print('Conv budget: ', alloc.conversation, 'tokens')
print('Summary:', mgr.summary())
"
```

📊 Phase 4 Completion Checklist

Component	Status

`ProviderLimits` — 30+ models across 5 providers with exact window sizes	✅
`TokenCounter` — approximate + tiktoken exact counting	✅
`TokenBudgetManager` — per-strategy allocation with runtime switching	✅
`TFIDF` — zero-dependency TF-IDF implementation	✅
`RelevanceRanker` — 5-factor scoring with explain()	✅
`InjectionStrategy` — Conservative / Balanced / Aggressive + fluent API	✅
`SkepticalFormatter` — full / compact / minimal formats with confidence emojis	✅
`ContextCache` — TTL-based with topic-aware invalidation	✅
`ContextPressureMonitor` — 4-level pressure with escalation callbacks	✅
`ContextBuilder` — full pipeline: budget → rank → load → format → cache	✅
`StreamingContextUpdater` — real-time signal detection in streams	✅
`InjectionPrompts` — system prompt wrappers	✅

`MemoryManager` integration — `build_context()`, `switch_injection_strategy()`	✅
Full test suite — 8 test files, 50+ test cases	✅
Phase 4 demo — 6 scenarios including end-to-end pipeline	✅

🔍 PHASE 5 — RELEVANCE ENGINE: SEMANTIC SEARCH & EMBEDDINGS

The upgrade from keyword matching to true semantic understanding — MemoGraph now knows that "auth" and "authentication" are the same thing, that "we use postgres" and "database is postgresql" are related, and that two facts saying opposite things should be flagged as contradictions even when they share no words.

📋 Phase 5 Scope

Component	Description

EmbeddingProvider	Model-agnostic embedding interface (Ollama/OpenAI/Cohere/local)
VectorStore	Abstract vector store with FAISS, ChromaDB, and SQLite-vec backends
SemanticRanker	Replaces Phase 4's TF-IDF with cosine similarity + hybrid re-ranking
EmbeddingCache	Persistent embedding cache (avoid re-embedding unchanged facts)
SemanticDeduplicator	Detect near-duplicate facts across topics
ContradictionDetector	Find semantically contradicting facts without LLM
MemoryClusterer	Group related topics by semantic similarity
CrossSessionSearch	Search across all sessions by meaning, not keywords
HybridRanker	Combine TF-IDF (Phase 4) + embeddings for best results
Full test suite	Unit + integration + benchmark tests

New Files (Phase 5)

```
text
```

```
memograph/
├── embeddings/
│   ├── __init__.py
```

```
│   ├── base.py                  # Abstract embedding provider
│   ├── providers/
│   │   ├── __init__.py
│   │   ├── ollama_embeddings.py # Ollama nomic-embed-text, mxbai, etc.
│   │   ├── openai_embeddings.py # text-embedding-3-small/large
│   │   ├── cohere_embeddings.py # embed-english-v3
│   │   └── local_embeddings.py  # sentence-transformers (no API)
│   ├── cache.py                 # Persistent embedding cache
│   └── factory.py               # Embedding provider factory
│
├── vector_store/
│   ├── __init__.py
│   ├── base.py                  # Abstract vector store
│   ├── sqlite_vec_store.py      # SQLite-based (zero new deps)
│   ├── faiss_store.py           # FAISS (optional, fast)
│   └── chroma_store.py          # ChromaDB (optional, persistent)
│
├── semantic/
│   ├── __init__.py
│   ├── ranker.py                # Semantic + hybrid ranker
│   ├── deduplicator.py          # Near-duplicate detection
│   ├── contradiction_detector.py # Semantic contradiction finding
│   ├── clusterer.py             # Topic clustering
│   └── cross_session_search.py  # Cross-session semantic search
│
└── tests/
    ├── test_embeddings.py
    ├── test_vector_store.py
    ├── test_semantic_ranker.py
    ├── test_deduplicator.py
    ├── test_contradiction_detector.py
    ├── test_clusterer.py
    └── test_phase5_integration.py
```

---

1. Database Schema — Phase 5 Additions

SQL

```sql
-- memograph/db/migrations/003_embeddings.sql
-- Migration 003: Embedding storage and vector indexes

-- ═══════════════════════════════════════════════════════════════
-- EMBEDDINGS
-- Stores computed embeddings for facts and topic summaries.
-- Keyed by content hash to avoid re-embedding unchanged content.
-- ═══════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS embeddings (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
```

```
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,

    -- What this embedding represents
    entity_type         TEXT    NOT NULL,  -- fact|topic_summary|session_turn
    entity_id           TEXT    NOT NULL,  -- fact_id|topic_id|session_id:line_num
    topic_id            TEXT,              -- Null for session turns

    -- Content fingerprint (avoid re-embedding identical content)
    content_hash        TEXT    NOT NULL,
    content_preview     TEXT    NOT NULL,  -- First 100 chars for debugging

    -- Embedding data
    provider            TEXT    NOT NULL,  -- ollama|openai|cohere|local
    model               TEXT    NOT NULL,  -- nomic-embed-text|text-embedding-3-small
    dimensions          INTEGER NOT NULL,
    embedding_blob      BLOB    NOT NULL,  -- Raw float32 bytes

    -- Metadata
    created_at          TEXT    NOT NULL DEFAULT (datetime('now')),
    last_used           TEXT,
    use_count           INTEGER NOT NULL DEFAULT 0,

    UNIQUE(agent_id, entity_type, entity_id)
);

CREATE INDEX IF NOT EXISTS idx_embeddings_agent_type
    ON embeddings(agent_id, entity_type);

CREATE INDEX IF NOT EXISTS idx_embeddings_hash
    ON embeddings(content_hash);

CREATE INDEX IF NOT EXISTS idx_embeddings_topic
    ON embeddings(agent_id, topic_id);

-- ─────────────────────────────────────────────────────────────────────
-- SEMANTIC SIMILARITIES
-- Cache of computed pairwise similarities (expensive to recompute).
-- ─────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS semantic_similarities (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    entity_a_id         TEXT    NOT NULL,
    entity_b_id         TEXT    NOT NULL,
    similarity          REAL    NOT NULL,  -- 0.0 to 1.0
    computed_at         TEXT    NOT NULL DEFAULT (datetime('now')),
    flagged_duplicate   INTEGER NOT NULL DEFAULT 0,  -- >= 0.92 similarity
    flagged_contradiction INTEGER NOT NULL DEFAULT 0, -- high similarity + opposite meaning

    UNIQUE(agent_id, entity_a_id, entity_b_id)
);

CREATE INDEX IF NOT EXISTS idx_similarities_agent
    ON semantic_similarities(agent_id, similarity DESC);

CREATE INDEX IF NOT EXISTS idx_similarities_duplicates
    ON semantic_similarities(agent_id, flagged_duplicate);

-- ─────────────────────────────────────────────────────────────────────
```

```
-- MEMORY CLUSTERS
-- Groups of semantically related topics.
-- Rebuilt periodically by the clusterer.
-- ─────────────────────────────────────────────────────────────────────
CREATE TABLE IF NOT EXISTS memory_clusters (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    cluster_id          TEXT    NOT NULL,
    cluster_name        TEXT    NOT NULL,
    centroid_blob       BLOB,              -- Mean embedding of cluster members
    topic_ids           TEXT    NOT NULL DEFAULT '[]',  -- JSON array
    cohesion_score      REAL    NOT NULL DEFAULT 0.0,
    created_at          TEXT    NOT NULL DEFAULT (datetime('now')),
    updated_at          TEXT    NOT NULL DEFAULT (datetime('now')),

    UNIQUE(agent_id, cluster_id)
);

CREATE INDEX IF NOT EXISTS idx_clusters_agent
    ON memory_clusters(agent_id);

INSERT OR IGNORE INTO schema_version(version, description)
VALUES (3, 'Phase 5: embeddings, semantic_similarities, memory_clusters tables');
```

---

2. Embedding Base Interface

Python

```
# memograph/embeddings/base.py
"""
Abstract embedding provider interface.

All embedding providers speak this protocol:
- embed(text) → list[float]
- embed_batch(texts) → list[list[float]]
- dimensions → int
- model_name → str
- health_check() → bool

Design notes:
- Embeddings are always L2-normalized on output
  (cosine similarity = dot product for unit vectors)
- Batch operations are preferred for efficiency
- All providers handle rate limiting internally
"""

from __future__ import annotations

import hashlib
import math
import struct
from abc import ABC, abstractmethod
```

```
from dataclasses import dataclass
from typing import Optional


@dataclass
class EmbeddingResult:
    """Result from an embedding call."""
    embedding:      list[float]
    model:          str
    provider:       str
    dimensions:     int
    content_hash:   str
    tokens_used:    int = 0

    def to_bytes(self) -> bytes:
        """Serialize embedding to bytes (float32 little-endian)."""
        return struct.pack(f"<{len(self.embedding)}f", *self.embedding)

    @classmethod
    def from_bytes(
        cls,
        data:     bytes,
        model:    str     = "",
        provider: str     = "",
    ) -> "EmbeddingResult":
        """Deserialize embedding from bytes."""
        n = len(data) // 4   # 4 bytes per float32
        embedding = list(struct.unpack(f"<{n}f", data))
        return cls(
            embedding=embedding,
            model=model,
            provider=provider,
            dimensions=n,
            content_hash="",
        )

    def normalized(self) -> "EmbeddingResult":
        """Return L2-normalized copy."""
        norm = math.sqrt(sum(x * x for x in self.embedding))
        if norm == 0:
            return self
        normalized = [x / norm for x in self.embedding]
        return EmbeddingResult(
            embedding=normalized,
            model=self.model,
            provider=self.provider,
            dimensions=self.dimensions,
            content_hash=self.content_hash,
            tokens_used=self.tokens_used,
        )


class BaseEmbeddingProvider(ABC):
    """Abstract base for all embedding providers."""

    provider_name: str = "base"
    default_model: str = ""
```

```python
    @property
    @abstractmethod
    def dimensions(self) -> int:
        """Embedding dimensionality."""
        ...

    @property
    def model_name(self) -> str:
        return self.default_model

    @abstractmethod
    async def embed(
        self,
        text:      str,
        normalize: bool = True,
    ) -> EmbeddingResult:
        """Embed a single text."""
        ...

    @abstractmethod
    async def embed_batch(
        self,
        texts:     list[str],
        normalize: bool = True,
    ) -> list[EmbeddingResult]:
        """Embed multiple texts efficiently."""
        ...

    @abstractmethod
    async def health_check(self) -> bool:
        """Check if the provider is reachable."""
        ...

    @staticmethod
    def hash_content(text: str) -> str:
        """SHA-256 hash of text for cache keying."""
        return hashlib.sha256(text.encode()).hexdigest()[:16]

    @staticmethod
    def cosine_similarity(a: list[float], b: list[float]) -> float:
        """
        Cosine similarity between two vectors.
        Returns -1.0 to 1.0.
        If vectors are pre-normalized, this equals their dot product.
        """
        if len(a) != len(b):
            raise ValueError(
                f"Vector dimension mismatch: {len(a)} vs {len(b)}"
            )
        dot  = sum(x * y for x, y in zip(a, b))
        norm_a = math.sqrt(sum(x * x for x in a))
        norm_b = math.sqrt(sum(x * x for x in b))
        if norm_a == 0 or norm_b == 0:
            return 0.0
        return dot / (norm_a * norm_b)

    @staticmethod
    def batch_cosine_similarity(
```

```
        query:     list[float],
        vectors:   list[list[float]],
    ) -> list[float]:
        """Compute cosine similarity of query against all vectors."""
        norm_q = math.sqrt(sum(x * x for x in query))
        if norm_q == 0:
            return [0.0] * len(vectors)

        results = []
        for v in vectors:
            norm_v = math.sqrt(sum(x * x for x in v))
            if norm_v == 0:
                results.append(0.0)
                continue
            dot = sum(x * y for x, y in zip(query, v))
            results.append(dot / (norm_q * norm_v))
        return results

    @staticmethod
    def normalize(vector: list[float]) -> list[float]:
        """L2-normalize a vector."""
        norm = math.sqrt(sum(x * x for x in vector))
        if norm == 0:
            return vector
        return [x / norm for x in vector]
```

---

3. Ollama Embedding Provider

Python

```
# memograph/embeddings/providers/ollama_embeddings.py
"""
Ollama embedding provider.

Recommended models (pull before use):
  ollama pull nomic-embed-text        # 768-dim, best quality
  ollama pull mxbai-embed-large       # 1024-dim, MTEB SOTA
  ollama pull all-minilm              # 384-dim, fast/small

Usage:
  provider = OllamaEmbeddingProvider(model="nomic-embed-text")
  result   = await provider.embed("The system uses JWT authentication")
"""

from __future__ import annotations

import logging
import math
import time
from typing import Optional

import httpx
```

```python
from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult

logger = logging.getLogger("memograph.embeddings.ollama")

# Known dimensions for common Ollama embedding models
OLLAMA_EMBEDDING_DIMS: dict[str, int] = {
    "nomic-embed-text":     768,
    "mxbai-embed-large":    1024,
    "all-minilm":           384,
    "all-minilm:l6-v2":    384,
    "all-minilm:l12-v2":   384,
    "snowflake-arctic-embed": 1024,
    "bge-m3":               1024,
    "bge-large":            1024,
    "bge-base":             768,
    "e5-mistral-7b-instruct": 4096,
}


class OllamaEmbeddingProvider(BaseEmbeddingProvider):
    """
    Ollama-based embeddings — fully local, no API key.

    Features:
    - Auto-detects embedding dimensions from first call
    - Handles batch as sequential calls (Ollama has no native batching)
    - Falls back gracefully if model not available
    """

    provider_name = "ollama"

    def __init__(
        self,
        model:    str   = "nomic-embed-text",
        base_url: str   = "http://localhost:11434",
        timeout:  int   = 60,
    ):
        self.default_model = model
        self._base_url     = base_url.rstrip("/")
        self._timeout      = timeout
        self._client       = httpx.AsyncClient(timeout=timeout)
        self._dims: Optional[int] = OLLAMA_EMBEDDING_DIMS.get(
            model.split(":")[0], None
        )

    @property
    def dimensions(self) -> int:
        return self._dims or 768   # Safe default

    @property
    def model_name(self) -> str:
        return self.default_model

    async def embed(
        self,
        text:      str,
        normalize: bool = True,
```

```
    ) -> EmbeddingResult:
        """Embed a single text using Ollama."""
        t0 = time.monotonic()

        try:
            resp = await self._client.post(
                f"{self._base_url}/api/embeddings",
                json={
                    "model":  self.default_model,
                    "prompt": text,
                },
            )
            resp.raise_for_status()
            data      = resp.json()
            embedding = data["embedding"]

            # Auto-detect dimensions
            if self._dims is None:
                self._dims = len(embedding)

            if normalize:
                embedding = self.normalize(embedding)

            latency_ms = int((time.monotonic() - t0) * 1000)
            logger.debug(
                f"Embedded {len(text)} chars → {len(embedding)} dims "
                f"in {latency_ms}ms"
            )

            return EmbeddingResult(
                embedding=embedding,
                model=self.default_model,
                provider=self.provider_name,
                dimensions=len(embedding),
                content_hash=self.hash_content(text),
            )

        except httpx.ConnectError as e:
            raise ConnectionError(
                f"Cannot reach Ollama at {self._base_url}. "
                f"Is 'ollama serve' running? Error: {e}"
            ) from e
        except httpx.HTTPStatusError as e:
            if e.response.status_code == 404:
                raise RuntimeError(
                    f"Ollama model '{self.default_model}' not found. "
                    f"Run: ollama pull {self.default_model}"
                ) from e
            raise

    async def embed_batch(
        self,
        texts:     list[str],
        normalize: bool = True,
    ) -> list[EmbeddingResult]:
        """
        Embed multiple texts.
        Ollama doesn't support native batching — runs sequentially.
```

```
        For better performance, use OpenAI or Cohere providers.
        """
        results = []
        for text in texts:
            result = await self.embed(text, normalize=normalize)
            results.append(result)
        return results

    async def health_check(self) -> bool:
        """Check if Ollama is running and the model is available."""
        try:
            resp = await self._client.get(
                f"{self._base_url}/api/tags",
                timeout=5,
            )
            if resp.status_code != 200:
                return False

            models     = [m["name"] for m in resp.json().get("models", [])]
            base_model = self.default_model.split(":")[0]
            available  = any(m.startswith(base_model) for m in models)

            if not available:
                logger.warning(
                    f"Ollama model '{self.default_model}' not found. "
                    f"Available: {models}"
                )
            return available

        except Exception as e:
            logger.debug(f"Ollama health check failed: {e}")
            return False

    async def list_embedding_models(self) -> list[str]:
        """List all locally available Ollama embedding models."""
        embedding_keywords = [
            "embed", "minilm", "bge", "e5", "arctic",
        ]
        try:
            resp   = await self._client.get(f"{self._base_url}/api/tags")
            models = [m["name"] for m in resp.json().get("models", [])]
            return [
                m for m in models
                if any(k in m.lower() for k in embedding_keywords)
            ]
        except Exception:
            return []

    async def close(self) -> None:
        await self._client.aclose()
```

---

4. OpenAI Embedding Provider

Python

```python
# memograph/embeddings/providers/openai_embeddings.py
"""
OpenAI embedding provider.

Models:
  text-embedding-3-small  — 1536 dims, cheap, good quality
  text-embedding-3-large  — 3072 dims, best quality
  text-embedding-ada-002  — 1536 dims, legacy

Also works with:
  - Azure OpenAI (set base_url)
  - Any OpenAI-compatible embedding endpoint
"""

from __future__ import annotations

import logging
import time
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult

logger = logging.getLogger("memograph.embeddings.openai")

OPENAI_EMBEDDING_DIMS = {
    "text-embedding-3-small":  1536,
    "text-embedding-3-large":  3072,
    "text-embedding-ada-002":  1536,
}


class OpenAIEmbeddingProvider(BaseEmbeddingProvider):
    """OpenAI text embeddings — supports true batch requests."""

    provider_name = "openai"

    def __init__(
        self,
        api_key:  str  = "",
        model:    str  = "text-embedding-3-small",
        base_url: str  = "",
        timeout:  int  = 30,
    ):
        try:
            import openai
            self._client = openai.AsyncOpenAI(
                api_key=api_key or "placeholder",
                base_url=base_url or None,
                timeout=timeout,
            )
        except ImportError:
            raise ImportError(
                "openai package not installed. "
                "Run: pip install memograph[openai]"
            )
```

```
        self.default_model = model
        self._dims = OPENAI_EMBEDDING_DIMS.get(model, 1536)

    @property
    def dimensions(self) -> int:
        return self._dims

    async def embed(
        self,
        text:      str,
        normalize: bool = True,
    ) -> EmbeddingResult:
        results = await self.embed_batch([text], normalize=normalize)
        return results[0]

    async def embed_batch(
        self,
        texts:     list[str],
        normalize: bool = True,
    ) -> list[EmbeddingResult]:
        """Native batch embedding — efficient for large sets."""
        t0 = time.monotonic()

        try:
            response = await self._client.embeddings.create(
                model=self.default_model,
                input=texts,
                encoding_format="float",
            )
        except Exception as e:
            raise RuntimeError(f"OpenAI embedding failed: {e}") from e

        latency_ms = int((time.monotonic() - t0) * 1000)
        logger.debug(
            f"Embedded {len(texts)} texts in {latency_ms}ms "
            f"({response.usage.total_tokens} tokens)"
        )

        results = []
        for i, item in enumerate(response.data):
            emb = item.embedding
            if normalize:
                emb = self.normalize(emb)
            results.append(EmbeddingResult(
                embedding=emb,
                model=self.default_model,
                provider=self.provider_name,
                dimensions=len(emb),
                content_hash=self.hash_content(texts[i]),
                tokens_used=response.usage.total_tokens // len(texts),
            ))

        return results

    async def health_check(self) -> bool:
        try:
            await self.embed("test")
            return True
```

```
        except Exception:
            return False
```

---

5. Local Embeddings (No API Key)

Python

```
# memograph/embeddings/providers/local_embeddings.py
"""
Local embedding provider using sentence-transformers.
Zero API cost, zero network, fully private.

Install:
    pip install sentence-transformers

Recommended models:
    all-MiniLM-L6-v2           (384 dims, fast, good quality)
    all-mpnet-base-v2           (768 dims, better quality)
    multi-qa-mpnet-base-dot-v1  (768 dims, best for Q&A)
    paraphrase-multilingual...  (384 dims, multilingual)
"""

from __future__ import annotations

import logging
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult

logger = logging.getLogger("memograph.embeddings.local")

LOCAL_MODEL_DIMS = {
    "all-MiniLM-L6-v2":            384,
    "all-MiniLM-L12-v2":           384,
    "all-mpnet-base-v2":            768,
    "multi-qa-mpnet-base-dot-v1":   768,
    "paraphrase-multilingual-MiniLM-L12-v2": 384,
    "paraphrase-MiniLM-L6-v2":     384,
    "sentence-t5-base":             768,
    "BAAI/bge-small-en-v1.5":      384,
    "BAAI/bge-base-en-v1.5":       768,
    "BAAI/bge-large-en-v1.5":      1024,
}


class LocalEmbeddingProvider(BaseEmbeddingProvider):
    """
    sentence-transformers based local embeddings.
    Models are downloaded automatically on first use.
    """

    provider_name = "local"
```

```python
    def __init__(
        self,
        model:      str  = "all-MiniLM-L6-v2",
        device:     str  = "cpu",    # "cuda" if GPU available
        batch_size: int  = 64,
    ):
        self.default_model = model
        self._device       = device
        self._batch_size   = batch_size
        self._model        = None   # Lazy-loaded
        self._dims         = LOCAL_MODEL_DIMS.get(model)

    @property
    def dimensions(self) -> int:
        if self._dims:
            return self._dims
        if self._model:
            return self._model.get_sentence_embedding_dimension()
        return 384   # Safe default

    def _load_model(self):
        """Lazy-load the sentence-transformers model."""
        if self._model is None:
            try:
                from sentence_transformers import SentenceTransformer
                logger.info(
                    f"Loading sentence-transformers model: {self.default_model}"
                )
                self._model = SentenceTransformer(
                    self.default_model,
                    device=self._device,
                )
                self._dims = self._model.get_sentence_embedding_dimension()
                logger.info(
                    f"Model loaded: {self.default_model} "
                    f"({self._dims} dims)"
                )
            except ImportError:
                raise ImportError(
                    "sentence-transformers not installed. "
                    "Run: pip install sentence-transformers"
                )
        return self._model

    async def embed(
        self,
        text:      str,
        normalize: bool = True,
    ) -> EmbeddingResult:
        results = await self.embed_batch([text], normalize=normalize)
        return results[0]

    async def embed_batch(
        self,
        texts:     list[str],
        normalize: bool = True,
    ) -> list[EmbeddingResult]:
```

```
        """
        Batch embed using sentence-transformers.
        Runs synchronously in executor to avoid blocking event loop.
        """
        import asyncio

        def _encode():
            model  = self._load_model()
            import numpy as np
            embeddings = model.encode(
                texts,
                batch_size=self._batch_size,
                normalize_embeddings=normalize,
                show_progress_bar=False,
                convert_to_numpy=True,
            )
            return embeddings

        loop       = asyncio.get_event_loop()
        embeddings = await loop.run_in_executor(None, _encode)

        results = []
        for i, emb in enumerate(embeddings):
            emb_list = emb.tolist()
            results.append(EmbeddingResult(
                embedding=emb_list,
                model=self.default_model,
                provider=self.provider_name,
                dimensions=len(emb_list),
                content_hash=self.hash_content(texts[i]),
            ))
        return results

    async def health_check(self) -> bool:
        try:
            self._load_model()
            return True
        except Exception:
            return False
```

---

6. Embedding Cache

Python

```
# memograph/embeddings/cache.py
"""
Persistent embedding cache.

Stores computed embeddings in SQLite to avoid re-computing.
Cache hit = identical content hash → skip embedding API call entirely.

Cache strategy:
```

```
- Key:   SHA-256(content)[:16] + provider + model
- Store: SQLite BLOB (float32 binary)
- TTL:   None (embeddings don't expire — content hash guarantees freshness)
- Evict: LRU when over max_entries (default: 50,000)
"""

from __future__ import annotations

import logging
import struct
import time
from pathlib import Path
from typing import Optional

import aiosqlite

from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult

logger = logging.getLogger("memograph.embeddings.cache")

CACHE_SCHEMA = """
CREATE TABLE IF NOT EXISTS embedding_cache (
    key          TEXT    PRIMARY KEY,
    content_hash TEXT    NOT NULL,
    provider     TEXT    NOT NULL,
    model        TEXT    NOT NULL,
    dimensions   INTEGER NOT NULL,
    embedding    BLOB    NOT NULL,
    created_at   REAL    NOT NULL,
    last_used    REAL    NOT NULL,
    use_count    INTEGER NOT NULL DEFAULT 1
);
CREATE INDEX IF NOT EXISTS idx_cache_hash ON embedding_cache(content_hash);
CREATE INDEX IF NOT EXISTS idx_cache_lru  ON embedding_cache(last_used);
"""


class EmbeddingCache:
    """
    SQLite-backed persistent embedding cache.

    Survives process restarts.
    Thread/async-safe via aiosqlite.
    """

    def __init__(
        self,
        cache_path:  Path,
        max_entries: int = 50_000,
    ):
        self.cache_path  = Path(cache_path)
        self.max_entries = max_entries
        self._conn: Optional[aiosqlite.Connection] = None
        self._hits   = 0
        self._misses = 0

    async def connect(self) -> None:
        self.cache_path.parent.mkdir(parents=True, exist_ok=True)
```

```
        self._conn = await aiosqlite.connect(str(self.cache_path))
        self._conn.row_factory = aiosqlite.Row
        await self._conn.executescript(CACHE_SCHEMA)
        await self._conn.commit()

    async def close(self) -> None:
        if self._conn:
            await self._conn.close()
            self._conn = None

    def _make_key(
        self,
        content_hash: str,
        provider:     str,
        model:        str,
    ) -> str:
        return f"{content_hash}::{provider}::{model}"

    async def get(
        self,
        content_hash: str,
        provider:     str,
        model:        str,
    ) -> Optional[EmbeddingResult]:
        """Get a cached embedding. Returns None on miss."""
        assert self._conn, "Cache not connected"
        key = self._make_key(content_hash, provider, model)

        async with self._conn.execute(
            "SELECT * FROM embedding_cache WHERE key = ?",
            (key,),
        ) as cur:
            row = await cur.fetchone()

        if row is None:
            self._misses += 1
            return None

        # Update LRU metadata
        await self._conn.execute(
            """
            UPDATE embedding_cache
            SET last_used = ?, use_count = use_count + 1
            WHERE key = ?
            """,
            (time.time(), key),
        )
        await self._conn.commit()

        # Deserialize embedding
        n          = row["dimensions"]
        embedding  = list(struct.unpack(f"<{n}f", row["embedding"]))

        self._hits += 1
        return EmbeddingResult(
            embedding=embedding,
            model=row["model"],
            provider=row["provider"],
```

```
            dimensions=n,
            content_hash=content_hash,
        )

    async def put(
        self,
        content_hash: str,
        result:       EmbeddingResult,
    ) -> None:
        """Store an embedding in the cache."""
        assert self._conn, "Cache not connected"
        key = self._make_key(content_hash, result.provider, result.model)
        now = time.time()

        blob = struct.pack(
            f"<{len(result.embedding)}f",
            *result.embedding,
        )

        await self._conn.execute(
            """
            INSERT OR REPLACE INTO embedding_cache
            (key, content_hash, provider, model, dimensions, embedding,
             created_at, last_used, use_count)
            VALUES (?,?,?,?,?,?,?,?,1)
            """,
            (
                key, content_hash, result.provider, result.model,
                result.dimensions, blob, now, now,
            ),
        )
        await self._conn.commit()

        # Evict LRU if over limit
        await self._evict_if_needed()

    async def _evict_if_needed(self) -> None:
        """Evict oldest entries if over max_entries."""
        async with self._conn.execute(
            "SELECT COUNT(*) as n FROM embedding_cache"
        ) as cur:
            row   = await cur.fetchone()
            count = row["n"] if row else 0

        if count > self.max_entries:
            evict_n = count - self.max_entries + 100   # Batch evict
            await self._conn.execute(
                """
                DELETE FROM embedding_cache
                WHERE key IN (
                    SELECT key FROM embedding_cache
                    ORDER BY last_used ASC
                    LIMIT ?
                )
                """,
                (evict_n,),
            )
            await self._conn.commit()
```

```
            logger.debug(f"Evicted {evict_n} LRU cache entries")

    async def invalidate_provider(self, provider: str, model: str) -> int:
        """Remove all cached embeddings for a provider/model."""
        assert self._conn
        async with self._conn.execute(
            "DELETE FROM embedding_cache WHERE provider=? AND model=?",
            (provider, model),
        ) as cur:
            count = cur.rowcount
        await self._conn.commit()
        return count

    async def stats(self) -> dict:
        """Cache statistics."""
        assert self._conn
        async with self._conn.execute(
            """
            SELECT
                COUNT(*)        AS entries,
                SUM(use_count) AS total_uses,
                AVG(use_count) AS avg_uses,
                MIN(created_at) AS oldest,
                MAX(last_used) AS newest
            FROM embedding_cache
            """
        ) as cur:
            row = await cur.fetchone()

        total = self._hits + self._misses
        return {
            "entries":    row["entries"]      if row else 0,
            "total_uses": row["total_uses"]   if row else 0,
            "avg_uses":   round(row["avg_uses"] or 0, 2),
            "hits":       self._hits,
            "misses":     self._misses,
            "hit_rate":   f"{self._hits/total:.1%}" if total > 0 else "N/A",
        }

    async def __aenter__(self) -> "EmbeddingCache":
        await self.connect()
        return self

    async def __aexit__(self, *args) -> None:
        await self.close()
```

---

7. Embedding Factory

Python

```
# memograph/embeddings/factory.py
"""
```

```
Embedding provider factory — create the right provider from config.
"""

from __future__ import annotations

import logging
from typing import Optional

from memograph.config import LLMProvider, MemoGraphConfig
from memograph.embeddings.base import BaseEmbeddingProvider

logger = logging.getLogger("memograph.embeddings.factory")


def create_embedding_provider(
    provider:    str  = "ollama",
    model:       str  = "",
    api_key:     str  = "",
    base_url:    str  = "",
    config:      Optional[MemoGraphConfig] = None,
) -> BaseEmbeddingProvider:
    """
    Create an embedding provider.

    Provider/model shorthand:
        "ollama:nomic-embed-text"
        "openai:text-embedding-3-small"
        "local:all-MiniLM-L6-v2"
        "cohere:embed-english-v3.0"

    Args:
        provider:  Provider name or "provider:model" shorthand
        model:     Model name (overrides shorthand)
        api_key:   API key (overrides env)
        base_url:  Base URL (overrides default)
        config:    MemoGraphConfig (uses llm_provider as fallback)

    Returns:
        Configured BaseEmbeddingProvider
    """
    # Parse provider:model shorthand
    if ":" in provider and "/" not in provider:
        parts    = provider.split(":", 1)
        provider = parts[0]
        model    = model or parts[1]

    provider = provider.lower().strip()

    if provider == "ollama":
        from memograph.embeddings.providers.ollama_embeddings import (
            OllamaEmbeddingProvider,
        )
        cfg = config.ollama if config else None
        return OllamaEmbeddingProvider(
            model=model or (cfg and cfg.model) or "nomic-embed-text",
            base_url=base_url or (cfg and cfg.base_url) or "http://localhost:11434",
        )
```

```
    elif provider == "openai":
        from memograph.embeddings.providers.openai_embeddings import (
            OpenAIEmbeddingProvider,
        )
        cfg = config.openai if config else None
        return OpenAIEmbeddingProvider(
            api_key=api_key or (cfg and cfg.api_key) or "",
            model=model or "text-embedding-3-small",
            base_url=base_url or (cfg and cfg.base_url) or "",
        )

    elif provider in ("local", "sentence-transformers", "st"):
        from memograph.embeddings.providers.local_embeddings import (
            LocalEmbeddingProvider,
        )
        return LocalEmbeddingProvider(
            model=model or "all-MiniLM-L6-v2",
        )

    elif provider == "cohere":
        from memograph.embeddings.providers.cohere_embeddings import (
            CohereEmbeddingProvider,
        )
        return CohereEmbeddingProvider(
            api_key=api_key,
            model=model or "embed-english-v3.0",
        )

    else:
        logger.warning(
            f"Unknown embedding provider '{provider}' — "
            f"falling back to local"
        )
        from memograph.embeddings.providers.local_embeddings import (
            LocalEmbeddingProvider,
        )
        return LocalEmbeddingProvider()


async def probe_embedding_providers() -> dict[str, bool]:
    """Check which embedding providers are available."""
    results: dict[str, bool] = {}

    for name, kwargs in [
        ("ollama", {"provider": "ollama", "model": "nomic-embed-text"}),
        ("openai", {"provider": "openai"}),
        ("local",  {"provider": "local"}),
    ]:
        try:
            p = create_embedding_provider(**kwargs)
            results[name] = await p.health_check()
        except Exception:
            results[name] = False

    return results
```

---

8. Vector Store — SQLite Backend (Zero New Dependencies)

Python

```python
# memograph/vector_store/base.py
"""Abstract vector store interface."""

from __future__ import annotations

from abc import ABC, abstractmethod
from dataclasses import dataclass
from typing import Optional


@dataclass
class VectorEntry:
    """A stored vector with metadata."""
    id:         str
    vector:     list[float]
    metadata:   dict
    score:      float = 0.0   # Populated by search results


class BaseVectorStore(ABC):
    """Abstract vector store."""

    @abstractmethod
    async def upsert(self, entry: VectorEntry) -> None: ...

    @abstractmethod
    async def upsert_batch(self, entries: list[VectorEntry]) -> None: ...

    @abstractmethod
    async def search(
        self,
        query_vector: list[float],
        top_k:        int   = 10,
        min_score:    float = 0.0,
        filter_meta:  Optional[dict] = None,
    ) -> list[VectorEntry]: ...

    @abstractmethod
    async def delete(self, id: str) -> bool: ...

    @abstractmethod
    async def get(self, id: str) -> Optional[VectorEntry]: ...

    @abstractmethod
    async def count(self) -> int: ...
```

Python

```python
# memograph/vector_store/sqlite_vec_store.py
"""
SQLite-based vector store — zero additional dependencies.

Uses Python's struct module to store float32 vectors as BLOBs.
Performs exact cosine similarity search.
Fast enough for < 10,000 vectors; use FAISS for larger.

For very large collections (> 100K vectors), upgrade to:
    faiss_store.py  — in-memory ANN search
    chroma_store.py — persistent ANN search
"""

from __future__ import annotations

import json
import logging
import math
import struct
import time
from pathlib import Path
from typing import Optional

import aiosqlite

from memograph.vector_store.base import BaseVectorStore, VectorEntry

logger = logging.getLogger("memograph.vector_store.sqlite")

SCHEMA = """
CREATE TABLE IF NOT EXISTS vectors (
    id           TEXT    PRIMARY KEY,
    vector_blob  BLOB    NOT NULL,
    dimensions   INTEGER NOT NULL,
    metadata     TEXT    NOT NULL DEFAULT '{}',
    created_at   REAL    NOT NULL,
    updated_at   REAL    NOT NULL
);
CREATE INDEX IF NOT EXISTS idx_vectors_meta
    ON vectors(metadata);
"""


class SQLiteVectorStore(BaseVectorStore):
    """
    SQLite vector store with exact cosine similarity search.

    Performance characteristics:
    - Insert/update:   O(1)
    - Exact search:    O(n × d) where n=vectors, d=dimensions
    - Suitable for:    Up to ~10,000 vectors
    - Beyond that:     Use FAISSVectorStore
    """

    def __init__(self, db_path: Path):
```

```
        self.db_path = Path(db_path)
        self._conn:  Optional[aiosqlite.Connection] = None

    async def connect(self) -> None:
        self.db_path.parent.mkdir(parents=True, exist_ok=True)
        self._conn = await aiosqlite.connect(str(self.db_path))
        self._conn.row_factory = aiosqlite.Row
        await self._conn.executescript(SCHEMA)
        await self._conn.commit()

    async def close(self) -> None:
        if self._conn:
            await self._conn.close()
            self._conn = None

    async def upsert(self, entry: VectorEntry) -> None:
        assert self._conn
        blob = struct.pack(f"<{len(entry.vector)}f", *entry.vector)
        now  = time.time()
        await self._conn.execute(
            """
            INSERT OR REPLACE INTO vectors
            (id, vector_blob, dimensions, metadata, created_at, updated_at)
            VALUES (?,?,?,?,
                COALESCE((SELECT created_at FROM vectors WHERE id=?), ?),
                ?)
            """,
            (
                entry.id, blob, len(entry.vector),
                json.dumps(entry.metadata),
                entry.id, now, now,
            ),
        )
        await self._conn.commit()

    async def upsert_batch(self, entries: list[VectorEntry]) -> None:
        assert self._conn
        now = time.time()
        data = [
            (
                e.id,
                struct.pack(f"<{len(e.vector)}f", *e.vector),
                len(e.vector),
                json.dumps(e.metadata),
                now, now,
            )
            for e in entries
        ]
        await self._conn.executemany(
            """
            INSERT OR REPLACE INTO vectors
            (id, vector_blob, dimensions, metadata, created_at, updated_at)
            VALUES (?,?,?,?,?,?)
            """,
            data,
        )
        await self._conn.commit()
```

```python
    async def search(
        self,
        query_vector: list[float],
        top_k:        int   = 10,
        min_score:    float = 0.0,
        filter_meta:  Optional[dict] = None,
    ) -> list[VectorEntry]:
        """
        Exact cosine similarity search.
        Loads all vectors into memory and ranks by similarity.
        """
        assert self._conn

        # Apply metadata filter if provided
        if filter_meta:
            conditions = " AND ".join(
                f"json_extract(metadata, '$.{k}') = ?"
                for k in filter_meta
            )
            sql    = f"SELECT * FROM vectors WHERE {conditions}"
            params = list(filter_meta.values())
        else:
            sql    = "SELECT * FROM vectors"
            params = []

        async with self._conn.execute(sql, params) as cur:
            rows = await cur.fetchall()

        if not rows:
            return []

        # Compute cosine similarity for all rows
        norm_q = math.sqrt(sum(x * x for x in query_vector))
        if norm_q == 0:
            return []

        scored: list[tuple[float, VectorEntry]] = []

        for row in rows:
            n         = row["dimensions"]
            stored    = list(struct.unpack(f"<{n}f", row["vector_blob"]))
            meta      = json.loads(row["metadata"])

            # Dot product (vectors are pre-normalized → = cosine similarity)
            dot       = sum(q * s for q, s in zip(query_vector, stored))
            norm_s    = math.sqrt(sum(x * x for x in stored))
            similarity = dot / (norm_q * norm_s) if norm_s > 0 else 0.0

            if similarity >= min_score:
                scored.append((similarity, VectorEntry(
                    id=row["id"],
                    vector=stored,
                    metadata=meta,
                    score=similarity,
                )))

        scored.sort(key=lambda x: x[0], reverse=True)
        return [entry for _, entry in scored[:top_k]]
```

```
    async def delete(self, id: str) -> bool:
        assert self._conn
        async with self._conn.execute(
            "DELETE FROM vectors WHERE id = ?", (id,)
        ) as cur:
            deleted = cur.rowcount > 0
        await self._conn.commit()
        return deleted

    async def get(self, id: str) -> Optional[VectorEntry]:
        assert self._conn
        async with self._conn.execute(
            "SELECT * FROM vectors WHERE id = ?", (id,)
        ) as cur:
            row = await cur.fetchone()
        if not row:
            return None
        n      = row["dimensions"]
        vector = list(struct.unpack(f"<{n}f", row["vector_blob"]))
        return VectorEntry(
            id=row["id"],
            vector=vector,
            metadata=json.loads(row["metadata"]),
        )

    async def count(self) -> int:
        assert self._conn
        async with self._conn.execute("SELECT COUNT(*) as n FROM vectors") as cur:
            row = await cur.fetchone()
        return row["n"] if row else 0

    async def __aenter__(self) -> "SQLiteVectorStore":
        await self.connect()
        return self

    async def __aexit__(self, *args) -> None:

        await self.close()
```

---

9. FAISS Vector Store (Optional, Fast)

Python

```
# memograph/vector_store/faiss_store.py
"""
FAISS-based vector store for large collections (> 10K vectors).

Install:
    pip install faiss-cpu   # CPU version
    pip install faiss-gpu   # GPU version (requires CUDA)
```

```
Characteristics:
- ANN search (approximate nearest neighbors)
- Sub-millisecond search over millions of vectors
- In-memory index (persisted to disk via save/load)
- IVF index: fast for >= 10K vectors
- Flat index: exact, good for < 10K vectors
"""

from __future__ import annotations

import json
import logging
import pickle
import struct
from pathlib import Path
from typing import Optional

from memograph.vector_store.base import BaseVectorStore, VectorEntry

logger = logging.getLogger("memograph.vector_store.faiss")


class FAISSVectorStore(BaseVectorStore):
    """
    FAISS-backed vector store.
    Falls back to flat exact search for small collections.
    Auto-upgrades to IVF index when count > 1000.
    """

    FLAT_THRESHOLD  = 1000    # Below this: use Flat index
    IVF_NLIST       = 100     # IVF clusters

    def __init__(
        self,
        dimensions:   int,
        index_path:   Optional[Path] = None,
        use_gpu:      bool  = False,
    ):
        try:
            import faiss
            self._faiss = faiss
        except ImportError:
            raise ImportError(
                "faiss-cpu not installed. "
                "Run: pip install faiss-cpu"
            )

        self.dimensions  = dimensions
        self.index_path  = index_path
        self._use_gpu    = use_gpu
        self._index      = None
        self._id_map:    dict[int, str] = {}    # faiss_id → entry_id
        self._meta_map:  dict[str, dict] = {}   # entry_id → metadata
        self._rev_map:   dict[str, int] = {}    # entry_id → faiss_id
        self._next_id    = 0

        self._init_index()
```

```
    def _init_index(self) -> None:
        """Initialize or load FAISS index."""
        if self.index_path and self.index_path.exists():
            self._load()
            return

        # Start with flat (exact) index
        self._index = self._faiss.IndexFlatIP(self.dimensions)   # Inner product = cosine for
normalized
        logger.debug(f"FAISS Flat index created ({self.dimensions} dims)")

    async def upsert(self, entry: VectorEntry) -> None:
        """Add or update a vector."""
        import numpy as np

        vector = np.array([entry.vector], dtype=np.float32)

        if entry.id in self._rev_map:
            # FAISS doesn't support in-place update — mark old as deleted
            # (For production use, periodically rebuild the index)
            pass
        else:
            faiss_id = self._next_id
            self._next_id += 1
            self._id_map[faiss_id] = entry.id
            self._rev_map[entry.id] = faiss_id

        self._index.add(vector)
        self._meta_map[entry.id] = entry.metadata

        # Auto-upgrade to IVF if needed
        if self._index.ntotal > self.FLAT_THRESHOLD:
            self._maybe_upgrade_to_ivf()

    async def upsert_batch(self, entries: list[VectorEntry]) -> None:
        for entry in entries:
            await self.upsert(entry)

    async def search(
        self,
        query_vector: list[float],
        top_k:        int   = 10,
        min_score:    float = 0.0,
        filter_meta:  Optional[dict] = None,
    ) -> list[VectorEntry]:
        import numpy as np

        if self._index.ntotal == 0:
            return []

        query = np.array([query_vector], dtype=np.float32)
        k     = min(top_k * 2, self._index.ntotal)  # Oversample for filtering
        distances, indices = self._index.search(query, k)

        results = []
        for score, idx in zip(distances[0], indices[0]):
            if idx == -1 or score < min_score:
```

```
                continue

            entry_id = self._id_map.get(int(idx))
            if not entry_id:
                continue

            meta = self._meta_map.get(entry_id, {})

            # Apply metadata filter
            if filter_meta:
                if not all(meta.get(k) == v for k, v in filter_meta.items()):
                    continue

            results.append(VectorEntry(
                id=entry_id,
                vector=[],   # Don't reconstruct for performance
                metadata=meta,
                score=float(score),
            ))

            if len(results) >= top_k:
                break

        return results

    async def delete(self, id: str) -> bool:
        if id in self._rev_map:
            del self._rev_map[id]
            del self._meta_map[id]
            # Note: FAISS doesn't support direct deletion
            # Rebuild index on next compact operation
            return True
        return False

    async def get(self, id: str) -> Optional[VectorEntry]:
        if id not in self._rev_map:
            return None
        return VectorEntry(
            id=id,
            vector=[],
            metadata=self._meta_map.get(id, {}),
        )

    async def count(self) -> int:
        return len(self._rev_map)

    def _maybe_upgrade_to_ivf(self) -> None:
        """Upgrade from Flat to IVF index for faster search."""
        import numpy as np

        if isinstance(self._index, self._faiss.IndexIVFFlat):
            return   # Already IVF

        if self._index.ntotal < self.FLAT_THRESHOLD:
            return

        logger.info(
            f"Upgrading FAISS index to IVF "
```

```
            f"({self._index.ntotal} vectors)"
        )

        # Create IVF index
        quantizer = self._faiss.IndexFlatIP(self.dimensions)
        ivf_index = self._faiss.IndexIVFFlat(
            quantizer,
            self.dimensions,
            min(self.IVF_NLIST, self._index.ntotal // 10),
            self._faiss.METRIC_INNER_PRODUCT,
        )

        # Train on existing vectors
        all_vectors = self._faiss.rev_swig_ptr(
            self._index.xb.data(),
            self._index.ntotal * self.dimensions,
        )
        vectors_np = np.frombuffer(
            all_vectors, dtype=np.float32
        ).reshape(-1, self.dimensions)

        ivf_index.train(vectors_np)
        ivf_index.add(vectors_np)
        self._index = ivf_index
        logger.info("FAISS IVF index upgrade complete")

    def save(self) -> None:
        """Persist index to disk."""
        if not self.index_path:
            return
        self.index_path.parent.mkdir(parents=True, exist_ok=True)
        self._faiss.write_index(self._index, str(self.index_path))
        meta_path = self.index_path.with_suffix(".meta.pkl")
        with open(meta_path, "wb") as f:
            pickle.dump({
                "id_map":   self._id_map,
                "meta_map": self._meta_map,
                "rev_map":  self._rev_map,
                "next_id":  self._next_id,
            }, f)
        logger.debug(f"FAISS index saved to {self.index_path}")

    def _load(self) -> None:
        """Load index from disk."""
        self._index = self._faiss.read_index(str(self.index_path))
        meta_path   = self.index_path.with_suffix(".meta.pkl")
        if meta_path.exists():
            with open(meta_path, "rb") as f:
                data = pickle.load(f)
            self._id_map   = data["id_map"]
            self._meta_map = data["meta_map"]
            self._rev_map  = data["rev_map"]
            self._next_id  = data["next_id"]
        logger.info(
            f"FAISS index loaded: {self._index.ntotal} vectors"
        )
```

10. Semantic Ranker (Hybrid TF-IDF + Embeddings)

Python

```python
# memograph/semantic/ranker.py
"""
Hybrid semantic ranker — combines Phase 4's TF-IDF with embeddings.

Architecture:
  1. Embed the query (cached)
  2. Search vector store for top-K by cosine similarity
  3. Re-rank with TF-IDF signal (keyword overlap)
  4. Combine scores: α × semantic + β × tfidf + boosts
  5. Return final ranked list

This gives the best of both worlds:
- Semantics: "auth" matches "authentication" matches "JWT"
- Keywords:  Exact term matches get a boost
- Recency/confidence: Same boosts as Phase 4
"""

from __future__ import annotations

import logging
import math
from dataclasses import dataclass
from datetime import datetime
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider
from memograph.embeddings.cache import EmbeddingCache
from memograph.injection.relevance_ranker import RelevanceRanker, RankedPointer
from memograph.models.index import IndexPointer
from memograph.vector_store.base import BaseVectorStore, VectorEntry

logger = logging.getLogger("memograph.semantic.ranker")


@dataclass
class HybridScore:
    """Full scoring breakdown for a ranked pointer."""
    topic_id:          str
    final_score:       float
    semantic_score:    float    # Cosine similarity
    tfidf_score:       float    # TF-IDF keyword score
    recency_boost:     float
    confidence_boost:  float
    is_exact_match:    bool
    is_stale:          bool
```

```
    def to_dict(self) -> dict:
        return {
            "topic_id":       self.topic_id,
            "final":          round(self.final_score, 4),
            "semantic":       round(self.semantic_score, 4),
            "tfidf":          round(self.tfidf_score, 4),
            "recency":        round(self.recency_boost, 4),
            "confidence":     round(self.confidence_boost, 4),
            "exact_match":    self.is_exact_match,
            "stale":          self.is_stale,
        }


class SemanticRanker:
    """
    Hybrid semantic + TF-IDF ranker.

    When embeddings are available:
        final = α × semantic + β × tfidf + γ × recency + δ × confidence

    When embeddings unavailable (no provider):
        final = tfidf + recency + confidence  (Phase 4 behavior)
    """

    def __init__(
        self,
        embedding_provider: Optional[BaseEmbeddingProvider] = None,
        vector_store:       Optional[BaseVectorStore]       = None,
        embedding_cache:    Optional[EmbeddingCache]        = None,
        semantic_weight:    float = 0.50,
        tfidf_weight:       float = 0.25,
        recency_weight:     float = 0.15,
        confidence_weight:  float = 0.10,
        stale_penalty:      float = 0.40,
        exact_match_bonus:  float = 1.30,
    ):
        self._embedder  = embedding_provider
        self._store     = vector_store
        self._emb_cache = embedding_cache

        self.w_semantic    = semantic_weight
        self.w_tfidf       = tfidf_weight
        self.w_recency     = recency_weight
        self.w_confidence  = confidence_weight
        self.stale_penalty = stale_penalty
        self.exact_bonus   = exact_match_bonus

        # Phase 4 TF-IDF ranker as fallback / secondary signal
        self._tfidf_ranker = RelevanceRanker(
            weight_overlap=0.40,
            weight_tfidf=0.40,
            weight_recency=0.10,
            weight_confidence=0.10,
        )

        # Embedding index sync state
        self._indexed_topics: set[str] = set()
```

```
    async def index_pointer(self, pointer: IndexPointer) -> None:
        """
        Add or update a pointer in the vector index.
        Called when a new topic is added or updated.
        """
        if not self._embedder or not self._store:
            return

        text   = f"{pointer.topic_id}: {pointer.summary}"
        result = await self._get_or_compute_embedding(text)

        await self._store.upsert(VectorEntry(
            id=pointer.topic_id,
            vector=result.embedding,
            metadata={
                "topic_id":   pointer.topic_id,
                "summary":    pointer.summary,
                "confidence": pointer.confidence,
                "is_stale":   pointer.is_stale,
            },
        ))
        self._indexed_topics.add(pointer.topic_id)
        self._tfidf_ranker.update_corpus(pointer)

    async def index_pointers_batch(
        self,
        pointers: list[IndexPointer],
    ) -> None:
        """Batch index multiple pointers."""
        if not self._embedder or not self._store:
            self._tfidf_ranker.fit_corpus(pointers)
            return

        texts = [f"{p.topic_id}: {p.summary}" for p in pointers]

        # Batch embed (efficient for OpenAI/Cohere)
        if self._emb_cache:
            results = []
            to_embed_texts = []
            to_embed_idxs  = []

            for i, (text, p) in enumerate(zip(texts, pointers)):
                h      = BaseEmbeddingProvider.hash_content(text)
                cached = await self._emb_cache.get(
                    h, self._embedder.provider_name, self._embedder.model_name
                )
                if cached:
                    results.append((i, cached))
                else:
                    to_embed_texts.append(text)
                    to_embed_idxs.append(i)

            if to_embed_texts:
                new_results = await self._embedder.embed_batch(to_embed_texts)
                for idx, res in zip(to_embed_idxs, new_results):
                    h = BaseEmbeddingProvider.hash_content(texts[idx])
                    await self._emb_cache.put(h, res)
```

```
                    results.append((idx, res))

            results.sort(key=lambda x: x[0])
            embedding_results = [r for _, r in results]
        else:
            embedding_results = await self._embedder.embed_batch(texts)

        entries = [
            VectorEntry(
                id=p.topic_id,
                vector=embedding_results[i].embedding,
                metadata={
                    "topic_id":   p.topic_id,
                    "summary":    p.summary,
                    "confidence": p.confidence,
                    "is_stale":   p.is_stale,
                },
            )
            for i, p in enumerate(pointers)
        ]

        await self._store.upsert_batch(entries)
        self._indexed_topics.update(p.topic_id for p in pointers)
        self._tfidf_ranker.fit_corpus(pointers)

        logger.debug(f"Indexed {len(pointers)} pointers in vector store")

    async def rank(
        self,
        query:    str,
        pointers: list[IndexPointer],
        top_k:    int   = 10,
        min_score: float = 0.0,
    ) -> list[HybridScore]:
        """
        Rank pointers by hybrid semantic + TF-IDF relevance.

        Returns list of HybridScore sorted by final_score descending.
        """
        if not pointers:
            return []

        # Ensure corpus is fitted
        if not self._indexed_topics:
            await self.index_pointers_batch(pointers)

        now = datetime.now()

        # ── Semantic scores ──────────────────────────────────────────
        semantic_map: dict[str, float] = {}

        if self._embedder and self._store:
            try:
                query_result = await self._get_or_compute_embedding(query)
                vector_results = await self._store.search(
                    query_vector=query_result.embedding,
                    top_k=top_k * 2,
                    min_score=0.0,
```

```
                )
                for vr in vector_results:
                    semantic_map[vr.id] = max(0.0, float(vr.score))
            except Exception as e:
                logger.warning(f"Semantic search failed: {e} — using TF-IDF only")

        # ── TF-IDF scores ──────────────────────────────────────────────
        tfidf_ranked = self._tfidf_ranker.rank(
            query=query,
            pointers=pointers,
            top_k=top_k * 2,
            min_score=0.0,
        )
        tfidf_map = {r.pointer.topic_id: r for r in tfidf_ranked}

        # ── Combine scores ─────────────────────────────────────────────
        pointer_map = {p.topic_id: p for p in pointers}
        candidates  = set(semantic_map) | set(tfidf_map)
        all_scores: list[HybridScore] = []

        for topic_id in candidates:
            pointer = pointer_map.get(topic_id)
            if not pointer:
                continue

            sem   = semantic_map.get(topic_id, 0.0)
            tr    = tfidf_map.get(topic_id)
            tfidf = tr.score if tr else 0.0

            # Recency boost: exponential decay
            days_old      = (now - pointer.last_updated).days
            recency_boost = math.exp(-math.log(2) * days_old / 30)

            conf_boost = pointer.confidence

            # Exact match check
            query_lower = query.lower()
            is_exact    = (
                pointer.topic_id.lower() in query_lower
                or any(
                    w in query_lower
                    for w in pointer.topic_id.replace("_", " ").split()
                    if len(w) > 3
                )
            )

            # Combine
            if semantic_map:
                combined = (
                    self.w_semantic   * sem        +
                    self.w_tfidf      * tfidf      +
                    self.w_recency    * recency_boost +
                    self.w_confidence * conf_boost
                )
            else:
                # Fallback to TF-IDF-only weights
                combined = (
                    0.50 * tfidf     +
```

```
                    0.30 * recency_boost +
                    0.20 * conf_boost
                )

            if is_exact:
                combined *= self.exact_bonus

            if pointer.is_stale:
                combined *= self.stale_penalty

            score = HybridScore(
                topic_id=topic_id,
                final_score=min(1.0, combined),
                semantic_score=sem,
                tfidf_score=tfidf,
                recency_boost=recency_boost,
                confidence_boost=conf_boost,
                is_exact_match=is_exact,
                is_stale=pointer.is_stale,
            )

            if score.final_score >= min_score:
                all_scores.append(score)

        all_scores.sort(key=lambda s: s.final_score, reverse=True)
        return all_scores[:top_k]

    async def _get_or_compute_embedding(
        self,
        text: str,
    ) -> "EmbeddingResult":
        """Get from cache or compute fresh embedding."""
        from memograph.embeddings.base import BaseEmbeddingProvider as BEP

        h = BEP.hash_content(text)

        if self._emb_cache:
            cached = await self._emb_cache.get(
                h,
                self._embedder.provider_name,
                self._embedder.model_name,
            )
            if cached:
                return cached

        result = await self._embedder.embed(text)

        if self._emb_cache:
            await self._emb_cache.put(h, result)

        return result

    def has_semantic_backend(self) -> bool:
        """True if semantic search is available."""
        return self._embedder is not None and self._store is not None
```

---

11. Semantic Deduplicator

Python

```python
# memograph/semantic/deduplicator.py
"""
Semantic deduplication — find near-duplicate facts across topics.

Two facts are near-duplicates if:
  cosine_similarity(embed(a), embed(b)) >= threshold

Default threshold: 0.92
(Tuned to avoid false positives — 0.95 for strict, 0.88 for loose)

Use cases:
1. After a dream consolidation — check if newly created facts
   duplicate existing ones
2. During memory audit — find redundant storage across topics
3. Before storing a new fact — check if it already exists

Output: list of DuplicateGroup containing fact IDs and their similarity
"""

from __future__ import annotations

import logging
from dataclasses import dataclass, field
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider
from memograph.embeddings.cache import EmbeddingCache
from memograph.models.topic import MemoryFact, TopicFile

logger = logging.getLogger("memograph.semantic.deduplicator")


@dataclass
class DuplicatePair:
    """A pair of near-duplicate facts."""
    fact_a_id:    str
    fact_b_id:    str
    topic_a_id:   str
    topic_b_id:   str
    content_a:    str
    content_b:    str
    similarity:   float
    same_topic:   bool


@dataclass
class DeduplicationReport:
    """Result of a deduplication scan."""
    scanned_facts:    int
    duplicate_pairs:  list[DuplicatePair]
```

```
    threshold:        float

    @property
    def has_duplicates(self) -> bool:
        return len(self.duplicate_pairs) > 0

    @property
    def duplicate_count(self) -> int:
        return len(self.duplicate_pairs)

    def to_dict(self) -> dict:
        return {
            "scanned_facts":   self.scanned_facts,
            "duplicate_pairs": self.duplicate_count,
            "threshold":       self.threshold,
            "pairs": [
                {
                    "fact_a": p.fact_a_id,
                    "fact_b": p.fact_b_id,
                    "topics": f"{p.topic_a_id} × {p.topic_b_id}",
                    "similarity": round(p.similarity, 4),
                    "same_topic": p.same_topic,
                }
                for p in self.duplicate_pairs
            ],
        }


class SemanticDeduplicator:
    """
    Finds near-duplicate facts using embedding similarity.

    Algorithm:
    1. Embed all facts in scope
    2. Compute pairwise cosine similarity
    3. Report pairs above threshold
    4. Optionally auto-merge obvious duplicates
    """

    def __init__(
        self,
        embedding_provider: BaseEmbeddingProvider,
        embedding_cache:    Optional[EmbeddingCache] = None,
        threshold:          float = 0.92,
    ):
        self._embedder  = embedding_provider
        self._emb_cache = embedding_cache
        self.threshold  = threshold

    async def scan_topics(
        self,
        topics:          list[TopicFile],
        cross_topic_only: bool = False,
    ) -> DeduplicationReport:
        """
        Scan a list of topics for near-duplicate facts.

        Args:
```

```
            topics:           List of topics to scan
            cross_topic_only: If True, only report cross-topic duplicates
                              (ignore within-topic duplicates)

        Returns:
            DeduplicationReport
        """
        # Collect all facts
        all_facts: list[tuple[str, MemoryFact]] = []    # (topic_id, fact)
        for topic in topics:
            for fact in topic.facts:
                all_facts.append((topic.topic_id, fact))

        if len(all_facts) < 2:
            return DeduplicationReport(
                scanned_facts=len(all_facts),
                duplicate_pairs=[],
                threshold=self.threshold,
            )

        logger.info(f"Deduplication: scanning {len(all_facts)} facts")

        # Embed all facts
        texts = [f.content for _, f in all_facts]
        embeddings = await self._embed_batch_cached(texts)

        # Pairwise comparison
        pairs: list[DuplicatePair] = []
        n = len(all_facts)

        for i in range(n):
            for j in range(i + 1, n):
                topic_i, fact_i = all_facts[i]
                topic_j, fact_j = all_facts[j]

                same_topic = topic_i == topic_j

                if cross_topic_only and same_topic:
                    continue

                sim = BaseEmbeddingProvider.cosine_similarity(
                    embeddings[i], embeddings[j]
                )

                if sim >= self.threshold:
                    pairs.append(DuplicatePair(
                        fact_a_id=fact_i.fact_id,
                        fact_b_id=fact_j.fact_id,
                        topic_a_id=topic_i,
                        topic_b_id=topic_j,
                        content_a=fact_i.content,
                        content_b=fact_j.content,
                        similarity=sim,
                        same_topic=same_topic,
                    ))

        # Sort by similarity (highest first)
        pairs.sort(key=lambda p: p.similarity, reverse=True)
```

```
        logger.info(
            f"Deduplication: found {len(pairs)} duplicate pairs "
            f"(threshold={self.threshold})"
        )

        return DeduplicationReport(
            scanned_facts=n,
            duplicate_pairs=pairs,
            threshold=self.threshold,
        )

    async def is_duplicate_of_existing(
        self,
        new_content:  str,
        topic:        TopicFile,
    ) -> Optional[DuplicatePair]:
        """
        Check if new_content is a near-duplicate of any existing fact.
        Used before storing a new fact.

        Returns the DuplicatePair if a duplicate is found, None otherwise.
        """
        if not topic.facts:
            return None

        new_emb   = await self._embed_cached(new_content)
        fact_texts = [f.content for f in topic.facts]
        fact_embs  = await self._embed_batch_cached(fact_texts)

        for fact, fact_emb in zip(topic.facts, fact_embs):
            sim = BaseEmbeddingProvider.cosine_similarity(new_emb, fact_emb)
            if sim >= self.threshold:
                return DuplicatePair(
                    fact_a_id="new",
                    fact_b_id=fact.fact_id,
                    topic_a_id=topic.topic_id,
                    topic_b_id=topic.topic_id,
                    content_a=new_content,
                    content_b=fact.content,
                    similarity=sim,
                    same_topic=True,
                )

        return None

    async def _embed_cached(self, text: str) -> list[float]:
        """Get or compute embedding for a single text."""
        h = BaseEmbeddingProvider.hash_content(text)
        if self._emb_cache:
            cached = await self._emb_cache.get(
                h,
                self._embedder.provider_name,
                self._embedder.model_name,
            )
            if cached:
                return cached.embedding
```

```
        result = await self._embedder.embed(text)

        if self._emb_cache:
            await self._emb_cache.put(h, result)

        return result.embedding

    async def _embed_batch_cached(
        self,
        texts: list[str],
    ) -> list[list[float]]:
        """Batch embed with cache."""
        results:        list[Optional[list[float]]] = [None] * len(texts)
        to_embed_texts: list[str]  = []
        to_embed_idxs:  list[int]  = []

        for i, text in enumerate(texts):
            h = BaseEmbeddingProvider.hash_content(text)
            if self._emb_cache:
                cached = await self._emb_cache.get(
                    h,
                    self._embedder.provider_name,
                    self._embedder.model_name,
                )
                if cached:
                    results[i] = cached.embedding
                    continue

            to_embed_texts.append(text)
            to_embed_idxs.append(i)

        if to_embed_texts:
            new_results = await self._embedder.embed_batch(to_embed_texts)
            for idx, res in zip(to_embed_idxs, new_results):
                h = BaseEmbeddingProvider.hash_content(texts[idx])
                if self._emb_cache:
                    await self._emb_cache.put(h, res)
                results[idx] = res.embedding

        return [r for r in results if r is not None]
```

---

12. Contradiction Detector

Python

```
# memograph/semantic/contradiction_detector.py
"""
Semantic contradiction detector — no LLM required.

Strategy:
1. Find pairs with HIGH semantic similarity (same topic/concept)
2. Within those pairs, look for linguistic negation patterns
```

```
3. Flag pairs where:
   - Similarity > 0.75 (same subject)
   - Content contains opposite indicators

Limitation: This catches obvious linguistic contradictions.
For nuanced contradictions, Phase 3's LLM consolidation is used.
"""

from __future__ import annotations

import logging
import re
from dataclasses import dataclass
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider
from memograph.embeddings.cache import EmbeddingCache
from memograph.models.topic import MemoryFact, TopicFile

logger = logging.getLogger("memograph.semantic.contradiction")

# Negation patterns that suggest contradiction
NEGATION_PATTERNS = [
    (r"\bnot\b",          r"\b(?!not\b)"),
    (r"\bnever\b",        r"\balways\b"),
    (r"\bno\b",           r"\byes\b"),
    (r"\bdisabled\b",     r"\benabled\b"),
    (r"\bremoved\b",      r"\badded\b"),
    (r"\bdeprecated\b",   r"\bcurrent\b"),
    (r"\bold\b",          r"\bnew\b"),
    (r"\bstopped\b",      r"\bstarted\b"),
    (r"\brejected\b",     r"\baccepted\b"),
    (r"\bfailed\b",       r"\bsucceeded\b"),
]

# Pairs of opposite words
ANTONYM_PAIRS = [
    ("true",      "false"),
    ("yes",       "no"),
    ("enabled",   "disabled"),
    ("on",        "off"),
    ("new",       "old"),
    ("current",   "deprecated"),
    ("added",     "removed"),
    ("always",    "never"),
    ("all",       "none"),
    ("fast",      "slow"),
    ("large",     "small"),
]


@dataclass
class ContradictionPair:
    """A pair of potentially contradicting facts."""
    fact_a_id:       str
    fact_b_id:       str
    topic_id:        str
    content_a:       str
```

```
    content_b:       str
    similarity:      float
    contradiction_signals: list[str]    # What triggered the detection
    confidence:      float              # How confident we are it's a contradiction


@dataclass
class ContradictionReport:
    """Result of a contradiction scan."""
    scanned_facts: int
    contradictions: list[ContradictionPair]

    @property
    def has_contradictions(self) -> bool:
        return len(self.contradictions) > 0

    def to_dict(self) -> dict:
        return {
            "scanned_facts":  self.scanned_facts,
            "contradictions": len(self.contradictions),
            "pairs": [
                {
                    "fact_a":    c.fact_a_id,
                    "fact_b":    c.fact_b_id,
                    "topic":     c.topic_id,
                    "content_a": c.content_a[:100],
                    "content_b": c.content_b[:100],
                    "similarity": round(c.similarity, 4),
                    "signals":   c.contradiction_signals,
                    "confidence": round(c.confidence, 4),
                }
                for c in self.contradictions
            ],
        }


class ContradictionDetector:
    """
    Rule-based + semantic contradiction detection.
    No LLM required — uses embedding similarity + linguistic patterns.
    """

    SIMILARITY_THRESHOLD = 0.75    # Same topic/concept
    CONTRADICTION_MIN_CONFIDENCE = 0.5

    def __init__(
        self,
        embedding_provider: BaseEmbeddingProvider,
        embedding_cache:    Optional[EmbeddingCache] = None,
    ):
        self._embedder  = embedding_provider
        self._emb_cache = embedding_cache

    async def scan_topic(self, topic: TopicFile) -> ContradictionReport:
        """
        Scan a topic for internal contradictions.
        """
        facts = topic.facts
```

```
        if len(facts) < 2:
            return ContradictionReport(scanned_facts=len(facts), contradictions=[])

        texts      = [f.content for f in facts]
        embeddings = await self._embed_batch_cached(texts)

        contradictions: list[ContradictionPair] = []
        n = len(facts)

        for i in range(n):
            for j in range(i + 1, n):
                fact_a = facts[i]
                fact_b = facts[j]
                emb_a  = embeddings[i]
                emb_b  = embeddings[j]

                sim = BaseEmbeddingProvider.cosine_similarity(emb_a, emb_b)

                # Only check pairs that are semantically similar
                # (same topic = potential contradiction)
                if sim < self.SIMILARITY_THRESHOLD:
                    continue

                signals, confidence = self._detect_contradiction_signals(
                    fact_a.content, fact_b.content
                )

                if confidence >= self.CONTRADICTION_MIN_CONFIDENCE:
                    contradictions.append(ContradictionPair(
                        fact_a_id=fact_a.fact_id,
                        fact_b_id=fact_b.fact_id,
                        topic_id=topic.topic_id,
                        content_a=fact_a.content,
                        content_b=fact_b.content,
                        similarity=sim,
                        contradiction_signals=signals,
                        confidence=confidence,
                    ))

        return ContradictionReport(
            scanned_facts=n,
            contradictions=contradictions,
        )

    def _detect_contradiction_signals(
        self,
        text_a: str,
        text_b: str,
    ) -> tuple[list[str], float]:
        """
        Detect contradiction signals between two texts.
        Returns (signals, confidence_score).
        """
        a_lower = text_a.lower()
        b_lower = text_b.lower()
        signals: list[str] = []
        confidence = 0.0
```

```
        # Check antonym pairs
        for word_a, word_b in ANTONYM_PAIRS:
            a_has_word_a = bool(re.search(rf"\b{word_a}\b", a_lower))
            b_has_word_a = bool(re.search(rf"\b{word_a}\b", b_lower))
            a_has_word_b = bool(re.search(rf"\b{word_b}\b", a_lower))
            b_has_word_b = bool(re.search(rf"\b{word_b}\b", b_lower))

            if (a_has_word_a and b_has_word_b) or (a_has_word_b and b_has_word_a):
                signals.append(f"antonym pair: '{word_a}' vs '{word_b}'")
                confidence += 0.4

        # Check negation patterns
        for neg_pattern, pos_pattern in NEGATION_PATTERNS:
            a_has_neg = bool(re.search(neg_pattern, a_lower))
            b_has_neg = bool(re.search(neg_pattern, b_lower))

            if a_has_neg != b_has_neg:  # One has negation, other doesn't
                signals.append(f"negation asymmetry: {neg_pattern}")
                confidence += 0.3

        # Check for direct number contradictions (e.g., "uses port 8080" vs "port 9000")
        nums_a = set(re.findall(r"\b\d{2,}\b", a_lower))
        nums_b = set(re.findall(r"\b\d{2,}\b", b_lower))
        if nums_a and nums_b and not (nums_a & nums_b):
            signals.append(f"conflicting numbers: {nums_a} vs {nums_b}")
            confidence += 0.3

        return signals, min(1.0, confidence)

    async def _embed_batch_cached(
        self,
        texts: list[str],
    ) -> list[list[float]]:
        """Embed with caching."""
        results:        list[Optional[list[float]]] = [None] * len(texts)
        to_embed_texts: list[str]  = []
        to_embed_idxs:  list[int]  = []

        for i, text in enumerate(texts):
            h = BaseEmbeddingProvider.hash_content(text)
            if self._emb_cache:
                cached = await self._emb_cache.get(
                    h,
                    self._embedder.provider_name,
                    self._embedder.model_name,
                )
                if cached:
                    results[i] = cached.embedding
                    continue

            to_embed_texts.append(text)
            to_embed_idxs.append(i)

        if to_embed_texts:
            new_results = await self._embedder.embed_batch(to_embed_texts)
            for idx, res in zip(to_embed_idxs, new_results):
                h = BaseEmbeddingProvider.hash_content(texts[idx])
                if self._emb_cache:
```

```
                    await self._emb_cache.put(h, res)
                results[idx] = res.embedding

        return [r for r in results if r is not None]
```

---

13. Memory Clusterer

Python

```
# memograph/semantic/clusterer.py
"""
Memory clustering — group semantically related topics.

Algorithm: K-Means on topic embeddings.
- Number of clusters: auto-determined (sqrt(n_topics) heuristic)
- Cluster names: generated from most representative topic summaries
- Cohesion score: average intra-cluster cosine similarity

Use cases:
1. Identify knowledge domains ("auth cluster", "deployment cluster")
2. Smart topic loading: load all topics in a cluster together
3. Memory audit: find isolated/orphaned topics
4. Context building: inject by cluster rather than individual topic
"""

from __future__ import annotations

import logging
import math
import random
import uuid
from dataclasses import dataclass, field
from typing import Optional

from memograph.embeddings.base import BaseEmbeddingProvider
from memograph.embeddings.cache import EmbeddingCache
from memograph.models.index import IndexPointer

logger = logging.getLogger("memograph.semantic.clusterer")


@dataclass
class MemoryCluster:
    """A group of semantically related topics."""
    cluster_id:     str
    cluster_name:   str
    topic_ids:      list[str]
    centroid:       list[float]
    cohesion_score: float       # Average intra-cluster similarity
    representative_topic: str   # Most central topic

    def to_dict(self) -> dict:
```

```
        return {
            "cluster_id":           self.cluster_id,
            "cluster_name":         self.cluster_name,
            "topic_ids":            self.topic_ids,
            "cohesion_score":       round(self.cohesion_score, 4),
            "representative_topic": self.representative_topic,
            "size":                 len(self.topic_ids),
        }


@dataclass
class ClusteringResult:
    """Result of a clustering run."""
    clusters:       list[MemoryCluster]
    unclustered:    list[str]   # Topics that didn't fit any cluster
    n_topics:       int
    n_clusters:     int

    def find_cluster_for_topic(self, topic_id: str) -> Optional[MemoryCluster]:
        """Find which cluster a topic belongs to."""
        return next(
            (c for c in self.clusters if topic_id in c.topic_ids),
            None,
        )

    def to_dict(self) -> dict:
        return {
            "n_topics":    self.n_topics,
            "n_clusters":  self.n_clusters,
            "unclustered": len(self.unclustered),
            "clusters":    [c.to_dict() for c in self.clusters],
        }


class KMeansClusterer:
    """
    Simple K-Means clustering for memory topics.
    Pure Python — no NumPy/sklearn required.
    """

    def __init__(
        self,
        n_clusters:   Optional[int] = None,   # Auto if None
        max_iter:     int           = 50,
        tolerance:    float         = 1e-4,
        random_seed:  int           = 42,
    ):
        self.n_clusters  = n_clusters
        self.max_iter    = max_iter
        self.tolerance   = tolerance
        self.random_seed = random_seed

    def fit(
        self,
        vectors:    list[list[float]],
        topic_ids:  list[str],
        summaries:  list[str],
    ) -> ClusteringResult:
```

```
        """
        Run K-Means clustering.
        Returns ClusteringResult with cluster assignments.
        """
        n = len(vectors)
        if n == 0:
            return ClusteringResult([], [], 0, 0)

        if n == 1:
            cluster = MemoryCluster(
                cluster_id=str(uuid.uuid4())[:8],
                cluster_name=summaries[0][:30],
                topic_ids=[topic_ids[0]],
                centroid=vectors[0],
                cohesion_score=1.0,
                representative_topic=topic_ids[0],
            )
            return ClusteringResult([cluster], [], 1, 1)

        # Auto-determine cluster count
        k = self.n_clusters or max(2, int(math.sqrt(n)))
        k = min(k, n)

        # Initialize centroids (k-means++ style)
        centroids = self._init_centroids_pp(vectors, k)

        # Iterate
        assignments = [0] * n
        for iteration in range(self.max_iter):
            # Assign each point to nearest centroid
            new_assignments = self._assign(vectors, centroids)

            if new_assignments == assignments and iteration > 0:
                break   # Converged

            assignments = new_assignments

            # Update centroids
            new_centroids = self._update_centroids(vectors, assignments, k)

            # Check convergence
            max_shift = max(
                self._distance(c, nc)
                for c, nc in zip(centroids, new_centroids)
            )

            centroids = new_centroids

            if max_shift < self.tolerance:
                logger.debug(f"K-Means converged at iteration {iteration}")
                break

        # Build cluster objects
        clusters: list[MemoryCluster] = []
        for c_idx in range(k):
            member_indices = [
                i for i, a in enumerate(assignments) if a == c_idx
            ]
```

```
            if not member_indices:
                continue

            member_topic_ids = [topic_ids[i] for i in member_indices]
            member_vectors   = [vectors[i] for i in member_indices]
            centroid         = centroids[c_idx]

            # Cohesion = average similarity to centroid
            similarities = [
                BaseEmbeddingProvider.cosine_similarity(v, centroid)
                for v in member_vectors
            ]
            cohesion = sum(similarities) / len(similarities)

            # Representative = closest to centroid
            rep_idx = max(
                range(len(member_indices)),
                key=lambda i: similarities[i],
            )
            representative = member_topic_ids[rep_idx]

            # Cluster name = first N words of representative summary
            rep_summary = summaries[member_indices[rep_idx]]
            cluster_name = " ".join(rep_summary.split()[:4])

            clusters.append(MemoryCluster(
                cluster_id=str(uuid.uuid4())[:8],
                cluster_name=cluster_name,
                topic_ids=member_topic_ids,
                centroid=centroid,
                cohesion_score=cohesion,
                representative_topic=representative,
            ))

        # Sort clusters by cohesion descending
        clusters.sort(key=lambda c: c.cohesion_score, reverse=True)

        return ClusteringResult(
            clusters=clusters,
            unclustered=[],
            n_topics=n,
            n_clusters=len(clusters),
        )

    def _init_centroids_pp(
        self,
        vectors: list[list[float]],
        k:       int,
    ) -> list[list[float]]:
        """K-Means++ initialization — better than random."""
        random.seed(self.random_seed)
        centroids = [random.choice(vectors)]

        for _ in range(1, k):
            # Compute distance of each point to nearest centroid
            distances = [
                min(
```

```
                    1.0 - BaseEmbeddingProvider.cosine_similarity(v, c)
                    for c in centroids
                )
                for v in vectors
            ]
            total = sum(distances)
            if total == 0:
                centroids.append(random.choice(vectors))
                continue

            # Sample proportional to distance squared
            probs      = [d * d / sum(dd * dd for dd in distances) for d in distances]
            cumulative = 0.0
            r          = random.random()
            for i, p in enumerate(probs):
                cumulative += p
                if r <= cumulative:
                    centroids.append(vectors[i])
                    break
            else:
                centroids.append(vectors[-1])

        return centroids

    def _assign(
        self,
        vectors:   list[list[float]],
        centroids: list[list[float]],
    ) -> list[int]:
        """Assign each vector to nearest centroid."""
        assignments = []
        for v in vectors:
            similarities = [
                BaseEmbeddingProvider.cosine_similarity(v, c)
                for c in centroids
            ]
            assignments.append(similarities.index(max(similarities)))
        return assignments

    def _update_centroids(
        self,
        vectors:     list[list[float]],
        assignments: list[int],
        k:           int,
    ) -> list[list[float]]:
        """Compute new centroids as mean of assigned vectors."""
        new_centroids = []
        for c_idx in range(k):
            members = [v for v, a in zip(vectors, assignments) if a == c_idx]
            if not members:
                # Empty cluster — reinitialize to random point
                new_centroids.append(random.choice(vectors))
                continue

            # Mean of members
            dims   = len(members[0])
            mean   = [sum(v[d] for v in members) / len(members) for d in range(dims)]
            mean   = BaseEmbeddingProvider.normalize(mean)
```

```
            new_centroids.append(mean)

        return new_centroids

    @staticmethod
    def _distance(a: list[float], b: list[float]) -> float:
        """Euclidean distance."""
        return math.sqrt(sum((x - y) ** 2 for x, y in zip(a, b)))


class MemoryClusterer:
    """
    High-level memory clustering service.
    Wraps K-Means with embedding and persistence.
    """

    def __init__(
        self,
        embedding_provider: BaseEmbeddingProvider,
        embedding_cache:    Optional[EmbeddingCache] = None,
        n_clusters:         Optional[int]            = None,
    ):
        self._embedder  = embedding_provider
        self._emb_cache = embedding_cache
        self._kmeans    = KMeansClusterer(n_clusters=n_clusters)

    async def cluster_pointers(
        self,
        pointers: list[IndexPointer],
    ) -> ClusteringResult:
        """
        Cluster index pointers by semantic similarity.
        """
        if len(pointers) < 2:
            if pointers:
                cluster = MemoryCluster(
                    cluster_id=str(uuid.uuid4())[:8],
                    cluster_name=pointers[0].summary[:30],
                    topic_ids=[pointers[0].topic_id],
                    centroid=[],
                    cohesion_score=1.0,
                    representative_topic=pointers[0].topic_id,
                )
                return ClusteringResult([cluster], [], 1, 1)
            return ClusteringResult([], [], 0, 0)

        # Embed all pointer summaries
        texts = [
            f"{p.topic_id}: {p.summary}" for p in pointers
        ]
        embeddings = await self._embed_batch_cached(texts)

        topic_ids  = [p.topic_id  for p in pointers]
        summaries  = [p.summary   for p in pointers]

        result = self._kmeans.fit(embeddings, topic_ids, summaries)

        logger.info(
```

```
            f"Clustered {len(pointers)} topics into "
            f"{result.n_clusters} clusters"
        )

        return result

    async def _embed_batch_cached(
        self,
        texts: list[str],
    ) -> list[list[float]]:
        """Batch embed with caching."""
        from memograph.semantic.deduplicator import SemanticDeduplicator
        dedup = SemanticDeduplicator(self._embedder, self._emb_cache)
        return await dedup._embed_batch_cached(texts)
```

---

14. Cross-Session Semantic Search

Python

```
# memograph/semantic/cross_session_search.py
"""
Cross-session semantic search.

Searches across ALL session transcripts by meaning, not just keywords.
Unlike the Phase 1 grep (exact pattern matching), this finds
semantically related content even with different wording.

Use cases:
1. "Find sessions where we discussed authentication"
   → Returns sessions mentioning JWT, OAuth, login, tokens, etc.
2. "What did we decide about the database?"
   → Returns transcript segments about PostgreSQL, migrations, schema, etc.
3. AutoDream gather phase: find relevant past decisions for current topic
"""

from __future__ import annotations

import json
import logging
from dataclasses import dataclass, field
from pathlib import Path
from typing import AsyncIterator, Optional

import aiofiles

from memograph.embeddings.base import BaseEmbeddingProvider
from memograph.embeddings.cache import EmbeddingCache
from memograph.vector_store.base import BaseVectorStore, VectorEntry

logger = logging.getLogger("memograph.semantic.cross_session")
```

```python
@dataclass
class TranscriptMatch:
    """A semantically relevant transcript segment."""
    session_id:  str
    role:        str
    content:     str
    similarity:  float
    line_number: int
    context:     str   # Surrounding lines for context


@dataclass
class CrossSessionSearchResult:
    """Results from a cross-session semantic search."""
    query:            str
    matches:          list[TranscriptMatch]
    sessions_searched: int
    lines_indexed:    int

    def top_matches(self, n: int = 5) -> list[TranscriptMatch]:
        return sorted(
            self.matches, key=lambda m: m.similarity, reverse=True
        )[:n]


class CrossSessionSearcher:
    """
    Semantic search across session transcripts.

    Architecture:
    1. At session end → index all turns in vector store
    2. At search time → embed query, search vector store
    3. Return top-K matches with context

    The vector store uses the turn's content hash as ID,
    with session_id/role/line_num in metadata.
    """

    # Don't index very short turns (noise)
    MIN_CONTENT_LENGTH = 30

    def __init__(
        self,
        embedding_provider:  BaseEmbeddingProvider,
        vector_store:        BaseVectorStore,
        transcripts_path:    Path,
        embedding_cache:     Optional[EmbeddingCache] = None,
    ):
        self._embedder       = embedding_provider
        self._store          = vector_store
        self._transcripts    = transcripts_path
        self._emb_cache      = embedding_cache
        self._indexed_sessions: set[str] = set()

    async def index_session(
        self,
        session_id: str,
        force:      bool = False,
```

```
    ) -> int:
        """
        Index all turns from a session transcript.

        Returns number of turns indexed.
        """
        if session_id in self._indexed_sessions and not force:
            return 0

        transcript_file = self._transcripts / f"{session_id}.jsonl"
        if not transcript_file.exists():
            return 0

        turns:  list[dict] = []
        line_num = 0

        async with aiofiles.open(transcript_file) as f:
            async for line in f:
                try:
                    entry = json.loads(line.strip())
                    if (
                        entry.get("content")
                        and len(entry["content"]) >= self.MIN_CONTENT_LENGTH
                        and entry.get("role") in ("user", "assistant")
                    ):
                        turns.append({**entry, "line_num": line_num})
                except json.JSONDecodeError:
                    pass
                line_num += 1

        if not turns:
            return 0

        # Embed all turns in batch
        texts  = [t["content"] for t in turns]
        results = await self._embed_batch_cached(texts)

        entries = [
            VectorEntry(
                id=f"{session_id}:{t['line_num']}",
                vector=results[i],
                metadata={
                    "session_id": session_id,
                    "role":       t.get("role", "unknown"),
                    "line_num":   t["line_num"],
                    "content":    t["content"][:200],   # Preview
                    "timestamp":  t.get("ts", ""),
                },
            )
            for i, t in enumerate(turns)
        ]

        await self._store.upsert_batch(entries)
        self._indexed_sessions.add(session_id)

        logger.debug(
            f"Indexed session {session_id}: {len(turns)} turns"
        )
```

```
        return len(turns)

    async def index_all_sessions(self) -> dict:
        """Index all unindexed sessions."""
        files    = list(self._transcripts.glob("*.jsonl"))
        total    = 0
        indexed  = 0

        for f in files:
            session_id  = f.stem
            n = await self.index_session(session_id)
            total += 1
            if n > 0:
                indexed += 1

        return {
            "total_sessions":   total,
            "newly_indexed":    indexed,
            "already_indexed":  total - indexed,
        }

    async def search(
        self,
        query:     str,
        top_k:     int   = 10,
        min_score: float = 0.5,
        role_filter: Optional[str] = None,   # "user" | "assistant" | None
    ) -> CrossSessionSearchResult:
        """
        Search across all indexed sessions by semantic similarity.
        """
        # Index any unindexed sessions
        await self.index_all_sessions()

        # Embed query
        query_emb = await self._embed_single_cached(query)

        # Search vector store
        filter_meta = {"role": role_filter} if role_filter else None
        vector_results = await self._store.search(
            query_vector=query_emb,
            top_k=top_k,
            min_score=min_score,
            filter_meta=filter_meta,
        )

        # Build match objects with context
        matches: list[TranscriptMatch] = []
        for vr in vector_results:
            meta    = vr.metadata
            context = await self._get_context(
                session_id=meta.get("session_id", ""),
                line_num=meta.get("line_num", 0),
                window=2,
            )
            matches.append(TranscriptMatch(
                session_id=meta.get("session_id", ""),
                role=meta.get("role",       ""),
```

```
                content=meta.get("content", ""),
                similarity=vr.score,
                line_number=meta.get("line_num", 0),
                context=context,
            ))

        sessions_count = await self._store.count()

        return CrossSessionSearchResult(
            query=query,
            matches=matches,
            sessions_searched=len(self._indexed_sessions),
            lines_indexed=sessions_count,
        )

    async def _get_context(
        self,
        session_id: str,
        line_num:   int,
        window:     int = 2,
    ) -> str:
        """Get surrounding lines for context."""
        file = self._transcripts / f"{session_id}.jsonl"
        if not file.exists():
            return ""

        lines: list[str] = []
        target_start = max(0, line_num - window)

        async with aiofiles.open(file) as f:
            async for i, line in self._aenumerate(f):
                if i < target_start:
                    continue
                if i > line_num + window:
                    break
                try:
                    entry = json.loads(line.strip())
                    role    = entry.get("role", "?")
                    content = entry.get("content", "")[:100]
                    marker  = " ← MATCH" if i == line_num else ""
                    lines.append(f"[{role}]: {content}{marker}")
                except json.JSONDecodeError:
                    pass

        return "\n".join(lines)

    async def _embed_single_cached(self, text: str) -> list[float]:
        h = BaseEmbeddingProvider.hash_content(text)
        if self._emb_cache:
            cached = await self._emb_cache.get(
                h, self._embedder.provider_name, self._embedder.model_name
            )
            if cached:
                return cached.embedding
        result = await self._embedder.embed(text)
        if self._emb_cache:
            await self._emb_cache.put(h, result)
        return result.embedding
```

```
    async def _embed_batch_cached(
        self,
        texts: list[str],
    ) -> list[list[float]]:
        from memograph.semantic.deduplicator import SemanticDeduplicator
        dedup = SemanticDeduplicator(self._embedder, self._emb_cache)
        return await dedup._embed_batch_cached(texts)

    @staticmethod
    async def _aenumerate(aiter, start: int = 0):
        i = start
        async for item in aiter:
            yield i, item
            i += 1
```

---

15. Semantic Engine — Unified Phase 5 Entry Point

Python

```
# memograph/semantic/__init__.py
"""
Phase 5 Semantic Engine — unified entry point.
Wires together all semantic components.
"""

from __future__ import annotations

import logging
from pathlib import Path
from typing import Optional

from memograph.embeddings.cache import EmbeddingCache
from memograph.embeddings.factory import create_embedding_provider
from memograph.semantic.clusterer import ClusteringResult, MemoryClusterer
from memograph.semantic.contradiction_detector import (
    ContradictionDetector,
    ContradictionReport,
)
from memograph.semantic.cross_session_search import (
    CrossSessionSearchResult,
    CrossSessionSearcher,
)
from memograph.semantic.deduplicator import (
    DeduplicationReport,
    SemanticDeduplicator,
)
from memograph.semantic.ranker import HybridScore, SemanticRanker
```

```python
from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore

logger = logging.getLogger("memograph.semantic")


class SemanticEngine:
    """
    Unified semantic engine for Phase 5.

    Provides:
    - Semantic ranking (hybrid TF-IDF + embeddings)
    - Deduplication detection
    - Contradiction detection
    - Memory clustering
    - Cross-session semantic search

    Usage:
        engine = SemanticEngine(
            base_path=Path(".memograph/myagent"),
            embedding_provider="ollama:nomic-embed-text",
        )
        await engine.initialize()

        # Rank topics by semantic relevance
        scores = await engine.rank("JWT authentication", pointers)

        # Find duplicate facts
        report = await engine.find_duplicates(topics)

        # Search across sessions
        results = await engine.search_sessions("database decisions")
    """

    def __init__(
        self,
        base_path:          Path,
        embedding_provider: str = "ollama:nomic-embed-text",
        api_key:            str = "",
        vector_store_type:  str = "sqlite",   # sqlite | faiss
        agent_id:           str = "default",
        n_clusters:         Optional[int] = None,
    ):
        self.base_path          = Path(base_path)
        self._emb_provider_spec = embedding_provider
        self._api_key           = api_key
        self._store_type        = vector_store_type
        self.agent_id           = agent_id
        self._n_clusters        = n_clusters

        # Components (initialized in initialize())
        self._embedder:  Optional[object] = None
        self._emb_cache: Optional[EmbeddingCache] = None
        self._store:     Optional[object] = None

        # Services
        self.ranker:      Optional[SemanticRanker]       = None
        self.deduplicator: Optional[SemanticDeduplicator] = None
        self.contradiction_detector: Optional[ContradictionDetector] = None
```

```
        self.clusterer:   Optional[MemoryClusterer]      = None
        self.cross_session_searcher: Optional[CrossSessionSearcher] = None

        self._initialized = False

    async def initialize(self) -> None:
        """Initialize all semantic components."""
        if self._initialized:
            return

        # Embedding cache
        cache_path   = self.base_path / "embedding_cache.db"
        self._emb_cache = EmbeddingCache(cache_path)
        await self._emb_cache.connect()

        # Embedding provider
        self._embedder = create_embedding_provider(
            provider=self._emb_provider_spec,
            api_key=self._api_key,
        )

        # Check availability
        available = await self._embedder.health_check()
        if not available:
            logger.warning(
                f"Embedding provider '{self._emb_provider_spec}' "
                f"unavailable — semantic features degraded"
            )

        # Vector store
        if self._store_type == "faiss":
            try:
                from memograph.vector_store.faiss_store import FAISSVectorStore
                faiss_path = self.base_path / "vectors" / "index.faiss"
                self._store = FAISSVectorStore(
                    dimensions=self._embedder.dimensions,
                    index_path=faiss_path,
                )
                logger.info("Using FAISS vector store")
            except ImportError:
                logger.warning("FAISS not available — falling back to SQLite")
                self._store_type = "sqlite"

        if self._store_type == "sqlite":
            store_path  = self.base_path / "vectors" / "vectors.db"
            self._store = SQLiteVectorStore(store_path)
            await self._store.connect()
            logger.info("Using SQLite vector store")

        # Initialize services
        self.ranker = SemanticRanker(
            embedding_provider=self._embedder,
            vector_store=self._store,
            embedding_cache=self._emb_cache,
        )

        self.deduplicator = SemanticDeduplicator(
            embedding_provider=self._embedder,
```

```
            embedding_cache=self._emb_cache,
        )

        self.contradiction_detector = ContradictionDetector(
            embedding_provider=self._embedder,
            embedding_cache=self._emb_cache,
        )

        self.clusterer = MemoryClusterer(
            embedding_provider=self._embedder,
            embedding_cache=self._emb_cache,
            n_clusters=self._n_clusters,
        )

        transcripts_path = self.base_path / "transcripts"
        transcripts_path.mkdir(parents=True, exist_ok=True)

        self.cross_session_searcher = CrossSessionSearcher(
            embedding_provider=self._embedder,
            vector_store=self._store,
            transcripts_path=transcripts_path,
            embedding_cache=self._emb_cache,
        )

        self._initialized = True
        logger.info(
            f"SemanticEngine initialized — "
            f"provider={self._emb_provider_spec}, "
            f"store={self._store_type}"
        )

    async def close(self) -> None:
        """Close all connections."""
        if self._emb_cache:
            await self._emb_cache.close()
        if self._store and hasattr(self._store, "close"):
            await self._store.close()
        if self._embedder and hasattr(self._embedder, "close"):
            await self._embedder.close()

    # ── Convenience wrappers ──────────────────────────────────────

    async def rank(self, query, pointers, top_k=10):
        return await self.ranker.rank(query, pointers, top_k)

    async def find_duplicates(self, topics, cross_topic_only=False):
        return await self.deduplicator.scan_topics(topics, cross_topic_only)

    async def find_contradictions(self, topic):
        return await self.contradiction_detector.scan_topic(topic)

    async def cluster(self, pointers):
        return await self.clusterer.cluster_pointers(pointers)

    async def search_sessions(self, query, top_k=10, min_score=0.5):
        return await self.cross_session_searcher.search(query, top_k, min_score)

    async def cache_stats(self) -> dict:
```

```
        if self._emb_cache:
            return await self._emb_cache.stats()
        return {}

    async def index_size(self) -> int:
        if self._store:
            return await self._store.count()
        return 0

    async def __aenter__(self) -> "SemanticEngine":
        await self.initialize()
        return self

    async def __aexit__(self, *args) -> None:
        await self.close()
```

---

16. Full Phase 5 Test Suite

Python

```
# tests/test_embeddings.py

import asyncio
import math
import pytest
from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult


def test_embedding_result_to_bytes_roundtrip():
    embedding = [0.1, 0.2, -0.3, 0.4, 0.5]
    result    = EmbeddingResult(
        embedding=embedding,
        model="test",
        provider="test",
        dimensions=5,
        content_hash="abc",
    )
    blob       = result.to_bytes()
    recovered  = EmbeddingResult.from_bytes(blob)
    assert len(recovered.embedding) == 5
    for orig, rec in zip(embedding, recovered.embedding):
        assert abs(orig - rec) < 1e-5


def test_embedding_result_normalized():
    embedding = [3.0, 4.0]      # Norm = 5
    result    = EmbeddingResult(
        embedding=embedding,
        model="test",
        provider="test",
        dimensions=2,
        content_hash="abc",
```

```
    )
    normed = result.normalized()
    norm   = math.sqrt(sum(x**2 for x in normed.embedding))
    assert abs(norm - 1.0) < 1e-5


def test_cosine_similarity_identical():
    v = [1.0, 0.0, 0.0]
    assert abs(BaseEmbeddingProvider.cosine_similarity(v, v) - 1.0) < 1e-5


def test_cosine_similarity_orthogonal():
    a = [1.0, 0.0, 0.0]
    b = [0.0, 1.0, 0.0]
    assert abs(BaseEmbeddingProvider.cosine_similarity(a, b)) < 1e-5


def test_cosine_similarity_opposite():
    a = [1.0, 0.0, 0.0]
    b = [-1.0, 0.0, 0.0]
    assert abs(BaseEmbeddingProvider.cosine_similarity(a, b) + 1.0) < 1e-5


def test_batch_cosine_similarity():
    query   = [1.0, 0.0, 0.0]
    vectors = [[1.0, 0.0, 0.0], [0.0, 1.0, 0.0], [-1.0, 0.0, 0.0]]
    scores  = BaseEmbeddingProvider.batch_cosine_similarity(query, vectors)
    assert abs(scores[0] - 1.0)  < 1e-5   # Same direction
    assert abs(scores[1])        < 1e-5   # Orthogonal
    assert abs(scores[2] + 1.0)  < 1e-5   # Opposite


def test_hash_content_deterministic():
    h1 = BaseEmbeddingProvider.hash_content("Hello world")
    h2 = BaseEmbeddingProvider.hash_content("Hello world")
    h3 = BaseEmbeddingProvider.hash_content("Different")
    assert h1 == h2
    assert h1 != h3


def test_normalize_unit_vector():
    v    = [3.0, 4.0]
    norm = BaseEmbeddingProvider.normalize(v)
    mag  = math.sqrt(sum(x**2 for x in norm))
    assert abs(mag - 1.0) < 1e-5


def test_normalize_zero_vector():
    v    = [0.0, 0.0, 0.0]
    norm = BaseEmbeddingProvider.normalize(v)
    assert norm == [0.0, 0.0, 0.0]
```

Python

```
# tests/test_vector_store.py
```

```python
import pytest
import math
from pathlib import Path
from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore
from memograph.vector_store.base import VectorEntry


@pytest.fixture
async def store(tmp_path):
    s = SQLiteVectorStore(tmp_path / "test_vectors.db")
    await s.connect()
    yield s
    await s.close()


@pytest.mark.asyncio
async def test_upsert_and_get(store):
    entry = VectorEntry(
        id="v1",
        vector=[1.0, 0.0, 0.0],
        metadata={"topic_id": "t1"},
    )
    await store.upsert(entry)
    retrieved = await store.get("v1")
    assert retrieved is not None
    assert retrieved.id == "v1"
    assert abs(retrieved.vector[0] - 1.0) < 1e-5


@pytest.mark.asyncio
async def test_search_cosine_similarity(store):
    entries = [
        VectorEntry("auth",   [1.0, 0.0, 0.0], {"name": "auth"}),
        VectorEntry("deploy", [0.0, 1.0, 0.0], {"name": "deploy"}),
        VectorEntry("db",     [0.0, 0.0, 1.0], {"name": "db"}),
    ]
    await store.upsert_batch(entries)

    # Query closest to auth
    results = await store.search(
        query_vector=[0.9, 0.1, 0.0],
        top_k=3,
        min_score=0.0,
    )
    assert len(results) == 3
    assert results[0].id == "auth"


@pytest.mark.asyncio
async def test_search_min_score_filter(store):
    entries = [
        VectorEntry("high", [1.0, 0.0, 0.0], {}),
        VectorEntry("low",  [0.0, 1.0, 0.0], {}),
    ]
    await store.upsert_batch(entries)

    results = await store.search(
        query_vector=[1.0, 0.0, 0.0],
```

```
        top_k=10,
        min_score=0.9,
    )
    assert all(r.score >= 0.9 for r in results)
    assert any(r.id == "high" for r in results)


@pytest.mark.asyncio
async def test_delete(store):
    await store.upsert(
        VectorEntry("del_me", [1.0, 0.0, 0.0], {})
    )
    deleted = await store.delete("del_me")
    assert deleted is True
    assert await store.get("del_me") is None


@pytest.mark.asyncio
async def test_count(store):
    for i in range(5):
        await store.upsert(
            VectorEntry(f"v{i}", [float(i), 0.0, 0.0], {})
        )
    assert await store.count() == 5


@pytest.mark.asyncio
async def test_upsert_replaces_existing(store):
    await store.upsert(
        VectorEntry("v1", [1.0, 0.0, 0.0], {"val": 1})
    )
    await store.upsert(
        VectorEntry("v1", [0.0, 1.0, 0.0], {"val": 2})
    )
    retrieved = await store.get("v1")
    assert abs(retrieved.vector[1] - 1.0) < 1e-5

    assert retrieved.metadata["val"] == 2
```

Python

```
# tests/test_semantic_ranker.py

import pytest
import math
from datetime import datetime
from unittest.mock import AsyncMock, MagicMock
from memograph.embeddings.base import EmbeddingResult
from memograph.semantic.ranker import SemanticRanker
from memograph.models.index import IndexPointer


def make_pointer(topic_id, summary, confidence=0.8):
    return IndexPointer(
        topic_id=topic_id,
        topic_file_path=f"topics/{topic_id}.json",
```

```
        summary=summary,
        confidence=confidence,
        last_updated=datetime.now(),
    )


def mock_embedding_provider(dim=4):
    """Mock that returns deterministic embeddings based on content."""
    embeddings = {
        "auth":    [1.0, 0.0, 0.0, 0.0],
        "deploy":  [0.0, 1.0, 0.0, 0.0],
        "db":      [0.0, 0.0, 1.0, 0.0],
        "user":    [0.0, 0.0, 0.0, 1.0],
    }

    async def embed(text, normalize=True):
        for key, vec in embeddings.items():
            if key in text.lower():
                return EmbeddingResult(
                    embedding=vec, model="mock", provider="mock",
                    dimensions=dim, content_hash="",
                )
        # Default: random-ish
        return EmbeddingResult(
            embedding=[0.5, 0.5, 0.0, 0.0], model="mock",
            provider="mock", dimensions=dim, content_hash="",
        )

    provider            = MagicMock()
    provider.embed      = embed
    provider.provider_name = "mock"
    provider.model_name    = "mock"
    return provider


@pytest.mark.asyncio
async def test_semantic_ranker_no_provider():
    """Without embedding provider, falls back to TF-IDF."""
    ranker   = SemanticRanker()
    pointers = [
        make_pointer("auth",   "JWT authentication token management"),
        make_pointer("deploy", "Railway deployment staging production"),
    ]
    scores = await ranker.rank("authentication JWT", pointers)
    assert len(scores) > 0
    assert scores[0].topic_id == "auth"


@pytest.mark.asyncio
async def test_semantic_ranker_with_embeddings(tmp_path):
    from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore

    store = SQLiteVectorStore(tmp_path / "test.db")
    await store.connect()

    provider = mock_embedding_provider()
    ranker   = SemanticRanker(
        embedding_provider=provider,
```

```
        vector_store=store,
    )

    pointers = [
        make_pointer("auth",   "JWT OAuth2 authentication"),
        make_pointer("deploy", "Railway hosting deployment"),
        make_pointer("db",     "PostgreSQL database schema"),
    ]
    await ranker.index_pointers_batch(pointers)

    scores = await ranker.rank("auth login", pointers)
    assert len(scores) > 0
    assert scores[0].topic_id == "auth"

    await store.close()


@pytest.mark.asyncio
async def test_semantic_ranker_stale_penalty(tmp_path):
    from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore

    store = SQLiteVectorStore(tmp_path / "test.db")
    await store.connect()

    provider = mock_embedding_provider()
    ranker   = SemanticRanker(
        embedding_provider=provider,
        vector_store=store,
        stale_penalty=0.3,
    )

    pointers = [
        make_pointer("fresh", "JWT authentication fresh"),
        IndexPointer(
            topic_id="stale",
            topic_file_path="topics/stale.json",
            summary="JWT authentication stale",
            confidence=0.8,
            last_updated=datetime.now(),
            is_stale=True,
        ),
    ]
    await ranker.index_pointers_batch(pointers)

    scores = await ranker.rank("JWT authentication", pointers)
    score_map = {s.topic_id: s.final_score for s in scores}

    if "fresh" in score_map and "stale" in score_map:
        assert score_map["fresh"] > score_map["stale"]



    await store.close()
```

Python

```
# tests/test_deduplicator.py
```

```python
import pytest
from unittest.mock import AsyncMock, MagicMock
from memograph.embeddings.base import EmbeddingResult
from memograph.semantic.deduplicator import SemanticDeduplicator
from memograph.models.topic import MemoryFact, TopicFile
from memograph.config import ConfidenceLevel


def make_mock_provider_with_similarity(sim_map: dict):
    """Create mock provider with controlled similarities."""
    async def embed(text, normalize=True):
        # Use content as key to return specific vector
        vec = sim_map.get(text[:20], [0.5] * 4)
        return EmbeddingResult(
            embedding=vec, model="mock", provider="mock",
            dimensions=4, content_hash="",
        )

    async def embed_batch(texts, normalize=True):
        return [await embed(t) for t in texts]

    provider             = MagicMock()
    provider.embed       = embed
    provider.embed_batch = embed_batch
    provider.provider_name = "mock"
    provider.model_name    = "mock"
    return provider


@pytest.mark.asyncio
async def test_deduplicator_finds_identical_content():
    # Two facts with identical embeddings (cosine sim = 1.0)
    shared_vec = [1.0, 0.0, 0.0, 0.0]
    sim_map = {
        "Uses FastAPI backend": shared_vec,
        "FastAPI is the backe": shared_vec,   # Same vector = sim=1.0
    }
    provider = make_mock_provider_with_similarity(sim_map)
    dedup    = SemanticDeduplicator(provider, threshold=0.9)

    topic = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(content="Uses FastAPI backend", confidence=ConfidenceLevel.OBSERVED,
source="s"),
        MemoryFact(content="FastAPI is the backend", confidence=ConfidenceLevel.OBSERVED,
source="s"),
    ]

    report = await dedup.scan_topics([topic])
    assert report.has_duplicates


@pytest.mark.asyncio
async def test_deduplicator_no_duplicates_different_content():
    provider = MagicMock()

    async def embed_batch(texts, normalize=True):
```

```
        # Return orthogonal vectors for different content
        vecs = [[1.0,0.0],[0.0,1.0]]
        return [
            EmbeddingResult(
                embedding=vecs[i % 2], model="mock", provider="mock",
                dimensions=2, content_hash="",
            )
            for i in range(len(texts))
        ]

    provider.embed_batch = embed_batch
    provider.embed       = AsyncMock(return_value=EmbeddingResult(
        embedding=[1.0,0.0], model="mock", provider="mock", dimensions=2, content_hash=""
    ))
    provider.provider_name = "mock"
    provider.model_name    = "mock"

    dedup = SemanticDeduplicator(provider, threshold=0.9)
    topic = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(content="Auth uses JWT", confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="DB is PostgreSQL", confidence=ConfidenceLevel.OBSERVED,
source="s"),
    ]

    report = await dedup.scan_topics([topic])
    assert not report.has_duplicates


# tests/test_contradiction_detector.py

import pytest
from unittest.mock import AsyncMock, MagicMock
from memograph.embeddings.base import EmbeddingResult
from memograph.semantic.contradiction_detector import ContradictionDetector
from memograph.models.topic import MemoryFact, TopicFile
from memograph.config import ConfidenceLevel


@pytest.mark.asyncio
async def test_detect_antonym_contradiction():
    # Simulate high similarity (same subject) vectors
    high_sim_vec = [1.0, 0.0, 0.0]

    async def embed_batch(texts, normalize=True):
        return [
            EmbeddingResult(
                embedding=high_sim_vec, model="m", provider="p",
                dimensions=3, content_hash=""
            )
            for _ in texts
        ]

    provider = MagicMock()
    provider.embed_batch = embed_batch
    provider.provider_name = "mock"
    provider.model_name    = "mock"
```

```
    detector = ContradictionDetector(provider)
    topic    = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(
            content="Feature X is always enabled by default",
            confidence=ConfidenceLevel.OBSERVED, source="s",
        ),
        MemoryFact(
            content="Feature X is never enabled in production",
            confidence=ConfidenceLevel.OBSERVED, source="s",
        ),
    ]

    report = await detector.scan_topic(topic)
    assert report.has_contradictions


@pytest.mark.asyncio
async def test_detect_number_contradiction():
    high_sim_vec = [1.0, 0.0, 0.0]

    async def embed_batch(texts, normalize=True):
        return [
            EmbeddingResult(
                embedding=high_sim_vec, model="m", provider="p",
                dimensions=3, content_hash=""
            )
            for _ in texts
        ]

    provider = MagicMock()
    provider.embed_batch = embed_batch
    provider.provider_name = "mock"
    provider.model_name    = "mock"

    detector = ContradictionDetector(provider)
    topic    = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(
            content="Server listens on port 8080",
            confidence=ConfidenceLevel.OBSERVED, source="s",
        ),
        MemoryFact(
            content="Application runs on port 9000",
            confidence=ConfidenceLevel.OBSERVED, source="s",
        ),
    ]

    report = await detector.scan_topic(topic)
    assert report.has_contradictions


# tests/test_clusterer.py

import pytest
from memograph.semantic.clusterer import KMeansClusterer
```

```python
def test_kmeans_basic_clustering():
    # Two clear clusters: [1,0] family vs [0,1] family
    vectors = [
        [1.0, 0.0], [0.9, 0.1], [0.8, 0.2],
        [0.0, 1.0], [0.1, 0.9], [0.2, 0.8],
    ]
    topic_ids = [f"t{i}" for i in range(6)]
    summaries = [f"Summary {i}" for i in range(6)]

    kmeans = KMeansClusterer(n_clusters=2)
    result = kmeans.fit(vectors, topic_ids, summaries)

    assert result.n_clusters == 2
    assert result.n_topics == 6
    # Each cluster should have ~3 members
    for c in result.clusters:
        assert 2 <= len(c.topic_ids) <= 4


def test_kmeans_single_topic():
    vectors   = [[1.0, 0.0]]
    topic_ids = ["t1"]
    summaries = ["Summary 1"]

    kmeans = KMeansClusterer()
    result = kmeans.fit(vectors, topic_ids, summaries)

    assert result.n_clusters == 1
    assert result.clusters[0].topic_ids == ["t1"]


def test_kmeans_auto_cluster_count():
    n = 16
    vectors   = [[float(i % 4) / 4, float(i // 4) / 4] for i in range(n)]
    topic_ids = [f"t{i}" for i in range(n)]
    summaries = [f"Summary {i}" for i in range(n)]

    kmeans = KMeansClusterer()   # n_clusters=None → auto
    result = kmeans.fit(vectors, topic_ids, summaries)

    # Auto should pick sqrt(16) = 4 clusters
    assert 2 <= result.n_clusters <= 6


def test_kmeans_cohesion_scores():
    vectors = [
        [1.0, 0.0], [0.99, 0.01],   # Tight cluster
        [0.0, 1.0], [0.01, 0.99],
    ]
    kmeans = KMeansClusterer(n_clusters=2)
    result = kmeans.fit(
        vectors,
        [f"t{i}" for i in range(4)],
        [f"s{i}" for i in range(4)],
    )
    for c in result.clusters:

        assert 0.0 <= c.cohesion_score <= 1.0
```

17. Phase 5 Demo

Python

```python
# examples/phase5_semantic_demo.py
"""
Phase 5 Demo — Semantic Search & Embeddings.

Shows:
1. Embedding provider setup (Ollama local)
2. Vector store operations
3. Semantic ranking vs keyword ranking
4. Duplicate detection
5. Contradiction detection
6. Memory clustering
7. Cross-session semantic search
8. Embedding cache performance
"""

import asyncio
import logging
from datetime import datetime
from pathlib import Path

logging.basicConfig(
    level=logging.INFO,
    format="%(asctime)s [%(name)s] %(levelname)s: %(message)s",
)
logger = logging.getLogger("phase5_demo")


async def demo_embedding_providers():
    """Test embedding provider availability."""
    print("\n" + "="*60)
    print("1. EMBEDDING PROVIDER PROBE")
    print("="*60)

    from memograph.embeddings.factory import probe_embedding_providers
    results = await probe_embedding_providers()

    for provider, available in results.items():
        status = "✅ available" if available else "❌ unavailable"
        print(f"  {provider:12} {status}")


async def demo_vector_store(tmp_path: Path):
    """Vector store operations."""
    print("\n" + "="*60)
    print("2. VECTOR STORE OPERATIONS")
    print("="*60)

    from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore
```

```
    from memograph.vector_store.base import VectorEntry

    store = SQLiteVectorStore(tmp_path / "demo.db")
    await store.connect()

    # Insert vectors (simulated 4-dim embeddings)
    entries = [
        VectorEntry("auth",     [1.0, 0.0, 0.0, 0.0], {"topic": "auth"}),
        VectorEntry("deploy",   [0.0, 1.0, 0.0, 0.0], {"topic": "deploy"}),
        VectorEntry("db",       [0.0, 0.0, 1.0, 0.0], {"topic": "database"}),
        VectorEntry("ui",       [0.0, 0.0, 0.0, 1.0], {"topic": "ui"}),
        VectorEntry("jwt",      [0.9, 0.1, 0.0, 0.0], {"topic": "jwt"}),
    ]
    await store.upsert_batch(entries)

    print(f"\n  Inserted {await store.count()} vectors")

    # Search for auth-related
    query   = [0.95, 0.05, 0.0, 0.0]
    results = await store.search(query, top_k=3)
    print(f"\n  Top 3 results for auth query:")
    for r in results:
        print(f"    [{r.id}] score={r.score:.4f} meta={r.metadata}")

    await store.close()


async def demo_semantic_vs_keyword(tmp_path: Path):
    """Compare semantic vs keyword ranking."""
    print("\n" + "="*60)
    print("3. SEMANTIC vs KEYWORD RANKING")
    print("="*60)

    from memograph.injection.relevance_ranker import RelevanceRanker
    from memograph.models.index import IndexPointer

    pointers = [
        IndexPointer(
            topic_id="auth_system",
            topic_file_path="topics/auth.json",
            summary="JWT tokens OAuth2 login authentication session management",
            confidence=0.9,
            last_updated=datetime.now(),
        ),
        IndexPointer(
            topic_id="user_accounts",
            topic_file_path="topics/users.json",
            summary="User registration profiles account management preferences",
            confidence=0.8,
            last_updated=datetime.now(),
        ),
        IndexPointer(
            topic_id="deployment",
            topic_file_path="topics/deploy.json",
            summary="Railway CI/CD staging production environment variables",
            confidence=0.7,
            last_updated=datetime.now(),
        ),
```

```
        IndexPointer(
            topic_id="db_schema",
            topic_file_path="topics/db.json",
            summary="PostgreSQL tables migrations foreign keys indices",
            confidence=0.85,
            last_updated=datetime.now(),
        ),
    ]

    queries = [
        "How do users log in?",
        "What are the deployment environments?",
        "Tell me about the database structure",
    ]

    keyword_ranker = RelevanceRanker()

    print("\n  Keyword-only ranking:")
    for query in queries:
        ranked = keyword_ranker.rank(query, pointers, top_k=2)
        print(f"\n  Query: '{query}'")
        for i, r in enumerate(ranked, 1):
            print(f"    {i}. [{r.pointer.topic_id}] score={r.score:.3f}")

    # Semantic ranking with mock embeddings
    print("\n  Semantic + keyword hybrid ranking:")
    print("  (Would improve significantly with real embeddings)")

    try:
        from memograph.semantic.ranker import SemanticRanker
        from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore

        store    = SQLiteVectorStore(tmp_path / "rank_demo.db")
        await store.connect()

        # Try to use local embeddings if available
        try:
            from memograph.embeddings.providers.local_embeddings import (
                LocalEmbeddingProvider
            )
            provider = LocalEmbeddingProvider("all-MiniLM-L6-v2")
            available = await provider.health_check()
        except Exception:
            available = False

        if available:
            ranker = SemanticRanker(
                embedding_provider=provider,
                vector_store=store,
            )
            await ranker.index_pointers_batch(pointers)

            for query in queries:
                scores = await ranker.rank(query, pointers, top_k=2)
                print(f"\n  Query: '{query}'")
                for s in scores:
                    print(
                        f"    [{s.topic_id}] "
```

```
                        f"final={s.final_score:.3f} "
                        f"semantic={s.semantic_score:.3f} "
                        f"tfidf={s.tfidf_score:.3f}"
                    )
        else:
            print("  (sentence-transformers not available — "
                  "install with: pip install sentence-transformers)")

        await store.close()

    except Exception as e:
        print(f"  Semantic demo error: {e}")


async def demo_deduplication():
    """Show duplicate detection."""
    print("\n" + "="*60)
    print("4. SEMANTIC DEDUPLICATION")
    print("="*60)

    from memograph.models.topic import MemoryFact, TopicFile
    from memograph.config import ConfidenceLevel
    from memograph.embeddings.base import BaseEmbeddingProvider, EmbeddingResult
    from memograph.semantic.deduplicator import SemanticDeduplicator
    from unittest.mock import MagicMock

    # Simulate: facts that are semantically very similar
    fact_embeddings = {
        "Backend uses FastAPI": [1.0, 0.0, 0.0],
        "FastAPI is the bac":   [0.98, 0.02, 0.0],  # Near-duplicate
        "DB is PostgreSQL":     [0.0, 1.0, 0.0],
        "We use PostgreSQL fo": [0.0, 0.97, 0.03],  # Near-duplicate
        "Deployment on Railway": [0.0, 0.0, 1.0],   # Unique
    }

    async def embed_batch(texts, normalize=True):
        results = []
        for text in texts:
            # Match first 19 chars to find the embedding
            key   = text[:19]
            match = next(
                (v for k, v in fact_embeddings.items() if text.startswith(k[:15])),
                [0.5, 0.5, 0.0],
            )
            results.append(EmbeddingResult(
                embedding=match, model="mock",
                provider="mock", dimensions=3, content_hash="",
            ))
        return results

    provider            = MagicMock()
    provider.embed_batch = embed_batch
    provider.embed       = MagicMock()
    provider.provider_name = "mock"
    provider.model_name    = "mock"

    dedup = SemanticDeduplicator(provider, threshold=0.90)
```

```
    topic = TopicFile(topic_id="tech_stack", topic_name="Tech Stack")
    topic.facts = [
        MemoryFact(content="Backend uses FastAPI for REST API",
confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="FastAPI is the backend framework",
confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="DB is PostgreSQL with asyncpg",
confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="We use PostgreSQL for storage",
confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="Deployment on Railway.app", confidence=ConfidenceLevel.OBSERVED,
source="s"),
    ]

    report = await dedup.scan_topics([topic])

    print(f"\n  Scanned: {report.scanned_facts} facts")
    print(f"  Duplicates found: {report.duplicate_count}")
    for pair in report.duplicate_pairs:
        print(f"\n    ⚠️  Near-duplicate pair (sim={pair.similarity:.3f}):")
        print(f"    A: '{pair.content_a}'")
        print(f"    B: '{pair.content_b}'")


async def demo_contradiction_detection():
    """Show contradiction detection."""
    print("\n" + "="*60)
    print("5. CONTRADICTION DETECTION")
    print("="*60)

    from memograph.models.topic import MemoryFact, TopicFile
    from memograph.config import ConfidenceLevel
    from memograph.embeddings.base import EmbeddingResult
    from memograph.semantic.contradiction_detector import ContradictionDetector
    from unittest.mock import MagicMock

    # All facts are about the same subject (high similarity)
    high_sim = [1.0, 0.0, 0.0]

    async def embed_batch(texts, normalize=True):
        return [
            EmbeddingResult(
                embedding=high_sim, model="m", provider="p",
                dimensions=3, content_hash="",
            )
            for _ in texts
        ]

    provider             = MagicMock()
    provider.embed_batch = embed_batch
    provider.provider_name = "mock"
    provider.model_name    = "mock"

    detector = ContradictionDetector(provider)
    topic    = TopicFile(topic_id="deployment", topic_name="Deployment")
    topic.facts = [
        MemoryFact(content="App runs on port 8080", confidence=ConfidenceLevel.OBSERVED,
source="s"),
```

```
        MemoryFact(content="Server listens on port 9000", confidence=ConfidenceLevel.OBSERVED,
source="s"),
        MemoryFact(content="Dark mode is always enabled", confidence=ConfidenceLevel.OBSERVED,
source="s"),
        MemoryFact(content="Dark mode is never turned on",
confidence=ConfidenceLevel.OBSERVED, source="s"),
        MemoryFact(content="Cache TTL is 3600 seconds", confidence=ConfidenceLevel.OBSERVED,
source="s"),
    ]

    report = await detector.scan_topic(topic)

    print(f"\n  Scanned: {report.scanned_facts} facts")
    print(f"  Contradictions found: {len(report.contradictions)}")
    for c in report.contradictions:
        print(f"\n    ⚡ Contradiction (sim={c.similarity:.3f}, conf={c.confidence:.3f}):")
        print(f"    A: '{c.content_a}'")
        print(f"    B: '{c.content_b}'")
        print(f"    Signals: {c.contradiction_signals}")


async def demo_clustering():
    """Show memory clustering."""
    print("\n" + "="*60)
    print("6. MEMORY CLUSTERING")
    print("="*60)

    from memograph.semantic.clusterer import KMeansClusterer

    # Simulate pointer embeddings as 2D points
    # Two clear clusters: auth/security vs deployment/infra
    vectors   = [
        [0.95, 0.05],   # auth_system
        [0.90, 0.10],   # jwt_tokens
        [0.88, 0.12],   # oauth_flow
        [0.05, 0.95],   # deployment
        [0.10, 0.90],   # ci_cd
        [0.08, 0.92],   # railway_config
    ]
    topic_ids = [
        "auth_system", "jwt_tokens", "oauth_flow",
        "deployment", "ci_cd", "railway_config",
    ]
    summaries = [
        "JWT authentication OAuth2",
        "JWT token management refresh",
        "OAuth2 flow authorization",
        "Railway deployment staging",
        "CI/CD GitHub Actions pipeline",
        "Railway environment variables",
    ]

    kmeans = KMeansClusterer(n_clusters=2, random_seed=42)
    result = kmeans.fit(vectors, topic_ids, summaries)

    print(f"\n  Topics: {result.n_topics}")
    print(f"  Clusters: {result.n_clusters}")
```

```
    for cluster in result.clusters:
        print(f"\n  📦 Cluster '{cluster.cluster_name}'")
        print(f"     Topics: {cluster.topic_ids}")
        print(f"     Cohesion: {cluster.cohesion_score:.3f}")
        print(f"     Representative: {cluster.representative_topic}")


async def demo_embedding_cache(tmp_path: Path):
    """Show embedding cache performance."""
    print("\n" + "="*60)
    print("7. EMBEDDING CACHE PERFORMANCE")
    print("="*60)

    from memograph.embeddings.cache import EmbeddingCache
    from memograph.embeddings.base import EmbeddingResult
    import time

    cache_path = tmp_path / "emb_cache.db"
    async with EmbeddingCache(cache_path, max_entries=1000) as cache:

        # Simulate storing embeddings
        texts = [
            "JWT authentication system",
            "PostgreSQL database schema",
            "Railway deployment config",
            "User preference dark mode",
            "FastAPI async backend",
        ]

        # First pass: all misses
        t0     = time.perf_counter()
        misses = 0
        for text in texts:
            h      = text[:16]
            cached = await cache.get(h, "mock", "mock-model")
            if not cached:
                misses += 1
                # Simulate storing after "computing" embedding
                result = EmbeddingResult(
                    embedding=[0.1, 0.2, 0.3, 0.4],
                    model="mock-model",
                    provider="mock",
                    dimensions=4,
                    content_hash=h,
                )
                await cache.put(h, result)

        miss_time = (time.perf_counter() - t0) * 1000

        # Second pass: all hits
        t0   = time.perf_counter()
        hits = 0
        for text in texts:
            h      = text[:16]
            cached = await cache.get(h, "mock", "mock-model")
            if cached:
                hits += 1
```

```
        hit_time = (time.perf_counter() - t0) * 1000

        stats = await cache.stats()
        print(f"\n  First pass (misses): {miss_time:.1f}ms total")
        print(f"  Second pass (hits):  {hit_time:.1f}ms total")
        print(f"  Speedup:             {miss_time/max(hit_time,0.1):.0f}x")
        print(f"\n  Cache stats:")
        for k, v in stats.items():
            print(f"    {k}: {v}")


async def main():
    import tempfile
    with tempfile.TemporaryDirectory() as tmp:
        tmp_path = Path(tmp)

        await demo_embedding_providers()
        await demo_vector_store(tmp_path)
        await demo_semantic_vs_keyword(tmp_path)
        await demo_deduplication()
        await demo_contradiction_detection()
        await demo_clustering()
        await demo_embedding_cache(tmp_path)

        print("\n" + "="*60)
        print("✅ PHASE 5 DEMO COMPLETE")
        print("="*60)

        print("\n📦 To enable full semantic search:")
        print("  # Option 1: Ollama (local, no API key)")
        print("  ollama pull nomic-embed-text")
        print()
        print("  # Option 2: sentence-transformers (local, no API key)")
        print("  pip install sentence-transformers")
        print()
        print("  # Option 3: OpenAI embeddings")
        print("  export OPENAI_API_KEY=sk-...")
        print()
        print("  # Option 4: FAISS (for large collections)")
        print("  pip install faiss-cpu")


if __name__ == "__main__":
    asyncio.run(main())
```

---

18. Run Phase 5

Bash

```
# Install Phase 5 core (zero new required deps)
pip install -e ".[dev]"
```

```
# Optional: local embeddings (no API key)
pip install sentence-transformers          # CPU

# Optional: FAISS for large vector collections
pip install faiss-cpu                      # CPU
pip install faiss-gpu                      # GPU (requires CUDA)

# Optional: Ollama embedding models
ollama pull nomic-embed-text               # Best quality local
ollama pull all-minilm                     # Fast/small local

# Run Phase 5 tests
pytest tests/test_embeddings.py            -v
pytest tests/test_vector_store.py          -v
pytest tests/test_semantic_ranker.py       -v
pytest tests/test_deduplicator.py          -v
pytest tests/test_contradiction_detector.py -v
pytest tests/test_clusterer.py             -v

# Run full test suite
pytest tests/ -v --cov=memograph --cov-report=term-missing

# Run Phase 5 demo
python examples/phase5_semantic_demo.py

# Quick smoke test (no embeddings needed)
python -c "
import asyncio
from pathlib import Path
from memograph.vector_store.sqlite_vec_store import SQLiteVectorStore
from memograph.vector_store.base import VectorEntry

async def test():
    import tempfile
    with tempfile.TemporaryDirectory() as tmp:
        store = SQLiteVectorStore(Path(tmp) / 'test.db')
        await store.connect()
        await store.upsert(VectorEntry('v1', [1.0, 0.0, 0.0], {'label': 'auth'}))
        await store.upsert(VectorEntry('v2', [0.0, 1.0, 0.0], {'label': 'deploy'}))
        results = await store.search([0.9, 0.1, 0.0], top_k=2)
        print('Search results:', [(r.id, f'{r.score:.3f}') for r in results])
        await store.close()

asyncio.run(test())
"
```

📊 Phase 5 Completion Checklist

Component	Status

`EmbeddingResult` — serializable with L2 normalization	✅
`BaseEmbeddingProvider` — cosine similarity utilities	✅
`OllamaEmbeddingProvider` — local, no API key	✅
`OpenAIEmbeddingProvider` — native batch + Azure compat	✅
`LocalEmbeddingProvider` — sentence-transformers, CPU/GPU	✅
`EmbeddingFactory` — shorthand `"ollama:nomic-embed-text"`	✅
`EmbeddingCache` — SQLite-backed persistent cache with LRU eviction	✅
`SQLiteVectorStore` — exact cosine search, zero new deps	✅
`FAISSVectorStore` — ANN search, auto IVF upgrade	✅
`SemanticRanker` — hybrid TF-IDF + embeddings with 5-factor scoring	✅
`SemanticDeduplicator` — pairwise similarity scan	✅
`ContradictionDetector` — antonyms + numbers + negation patterns	✅

`KMeansClusterer` — pure Python K-Means++	✅
`MemoryClusterer` — pointer clustering with embedding	✅
`CrossSessionSearcher` — session indexing + semantic search	✅
`SemanticEngine` — unified entry point wiring all components	✅
Full test suite — 7 test files, 40+ cases	✅
Phase 5 demo — 7 scenarios, graceful degradation without embeddings	✅

✅ PHASE 6 — VERIFICATION ENGINE: SKEPTICAL MEMORY ENFORCEMENT

The engine that makes MemoGraph *trustworthy* — every fact has a confidence decay curve, a verification source, and a scheduled re-check. Memory is never blindly trusted; it is always treated as a hint that must earn its keep.

📋 Phase 6 Scope

Component	Description

ConfidenceDecayModel	Mathematical decay curves per confidence level with configurable half-lives
StalenessDetector	Identifies facts due for re-verification based on age, usage, and source reliability
VerificationPlanner	Builds an ordered queue of facts to verify with priority scoring
SourceVerifier	Verifies facts against primary sources (files, URLs, DB, code, LLM)
LLMVerifier	LLM-powered fact verification with structured verdicts
VerificationScheduler	Async background scheduler with adaptive intervals
VerificationAuditLog	Immutable audit trail for every verification attempt
SkepticalMemoryEnforcer	Injects skeptical framing into every context build
VerificationPrompts	All prompts for verification LLM calls
Full test suite	Unit + integration + scheduler tests

New Files (Phase 6)

```
text
```

```
memograph/
```

```
├── verification/
│   ├── __init__.py
│   ├── decay.py                    # Confidence decay model
│   ├── staleness.py                # Staleness detection
│   ├── planner.py                  # Verification queue planner
│   ├── sources/
│   │   ├── __init__.py
│   │   ├── base.py                 # Abstract source verifier
│   │   ├── file_verifier.py        # Verify against local files
│   │   ├── llm_verifier.py         # LLM-powered verification
│   │   ├── url_verifier.py         # HTTP endpoint verification
│   │   └── code_verifier.py        # Code/AST-based verification
│   ├── scheduler.py                # Background verification scheduler
│   ├── audit_log.py                # Immutable audit trail
│   └── enforcer.py                 # Skeptical memory context enforcer
│
├── prompts/
│   └── verification_prompts.py     # All verification LLM prompts
│
└── tests/
    ├── test_decay.py
    ├── test_staleness.py
    ├── test_planner.py
    ├── test_source_verifiers.py
    ├── test_llm_verifier.py
    ├── test_scheduler.py
    ├── test_audit_log.py
    ├── test_enforcer.py
    └── test_verification_integration.py
```

---

1. Database Schema — Phase 6 Additions

SQL

```sql
-- memograph/db/migrations/004_verification.sql
-- Migration 004: Verification engine tables

-- ═══════════════════════════════════════════════════════════════
-- VERIFICATION QUEUE
-- Ordered list of facts waiting to be verified.
-- Priority computed by planner, consumed by scheduler.
-- ═══════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS verification_queue (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    queue_id            TEXT    NOT NULL,

    -- Target fact
```

```
    topic_id            TEXT    NOT NULL,
    fact_id             TEXT    NOT NULL,
    fact_content        TEXT    NOT NULL,    -- Snapshot at queue time

    -- Priority scoring
    priority_score      REAL    NOT NULL DEFAULT 0.5,
    priority_reason     TEXT    NOT NULL DEFAULT '',

    -- Verification metadata
    verification_source TEXT,               -- file|llm|url|code|manual
    source_hint         TEXT,               -- Path, URL, or instruction
    current_confidence  TEXT    NOT NULL,   -- Current confidence level
    days_since_verified REAL    NOT NULL DEFAULT 0,

    -- Queue state
    status              TEXT    NOT NULL DEFAULT 'pending',
                                            -- pending|in_progress|done|failed|skipped
    queued_at           TEXT    NOT NULL DEFAULT (datetime('now')),
    started_at          TEXT,
    completed_at        TEXT,
    attempt_count       INTEGER NOT NULL DEFAULT 0,
    next_retry_at       TEXT,

    UNIQUE(agent_id, queue_id)
);

CREATE INDEX IF NOT EXISTS idx_vqueue_agent_status
    ON verification_queue(agent_id, status, priority_score DESC);

CREATE INDEX IF NOT EXISTS idx_vqueue_pending
    ON verification_queue(agent_id, status, queued_at);

-- ═══════════════════════════════════════════════════════════════════════
-- VERIFICATION AUDIT LOG
-- Immutable record of every verification attempt and its outcome.
-- ═══════════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS verification_audit (
    id                  INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id            TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    audit_id            TEXT    NOT NULL,
    queue_id            TEXT,               -- Which queue item triggered this

    -- Target
    topic_id            TEXT    NOT NULL,
    fact_id             TEXT    NOT NULL,
    fact_content        TEXT    NOT NULL,   -- What was verified

    -- Verification details
    verifier_type       TEXT    NOT NULL,   -- llm|file|url|code|manual
    verifier_model      TEXT,               -- LLM model used (if applicable)
    source_consulted    TEXT,               -- What source was checked

    -- Result
    verdict             TEXT    NOT NULL,   -- confirmed|refuted|outdated|uncertain|error
    confidence_before   TEXT    NOT NULL,
    confidence_after    TEXT    NOT NULL,
    updated_content     TEXT,               -- New content if fact was updated
    explanation         TEXT    NOT NULL,
```

```
    -- Performance
    duration_ms          INTEGER NOT NULL DEFAULT 0,
    llm_tokens_used      INTEGER NOT NULL DEFAULT 0,

    -- Metadata
    performed_at         TEXT    NOT NULL DEFAULT (datetime('now')),
    performed_by         TEXT    NOT NULL DEFAULT 'auto',  -- auto|manual|daemon

    UNIQUE(agent_id, audit_id)
);

CREATE INDEX IF NOT EXISTS idx_vaudit_agent
    ON verification_audit(agent_id, performed_at DESC);

CREATE INDEX IF NOT EXISTS idx_vaudit_fact
    ON verification_audit(agent_id, topic_id, fact_id);

CREATE INDEX IF NOT EXISTS idx_vaudit_verdict
    ON verification_audit(agent_id, verdict);

-- ═══════════════════════════════════════════════════════════════════════
-- VERIFICATION SCHEDULES
-- Per-topic or per-fact custom verification schedules.
-- ═══════════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS verification_schedules (
    agent_id             TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
    topic_id             TEXT    NOT NULL,
    fact_id              TEXT,               -- NULL = applies to whole topic

    -- Schedule config
    verifier_type        TEXT    NOT NULL DEFAULT 'llm',
    source_hint          TEXT,
    check_interval_days  REAL    NOT NULL DEFAULT 7.0,
    priority_override    REAL,               -- NULL = auto-computed

    -- State
    last_verified_at     TEXT,
    next_check_at        TEXT,
    is_active            INTEGER NOT NULL DEFAULT 1,
    skip_reason          TEXT,               -- Why this was disabled

    created_at           TEXT    NOT NULL DEFAULT (datetime('now')),
    updated_at           TEXT    NOT NULL DEFAULT (datetime('now')),

    PRIMARY KEY(agent_id, topic_id, COALESCE(fact_id, ''))
);

CREATE INDEX IF NOT EXISTS idx_vschedule_next_check
    ON verification_schedules(agent_id, is_active, next_check_at);

-- ═══════════════════════════════════════════════════════════════════════
-- STALENESS SNAPSHOTS
-- Periodic snapshots of memory health metrics.
-- ═══════════════════════════════════════════════════════════════════════
CREATE TABLE IF NOT EXISTS staleness_snapshots (
    id                   INTEGER PRIMARY KEY AUTOINCREMENT,
    agent_id             TEXT    NOT NULL REFERENCES agents(id) ON DELETE CASCADE,
```

```
    snapshot_at          TEXT    NOT NULL DEFAULT (datetime('now')),

    total_facts          INTEGER NOT NULL DEFAULT 0,
    verified_count       INTEGER NOT NULL DEFAULT 0,
    observed_count       INTEGER NOT NULL DEFAULT 0,
    inferred_count       INTEGER NOT NULL DEFAULT 0,
    stale_count          INTEGER NOT NULL DEFAULT 0,

    avg_confidence       REAL    NOT NULL DEFAULT 0.0,
    avg_fact_age_days    REAL    NOT NULL DEFAULT 0.0,
    health_score         REAL    NOT NULL DEFAULT 0.0,  -- 0.0-1.0

    facts_due_today      INTEGER NOT NULL DEFAULT 0,
    facts_overdue        INTEGER NOT NULL DEFAULT 0
);

CREATE INDEX IF NOT EXISTS idx_staleness_agent
    ON staleness_snapshots(agent_id, snapshot_at DESC);

INSERT OR IGNORE INTO schema_version(version, description)
VALUES (4, 'Phase 6: verification_queue, verification_audit, verification_schedules,
staleness_snapshots');
```

---

2. Confidence Decay Model

Python

```
# memograph/verification/decay.py
"""
Confidence decay model.

Every stored fact has an implicit "freshness" that decays over time.
The decay rate depends on:
  1. The confidence level (verified decays slowest)
  2. The source type (primary source = slow decay, observation = fast)
  3. The domain (code = slow, user preference = medium, external = fast)

Mathematical model:
  freshness(t) = confidence_0 × exp(-λ × t)

  where:
    λ = ln(2) / half_life_days  (exponential decay)
    t = days since last verified

When freshness falls below a threshold, the fact is marked stale.

Half-lives by confidence level (configurable):
  verified:  60 days  (confirmed against primary source)
  observed:  14 days  (seen but not explicitly confirmed)
  inferred:   7 days  (derived by reasoning)
  stale:      0 days  (already marked stale — re-verify immediately)
```

```
"""

from __future__ import annotations

import math
from dataclasses import dataclass, field
from datetime import datetime, timedelta
from enum import Enum
from typing import Optional

from memograph.config import ConfidenceLevel


class SourceReliability(str, Enum):
    """How reliable is the source of a fact?"""
    PRIMARY    = "primary"    # Direct from source code, config, DB
    SECONDARY  = "secondary"  # From docs, tests, comments
    OBSERVED   = "observed"   # Seen in practice, not formally documented
    INFERRED   = "inferred"   # Derived by reasoning
    UNKNOWN    = "unknown"    # Source not specified


class FactDomain(str, Enum):
    """Domain affects how quickly facts go stale."""
    CODE_STRUCTURE  = "code_structure"   # Class names, function signatures
    CONFIGURATION   = "configuration"    # Config files, env vars
    USER_PREFERENCE = "user_preference"  # User preferences and habits
    ARCHITECTURAL   = "architectural"    # Design decisions
    EXTERNAL_API    = "external_api"     # Third-party services
    EPHEMERAL       = "ephemeral"        # Session-specific, very short-lived
    GENERAL         = "general"          # Default


# Half-lives in days by (confidence_level, domain)
HALF_LIFE_TABLE: dict[tuple[ConfidenceLevel, FactDomain], float] = {
    # Verified facts decay slowly
    (ConfidenceLevel.VERIFIED, FactDomain.CODE_STRUCTURE):  90.0,
    (ConfidenceLevel.VERIFIED, FactDomain.CONFIGURATION):   60.0,
    (ConfidenceLevel.VERIFIED, FactDomain.USER_PREFERENCE): 45.0,
    (ConfidenceLevel.VERIFIED, FactDomain.ARCHITECTURAL):   120.0,
    (ConfidenceLevel.VERIFIED, FactDomain.EXTERNAL_API):    30.0,
    (ConfidenceLevel.VERIFIED, FactDomain.EPHEMERAL):        1.0,
    (ConfidenceLevel.VERIFIED, FactDomain.GENERAL):          60.0,
    # Observed facts decay moderately
    (ConfidenceLevel.OBSERVED, FactDomain.CODE_STRUCTURE):  21.0,
    (ConfidenceLevel.OBSERVED, FactDomain.CONFIGURATION):   14.0,
    (ConfidenceLevel.OBSERVED, FactDomain.USER_PREFERENCE): 14.0,
    (ConfidenceLevel.OBSERVED, FactDomain.ARCHITECTURAL):   30.0,
    (ConfidenceLevel.OBSERVED, FactDomain.EXTERNAL_API):     7.0,
    (ConfidenceLevel.OBSERVED, FactDomain.EPHEMERAL):        0.5,
    (ConfidenceLevel.OBSERVED, FactDomain.GENERAL):          14.0,
    # Inferred facts decay quickly
    (ConfidenceLevel.INFERRED, FactDomain.CODE_STRUCTURE):   7.0,
    (ConfidenceLevel.INFERRED, FactDomain.CONFIGURATION):    5.0,
    (ConfidenceLevel.INFERRED, FactDomain.USER_PREFERENCE):  5.0,
    (ConfidenceLevel.INFERRED, FactDomain.ARCHITECTURAL):   14.0,
    (ConfidenceLevel.INFERRED, FactDomain.EXTERNAL_API):     3.0,
    (ConfidenceLevel.INFERRED, FactDomain.EPHEMERAL):        0.25,
```

```
    (ConfidenceLevel.INFERRED, FactDomain.GENERAL):           7.0,
    # Stale facts are always at zero
    (ConfidenceLevel.STALE,    FactDomain.GENERAL):           0.0,
}

# Fallback half-lives by confidence level only
CONFIDENCE_HALF_LIVES: dict[ConfidenceLevel, float] = {
    ConfidenceLevel.VERIFIED: 60.0,
    ConfidenceLevel.OBSERVED: 14.0,
    ConfidenceLevel.INFERRED:  7.0,
    ConfidenceLevel.STALE:     0.0,
}

# Staleness threshold — below this freshness score → mark stale
STALENESS_THRESHOLD = 0.25


@dataclass
class DecayResult:
    """Result of computing decay for a fact."""
    fact_id:            str
    topic_id:           str
    confidence:         ConfidenceLevel
    domain:             FactDomain
    days_elapsed:       float
    half_life_days:     float
    decay_rate:         float       # λ = ln(2) / half_life
    freshness:          float       # 0.0–1.0 (1.0 = just verified)
    is_stale:           bool
    days_until_stale:   Optional[float]   # None if already stale
    next_check_date:    Optional[datetime]


@dataclass
class DecayConfig:
    """Configuration for the decay model."""
    staleness_threshold:    float = STALENESS_THRESHOLD
    custom_half_lives:      dict  = field(default_factory=dict)
    source_reliability_multipliers: dict = field(default_factory=lambda: {
        SourceReliability.PRIMARY:   2.0,   # Primary sources: 2x half-life
        SourceReliability.SECONDARY: 1.5,
        SourceReliability.OBSERVED:  1.0,
        SourceReliability.INFERRED:  0.7,   # Inferred: 0.7x half-life
        SourceReliability.UNKNOWN:   0.8,
    })


class ConfidenceDecayModel:
    """
    Computes confidence decay for memory facts.

    Usage:
        model  = ConfidenceDecayModel()
        result = model.compute_decay(
            fact_id="abc123",
            topic_id="tech_stack",
            confidence=ConfidenceLevel.OBSERVED,
            last_verified=datetime.now() - timedelta(days=20),
```

```
            domain=FactDomain.CONFIGURATION,
        )
        if result.is_stale:
            mark_for_reverification(fact)
    """

    def __init__(self, config: Optional[DecayConfig] = None):
        self.config = config or DecayConfig()

    def compute_decay(
        self,
        fact_id:          str,
        topic_id:         str,
        confidence:       ConfidenceLevel,
        last_verified:    Optional[datetime],
        created_at:       Optional[datetime]  = None,
        domain:           FactDomain          = FactDomain.GENERAL,
        source_reliability: SourceReliability = SourceReliability.UNKNOWN,
    ) -> DecayResult:
        """
        Compute the current freshness of a fact.

        Returns DecayResult with freshness score and staleness status.
        """
        now = datetime.now()

        # Reference date: use last_verified if available, else created_at
        ref_date = last_verified or created_at or now
        days_elapsed = max(0.0, (now - ref_date).total_seconds() / 86400)

        # Get base half-life
        half_life = self._get_half_life(confidence, domain)

        # Apply source reliability multiplier
        reliability_mult = self.config.source_reliability_multipliers.get(
            source_reliability, 1.0
        )
        adjusted_half_life = half_life * reliability_mult

        # Compute decay rate λ = ln(2) / half_life
        if adjusted_half_life <= 0:
            # Zero half-life → immediately stale
            freshness    = 0.0
            decay_rate   = float('inf')
        else:
            decay_rate = math.log(2) / adjusted_half_life
            # Freshness: f(t) = exp(-λt)
            freshness  = math.exp(-decay_rate * days_elapsed)

        is_stale = freshness < self.config.staleness_threshold

        # Compute days until stale (from now)
        days_until_stale: Optional[float] = None
        next_check: Optional[datetime]    = None

        if not is_stale and adjusted_half_life > 0:
            # Solve for t: threshold = exp(-λt) → t = -ln(threshold) / λ
            days_until_stale_total = (
```

```
                -math.log(self.config.staleness_threshold) / decay_rate
            )
            days_until_stale = max(0.0, days_until_stale_total - days_elapsed)
            # Schedule next check at 50% of remaining freshness
            next_check = now + timedelta(days=days_until_stale * 0.5)

        return DecayResult(
            fact_id=fact_id,
            topic_id=topic_id,
            confidence=confidence,
            domain=domain,
            days_elapsed=days_elapsed,
            half_life_days=adjusted_half_life,
            decay_rate=decay_rate if adjusted_half_life > 0 else 0.0,
            freshness=freshness,
            is_stale=is_stale,
            days_until_stale=days_until_stale,
            next_check_date=next_check,
        )

    def compute_batch(
        self,
        facts: list[dict],
    ) -> list[DecayResult]:
        """
        Batch compute decay for multiple facts.

        Each dict should have:
            fact_id, topic_id, confidence, last_verified,
            created_at (optional), domain (optional), source_reliability (optional)
        """
        return [
            self.compute_decay(
                fact_id=f["fact_id"],
                topic_id=f["topic_id"],
                confidence=ConfidenceLevel(f["confidence"]),
                last_verified=f.get("last_verified"),
                created_at=f.get("created_at"),
                domain=FactDomain(f.get("domain", "general")),
                source_reliability=SourceReliability(
                    f.get("source_reliability", "unknown")
                ),
            )
            for f in facts
        ]

    def days_to_stale(
        self,
        confidence:      ConfidenceLevel,
        domain:          FactDomain          = FactDomain.GENERAL,
        source_reliability: SourceReliability = SourceReliability.UNKNOWN,
    ) -> float:
        """How many days from now until a fresh fact becomes stale?"""
        half_life = self._get_half_life(confidence, domain)
        mult      = self.config.source_reliability_multipliers.get(
            source_reliability, 1.0
        )
        adjusted = half_life * mult
```

```
        if adjusted <= 0:
            return 0.0

        decay_rate = math.log(2) / adjusted
        return -math.log(self.config.staleness_threshold) / decay_rate

    def freshness_at(
        self,
        confidence:    ConfidenceLevel,
        days_elapsed:  float,
        domain:        FactDomain = FactDomain.GENERAL,
    ) -> float:
        """Compute freshness at a specific age."""
        half_life = self._get_half_life(confidence, domain)
        if half_life <= 0:
            return 0.0
        decay_rate = math.log(2) / half_life
        return math.exp(-decay_rate * days_elapsed)

    def _get_half_life(
        self,
        confidence: ConfidenceLevel,
        domain:     FactDomain,
    ) -> float:
        """Get the half-life for a confidence+domain combination."""
        # Check custom overrides first
        key = f"{confidence.value}:{domain.value}"
        if key in self.config.custom_half_lives:
            return float(self.config.custom_half_lives[key])

        # Look up in table
        table_hl = HALF_LIFE_TABLE.get((confidence, domain))
        if table_hl is not None:
            return table_hl

        # Fall back to confidence-only half-life
        return CONFIDENCE_HALF_LIVES.get(confidence, 14.0)

    def generate_decay_schedule(
        self,
        confidence:   ConfidenceLevel,
        domain:       FactDomain = FactDomain.GENERAL,
        days_ahead:   int        = 90,
        points:       int        = 10,
    ) -> list[tuple[float, float]]:
        """
        Generate a decay curve: list of (days, freshness) points.
        Useful for visualization and planning.
        """
        step = days_ahead / points
        return [
            (i * step, self.freshness_at(confidence, i * step, domain))
            for i in range(points + 1)
        ]
```

---

3. Staleness Detector

Python

```python
# memograph/verification/staleness.py
"""
Staleness detector — scans memory and identifies facts due for verification.

Works in two modes:
1. PASSIVE:  Marks facts as stale based on decay model (no I/O)
2. ACTIVE:   Scans topic files and updates DB staleness records

Output feeds into the VerificationPlanner which prioritizes verification work.
"""

from __future__ import annotations

import logging
from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional

from memograph.config import ConfidenceLevel
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.models.topic import MemoryFact, TopicFile
from memograph.verification.decay import (
    ConfidenceDecayModel,
    DecayConfig,
    DecayResult,
    FactDomain,
    SourceReliability,
)

logger = logging.getLogger("memograph.verification.staleness")


@dataclass
class StaleFactRecord:
    """A fact identified as stale or near-stale."""
    fact_id:          str
    topic_id:         str
    fact_content:     str
    confidence:       ConfidenceLevel
    freshness:        float
    days_elapsed:     float
    days_until_stale: Optional[float]
    is_overdue:       bool            # freshness == 0 (way past threshold)
    priority_score:   float           # 0.0–1.0 (higher = verify sooner)
    source:           str
    verification_hint: Optional[str]
    decay_result:     DecayResult
```

```python
@dataclass
class StalenessReport:
    """Full staleness scan report."""
    agent_id:          str
    scanned_topics:    int
    scanned_facts:     int
    stale_facts:       list[StaleFactRecord]
    near_stale_facts:  list[StaleFactRecord]  # Will be stale within 3 days
    health_score:      float                  # 0.0-1.0 (1.0 = all fresh)
    generated_at:      datetime = field(default_factory=datetime.now)

    @property
    def total_stale(self) -> int:
        return len(self.stale_facts)

    @property
    def total_at_risk(self) -> int:
        return len(self.stale_facts) + len(self.near_stale_facts)

    @property
    def overdue_facts(self) -> list[StaleFactRecord]:
        return [f for f in self.stale_facts if f.is_overdue]

    def to_dict(self) -> dict:
        return {
            "agent_id":       self.agent_id,
            "scanned_topics": self.scanned_topics,
            "scanned_facts":  self.scanned_facts,
            "stale_facts":    len(self.stale_facts),
            "near_stale":     len(self.near_stale_facts),
            "overdue":        len(self.overdue_facts),
            "health_score":   round(self.health_score, 3),
            "generated_at":   self.generated_at.isoformat(),
            "stale_list": [
                {
                    "fact_id":    s.fact_id,
                    "topic_id":   s.topic_id,
                    "content":    s.fact_content[:80],
                    "freshness":  round(s.freshness, 3),
                    "days_old":   round(s.days_elapsed, 1),
                    "priority":   round(s.priority_score, 3),
                }
                for s in sorted(
                    self.stale_facts, key=lambda x: x.priority_score, reverse=True
                )[:20]
            ],
        }


class StalenessDetector:
    """
    Scans memory and identifies facts that need re-verification.

    Algorithm:
    1. Load all topic files
    2. For each fact, compute freshness via ConfidenceDecayModel
    3. Collect facts below staleness threshold
    4. Prioritize by: days_elapsed × (1 / confidence_score) × usage_frequency
```

```
    5. Return StalenessReport + update DB
    """

    NEAR_STALE_DAYS = 3.0    # Facts expiring within N days are "near-stale"

    def __init__(
        self,
        topic_manager:  TopicManager,
        db:             DatabaseManager,
        agent_id:       str,
        decay_config:   Optional[DecayConfig] = None,
    ):
        self.topic_manager = topic_manager
        self.db            = db
        self.agent_id      = agent_id
        self.decay_model   = ConfidenceDecayModel(decay_config)

    async def scan(
        self,
        topic_ids:        Optional[list[str]] = None,
        include_inferred: bool                = True,
        update_db:        bool                = True,
    ) -> StalenessReport:
        """
        Run a full staleness scan.

        Args:
            topic_ids:        Specific topics to scan (None = all)
            include_inferred: Include inferred facts in scan
            update_db:        Write staleness updates back to DB

        Returns:
            StalenessReport with prioritized stale facts
        """
        # Resolve topic list
        if topic_ids is None:
            all_topics = await self.db.get_topics(self.agent_id)
            topic_ids  = [t["topic_id"] for t in all_topics]

        stale_facts:      list[StaleFactRecord] = []
        near_stale_facts: list[StaleFactRecord] = []
        total_facts       = 0
        fresh_facts       = 0

        for topic_id in topic_ids:
            topic = await self.topic_manager.get_topic(topic_id)
            if not topic:
                continue

            for fact in topic.facts:
                if not include_inferred and fact.confidence == ConfidenceLevel.INFERRED:
                    continue

                total_facts += 1

                decay = self.decay_model.compute_decay(
                    fact_id=fact.fact_id,
                    topic_id=topic_id,
```

```
                    confidence=fact.confidence,
                    last_verified=fact.last_verified,
                    created_at=fact.created_at,
                    domain=self._infer_domain(fact, topic),
                    source_reliability=self._infer_source_reliability(fact),
                )

                if decay.is_stale:
                    record = self._build_record(fact, topic_id, decay)
                    stale_facts.append(record)

                    if update_db:
                        await self._mark_stale_in_db(topic_id, fact.fact_id)

                elif (
                    decay.days_until_stale is not None
                    and decay.days_until_stale <= self.NEAR_STALE_DAYS
                ):
                    record = self._build_record(fact, topic_id, decay)
                    near_stale_facts.append(record)
                else:
                    fresh_facts += 1

        # Sort by priority (highest first)
        stale_facts.sort(key=lambda r: r.priority_score, reverse=True)
        near_stale_facts.sort(key=lambda r: r.priority_score, reverse=True)

        # Compute health score
        health_score = (
            fresh_facts / total_facts
            if total_facts > 0 else 1.0
        )

        # Save snapshot to DB
        if update_db and total_facts > 0:
            await self._save_snapshot(
                total_facts=total_facts,
                stale_count=len(stale_facts),
                near_stale_count=len(near_stale_facts),
                health_score=health_score,
            )

        logger.info(
            f"Staleness scan: {total_facts} facts, "
            f"{len(stale_facts)} stale, "
            f"{len(near_stale_facts)} near-stale, "
            f"health={health_score:.1%}"
        )

        return StalenessReport(
            agent_id=self.agent_id,
            scanned_topics=len(topic_ids),
            scanned_facts=total_facts,
            stale_facts=stale_facts,
            near_stale_facts=near_stale_facts,
            health_score=health_score,
        )
```

```python
    def apply_decay_to_topic(
        self,
        topic: TopicFile,
        mutate: bool = True,
    ) -> tuple[TopicFile, list[DecayResult]]:
        """
        Apply decay model to all facts in a topic.
        If mutate=True, updates fact.confidence to STALE in-place.
        Returns (updated_topic, decay_results).
        """
        results = []

        for fact in topic.facts:
            decay = self.decay_model.compute_decay(
                fact_id=fact.fact_id,
                topic_id=topic.topic_id,
                confidence=fact.confidence,
                last_verified=fact.last_verified,
                created_at=fact.created_at,
                domain=self._infer_domain(fact, topic),
            )
            results.append(decay)

            if mutate and decay.is_stale and fact.confidence != ConfidenceLevel.STALE:
                fact.confidence = ConfidenceLevel.STALE
                logger.debug(
                    f"Marked stale: {fact.fact_id} in {topic.topic_id} "
                    f"(freshness={decay.freshness:.3f})"
                )

        return topic, results

    # ──────────────────────────────────────────────────────────────────────
    # PRIVATE
    # ──────────────────────────────────────────────────────────────────────

    def _build_record(
        self,
        fact:     MemoryFact,
        topic_id: str,
        decay:    DecayResult,
    ) -> StaleFactRecord:
        """Build a StaleFactRecord from a fact + decay result."""
        priority = self._compute_priority(fact, decay)

        return StaleFactRecord(
            fact_id=fact.fact_id,
            topic_id=topic_id,
            fact_content=fact.content,
            confidence=fact.confidence,
            freshness=decay.freshness,
            days_elapsed=decay.days_elapsed,
            days_until_stale=decay.days_until_stale,
            is_overdue=decay.freshness <= 0.0,
            priority_score=priority,
            source=fact.source,
            verification_hint=fact.verification_hint,
            decay_result=decay,
```

```
        )

    def _compute_priority(
        self,
        fact:  MemoryFact,
        decay: DecayResult,
    ) -> float:
        """
        Priority score for verification queue ordering.

        Factors:
        - How stale (lower freshness = higher priority)
        - Original confidence (higher confidence = higher priority to re-verify)
        - Whether it has a verification hint (hinted = easier to verify = higher priority)
        - Overdue penalty (way past threshold = maximum priority)
        """
        if decay.is_overdue:
            base = 1.0
        else:
            base = 1.0 - decay.freshness    # 0=fresh, 1=very stale

        conf_weight = {
            ConfidenceLevel.VERIFIED: 1.0,
            ConfidenceLevel.OBSERVED: 0.7,
            ConfidenceLevel.INFERRED: 0.5,
            ConfidenceLevel.STALE:    0.8,
        }.get(fact.confidence, 0.6)

        hint_bonus   = 0.1 if fact.verification_hint else 0.0
        overdue_bonus = 0.2 if decay.is_overdue else 0.0

        return min(1.0, base * conf_weight + hint_bonus + overdue_bonus)

    def _infer_domain(
        self,
        fact:  MemoryFact,
        topic: TopicFile,
    ) -> FactDomain:
        """Infer the fact domain from its content and tags."""
        content_lower = fact.content.lower()
        tags          = [t.lower() for t in topic.tags]

        if any(k in content_lower for k in ["import", "class ", "def ", "function",
"module"]):
            return FactDomain.CODE_STRUCTURE
        if any(k in content_lower for k in ["config", "env", ".env", "secret", "key", "token",
"port"]):
            return FactDomain.CONFIGURATION
        if any(k in content_lower for k in ["prefer", "always", "never", "wants", "likes"]):
            return FactDomain.USER_PREFERENCE
        if any(k in content_lower for k in ["decided", "architecture", "design", "pattern",
"approach"]):
            return FactDomain.ARCHITECTURAL
        if any(k in content_lower for k in ["api", "endpoint", "http", "webhook", "service"]):
            return FactDomain.EXTERNAL_API
        if any(k in tags for k in ["ephemeral", "temp", "session"]):
            return FactDomain.EPHEMERAL
```

```
        return FactDomain.GENERAL

    def _infer_source_reliability(
        self,
        fact: MemoryFact,
    ) -> SourceReliability:
        """Infer source reliability from fact.source string."""
        source_lower = fact.source.lower()

        if any(k in source_lower for k in ["code", "file", "config", "codebase", "src"]):
            return SourceReliability.PRIMARY
        if any(k in source_lower for k in ["doc", "readme", "test", "spec"]):
            return SourceReliability.SECONDARY
        if any(k in source_lower for k in ["observe", "seen", "noticed", "conversation"]):
            return SourceReliability.OBSERVED
        if any(k in source_lower for k in ["infer", "deduc", "assum", "guess"]):
            return SourceReliability.INFERRED

        return SourceReliability.UNKNOWN

    async def _mark_stale_in_db(self, topic_id: str, fact_id: str) -> None:
        """Update confidence to STALE in the DB."""
        await self.db.update_fact_confidence(
            self.agent_id, topic_id, fact_id, ConfidenceLevel.STALE.value
        )

    async def _save_snapshot(
        self,
        total_facts:     int,
        stale_count:     int,
        near_stale_count: int,
        health_score:    float,
    ) -> None:
        """Save a staleness snapshot to the DB."""
        await self.db.execute(
            """
            INSERT INTO staleness_snapshots(
                agent_id, total_facts, stale_count, health_score
            ) VALUES (?,?,?,?)
            """,
            (self.agent_id, total_facts, stale_count, health_score),
        )
```

---

4. Verification Prompts

Python

```
# memograph/prompts/verification_prompts.py
"""
All prompts for the verification LLM calls.
"""
```

```python
from __future__ import annotations

from typing import Optional


# ──────────────────────────────────────────────────────────────────────────────
# FACT VERIFICATION — Main verification prompt
# ──────────────────────────────────────────────────────────────────────────────
FACT_VERIFIER_SYSTEM = """\
You are a MemoGraph Fact Verifier — a precision verification agent.

Your role is to check whether a stored memory fact is still accurate.
You are given the fact, its source, and current evidence/context.

## Verification Verdicts

- **confirmed**:   Evidence clearly supports the fact. It is still accurate.
- **refuted**:     Evidence clearly contradicts the fact. It should be updated.
- **outdated**:    The fact was once true but circumstances have changed.
- **uncertain**:   You cannot determine accuracy from available evidence.
- **not_verifiable**: No evidence is available to check this fact.

## Confidence Mapping

After your verdict, assign a new confidence level:
- confirmed + strong evidence  → "verified"
- confirmed + weak evidence    → "observed"
- uncertain                    → "inferred"
- refuted / outdated           → "stale"
- not_verifiable               → keep existing (unchanged)

## Rules

1. Be CONSERVATIVE — only mark "refuted" if you have clear contradicting evidence
2. Be EXPLICIT — always cite what evidence led to your verdict
3. Never fabricate evidence — if you cannot verify, say "uncertain"
4. If the fact can be re-derived from available code/docs, note that
5. Keep updated_content ≤ 200 chars if the fact needs updating

## Output Format — JSON only, no prose, no markdown fences.

{
  "fact_id":           "...",
  "verdict":           "confirmed|refuted|outdated|uncertain|not_verifiable",
  "new_confidence":    "verified|observed|inferred|stale",
  "explanation":       "Brief explanation citing specific evidence (≤200 chars)",
  "updated_content":   null,
  "should_update":     false,
  "re_derivable":      false,
  "re_derive_from":    null,
  "verification_notes": "Any additional context for future verification"
}
"""


def build_fact_verification_prompt(
    fact_id:          str,
    fact_content:     str,
```

```
    current_confidence: str,
    source:           str,
    verification_hint: Optional[str],
    days_since_verified: float,
    evidence:         str,
) -> str:
    """Build the user-turn for fact verification."""
    hint_section = (
        f"\nVerification hint: {verification_hint}"
        if verification_hint else ""
    )
    return f"""\
## Fact to Verify

Fact ID:    {fact_id}
Content:    {fact_content}
Confidence: {current_confidence}
Source:     {source}
Age:        {days_since_verified:.1f} days since last verified{hint_section}

## Available Evidence

{evidence[:4000] if evidence else "No specific evidence provided — use general knowledge."}

Verify this fact. Is it still accurate?"""


# ─────────────────────────────────────────────────────────────────────────────
# BATCH VERIFICATION — Verify multiple facts at once
# ─────────────────────────────────────────────────────────────────────────────
BATCH_VERIFIER_SYSTEM = """\
You are verifying a batch of memory facts against provided evidence.
For each fact, apply the same verification criteria as a single verification.

Output a JSON array of verification results, one per fact:

[
  {
    "fact_id": "...",
    "verdict": "confirmed|refuted|outdated|uncertain|not_verifiable",
    "new_confidence": "verified|observed|inferred|stale",
    "explanation": "...",
    "updated_content": null,
    "should_update": false
  }
]

Be efficient — process all facts in a single response.
"""


def build_batch_verification_prompt(
    facts: list[dict],
    evidence: str,
) -> str:
    """Build batch verification prompt."""
    facts_section = "\n".join([
        f"  [{i+1}] ID={f['fact_id']} | {f['confidence']} | {f['content']}"
```

```
        for i, f in enumerate(facts)
    ])
    return f"""\
## Facts to Verify

{facts_section}

## Available Evidence

{evidence[:5000] if evidence else "No specific evidence — use general knowledge."}

Verify all facts above. Output JSON array."""


# ═══════════════════════════════════════════════════════════════
# EVIDENCE EXTRACTION — Extract relevant evidence from context
# ═══════════════════════════════════════════════════════════════
EVIDENCE_EXTRACTOR_SYSTEM = """\
You are extracting evidence relevant to verifying a specific memory fact.

Given a large context (file contents, docs, conversation), extract ONLY
the passages that are relevant to the fact being verified.

Output JSON:
{
  "relevant_passages": ["passage 1", "passage 2"],
  "relevance_score": 0.0,
  "summary": "Brief summary of what the evidence says about the fact"
}

Be selective — only include passages that directly relate to the fact.
Maximum 3 passages, each ≤ 200 chars.
"""


def build_evidence_extraction_prompt(fact_content: str, context: str) -> str:
    return f"""\
## Fact to verify:
{fact_content}

## Context to extract evidence from:
{context[:6000]}

Extract relevant evidence for verifying the fact above."""


# ═══════════════════════════════════════════════════════════════
# VERIFICATION HINT GENERATOR
# ═══════════════════════════════════════════════════════════════
HINT_GENERATOR_SYSTEM = """\
You are generating verification hints for memory facts.

A verification hint tells the agent WHERE and HOW to verify a fact.

Examples of good hints:
  - "Check src/auth/jwt.py for token expiry settings"
  - "Verify in .env.example — look for PORT variable"
  - "Read README.md deployment section"
```

```
  - "Run: git log --oneline -5 to check recent changes"
  - "Ask user directly: 'Do you still prefer dark mode?'"

Output JSON:
{
  "hint": "Specific verification instruction (≤150 chars)",
  "source_type": "file|command|question|url|manual",
  "source_path": "Exact path/command/URL if applicable",
  "estimated_effort": "trivial|low|medium|high"
}
"""


def build_hint_generation_prompt(
    fact_content: str,
    topic_id:     str,
    source:       str,
) -> str:
    return f"""\
Generate a verification hint for this memory fact.

Topic:   {topic_id}
Source:  {source}
Fact:    {fact_content}

How should a future agent verify this fact?"""
```

---

5. Source Verifiers

Python

```
# memograph/verification/sources/base.py
"""Abstract source verifier interface."""

from __future__ import annotations

from abc import ABC, abstractmethod
from dataclasses import dataclass
from enum import Enum
from typing import Optional


class VerificationVerdict(str, Enum):
    CONFIRMED       = "confirmed"
    REFUTED         = "refuted"
    OUTDATED        = "outdated"
    UNCERTAIN       = "uncertain"
    NOT_VERIFIABLE  = "not_verifiable"
    ERROR           = "error"


@dataclass
```

```python
class VerificationResult:
    """Result from any source verifier."""
    fact_id:          str
    verdict:          VerificationVerdict
    new_confidence:   str           # "verified"|"observed"|"inferred"|"stale"
    explanation:      str
    updated_content:  Optional[str] = None
    should_update:    bool          = False
    re_derivable:     bool          = False
    re_derive_from:   Optional[str] = None
    evidence_used:    Optional[str] = None
    duration_ms:      int           = 0
    tokens_used:      int           = 0
    verifier_type:    str           = "unknown"

    @property
    def confirmed(self) -> bool:
        return self.verdict == VerificationVerdict.CONFIRMED

    @property
    def refuted(self) -> bool:
        return self.verdict == VerificationVerdict.REFUTED


class BaseSourceVerifier(ABC):
    """Abstract source verifier."""

    verifier_type: str = "base"

    @abstractmethod
    async def verify(
        self,
        fact_id:          str,
        fact_content:     str,
        current_confidence: str,
        source_hint:      Optional[str],
        context:          Optional[str] = None,
    ) -> VerificationResult:
        """Attempt to verify a fact."""
        ...

    @abstractmethod
    async def can_verify(
        self,
        fact_content: str,
        source_hint:  Optional[str],
    ) -> bool:
        """Check if this verifier can handle the given fact."""
        ...
```

Python

```python
# memograph/verification/sources/file_verifier.py
"""
File-based verifier — checks facts against local file contents.
```

```
Handles:
- Source code files (exact string search + AST analysis)
- Config files (.env, YAML, JSON, TOML)
- Documentation files (README, docs/)
- Log files (recent log entries)
"""

from __future__ import annotations

import json
import logging
import re
import time
from pathlib import Path
from typing import Optional

import aiofiles

from memograph.verification.sources.base import (
    BaseSourceVerifier,
    VerificationResult,
    VerificationVerdict,
)

logger = logging.getLogger("memograph.verification.file")


class FileVerifier(BaseSourceVerifier):
    """
    Verifies facts by searching relevant local files.

    Source hint format examples:
      "src/auth/jwt.py"
      "config/.env.example"
      "docs/architecture.md"
      "src/  (search recursively)"

    Matching strategy:
    1. Parse key terms from fact content
    2. Search file(s) for those terms
    3. Return surrounding context as evidence
    4. Pass evidence to LLM for verdict
    """

    verifier_type = "file"

    def __init__(
        self,
        base_path:     Path,
        max_file_size: int = 100_000,   # 100KB cap
        context_lines: int = 5,
    ):
        self.base_path    = Path(base_path)
        self.max_file_size = max_file_size
        self.context_lines = context_lines

    async def can_verify(
        self,
```

```
        fact_content: str,
        source_hint:  Optional[str],
    ) -> bool:
        """True if source_hint points to an existing file/dir."""
        if not source_hint:
            return False

        # Check if it looks like a file path
        if any(source_hint.startswith(p) for p in ("src/", "docs/", "config/", ".")):
            candidate = self.base_path / source_hint
            return candidate.exists()

        return False

    async def verify(
        self,
        fact_id:          str,
        fact_content:     str,
        current_confidence: str,
        source_hint:      Optional[str],
        context:          Optional[str] = None,
    ) -> VerificationResult:
        """Search local files for evidence to verify the fact."""
        t0 = time.monotonic()

        if not source_hint:
            return VerificationResult(
                fact_id=fact_id,
                verdict=VerificationVerdict.NOT_VERIFIABLE,
                new_confidence=current_confidence,
                explanation="No file source hint provided",
                verifier_type=self.verifier_type,
            )

        try:
            # Gather file contents
            evidence = await self._gather_evidence(fact_content, source_hint)

            if not evidence:
                return VerificationResult(
                    fact_id=fact_id,
                    verdict=VerificationVerdict.NOT_VERIFIABLE,
                    new_confidence=current_confidence,
                    explanation=f"File(s) at '{source_hint}' not found or empty",
                    verifier_type=self.verifier_type,
                    duration_ms=int((time.monotonic() - t0) * 1000),
                )

            # Simple keyword matching for a quick verdict
            verdict, explanation = self._analyze_evidence(fact_content, evidence)
            new_confidence = self._map_verdict_to_confidence(
                verdict, current_confidence
            )

            return VerificationResult(
                fact_id=fact_id,
                verdict=verdict,
                new_confidence=new_confidence,
```

```
                explanation=explanation,
                evidence_used=evidence[:500],
                verifier_type=self.verifier_type,
                duration_ms=int((time.monotonic() - t0) * 1000),
            )

        except Exception as e:
            logger.error(f"FileVerifier error for {fact_id}: {e}", exc_info=True)
            return VerificationResult(
                fact_id=fact_id,
                verdict=VerificationVerdict.ERROR,
                new_confidence=current_confidence,
                explanation=f"Verification error: {str(e)[:100]}",
                verifier_type=self.verifier_type,
                duration_ms=int((time.monotonic() - t0) * 1000),
            )

    async def _gather_evidence(
        self,
        fact_content: str,
        source_hint:  str,
    ) -> str:
        """Read relevant file content as evidence."""
        target = self.base_path / source_hint
        evidence_parts: list[str] = []

        if target.is_file():
            content = await self._read_file_safe(target)
            if content:
                # Find relevant lines
                matches = self._find_relevant_lines(fact_content, content)
                evidence_parts.append(f"# {target.name}\n{matches}")

        elif target.is_dir():
            # Search all files in directory (limited)
            files = list(target.rglob("*.py"))[:10]
            files += list(target.rglob("*.md"))[:5]
            files += list(target.rglob("*.yaml"))[:5]

            for f in files[:15]:
                content = await self._read_file_safe(f)
                if content:
                    matches = self._find_relevant_lines(fact_content, content)
                    if matches:
                        evidence_parts.append(f"# {f.name}\n{matches}")
                        if len("\n".join(evidence_parts)) > 3000:
                            break

        return "\n\n".join(evidence_parts)

    async def _read_file_safe(self, path: Path) -> Optional[str]:
        """Read a file with size limits."""
        try:
            if path.stat().st_size > self.max_file_size:
                async with aiofiles.open(path) as f:
                    return (await f.read(self.max_file_size)) + "\n[... file truncated ...]"
            async with aiofiles.open(path) as f:
                return await f.read()
```

```
        except (OSError, UnicodeDecodeError):
            return None

    def _find_relevant_lines(
        self,
        fact_content: str,
        file_content: str,
    ) -> str:
        """Extract lines relevant to the fact."""
        keywords = re.findall(r"\b\w{3,}\b", fact_content.lower())
        lines    = file_content.split("\n")
        result   = []

        for i, line in enumerate(lines):
            line_lower = line.lower()
            if any(kw in line_lower for kw in keywords):
                start = max(0, i - self.context_lines)
                end   = min(len(lines), i + self.context_lines + 1)
                context = lines[start:end]
                result.append(f"Line {i+1}: " + "\n".join(context))

                if len(result) >= 3:
                    break

        return "\n---\n".join(result) if result else ""

    def _analyze_evidence(
        self,
        fact_content: str,
        evidence:     str,
    ) -> tuple[VerificationVerdict, str]:
        """
        Quick keyword-based verdict from evidence.
        Returns (verdict, explanation).
        """
        if not evidence:
            return VerificationVerdict.UNCERTAIN, "No matching content found in files"

        fact_lower  = fact_content.lower()
        evid_lower  = evidence.lower()

        # Extract key terms from fact
        key_terms = re.findall(r"\b\w{4,}\b", fact_lower)

        # Count matching terms
        matches   = sum(1 for term in key_terms if term in evid_lower)
        coverage  = matches / max(len(key_terms), 1)

        if coverage > 0.6:
            return (
                VerificationVerdict.CONFIRMED,
                f"Found {matches}/{len(key_terms)} key terms in file evidence",
            )
        elif coverage > 0.3:
            return (
                VerificationVerdict.UNCERTAIN,
                f"Partial match ({matches}/{len(key_terms)} terms). Manual review
recommended",
```

```
            )
        else:
            return (
                VerificationVerdict.UNCERTAIN,
                f"Low match ({matches}/{len(key_terms)} terms). Fact may be outdated",
            )

    @staticmethod
    def _map_verdict_to_confidence(
        verdict:            VerificationVerdict,
        current_confidence: str,
    ) -> str:
        mapping = {
            VerificationVerdict.CONFIRMED:      "verified",
            VerificationVerdict.REFUTED:        "stale",
            VerificationVerdict.OUTDATED:       "stale",
            VerificationVerdict.UNCERTAIN:      "observed",
            VerificationVerdict.NOT_VERIFIABLE: current_confidence,
            VerificationVerdict.ERROR:          current_confidence,
        }

        return mapping.get(verdict, current_confidence)
```

Python

```
# memograph/verification/sources/llm_verifier.py
"""
LLM-powered fact verifier — the most powerful verifier.

Uses the configured LLM to:
1. Read the fact + evidence
2. Apply the verification prompt
3. Return a structured verdict

Falls back gracefully if LLM is unavailable.
"""

from __future__ import annotations

import json
import logging
import re
import time
from typing import Optional

from memograph.llm.base import BaseLLMProvider, LLMRequest, Message
from memograph.prompts.verification_prompts import (
    FACT_VERIFIER_SYSTEM,
    BATCH_VERIFIER_SYSTEM,
    build_fact_verification_prompt,
    build_batch_verification_prompt,
)
from memograph.verification.sources.base import (
    BaseSourceVerifier,
    VerificationResult,
    VerificationVerdict,
```

```
)

logger = logging.getLogger("memograph.verification.llm")


class LLMVerifier(BaseSourceVerifier):
    """
    LLM-powered fact verifier.

    This is the highest-quality verifier — it understands nuance,
    handles partial evidence, and can reason across multiple sources.

    Used when:
    - No specific file source is known
    - File verification returned UNCERTAIN
    - Fact requires reasoning (not just keyword matching)
    - Fact involves user preferences or architectural decisions
    """

    verifier_type = "llm"

    def __init__(
        self,
        llm:        BaseLLMProvider,
        max_tokens: int = 512,
    ):
        self.llm        = llm
        self.max_tokens = max_tokens

    async def can_verify(
        self,
        fact_content: str,
        source_hint:  Optional[str],
    ) -> bool:
        """LLM can always attempt verification."""
        return True

    async def verify(
        self,
        fact_id:           str,
        fact_content:      str,
        current_confidence: str,
        source_hint:       Optional[str],
        context:           Optional[str]  = None,
        days_since_verified: float        = 0.0,
        source:            str            = "",
    ) -> VerificationResult:
        """Use LLM to verify a single fact."""
        t0 = time.monotonic()

        prompt = build_fact_verification_prompt(
            fact_id=fact_id,
            fact_content=fact_content,
            current_confidence=current_confidence,
            source=source or source_hint or "unknown",
            verification_hint=source_hint,
            days_since_verified=days_since_verified,
            evidence=context or "",
```

```
        )

        try:
            request = LLMRequest(
                messages=[Message("user", prompt)],
                system_prompt=FACT_VERIFIER_SYSTEM,
                max_tokens=self.max_tokens,
                temperature=0.0,   # Deterministic verification
                purpose="verification",
            )
            request = request.with_system(FACT_VERIFIER_SYSTEM)
            response = await self.llm.complete(request)

            latency_ms = int((time.monotonic() - t0) * 1000)
            data       = self._parse_json(response.content)

            if not data:
                return VerificationResult(
                    fact_id=fact_id,
                    verdict=VerificationVerdict.UNCERTAIN,
                    new_confidence=current_confidence,
                    explanation="LLM returned unparseable response",
                    verifier_type=self.verifier_type,
                    duration_ms=latency_ms,
                    tokens_used=response.total_tokens,
                )

            return VerificationResult(
                fact_id=fact_id,
                verdict=VerificationVerdict(
                    data.get("verdict", "uncertain")
                ),
                new_confidence=data.get("new_confidence", current_confidence),
                explanation=data.get("explanation", "")[:300],
                updated_content=data.get("updated_content"),
                should_update=data.get("should_update", False),
                re_derivable=data.get("re_derivable", False),
                re_derive_from=data.get("re_derive_from"),
                verifier_type=self.verifier_type,
                duration_ms=latency_ms,
                tokens_used=response.total_tokens,
            )

        except Exception as e:
            logger.error(f"LLMVerifier error for {fact_id}: {e}", exc_info=True)
            return VerificationResult(
                fact_id=fact_id,
                verdict=VerificationVerdict.ERROR,
                new_confidence=current_confidence,
                explanation=f"LLM verification error: {str(e)[:100]}",
                verifier_type=self.verifier_type,
                duration_ms=int((time.monotonic() - t0) * 1000),
            )

    async def verify_batch(
        self,
        facts:   list[dict],
        context: Optional[str] = None,
```

```
    ) -> list[VerificationResult]:
        """
        Verify multiple facts in a single LLM call.
        More efficient than individual calls for large batches.
        """
        t0     = time.monotonic()
        prompt = build_batch_verification_prompt(facts, context or "")

        try:
            request = LLMRequest(
                messages=[Message("user", prompt)],
                system_prompt=BATCH_VERIFIER_SYSTEM,
                max_tokens=len(facts) * 150 + 200,
                temperature=0.0,
                purpose="verification",
            )
            request  = request.with_system(BATCH_VERIFIER_SYSTEM)
            response = await self.llm.complete(request)

            latency_ms = int((time.monotonic() - t0) * 1000)
            results    = self._parse_json(response.content)

            if not isinstance(results, list):
                results = results.get("results", []) if isinstance(results, dict) else []

            output = []
            for r, fact in zip(results, facts):
                output.append(VerificationResult(
                    fact_id=r.get("fact_id", fact["fact_id"]),
                    verdict=VerificationVerdict(r.get("verdict", "uncertain")),
                    new_confidence=r.get(
                        "new_confidence", fact.get("confidence", "observed")
                    ),
                    explanation=r.get("explanation", "")[:200],
                    updated_content=r.get("updated_content"),
                    should_update=r.get("should_update", False),
                    verifier_type=self.verifier_type,
                    duration_ms=latency_ms // len(facts),
                    tokens_used=response.total_tokens // len(facts),
                ))
            return output

        except Exception as e:
            logger.error(f"Batch LLM verification error: {e}", exc_info=True)
            return [
                VerificationResult(
                    fact_id=f["fact_id"],
                    verdict=VerificationVerdict.ERROR,
                    new_confidence=f.get("confidence", "observed"),
                    explanation=f"Batch error: {str(e)[:100]}",
                    verifier_type=self.verifier_type,
                )
                for f in facts
            ]

    @staticmethod
    def _parse_json(text: str) -> dict | list:
        """Parse JSON from LLM response."""
```

```
        text = text.strip()
        match = re.search(r"```(?:json)?\n?(.*?)\n?```", text, re.DOTALL)
        if match:
            text = match.group(1).strip()
        try:
            return json.loads(text)
        except json.JSONDecodeError:

            return {}
```

---

6. Verification Planner

Python

```
# memograph/verification/planner.py
"""
Verification planner — builds and prioritizes the verification queue.

Priority algorithm:
  score = decay_urgency × confidence_weight × source_type_weight
          + overdue_bonus + hint_bonus

  Factors:
  - decay_urgency:      How close to (or past) the staleness threshold
  - confidence_weight:  Higher original confidence = more important to reverify
  - source_type_weight: Primary source facts = more trustworthy if verified
  - overdue_bonus:      Facts past threshold get flat bonus
  - hint_bonus:         Facts with clear hints are easy to verify = schedule first
"""

from __future__ import annotations

import logging
import uuid
from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional

from memograph.db.database import DatabaseManager
from memograph.verification.staleness import StalenessReport, StaleFactRecord

logger = logging.getLogger("memograph.verification.planner")


@dataclass
class QueueItem:
    """A single item in the verification queue."""
    queue_id:           str   = field(default_factory=lambda: str(uuid.uuid4())[:12])
    agent_id:           str   = ""
    topic_id:           str   = ""
    fact_id:            str   = ""
```

```
    fact_content:       str   = ""
    priority_score:     float = 0.5
    priority_reason:    str   = ""
    verification_source: Optional[str] = None
    source_hint:        Optional[str]  = None
    current_confidence: str   = "observed"
    days_since_verified: float = 0.0
    status:             str   = "pending"


@dataclass
class VerificationPlan:
    """A complete verification plan from a staleness scan."""
    agent_id:      str
    total_items:   int
    queue_items:   list[QueueItem]
    estimated_llm_calls: int
    estimated_tokens:    int
    plan_created_at:     datetime = field(default_factory=datetime.now)

    def high_priority(self, threshold: float = 0.7) -> list[QueueItem]:
        return [q for q in self.queue_items if q.priority_score >= threshold]

    def medium_priority(self, low=0.4, high=0.7) -> list[QueueItem]:
        return [q for q in self.queue_items if low <= q.priority_score < high]

    def low_priority(self, threshold: float = 0.4) -> list[QueueItem]:
        return [q for q in self.queue_items if q.priority_score < threshold]


class VerificationPlanner:
    """
    Builds ordered verification queues from staleness reports.

    Usage:
        planner = VerificationPlanner(db, agent_id="myagent")
        plan    = await planner.build_plan(staleness_report)
        await planner.enqueue(plan)
    """

    # Token estimates per verification type
    TOKEN_ESTIMATES = {
        "file":   50,    # Fast file search
        "llm":    400,   # Full LLM call
        "url":    100,   # HTTP fetch + parse
        "code":   150,   # AST analysis
        "manual": 0,     # No tokens
    }

    def __init__(
        self,
        db:             DatabaseManager,
        agent_id:       str,
        max_queue_size: int = 200,
    ):
        self.db             = db
        self.agent_id       = agent_id
        self.max_queue_size = max_queue_size
```

```python
    async def build_plan(
        self,
        report:            StalenessReport,
        include_near_stale: bool = True,
        batch_size:         int  = 50,
    ) -> VerificationPlan:
        """
        Build a verification plan from a staleness report.
        Prioritizes stale facts first, then near-stale.
        """
        items: list[QueueItem] = []

        # Process stale facts (high priority)
        for record in report.stale_facts[:self.max_queue_size]:
            item = self._record_to_queue_item(record)
            items.append(item)

        # Process near-stale facts (medium priority)
        if include_near_stale:
            remaining = self.max_queue_size - len(items)
            for record in report.near_stale_facts[:remaining]:
                item = self._record_to_queue_item(record)
                items.append(item)

        # Sort by priority
        items.sort(key=lambda x: x.priority_score, reverse=True)

        # Estimate LLM calls and tokens
        llm_calls  = sum(1 for i in items if i.verification_source == "llm")
        file_calls = sum(1 for i in items if i.verification_source == "file")
        est_tokens = (
            llm_calls  * self.TOKEN_ESTIMATES["llm"] +
            file_calls * self.TOKEN_ESTIMATES["file"]
        )

        return VerificationPlan(
            agent_id=self.agent_id,
            total_items=len(items),
            queue_items=items,
            estimated_llm_calls=llm_calls,
            estimated_tokens=est_tokens,
        )

    async def enqueue(self, plan: VerificationPlan) -> int:
        """
        Write verification plan to the DB queue.
        Returns number of items enqueued.
        """
        enqueued = 0
        for item in plan.queue_items:
            try:
                await self.db.execute(
                    """
                    INSERT OR IGNORE INTO verification_queue(
                        agent_id, queue_id, topic_id, fact_id, fact_content,
                        priority_score, priority_reason, verification_source,
                        source_hint, current_confidence, days_since_verified
```

```
                    ) VALUES (?,?,?,?,?,?,?,?,?,?,?)
                    """,
                    (
                        self.agent_id, item.queue_id,
                        item.topic_id, item.fact_id,
                        item.fact_content, item.priority_score,
                        item.priority_reason, item.verification_source,
                        item.source_hint, item.current_confidence,
                        item.days_since_verified,
                    ),
                )
                enqueued += 1
            except Exception as e:
                logger.warning(f"Failed to enqueue {item.fact_id}: {e}")

        logger.info(
            f"Enqueued {enqueued}/{plan.total_items} verification items"
        )
        return enqueued

    async def get_next_batch(
        self,
        batch_size: int = 10,
        source_filter: Optional[str] = None,
    ) -> list[QueueItem]:
        """
        Dequeue the next batch of items for processing.
        Marks them as in_progress.
        """
        if source_filter:
            rows = await self.db.fetchall(
                """
                SELECT * FROM verification_queue
                WHERE agent_id = ? AND status = 'pending'
                  AND verification_source = ?
                ORDER BY priority_score DESC
                LIMIT ?
                """,
                (self.agent_id, source_filter, batch_size),
            )
        else:
            rows = await self.db.fetchall(
                """
                SELECT * FROM verification_queue
                WHERE agent_id = ? AND status = 'pending'
                ORDER BY priority_score DESC
                LIMIT ?
                """,
                (self.agent_id, batch_size),
            )

        items = [self._row_to_item(r) for r in rows]

        # Mark as in_progress
        if items:
            ids = [i.queue_id for i in items]
            placeholders = ",".join("?" * len(ids))
            await self.db.execute(
```

```
                f"""
                UPDATE verification_queue
                SET status = 'in_progress', started_at = datetime('now')
                WHERE agent_id = ? AND queue_id IN ({placeholders})
                """,
                (self.agent_id, *ids),
            )

        return items

    async def mark_done(
        self,
        queue_id: str,
        success:  bool = True,
    ) -> None:
        """Mark a queue item as completed or failed."""
        status = "done" if success else "failed"
        await self.db.execute(
            """
            UPDATE verification_queue
            SET status = ?, completed_at = datetime('now'),
                attempt_count = attempt_count + 1
            WHERE agent_id = ? AND queue_id = ?
            """,
            (status, self.agent_id, queue_id),
        )

    async def get_queue_stats(self) -> dict:
        """Queue statistics."""
        row = await self.db.fetchone(
            """
            SELECT
                COUNT(*) FILTER (WHERE status = 'pending')     AS pending,
                COUNT(*) FILTER (WHERE status = 'in_progress') AS in_progress,
                COUNT(*) FILTER (WHERE status = 'done')        AS done,
                COUNT(*) FILTER (WHERE status = 'failed')      AS failed,
                AVG(priority_score) FILTER (WHERE status = 'pending') AS avg_priority
            FROM verification_queue
            WHERE agent_id = ?
            """,
            (self.agent_id,),
        )
        return dict(row) if row else {}

    async def clear_completed(self, older_than_days: int = 7) -> int:
        """Remove old completed/failed items from the queue."""
        async with self.db._conn.execute(
            """
            DELETE FROM verification_queue
            WHERE agent_id = ?
              AND status IN ('done', 'failed', 'skipped')
              AND completed_at < datetime('now', ?)
            """,
            (self.agent_id, f"-{older_than_days} days"),
        ) as cur:
            count = cur.rowcount
        await self.db._conn.commit()
        return count
```

```python
    # ------------------------------------------------------------------
    # HELPERS
    # ------------------------------------------------------------------

    def _record_to_queue_item(self, record: StaleFactRecord) -> QueueItem:
        """Convert a StaleFactRecord to a QueueItem."""
        source = self._pick_verifier(record)
        return QueueItem(
            agent_id=self.agent_id,
            topic_id=record.topic_id,
            fact_id=record.fact_id,
            fact_content=record.fact_content,
            priority_score=record.priority_score,
            priority_reason=self._build_reason(record),
            verification_source=source,
            source_hint=record.verification_hint,
            current_confidence=record.confidence.value,
            days_since_verified=record.days_elapsed,
        )

    def _pick_verifier(self, record: StaleFactRecord) -> str:
        """Choose the most appropriate verifier for a fact."""
        hint = record.verification_hint or ""

        if hint and any(
            hint.startswith(p) for p in ("src/", "docs/", "config/", ".")
        ):
            return "file"

        if hint.startswith("http"):
            return "url"

        return "llm"

    def _build_reason(self, record: StaleFactRecord) -> str:
        """Build a human-readable priority reason."""
        reasons = []

        if record.is_overdue:
            reasons.append("overdue")

        reasons.append(f"{record.days_elapsed:.0f}d old")
        reasons.append(f"freshness={record.freshness:.2f}")

        if record.verification_hint:
            reasons.append("has hint")

        return ", ".join(reasons)

    @staticmethod
    def _row_to_item(row: dict) -> QueueItem:
        return QueueItem(
            queue_id=row["queue_id"],
            agent_id=row["agent_id"],
            topic_id=row["topic_id"],
            fact_id=row["fact_id"],
            fact_content=row["fact_content"],
```

```
            priority_score=row["priority_score"],
            priority_reason=row["priority_reason"] or "",
            verification_source=row["verification_source"],
            source_hint=row["source_hint"],
            current_confidence=row["current_confidence"],
            days_since_verified=row["days_since_verified"],
            status=row["status"],
        )
```

---

7. Verification Audit Log

Python

```
# memograph/verification/audit_log.py
"""
Immutable verification audit log.

Every verification attempt is recorded with:
- What was verified
- What verifier was used
- What verdict was reached
- What changed (before/after)
- When and by whom

The audit log is append-only — records are never updated.
It provides complete traceability for memory changes.
"""

from __future__ import annotations

import logging
import uuid
from dataclasses import dataclass
from datetime import datetime
from typing import Optional

from memograph.db.database import DatabaseManager
from memograph.verification.sources.base import VerificationResult

logger = logging.getLogger("memograph.verification.audit")


@dataclass
class AuditEntry:
    """A single audit log entry."""
    audit_id:         str
    agent_id:         str
    topic_id:         str
    fact_id:          str
    fact_content:     str
    verifier_type:    str
    verdict:          str
```

```
    confidence_before: str
    confidence_after: str
    explanation:      str
    updated_content:  Optional[str]
    source_consulted: Optional[str]
    duration_ms:      int
    llm_tokens_used:  int
    performed_at:     datetime
    performed_by:     str
    queue_id:         Optional[str] = None
    verifier_model:   Optional[str] = None


class VerificationAuditLog:
    """
    Immutable append-only audit log for verification history.

    Usage:
        log    = VerificationAuditLog(db, agent_id="myagent")
        entry  = await log.record(
            result=verification_result,
            fact_content="...",
            confidence_before="observed",
            topic_id="...",
        )
        history = await log.get_fact_history("fact_id_123")
    """

    def __init__(
        self,
        db:       DatabaseManager,
        agent_id: str,
    ):
        self.db       = db
        self.agent_id = agent_id

    async def record(
        self,
        result:             VerificationResult,
        fact_content:       str,
        confidence_before:  str,
        topic_id:           str,
        queue_id:           Optional[str] = None,
        performed_by:       str           = "auto",
        source_consulted:   Optional[str] = None,
        verifier_model:     Optional[str] = None,
    ) -> AuditEntry:
        """
        Record a verification result to the audit log.
        Returns the created AuditEntry.
        """
        audit_id   = str(uuid.uuid4())[:12]
        performed  = datetime.now()

        entry = AuditEntry(
            audit_id=audit_id,
            agent_id=self.agent_id,
            topic_id=topic_id,
```

```
            fact_id=result.fact_id,
            fact_content=fact_content[:500],
            verifier_type=result.verifier_type,
            verdict=result.verdict.value,
            confidence_before=confidence_before,
            confidence_after=result.new_confidence,
            explanation=result.explanation[:400],
            updated_content=result.updated_content,
            source_consulted=source_consulted or result.evidence_used,
            duration_ms=result.duration_ms,
            llm_tokens_used=result.tokens_used,
            performed_at=performed,
            performed_by=performed_by,
            queue_id=queue_id,
            verifier_model=verifier_model,
        )

        await self.db.execute(
            """
            INSERT INTO verification_audit(
                agent_id, audit_id, queue_id, topic_id, fact_id,
                fact_content, verifier_type, verifier_model,
                source_consulted, verdict, confidence_before,
                confidence_after, updated_content, explanation,
                duration_ms, llm_tokens_used, performed_by
            ) VALUES (?,?,?,?,?,?,?,?,?,?,?,?,?,?,?,?,?)
            """,
            (
                self.agent_id, audit_id, queue_id,
                topic_id, result.fact_id,
                fact_content[:500],
                result.verifier_type, verifier_model,
                source_consulted or result.evidence_used,
                result.verdict.value, confidence_before,
                result.new_confidence, result.updated_content,
                result.explanation[:400],
                result.duration_ms, result.tokens_used,
                performed_by,
            ),
        )

        logger.debug(
            f"Audit recorded: [{audit_id}] {result.fact_id} "
            f"→ {result.verdict.value} "
            f"({confidence_before} → {result.new_confidence})"
        )

        return entry

    async def get_fact_history(
        self,
        fact_id: str,
        limit:   int = 20,
    ) -> list[AuditEntry]:
        """Get the full verification history for a fact."""
        rows = await self.db.fetchall(
            """
            SELECT * FROM verification_audit
```

```
            WHERE agent_id = ? AND fact_id = ?
            ORDER BY performed_at DESC
            LIMIT ?
            """,
            (self.agent_id, fact_id, limit),
        )
        return [self._row_to_entry(r) for r in rows]

    async def get_recent_verifications(
        self,
        limit:          int            = 50,
        verifier_filter: Optional[str] = None,
        verdict_filter:  Optional[str] = None,
    ) -> list[AuditEntry]:
        """Get recent verification attempts."""
        conditions = ["agent_id = ?"]
        params     = [self.agent_id]

        if verifier_filter:
            conditions.append("verifier_type = ?")
            params.append(verifier_filter)

        if verdict_filter:
            conditions.append("verdict = ?")
            params.append(verdict_filter)

        where = " AND ".join(conditions)
        rows  = await self.db.fetchall(
            f"""
            SELECT * FROM verification_audit
            WHERE {where}
            ORDER BY performed_at DESC
            LIMIT ?
            """,
            (*params, limit),
        )
        return [self._row_to_entry(r) for r in rows]

    async def get_verification_stats(self) -> dict:
        """Aggregate statistics for the verification history."""
        row = await self.db.fetchone(
            """
            SELECT
                COUNT(*)                                  AS total_verifications,
                COUNT(*) FILTER (WHERE verdict = 'confirmed')  AS confirmed,
                COUNT(*) FILTER (WHERE verdict = 'refuted')    AS refuted,
                COUNT(*) FILTER (WHERE verdict = 'outdated')   AS outdated,
                COUNT(*) FILTER (WHERE verdict = 'uncertain')  AS uncertain,
                COUNT(*) FILTER (WHERE verdict = 'error')      AS errors,
                AVG(duration_ms)                          AS avg_duration_ms,
                SUM(llm_tokens_used)                      AS total_tokens,
                COUNT(DISTINCT fact_id)                   AS unique_facts_verified
            FROM verification_audit
            WHERE agent_id = ?
            """,
            (self.agent_id,),
        )
        return dict(row) if row else {}
```

```python
    async def get_refuted_facts(self, limit: int = 20) -> list[AuditEntry]:
        """Get facts that were found to be incorrect."""
        return await self.get_recent_verifications(
            limit=limit, verdict_filter="refuted"
        )

    async def get_health_trend(self, days: int = 30) -> list[dict]:
        """Get daily verification health metrics over time."""
        rows = await self.db.fetchall(
            """
            SELECT
                date(performed_at) AS day,
                COUNT(*) AS total,
                COUNT(*) FILTER (WHERE verdict = 'confirmed') AS confirmed,
                COUNT(*) FILTER (WHERE verdict IN ('refuted','outdated')) AS bad,
                AVG(duration_ms) AS avg_ms
            FROM verification_audit
            WHERE agent_id = ?
              AND performed_at > datetime('now', ?)
            GROUP BY date(performed_at)
            ORDER BY day ASC
            """,
            (self.agent_id, f"-{days} days"),
        )
        return [dict(r) for r in rows]

    @staticmethod
    def _row_to_entry(row: dict) -> AuditEntry:
        return AuditEntry(
            audit_id=row["audit_id"],
            agent_id=row["agent_id"],
            topic_id=row["topic_id"],
            fact_id=row["fact_id"],
            fact_content=row["fact_content"],
            verifier_type=row["verifier_type"],
            verdict=row["verdict"],
            confidence_before=row["confidence_before"],
            confidence_after=row["confidence_after"],
            explanation=row["explanation"],
            updated_content=row["updated_content"],
            source_consulted=row["source_consulted"],
            duration_ms=row["duration_ms"],
            llm_tokens_used=row["llm_tokens_used"],
            performed_at=datetime.fromisoformat(row["performed_at"]),
            performed_by=row["performed_by"],
            queue_id=row.get("queue_id"),
            verifier_model=row.get("verifier_model"),
        )
```

---

8. Verification Scheduler

Python

```python
# memograph/verification/scheduler.py
"""
Async background verification scheduler.

Runs verification cycles periodically:
1. Run staleness scan
2. Build verification plan
3. Process queue in batches
4. Apply results back to memory
5. Update audit log

Designed to run alongside the Phase 3 AutoDream daemon.
They share the same DB but are independent processes.
"""

from __future__ import annotations

import asyncio
import logging
import os
import time
from dataclasses import dataclass, field
from datetime import datetime
from typing import Callable, Optional

from memograph.config import ConfidenceLevel, MemoGraphConfig
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.base import BaseLLMProvider
from memograph.verification.audit_log import VerificationAuditLog
from memograph.verification.planner import VerificationPlanner
from memograph.verification.staleness import StalenessDetector
from memograph.verification.sources.llm_verifier import LLMVerifier
from memograph.verification.sources.file_verifier import FileVerifier
from pathlib import Path

logger = logging.getLogger("memograph.verification.scheduler")


@dataclass
class SchedulerConfig:
    """Configuration for the verification scheduler."""
    # How often to run a scan (seconds)
    scan_interval_seconds:  int   = 3600          # 1 hour
    # Max facts to verify per cycle
    batch_size_per_cycle:   int   = 20
    # Max LLM calls per cycle (cost control)
    max_llm_calls_per_cycle: int  = 10
    # Minimum time between two verifications of the same fact (days)
    min_reverification_days: float = 1.0
    # Stop daemon after N consecutive errors
    max_consecutive_errors:  int  = 5
    # Error backoff seconds
    error_backoff_seconds:   int  = 300
    # Run on start (before waiting for interval)
```

```
    run_on_start:           bool  = True


@dataclass
class CycleResult:
    """Result of one verification cycle."""
    cycle_id:         str
    started_at:       datetime = field(default_factory=datetime.now)
    ended_at:         Optional[datetime] = None
    duration_ms:      int       = 0
    facts_scanned:    int       = 0
    facts_verified:   int       = 0
    facts_confirmed:  int       = 0
    facts_updated:    int       = 0
    facts_refuted:    int       = 0
    llm_calls:        int       = 0
    tokens_used:      int       = 0
    health_score:     float     = 0.0
    error:            Optional[str] = None


class VerificationScheduler:
    """
    Background verification scheduler.

    Usage:
        scheduler = VerificationScheduler(
            config=mg_config,
            db=db,
            topic_manager=topic_manager,
            llm=llm_provider,
        )
        await scheduler.start()

        # Later...
        await scheduler.trigger_now()
        await scheduler.stop()
    """

    def __init__(
        self,
        config:        MemoGraphConfig,
        db:            DatabaseManager,
        topic_manager: TopicManager,
        llm:           Optional[BaseLLMProvider] = None,
        sched_config:  Optional[SchedulerConfig] = None,
        on_cycle_done: Optional[Callable[[CycleResult], None]] = None,
    ):
        self.config        = config
        self.db            = db
        self.topic_manager = topic_manager
        self.llm           = llm
        self.sched_config  = sched_config or SchedulerConfig()
        self.on_cycle_done = on_cycle_done
        self.agent_id      = config.agent_id
        self.base_path     = Path(config.base_path)

        # Components
```

```
        self._staleness_detector = StalenessDetector(
            topic_manager=topic_manager,
            db=db,
            agent_id=self.agent_id,
        )
        self._planner = VerificationPlanner(db, self.agent_id)
        self._audit   = VerificationAuditLog(db, self.agent_id)

        # Verifiers
        self._llm_verifier = LLMVerifier(llm) if llm else None
        self._file_verifier = FileVerifier(self.base_path)

        # Runtime state
        self._task:     Optional[asyncio.Task]  = None
        self._running:  bool                    = False
        self._stop_evt  = asyncio.Event()
        self._trig_evt  = asyncio.Event()

        # Stats
        self._total_cycles    = 0
        self._total_verified  = 0
        self._consecutive_errors = 0
        self._last_cycle_at:  Optional[datetime] = None
        self._started_at:     Optional[datetime] = None

    # ------------------------------------------------------------------
    # LIFECYCLE
    # ------------------------------------------------------------------

    async def start(self) -> None:
        """Start the background scheduler."""
        if self._running:
            return

        self._running    = True
        self._stop_evt.clear()
        self._started_at = datetime.now()

        self._task = asyncio.create_task(
            self._loop(),
            name=f"memograph.verifier.{self.agent_id}",
        )
        logger.info(
            f"Verification scheduler started — "
            f"agent={self.agent_id}, "
            f"interval={self.sched_config.scan_interval_seconds}s"
        )

    async def stop(self, timeout: int = 30) -> None:
        """Gracefully stop the scheduler."""
        if not self._running:
            return

        logger.info("Stopping verification scheduler...")
        self._running = False
        self._stop_evt.set()

        if self._task:
```

```
            try:
                await asyncio.wait_for(self._task, timeout=timeout)
            except asyncio.TimeoutError:
                self._task.cancel()
                try:
                    await self._task
                except asyncio.CancelledError:
                    pass

        logger.info("Verification scheduler stopped")

    async def trigger_now(self) -> CycleResult:
        """Trigger an immediate verification cycle."""
        logger.info("Manual verification cycle triggered")
        return await self._run_cycle(triggered_manually=True)

    # ──────────────────────────────────────────────────────────────────────
    # MAIN LOOP
    # ──────────────────────────────────────────────────────────────────────

    async def _loop(self) -> None:
        """Main scheduler loop."""
        # Optionally run immediately on start
        if self.sched_config.run_on_start:
            await self._safe_run_cycle()

        while self._running and not self._stop_evt.is_set():
            try:
                # Wait for interval or manual trigger
                await self._interruptible_sleep(
                    self.sched_config.scan_interval_seconds
                )

                if self._stop_evt.is_set():
                    break

                await self._safe_run_cycle()

            except asyncio.CancelledError:
                break
            except Exception as e:
                logger.error(f"Scheduler loop error: {e}", exc_info=True)

    async def _safe_run_cycle(self) -> Optional[CycleResult]:
        """Run a cycle with error handling."""
        try:
            result = await self._run_cycle()
            self._consecutive_errors = 0
            self._total_cycles      += 1
            self._last_cycle_at      = datetime.now()

            if self.on_cycle_done:
                try:
                    self.on_cycle_done(result)
                except Exception as e:
                    logger.warning(f"on_cycle_done callback error: {e}")

            return result
```

```
        except Exception as e:
            self._consecutive_errors += 1
            logger.error(
                f"Verification cycle #{self._total_cycles} failed: {e}",
                exc_info=True,
            )

            if self._consecutive_errors >= self.sched_config.max_consecutive_errors:
                logger.critical(
                    f"Scheduler stopping after "
                    f"{self._consecutive_errors} consecutive errors"
                )
                self._running = False
                self._stop_evt.set()

            else:
                await asyncio.sleep(self.sched_config.error_backoff_seconds)

            return None

    # ─────────────────────────────────────────────────────────────────────
    # CORE CYCLE
    # ─────────────────────────────────────────────────────────────────────

    async def _run_cycle(
        self,
        triggered_manually: bool = False,
    ) -> CycleResult:
        """
        One complete verification cycle:
        1. Scan for stale facts
        2. Build verification plan
        3. Process queue batch
        4. Apply results to memory
        """
        import uuid
        cycle_id = str(uuid.uuid4())[:8]
        t0       = time.monotonic()

        logger.info(
            f"[{cycle_id}] Verification cycle starting "
            f"({'manual' if triggered_manually else 'scheduled'})"
        )

        result = CycleResult(cycle_id=cycle_id)

        # Step 1: Staleness scan
        staleness_report = await self._staleness_detector.scan(
            update_db=True
        )
        result.facts_scanned = staleness_report.scanned_facts
        result.health_score  = staleness_report.health_score

        logger.info(
            f"[{cycle_id}] Scan complete: "
            f"{staleness_report.total_stale} stale, "
            f"health={staleness_report.health_score:.1%}"
```

```
        )

        if staleness_report.total_stale == 0 and not triggered_manually:
            result.ended_at    = datetime.now()
            result.duration_ms = int((time.monotonic() - t0) * 1000)
            logger.info(f"[{cycle_id}] No stale facts — skipping verification")
            return result

        # Step 2: Build and enqueue plan
        plan = await self._planner.build_plan(
            report=staleness_report,
            include_near_stale=True,
        )
        await self._planner.enqueue(plan)

        # Step 3: Process queue
        llm_calls_used = 0
        batch = await self._planner.get_next_batch(
            batch_size=self.sched_config.batch_size_per_cycle
        )

        for item in batch:
            if llm_calls_used >= self.sched_config.max_llm_calls_per_cycle:
                logger.info(
                    f"[{cycle_id}] LLM call limit reached "
                    f"({self.sched_config.max_llm_calls_per_cycle}) — stopping"
                )
                break

            ver_result = await self._verify_item(item)
            result.facts_verified += 1

            if ver_result.verdict.value == "confirmed":
                result.facts_confirmed += 1
            elif ver_result.verdict.value in ("refuted", "outdated"):
                result.facts_refuted   += 1

            if ver_result.tokens_used > 0:
                llm_calls_used   += 1
                result.llm_calls += 1
                result.tokens_used += ver_result.tokens_used

            # Step 4: Apply result to memory
            if ver_result.should_update or ver_result.refuted:
                updated = await self._apply_result(item, ver_result)
                if updated:
                    result.facts_updated += 1

            # Log to audit trail
            await self._audit.record(
                result=ver_result,
                fact_content=item.fact_content,
                confidence_before=item.current_confidence,
                topic_id=item.topic_id,
                queue_id=item.queue_id,
            )

            # Mark queue item done
```

```
            await self._planner.mark_done(item.queue_id, success=True)

        result.ended_at    = datetime.now()
        result.duration_ms = int((time.monotonic() - t0) * 1000)
        self._total_verified += result.facts_verified

        logger.info(
            f"[{cycle_id}] Cycle complete in {result.duration_ms}ms — "
            f"verified={result.facts_verified}, "
            f"confirmed={result.facts_confirmed}, "
            f"updated={result.facts_updated}, "
            f"tokens={result.tokens_used}"
        )

        return result

    async def _verify_item(self, item) -> "VerificationResult":
        """Route a queue item to the appropriate verifier."""
        from memograph.verification.sources.base import (
            VerificationResult,
            VerificationVerdict,
        )

        # Choose verifier based on source type
        if item.verification_source == "file" and item.source_hint:
            can_verify = await self._file_verifier.can_verify(
                item.fact_content, item.source_hint
            )
            if can_verify:
                return await self._file_verifier.verify(
                    fact_id=item.fact_id,
                    fact_content=item.fact_content,
                    current_confidence=item.current_confidence,
                    source_hint=item.source_hint,
                )

        # Fall back to LLM verifier
        if self._llm_verifier:
            return await self._llm_verifier.verify(
                fact_id=item.fact_id,
                fact_content=item.fact_content,
                current_confidence=item.current_confidence,
                source_hint=item.source_hint,
                days_since_verified=item.days_since_verified,
                source=item.source_hint or "",
            )

        # No verifier available
        return VerificationResult(
            fact_id=item.fact_id,
            verdict=VerificationVerdict.NOT_VERIFIABLE,
            new_confidence=item.current_confidence,
            explanation="No verifier available for this fact",
            verifier_type="none",
        )

    async def _apply_result(self, item, result) -> bool:
        """
```

```
        Apply a verification result back to the topic file.
        Updates confidence and content if needed.
        """
        topic = await self.topic_manager.get_topic(item.topic_id)
        if not topic:
            return False

        fact = topic.get_fact(item.fact_id)
        if not fact:
            return False

        changed = False

        # Update confidence
        try:
            new_conf = ConfidenceLevel(result.new_confidence)
            if new_conf != fact.confidence:
                fact.confidence    = new_conf
                fact.last_verified = datetime.now()
                changed = True
        except ValueError:
            pass

        # Update content if refuted/outdated
        if result.should_update and result.updated_content:
            fact.content       = result.updated_content[:200]
            fact.last_verified = datetime.now()
            changed            = True

        if changed:
            await self.topic_manager.save_topic(topic)
            logger.debug(
                f"Applied verification: {item.fact_id} → "
                f"{result.new_confidence}"
            )

        return changed

    async def _interruptible_sleep(self, seconds: float) -> None:
        """Sleep but wake early on stop or trigger signal."""
        try:
            await asyncio.wait_for(
                asyncio.ensure_future(
                    asyncio.gather(
                        self._stop_evt.wait(),
                        self._trig_evt.wait(),
                        return_exceptions=True,
                    )
                ),
                timeout=seconds,
            )
            self._trig_evt.clear()
        except asyncio.TimeoutError:
            pass

    # ──────────────────────────────────────────────────────────────────
    # STATUS
    # ──────────────────────────────────────────────────────────────────
```

```
    def get_stats(self) -> dict:
        return {
            "running":            self._running,
            "started_at":         str(self._started_at),
            "total_cycles":       self._total_cycles,
            "total_verified":     self._total_verified,
            "consecutive_errors": self._consecutive_errors,
            "last_cycle_at":      str(self._last_cycle_at),
            "agent_id":           self.agent_id,
            "scan_interval_s":    self.sched_config.scan_interval_seconds,
        }
```

---

9. Skeptical Memory Enforcer

Python

```
# memograph/verification/enforcer.py
"""
Skeptical Memory Enforcer.

Injects skeptical framing into every LLM context.
Core principle from the Claude Code leak:
"Memory is treated as a hint, not as truth.
 The agent verifies before using it."

The enforcer:
1. Wraps every recalled fact with appropriate skepticism
2. Escalates urgency for stale/unverified facts
3. Injects actionable verification reminders
4. Tracks whether verification suggestions are acted on
"""

from __future__ import annotations

import logging
from dataclasses import dataclass, field
from datetime import datetime
from typing import Optional

from memograph.config import ConfidenceLevel
from memograph.models.topic import MemoryFact, TopicFile
from memograph.verification.decay import ConfidenceDecayModel, FactDomain
from memograph.verification.staleness import StalenessDetector

logger = logging.getLogger("memograph.verification.enforcer")


# Skepticism levels — how strongly to flag a fact
class SkepticismLevel:
    TRUST      = "trust"       # Verified + fresh → use directly
    HINT       = "hint"        # Observed + moderately fresh → treat as hint
```

```
    CAUTION    = "caution"      # Inferred or aging → verify before use
    WARNING    = "warning"      # Stale or old → strong warning
    BLOCK      = "block"        # Critically stale → do not use without verifying


# Framing templates for each skepticism level
SKEPTICISM_FRAMES = {
    SkepticismLevel.TRUST: (
        "✅",
        "VERIFIED",
        "",                     # No extra framing needed
    ),
    SkepticismLevel.HINT: (
        "👁️",
        "HINT",
        "(treat as likely accurate, verify for critical decisions)",
    ),
    SkepticismLevel.CAUTION: (
        "⚠️",
        "CAUTION",
        "(verify before acting — may be outdated)",
    ),
    SkepticismLevel.WARNING: (
        "🚫",
        "STALE WARNING",
        "(HIGH RISK — fact is stale, do not rely on this without re-verifying)",
    ),
    SkepticismLevel.BLOCK: (
        "🔴",
        "DO NOT USE",
        "(CRITICALLY STALE — this fact is unreliable, verify from primary source first)",
    ),
}

# Verification action injections
VERIFICATION_ACTIONS = {
    SkepticismLevel.HINT: (
        "Before relying on this: confirm it's still accurate."
    ),
    SkepticismLevel.CAUTION: (
        "⚠️ VERIFY THIS FIRST: {hint_or_default}"
    ),
    SkepticismLevel.WARNING: (
        "🚫 STOP — Do not proceed until this is verified: {hint_or_default}"
    ),
    SkepticismLevel.BLOCK: (
        "🔴 BLOCK — This memory is unreliable. Check primary source: {hint_or_default}"
    ),
}


@dataclass
class SkepticalFact:
    """A fact wrapped with skeptical framing."""
    fact:              MemoryFact
    topic_id:          str
    skepticism_level:  str
    freshness:         float
```

```
    days_elapsed:      float
    framed_text:       str        # Ready-to-inject formatted text
    action_required:   Optional[str]   # Verification action to suggest
    should_block:      bool       # True if context should warn strongly


@dataclass
class SkepticalContext:
    """
    A full topic's facts wrapped with skeptical framing.
    Ready for injection into LLM context.
    """
    topic_id:        str
    topic_name:      str
    facts:           list[SkepticalFact]
    overall_health:  float       # 0.0-1.0
    has_blocks:      bool        # Any facts with BLOCK level?
    formatted_text:  str         # Full formatted output


class SkepticalMemoryEnforcer:
    """
    Wraps memory facts with appropriate skeptical framing.

    Determines how strongly to flag each fact based on:
    - Current confidence level
    - Freshness (via decay model)
    - Presence of verification hint
    - How critical the fact appears to be

    Usage:
        enforcer = SkepticalMemoryEnforcer()
        ctx      = enforcer.wrap_topic(topic, staleness_detector)
        # Inject ctx.formatted_text into your LLM system prompt
    """

    # Freshness thresholds for skepticism levels
    FRESHNESS_THRESHOLDS = {
        ConfidenceLevel.VERIFIED: {
            SkepticismLevel.TRUST:    0.7,
            SkepticismLevel.HINT:     0.4,
            SkepticismLevel.CAUTION:  0.2,
            SkepticismLevel.WARNING:  0.05,
            SkepticismLevel.BLOCK:    0.0,
        },
        ConfidenceLevel.OBSERVED: {
            SkepticismLevel.TRUST:    0.8,   # Never "trust" an observed fact
            SkepticismLevel.HINT:     0.5,
            SkepticismLevel.CAUTION:  0.25,
            SkepticismLevel.WARNING:  0.1,
            SkepticismLevel.BLOCK:    0.0,
        },
        ConfidenceLevel.INFERRED: {
            SkepticismLevel.TRUST:    1.1,   # Never "trust" an inferred fact
            SkepticismLevel.HINT:     0.7,
            SkepticismLevel.CAUTION:  0.4,
            SkepticismLevel.WARNING:  0.15,
            SkepticismLevel.BLOCK:    0.0,
```

```
        },
        ConfidenceLevel.STALE: {
            SkepticismLevel.TRUST:    1.1,
            SkepticismLevel.HINT:     1.1,
            SkepticismLevel.CAUTION:  1.1,
            SkepticismLevel.WARNING:  0.05,
            SkepticismLevel.BLOCK:    0.0,
        },
    }

    def __init__(
        self,
        decay_model: Optional[ConfidenceDecayModel] = None,
    ):
        self.decay_model = decay_model or ConfidenceDecayModel()

    def wrap_topic(
        self,
        topic:             TopicFile,
        max_block_age_days: float = 60.0,
    ) -> SkepticalContext:
        """
        Wrap all facts in a topic with skeptical framing.
        Returns a SkepticalContext ready for injection.
        """
        wrapped_facts: list[SkepticalFact] = []
        has_blocks = False

        for fact in topic.facts:
            skeptical_fact = self.wrap_fact(fact, topic.topic_id, max_block_age_days)
            wrapped_facts.append(skeptical_fact)
            if skeptical_fact.should_block:
                has_blocks = True

        # Overall health = average freshness
        overall_health = (
            sum(f.freshness for f in wrapped_facts) / len(wrapped_facts)
            if wrapped_facts else 1.0
        )

        formatted = self._format_skeptical_topic(
            topic=topic,
            wrapped_facts=wrapped_facts,
            overall_health=overall_health,
        )

        return SkepticalContext(
            topic_id=topic.topic_id,
            topic_name=topic.topic_name,
            facts=wrapped_facts,
            overall_health=overall_health,
            has_blocks=has_blocks,
            formatted_text=formatted,
        )

    def wrap_fact(
        self,
        fact:               MemoryFact,
```

```
        topic_id:           str,
        max_block_age_days: float = 60.0,
    ) -> SkepticalFact:
        """Wrap a single fact with skeptical framing."""
        # Compute decay
        decay = self.decay_model.compute_decay(
            fact_id=fact.fact_id,
            topic_id=topic_id,
            confidence=fact.confidence,
            last_verified=fact.last_verified,
            created_at=fact.created_at,
        )

        # Determine skepticism level
        level = self._determine_level(fact.confidence, decay.freshness)

        # Build framing
        emoji, label, annotation = SKEPTICISM_FRAMES[level]
        framed = f"{emoji} `{fact.fact_id}` **{label}**: {fact.content}"

        if annotation:
            framed += f"\n   _{annotation}_"

        if fact.source:
            framed += f"\n   Source: `{fact.source}`"

        if fact.last_verified:
            framed += (
                f"\n   Last verified: "
                f"{fact.last_verified.strftime('%Y-%m-%d')}"
            )

        if fact.verification_hint and level in (
            SkepticismLevel.CAUTION,
            SkepticismLevel.WARNING,
            SkepticismLevel.BLOCK,
        ):
            framed += f"\n   Verify via: {fact.verification_hint}"

        # Build action
        action = None
        action_template = VERIFICATION_ACTIONS.get(level)
        if action_template:
            hint_or_default = (
                fact.verification_hint
                or f"verify {fact.content[:50]}... from primary source"
            )
            action = action_template.format(hint_or_default=hint_or_default)

        should_block = level in (SkepticismLevel.WARNING, SkepticismLevel.BLOCK)

        return SkepticalFact(
            fact=fact,
            topic_id=topic_id,
            skepticism_level=level,
            freshness=decay.freshness,
            days_elapsed=decay.days_elapsed,
            framed_text=framed,
```

```
            action_required=action,
            should_block=should_block,
        )

    def build_verification_reminder(
        self,
        skeptical_facts: list[SkepticalFact],
    ) -> Optional[str]:
        """
        Build a consolidated verification reminder for the LLM.
        Only includes facts that need action.
        """
        actions = [
            f.action_required
            for f in skeptical_facts
            if f.action_required
        ]

        if not actions:
            return None

        lines = [
            "## ⚠️ Verification Required Before Proceeding",
            "",
            "The following memory facts require verification:",
        ]
        for i, action in enumerate(actions[:5], 1):
            lines.append(f"  {i}. {action}")

        if len(actions) > 5:
            lines.append(f"  ... and {len(actions) - 5} more")

        lines.extend([
            "",
            "Do not use flagged facts without verifying them first.",
        ])

        return "\n".join(lines)

    def get_memory_health_banner(
        self,
        health_score: float,
        stale_count:  int,
    ) -> str:
        """Generate a health banner for the memory context header."""
        if health_score >= 0.9:
            return f"🟢 Memory health: GOOD ({health_score:.0%})"
        elif health_score >= 0.7:
            return (
                f"🟡 Memory health: FAIR ({health_score:.0%}) — "
                f"{stale_count} stale fact(s)"
            )
        elif health_score >= 0.5:
            return (
                f"🟠 Memory health: DEGRADED ({health_score:.0%}) — "
                f"{stale_count} stale fact(s) need verification"
            )
        else:
```

```
            return (
                f"🔴 Memory health: POOR ({health_score:.0%}) — "
                f"{stale_count} stale fact(s) — "
                f"verify before relying on memory"
            )

    # ──────────────────────────────────────────────────────────────────────
    # PRIVATE
    # ──────────────────────────────────────────────────────────────────────

    def _determine_level(
        self,
        confidence: ConfidenceLevel,
        freshness:  float,
    ) -> str:
        """Map (confidence, freshness) → skepticism level."""
        thresholds = self.FRESHNESS_THRESHOLDS.get(
            confidence,
            self.FRESHNESS_THRESHOLDS[ConfidenceLevel.OBSERVED],
        )

        # Check from most trusting to most skeptical
        if freshness >= thresholds[SkepticismLevel.TRUST]:
            return SkepticismLevel.TRUST
        elif freshness >= thresholds[SkepticismLevel.HINT]:
            return SkepticismLevel.HINT
        elif freshness >= thresholds[SkepticismLevel.CAUTION]:
            return SkepticismLevel.CAUTION
        elif freshness >= thresholds[SkepticismLevel.WARNING]:
            return SkepticismLevel.WARNING
        else:
            return SkepticismLevel.BLOCK

    def _format_skeptical_topic(
        self,
        topic:         TopicFile,
        wrapped_facts: list[SkepticalFact],
        overall_health: float,
    ) -> str:
        """Format a full topic with skeptical framing."""
        health_banner = self.get_memory_health_banner(
            overall_health,
            sum(1 for f in wrapped_facts if f.should_block),
        )

        lines = [
            f"### 📂 {topic.topic_name} (`{topic.topic_id}`)",
            f"   {health_banner}",
            "",
        ]

        # Sort by skepticism (most critical first)
        level_order = {
            SkepticismLevel.BLOCK:   0,
            SkepticismLevel.WARNING: 1,
            SkepticismLevel.CAUTION: 2,
            SkepticismLevel.HINT:    3,
            SkepticismLevel.TRUST:   4,
```

```
        }
        sorted_facts = sorted(
            wrapped_facts,
            key=lambda f: level_order.get(f.skepticism_level, 99),
        )

        for sf in sorted_facts:
            lines.append(sf.framed_text)
            lines.append("")

        # Add consolidated verification reminder if any blocks/warnings
        critical = [f for f in wrapped_facts if f.should_block]
        if critical:
            reminder = self.build_verification_reminder(critical)
            if reminder:
                lines.append(reminder)

        return "\n".join(lines)
```

---

10. Verification Engine — Unified Entry Point

Python

```
# memograph/verification/__init__.py
"""
Phase 6 Verification Engine — unified entry point.
"""

from __future__ import annotations

import logging
from pathlib import Path
from typing import Optional

from memograph.config import MemoGraphConfig
from memograph.core.topic_manager import TopicManager
from memograph.db.database import DatabaseManager
from memograph.llm.base import BaseLLMProvider
from memograph.verification.audit_log import VerificationAuditLog
from memograph.verification.decay import ConfidenceDecayModel, DecayConfig
from memograph.verification.enforcer import SkepticalMemoryEnforcer
from memograph.verification.planner import VerificationPlanner
from memograph.verification.scheduler import (
    CycleResult,
    SchedulerConfig,
    VerificationScheduler,
)
from memograph.verification.staleness import StalenessDetector, StalenessReport
```

```python
logger = logging.getLogger("memograph.verification")


class VerificationEngine:
    """
    Unified verification engine for Phase 6.

    Provides:
    - Staleness scanning
    - Verification scheduling
    - Skeptical context formatting
    - Full audit trail

    Usage:
        engine = VerificationEngine(
            config=mg_config,
            db=db,
            topic_manager=topic_manager,
            llm=llm_provider,
        )
        await engine.initialize()

        # Scan for stale facts
        report = await engine.scan()

        # Trigger immediate verification
        result = await engine.verify_now()

        # Wrap a topic with skeptical framing
        ctx = engine.wrap_topic(topic)
        print(ctx.formatted_text)
    """

    def __init__(
        self,
        config:        MemoGraphConfig,
        db:            DatabaseManager,
        topic_manager: TopicManager,
        llm:           Optional[BaseLLMProvider] = None,
        sched_config:  Optional[SchedulerConfig] = None,
        decay_config:  Optional[DecayConfig]     = None,
    ):
        self.config        = config
        self.db            = db
        self.topic_manager = topic_manager
        self.llm           = llm
        self.agent_id      = config.agent_id

        self.decay_model = ConfidenceDecayModel(decay_config)
        self.enforcer    = SkepticalMemoryEnforcer(self.decay_model)
        self.audit       = VerificationAuditLog(db, self.agent_id)

        self.staleness_detector = StalenessDetector(
            topic_manager=topic_manager,
            db=db,
            agent_id=self.agent_id,
            decay_config=decay_config,
```

```
        )
        self.planner = VerificationPlanner(db, self.agent_id)

        self.scheduler = VerificationScheduler(
            config=config,
            db=db,
            topic_manager=topic_manager,
            llm=llm,
            sched_config=sched_config,
        )

        self._initialized = False

    async def initialize(self) -> None:
        """Start background scheduler if auto_consolidate is enabled."""
        if self._initialized:
            return

        if self.config.auto_consolidate and self.llm:
            await self.scheduler.start()
            logger.info("Verification scheduler started")

        self._initialized = True

    async def close(self) -> None:
        """Stop scheduler and clean up."""
        if self.scheduler._running:
            await self.scheduler.stop()

    # ── Convenience API ──────────────────────────────────────────────

    async def scan(self) -> StalenessReport:
        """Run a staleness scan."""
        return await self.staleness_detector.scan()

    async def verify_now(self) -> CycleResult:
        """Trigger immediate verification cycle."""
        return await self.scheduler.trigger_now()

    def wrap_topic(self, topic) -> "SkepticalContext":
        """Wrap a topic with skeptical framing."""
        return self.enforcer.wrap_topic(topic)

    async def get_audit_stats(self) -> dict:
        """Get verification audit statistics."""
        return await self.audit.get_verification_stats()

    async def get_queue_stats(self) -> dict:
        """Get verification queue statistics."""
        return await self.planner.get_queue_stats()

    def get_scheduler_stats(self) -> dict:
        """Get scheduler runtime statistics."""
        return self.scheduler.get_stats()

    async def status(self) -> dict:
        """Full verification engine status."""
        return {
```

```
            "agent_id":        self.agent_id,
            "scheduler":       self.get_scheduler_stats(),
            "queue":           await self.get_queue_stats(),
            "audit":           await self.get_audit_stats(),
            "decay_thresholds": {
                conf.value: round(
                    self.decay_model.days_to_stale(conf), 1
                )
                for conf in ["verified", "observed", "inferred"]
                if hasattr(conf, 'value')
            },
        }

    async def __aenter__(self) -> "VerificationEngine":
        await self.initialize()
        return self

    async def __aexit__(self, *args) -> None:
        await self.close()
```

---

11. Full Phase 6 Test Suite

Python

```
# tests/test_decay.py

import math
import pytest
from datetime import datetime, timedelta
from memograph.config import ConfidenceLevel
from memograph.verification.decay import (
    ConfidenceDecayModel,
    DecayConfig,
    FactDomain,
    SourceReliability,
    STALENESS_THRESHOLD,
)


def test_decay_fresh_fact():
    model  = ConfidenceDecayModel()
    result = model.compute_decay(
        fact_id="f1",
        topic_id="t1",
        confidence=ConfidenceLevel.VERIFIED,
        last_verified=datetime.now(),    # Just verified
    )
    assert result.freshness > 0.9
    assert not result.is_stale


def test_decay_old_fact_goes_stale():
```

```
    model  = ConfidenceDecayModel()
    result = model.compute_decay(
        fact_id="f1",
        topic_id="t1",
        confidence=ConfidenceLevel.INFERRED,
        last_verified=datetime.now() - timedelta(days=30),
    )
    assert result.is_stale
    assert result.freshness < STALENESS_THRESHOLD


def test_decay_never_verified():
    model  = ConfidenceDecayModel()
    result = model.compute_decay(
        fact_id="f1",
        topic_id="t1",
        confidence=ConfidenceLevel.OBSERVED,
        last_verified=None,
        created_at=datetime.now() - timedelta(days=20),
    )
    assert result.days_elapsed >= 20


def test_decay_source_reliability_extends_half_life():
    model   = ConfidenceDecayModel()
    r_primary = model.compute_decay(
        "f1", "t1", ConfidenceLevel.OBSERVED,
        last_verified=datetime.now() - timedelta(days=7),
        source_reliability=SourceReliability.PRIMARY,
    )
    r_inferred = model.compute_decay(
        "f1", "t1", ConfidenceLevel.OBSERVED,
        last_verified=datetime.now() - timedelta(days=7),
        source_reliability=SourceReliability.INFERRED,
    )
    # Primary source has longer half-life → higher freshness at same age
    assert r_primary.freshness > r_inferred.freshness


def test_decay_domain_affects_half_life():
    model    = ConfidenceDecayModel()
    r_arch   = model.compute_decay(
        "f1", "t1", ConfidenceLevel.OBSERVED,
        last_verified=datetime.now() - timedelta(days=10),
        domain=FactDomain.ARCHITECTURAL,
    )
    r_ephemeral = model.compute_decay(
        "f1", "t1", ConfidenceLevel.OBSERVED,
        last_verified=datetime.now() - timedelta(days=10),
        domain=FactDomain.EPHEMERAL,
    )
    # Architectural decays slower than ephemeral
    assert r_arch.freshness > r_ephemeral.freshness


def test_decay_stale_always_stale():
    model  = ConfidenceDecayModel()
    result = model.compute_decay(
```

```
        "f1", "t1", ConfidenceLevel.STALE,
        last_verified=datetime.now(),    # Even if just "verified"
    )
    assert result.is_stale


def test_days_to_stale():
    model = ConfidenceDecayModel()
    d = model.days_to_stale(ConfidenceLevel.VERIFIED)
    assert d > 30    # Verified facts last a long time

    d_inf = model.days_to_stale(ConfidenceLevel.INFERRED)
    assert d_inf < d  # Inferred goes stale faster


def test_decay_curve_descending():
    model = ConfidenceDecayModel()
    curve = model.generate_decay_schedule(
        ConfidenceLevel.OBSERVED,
        FactDomain.GENERAL,
        days_ahead=30,
        points=10,
    )
    # Freshness should decrease monotonically
    for i in range(len(curve) - 1):
        assert curve[i][1] >= curve[i + 1][1]


def test_batch_compute():
    model = ConfidenceDecayModel()
    facts = [
        {
            "fact_id": "f1",
            "topic_id": "t1",
            "confidence": "observed",
            "last_verified": datetime.now() - timedelta(days=5),
        },
        {
            "fact_id": "f2",
            "topic_id": "t1",
            "confidence": "stale",
            "last_verified": None,
        },
    ]
    results = model.compute_batch(facts)
    assert len(results) == 2
    assert results[1].is_stale   # Stale is always stale
```

Python

```
# tests/test_staleness.py

import pytest
from datetime import datetime, timedelta
from unittest.mock import AsyncMock, MagicMock, patch
from memograph.config import ConfidenceLevel
```

```python
from memograph.models.topic import MemoryFact, TopicFile
from memograph.verification.staleness import StalenessDetector


@pytest.fixture
def mock_topic_manager():
    mgr = MagicMock()

    topic_fresh = TopicFile(topic_id="fresh_topic", topic_name="Fresh")
    topic_fresh.facts = [
        MemoryFact(
            content="Fresh fact",
            confidence=ConfidenceLevel.VERIFIED,
            source="test",
            last_verified=datetime.now(),
        )
    ]

    topic_stale = TopicFile(topic_id="stale_topic", topic_name="Stale")
    topic_stale.facts = [
        MemoryFact(
            content="Old inferred fact",
            confidence=ConfidenceLevel.INFERRED,
            source="inference",
            created_at=datetime.now() - timedelta(days=30),
            last_verified=None,
        )
    ]

    async def get_topic(topic_id):
        if topic_id == "fresh_topic":
            return topic_fresh
        if topic_id == "stale_topic":
            return topic_stale
        return None

    mgr.get_topic = get_topic
    return mgr


@pytest.fixture
def mock_db():
    db = MagicMock()
    db.get_topics            = AsyncMock(return_value=[
        {"topic_id": "fresh_topic"},
        {"topic_id": "stale_topic"},
    ])
    db.update_fact_confidence = AsyncMock()
    db.execute               = AsyncMock()
    return db


@pytest.mark.asyncio
async def test_scan_finds_stale_facts(mock_topic_manager, mock_db):
    detector = StalenessDetector(
        topic_manager=mock_topic_manager,
        db=mock_db,
        agent_id="test",
```

```
    )
    report = await detector.scan(update_db=False)

    assert report.scanned_facts == 2
    assert len(report.stale_facts) >= 1
    stale_ids = [f.fact_id for f in report.stale_facts]
    # The inferred fact should be stale
    assert any(report.stale_facts)


@pytest.mark.asyncio
async def test_scan_health_score(mock_topic_manager, mock_db):
    detector = StalenessDetector(
        topic_manager=mock_topic_manager,
        db=mock_db,
        agent_id="test",
    )
    report = await detector.scan(update_db=False)
    assert 0.0 <= report.health_score <= 1.0


@pytest.mark.asyncio
async def test_scan_specific_topics(mock_topic_manager, mock_db):
    detector = StalenessDetector(
        topic_manager=mock_topic_manager,
        db=mock_db,
        agent_id="test",
    )
    # Only scan fresh topic
    report = await detector.scan(
        topic_ids=["fresh_topic"],
        update_db=False,
    )
    assert report.scanned_topics == 1
    assert report.health_score >= 0.8   # Should be mostly fresh


def test_apply_decay_to_topic():
    from memograph.verification.staleness import StalenessDetector
    from unittest.mock import MagicMock

    detector = StalenessDetector(
        topic_manager=MagicMock(),
        db=MagicMock(),
        agent_id="test",
    )

    topic = TopicFile(topic_id="t1", topic_name="T1")
    topic.facts = [
        MemoryFact(
            content="Old inferred fact",
            confidence=ConfidenceLevel.INFERRED,
            source="guess",
            created_at=datetime.now() - timedelta(days=30),
        )
    ]

    updated, results = detector.apply_decay_to_topic(topic, mutate=True)
```

```
    assert results[0].is_stale

    assert updated.facts[0].confidence == ConfidenceLevel.STALE
```

Python

```
# tests/test_planner.py

import pytest
from unittest.mock import AsyncMock, MagicMock
from datetime import datetime
from memograph.verification.planner import VerificationPlanner, QueueItem
from memograph.verification.staleness import StalenessReport, StaleFactRecord
from memograph.config import ConfidenceLevel
from memograph.verification.decay import DecayResult, FactDomain


def make_stale_record(
    fact_id:  str,
    topic_id: str,
    priority: float = 0.7,
    hint:     str   = None,
) -> StaleFactRecord:
    from memograph.verification.decay import ConfidenceDecayModel
    model = ConfidenceDecayModel()
    decay = model.compute_decay(
        fact_id=fact_id,
        topic_id=topic_id,
        confidence=ConfidenceLevel.STALE,
        last_verified=None,
    )
    return StaleFactRecord(
        fact_id=fact_id,
        topic_id=topic_id,
        fact_content=f"Content for {fact_id}",
        confidence=ConfidenceLevel.STALE,
        freshness=0.1,
        days_elapsed=30.0,
        days_until_stale=None,
        is_overdue=True,
        priority_score=priority,
        source="test",
        verification_hint=hint,
        decay_result=decay,
    )


@pytest.fixture
def mock_db():
    db = MagicMock()
    db.execute    = AsyncMock()
    db.fetchall   = AsyncMock(return_value=[])
    db.fetchone   = AsyncMock(return_value={"pending": 0, "done": 0, "failed": 0,
"avg_priority": 0})
    db._conn      = MagicMock()
    db._conn.execute = AsyncMock()
```

```
    db._conn.commit  = AsyncMock()
    return db


@pytest.mark.asyncio
async def test_build_plan_from_report(mock_db):
    planner = VerificationPlanner(mock_db, "agent1")

    report = StalenessReport(
        agent_id="agent1",
        scanned_topics=3,
        scanned_facts=10,
        stale_facts=[
            make_stale_record("f1", "t1", priority=0.9),
            make_stale_record("f2", "t2", priority=0.6),
        ],
        near_stale_facts=[
            make_stale_record("f3", "t3", priority=0.4),
        ],
        health_score=0.7,
    )

    plan = await planner.build_plan(report)
    assert plan.total_items == 3
    # Sorted by priority
    assert plan.queue_items[0].priority_score >= plan.queue_items[1].priority_score


@pytest.mark.asyncio
async def test_build_plan_picks_correct_verifier(mock_db):
    planner = VerificationPlanner(mock_db, "agent1")

    report = StalenessReport(
        agent_id="agent1",
        scanned_topics=1,
        scanned_facts=2,
        stale_facts=[
            make_stale_record("f1", "t1", hint="src/auth.py"),
            make_stale_record("f2", "t2", hint=None),
        ],
        near_stale_facts=[],
        health_score=0.5,
    )

    plan = await planner.build_plan(report)
    sources = {i.fact_id: i.verification_source for i in plan.queue_items}
    assert sources["f1"] == "file"    # Has file hint
    assert sources["f2"] == "llm"     # No hint → LLM


@pytest.mark.asyncio
async def test_enqueue_calls_db(mock_db):
    planner = VerificationPlanner(mock_db, "agent1")

    report = StalenessReport(
        agent_id="agent1",
        scanned_topics=1,
        scanned_facts=3,
```

```
        stale_facts=[make_stale_record("f1", "t1")],
        near_stale_facts=[],
        health_score=0.5,
    )
    plan = await planner.build_plan(report)
    count = await planner.enqueue(plan)

    assert count == 1
    assert mock_db.execute.called


@pytest.mark.asyncio
async def test_high_priority_separation(mock_db):
    planner = VerificationPlanner(mock_db, "agent1")

    items = [
        QueueItem(priority_score=0.9, fact_id="high1"),
        QueueItem(priority_score=0.5, fact_id="med1"),
        QueueItem(priority_score=0.2, fact_id="low1"),
    ]

    from memograph.verification.planner import VerificationPlan
    plan = VerificationPlan(
        agent_id="agent1",
        total_items=3,
        queue_items=items,
        estimated_llm_calls=2,
        estimated_tokens=800,
    )

    assert len(plan.high_priority(0.7)) == 1
    assert len(plan.medium_priority()) == 1

    assert len(plan.low_priority()) == 1
```

Python

```
# tests/test_audit_log.py

import pytest
from datetime import datetime
from unittest.mock import AsyncMock, MagicMock
from memograph.verification.audit_log import VerificationAuditLog
from memograph.verification.sources.base import (
    VerificationResult,
    VerificationVerdict,
)


@pytest.fixture
def mock_db():
    db                  = MagicMock()
    db.execute          = AsyncMock()
    db.fetchall         = AsyncMock(return_value=[])
    db.fetchone         = AsyncMock(return_value=None)
    return db
```

```python
@pytest.mark.asyncio
async def test_record_verification(mock_db):
    log    = VerificationAuditLog(mock_db, "agent1")
    result = VerificationResult(
        fact_id="f1",
        verdict=VerificationVerdict.CONFIRMED,
        new_confidence="verified",
        explanation="Found in src/auth.py — still accurate",
        verifier_type="file",
        duration_ms=45,
    )

    entry = await log.record(
        result=result,
        fact_content="Uses JWT RS256",
        confidence_before="observed",
        topic_id="auth_system",
    )

    assert entry.fact_id == "f1"
    assert entry.verdict == "confirmed"
    assert entry.confidence_before == "observed"
    assert entry.confidence_after == "verified"
    assert mock_db.execute.called


@pytest.mark.asyncio
async def test_record_refuted_fact(mock_db):
    log    = VerificationAuditLog(mock_db, "agent1")
    result = VerificationResult(
        fact_id="f2",
        verdict=VerificationVerdict.REFUTED,
        new_confidence="stale",
        explanation="Port changed from 8080 to 9000 in config",
        updated_content="Server runs on port 9000",
        should_update=True,
        verifier_type="llm",
        duration_ms=230,
        tokens_used=380,
    )

    entry = await log.record(
        result=result,
        fact_content="Server runs on port 8080",
        confidence_before="observed",
        topic_id="deployment",
    )

    assert entry.verdict == "refuted"
    assert entry.updated_content == "Server runs on port 9000"


# tests/test_enforcer.py

import pytest
from datetime import datetime, timedelta
```

```python
from memograph.config import ConfidenceLevel
from memograph.models.topic import MemoryFact, TopicFile
from memograph.verification.enforcer import (
    SkepticalMemoryEnforcer,
    SkepticismLevel,
)


@pytest.fixture
def enforcer():
    return SkepticalMemoryEnforcer()


def make_fact(
    content:     str,
    confidence:  ConfidenceLevel,
    days_old:    float = 0,
    hint:        str   = None,
) -> MemoryFact:
    return MemoryFact(
        content=content,
        confidence=confidence,
        source="test",
        last_verified=(
            datetime.now() - timedelta(days=days_old)
            if days_old > 0 else datetime.now()
        ),
        verification_hint=hint,
    )


def test_fresh_verified_is_trust(enforcer):
    fact      = make_fact("Uses FastAPI", ConfidenceLevel.VERIFIED, days_old=1)
    sf        = enforcer.wrap_fact(fact, "t1")
    assert sf.skepticism_level == SkepticismLevel.TRUST
    assert not sf.should_block


def test_old_inferred_is_warning_or_block(enforcer):
    fact = make_fact("Might use Redis", ConfidenceLevel.INFERRED, days_old=30)
    sf   = enforcer.wrap_fact(fact, "t1")
    assert sf.skepticism_level in (SkepticismLevel.WARNING, SkepticismLevel.BLOCK)
    assert sf.should_block


def test_stale_confidence_always_flagged(enforcer):
    fact = make_fact("Old fact", ConfidenceLevel.STALE, days_old=0)
    sf   = enforcer.wrap_fact(fact, "t1")
    assert sf.skepticism_level in (SkepticismLevel.WARNING, SkepticismLevel.BLOCK)


def test_verification_hint_included_in_framing(enforcer):
    fact = make_fact(
        "Uses port 8080",
        ConfidenceLevel.STALE,
        days_old=20,
        hint="Check config/.env",
    )
```

```
    sf = enforcer.wrap_fact(fact, "t1")
    assert "Check config/.env" in sf.framed_text


def test_wrap_topic_formats_all_facts(enforcer):
    topic = TopicFile(topic_id="t1", topic_name="Tech Stack")
    topic.facts = [
        make_fact("FastAPI backend", ConfidenceLevel.VERIFIED, days_old=1),
        make_fact("Old guess", ConfidenceLevel.STALE, days_old=30),
    ]
    ctx = enforcer.wrap_topic(topic)
    assert ctx.topic_id == "t1"
    assert len(ctx.facts) == 2
    assert ctx.has_blocks


def test_health_banner_tiers(enforcer):
    assert "GOOD"     in enforcer.get_memory_health_banner(0.95, 0)
    assert "FAIR"     in enforcer.get_memory_health_banner(0.75, 2)
    assert "DEGRADED" in enforcer.get_memory_health_banner(0.55, 5)
    assert "POOR"     in enforcer.get_memory_health_banner(0.30, 10)


def test_no_action_for_fresh_verified(enforcer):
    fact = make_fact("Confirmed fact", ConfidenceLevel.VERIFIED, days_old=1)
    sf   = enforcer.wrap_fact(fact, "t1")
    assert sf.action_required is None


def test_action_required_for_stale(enforcer):
    fact = make_fact("Old fact", ConfidenceLevel.STALE, days_old=30)
    sf   = enforcer.wrap_fact(fact, "t1")
    assert sf.action_required is not None
    assert len(sf.action_required) > 0


# tests/test_verification_integration.py

import asyncio
import pytest
from pathlib import Path
from datetime import datetime, timedelta
from unittest.mock import AsyncMock, MagicMock

from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
from memograph.db.database import DatabaseManager
from memograph.core.topic_manager import TopicManager
from memograph.models.topic import MemoryFact, TopicFile
from memograph.verification.decay import ConfidenceDecayModel
from memograph.verification.staleness import StalenessDetector
from memograph.verification.planner import VerificationPlanner
from memograph.verification.audit_log import VerificationAuditLog
from memograph.verification.enforcer import SkepticalMemoryEnforcer
from memograph.verification.sources.base import VerificationResult, VerificationVerdict


@pytest.fixture
async def verification_setup(tmp_path):
```

```
    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "test.db"),
        agent_id="ver_test",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
    )

    db = DatabaseManager(config.db_path)
    await db.connect()
    await db.ensure_agent(config.agent_id)

    topic_manager = TopicManager(config, db)

    # Create topics with mixed freshness
    topics = [
        ("fresh_topic",   "Fresh",   ConfidenceLevel.VERIFIED,  1),
        ("aging_topic",   "Aging",   ConfidenceLevel.OBSERVED,  12),
        ("stale_topic",   "Stale",   ConfidenceLevel.INFERRED,  25),
        ("very_stale",    "V.Stale", ConfidenceLevel.STALE,     60),
    ]

    for topic_id, name, conf, days_old in topics:
        topic = TopicFile(
            topic_id=topic_id,
            topic_name=name,
            agent_id="ver_test",
        )
        topic.facts.append(MemoryFact(
            content=f"Fact in {topic_id}",
            confidence=conf,
            source="test",
            created_at=datetime.now() - timedelta(days=days_old),
            last_verified=datetime.now() - timedelta(days=days_old),
        ))
        await topic_manager.save_topic(topic)

    yield config, db, topic_manager

    await db.disconnect()


@pytest.mark.asyncio
async def test_full_staleness_scan(verification_setup):
    config, db, tm = verification_setup

    detector = StalenessDetector(tm, db, "ver_test")
    report   = await detector.scan(update_db=False)

    assert report.scanned_facts >= 4
    assert report.total_stale >= 1
    assert 0.0 <= report.health_score <= 1.0


@pytest.mark.asyncio
async def test_planner_builds_from_scan(verification_setup):
    config, db, tm = verification_setup
```

```
    detector = StalenessDetector(tm, db, "ver_test")
    report   = await detector.scan(update_db=False)

    planner  = VerificationPlanner(db, "ver_test")
    plan     = await planner.build_plan(report)

    assert plan.total_items > 0
    # Items should be sorted by priority
    if len(plan.queue_items) > 1:
        assert plan.queue_items[0].priority_score >= plan.queue_items[1].priority_score


@pytest.mark.asyncio
async def test_audit_log_records_results(verification_setup):
    config, db, tm = verification_setup
    audit = VerificationAuditLog(db, "ver_test")

    result = VerificationResult(
        fact_id="test_fact_001",
        verdict=VerificationVerdict.CONFIRMED,
        new_confidence="verified",
        explanation="File evidence confirmed",
        verifier_type="file",
        duration_ms=50,
    )

    entry = await audit.record(
        result=result,
        fact_content="Test fact content",
        confidence_before="observed",
        topic_id="fresh_topic",
    )

    assert entry.audit_id is not None
    assert entry.verdict == "confirmed"

    history = await audit.get_fact_history("test_fact_001")
    assert len(history) >= 1


@pytest.mark.asyncio
async def test_enforcer_wraps_all_topics(verification_setup):
    config, db, tm = verification_setup
    enforcer = SkepticalMemoryEnforcer()

    stale_topic = await tm.get_topic("very_stale")
    assert stale_topic is not None

    ctx = enforcer.wrap_topic(stale_topic)
    assert ctx.has_blocks
    assert "STALE" in ctx.formatted_text or "WARNING" in ctx.formatted_text


@pytest.mark.asyncio
async def test_decay_model_consistency(verification_setup):
    config, db, tm = verification_setup

    model  = ConfidenceDecayModel()
```

```
    topics = ["fresh_topic", "stale_topic"]

    for topic_id in topics:
        topic = await tm.get_topic(topic_id)
        if topic:
            for fact in topic.facts:
                result = model.compute_decay(
                    fact_id=fact.fact_id,
                    topic_id=topic_id,
                    confidence=fact.confidence,
                    last_verified=fact.last_verified,
                    created_at=fact.created_at,
                )
                assert 0.0 <= result.freshness <= 1.0

                assert result.days_elapsed >= 0
```

---

12. Phase 6 Demo

Python

```
# examples/phase6_verification_demo.py
"""
Phase 6 Demo — Verification Engine.

Shows:
1. Confidence decay model — how facts age
2. Staleness scanning — finding stale facts
3. Skeptical framing — wrapping facts with skepticism levels
4. Verification planner — building a verification queue
5. LLM-based fact verification
6. Audit trail
7. Full integration demo
"""

import asyncio
import logging
from datetime import datetime, timedelta
from pathlib import Path

logging.basicConfig(
    level=logging.INFO,
    format="%(asctime)s [%(name)s] %(levelname)s: %(message)s",
)
logger = logging.getLogger("phase6_demo")


async def demo_decay_model():
    """Show how confidence decays over time."""
    print("\n" + "="*60)
    print("1. CONFIDENCE DECAY MODEL")
```

```
    print("="*60)

    from memograph.config import ConfidenceLevel
    from memograph.verification.decay import (
        ConfidenceDecayModel,
        FactDomain,
        SourceReliability,
    )

    model = ConfidenceDecayModel()

    print("\n  Freshness over time (days → freshness score):\n")
    print(f"  {'Confidence':<12} {'Domain':<15} ", end="")
    for day in [0, 7, 14, 30, 60, 90]:
        print(f"  {day}d", end="")
    print()
    print("  " + "-" * 70)

    cases = [
        (ConfidenceLevel.VERIFIED, FactDomain.ARCHITECTURAL,  "conf=verified, arch"),
        (ConfidenceLevel.VERIFIED, FactDomain.CONFIGURATION,  "conf=verified, config"),
        (ConfidenceLevel.OBSERVED, FactDomain.GENERAL,        "conf=observed, general"),
        (ConfidenceLevel.INFERRED, FactDomain.USER_PREFERENCE,"conf=inferred, prefs"),
        (ConfidenceLevel.OBSERVED, FactDomain.EXTERNAL_API,   "conf=observed, api"),
    ]

    for conf, domain, label in cases:
        print(f"  {label:<26}", end="")
        for days in [0, 7, 14, 30, 60, 90]:
            f = model.freshness_at(conf, float(days), domain)
            bar = "█" if f > 0.5 else ("▒" if f > THRESHOLD else "░")
            print(f"  {bar}{f:.2f}", end="")
        print()

    THRESHOLD = 0.25
    print(f"\n  Staleness threshold: {THRESHOLD}")
    print(f"  █ = fresh (>{THRESHOLD:.0%})  ▒ = aging  ░ = stale")

    print("\n  Days until stale by confidence:")
    for conf in [
        ConfidenceLevel.VERIFIED,
        ConfidenceLevel.OBSERVED,
        ConfidenceLevel.INFERRED,
    ]:
        d = model.days_to_stale(conf)
        print(f"    {conf.value:<12} → stale after ~{d:.0f} days")


async def demo_staleness_scan(tmp_path: Path):
    """Show staleness scanning."""
    print("\n" + "="*60)
    print("2. STALENESS SCAN")
    print("="*60)

    from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
    from memograph.core.topic_manager import TopicManager
    from memograph.db.database import DatabaseManager
    from memograph.models.topic import MemoryFact, TopicFile
```

```
    from memograph.verification.staleness import StalenessDetector

    config = MemoGraphConfig(
        base_path=str(tmp_path / "mg"),
        db_path=str(tmp_path / "mg" / "demo.db"),
        agent_id="demo",
        llm_provider=LLMProvider.OLLAMA,
    )

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent("demo")
        tm = TopicManager(config, db)

        # Create topics with different ages
        age_cases = [
            ("arch_decisions", ConfidenceLevel.VERIFIED,  2,  "Architecture"),
            ("config_values",  ConfidenceLevel.OBSERVED,  10, "Config"),
            ("user_prefs",     ConfidenceLevel.OBSERVED,  18, "User Prefs"),
            ("old_guess",      ConfidenceLevel.INFERRED,  20, "Old Guess"),
            ("forgotten",      ConfidenceLevel.STALE,     45, "Forgotten"),
        ]

        for topic_id, conf, days, name in age_cases:
            topic = TopicFile(
                topic_id=topic_id,
                topic_name=name,
                agent_id="demo",
            )
            topic.facts.append(MemoryFact(
                content=f"This is a {conf.value} fact in {name}",
                confidence=conf,
                source="demo",
                created_at=datetime.now() - timedelta(days=days),
                last_verified=datetime.now() - timedelta(days=days),
            ))
            await tm.save_topic(topic)

        detector = StalenessDetector(tm, db, "demo")
        report   = await detector.scan(update_db=False)

        print(f"\n  Scanned {report.scanned_facts} facts across "
              f"{report.scanned_topics} topics")
        print(f"  Health score: {report.health_score:.1%}")
        print(f"  Stale facts:  {report.total_stale}")
        print(f"  Near-stale:   {len(report.near_stale_facts)}")

        print(f"\n  Top stale facts (by priority):")
        for rec in report.stale_facts[:5]:
            print(
                f"    [{rec.topic_id}] {rec.fact_content[:50]}..."
                f"\n      freshness={rec.freshness:.3f} "
                f"age={rec.days_elapsed:.0f}d "
                f"priority={rec.priority_score:.3f}"
            )


async def demo_skeptical_framing():
    """Show skeptical memory framing."""
```

```
    print("\n" + "="*60)
    print("3. SKEPTICAL MEMORY FRAMING")
    print("="*60)

    from memograph.config import ConfidenceLevel
    from memograph.models.topic import MemoryFact, TopicFile
    from memograph.verification.enforcer import (
        SkepticalMemoryEnforcer,
        SkepticismLevel,
    )

    enforcer = SkepticalMemoryEnforcer()

    topic = TopicFile(topic_id="tech_stack", topic_name="Tech Stack")
    topic.facts = [
        MemoryFact(
            content="Backend uses FastAPI 0.111 with Python 3.11",
            confidence=ConfidenceLevel.VERIFIED,
            source="architecture_doc",
            last_verified=datetime.now() - timedelta(days=2),
        ),
        MemoryFact(
            content="PostgreSQL is the primary database",
            confidence=ConfidenceLevel.OBSERVED,
            source="seen_in_codebase",
            last_verified=datetime.now() - timedelta(days=12),
        ),
        MemoryFact(
            content="Redis might be used for caching",
            confidence=ConfidenceLevel.INFERRED,
            source="team_discussion",
            created_at=datetime.now() - timedelta(days=20),
            last_verified=datetime.now() - timedelta(days=20),
            verification_hint="Check docker-compose.yml",
        ),
        MemoryFact(
            content="App runs on port 8080 (might have changed)",
            confidence=ConfidenceLevel.STALE,
            source="old_config",
            created_at=datetime.now() - timedelta(days=45),
            verification_hint="grep -r PORT config/",
        ),
    ]

    ctx = enforcer.wrap_topic(topic)

    print(f"\n  Topic health: {ctx.overall_health:.1%}")
    print(f"  Has blocking facts: {ctx.has_blocks}")
    print(f"\n  Formatted output:")
    print("  " + "-" * 56)
    # Indent each line
    for line in ctx.formatted_text.split("\n"):
        print(f"  {line}")


async def demo_verification_planner(tmp_path: Path):
    """Show the verification planner building a queue."""
    print("\n" + "="*60)
```

```
    print("4. VERIFICATION PLANNER")
    print("="*60)

    from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
    from memograph.core.topic_manager import TopicManager
    from memograph.db.database import DatabaseManager
    from memograph.models.topic import MemoryFact, TopicFile
    from memograph.verification.staleness import StalenessDetector
    from memograph.verification.planner import VerificationPlanner

    config = MemoGraphConfig(
        base_path=str(tmp_path / "plan"),
        db_path=str(tmp_path / "plan" / "demo.db"),
        agent_id="planner_demo",
        llm_provider=LLMProvider.OLLAMA,
    )

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent("planner_demo")
        tm = TopicManager(config, db)

        # Populate with stale facts
        for i in range(6):
            topic = TopicFile(
                topic_id=f"topic_{i}",
                topic_name=f"Topic {i}",
                agent_id="planner_demo",
            )
            hint = f"src/module_{i}.py" if i % 2 == 0 else None
            topic.facts.append(MemoryFact(
                content=f"Stale fact in topic {i}",
                confidence=ConfidenceLevel.INFERRED,
                source="old_observation",
                created_at=datetime.now() - timedelta(days=20 + i * 5),
                last_verified=datetime.now() - timedelta(days=20 + i * 5),
                verification_hint=hint,
            ))
            await tm.save_topic(topic)

        detector = StalenessDetector(tm, db, "planner_demo")
        report   = await detector.scan(update_db=False)

        planner = VerificationPlanner(db, "planner_demo")
        plan    = await planner.build_plan(report)

        print(f"\n  Plan built for {plan.total_items} items")
        print(f"  Estimated LLM calls: {plan.estimated_llm_calls}")
        print(f"  Estimated tokens: {plan.estimated_tokens:,}")

        print(f"\n  Queue preview (top 5):")
        print(f"  {'Fact ID':<12} {'Source':<8} {'Priority':<10} {'Hint'}")
        print("  " + "-"*55)
        for item in plan.queue_items[:5]:
            hint = item.source_hint[:20] if item.source_hint else "none"
            print(
                f"  {item.fact_id[:10]:<12} "
                f"{item.verification_source:<8} "
                f"{item.priority_score:.3f}     "
```

```
                f"{hint}"
            )

        high  = len(plan.high_priority(0.7))
        med   = len(plan.medium_priority())
        low   = len(plan.low_priority())
        print(f"\n  Priority breakdown: {high} high, {med} medium, {low} low")


async def demo_llm_verification():
    """Show LLM-based fact verification."""
    print("\n" + "="*60)
    print("5. LLM FACT VERIFICATION")
    print("="*60)

    from memograph.verification.sources.llm_verifier import LLMVerifier
    from memograph.verification.sources.base import VerificationVerdict
    from unittest.mock import AsyncMock, MagicMock
    from memograph.llm.base import LLMResponse

    # Mock LLM returning verification verdicts
    mock_llm        = MagicMock()
    mock_llm.complete = AsyncMock(return_value=LLMResponse(
        content="""{
  "fact_id": "fact_abc",
  "verdict": "confirmed",
  "new_confidence": "verified",
  "explanation": "FastAPI is clearly the backend framework based on imports in main.py",
  "updated_content": null,
  "should_update": false,
  "re_derivable": true,
  "re_derive_from": "src/main.py"
}""",
        provider="mock",
        model="mock-model",
        prompt_tokens=200,
        completion_tokens=80,
    ))
    mock_llm.provider_name = "mock"

    verifier = LLMVerifier(mock_llm)
    result   = await verifier.verify(
        fact_id="fact_abc",
        fact_content="Backend uses FastAPI for all REST endpoints",
        current_confidence="observed",
        source_hint="src/main.py",
        context="""
# From src/main.py:
from fastapi import FastAPI, HTTPException
from fastapi.middleware.cors import CORSMiddleware

app = FastAPI(title="MyAPI", version="2.1.0")
""",
        days_since_verified=12.0,
        source="code_review",
    )

    print(f"\n  Fact: 'Backend uses FastAPI for all REST endpoints'")
```

```
    print(f"  Verdict:    {result.verdict.value}")
    print(f"  Confidence: observed → {result.new_confidence}")
    print(f"  Explanation: {result.explanation}")
    print(f"  Re-derivable: {result.re_derivable}")
    if result.re_derive_from:
        print(f"  Derive from: {result.re_derive_from}")
    print(f"  Tokens used: {result.tokens_used}")
    print(f"  Duration: {result.duration_ms}ms")


async def demo_audit_trail(tmp_path: Path):
    """Show the verification audit trail."""
    print("\n" + "="*60)
    print("6. VERIFICATION AUDIT TRAIL")
    print("="*60)

    from memograph.config import MemoGraphConfig, LLMProvider
    from memograph.db.database import DatabaseManager
    from memograph.verification.audit_log import VerificationAuditLog
    from memograph.verification.sources.base import (
        VerificationResult,
        VerificationVerdict,
    )

    config = MemoGraphConfig(
        base_path=str(tmp_path / "audit"),
        db_path=str(tmp_path / "audit" / "demo.db"),
        agent_id="audit_demo",
        llm_provider=LLMProvider.OLLAMA,
    )

    async with DatabaseManager(config.db_path) as db:
        await db.ensure_agent("audit_demo")
        audit = VerificationAuditLog(db, "audit_demo")

        # Record several verification results
        verdicts = [
            ("fact_001", VerificationVerdict.CONFIRMED, "observed", "verified",
             "Still accurate in v2.1 codebase"),
            ("fact_002", VerificationVerdict.REFUTED,   "observed", "stale",
             "Port changed from 8080 to 9000 in latest deploy"),
            ("fact_003", VerificationVerdict.OUTDATED,  "verified", "stale",
             "Library version updated from 1.x to 2.x"),
            ("fact_004", VerificationVerdict.UNCERTAIN, "inferred", "inferred",
             "Cannot verify from available context"),
        ]

        for fact_id, verdict, before, after, explanation in verdicts:
            result = VerificationResult(
                fact_id=fact_id,
                verdict=verdict,
                new_confidence=after,
                explanation=explanation,
                verifier_type="llm",
                duration_ms=150 + len(fact_id),
                tokens_used=350,
            )
            await audit.record(
```

```
                result=result,
                fact_content=f"Content of {fact_id}",
                confidence_before=before,
                topic_id="demo_topic",
            )

        stats = await audit.get_verification_stats()

        print(f"\n  Audit statistics:")
        print(f"    Total verifications: {stats.get('total_verifications', 0)}")
        print(f"    Confirmed:    {stats.get('confirmed', 0)}")
        print(f"    Refuted:      {stats.get('refuted', 0)}")
        print(f"    Outdated:     {stats.get('outdated', 0)}")
        print(f"    Uncertain:    {stats.get('uncertain', 0)}")
        print(f"    Avg duration: {stats.get('avg_duration_ms', 0):.0f}ms")
        print(f"    Total tokens: {stats.get('total_tokens', 0):,}")

        print(f"\n  History for fact_001:")
        history = await audit.get_fact_history("fact_001")
        for entry in history:
            print(
                f"    [{entry.audit_id}] "
                f"{entry.performed_at.strftime('%H:%M:%S')} "
                f"{entry.confidence_before} → {entry.confidence_after} "
                f"({entry.verdict})"
            )


async def demo_full_verification_pipeline(tmp_path: Path):
    """End-to-end verification pipeline."""
    print("\n" + "="*60)
    print("7. FULL VERIFICATION PIPELINE")
    print("="*60)

    from memograph.config import ConfidenceLevel, MemoGraphConfig, LLMProvider
    from memograph.core.topic_manager import TopicManager
    from memograph.core.index_engine import IndexEngine
    from memograph.core.memory_manager import MemoryManagerV2
    from memograph.db.database import DatabaseManager
    from memograph.verification.decay import ConfidenceDecayModel
    from memograph.verification.staleness import StalenessDetector
    from memograph.verification.planner import VerificationPlanner
    from memograph.verification.audit_log import VerificationAuditLog
    from memograph.verification.enforcer import SkepticalMemoryEnforcer
    from memograph.llm.base import LLMResponse
    from unittest.mock import AsyncMock, MagicMock

    config = MemoGraphConfig(
        base_path=str(tmp_path / "pipeline"),
        db_path=str(tmp_path / "pipeline" / "demo.db"),
        agent_id="pipeline_demo",
        llm_provider=LLMProvider.OLLAMA,
        auto_consolidate=False,
    )

    mock_llm = MagicMock()
    mock_llm.complete = AsyncMock(return_value=LLMResponse(
```

```
content='{"fact_id":"f1","verdict":"confirmed","new_confidence":"verified","explanation":"Conf
irmed via
context","updated_content":null,"should_update":false,"re_derivable":false,"re_derive_from":nu
ll}',
        provider="mock", model="mock", prompt_tokens=200, completion_tokens=60,
    ))
    mock_llm.complete_simple = AsyncMock(
        return_value='{"has_contradiction": false}'
    )
    mock_llm.provider_name = "mock"

    async with DatabaseManager(config.db_path) as db:
        mgr = MemoryManagerV2(config=config, llm=mock_llm, db=db)
        await mgr.initialize()

        # Store facts with various ages
        facts_to_store = [
            ("tech_stack",   "FastAPI Python 3.11 backend framework"),
            ("deployment",   "Deployed on Railway.app staging + production"),
            ("auth_system",  "JWT RS256 tokens, 15min TTL, Redis refresh"),
            ("db_config",    "PostgreSQL 15 with asyncpg and connection pool"),
        ]

        for topic_id, content in facts_to_store:
            await mgr.remember(
                topic_id=topic_id,
                content=content,
                source="architecture_review",
                confidence=ConfidenceLevel.OBSERVED,
            )

        print(f"\n  Stored {len(facts_to_store)} facts")

        # Run staleness scan
        detector = StalenessDetector(mgr._topic_manager, db, "pipeline_demo")
        report   = await detector.scan(update_db=True)

        print(f"  Scan results:")
        print(f"    Facts scanned: {report.scanned_facts}")
        print(f"    Memory health: {report.health_score:.1%}")
        print(f"    Stale facts:   {report.total_stale}")

        # Build verification plan
        planner = VerificationPlanner(db, "pipeline_demo")
        plan    = await planner.build_plan(report)
        print(f"\n  Verification plan: {plan.total_items} items queued")

        # Wrap topics with skeptical framing
        enforcer = SkepticalMemoryEnforcer()
        index    = await mgr.get_index()

        total_trust   = 0
        total_caution = 0

        for pointer in index.pointers[:3]:
            topic = await mgr.get_topic(pointer.topic_id)
            if topic:
```

```
                ctx = enforcer.wrap_topic(topic)
                level_counts = {}
                for sf in ctx.facts:
                    level_counts[sf.skepticism_level] = (
                        level_counts.get(sf.skepticism_level, 0) + 1
                    )
                total_trust   += level_counts.get("trust", 0)
                total_caution += level_counts.get("caution", 0) + level_counts.get("warning",
0)

        print(f"\n  Skeptical framing summary:")
        print(f"    Trust:          {total_trust} facts")
        print(f"    Caution/Warn:   {total_caution} facts")

        # Build context with skeptical memory
        ctx = await mgr.build_context(query="How does authentication work?")
        print(f"\n  Context build:")
        print(f"    Tokens:      {ctx.total_tokens}")
        print(f"    Topics:      {ctx.topics_loaded}")
        print(f"    Pressure:    {ctx.pressure_level}")

        print(f"\n  ✅ Full verification pipeline complete")


async def main():
    import tempfile
    with tempfile.TemporaryDirectory() as tmp:
        tmp_path = Path(tmp)

        await demo_decay_model()
        await demo_staleness_scan(tmp_path)
        await demo_skeptical_framing()
        await demo_verification_planner(tmp_path)
        await demo_llm_verification()
        await demo_audit_trail(tmp_path)
        await demo_full_verification_pipeline(tmp_path)

        print("\n" + "="*60)
        print("✅ PHASE 6 DEMO COMPLETE")
        print("="*60)
        print("\nPhase 7 next: Adapter layers (LangChain, CrewAI, AutoGen)")


if __name__ == "__main__":
    asyncio.run(main())
```

---

13. Run Phase 6

Bash

```
# Install dependencies (no new required deps)
pip install -e ".[dev]"
```

```
# Run Phase 6 tests
pytest tests/test_decay.py                    -v
pytest tests/test_staleness.py                -v
pytest tests/test_planner.py                  -v
pytest tests/test_audit_log.py                -v
pytest tests/test_enforcer.py                 -v
pytest tests/test_verification_integration.py  -v

# Run full test suite
pytest tests/ -v --cov=memograph --cov-report=term-missing

# Run Phase 6 demo
python examples/phase6_verification_demo.py

# Quick smoke test
python -c "
from memograph.verification.decay import ConfidenceDecayModel, FactDomain
from memograph.config import ConfidenceLevel
from datetime import datetime, timedelta

model = ConfidenceDecayModel()

# Test decay for various fact types
for conf in ['verified', 'observed', 'inferred']:
    days = model.days_to_stale(ConfidenceLevel(conf))
    print(f'{conf:12} → stale after {days:.0f} days')

# Test a specific fact
result = model.compute_decay(
    fact_id='test',
    topic_id='demo',
    confidence=ConfidenceLevel.OBSERVED,
    last_verified=datetime.now() - timedelta(days=10),
    domain=FactDomain.CONFIGURATION,
)
print(f'Freshness at 10 days: {result.freshness:.3f}')
print(f'Is stale: {result.is_stale}')
"
```

📊 Phase 6 Completion Checklist

Component	Status
`ConfidenceDecayModel` — exponential decay with domain + source reliability modifiers	✅

`HALF_LIFE_TABLE` — 28-entry lookup table across 4 confidence levels × 7 domains	✅
`StalenessDetector` — full scan with priority scoring and DB update	✅
`VerificationPlanner` — builds ordered queue from staleness report	✅
`VerificationAuditLog` — immutable append-only audit trail	✅
`FileVerifier` — keyword-based file evidence search	✅
`LLMVerifier` — structured LLM verification + batch mode	✅
`VerificationScheduler` — async background daemon with error backoff	✅
`SkepticalMemoryEnforcer` — 5-tier skepticism framing (TRUST→BLOCK)	✅
`VerificationEngine` — unified entry point wiring all components	✅
`VerificationPrompts` — fact verifier, batch verifier, evidence extractor, hint generator	✅
DB schema migration 004 — 4 new tables	✅
Full test suite — 8 test files, 45+ test cases	✅

✅

Phase 6 demo — 7 scenarios end-to-end