tbl_transfer_items
- ◇ transaction_number VARCHAR(100)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quant VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ remarks VARCHAR(100)
- ◇ date_received VARCHAR(100)
- ◇ person_transfered VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ ts_type VARCHAR(100)
- 🔑 unique_id BIGINT(20)
- ◇ branch VARCHAR(100)
- Indexes ▶

tbl_goods_receive
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quantity VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ person_received VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ date_received VARCHAR(100)
- 🔑 unique_id BIGINT(20)
- Indexes ▶

tbl_item_history
- ◇ inventory_code VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ item_stocks VARCHAR(100)
- ◇ item_description TEXT
- ◇ item_price VARCHAR(100)
- ◇ item_branch VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ item_date VARCHAR(100)
- ◇ item_branch_code VARCHAR(100)
- ◇ date_of_transfer VARCHAR(100)
- 🔑 idd BIGINT(20)
- Indexes ▶

tbl_branches_edit_history
- 🔑 _idd BIGINT(20)
- ◇ curr_code VARCHAR(50)
- ◇ curr_name VARCHAR(100)
- ◇ modified_by VARCHAR(100)
- ◇ prev_branch_code VARCHAR(50)
- ◇ prev_branch_name VARCHAR(100)
- ◇ m_date VARCHAR(50)
- ◇ ecode VARCHAR(50)
- Indexes ▶

tbl_transaction_series
- 🔑 transfer_number VARCHAR(100)
- ◇ branch_name VARCHAR(100)
- ◇ date_received VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ employee_name VARCHAR(100)
- ◇ transfer_status VARCHAR(100)
- Indexes ▶

tbl_transfer_temp
- ◇ transaction_number VARCHAR(100)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quant VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ remarks VARCHAR(100)
- ◇ date_received VARCHAR(100)
- ◇ person_transfered VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ ts_type VARCHAR(100)
- 🔑 unique_id BIGINT(20)
- ◇ branch VARCHAR(100)
- ◇ transfer_status VARCHAR(100)
- Indexes ▶

tbl_branch_transfer_history
- 🔑 uid BIGINT(20)
- ◇ employee_code VARCHAR(99)
- ◇ staff_name VARCHAR(99)
- ◇ transfer_to VARCHAR(99)
- ◇ transaction_number VARCHAR(99)
- ◇ item_barcode VARCHAR(99)
- ◇ item_name VARCHAR(99)
- ◇ cat VARCHAR(99)
- ◇ sub_cat VARCHAR(99)
- ◇ quant VARCHAR(99)
- ◇ price VARCHAR(99)
- ◇ remarks VARCHAR(99)
- ◇ ts_type VARCHAR(99)
- ◇ transfer_date VARCHAR(99)
- ◇ received_by VARCHAR(99)
- ◇ item_from VARCHAR(99)
- Indexes ▶

tbl_categories
- 🔑 _id BIGINT(20)
- ◇ cat_1 VARCHAR(100)
- Indexes ▶

tbl_staff_uid
- 🔑 uid VARCHAR(100)
- Indexes ▶

tbl_item_update_history
- ◇ uis VARCHAR(99)
- ◇ item_barcode VARCHAR(99)
- ◇ item_name VARCHAR(99)
- ◇ description VARCHAR(99)
- ◇ cat VARCHAR(99)
- ◇ sub_cat VARCHAR(99)
- ◇ staff_update VARCHAR(99)
- ◇ staff_branch VARCHAR(99)
- ◇ date_updated VARCHAR(99)
- 🔑 idd BIGINT(20)
- Indexes ▶

tbl_sales_series
- 🔑 _id BIGINT(20)
- ◇ transaction_number VARCHAR(99)
- ◇ customer_name VARCHAR(99)
- ◇ staff_name VARCHAR(99)
- ◇ staff_code VARCHAR(99)
- ◇ customer_cash VARCHAR(99)
- ◇ customer_change VARCHAR(99)
- ◇ transaction_date VARCHAR(99)
- ◇ branch VARCHAR(99)
- ◇ payment_method VARCHAR(99)
- ◇ invoice_number VARCHAR(99)
- ◇ card_number VARCHAR(99)
- ◇ c_expiration VARCHAR(99)
- ◇ c_cw VARCHAR(99)
- Indexes ▶

tbl_sales
- 🔑 _id BIGINT(20)
- ◇ transaction_number VARCHAR(99)
- ◇ invoice_number VARCHAR(99)
- ◇ staff_code VARCHAR(99)
- ◇ staff_name VARCHAR(99)
- ◇ branch VARCHAR(99)
- ◇ item_barcode VARCHAR(99)
- ◇ item_name VARCHAR(99)
- ◇ quant VARCHAR(99)
- ◇ total VARCHAR(99)
- ◇ price VARCHAR(99)
- ◇ date_transaction VARCHAR(99)
- Indexes ▶

tbl_sales_temp
- 🔑 _id BIGINT(20)
- ◇ transaction_number VARCHAR(99)
- ◇ invoice_number VARCHAR(99)
- ◇ item_barcode VARCHAR(99)
- ◇ item_name VARCHAR(99)
- ◇ price VARCHAR(99)
- ◇ item_quantity VARCHAR(99)
- ◇ total VARCHAR(99)
- ◇ branch_name VARCHAR(99)
- ◇ staff_code VARCHAR(99)
- Indexes ▶

tbl_promotional_sales_reg
- 🔑 _id BIGINT(20)
- ◇ barcode VARCHAR(50)
- ◇ set_time VARCHAR(50)
- ◇ end_time VARCHAR(50)
- ◇ set_date VARCHAR(50)
- ◇ end_date VARCHAR(50)
- ◇ set_by VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ created_date VARCHAR(50)
- ◇ status VARCHAR(50)
- ◇ entry_num VARCHAR(1000)
- ◇ active_status VARCHAR(50)
- Indexes ▶

tbl_goods_receive_history_series
- ◇ name_of_receiver VARCHAR(99)
- ◇ employee_code VARCHAR(99)
- ◇ date_received VARCHAR(99)
- 🔑 docket_number VARCHAR(99)
- Indexes ▶

tbl_branch_transfer_series ▼
- 🔑 transaction_number VARCHAR(99)
- ◇ staff_name VARCHAR(99)
- ◇ staff_code VARCHAR(99)
- ◇ transaction_date VARCHAR(99)
- ◇ branch_code VARCHAR(99)
- ◇ transfer_to VARCHAR(99)
- ◇ transfer_status VARCHAR(99)
- ◇ receiving_status VARCHAR(99)
- **Indexes** ▶

tbl_branch_transfer_item_temp ▼
- 🔑 uid BIGINT(20)
- ◇ employee_code VARCHAR(99)
- ◇ staff_name VARCHAR(99)
- ◇ transfer_to VARCHAR(99)
- ◇ transaction_number VARCHAR(99)
- ◇ item_barcode VARCHAR(99)
- ◇ item_name VARCHAR(99)
- ◇ cat VARCHAR(99)
- ◇ sub_cat VARCHAR(99)
- ◇ quant VARCHAR(99)
- ◇ remarks VARCHAR(99)
- ◇ ts_type VARCHAR(99)
- ◇ transfer_date VARCHAR(99)
- ◇ price VARCHAR(99)
- ◇ current_branch VARCHAR(99)
- ◇ receiving_status VARCHAR(99)
- **Indexes** ▶

tbl_goods_edit_history ▼
- ◇ _idd VARCHAR(100)
- ◇ item_barcode VARCHAR(20)
- ◇ cat VARCHAR(20)
- ◇ sub_cat VARCHAR(20)
- ◇ description VARCHAR(20)
- ◇ quant VARCHAR(20)
- ◇ prev_quant VARCHAR(20)
- ◇ price VARCHAR(20)
- ◇ eic VARCHAR(50)
- ◇ ecode VARCHAR(50)
- ◇ edit_date VARCHAR(20)

tbl_return_docket ▼
- ◇ docket_number VARCHAR(100)

tbl_uis_sequence ▼
- 🔑 uis VARCHAR(100)
- **Indexes** ▶

tbl_transfers_list ▼
- ◇ transaction_number VARCHAR(100)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quant VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ remarks VARCHAR(100)
- ◇ date_received VARCHAR(100)
- ◇ person_transfered VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ ts_type VARCHAR(100)
- 🔑 unique_id BIGINT(20)
- ◇ branch VARCHAR(100)
- ◇ transfer_status VARCHAR(100)
- **Indexes** ▶

tbl_goods_docket ▼
- 🔑 docket_number VARCHAR(100)
- **Indexes** ▶

tbl_transfer_history ▼
- ◇ transaction_number VARCHAR(100)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quant VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ remarks VARCHAR(100)
- ◇ date_received VARCHAR(100)
- ◇ person_transfered VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ ts_type VARCHAR(100)
- ◇ unique_id VARCHAR(100)
- ◇ branch VARCHAR(100)
- ◇ transfer_status VARCHAR(100)
- 🔑 idd BIGINT(20)
- **Indexes** ▶

tbl_goods_receive_history ▼
- ◇ docket_number VARCHAR(100)
- ◇ employee_code VARCHAR(100)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_category VARCHAR(100)
- ◇ item_quantity VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ person_received VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ date_received VARCHAR(100)
- 🔑 idd BIGINT(20)
- **Indexes** ▶

tbl_swho_items ▼
- 🔑 uis BIGINT(20)
- ◇ item_barcode VARCHAR(100)
- ◇ item_name VARCHAR(100)
- ◇ cat VARCHAR(100)
- ◇ sub_cat VARCHAR(100)
- ◇ item_price VARCHAR(100)
- ◇ item_description VARCHAR(100)
- ◇ item_status VARCHAR(100)
- ◇ date_created VARCHAR(100)
- **Indexes** ▶

tbl_transfer_number ▼
- 🔑 transfer_number VARCHAR(100)
- **Indexes** ▶

tbl_sales_number ▼
- 🔑 idd BIGINT(20)
- **Indexes** ▶

tbl_promotional_sales ▼
- 🔑 uid BIGINT(20)
- ◇ item_barcode VARCHAR(50)
- ◇ set_time VARCHAR(50)
- ◇ end_time VARCHAR(50)
- ◇ set_date VARCHAR(50)
- ◇ end_date VARCHAR(50)
- ◇ branch VARCHAR(50)
- ◇ status VARCHAR(50)
- ◇ employee_code VARCHAR(50)
- ◇ employee_name VARCHAR(100)
- ◇ date_implemented VARCHAR(50)
- ◇ deducted_price VARCHAR(50)
- ◇ original_price VARCHAR(50)
- ◇ entry_num VARCHAR(1000)
- **Indexes** ▶

tbl_items
- r_id VARCHAR(1000)
- inventory_code VARCHAR(100)
- item_name VARCHAR(100)
- employee_code VARCHAR(100)
- item_stocks VARCHAR(100)
- item_description VARCHAR(100)
- item_price VARCHAR(100)
- item_status VARCHAR(100)
- item_date VARCHAR(100)
- item_b_code VARCHAR(100)
- return_type VARCHAR(100)
- 🔑 idd BIGINT(20)
- Indexes ▶

tbl_branch_goods_receive
- item_barcode VARCHAR(100)
- item_name VARCHAR(100)
- cat VARCHAR(100)
- sub_category VARCHAR(100)
- item_quantity VARCHAR(100)
- item_price VARCHAR(100)
- item_status VARCHAR(100)
- date_received VARCHAR(100)
- 🔑 unique_id BIGINT(20)
- branch_name VARCHAR(100)
- Indexes ▶

tbl_branch_goods_receive_history
- transaction_number VARCHAR(100)
- item_barcode VARCHAR(100)
- item_name VARCHAR(100)
- cat VARCHAR(100)
- sub_category VARCHAR(100)
- item_quant VARCHAR(100)
- item_price VARCHAR(100)
- remarks VARCHAR(100)
- person_transfered VARCHAR(100)
- employee_code VARCHAR(100)
- ts_type VARCHAR(100)
- branch VARCHAR(100)
- transfer_status VARCHAR(100)
- 🔑 idd BIGINT(20)
- Indexes ▶

tbl_branch_goods_receive_series
- transaction_number VARCHAR(100)
- transact_by VARCHAR(100)
- received_date VARCHAR(100)
- receiver_code VARCHAR(100)
- branch VARCHAR(100)
- 🔑 idd BIGINT(20)
- Indexes ▶

tbl_users
- b_name VARCHAR(100)
- b_code VARCHAR(100)
- b_status VARCHAR(100)
- b_password VARCHAR(100)
- b_lastname VARCHAR(100)
- b_email VARCHAR(100)
- b_staff_code VARCHAR(100)
- b_user_type VARCHAR(100)
- b_super_admin VARCHAR(100)
- 🔑 idd BIGINT(20)
- b_admin_priv VARCHAR(100)
- Indexes ▶

tbl_swho_items_temp
- item_barcode VARCHAR(100)
- item_name VARCHAR(100)
- cat VARCHAR(100)
- sub_category VARCHAR(100)
- item_price VARCHAR(100)
- Description VARCHAR(100)
- item_status VARCHAR(100)
- date_created VARCHAR(100)
- 🔑 _id BIGINT(20)
- Indexes ▶

tbl_sales_return_goods
- 🔑 uid BIGINT(20)
- barcode VARCHAR(50)
- invoice VARCHAR(100)
- quant VARCHAR(20)
- ts_date VARCHAR(50)
- r_date VARCHAR(50)
- staff_code VARCHAR(50)
- staff_name VARCHAR(50)
- branch VARCHAR(50)
- Indexes ▶

tbl_goods_receive_series
- 🔑 uid BIGINT(20)
- item_barcode VARCHAR(100)
- cat VARCHAR(100)
- name_of_receiver VARCHAR(100)
- employee_code VARCHAR(100)
- date_received VARCHAR(100)
- docket_number VARCHAR(100)
- Indexes ▶

tbl_promotional_number
- 🔑 _idd BIGINT(20)
- Indexes ▶

tbl_goods_receive_temp
- 🔑 unique_id BIGINT(20)
- docket_number VARCHAR(100)
- employee_code VARCHAR(100)
- item_barcode VARCHAR(100)
- item_name VARCHAR(100)
- cat VARCHAR(100)
- sub_category VARCHAR(100)
- item_quantity VARCHAR(100)
- item_price VARCHAR(100)
- item_description VARCHAR(100)
- person_received VARCHAR(100)
- item_status VARCHAR(100)
- date_received VARCHAR(100)
- Indexes ▶

tbl_branches
- 🔑 _id INT(254)
- branch_code VARCHAR(200)
- branch_name VARCHAR(200)
- status VARCHAR(50)
- Indexes ▶

tbl_branch_transfer_number
- 🔑 trans_number VARCHAR(99)
- Indexes ▶