Leading provider of one-stop solutions for network security and industrial control

Motherboard core features:

- Intel® 12th generation Alder Lake-N low-power processor
- Standard 17x17 Mini-ITX board type DC12-19V wide voltage power supply
- Memory and M.2 SSD dual-slot back-mount design makes DIY chassis more user-friendly
- Dual M.2 NVMe (PCie 3.0 x1 signal) 2280 size
- The back-mounted MINI PCIe slot supports 4G/WiFi6 (signal is shared with PCIe)
- The onboard (JMB585 chip) supports 6 SATA3.0 6Gbps high-speed hard disk interfaces
- 1 SFF-8643 supports 1 drag 4 out of 4 SATA3.0
- 4 Inteli226-V 2. 5G network card chips
- 1 SO-DIMM DDR5 4800 memory slot compatible with 5200/5600MHz
- HDMI2.0+DP1.4 supports dual display 4K@60Hz
- 4 USB2.0+1 built-in set of USB3.0 pins
- 1 PCIe x1 slot supports expansion cards (shares signal with back-mounted WiFi/4G slot)

intel | PCIe PCI Express | 2500 Giga LAN | DDR5 single memory | SFF 8643 | HDMI 2.0 | DP 1.4 | SATA 6 | NVMe heat sink

Motherboard model: **CW-ADLN-NAS-DC**



Specifications:


Specification	
Motherboard features	- Matte black PCB - High-density moisture-free fiber 8-layer circuit board - Full protection (supports all USB, audio sources, and network interfaces)
processor	- Intel®Alder Lake-N N97 4 (Threads: 4) 6M Cache,Up to 3.6 GHz - Intel®Alder Lake-N N100 4 (Threads: 4) 6M Cache,Up to 3.4 GHz - Intel®Alder Lake-N N200 4 (Threads: 4) 6M Cache,Up to 3.7 GHz - Intel®Alder Lake-N i3-N305 8 (Threads: 8) 6M Cache,Up to 3.8 GHz
Memory	- Support notebook DDR5 memory technology - 1*SO-DIMM DDR5 memory slot - Compatible with DDR5 4800/5200/5600MHz (non-ECC) - Maximum capacity of a single memory: 32GB
TDP	-9-15W
store	-1 * SFF-86431 supports dragging 4 SATA -SATA1 is native (SATA2 interface is expanded by JMB585) - 2*M.2 NVMe x1 signal 1(2280)
network card	-4 * Intel i226-V 2.5G RJ45 network port
graphics card	- N97 integrated Intel® UHD graphics; 24EU - N100 integrated Intel® UHD Graphics; 24EU - N200 integrated Intel® UHD Graphics; 32EU -i3-N305 integrated Intel® UHD Graphics; 32EU -HDMI2.0 interface supports 4K@60Hz - DP1.4 interface supports 4K@60Hz
structure	- MINI-ITX specifications; 6.7-in x 6.7-in, 17.0cm x 17.0cm - all solid capacitor design
operating system	- Compatible with Microsoft@Windows 10/11 64-bi t- Compatible with Linux * Only supports UEFI mode
Motherboard size	120mm(W)X120mm(L)

Specification	
Front 1/O interface	- 4 * USB2.0 - 1 * HDMI - 1 * DP - 4 * RJ45 2.5G网口 - 1 * DC 12-19V
Internal 1/O interface	- 1 * FPANEL pin - 1 * TPM pin (compatible with 14-pin-SPI ASUS TPM module) - 1 * USB2.0 pin - 1 * CPU_FAN CPU fan 4pin socket (with temperature control) - 1 * SYS_FAN system fan 4pin socket (with temperature control) - 1 * USB3.0 socket (double-layer USB) - 1* USB3.0 socket (double-layer USB)

Network security industrial computer source factory

Product number：CW-ADLN-NAS-DC





Interface introduction

