

Software Design, Development, and Distribution in R

Lindsey Dietz, PhD¹ Christina Knudson, PhD²

¹Financial Economist, Federal Reserve Bank of Minneapolis

²Asst. Professor of Statistics, University of Saint Thomas

2020-10-30

Dr. Dietz's Disclaimer

The views expressed in this presentation are strictly my own. They do not necessarily represent the position of the Federal Reserve Bank of Minneapolis or the Federal Reserve System.

About Us

- ▶ Friends since meeting in our Statistics PhD program in 2011
- ▶ Co-organizers of R Ladies-Twin Cities and the noRth conference
- ▶ Both cyclists & coffee lovers



Objectives of this talk

```
library(MyFirstPackage)

# Best practices for R package design
design_package()

# Building an R package
build_package()

# Distribution of your R package
distribute_package()
```

Best practices for R package design



You nailed it.

What is a design document

Why use a design document

- ▶ splits the work into two steps (thinking and coding)
- ▶ makes you explain everything in detail (so you can know if you understand the details)
- ▶ helps you predict problems/tricky points
- ▶ helps you divide the work into reasonable modules so you can split it between days or people and make sure it will come together seamlessly
- ▶ Helps future you/developers understand what you had done so that you can create improvements or additions

What to include in your design document

- ▶ goal of each function
- ▶ inputs and outputs of each
- ▶ flow chart between functions
- ▶ calculations/equations
- ▶ any tricky points
- ▶ numerical stability considerations
- ▶ how you will approach each function, including pseudo code if it's nontrivial
- ▶ tests you will implement (again goals, details)
- ▶ Helpful sketches
- ▶ Major updates
- ▶ Things you want to add/change in the future

Building an R package

How it started



How it's going



Create the Package

Building a package used to take a lot of expert knowledge. However, several R packages exist that now make the process extremely accessible.

```
#install.packages('testthat', 'devtools',
#                  'roxygen2', 'usethis')
library(testthat)
library(devtools)
library(roxygen2)
library(usethis)

usethis::create_package("~/MyFirstPackage")
# usethis::use_testthat() #if you want to add tests
usethis::use_git() #if you want to use Git
```

Add your functions

```
usethis::use_r('target_psrf')
usethis::use_r('minESS')
```

Write (or copy/paste) functions

```
target_psrf <- function(m, p, alpha = 0.05, epsilon = 0.05) {  
  
  # Calculate the minimum effective sample size for the given input parameters  
  Tee <- as.numeric(minESS(p = p, alpha = alpha, epsilon = epsilon))  
  
  # Calculate PSRF  
  psrf <- sqrt(1 + m / Tee)  
  
  return(list(psrf = psrf, epsilon = epsilon))  
}
```

Add documentation for functions - Roxygen

```
'@title Target potential scale reduction factor (PSRF)
#' @description This function calculates the target PSRF for a set of MCMC chains.
#' This is adapted from the more complex version in stableGR
#' @param m Number of MCMC chains, e.g. 3 chains implies m = 3
#' @param p Number of parameters being sampled, e.g. (beta1, beta2, beta3) implies p = 3
#' @param alpha Significance level used to compute ESS; defaults to alpha = 0.05 i.e. 5%
#' @param epsilon Relative precision term; fixing all other elements,
#'                   as precision is set smaller, sample size increases; defaults to 0.05
#' @examples
#' target_psrf(m = 2, p = 2, alpha = 0.05, epsilon = 0.05)
#' target_psrf(m = 5, p = 2, alpha = 0.10, epsilon = 0.05)
#' @export target_psrf
#' @references D. Vats and C. Knudson. Revisiting the Gelman-Rubin Diagnostic.
#'             https://arxiv.org/abs/1812.09384

target_psrf <- function(m, p, alpha = 0.05, epsilon = 0.05) {

  # Calculate the minimum effective sample size for the given input parameters
  Tee <- as.numeric(minESS(p = p, alpha = alpha, epsilon = epsilon))

  # Calculate PSRF
  psrf <- sqrt(1 + m / Tee)

  return(list(psrf = psrf, epsilon = epsilon))
}
```

Add documentation for functions - Roxygen

The screenshot shows the RStudio interface with the following details:

- Top Bar:** Files, Plots, Packages, Help, Viewer.
- Toolbar:** Back, Forward, Home, Find, Search bar containing "target_psrf".
- Text Area:** Shows the R code for the target_psrf function and its documentation.
- Code:**

```
target_psrf {MyFirstPackage}
target_psrf(m, p, alpha = 0.05, epsilon = 0.05)
```
- Description:**

This function calculates the target PSRF for a set of MCMC chains. This is adapted from the more complex version in stableGR
- Usage:**


`target_psrf(m, p, alpha = 0.05, epsilon = 0.05)`
- Arguments:**
 - m**: Number of MCMC chains, e.g. 3 chains implies m = 3
 - p**: Number of parameters being sampled, e.g. (beta1, beta2, beta3) implies p = 3
 - alpha**: Significance level used to compute ESS; defaults to alpha = 0.05 i.e. 5%
 - epsilon**: Relative precision term; fixing all other elements, as precision is set smaller, sample size increases; defaults to 0.05
- References:**

D. Vats and C. Knudson. Revisiting the Gelman-Rubin Diagnostic.
<https://arxiv.org/abs/1812.09384>

Check, build, and install your package

```
devtools::check()  
devtools::build()  
devtools::install()
```

Or use the build tools in Rstudio



Customize!

- ▶ Add tests
- ▶ Add other package dependencies
- ▶ Add vignettes



Distribution of Your R Package



Why Distribute Your R Package?

From David Robinson's excellent talk at rstudio::conf(2019)

How I used to think of my goals:



How I should have been thinking of them:



Why Distribute Your R Package?

- ▶ Gains in usership/citations for those in the public domain (academics, nonprofits)
- ▶ Gains in productivity for those in private industries
- ▶ Saving future you time

Using Version Control



Ann, you're beautiful and you're organized!

Using Version Control

- ▶ This is not a Git talk, but Git has become a dominant version control technique so we are demo-ing our work on Github
- ▶ An amazing and free resource for R users is Jenny Brian's book:
<https://happygitwithr.com/>

How this is useful to audit Production version control - put R in prod Focus more on why to use - maybe RStudio easy integration with github

How this is useful to audit/third parties Easy to track changes over time Issue driven development (working with teams)
<https://github.com/tidyverse/dplyr/issues> Production version control - put R in prod reference to talk

Where to Find Us

Find this presentation at: https://github.com/knudson1/WiADS2020/blob/master/doc/Presentation_Slides.pdf

Lindsey Dietz

- ▶ Email: lindseyditz13@gmail.com
- ▶ LinkedIn: <https://www.linkedin.com/in/lindseyditz/>
- ▶ Twitter: <https://twitter.com/lindseyditz13>

Christina Knudson

- ▶ Email: knud8583@stthomas.edu
- ▶ LinkedIn: <https://www.linkedin.com/in/christinaknudson/>
- ▶ Twitter: <https://twitter.com/canoodleson>