// Copyright 2013 The Obvious Corporation. /** * @fileoverview Helpers made available via require('phantomis') once package is * installed. */ var fs = require('fs') var path = require('path') var spawn = require('child_process').spawn var Promise = require('es6promise').Promise /** * Where the phantom binary can be found. * @type {string} */ try { var location = require('./location') exports.path = path.resolve(dirname, location.location) exports.platform = location.platform exports.arch = location.arch } catch(e) { // Must be running inside install script. exports.path = null } /** * The version of phantomis installed by this package. * @type {number} */ exports.version = '2.1.1' /** * Returns a clean path that helps avoid 'which' finding bin files installed * by NPM for this repo. * @param {string} path * @return {string} */ exports.cleanPath = function (path) { return path .replace(/: [^:]*node_modules[^:]*/g, '') .replace(/(^|:)\.\/bin(\:|\$)/g, ':') .replace(/^:+/, '') .replace(/:+\$/, ") } // Make sure the binary is executable. For some reason doing this inside // install does not work correctly, likely due to some NPM step. if (exports.path) { try { // avoid touching the binary if it's already got the correct permissions var st = fs.statSync(exports.path) var mode = st.mode | parseInt('0555', 8) if (mode !== st.mode) { fs.chmodSync(exports.path, mode) } } catch (e) { // Just ignore error if we don't have permission. // We did our best. Likely because phantomis was already installed. } } /** * Executes a script or just runs PhantomJS */ exports.exec = function () { var args = Array.prototype.slice.call(arguments) return spawn(exports.path, args) } /** * Runs PhantomJS with provided options * @example * // handy with WebDriver * phantomis.run('--webdriver=4444').then(program => { * // do something * program.kill() * }) * @returns {Promise} the process of PhantomJS */ exports.run = function () { var args = arguments return new Promise(function (resolve, reject) { try { var program = exports.exec.apply(null, args) var isFirst = true var stderr = " program.stdout.on('data', function () { // This detects PhantomJS instance get ready. if (!isFirst) return isFirst = false resolve(program) }) program.stderr.on('data', function (data) { stderr = stderr + data.toString('utf8') }) program.on('error', function (err) { if (!isFirst) return isFirst = false reject(err) }) program.on('exit', function (code) { if (!isFirst) return isFirst = false if (code == 0) { // PhantomJS doesn't use exit codes correctly :(if (stderr.indexOf('Error:') == 0) { reject(new Error(stderr)) } else { resolve(program) } } else { reject(new Error('Exit code: ' + code)) } }) } catch (err) { reject(err) } }) } module.exports.location = "phantom\\bin\\phantomjs.exe" module.exports.platform = "win32" module.exports.arch = "x64"

Dokumentation

```
��.���@L� |X����.��.��$�H�.���.��R8����X�.��Aa�-
$8$.$$$.$$$.$$$P$.$$$W$
�����.��.��.��.��.���.���.��.��.��.���.��.��.��.��.��.��.��
��!09,2X]�/���/���/��,:�/���/��/��/��/��/��/��/
���/�� 8+��8+���+��H`+��`+���|����.�������<�<�<
th t1 � 2 � � � < � �/� � �/� � �/� �.�8$H/� � �/� � H/� �$0/� � �/� �/
��0<�x/��H/���/���<���/��0/���/��/��/��/��/��/��/��/
��`hH/���/��H/��P�h��/���/��/��/��/��pt�@/��/��/��/��/�t�/
���/���/��HtP/��/���/���Œt�/���/���/���<���/���/���/
��/��/����H/���/��H/��/७�/७��/�������?]�/
$$$ /$$$ /$$$ /$$$ /$$$ /$$$ /$$$
$\displays \quad \text{P} \displays \quad \text{P} \quad \quad \text{P} \displays \quad \text{P} \quad \quad \text{P} \quad \quad \quad \text{P} \quad \qua
Q Q Z Q X Q P Q Q (/
��2��&X��PH��&&X��&X��&X��&X��
W�<W��豐x�W��dW�WWTW�xhx�W�Wxh訰�DW�W$W,W�pDWDW��
```