

Chapter 1

List of papers

Chapter 2

Introduction

2.1 Introduction

2.2 Introduction

The broad topic of this thesis graph based reference genomes, and specifically of mapping and peak calling on such references. The introduction here is meant to provide an introduction to the topic as well as a coherent brief of the content of the provided papers. As is common in bioinformatics, full understanding of the field of graph based references requires at least a rudimentary understanding of the underlying biology, mathematics and informatics. An brief introduction to the specific subtopics

The first section will be an introduction to two main biological topics, reference genomes and genomic variation, in order to familiarize the reader with topics in addition to establish a perspective that establishes the benefits of graph based references. Section 2 introduces the concept of sequence graphs and their interpretation in different settings. Section 3 describes the mathematical formalism used in this thesis as well as the data structures embodying this formalism. These sections might be persived as too rigorous and opaque for a brief introduction, but this highlights one of the main drawbacks of graphical models, namely their complexity. Section 4 and 5 gets to the main focus of this thesis, covering the topics of read mapping and peak calling on graph based reference genomes.

2.3 Biology Background

2.3.1 DNA

At the heart of molecular biology is *deoxyribonucleic acid*, *DNA*. DNA-molecules consists of pairs of four different *nucleotides* linked together to form a double stranded helix. The four different nucleotides are often represented by the letters

A (*adenin*), C (*cytosin*), T (*thymine*) and G (*guanin*), forming an alphabet of nucleotides $\Gamma_{DNA} = \{A, C, T, G\}$. Each nucleotide can only be paired with one of the others, such that each base-pair in the helix is either (A-T) or (G-C) or opposite. *chromosomes*

The most important function of DNA is to serve as a template for the synthesis of proteins, which in turn are responsible for a wide range of bio-molecular functions. This is a two-step process where DNA is first *transcribed* to RNA, molecules similar to DNA but single stranded and with *thymine* replaced by *uracil* (U). The resulting RNA-sequence can in turn be translated to proteins by mapping triplets of ribonucleotides to amino acids, which are the building blocks of proteins.

Sequences of DNA that are transcribed to RNA that either has a function in itself, or is in turn translated to protein, are called *genes*. Genes constitute only a minor proportion of human DNA. The remaining DNA can be important due to the biochemical properties of the DNA itself.

2.3.2 Replication and Mutation

In addition to serving as template for RNA molecules, DNA can also be replicated. This leads to inheritance both on cellular and organismal level. In normal cell division, the chromosomes are replicated such that each of the two resulting cells have a copy of the DNA from the original cell. Furthermore, germ line cells are copied and transfer half of the organism's chromosomes to an offspring.

However, this DNA-replication is not always accurate. Errors can occur leading to a copy of the DNA molecule which is not identical with the original. Most common are the substitution of a single nucleotide, insertion of a small DNA sequence, or deletion of a small subsequence. Such errors lead to difference between cells within an organism, or difference between individuals.

more about variation

Difference in the DNA-sequence between two individuals can lead to a change in the transcribed RNA sequence and further in the sequence, and thereby the form and function, of the expressed protein. Or it can lead to less drastic changes such as changes in the RNA-structure or the shape of the DNA molecule itself. In this way genomic variation can determine differences between specimens of the same species and also differences between the species themselves.

2.3.3 Epigenomics

Difference in DNA-sequence can explain phenotypic *explain geno/pheno* difference between individuals, but fails to explain the difference between the different cells within an organism. Within an organism, the cells contain mostly the same DNA-sequences, but exhibit vastly different phenotypes.

The reason for this difference is fundamentally mostly attributed to differences in expression levels of genes. Much attention has been devoted in recent years to the mechanisms determining gene expression levels. Two high-level consortia, ENCODE ?? and Roadmap Epigenomics ??, have systematically

conducted experiments geared to understanding some of these factors, including: 3D-configuration of the chromosomes, accessibility of the DNA in different regions, transcription factor binding sites, and methylation patterns across the genome. This thesis is concentrated transcription factor binding sites, but for an introduction to epigenomics as a whole see ??.

Transcription factors are proteins that bind to DNA, with an affinity for certain DNA-sequences. These proteins function as signals to other proteins that a gene in its vicinity should be transcribed, thus affecting expression levels of genes. As such the presence or absence of transcription factors binding to a binding site can affect the phenotype of a cell. Also since the binding of transcription factors is dependent on the DNA-sequence, a mutation in the DNA-sequence in a binding site can affect the binding of the protein and thus the expression of a nearby gene.

2.3.4 Sequencing

Since differences in DNA-sequence can explain differences in biological function, it has long been a goal to read the DNA-sequence of a sample as accurately and efficiently as possible. Currently, no technology exists to accurately sequence whole molecules like a human chromosome with accuracy and thus sequencing has been dominated by reading small (50-600bp) sequence fragments. The ability to massively sequence short reads have been very influential in medicine and biology, with a wide range of applications. The ability to deduce DNA-sequences have

- DNA
- mutations,
- sequencing,
- assembly,
- alignment,
- read mapping,
- chip-seq,
- etc.

This should explain basics:

2.4 Alignment

This section is about sequence alignment. Although not in itself central for this thesis, it is introduced here for two reasons. Firstly it is the area where sequence graphs were first introduced, and also provides the most clear interpretation of a sequence graph. Secondly, it provides a good starting point for introducing read mapping which is discussed in the next section.

2.4.1 Pairwise Sequence Alignment

Pairwise sequence alignment is the problem of aligning letters in two sequences in a way that minimizes some distance measure between them. Typically one assumes that the two sequences are separated by a set of mutations (SNPs, deletions and insertions), where a cost is given to each mutation. For instance a single nucleotide substitution. For instance the alignment of the DNA-sequences *ATAGTGCCGTG* and *ACAGTGGTG*, would be (*ATAGTGCCGTG*, *ACAGTG-GTG*), which would have the simple edit distance 3 (1 substitution and 2 deletions). In general the optimal alignment given an affine gap penalty can be found using Needleman-Wunch [?] in $O(n * m)$ time by using the recurrence relation

$$D(s_{:k}, q_{:l}) = \min(D(s_{:k-1}, q_{:l-1}) + D(s_{k-1}, q_{l-1}), D(s_{:k-1}q_{:l} + G), D(s_{:k}q_{:l-1} + G)) \quad D(0, k) = D(k, 0) = Gk$$

Explain Backtracking

2.4.2 Multiple Sequence Alignment

2.4.3 Sequence Graph Alignment

Hein et al [?] showed that the needleman wunch could be generalized to align a sequence to a pair of already aligned sequences. This was done by representing an alignment as a simple *sequence graph*. A sequence graph in this setting is a graph where each node represents a letter, and an edge between two nodes means the two corresponding letters are consecutive in one of the sequences. Formally we let a *simple sequence graph* be a graph $G = (V, E)$ with a labeling $s : V \rightarrow \Gamma_{DNA}$. An pairwise alignment can be represented as a simple sequence graph by *Alignment to sequence graph*. Given a topological ordering $O(v)$ of the vertices in the sequence graph, the needleman wunch algorithm can be extended to sequence graphs by:

$$D(v_1, v_2) = \min(\{ \min(D(p_1, p_2) + D(p_1, p_2), D(p_1, v_2) + G, D(v_1, p_2) + G) \mid p_1 \in P(v_1) \wedge p_2 \in P(v_2) \}) \\ D(v_1, v_2) =$$

The interpretation of the sequence graph alignment is that a path in the sequence graph created from the alignment of two sequences represents a possible ancestor sequence of the two sequences and that the alignment of a third sequence to this graph represents the best alignment of this sequence to one of the possible ancestor sequences. Each sequence s_a created from a path in the graph has the property that $D(s_a, s_1) + D(s_a, s_2) = D(s_1, s_2)$. By doing a similar adaption to align sequence graphs to sequence graphs, and representing the alignments as a sequence graph of the the alignment of the two ancestor sequences, the sequence graph alignment represents a closed operation on simple sequence graphs. Thus a multiple sequence alignment can be produced by iteratively aligning sequence graphs [?].

2.4.4 Large Scale Sequence Alignment

In theory, pairwise sequence alignment could be used to find out where a small sequence originates from a large sequence. However, since the Needleman-Wunch algorithm has complexity $O(n * m)$, it is too computationally demanding to use this directly when dealing with large numbers of sequences and large sequences.

- Needleman Wunch,
- MSA
- graph needleman wunch
-

2.5 Mapping

Making sense of massive amounts of short reads from NGS experiments is of fundamental importance to modern bioinformatics. This can be done by analyzing the sequence overlaps of the reads to deduce longer contiguous sequences such as in genome assembly [?] and other reference-free methods [?]. This is however usually very computationally expensive, and demands large amounts of data in order to achieve certain results. When available, mapping the reads to a *reference genome* can both reduce the complexity and improve the results of the analysis. A reference genome gives a prior estimate of what the genome sequence of an individual of that population is. This makes it possible to look at each read from an experiment independently and get an estimate of where that read comes from in the genome. In this thesis' projects reference genomes for *Arabidopsis thaliana* [?], *Drosophila melanogaster* [?] and human [?] populations have been used. *Maybe mention graph based here* The following is a brief introduction to the field of mapping reads to a reference genomes.

2.5.1 Linear Mapping

Mapping a read $r \in \Gamma^*$ to a linear reference genome $G \in \Gamma^*$ can be seen as solving the problem of finding an interval $M(r|G) = (\hat{s}, \hat{e})$ that minimizes some edit distance $D(r, G_{\hat{s}:\hat{e}})$ as well as returning an uncertainty estimate of the mapping $\epsilon(r, G, (s, e))$. Given no restraints on computation time or memory usage, a local alignment of r versus G finds the exact minimum *which distance*. However since this algorithm has complexity $O(|r||G|)$, this is not possible in practice when dealing with million of reads and reference genomes with a length in the billions. Thus indexing and further approximations are needed to meet the demands of modern bioinformatics. A common approach is to generate an index that allows for efficient searching of subsequences, and to combine the matches from subsequences into a match for the whole sequence r . The projects in this thesis have used *BWA – mem* as the program to map reads to a linear

reference genome. In the following a brief description of the methods used in *BWA – mem* [?] is explained.

FM-index

An FM index [?] is a data structure that allows lookup of a sequence s in a reference sequence R in $O(|s|)$ time. It is based on a lexicographic sort of the suffixes of R BWT? and the index structure contains representations of two character vectors. One for the first letter of each suffix in sorted order and one for

BWA-mem

mem-chaining

2.5.2 Graph Mapping

Mapping to a graph based reference is similar to the linear case, except that instead of estimating a linear interval (\hat{s}, \hat{e}) , a graph interval $(\hat{s}, \hat{e}, \hat{v})$ is estimated. It is however deceptively more complicated. Firstly because the number of subsequences in a sequence graph grows exponentially with the complexity of the graph. And secondly since chaining subsequence-matches is more complicated due to the possible existence of multiple paths between two matches. *vg* has been at the forefront of mapping to a graph reference, showing that it can lead to better mapping accuracy than BWA-mem. But it is still too slow and memory- and disk-consuming for widespread use. Below is a brief description of the algorithms used by *vg*, but first a brief discussion of variation on genome scale.

GCSA-index

The GCSA-index [?, ?] is a generalization of the FM-index, where arbitrary-length sequences can be found in a sequence graph. Originally constructed to work on acyclic sequence graphs, *gcsa2* extends the functionality to general variation graphs. For simplicity we will here constrain the discussion to acyclic graphs.

Genome Scale Variation

On a larger scale the block format is inconvenient due to the redundancy in the sequences. It is then more common to use a single sequence as a reference sequence and then represent the different sequences only by the places they are different from the reference. This is common for example when representing multiple genomes from the same species. The variant common format? (VCF) [?] format is a common such format that represents the. It contains a list of variants represented by a position in the reference sequence, a subsequence from the reference from that positions, and the alternative sequence that

replaces the reference sequence. In addition it can contain extra columns for known haplotypes, specifying which variants are present in each haplotype.

Such vcf representations can also be represented uniquely by a sequence graph, by first representing the reference sequence as a linear sequence graph and then adding to the graph the nodes and edges to represent the variants. It is also here necessary to represent the haplotypes as paths through the graph in order to keep the haplotype information.

The most common variations (SNPs and indels), leads to directed acyclic graphs (DAG) when converted to a sequence graphs. However other types of variants does not have this property and thus leads to more complicated graphs.

Other types of variants Large scale variants that affects the ordering of the nucleotides are not well suited to being represented by DAGs. An example of this is transpositions, where a subsequence of DNA is moved to another location in the genome. This can be represented as a DAG by adding a new variant in the graph covering the whole sequence from covering both the old an new postions of the subsequence. However this can lead to much redundancy since the sequence between the two positions will be represented twice. The other alternative is to only add new edges to the graph, representing the sequence when the substring has been moved. This will however break the acyclicity of the graph, and thus complicate most operations one would do on the graph.

Another case which will lead to redundancy if represented as a graph is reversals. Here a piece of the DNA is reversed leading to the subsequence being substituted with its reverse complement. Adding a subsequence in the graph representing the reverse compliment is inderictly redundant. Even though the reverse compliment is not included as a path in the graph, it is directly deducible from a sequence in the graph. In order to represent suche reversals, and other things needing the reverse compement, the concept of a side graph has been introduced. In a side graph, all the nodes representing nucleotides have to sides and an edge is defined as going from one side of a node to a side of another node. One node-side represents the nucleotide, while the other side represents the complement in the other reading direction.

vg

At the heart of *vg* is the concept of Variation Graphs. A Variation Graph is an extension of simple sequence graphs, which can represent additional types of variation, and alos contains information about paths in the graph.

vg chaining

- Indexing,
- kmers,
- fm,
- BWA-mem,
- mapping bias,

- vg,
- gcsa2,
- combinatorial complexity

2.6 ChIP-seq

Chip-seq is an experiment designed to elucidate where a transcription factor binds. Immunoprecipitation is used to isolate small fragments of DNA which have the transcription factor bound to them. Ends of these fragments are then sequenced yielding reads that in general are assumed to be in the vicinity of a binding site. In order to find from this where the transcription factor was bound bioinformatics pipelines are needed. This in general consists of mapping the reads to a reference genome, and performing *peak calling* on the coordinates of the mapped reads. Peak calling is required to estimate from the mapped reads, only known to tend to be in the vicinity of a binding site, where the binding site is. The input to peak calling is a set of directed intervals and the output is generally either a set of positions, or a set of undirected intervals that denote the predicted binding sites.

$$PC : \mathbb{I}_G \rightarrow \mathbb{I}_G^+$$

A range of methods for performing peak calling exists [?, ?, ?]. In the following is described the algorithms used by MACS2 and the adaptations to those algorithms used by Graph Peak Caller described in Paper 3 and Paper 4.

2.6.1 MACS2

The input is a set of intervals $\{(s_k, e_k, d_k)\}$. The first step is to count how many extended reads cover each position of the reference genome, where each interval is extended to a length equaling a previously estimated fragment length f . I.e for each position i we want to find the count

$$P(i) = |\{k \mid d_k = 1 \wedge s_k \leq i < s_k + f\} \cup \{k \mid d_k = -1 \wedge e_k - f \leq i < e_k\}|$$

The pileup function P is represented sparsely by a set of indices $\{s_k\}$ and values $\{v_k\}$ such that

$$\forall k \forall j \in \{s_k, s_k + 1\}, \dots, s_{k+1} (P(j) = v_k)$$

the indices and values are found algorithmically as

```
def count_extended(intervals, f):
    starts = [s if d==1 else e-f for s, e, d in intervals]
    ends = [e if d==1 else s+f for s, e, d in intervals]
    changes = starts+ends
    args = argsort(changes)
    codes = [1 if arg<=len(starts) else -1 for arg in args]
    s = changes[args]
```

```

v = cumsum(codes)
return s, v

```

Which is done in $O(n \log n)$ time. The counts for each position is compared with a background track which represents a local average of reads. This is generated by using a large extension length and dividing the pileup values by the extension size. $s, v = \text{count_extended}(\text{control_intervals}, E)/E$; $v/=E$. Assuming that each count $P(i)$ are Poisson distributed as $P_i \text{Poisson}(\lambda_i)$, a null hypothesis of $H_0^i : \lambda_i = C(i), H_a^i : \lambda_i > C(i)$ is made for each position and a p-value calculated: $p_i = P(P_i \geq P(i) \text{ too many ps.})$. Too adjust for multiple testing, a final set of q values is calculated as $q_i = p_i N_i$ where $N_i = |\{k \in \{1, 2, \dots, |G|\} \mid p_k \leq p_i\}|$. The q values are thresholded on a given significance level α so we get $T(i) = q_i \leq \alpha$.

```

def get_p_values(pileup, background):
    indices = pileup.indices + background.indices
    indices.sort ()
    pileup_values = pileup.values[search_sorted(indices, pileup.indices)]
    background_values = background.values[search_sorted(indices,
        background.indices)]
    p_values = poisson.sf(pileup_values, background_values)
    return Pileup(indices, p_values)

```

Which is done in $O(n)$ time.

```

def get_q_values(p_values):
    counts = diff(p_values.indices)
    args = argsort(p_values.values)
    values, idxs = unique(p_values, return_index=True)
    N = cumsum(counts[args])[idxs]
    q_values = N*values
    all_q_values = zeros_like(p_values.values)
    all_q_values[idxs] = diff(q_values)
    all_q_values = cumsum(all_q_values)
    restored = zeros_like(all_q_values)
    restored[args] = all_q_values
    return Pileup(p_values.indices, restored)

```

The thresholded values are obtained simply by `Pileup(q_values.indices, q_values.values>alpha)`.

The final peaks are called in two steps from the thresholded values. First, joining peak intervals that are separated by less than the estimated read length, and secondly removing peaks that are shorter than the estimated fragment length f . Both steps can be made using the same function.

```

def remove_small(indices, size):
    indices = indices.reshape((-1, 2))

```

```

lengths = indices[:, 1]-indices[:, 0]
big_enough = lengths>=size
return indices[big_enough].ravel()

peaks = r_[indices[0], remove_small(indices[1:-1], read_length),
          indices[-1]]
peaks = remove_small(peaks, fragment_length)

```

2.6.2 Graph Peak Caller

The following is a brief description of the algorithms and data structures used in the adaptation of MACS2 to graph genomes. It is assumed here that the sequence graph is a compressed simple sequence graph, and therefore also acyclic. We also assume that the node ids are sorted according to a topological sort of the graph.

The fundamental data structure in for graph peak caller is the linear representation that converts coordinates from $LR : \mathbb{N}_{|V|} \times \mathbb{Z} \rightarrow \mathbb{N}_N$, where $N = \sum_{i=0}^{|V|-1} L(i)$ is the number of positions in the graph. This linear mapping is represented in the LinearRepr class, which has an array node_offsets where $\text{node_offsets}[i] = \sum_{k=0}^i L(k)$ such that a coordinate $(v, o) \in \Gamma$ is converted to $i \in \epsilon$ by $\text{node_offsets}[v] + o$. The inverse conversion of a coordinate $i \in \epsilon$ is done by $v = \text{searchsorted}(\text{node_offsets}, i)$; $o = i - \text{node_offsets}[v]$

A pileup is created in the linear coordinate space by the following method. For each interval (s, e, v, d) we define the extended interval as a tuple

$$\text{ext}(I_k, f) = \begin{cases} (\{s_k\}, E_k^+, X_k^+), & \text{if } d = 1 \\ (X_k^-, E_k^-, \{e_k\}), & \text{if } d = -1 \end{cases}$$

where

$$\begin{aligned}
E_k^+ &= \{(v_1, v_2) \in E \mid D(e_k, (v_2, 0)) \leq f\} \cup \{(v_1, v_2), (v_2, v_3), \dots, (v_{k-1}, v_k)\} \\
X_k^+ &= \{(v, o) \in \Gamma \mid D(e_k, (v, o)) = f\} \\
E_k^- &= \{(v_1, v_2) \in E \mid D((v_2, 0), s_k, \leq) f\} \cup \{(v_1, v_2), (v_2, v_3), \dots, (v_{k-1}, v_k)\} \\
X_k^- &= \{(v, o) \in \Gamma \mid D((v, o), s_k) = f\}
\end{aligned}$$

From this we can get the sparse pileup as

$$\delta(LP((v, o))) = \begin{cases} N_s((v, o)) - N_e((v, o)) + \delta_E((v, o)), & \text{if } o = 0 \\ N_s((v, o)) - N_e((v, o)), & \text{else} \end{cases}$$

$$\begin{aligned} N_s((v, o)) &= |\{(X_s, E, X_e) \in Ext \mid (v, o) \in X_s\}| \\ N_e((v, o)) &= |\{(X_s, E, X_e) \in Ext \mid (v, o) \in X_s\}| \\ \delta_E((v, o)) &= |\{(X_s, E, X_e) \in Ext \mid \exists v_0 \in V [(v_0, v) \in E]\}| \\ &\quad - |\{(X_s, E, X_e) \in Ext \mid \exists v_2 \in V [(v - 1, v_2) \in E]\}| \end{aligned}$$

Algorithmically this pileup is more complex to create than the linear pileup. The $O(|V| + fk|I|)$ algorithm used by graph peak caller is described below:

```
def extend_interval(interval, f, graph):
    starts = set([ interval.start ])
    edges = {(vertex, interval.vertices [i+1])
              for i, vertex in enumerate(interval.vertices[:-1])}
    \TODO{Rest of code if simple enough}
```

Given the sparse pileup in linear coordinates, the steps for calculating p - and q - values and thresholding for significance is the same as for the linear case.

Removing small holes in the intervals is again more complex than in the linear case. First the intervals in linear coordinates corresponding to significant q values are converted to intervals in graph coordinates, s.t

Secondly, these are graph intervals are clusered into connected subgraphs so that

Lastly, we join any two subgraphs that are connected by a path with distance shorter than the read length, i.e:

The penultimate step is to convert the resulting subgraphs into graph intervals, by choosing the edges with the highest coverage in the edge pileup. Finally these paths are filtered by their length so that all remaining intervals are longer than the estimated fragment length.

- MACS2,
- Graph-peak-caller,
- complexity

2.7 Discussion

- Complexity,
- haplotypes,
- pseudo-linearity

2.8 Recent Developments

Haplotype aware mapping

2.9 Summary of Papers