(ABAN)

IO LIST SYSTEM CONFIG PARAMETER SETTING

| INPUT | SLOT | | |
|--------------------|--------|----|---|
| TEMP_OUT | I1=AI3 | 1 | |
| | 12=AI4 | 2 | |
| AC_CONTROL | 13 | 3 | |
| FDBK_DRV_SUP | 14 | 4 | 1 |
| FDBK_DRV_RET | 15 | 5 | 1 |
| | 16 | 6 | |
| TEMP_IN | 17=AI1 | 7 | |
| HUMID_IN | 18=AI2 | 8 | |
| FAULT_DRV_SUP | 19 | 9 | |
| FAULT_DRV_RET | I10 | 10 | 2 |
| | | | |
| | | | |
| OUTPUT | SLOT | | |
| DRAIN_VALVE | Q1 | 1 | |
| FILLING_VALVE | Q2 | 2 | 1 |
| DRV_SUP_RUN | Q3 | 3 | 1 |
| DRV_RET_RUN | Q4 | 4 | |
| CIR_PUMP | Q5 | 5 | |
| WATER_HEATER_POWER | Q6 | 6 | 2 |
| POWER_DAMPER | Q7 | 7 | |
| | Q8 | 8 | |

| SLOT 1 | SLOT 2 | SLOT 3 | SLOT 4 |
|------------------------------|--|---|---|
| LOGO! 24 RCE 8 DI/4 DO | Digital module DM8 230R 4 DI/4 DO Relay | Analog output AM2 AQ EXPAN 2AQ 0-10V CH 0 :DRIVE SUP CH 1 :DRIVE RET | Analog output AM2 AQ EXPAN 2AQ 0-10V CH 0 :DAMPER |