

Bryan Mac Peteza
IT-401

Abbreviation - Full Form

CPU	-	Central Processing Unit
PCI	-	Peripheral Component Interconnect
SATA	-	Serial Advanced Technology Attachment
PATA	-	Parallel Advanced Technology Attachment
ATX	-	Advanced Technology eXtended
PCB	-	Printed Circuit Board
LPX	-	Low Profile eXtension
NLX	-	New Low Profile eXtended
RAM	-	Random Access Memory
HDD	-	Hard Disk Drive
ISA	-	Industry Standard Architecture
AGP	-	Accelerated Graphics Port
IDE	-	Integrated Drive Electronics
EIDE	-	Enhanced Integrated Drive Electronics
VGA	-	Video Graphics Array
SVGA	-	Super Video Graphics Array
HDMI	-	High-Definition Multimedia Interface

S/PDIF - Sony/Philips Digital Interface

DVI - Digital Visual Interface

CMOS - Complementary Metal-Oxide Semiconductor

BIOS - Basic Input/Output System

IC - Integrated Circuit

ALU - Arithmetic Logic Unit

MHz - Megahertz

GHz - Gigahertz

WORM - Write Once Read Many

DRAM - Dynamic Random Access Memory

SRAM - Static Random Access Memory

SDRAM - Synchronous Dynamic Random Access Memory

RDRAM - Rambus Dynamic Random Access Memory

DIP - Dual In-line Package

SIPP - Single In-line Pin Package

SIMM - Single In-line Memory Module

DIMM - Dual In-line Memory Module

RIMM - Rambus In-line Memory Module

SODIMM - Small Outline Dual In-line Memory Module

KB - Kilobyte

MB - Megabyte

GB - Gigabyte

TB - Terabyte

CRT - Cathode Ray Tube

LCD - Liquid Crystal Display

OLED - Organic Light-Emitting Diode

ESD - Electrostatic Discharge

OS - Operating System

POST - Power-On Self Test

RTC - Real-Time Clock

NVRAM - Non-Volatile Random Access Memory

NCQ - Native Command Queuing

SSD - Solid-State Drive

DDR - Double Data Rate

SCSI - Small Computer System Interface

CLJ - Color LaserJet

RAID - Redundant Array of Independent Disks

BSB - Back Side Bus

FSB - Front Side Bus

MMU - Memory Management Unit

MMX - MultiMedia eXtensions

AMD - Advanced Micro Devices

PSIA - Physical Security Interoperability Alliance