Proxmark — Wrong vs Correct Read Examples

Side-by-side examples for Page mapping and Offset misalignment. Copyable commands and exact expected outputs.

Problem: Page Mapping (WRONG)

You wrote to blank:

```
pm3> lf t55xx write --blk 1 --data A0000000
pm3> lf t55xx write --blk 2 --data E3F00D51
```

Read default page (page0):

```
pm3> lf t55xx read --blk 1 --r1
```

Output (WRONG):

```
[+] Page 0
[+] 01 | 00000000    <-- looks empty
```

Interpretation: Data likely stored on page1 (alternate memory page).

Fix: Use --pg1 (CORRECT)

Check alternate page1:

```
pm3> lf t55xx read --blk 1 --r1 --pg1
```

Output (CORRECT):

```
[+] Page 1
[+] 01 | A0000000    <-- target data found
```

Actions:

```
pm3> lf t55xx write --blk 1 --data A0000000 --pg1
pm3> lf t55xx write --blk 2 --data E3F00D51 --pg1
```

Tip: Use --pg1 for this blank batch.

Problem: Offset Misalignment (WRONG)

Detect shows offset (example):

```
pm3> lf t55xx detect
[=] Offset..... 53
```

Read without setting offset:

```
pm3> lf t55xx read --blk 1 --r1
```

Output (WRONG):

```
[+] Page 0
[+] 01 | 000010FF    <-- shifted/garbled
```

Interpretation: Start bit wrong (need to set offset).

Fix: Set --offset N (CORRECT)

Set offset and re-read:

```
pm3> lf t55xx config --offset 53
pm3> lf t55xx read --blk 1 --r1
```

Output (CORRECT):

```
[+] Page 0
[+] 01 | A0000000
[+] 02 | E3F00D51
```

Tip: Use detected Offset value from lf t55xx detect.

Quick Commands (copy/paste)

```
hw tune                 # check antenna coupling
lf search               # detect LF tags (Indala/EM410x)
hf search               # detect HF tags (MIFARE/DESFire)
lf t55xx detect         # detect T55x7 chip and offset
lf t55xx read --blk 1 --r1   # read block 1 (page0)
lf t55xx read --blk 1 --r1 --pg1  # read block 1 (page1)
lf t55xx config --offset <N> # set detected offset
lf indala clone -r <raw>     # clone Indala raw to blank
```

Troubleshooting Hints

- If write accepts but readback is garbage: try --pg1 or set offset.
- If lf t55xx detect can't auto-detect modulation: run lf t55xx config --PSK3 --rate 16 --r1 then detect again.
- Test at real reader: reader acceptance is the final verification.
- Keep notes: raw, blank type, offset, page used for future repeatability.

Carry this sheet on your phone. Only clone tags you own or have client authorization.