Where Proxmark Saves Raw Dumps — Quick Field Sheet

Clear, one-page guide: where lf indala read dumps are saved, example session, verification, transfer, and common mistakes.

1) Where it gets saved (rules)

- Relative filename (no leading /) → saved in the current working directory of the proxmark client process.
  Example: if you started the client from ~/proxmark3/client then client_raw.bin will appear in ~/proxmark3/client.
- Absolute path → saved exactly where you point it.
  Example: lf indala read -f /home/pm3/dumps/client_raw.bin saves into /home/pm3/dumps/.

2) Example session (exact commands + what to expect)

Open ProxSpace terminal and build/run client from repo root:

```
cd ~/proxmark3        # your proxmark repo root
sudo ./client/proxmark3 /dev/ttyACM0
```

Inside the pm3 prompt:

```
pm3> lf indala read -f client_raw.bin
[+] Indala read saved to client_raw.bin
[=] Done!
```

Now exit the pm3 prompt with exit (or open a second terminal) and check the file:

```
# still in ProxSpace shell
cd ~/proxmark3/client
ls -l client_raw.bin
# show contents (if it's hex/text)
hexdump -C client_raw.bin | sed -n '1,40p'
# or if it's text:
cat client_raw.bin
```

If you want it saved elsewhere (recommended for organization), use an absolute path:

```
pm3> lf indala read -f /home/pm3/dumps/condo123_raw.bin
```

Then on host:

```
ls -l /home/pm3/dumps/condo123_raw.bin
```

3) Quick verification commands (view the stored data)

Depending on whether the file is binary or plain hex text:

Try 'file' to identify:

```
file client_raw.bin
```

Show first 200 bytes in hex:

```
hexdump -C client_raw.bin | sed -n '1,20p'
```

If it’s a text hex dump, simply:

```
head -n 20 client_raw.bin
```

If you see the hex string like a0000000e3f00d51 in the file — perfect. That’s the <raw> you paste into clone commands.

4) Handy workflow: save with a clear name (copy/paste ready)

Use date + building id so you don’t overwrite:

```
pm3> lf indala read -f /home/pm3/dumps/2025-10-02_buildingA_unit12_raw.bin
```

Then later:

use the saved file when cloning (if the client supports -r from file)
pm3> lf indala clone -r /home/pm3/dumps/2025-10-02_buildingA_unit12_raw.bin
(If clone only accepts raw hex inline, open file and copy the hex string: cat file | tr -d '\n'.)

5) Transferring files off ProxSpace VM to your Windows host

If you need the files on your laptop (Windows) for records:

- If ProxSpace is a VM with a shared folder, save to that shared path, e.g. /mnt/share/dumps/....
- Or from host (Windows) use scp from Linux VM to Windows (if SSH server on Windows), or use scp to another machine you control.
- Easiest: cat file and copy-paste into an email or cloud note (if small and not sensitive).

Example to copy to a shared folder /mnt/hgfs/share/dumps/:
pm3> lf indala read -f /mnt/hgfs/share/dumps/condoA_unit12_raw.bin

6) Common mistakes & how to avoid them

Mistake: Running pm3 from a different folder and wondering where client_raw.bin ended up.
Fix: Always use absolute paths or pwd before launching the client:
pwd
sudo ./client/proxmark3 /dev/ttyACM0
Mistake: Overwriting files.
Fix: Use unique filenames (date + address + tag type).
Mistake: Thinking the file is on the Proxmark device. It’s on the computer (host), not in the proxmark hardware.

Keep clear filenames and backups. Store consent forms with the raw files for legal coverage.