■ Condo Access Tag Cloning Detailed Guide

Proxmark3 + Iceman Firmware (Step-by-Step Scripts)

■ STEP 1: Detect the Tag
CMD: lf search
Outcome: Proxmark shows if tag is EM410x, HID Prox, or Indala.

■ EM410x / EM4x Tags
CMD: lf em410x reader
Outcome: Shows 40-bit ID.
Clone:
lf em410x clone --to t55xx
Verify:
lf search

■ HID Prox Tags
CMD: lf hid reader
Outcome: Shows Facility Code (FC) + Card Number (CN).
Clone:
lf hid clone --fc <facility> --cn <cardnum>
Example: lf hid clone --fc 123 --cn 4567
Verify:
lf hid reader

■ Indala Tags (Cycle through methods if one fails)
CMD: lf indala reader
Outcome: Shows Raw, FC, CN, and Printed (Heden) ID.

Method 1 (Raw):
lf t55xx wipe
lf indala clone -r <rawhex>
Example: lf indala clone -r a0000000e3f00d51
lf search

If Raw fails, wipe and try Method 2.

Method 2 (Facility Code + Card Number):
lf t55xx wipe
lf indala clone --fc <facility> --cn <cardnum>
Example: lf indala clone --fc 134 --cn 47173
lf search

If FC/CN fails, wipe and try Method 3.

Method 3 (Printed / Heden ID):
lf t55xx wipe