

Median Filtering Regeneration

Tuna Alikasıfoğlu

March 19, 2023

1 Full Comparison

Full result comparison between the reported and regenerated median filtering experiments on *sea surface temperature* dataset is provided in table 1. The underlying graph of reported results are not provided in the original paper [1], the generated results are obtained with k -NN underlying graph structure with several k values. The k -NN structure is used because the papers that use the *sea surface temperature* dataset usually use 5-NN graph for underlying graph [2], [3], which are also cited in [1]. The best overall results are bolded, where best generated results are underlined.

σ	Reported with Unknown Graph			Generated with k -NN Graph								
	Noisy	\mathcal{M}_1	\mathcal{M}_2	$\forall k$	$k = 1$		$k = 3$		$k = 5$		$k = 10$	
				Noisy	\mathcal{M}_1	\mathcal{M}_2	\mathcal{M}_1	\mathcal{M}_2	\mathcal{M}_1	\mathcal{M}_2	\mathcal{M}_1	\mathcal{M}_2
0.05	22.63	27.69	27.26	22.63±0.05	<u>27.00±0.06</u>	26.39±0.06	26.58±0.08	24.93±0.06	25.87±0.06	23.40±0.06	22.59±0.04	20.64±0.02
0.10	16.62	23.54	25.09	16.61±0.05	<u>21.68±0.06</u>	22.64±0.08	22.30±0.08	<u>22.86±0.07</u>	22.21±0.07	22.02±0.07	20.87±0.08	20.24±0.07
0.15	13.10	20.59	22.93	13.08±0.05	<u>18.33±0.06</u>	19.72±0.09	19.38±0.09	<u>20.93±0.08</u>	19.69±0.08	20.71±0.09	19.43±0.08	19.72±0.09
0.20	10.61	18.30	21.05	10.59±0.05	<u>15.90±0.07</u>	17.45±0.09	17.15±0.10	<u>19.17±0.09</u>	17.71±0.09	<u>19.44±0.10</u>	18.10±0.07	19.12±0.10
0.25	8.66	16.50	19.49	8.65±0.05	<u>13.99±0.07</u>	15.63±0.09	15.34±0.10	17.63±0.10	16.05±0.09	18.24±0.11	16.87±0.08	<u>18.45±0.12</u>
0.30	7.06	14.96	18.08	7.06±0.05	<u>12.43±0.07</u>	14.11±0.09	13.83±0.10	16.28±0.10	14.64±0.09	17.12±0.11	15.74±0.08	<u>17.77±0.13</u>
0.35	5.72	13.59	16.78	5.72±0.05	<u>11.10±0.07</u>	12.81±0.09	12.53±0.11	15.10±0.10	13.42±0.09	16.09±0.12	14.71±0.08	17.08±0.14
0.40	4.57	12.53	15.73	4.57±0.05	<u>9.94±0.07</u>	11.67±0.09	11.40±0.11	14.04±0.11	12.33±0.09	15.15±0.12	13.77±0.08	16.39±0.15

Table 1: Full result comparison of SNR values of denoised signals between reported and generated versions.

2 Best Comparison

σ	\mathcal{M}_1 Reported	\mathcal{M}_1 Generated
0.05	27.69	
0.10	23.54	
0.15	20.59	
0.20	18.30	
0.25	16.50	
0.30	14.96	
0.35	13.59	
0.40	12.53	

Table 2: Best Comparison of \mathcal{M}_1

References

- [1] D. B. Tay and J. Jiang, “Time-varying graph signal denoising via median filters,” *IEEE Transactions on Circuits and Systems II: Express Briefs*, vol. 68, no. 3, pp. 1053–1057, 2021. DOI: 10.1109/TCSII.2020.3017800.

- [2] K. Qiu, X. Mao, X. Shen, X. Wang, T. Li, and Y. Gu, “Time-varying graph signal reconstruction,” *IEEE Journal of Selected Topics in Signal Processing*, vol. 11, no. 6, pp. 870–883, 2017. DOI: 10.1109/JSTSP.2017.2726969.
- [3] J. H. Giraldo, A. Mahmood, B. Garcia-Garcia, D. Thanou, and T. Bouwmans, “Reconstruction of time-varying graph signals via sobolev smoothness,” *IEEE Transactions on Signal and Information Processing over Networks*, vol. 8, pp. 201–214, 2022. DOI: 10.1109/TSIPN.2022.3156886.