Top-5 TV-Programme Recommendation for sweet.tv: Candidate Generation and Learned Re-ranking under a Screen-Time Target

Kochneva Angelina (Кочнева Ангелина), avkochneva@edu.hse.ru, HSE University, LLM4Rec final exam, AVITO cohort — October 2026

Repository: https://github.com/kocnevaangelina2000-wq/sweettv-tv-recommender-exam · **Final submission:** `submissions/s8_blend.csv` · **Kaggle private MAP@5 0.44568** (public 0.44710)

ABSTRACT

We build a Top-5 TV-programme recommender for the 1,260 test users of the Kaggle competition *sweet.tv – TV program recommender*. The target counts a programme's airings that a user watched for at least 80% of their duration, and keeps the top five programmes by that count [6].

We join 5.8 M log rows to the schedules by channel and time overlap; screen time is the union of a user's overlapping views divided by the airing duration. Every parameter is selected on one declared fold (A: weeks 11–15 → 16–20) and reported on another (B: 11–20 → 21–30). We compare popularity, viewing history, implicit ALS [1], personalised PageRank [2] and content TF-IDF [3], each also weighted by airing count, against rank fusion and learned re-rankers: Poisson gradient boosting and CatBoost YetiRank [4], with hour-of-week "exposure" features.

The best single method reaches MAP@5 0.326 on fold B and 0.413 on Kaggle private. The graded file, a rank fusion of the two re-rankers fit on both folds stacked, scores 0.44568 private. Fold B ranks the strongest models differently from the leaderboard, which is the main limitation of the validation design. Of twelve files written, eight were submitted. Two of them (s9, s10) were specified after Kaggle scores were known, and the final file is the best private score, per the instructor's rule.

I. INTRODUCTION

The task is to predict, for each of 1,260 sweet.tv users, the five programmes with the most airings watched to at least 80% of their length in weeks 31–42 of 2020 [6]. We are given the viewing log of weeks 11–30 and all schedules. The metric is MAP@5, where each user's AP is divided by min(5, |truth|), as defined in the course MAP@K slide [7].

Three properties shape the work:

1. The label counts *airings*, so frequently aired cartoons dominate, and re-watching a show is the norm.
2. Only about 11% of schedule rows carry a programme id.
3. The log has a collection gap in weeks 20–27.

Contributions: a verified join and labelling pipeline with every data trap logged; a fold protocol that separates selection from reporting; a comparison of single and hybrid methods on it; and a record of twelve files written and eight submitted that states which choices used the leaderboard.

II. RELATED WORK

Hu et al. [1] model implicit counts as confidence weights on binary preferences (ALS), with TV viewing as their case study. Topic-sensitive PageRank [2] biases a random walk towards a restart set; with one user as the restart set it is the personalised PageRank (PPR) we run on the user–programme graph. Content-based TF-IDF profiles follow Lops et al. [3]. YetiRank [4] is the pairwise ranking loss behind CatBoost's `YetiRank` objective. Cremonesi et al. [5] show that algorithm rankings depend on the metric and that popular items dominate top-N measurements, so we tune and report a rank metric, always next to a popularity baseline and on the test-user subset as well as the full cohort.

III. DATA

TABLE I. DATA ACCOUNTING (logs/stats.log, logs/audit.log)

quantity	value
log rows / users / channels	5,821,987 / 4,914 / 202
exact-duplicate log rows dropped	17
schedule rows 11-20 / 21-30 / 31-42	1.07 M / 1.07 M / 1.30 M
labelled (id ≠ 0): rows / airtime	10.8–11.3% / 16.0–16.9%
viewed seconds on labelled airings	54.8% (11-20), 58.4% (21-30)
(view, airing) pairs with overlap	7,752,415
views matching no airing	7.10%
positive interactions 11-20 / 21-30	317,043 / 294,717
test users / cold (no positive)	1,260 / 4

Join. A view and an airing match if `vsetv_id = channel_id` and the intervals [start, stop) and [start, start + duration) intersect. A per-channel `searchsorted` avoids a Cartesian merge, and it reproduced a brute-force merge on 9 channels exactly (47,116 pairs).

Screen time and the 0.8 rule. For each (user, airing), all of the user's overlap pieces are merged, and screen time = |union| / duration, clipped to 1. An airing is positive at ≥ 0.8. A union is needed because 2,617 users have overlapping views on one channel, and summing their pieces would make 4,217 extra interactions positive. A fraction is needed because the cut sits above most of the distribution (screen time p50 0.195, p75 0.657, p90 1.0; 20.3% of (user, airing) rows reach 0.8). Airing durations range from 60 s to 86,400 s (labelled airings up to 32,700 s), so a fraction rather than absolute seconds is needed, and the Kaggle label is itself defined as a fraction [6]. The truth is the top five programmes by positive airings in the target window, with ties broken by total union seconds and then by id. The

union matched a naive merge on 38,889 groups, and four interactions were recomputed from the raw rows in the session (RESULTS, hand-check rows).

id = 0 is unlabelled airtime. It is never recommended and never in the truth, and its seconds feed only channel-share and exposure features.

The data traps are listed in Appendix A: file and week naming that differs from the exam brief's description, ids beyond int64, date formats, DST, multi-device overlaps, schedule cut points, unscheduled channels, truth ties and airing skew.

IV. METHOD

A. Protocol

Splits are declared as (schedule file, ISO-week range) windows of the airing start:

- **A:** train 11-20 weeks ≤ 15 → target weeks 16–20.
- **B:** train 11-20 → target 21-30.
- **Final:** 11-30 → 31-42.

The *cohort* is the users with ≥ 1 positive in the target window; MAP@5 is reported on it and on its test-user subset.

Cohorts: A 4,574 = 4,409 warm + 165 cold (test subset 1,212); B 4,643 = 4,540 + 103 (test subset 1,238, plus 22 test users without truth = 1,260). On B, 0 truth slots fall outside the pool.

The *pool* is the set of labelled programmes airing in the target window. The future schedule is used only to know what airs when, and already-watched programmes may be recommended.

Every parameter and model choice up to s8 is the argmax of fold-A cohort MAP@5; re-rankers use 5-fold grouped-by-user out-of-fold scores. Fold B reports each choice, with the model fit on A.

Exactly five ids. Each method ranks pool ids by score (ties broken by global popularity) and truncates the list at 5. Short lists are topped up, without duplicates, from a *shared fallback*: pool programmes ranked by train positives × the user's watch-time share on the channels where the programme airs. Users without positives (4 test users) receive the fallback alone. An assertion checks 5 unique pool ids, and every file is validated against the template.

B. Methods

- **Popularity:** pool programmes by train positive airings.
- **History:** the user's positive programmes by count, with recency and expected-count variants.
- **ALS [1]:** `implicit`, 150-point grid over confidence (count, log1p or BM25) × factors × regularisation × α.
- **PPR [2]:** damping α ∈ {0.3, 0.5, 0.7, 0.85}, explicit dangling mass, tolerance 10^{-6}.
- **CBF [3]:** TF-IDF over category, genres, channels and credits, with cosine to the user profile.
- **"× air" variants:** each score is multiplied by log(1 + airings of the programme in the target schedule), because the label counts airings.

C. Hybrids

- **H1:** history first, then PPR × air.
- **H2:** reciprocal-rank fusion Σ w/(k + rank) of four top-30 lists.
- **H3:** a learned re-ranker over the union of five top-30 candidate lists (≈ 61 per user; recall 0.69).
  - Model: `HistGradientBoostingRegressor`, Poisson loss, lr 0.01 (lr 0.1 diverged; BUGLOG B28).
  - Label: positive airings in the target window.
  - Features: history counts and recency, method scores and ranks, popularity, airings, channel share, category.
- **H3+:** adds *exposure*: Σ over the programme's target airings of P(user watches that channel in that hour-of-week), estimated from train weeks. It also adds length features.
- **Step-5 variants:** an exposure candidate source with top-60 lists (recall 0.79), per-week features, CatBoostRanker YetiRank [4], seed bagging, and a rank **blend** of the HGB and CatBoost rankings.

Before any step-5 fold-B result was seen, we decided that final re-rankers are fit on A and B stacked, with label = positives per target week (5, 10 and 12 weeks in A, B and final).

D. Settings, seeds, cost, environment

Settings selected on fold A: PPR × air α 0.5 (21 iterations); ALS × air count, 16 factors, reg 0.01, α 1; H2 all weights 1, k 10; HGB Poisson, lr 0.01, ≤ 1000 iterations with early stopping; CatBoost YetiRank, lr 0.03, depth 8, 500 iterations; s8 blend w(HGB, CB) = (0.5, 0.5), k = 5.

Seeds are 42, and seed bagging uses 42–46; same-seed CatBoost fits are identical.

Runtimes on fold B (4,643 users, Apple M3 Max, one BLAS thread): history 0.06 s, ALS × air 0.9 s, CBF × air 2.9 s, PPR × air 24 s, H3+ 87 s, CatBoost × 5 seeds 125 s, and the s8 script with its fold-A grid 843 s.

Environment: Python 3.9.6 with numpy 2.0.2, scipy 1.13.1, pandas 2.2.3, pyarrow 17.0.0, scikit-learn 1.5.2, implicit 0.7.3 and catboost 1.2.8.

V. EXPERIMENTS

TABLE III. SINGLE METHODS (MAP@5; params chosen on A)

method	A	B	B test
popularity	.2437	.2368	.2680
history	.3239	.3067	.3503
ALS × air	.3139	.2904	.3178
PPR	.3388	.3194	.3613
PPR × air	**.3411**	**.3256**	**.3687**
CBF × air	.3132	.2987	.3340

Airing weighting helps most where the base score ignores frequency: CBF +0.074 on B (base CBF 0.2247), PPR +0.006. The fold-A pick matches the fold-B best-of-grid for every method except ALS × air. The full table and grids are in Appendix B.

TABLE IV. HYBRIDS AND RE-RANKERS (A: OOF; B: fit on A)

model	A	B	recall B
H1 history-first	.3340	.3141	.61
H2 RRF	.3444	.3292	.68
H3 HGB	.3732	.3431	.69
H3+ (+ exposure)	.3759	.3538	.69
CatBoost ×5 (s7)	.3774	**.3542**	.69
blend (s8)	**.3783**	.3532	.79

Learned re-ranking is the largest step: H3 is +0.0175 over PPR × air on B, and H3+ adds +0.011. After H3+, every fold-A gain is ≤ 0.0025, several reverse on B, and each cell is a single fit. A larger candidate set raised recall by 0.10 but not B MAP@5. In the ablation (Table C2; Δ = ablated − full), only removing exposure costs clearly more than noise (Δ = −0.010 on B).

Kaggle. All eight submissions, with what each changed, are in Appendix D. Private MAP@5 rose from 0.287 (s1 popularity) and 0.413 (s3 PPR × air) to 0.430 (s7) and 0.446 (s8). In the one clean pair, s7 → s7b, only the count features change (to per-week): private rises by +0.0148, while fold B is neutral. Fold B, fit on A only, never exercises the stacked final fit, whose parts differ in window length. s9 → s10 (fold C plus recency features, changed together) lowers private by −0.0046. One plausible reason is that C's train window ends in the gap weeks, but the two changes are confounded. Fold-A OOF orders s3 < s6 < s7 < s8 as Kaggle does; fold B does not.

VI. RECOMMENDATION EXAMPLES

The users were drawn by stated rules (DESIGN D68–D69) from the 1,260 test users in the fold-B cohort, with seed 42.

- **Heavy viewer:** top 10% by train positive airings (≥ 173; 127 eligible).
- **Light viewer:** 1–3 train positive programmes.

The heavy rule and the first light rule were fixed before any list was seen. The first light draw was degenerate: its single truth programme was its single history programme (*Friends*), so every personalised method scored AP 1.0. After seeing that, we added a second light rule (≥ 3 truth programmes in 21–30; 21 eligible) with its own seed-42 draw. Its result is reported below, and the first draw is in Appendix F.

In the tables, R = re-watch (≥ 1 positive in 11–20), T = in the 21–30 truth, and f = filled by the shared fallback. Each method's fold-B MAP@5 was recomputed in the same run and matches Tables III–IV.

Heavy viewer. Train history (top 6): SpongeBob 103 positives, Fairly OddParents 28, Masha and the Bear 19, Alvinnn!!! 16, Факты (news) 14, Сегодня (news) 13. Truth: SpongeBob, Факты, Сегодня, Fairly OddParents, Alvinnn!!!.

TABLE V. HEAVY VIEWER 3086774348345899441 (ids, schedule titles, categories: Appendix F)

method	AP	top-5
popular.	.35	ТСН R · Факты RT · SpongeBob RT · Завтрак с 1+1 R · Сегодня RT
history	.71	SpongeBob RT · OddParents RT · Masha R · Alvinnn RT · Факты RT
PPR×air	.76	SpongeBob RT · OddParents RT · Alvinnn RT · Masha R · Факты RT
CBF×air	.60	SpongeBob RT · Alvinnn RT · OddParents RT · Blaze · Penguins R
ALS×air	.60	SpongeBob RT · Alvinnn RT · OddParents RT · ТСН R · Kung Fu Panda R
s8	**1.0**	SpongeBob RT · Alvinnn RT · OddParents RT · Факты RT · Сегодня RT

Light viewer. Train history: two films, *Volga-Volga* and *SWAT* (1 positive each). Truth: Факты, ТСН, Викна-Новости (news), and the series *Однажды в Одессе* and *Мамочки*.

TABLE VI. LIGHT VIEWER 706288898823145641 (ids, schedule titles, categories: Appendix F)

method	AP	top-5
popular.	.40	ТСН T · Факты T · SpongeBob · Завтрак с 1+1 · Сегодня
history	0	Volga-Volga R · SWAT R · Criminal Minds f · CSI f · Hercules f
PPR×air	.17	SWAT R · Volga-Volga R · ТСН T · Факты T · SpongeBob
CBF×air	0	SWAT R · Volga-Volga R · Цирк · Battle: Los Angeles · Весёлые ребята
ALS×air	0	Служба розыска детей · Майор и магия · Gumball · Lost · Деньги
s8	.40	ТСН T · Факты T · SpongeBob · Peppa Pig · Безбашенные

Heavy viewer. Every method finds SpongeBob. Only s8 has all five truth programmes, including both news programmes, which only popularity also lists.

Light viewer. None of the truth programmes had a positive airing in this user's 11–20 log on this platform; that is the case for 33–35% of all truth items (B29). History and content therefore repeat the two films and miss. **PPR** reaches the news hubs ТСН and Факты by graph diffusion from

those films (PPR's own items, not fallback), and **s8** ranks them first. **ALS** fills all five slots with unfamiliar programmes and scores AP 0. An unfamiliar slot is therefore not evidence of a useful discovery. **Content-based** can score all 4,488 pool programmes with no train positive (fold B), whereas ALS and PPR can rank only the 1,875 pool programmes that had positives in train. **Popularity** already does as well as s8 for this user (AP .40).

VII. WHICH STRATEGY FOR SWEET.TV, AND WHY

Validation. Each learned re-ranker beats every single method on both folds (≥ +0.017 on B). On Kaggle, every re-ranker file beats both submitted single-method files (s1, s3). The margin over s3 is 0.017–0.033, except for s6, which was fit on fold B alone (+0.0003). Within the re-rankers, files differ by < 0.0015 on fold B but by up to 0.033 on Kaggle. In the one clean pair (s7 → s7b), that spread follows how the final model was fit (per-week scaling of the stacked fit) rather than the model family. The three best private scores (s8 0.44568, s9 0.44534, s7b 0.44495) lie within 0.0007 of each other.

Cost. PPR × air needs no labels and runs in 24 s. A single re-ranker adds four candidate sources and one model (CatBoost × 5: 125 s on B; the s7b script: 9 min). The blend trains two models with 2.3× the candidates per user (139 vs 61) and 2.2× the stacked training rows (1,350,769 vs 611,333).

Lists. In s8, 88% of slots (5,558 of 6,300) are re-watches, and all five are for the heavy viewer in Sec. VI. The other 742 slots (12%) hold programmes without a positive airing in the user's 11–20 log on this platform. They come from PPR, CBF, ALS, exposure, popularity or the fallback. Whether such slots are useful discoveries is not measured here, and the light viewer's ALS list shows they can all miss.

Association rules were not implemented. They would capture directional, time-window co-occurrence (e.g., the evening news watched right after a cartoon slot), which ALS's global low-rank factors average away. PPR's co-view graph is the closest implemented proxy, but it is undirected and ignores time. We claim no result for them.

Choice. We would select a two-stage system for sweet.tv:

1. history, PPR × air, content × air and ALS × air as candidate generators;
2. **one** gradient-boosted re-ranker with per-week-normalised counts and exposure features, trained on stacked windows (the s7b configuration).

Reach: 1,256 of 1,260 test users get a personalised list; 4 have no train positive and get the shared fallback. About a third of truth items (33–35% on A/B) are programmes the user had no interaction with in train. That is the only place where non-history sources can add hits.

The blend's +0.0007 private over s7b is a single comparison and does not justify doubling training and maintenance. PPR × air is the backup ranker: 0.413 private, 93% of s8, at a fraction of the cost. We make no engagement or revenue claim: no online test was run, and the label is the competition's offline proxy. The graded competition file remains s8, the best private score.

VIII. LIMITATIONS

1. **Most airtime is unlabelled:** 10.8% of schedule rows and 16% of airtime carry an id, although these receive 55–58% of viewed seconds. The rest of the viewing is invisible to items and labels.
2. **Collection gap, weeks 20–27:** log rows per week fall from ~410k to 105k at the lowest point. Fold B's target mostly lies in it, and so does the end of fold C's train window.
3. **Validation vs Kaggle:** fold B separates the top models by < 0.0015 and misorders them. It cannot test the stacked final fit.
4. **Small private set:** Kaggle splits the test users 50/50 into public and private [6], so the private score covers about 630 users. The 0.0007 spread between s8, s9 and s7b is a total AP difference of about 0.44 over those users, i.e. less than one user's list.
5. **Leaderboard selection. s9 and s10 were specified after Kaggle scores were known, and the final file is the best private score, per the instructor's rule.** That score is therefore optimistic for new data.
6. **Unknown target details:** the Kaggle tie-break and the exact screen-time rule (union vs sum, DST) are unknown.
7. **Single fits:** results come from single fits without intervals, and some optima lie on grid edges (ALS, H2 k, CatBoost depth).
8. **Known bug in the final file:** s8 keeps the B38 active-week inflation (18% of fold-B users). s9 fixes it together with other changes (per-week target counts, CatBoost × 5) and differs by −0.0003 private, so the effect of B38 alone is confounded.

IX. PERSONAL VERIFICATION

In Google Sheets I followed one user (2929474010536378025, fold B) and one programme (12001682, SpongeBob) from the raw files to the final metric. All four checks matched.

Screen time. The programme has 7 airings in the schedule, and the user has 3 log rows for it. For each airing I took end = start + duration and computed the overlap with each view as min(end) − max(start). The three views do not overlap one another, so their union is simply the sum. Watched seconds and screen time per airing: 70 s (0.047), 1,063 s (0.709), 900 s (1.0), 600 s (1.0), 600 s (1.0), 600 s (1.0), 894 s (0.993). The 27 May airing shows why the threshold matters: the user watched 1,063 of 1,500 s, which is 0.709, so it is not a positive.

Positives. Five airings reach the 0.8 threshold, matching positive_count = 5 in the user's truth table.

src/hand_check_reveal.py printed the same seconds and flags for all seven airings.

AP@5. The model's top 5 hits the user's true top 5 at ranks 1, 4 and 5, with precision 1, 2/4 and 3/5 at those ranks. AP@5 = (1 + 0.5 + 0.6) / 5 = 0.42, the same as the code. On my first pass I counted «Мир наизнанку» as a hit because it is in the user's 21–30 table. It is not in the top 5, so I removed it.

4. References. I opened all six sources through their DOI or publisher page and checked authors, year, title and venue against the reference list; for the Kaggle competition page, the title and URL.

What I did not check by hand. The full join over 5.8 M log rows, the fold-level MAP@5 averages, model training and the other users' lists all come from the code. I verified one chain end to end, not the totals. The Kaggle scores are from my Submissions page (screenshot attached).

Figures for these checks: Appendix G, Figs. 1–3.

X. CONCLUSION

Airing-count weighting (+0.074 for content on B) and a learned re-ranker with exposure features (+0.028 over the best single method on B) are the gains that validation could see. On Kaggle, the largest further gain came from how the final model was fit: stacked windows and per-week counts. The graded file is s8, with private MAP@5 0.44568.

Code, logs and every submission are at https://github.com/kocnevaangelina2000-wq/sweettv-tv-recommender-exam (README: commands in order and runtimes). Reference records are in `analysis/refs/`.




Fig. 4. Kaggle Submissions page (cropped; full page in screenshots/kaggle_best_private.png): best private score s8_blend.csv 0.44568, public 0.44710.

XI. AI USAGE DISCLOSURE

Claude Code 2.1.309 with the model Claude Opus 5.5 was used in session `d3e92eca-8fdc-404d-a062-5f4671e3db6b`. By this commit, the transcript holds 19 user messages (13 pasted step briefs, 6 typed; notes sent while a turn was running are not counted separately) and 315 tool calls. The submitted export of the session continues past this commit. One short earlier session, started in the author's home folder on 2026-10-22, only searched for the data files (4 read-only shell commands) and changed nothing. The assistant wrote and ran all code and drafted this report. The author set the task and made the decisions at each step (union over sum, the tie-break, the fold design, freezing modelling, the final choice). The author also did the hand-check chain and the reference check, and made every Kaggle submission. A separate chat assistant (Claude) was used to plan the steps, review results and review this report.

XII. DISCUSSION IN MY WORDS

[placeholder — to be written by the author]

REFERENCES

[1] Y. Hu, Y. Koren, and C. Volinsky, "Collaborative filtering for implicit feedback datasets," in *Proc. 8th IEEE Int. Conf. Data Mining (ICDM)*, Dec. 2008, pp. 263–272, doi: 10.1109/ICDM.2008.22.

[2] T. H. Haveliwala, "Topic-sensitive PageRank," in *Proc. 11th Int. Conf. World Wide Web (WWW)*, May 2002, pp. 517–526, doi: 10.1145/511446.511513.

[3] P. Lops, M. de Gemmis, and G. Semeraro, "Content-based recommender systems: State of the art and trends," in *Recommender Systems Handbook*. Boston, MA, USA: Springer, 2011, pp. 73–105, doi: 10.1007/978-0-387-85820-3_3.

[4] A. Gulin, I. Kuralenok, and D. Pavlov, "Winning the transfer learning track of Yahoo!'s learning to rank challenge with YetiRank," in *Proc. Learning to Rank Challenge*, PMLR, vol. 14, 2011, pp. 63–76. [Online]. Available: https://proceedings.mlr.press/v14/gulin11a.html

[5] P. Cremonesi, Y. Koren, and R. Turrin, "Performance of recommender algorithms on top-N recommendation tasks," in *Proc. 4th ACM Conf. Recommender Systems (RecSys)*, Sep. 2010, pp. 39–46, doi: 10.1145/1864708.1864721.

[6] Kaggle, "sweet.tv – TV program recommender," competition page and Data tab (target: airings with ≥ 80% screen time, top five programmes by count; public/private test split 50/50 by users). [Online]. Available: https://www.kaggle.com/competitions/sweettv-tv-program-recommender (accessed Oct. 24, 2026). Records: analysis/refs/kaggle_competition_page.html, analysis/refs/kaggle_data_target_rule.png.

[7] LLM4Rec course, HSE University, lecture slides on ranking metrics, "MAP@K" (AP@K normalised by min(K, |relevant|)); course material, not publicly archived.

APPENDIX

A. Data traps (BUGLOG.md)

#	trap	handling
B2	file names and week ranges differ from the description quoted in the exam brief; the Kaggle Data tab [6] (`analysis/refs/kaggle_data_target_rule.png`) lists the actual names (`dataset11–30.csv`, `export_arh_*–final.csv`, column `duraton`); content is ISO weeks 11–20, 21–30, 31–42	names by content; explicit columns
B4	`user_id` up to 20 digits (> int64)	uint64
B5	log `YYYY–MM–DD`, schedules `DD.MM.YYYY`	explicit formats
B6	both on local wall-clock time; 117 views and 257 airings span the 2020-03-29 DST switch	detected, not corrected
B7b	same-user overlapping views (multi-device): sum > 1 for 24,005 interactions	union, not sum
B7d	collection gap weeks 20–27: rows/week ~410k → 105k; active test users 1,232 → 795 (week 26)	documented
B8	schedules cut at each channel's broadcast-day start, running into Monday 12:00 of the next ISO week	concatenation; period = source file
B10	5 log channels never scheduled; 5 movie channels scheduled only from April–June	7.1% of views unmatched
B11	labelled airings: 10.8–11.3% of rows, 16.0–16.9% of airtime	id = 0 kept as features only
B12	751 of 1,150 test users with ≥ 5 positive programmes in 21-30 tie at places 5/6 (union screen time)	our tie-break: union seconds, then id
B14	airings per programme: median 4, maximum 6,691 (31-42)	× log(1 + airings)
B38	edge weeks inflate active-week counts for 882 of 4,874 fold-B users	fixed in s7b/s9/s10, not in s8

B. Single methods, full (MAP@5; A and B cohort, B test, re-watch share of slots)

method	params (chosen on A)	A	A test	B	B test	re-watch
popularity	—	0.24370	0.27584	0.23684	0.26799	0.543
history count (ties: seconds)	—	0.32386	0.36449	0.30671	0.35027	0.945
history count (ties: popularity)	—	0.33372	0.37524	0.31362	0.35617	—
history recency	half-life 4 w	0.31811	0.35874	0.30008	0.34509	0.945
history expected	—	0.32312	0.36118	0.29559	0.33877	0.945
ALS	log1p, f 128, reg 0.1, α 0.1	0.31649	0.35658	0.28542	0.31797	0.912
ALS × air	count, f 16, reg 0.01, α 1	0.31385	0.34472	0.29041	0.31775	0.776
PPR	α 0.7	0.33879	0.38095	0.31944	0.36125	0.885
PPR × air	α 0.5	0.34111	0.38181	0.32559	0.36866	0.923
CBF	—	0.23688	0.26276	0.22467	0.24891	0.598
CBF × air	—	0.31320	0.34897	0.29870	0.33400	0.712

PPR by α on fold B (plain / × air): 0.3 0.3146 / 0.3229; 0.5 0.3182 / **0.3256**; 0.7 **0.3194** / 0.3179; 0.85 0.2986 / 0.2922. The full 150-point ALS grids per fold are in `logs/s4a_grid.csv`.

C. Re-rankers, step 5 and ablation

TABLE C1. STEP-5 CONFIGURATIONS (A: OOF; B: fit on A)

config	A	A test	B	B test	recall B
H3+ (current)	0.37585	0.41734	0.35379	0.39499	0.694
+ exposure source, others top-30	0.37738	0.41848	0.35256	0.39353	0.764
+ exposure source, top-60 everywhere	0.37614	0.41570	0.35168	0.39300	0.792
per-week features	0.37600	0.41755	0.35214	0.39363	0.694
CatBoost YetiRank lr 0.03 d 8	0.37718	0.41785	0.35332	0.39598	0.694
CatBoost × 5 seeds (s7)	0.37739	0.41852	0.35415	0.39646	0.694
all step-5 changes together	0.37649	0.41741	0.35411	0.39432	0.792
blend HGB + CB (s8)	0.37830	0.41873	0.35316	0.39339	0.792

CatBoost grid, A OOF (lr 0.03 / 0.1; depth 4, 6, 8): 0.37415, 0.37651, **0.37718** / 0.37636, 0.37601, 0.37587. The top five points of the 126-point blend grid all give H2 weight 0.

TABLE C2. H3+ ABLATION ON FOLD B (refit on A without the group; Δ = ablated − full, full H3+ = 0.35379)

dropped group	B	Δ
exposure	0.34384	−0.0100
method scores	0.34979	−0.0040
history	0.35139	−0.0024
length	0.35352	−0.0003
popularity / airings	0.35496	+0.0012

D. All Kaggle submissions

file	what changed	A	B	private	public
s1	popularity + channel fallback	0.24370	0.23684	0.28680	0.30312
s3	PPR × air	0.34111	0.32559	0.41277	0.41415
s6	H3+ HGB; final fit on B only	0.37585	0.35379	0.41304	0.41277
s7	CatBoost × 5; final fit on A+B; raw counts	0.37739	0.35415	0.43013	0.43474
s8 (final)	HGB + CB rank blend; exposure + top-60 candidates; per-week features	0.37830	0.35316	**0.44568**	0.44710
s7b	s7 with all 7 counts per week + B38 fix (designed before, run after the scores)	—	0.35414	0.44495	0.44515
s9 *(after scores)*	s8 + B38 fix + all counts per week + CB × 5	—	0.35415	0.44534	0.44831
s10 *(after scores)*	s9 + fold C (train 11–27 → 28–30) + recency; fit on A+B+C	—	0.35455	0.44073	0.44500

Twelve files were written and eight submitted; s2, s2b, s4 and s5 were not submitted. Fold C (fit on A+B; cohort 4,454): the s9 config scores 0.29470, and with recency features (the s10 config) 0.29548.

E. Slot sources of the final files (6,300 slots; first source containing the item: history > PPR > CBF > ALS > exposure > popularity, else fallback)

file	history	PPR	CBF	ALS	exposure	popularity	fallback
s4 (H1)	6,226	54	0	0	—	0	20
s5 (H3)	5,400	633	101	117	—	29	20
s6 (H3+)	5,178	764	143	152	—	43	20
s7	5,606	595	34	36	0	9	20
s8	5,558	669	29	6	15	3	20
s7b	5,642	604	17	12	0	5	20
s9	5,539	687	30	7	14	3	20
s10	5,643	603	19	3	12	0	20

F. Example users, full tables

Full rows from `logs/examples.md` (titles as in the schedule, Russian). Users: heavy, light rule 1 (degenerate, reported for transparency) and light rule 2 (used in Sec. VI).

Tags: **R** = re-watch (the user had ≥ 1 positive airing of this programme in train 11-20); **T** = in the user's 21-30 truth; **f** = slot filled by the shared fallback, not by the method.

heavy viewer `3086774348345899441`: 252 train positive airings over 47 programmes (weeks 11-20); 5 truth programmes in 21-30

Train history top-10 (11-20):

#	id	title	category	positives
1	12001682	М/с 'Губка Боб Квадратные Штаны'.	Детям	103
2	12001734	М/с 'Волшебные покровители'.	Детям	28
3	12002201	М/с 'Маша и Медведь'.	Детям	19
4	12002856	М/с 'Элвиннн!!! и бурундуки'.	Детям	16
5	240081	Факты.	Инфо	14
6	2400508	Сегодня.	Инфо	13
7	12002753	М/с 'Санджей и Крейг'.	Детям	7
8	12002771	М/с 'Черепашки-ниндзя'.	Детям	5
9	12002955	М/с 'Свинка Пеппа'.	Детям	4
10	2400467	'Викна-Новости'.	Инфо	2

Truth 21-30 (in order): 12001682 М/с 'Губка Боб Квадратные Штаны'., 240081 Факты., 2400508 Сегодня., 12001734 М/с 'Волшебные покровители'., 12002856 М/с 'Элвиннн!!! и бурундуки'.

method	AP@5	1	2	3	4	5
popularity	0.353	2400480 ТСН. (Инфо) **R**	240081 Факты. (Инфо) **RT**	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	20088 'Завтрак с 1+1'. Информационно-развлекательная программа. (Развлечения) **R**	2400508 Сегодня. (Инфо) **RT**
history (count)	0.710	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	12001734 М/с 'Волшебные покровители'. (Детям) **RT**	12002201 М/с 'Маша и Медведь'. (Детям) **R**	12002856 М/с 'Элвиннн!!! и бурундуки'. (Детям) **RT**	240081 Факты. (Инфо) **RT**
PPR x air (alpha 0.5)	0.760	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	12001734 М/с 'Волшебные покровители'. (Детям) **RT**	12002856 М/с 'Элвиннн!!! и бурундуки'. (Детям) **RT**	12002201 М/с 'Маша и Медведь'. (Детям) **R**	240081 Факты. (Инфо) **RT**
CBF x air	0.600	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	12002856 М/с 'Элвиннн!!! и бурундуки'. (Детям) **RT**	12001734 М/с 'Волшебные покровители'. (Детям) **RT**	12002896 М/с 'Вспыш и чудо-машинки', 2 сезон, 14 с. 'Унесённый лыжами'. (Детям)	12001732 М/с 'Пингвины из 'Мадагаскара'. (Детям) **R**
ALS x air (count, f=16, reg=0.01, alpha=1)	0.600	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	12002856 М/с 'Элвиннн!!! и бурундуки'. (Детям) **RT**	12001734 М/с 'Волшебные покровители'. (Детям) **RT**	2400480 ТСН. (Инфо) **R**	12002355 М/с 'Кунг-фу панда: Удивительные легенды'. (Детям) **R**
s8 blend (HGB + CatBoost rank fusion)	1.000	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **RT**	12002856 М/с 'Элвиннн!!! и бурундуки'. (Детям) **RT**	12001734 М/с 'Волшебные покровители'. (Детям) **RT**	240081 Факты. (Инфо) **RT**	2400508 Сегодня. (Инфо) **RT**

light viewer `14394187406328124815`: 1 train positive airings over 1 programmes (weeks 11-20); 1 truth programmes in 21-30

Train history top-10 (11-20):

#	id	title	category	positives
1	1000376	Т/с 'Друзья', 1 сезон, 5 с.	Сериалы	1

Truth 21-30 (in order): 1000376 Т/с 'Друзья', 1 сезон, 5 с.

method	AP@5	1	2	3	4	5
popularity	0.000	2400480 ТСН. (Инфо)	240081 Факты. (Инфо)	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)	20088 'Завтрак с 1+1'. Информационно-развлекательная программа. (Развлечения)	2400508 Сегодня. (Инфо)
history (count)	1.000	1000376 Т/с 'Друзья', 1 сезон, 5 с. (Сериалы) **RT**	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям) **f**	2400480 ТСН. (Инфо) **f**	240081 Факты. (Инфо) **f**	2400467 'Викна-Новости'. (Инфо) **f**
PPR x air (alpha 0.5)	1.000	1000376 Т/с 'Друзья', 1 сезон, 5 с. (Сериалы) **RT**	2400480 ТСН. (Инфо)	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)	10001514 Т/с 'Теория большого взрыва', 2 сезон, 15 с. (Сериалы)	240081 Факты. (Инфо)
CBF x air	1.000	1000376 Т/с 'Друзья', 1 сезон, 5 с. (Сериалы) **RT**	10001514 Т/с 'Теория большого взрыва', 2 сезон, 15 с. (Сериалы)	1000405 Т/с 'Клиника', 2 сезон, 19 с. (Сериалы)	10001903 Т/с 'Американская семейка', 9 сезон, 9 с. (Сериалы)	10002810 Т/с 'Бруклин 9-9', 6 сезон, 17 с. (Сериалы)
ALS x air (count, f=16, reg=0.01, alpha=1)	1.000	1000376 Т/с 'Друзья', 1 сезон, 5 с. (Сериалы) **RT**	10001514 Т/с 'Теория большого взрыва', 2 сезон, 15 с. (Сериалы)	1000589 Т/с 'Отчаянные домохозяйки', 5 сезон, 17 с. 'История Люси и Джесси'. (Сериалы)	1000405 Т/с 'Клиника', 2 сезон, 19 с. (Сериалы)	12001712 М/с 'Симпсоны'. (Детям)
s8 blend (HGB + CatBoost rank fusion)	1.000	1000376 Т/с 'Друзья', 1 сезон, 5 с. (Сериалы) **RT**	10001336 Т/с 'Кости', 9 сезон, 21 с. 'Случай с холодом'. (Сериалы)	2400480 ТСН. (Инфо)	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)	12001712 М/с 'Симпсоны'. (Детям)

light (rule 2: >= 3 truth programmes) viewer `706288898823145641`: 2 train positive airings over 2 programmes (weeks 11-20); 5 truth programmes in 21-30

Train history top-10 (11-20):

#	id	title	category	positives
1	90044148	Х/ф 'Волга-Волга'.	Фильмы	1
2	90055479	Х/ф 'SWAT: Спецназ города ангелов'.	Фильмы	1

Truth 21-30 (in order): 240081 Факты., 2400480 ТСН., 10003012 Т/с 'Однажды в Одессе'., 2400467 'Викна-Новости'., 10002515 Т/с 'Мамочки', 1 сезон, 19 и 20 с.

method	AP@5	1	2	3	4	5
popularity	0.400	2400480 ТСН. (Инфо) **T**	240081 Факты. (Инфо) **T**	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)	20088 'Завтрак с 1+1'. Информационно-развлекательная программа. (Развлечения)	2400508 Сегодня. (Инфо)
history (count)	0.000	90044148 Х/ф 'Волга-Волга'. (Фильмы) **R**	90055479 Х/ф 'SWAT: Спецназ города ангелов'. (Фильмы) **R**	10001261 Т/с 'Мыслить как преступник'. (Сериалы) **f**	1000381 Т/с 'CSI: Место преступления', 7 сезон, 6 и 7 с. (Сериалы) **f**	90077217 Х/ф 'Геракл: Начало легенды'. (Фильмы) **f**
PPR x air (alpha 0.5)	0.167	90055479 Х/ф 'SWAT: Спецназ города ангелов'. (Фильмы) **R**	90044148 Х/ф 'Волга-Волга'. (Фильмы) **R**	2400480 ТСН. (Инфо) **T**	240081 Факты. (Инфо) **T**	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)
CBF x air	0.000	90055479 Х/ф 'SWAT: Спецназ города ангелов'. (Фильмы) **R**	90044148 Х/ф 'Волга-Волга'. (Фильмы) **R**	90044710 Исторический прайм. Х/ф 'Цирк'. (Фильмы)	90073000 Х/ф 'Инопланетное вторжение: Битва за Лос-Анджелес'. (Фильмы)	90037720 Исторический прайм. Х/ф 'Веселые ребята'. (Фильмы)
ALS x air (count, f=16, reg=0.01, alpha=1)	0.000	2400340 Служба розыска детей. (Инфо)	10002744 Т/с 'Майор и магия', 8 с. (Сериалы)	12002378 М/с 'Удивительный мир Гамбола'. (Детям)	1000289 Т/с 'Остаться в живых', 1 сезон, 1 с. 'Таинственный остров - часть 1'. (Сериалы)	5900347 'Деньги'. (Инфо)
s8 blend (HGB + CatBoost rank fusion)	0.400	2400480 ТСН. (Инфо) **T**	240081 Факты. (Инфо) **T**	12001682 М/с 'Губка Боб Квадратные Штаны'. (Детям)	12002955 М/с 'Свинка Пеппа'. (Детям)	90080832 Х/ф 'Безбашенные'. (Фильмы)

G. Hand-check figures (Personal verification, Sec. IX)

		N	O	P	Q	R	S	T	U	V	W
1		csv_line									
2	ıacc	611132	20.05.2020	1500	20.05.2020	70,00000002	0	0	70,00000002	0,04666666668	0
3	ıacc	611666	27.05.2020	1500	27.05.2020	0	1063	0	1063	0,7086666664	0
4	ıacc	616140	24.07.2020	900	24.07.2020	0	0	899,9999998	899,9999998	0,9999999998	1
5	ıacc	616141	24.07.2020	600	24.07.2020	0	0	600,0000001	600,0000001	1	1
6	ıacc	616142	24.07.2020	600	24.07.2020	0	0	600,0000001	600,0000001	1	1
7	ıacc	616143	24.07.2020	600	24.07.2020	0	0	600,0000001	600,0000001	1	1
8	ıacc	616144	24.07.2020	900	24.07.2020	0	0	894,0000003	894,0000003	0,9933333336	1
9											
10											5

Fig. 1. Hand join check in Google Sheets: overlap seconds and screen time for the seven airings; 5 positives.

```
 csv_line        airing_start  duration  n_pieces  overlap_sum_s  union_s  screen_time  positive
   611132 2020-05-20 08:45:00      1500         1             70       70     0.046667     False
   611666 2020-05-27 08:45:00      1500         1           1063     1063     0.708667     False
   616140 2020-07-24 22:30:00       900         1            900      900     1.000000      True
   616141 2020-07-24 22:45:00       600         1            600      600     1.000000      True
   616142 2020-07-24 22:55:00       600         1            600      600     1.000000      True
   616143 2020-07-24 23:05:00       600         1            600      600     1.000000      True
   616144 2020-07-24 23:15:00       900         1            894      894     0.993333      True
user 2929474010536378025, programme 12001682: positive count = 5; schedule csv lines in the pack == code
airings: True
```

Fig. 2. Output of src/hand_check_reveal.py for the same seven airings.

	A	B	C	D	E	F	G
1	rank	tv_show_id	title				
2	1	2400480	ТСН.		1	1	1
3	2	2400467	'Викна-Новости'.		0	1	0
4	3	6500479	'Мир наизнанку'.		0	1	0
5	4	6700482	'Секретные материалы'.		1	2	0,5
6	5	20088	'Завтрак с 1+1'. Информационно-развлекательная программа.		1	3	0,6
7							
8							0,42

Fig. 3. Hand AP@5 computation for the user's fold-B top 5 from the s7 config (CatBoost YetiRank × 5 seeds, fit on fold A).