Polynomial calculus degree at least 5 over F2 for the onto functional pigeonhole principle with surplus 8

Lindheim, Björn

DOI: 10.5281/zenodo.23999675

1 Introduction

Cite as: https://doi.org/10.5281/zenodo.23999675

Setting

The onto functional pigeonhole principle onto-FPHP$_n^{n+k}$ says that $n+k$ pigeons can be mapped one-to-one onto n holes; it is false for every $k \geq 1$. In Boolean variables x_{ij} (pigeon i in hole j) its axioms are $\sum_j x_{ij} - 1$, $\sum_i x_{ij} - 1$, $x_{ij}x_{i'j}$ and $x_{ij}x_{ij'}$, the linear encoding used for this family [1, 2]. A polynomial calculus (PC) refutation over $\mathbb{F}_2$ derives 1 from the axioms and the Boolean axioms $x^2 - x$ by linear combinations and multiplication by a variable; its degree is the largest degree of a line.

Over $\mathbb{F}_2$, with surplus $k = 2^\ell$, the PC degree is exactly 2 at $k = 2$ and exactly 4 at $k = 4$ (companion results in the same library). This finding is about $k = 8$.

Result

For every $n \geq 7$, onto-FPHP$_n^{n+8}$ has no PC refutation over $\mathbb{F}_2$ of degree 4. Its PC degree is therefore at least 5, while the general bound for surplus divisible by p^2 (companion finding) gives only 3 at $p = 2$. So at $p = 2$ the third level is strictly harder than the second for every $n \geq 7$.

The proof combines a general argument with a finite certificate of 95,550 steps, each checked by the Lean kernel.

Why it matters

Razborov's Question 7 asks whether PC degree for surplus p^ℓ stays bounded in characteristic p [2]. Riis and Sitharam's Theorem 33 gives degree at least 7 for $k = 8$ once $N \geq 196$ [4], which is stronger than this result for large n. The

range $7 \leq n < 196$ is not covered by that theorem. This result covers it, and it is machine-checked.

Proved vs checked

The result is proved in Lean 4 for every $n \geq 7$; the certificate is part of the proof, not a separate check up to a bound. The proof uses only the standard axioms `propext`, `Classical.choice` and `Quot.sound`. A second agent in the run checked the certificate independently, with its own program written from the Lean definitions, not from the author's code. That is an independent check of the certificate, not an independent Lean re-proof. No person has reviewed the proof. The same library also states the result for standard (syntactic) PC (`std_no_deg4_k8`).

Novelty statement

This result extends:

- Riis-Sitharam, ECCC TR97-048, Theorem 33: PC degree >= 2^l - 1 for onto-PHP^{N+p^l}_N over characteristic p once N >= (21+3p^2)(2^l - 2) - p (same family; proof not checked by us; at l = 2 this is >= 3 against our >= p+1 from n = 2p-1; at p = 2, l = 3 it is >= 7 for N >= 196 against our >= 5 for n >= 7).
- Beame-Riis 1998, Theorem 8.1 and Lemma 8.7: Nullstellensatz degree between 2^l - 1 and p^l - 1 (multiplier degree) for the same family; Section 10 lists polynomial-calculus lower bounds as open.
- Riis 1993, as Theorem 8 of Razborov's survey: degree-d PC refutations when C(m,d) and C(n,d) differ mod p, which gives the matching upper bound p for k = pc, p not dividing c (via Lucas).
- Razborov, Proof complexity of pigeonhole principles (2001), Question 7: the fixed-p, fixed-l bounded-degree question for onto-FPHP^{n+p^l}_n.
- Miksa-Nordstrom (JACM 2024): general PC degree method; onto-FPHP with m = n+1 easy (Riis); the case of characteristic dividing the surplus not covered.

Our prior-art search (2026-11-05) covered:

- Riis, Sitharam, Non-constant degree lower bounds imply linear degree lower bounds, ECCC TR97-048 (1997), pp. 36-38 and 45-46 (Theorem 33, Propositions 27 and 28), opened 2026-10-29
- Beame, Riis, More on the relative strength of counting principles, DIMACS Series 39 (1998), homes.cs.washington.edu/~beame/papers/riis.pdf: Theorem 8.1, Lemma 8.7, Section 10, opened 2026-10-27 and 2026-11-01

- Razborov, Proof complexity of pigeonhole principles, DLT 2001 (LNCS 2295), people.cs.uchicago.edu/~razborov/files/php_survey.pdf: Theorem 8, Question 7, footnote 5, opened 2026-10-27 and 2026-10-29
- Riis, BRICS Report RS-99-29, opened 2026-10-29
- Miksa, Nordstrom, A generalized method for proving polynomial calculus degree lower bounds (CCC 2015; JACM 2024; arXiv 1505.01358), opened 2026-10-27
- de Rezende et al., Theory of Computing 21(6) (2025), opened 2026-10-29
- Lauria et al., Theory of Computing 21(4) (2025), opened 2026-10-27

The checkers' full answers, with every query and file they searched, are published with this finding (`prior-art/`).

If you know of related work we missed, please open an issue.

This result was found by AI research agents (the autoresearch harness). It was proved in Lean; the proof and check files are included so anyone can re-run them.

How it was produced

Promoted declaring sources are included under `checks/library/`.

2 Claims

Claim K18

Lean `Work.L3.Main.no_deg4`: for every $n \geq 7$, `ontoFPHP n 8` (onto-FPHP$_n^{n+8}$, functional encoding) has no degree-4 `PPCRefutation 2` (polynomial calculus over $\mathbb{Z}/2$, line degree 4). Unconditional.

Status: proved (axioms: propext, Classical.choice, Quot.sound).

Verified. No check scripts.

Evidence.

- proof `checks/K18-Main.lean`: Work.L3.Main.no_deg4 — pass (`results/K18-4.json`)

Prior art. Partial prior art.

Provenance. Run `20261028-0841`, claims K18, run-folder commit `19b6167239a90c29b4a3f0ff0f64c79016f` published 2026-11-06.

3 Discussion

The upper bound from Riis's criterion is 8 [3, 2], so for $k = 8$ the degree lies between 5 and 8 for $n \geq 7$. This is one case, not a growth result in ℓ. We have not checked the proof of Theorem 33 and cite it for comparison only.

4 How to verify

Each finding has its check scripts in `claims/pc-degree-5-onto-fphp-surplus-8/checks/` of the findings repository. Run each with `python -I <script>`; it passes if it exits with status 0. Promoted declaring sources are included under `checks/library/`; publication checks import their modules and inspect theorem axioms. The checks are Python scripts and need the packages of the research image (the image's `requirements.txt`); the Lean checks also need `lean`.

5 Revisions

- 2026-11-06 — Math rendering on the site; paper lists only cited references

References

[1] Paul Beame and Søren Riis. More on the relative strength of counting principles. In *Proof Complexity and Feasible Arithmetics*, volume 39 of *DIMACS Series in Discrete Mathematics and Theoretical Computer Science*, pages 13–35. American Mathematical Society, 1998.

[2] Alexander A. Razborov. Proof complexity of pigeonhole principles. In *Developments in Language Theory (DLT 2001)*, volume 2295 of *Lecture Notes in Computer Science*, pages 100–116. Springer, 2002.

[3] Søren Riis. *Independence in Bounded Arithmetic*. PhD thesis, University of Oxford, 1993.

[4] Søren Riis and Meera Sitharam. Non-constant degree lower bounds imply linear degree lower bounds. Technical Report TR97-048, Electronic Colloquium on Computational Complexity, 1997.