


OpenCV- Working with OpenCV

Aresh T. Saharkhiz

Saturday, September 17, 2011

Blobs with opencv (internal function)




There are many open source opencv BLOB libraries that you can use. i have tried several of these, however because of the 64 bit machine that im using recompiling these are very troublesome.

If you have heard of these libraries:

1. "cvBlobsLib": <http://opencv.willowgarage.com/wiki/cvBlobsLib>
2. "cvBlob": <http://code.google.com/p/cvblob/>
3. "Bloblib" by Dave Grossman (also referred to as "Blob Analysis Package"): Go to <http://tech.groups.yahoo.com/group/OpenCV/files/>

You will know that opencv also has a built in function that can help you find blobs using `cv::findContour` and see some statistics using the `cv::moments`. eventually make these functions similar to `regionprops` Matlab function



The BLOB FINDER CLASS:

```
class atsBlobFinder
{
public:
    atsBlobFinder(cv::Mat src)
    {
        numBlobs = 0;
        cv::Mat img; //must create a temporary Matrix to hold the gray scale or
        wont work
        cv::cvtColor(src,img,CV_BGR2GRAY); //Convert image to GrayScale
```

Popular Posts

[Blob Detection, Connected Component \(Pure OpenCV\)](#)

Connected-component labeling (alternatively connected-component analysis, blob extraction, region labeling, blob discovery, or region ex...

[Blobs with opencv \(internal function\)](#)

There are many open source opencv BLOB libraries that you can use. i have tried several of these, however because of the 64 bit machine that...

[Template Matching using OpenCV internal function](#)

For this example we need to add the following to the linker dependencies:
opencv_core220d.lib opencv_highgui220d.lib
opencv_imgproc220d.lib...

[2D/3D estimation using solvePnP in opencv \(NOT SOLVED\)](#)

In opencv "solvePnP" is used to find known points on a known 3D object. doing so the objects orientation relative to the camera co...

[Load a Video in OpenCV](#)

```
#include <stdlib.h> #include <stdio.h> #include
<math.h> #include <string.h>
#include<opencv2/opencv.hpp>...
```

Live tracker

```

img = img > 1; //create the binary image

///cv::adaptiveThreshold(src,src,64,ADAPTIVE_THRESH_MEAN_C,THRESH_BINARY,7,13);
//create a binary image

    findContours( img, contours, hierarchy, CV_RETR_CCOMP,
CV_CHAIN_APPROX_SIMPLE ); //Find the Contour BLOBS
vector<Moments> _mu(contours.size() );
vector<Point2f> _mc( contours.size() );
for( int i = 0; i < contours.size(); i++ )
{
    _mu[i] = moments( Mat(contours[i]), false );
    _mc[i] = Point2f( _mu[i].m10/_mu[i].m00 , _mu[i].m01/_mu[i].m00);
}
mu = _mu;
mc = _mc;
numBlobs = contours.size();
}


void Draw(cv::Mat &dst)
{
    // iterate through all the top-level contours,
    // draw each connected component with its own random color
    for( int i = 0; i < contours.size(); i++ )
    {
        Scalar color(  rng.uniform(0,255),  rng.uniform(0,255),
rng.uniform(0,255) );
        drawContours( dst, contours, i, color, CV_FILLED, 8, hierarchy );
        // drawCross(mc[i],Scalar(0,0,255), 5,dst); //put a cross
        char buff[255];
        sprintf(buff, "%d", i);

        string text = std::string(buff);
        cv::putText( dst,text,mc[i],0,0.5,Scalar(0,0,255),1,8,false);
    }
}

int getNumBlobs()
{
    //need to create a buffer for output or wrong reference
    /*char buff[255];
    sprintf(buff, "%d", numBlobs);*/
    return numBlobs;
}

private:
    vector<vector<Point> > contours;
    vector<Vec4i> hierarchy;
    vector<Moments> mu;
    vector<Point2f> mc;
    int numBlobs;
};

```



```

#include <iostream>

// Include OpenCV
#include <opencv/cv.h>
#include <opencv/highgui.h>

using namespace cv;

```

Live Traffic Feed

on 1 Account - \$3.95/mo
Web Hosting bluehost

A visitor from
Chelmsford,
Massachusetts viewed
"OpenCV- Working with
OpenCV: Blobs with
opencv (internal function)"
25 secs ago
Horizonte, Minas Gerais
viewed "OpenCV-
Working with OpenCV:
Artificial Intelligence (K
Nearest Neighbor) in
OpenCV" 1 min ago
A visitor from Surabaya,
Jawa Timur viewed
"OpenCV- Working with
OpenCV: Blob Detection,
Connected Component
(Pure Opencv)" via
A visitor from Kraków,
Malińskie viewed
"OpenCV- Working with
OpenCV: Opencv with
OpenGL (installation and
tests)" 1 hr 2 mins ago
Niederösterreich viewed
"OpenCV- Working with
OpenCV: Nose Tracking
using Kalman Filter and
Viola-Jones Classifier" 1 hr 48 mins
ago
A visitor from Chennai,
Tamil Nadu viewed
"OpenCV- Working with
OpenCV: finding the
center of gravity in
OpenCV" 2 hrs 5 mins ago
A visitor from Mumbai,
Maharashtra viewed
"OpenCV- Working with
OpenCV: Artificial
Intelligence (K Nearest
Neighbor in OpenCV)" 2
hrs 38 mins ago
A visitor from Mayt,
Borsod-Abauszemplen
viewed "OpenCV-
Working with OpenCV:
Blobs with opencv
(internal function)" 2 hrs
40 mins ago
A visitor from Korea
Republic of viewed
"OpenCV- Working with
OpenCV: SURF
keypoints using a camera"
A visitor from Surabaya,
Jawa Timur viewed
"OpenCV- Working with
OpenCV: Region of
interest selection ROI" 3
Real-time view · Menu

FEEDJIT Live Traffic

About Me



saharkiz

All Content are taken
from copyrighted

Blog Archive

- 2012 (3)
- ▼ 2011 (16)
 - December (3)
 - October (1)
 - ▼ September

```
#define drawCross( center, color, d, drawing ) \
    line( drawing, Point( center.x - d, center.y - d ), \
    Point( center.x + d, center.y + d ), color, 2, CV_AA, 0); \
    line( drawing, Point( center.x + d, center.y - d ), \
    Point( center.x - d, center.y + d ), color, 2, CV_AA, 0 )

RNG rng(12345);
int main( int argc, char** argv )
{
    Mat src;
    // the first command line parameter must be file name of binary
    // (black-n-white) image
    if(!(src=imread("pic6.png", CV_LOAD_IMAGE_GRAYSCALE)).data)
    {
        printf("OOOPS");
        waitKey(0);
        return -1;
    }

    Mat dst = Mat::zeros(src.rows, src.cols, CV_8UC3);

    src = src > 1;
    //cv::adaptiveThreshold(src,src,64,ADAPTIVE_THRESH_MEAN_C,THRESH_BINARY,7,13);
    namedWindow( "Source", 1 );
    imshow( "Source", src );

    vector<vector<Point> > contours;
    vector<Vec4i> hierarchy;

    findContours( src, contours, hierarchy,
        CV_RETR_CCOMP, CV_CHAIN_APPROX_SIMPLE );

    /// Get the moments
    vector<Moments> mu(contours.size() );
    vector<Point2f> mc( contours.size() );
    for( int i = 0; i < contours.size(); i++ )
    {
        mu[i] = moments( Mat(contours[i]), false );
        mc[i] = Point2f( mu[i].m10/mu[i].m00 , mu[i].m01/mu[i].m00);
    }

    // iterate through all the top-level contours,
    // draw each connected component with its own random color
    for( int i = 0; i < contours.size(); i++ )
    {
        Scalar color( rng.uniform(0,255), rng.uniform(0,255), rng.uniform(0,255) );

        drawContours( dst, contours, i, color, CV_FILLED, 8, hierarchy );
        // drawCross(mc[i],Scalar(0,0,255), 5,dst); //put a cross
        char buff[255];
        sprintf(buff, "%d", i);

        string text = std::string(buff);
        cv::putText(dst,text,mc[i],0,0.5,Scalar(0,0,255),1,8,false);
    }

    namedWindow( "Components", 1 );
    imshow( "Components", dst );
    waitKey(0);
}
```

material for educational use ONLY!
[View my complete profile](#)

(6)
Blobs with opencv (internal function)
finding the center of gravity in opencv
2D/3D estimation using solve PnP in opencv (NOT SOL...
Opencv with OpenGL (installation and trials)
Histogram computation on a video
Nose Tracking using Kalman Filter and Viola and Jo...

► July (6)
► 2010 (15)

Followers

Join this site with Google Friend Connect

Members (5)



Posted by [saharkiz](#) at 7:49 AM

+1 Recommend this on Google

Labels: [drawcontours](#), [findcontours](#), [moments](#), [opencv](#)

Already a member? [Sign in](#)

1 comment:



Patrick J.P - Os visionários eram chamados de loucos. August 7, 2012 at 6:16 AM

Ty!

I loved your code.

you can use filter2D, threshold and Canny to make more precise !

ty again !

[Reply](#)

Enter your comment...

Comment as:

Google Account

[Publish](#)

[Preview](#)

[Newer Post](#)

[Home](#)

[Older Post](#)

Subscribe to: [Post Comments \(Atom\)](#)

Ethereal template. Powered by [Blogger](#).

This ad is supporting your extension *Bookmark Sentry*: [More info](#) | [Privacy Policy](#) | [Hide on this page](#)