Installation Manual - mCloud Version 1

Koen van der Kruk

June 5, 2016

Contents

1	Intr	roduction	2
2	Rec	quirements	2
3	Inst	stallation	
	3.1	Installation - Server Side	2
	3.2	Installation - Client Side	4
		3.2.1 Make connection	5

1 Introduction

This document will describe the installation of a custom created cloud storage by Koen van der Kruk in collaboration with Nanquanu (cg?).

This tutorial can be used for server- and client side usage with mCloud. Choose the right section for your own needs.

The latest mCloud version can be found at the following place:

https://github.com/koen-github/mCloud

I am not responsible for any damage that possibly can happen when using this tutorial, including the usage of mCloud. I test all the steps in a virtualbox machine running 'Debian GNU/Linux 8 (jessie) 64-bit'

I recommend to firstly try to successfully setup a full working mCloud in a virtualbox, and later try to install it in your normal workspace. Note: Make sure to read also the text BEFORE you run the unix-command. Sometimes the command has to be changed to fill in the specific needs of your own setup.

2 Requirements

I assume you have the at least a Debian distribution running like: Ubuntu, Linux Mint, Xubuntu or Debian.

- A PC running a debian distribution
- Internet Connection
- Some linux knowledge about running commands in terminal and googling your own problems.
- Central server system also containing mCloud
- As client and server it's required to have full administrator (root) rights onto your box.

3 Installation

You can choose what kind of mCLoud installation you want. If you're just a normal user who has been ordered to install mCloud on your local machine, you can choose for Client Side installation.

3.1 Installation - Server Side

As admin you probably know a lot about ubuntu and debian, but I will still explain every step. Start by opening a new terminal.

- 1. Clone the mCloud repository in a new and clean directory.
 - # git clone git@github.com:koen-github/mCloud.git
- 2. Change directory into mCloud using
 - # cd mCloud/
- 3. First make sure you have all the dependencies installed on your PC:
 - # sudo apt-get install sshfs lvm2 cryptsetup openssh-server openssh-client nfs-kernel-server nfs-common portmap acl
- 4. Now install the debian package in the mCloud/ folder. Run this command:
 - # sudo dpkg -i mcloud-*.deb
- 5. Open a new terminal, so do not yet follow the steps onscreen of the dpkg installer.
- 6. Create a new directory in your home folder where you want to locate the mCloud encrypted image. Change IMAGE_MCLOUD to something of your own!
 - # mkdir IMAGE_MCLOUD
- 7. Go back to the installation window of mCloud, choose 'server' and press Enter.
- 8. Go inside the newly created folder of IMAGE_MCLOUD with:
 - # cd IMAGE_MCLOUD
- 9. Get the full installation path of mCloud using this command
 - # pwd

This will return something like:

- # /home/koen/IMAGE_MCLOUD
- 10. Paste it into the installation window of mCloud and press Enter.
- 11. Type into the installation window the image size, like: 100M, 200M or something larger and press Enter
- 12. Type in a name of your mCloud image and press enter
- 13. Choose YES to setup mCloud with ACL permissions and press Enter. After the installation is finished, you have to follow these steps online: https://help.ubuntu.com/community/FilePermissionsACLs#Enabling_ACLs_in_the_Filesystem

After you followed these steps, you have to run the commands specified on the terminal.

- 14. Add mcloud-users to your sudoers, so users can create their own groups of people with own repositories and press Enter.
- 15. Now carefully read the log in the terminal to make sure you finished all the steps.

3.2 Installation - Client Side

This is a step for step guide to install mCloud on your local machine as normal user.

- 1. Clone the mCloud repository in a new and clean directory.
 - # git clone git@github.com:koen-github/mCloud.git
- 2. Change directory into mCloud using
 - # cd mCloud/
- 3. First make sure you have all the dependencies installed on your PC:
 - # sudo apt-get install sshfs lvm2 cryptsetup openssh-server openssh-client nfs-kernel-server nfs-common portmap acl
- 4. Now install the debian package in the mCloud/ folder. Run this command:
 - # sudo dpkg -i mcloud-*.deb
- 5. Open a new terminal, so do not yet follow the steps onscreen of the dpkg installer.
- 6. Create a new directory in your home folder where you want to locate the mCloud encrypted image. Change IMAGE_MCLOUD to something of your own!
 - # mkdir IMAGE_MCLOUD
- 7. Go back to the installation window of mCloud, choose 'client' and press Enter.
- 8. Go inside the newly created folder of IMAGE_MCLOUD with:
 - # cd IMAGE_MCLOUD

- 9. Get the full installation path of mCloud using this command
 - # pwd

This will return something like:

- # /home/koen/IMAGE_MCLOUD
- 10. Paste it into the installation window of mCloud and press Enter.
- 11. Type into the installation window the image size, like: 100M, 200M or something larger and press Enter
- 12. Type in a name of your mCloud image and press enter
- 13. Now carefully read the log in the terminal to make sure you finished all the steps.

3.2.1 Make connection

To setup a connection to a central server, run this command:

mcloud assignServer

Generate a new SSH key pair on the default location, if you already have one you can send that one out to the central server.

You also have to know the IP of the central server.

Wait for the server admin to apply your rights on the central server.