# IDEA Demo Server: Remote Access for Justice

Reaching wizardly-hugle over Tailscale

For Justice (Part B) and Koen (Part A). Version 1.0, 13 October 2026

IDEA - offline school computing. Prepared for Koen Swings's team.
No passwords, keys or tokens are included. Koen sends the passwords separately.

# Contents


How to use this guide ..... 3
1. What this is and why ..... 4
  1.1 In plain words ..... 4
  1.2 The steps at a glance ..... 5
  1.3 What you need ..... 5
  1.4 The addresses ..... 5
2. Sharing wizardly-hugle with Justice ..... 7
  2.1 Before you start ..... 7
  2.2 Share the machine ..... 7
  2.3 Stop the share later (revoke) ..... 8
  2.4 Good to know for Koen ..... 8
3. Setting up Tailscale on your devices ..... 10
  3.1 Create your Tailscale account ..... 10
  3.2 Install on Ubuntu (your Raspberry Pi) ..... 10
  3.3 Install on Windows ..... 11
  3.4 Install on macOS ..... 11
  3.5 Install on Android ..... 12
  3.6 Install on iPhone or iPad ..... 12
4. Accepting the share invite ..... 13
5. Checking that it works ..... 14
  5.1 On your Ubuntu Pi (terminal) ..... 14
  5.2 On a phone, tablet, Windows PC or Mac ..... 14
6. Opening the IDEA Console and the apps ..... 15
  6.1 The IDEA Console ..... 15
  6.2 Kolibri ..... 15
  6.3 Nextcloud ..... 15
  6.4 Kiwix (offline Wikipedia) ..... 16
  6.5 Bookmarks ..... 16
  6.6 Following the teacher tutorial remotely ..... 16
7. Troubleshooting ..... 17
  7.1 Tailscale is not connected or you are logged out ..... 17
  7.2 wizardly-hugle is not in your machine list ..... 17
  7.3 tailscale up says you need sudo ..... 17
  7.4 The page does not load ..... 18
  7.5 wizardly-hugle is switched off, asleep or offline ..... 18
  7.6 Everything is very slow ..... 18
8. Do's and don'ts, and privacy ..... 19
  8.1 Do's and don'ts ..... 19
  8.2 Privacy: what each side can see ..... 20
Appendix A. Quick reference ..... 21
Appendix B. Sources (read on 13 October 2026) ..... 22

# How to use this guide

This guide explains how Justice can use Koen's IDEA demo server, **wizardly-hugle**, from anywhere in the world: from Zimbabwe, from a hotel, or from home. Justice uses it to give demos and to follow the teacher tutorial (`IDEA-teacher-tutorial.pdf`) without being in Belgium.

The guide has two parts:

- **Part A, for Koen** (section 2): share the one machine wizardly-hugle with Justice, and stop the share later.
- **Part B, for Justice** (sections 3 to 8): install Tailscale, accept the share, open the IDEA Console and the apps, and fix common problems.

Each step has:

1. **Do:** what to do.
2. ✔ **Check:** how to see that it worked.

> **No passwords in this guide.** The passwords for the IDEA Console and for the demo accounts in Kolibri and Nextcloud are **not** written here. Koen sends them to Justice separately (for example in a private message). Keep them private and do not write them on paper that stays at a school.

> **wizardly-hugle is also a real working server.** Next to the demo apps it runs **MilkWise**, an app that Koen's family uses every day. Use only the IDEA Console and the demo apps (Kolibri, Nextcloud, Kiwix). **Never open, stop or remove MilkWise**, and never stop or remove any app that you did not install yourself. See section 8.

# 1. What this is and why

## 1.1 In plain words

wizardly-hugle is a Raspberry Pi in Koen's home in Belgium. It runs the same IDEA software as the school servers that Justice takes to Zimbabwe: the **IDEA Console** and the apps **Kolibri**, **Nextcloud** and **Kiwix** (offline Wikipedia).

wizardly-hugle is **not** open to the public internet. To reach it from far away, we use **Tailscale**. Tailscale is a free app that builds a private, encrypted connection ("tunnel") between devices over the normal internet. Each Tailscale user has their own private network of devices, called a **tailnet**.

- Justice installs Tailscale on his own devices and signs in with **his own** Tailscale account. He gets his own tailnet.
- Koen **shares** only the one machine wizardly-hugle with Justice's account. Justice does **not** join Koen's tailnet and cannot see Koen's other devices.
- After that, Justice opens wizardly-hugle's web pages in a normal web browser, using the address `100.115.60.6`.




**Figure 1.** Justice's device connects over the internet, through an encrypted Tailscale tunnel, to wizardly-hugle in Belgium

## 1.2 The steps at a glance





**Figure 2.** The five steps: Justice creates an account and installs Tailscale, sends his email address, Koen shares the machine, Justice accepts the invite and opens the Console

## 1.3 What you need

| ☐ | What | Notes |
|---|---|---|
| ☐ | A device with a web browser | Justice's Raspberry Pi with Ubuntu, or a Windows PC, Mac, Android phone or tablet, iPhone or iPad. |
| ☐ | Internet access | Any internet works: Starlink, mobile data, hotel Wi-Fi. |
| ☐ | A Google, Microsoft, Apple or GitHub account | Tailscale has no passwords of its own: you sign in with one of these accounts [3]. |
| ☐ | The passwords from Koen | Sent separately, not in this guide. |

## 1.4 The addresses

| Service | Address to type in the browser |
|---|---|
| IDEA Console | `http://100.115.60.6:8081` |
| Kolibri | `http://100.115.60.6:54189` |
| Nextcloud | `http://100.115.60.6:50065` |
| Kiwix (offline Wikipedia) | `http://100.115.60.6:61312` |

`100.115.60.6` is wizardly-hugle's Tailscale address. The number after the colon (`:8081` and so on) is the **port**: it chooses the app. These addresses only work while Tailscale is running and connected on your device.

# Part A: For Koen

# 2. Sharing wizardly-hugle with Justice

This part is for Koen. It takes about five minutes. The menu names below are from Tailscale's sharing documentation [1].

## 2.1 Before you start

1. **Do:** Wait for Justice's email with the address of **his** Tailscale account (Part B, section 3.1).
2. **Do:** Sign in to the Tailscale admin console at `https://login.tailscale.com/admin/machines` with Koen's account. Only an **Owner**, **Admin** or **IT admin** of the tailnet can share a machine [1].
3. **Do:** Find wizardly-hugle on the **Machines** page. Type `100.115.60.6` in the search box.

> **Name in Tailscale.** In Koen's Machines list, wizardly-hugle is currently listed under its Tailscale machine name **idea** (full name `idea.tail2d60.ts.net`), with the address `100.115.60.6`. The IDEA Console calls the same box wizardly-hugle. Always check the address `100.115.60.6` before you share, so you share the right machine.

✔ **Check:** you see one row with the address `100.115.60.6`.

## 2.2 Share the machine

**Option 1: share by email (recommended).** Tailscale sends Justice a single-use invite link [1].

1. **Do:** In the row of wizardly-hugle, select the **...** menu (three dots), then select **Share**. The **Share** dialog opens.
2. **Do:** Select the **Share by email** tab.
3. **Do:** Type Justice's email address.
4. **Do:** Select **Share**.

**Option 2: share with a link.** Use this if the email does not arrive.

1. **Do:** In the row of wizardly-hugle, select the **...** menu, then **Share**.
2. **Do:** Select the **Copy invite link** tab. Leave **Reusable link** switched **off**: the link is then single-use, so only one person can accept it.
3. **Do:** Select **Copy share link**. The link is now on your clipboard.
4. **Do:** Send the link to Justice in a private message (WhatsApp, Signal or email).

> **Treat the invite link like a password.** Whoever accepts it first can reach wizardly-hugle [1]. Do not post it in a group chat. An unused invite link expires after **30 days** [1].

✔ **Check:** after Justice has accepted, his picture and email address appear in the **Share** dialog of wizardly-hugle, and the Machines list shows that wizardly-hugle is shared with an external user [1].

Then send Justice the passwords for the IDEA Console and the demo accounts, **separately** (not in the same message as the invite link).

## 2.3 Stop the share later (revoke)

Revoke the share when Justice no longer needs it, or at once if a device of his is lost or stolen.

1. **Do:** Open the **Machines** page of the admin console.
2. **Do:** For wizardly-hugle, select the **...** menu, then **Share**.
3. **Do:** In the **Share** dialog, select the **...** menu next to Justice's invite, then select **Revoke invite** [1].

✔ **Check:** Justice's name is gone from the Share dialog. From now on he cannot reach wizardly-hugle. To give access again, send a new invite; he must accept the new one [1].

If you also want to lock him out of the apps, change the IDEA Console and demo passwords.

## 2.4 Good to know for Koen

- **Justice sees only this one machine.** A shared machine is visible only to the person who accepted it, not to the rest of his tailnet, and not to Koen's other machines [1].
- **Quarantine.** A shared machine can answer connections from Justice, but it **cannot start** connections to Justice's devices [1].
- **Access rules.** Sharing follows the access control policy of Koen's tailnet [1]. If Justice sees wizardly-hugle but no page loads, check that the tailnet policy file allows his email address (or `autogroup:shared`) to reach `100.115.60.6` on ports 8081, 54189, 50065 and 61312 [1].
- **Key expiry.** If wizardly-hugle's Tailscale key expires, nobody can reach it until it signs in again. For an always-on server, Tailscale suggests **Disable key expiry** in the machine's **...** menu on the Machines page [2].
- **Keep the Pi on.** Justice can only use wizardly-hugle while it is powered on and online. Tell him before you switch it off or move it.

# Part B: For Justice

# 3. Setting up Tailscale on your devices

Do 3.1 once. Then install Tailscale on each device you want to use: 3.2 for your Raspberry Pi with Ubuntu, and 3.3 to 3.6 for other devices. Sign in with **the same account** on every device.

## 3.1 Create your Tailscale account

Tailscale has no passwords of its own. You sign in with an account you already have: **Google** (Gmail), **Microsoft** (Outlook, Hotmail), **Apple** or **GitHub** [3]. The first time you sign in, Tailscale creates your own tailnet. You do this during the install on your first device (3.2, step 5).

- Use a **personal** address such as Gmail or Outlook. With such an address Tailscale puts you on the free **Personal** plan [4].
- If you sign in with a work or school address that has its own domain, Tailscale starts a business trial instead [4]. Avoid this.

**Do:** Send Koen the email address of the account you will use for Tailscale, for example "my Tailscale account is the Gmail address ...". Koen needs it to share wizardly-hugle with you (Part A).

✔ **Check:** Koen has your email address.

## 3.2 Install on Ubuntu (your Raspberry Pi)

These commands come from Tailscale's Linux install guide [2]. They work on Ubuntu on a Raspberry Pi. You need internet and the password of your Ubuntu user (for `sudo`).

1. **Do:** Open a terminal: press **Ctrl + Alt + T**.
2. **Do:** Make sure `curl` (a small download tool) is installed:

```
sudo apt update
sudo apt install -y curl
```

✔ **Check:** the last line says `curl` is already the newest version, or that it was installed.

3. **Do:** Install Tailscale with the official install script:

```
curl -fsSL https://tailscale.com/install.sh | sh
```

The script asks for your Ubuntu password. Type it and press **Enter** (the password does not show while you type).

✔ **Check:** the script ends without an error message. `tailscale version` now prints a version number.

4. **Do:** Start Tailscale:

```
sudo tailscale up
```

✔ **Check:** the terminal shows `To authenticate, visit:` followed by a web address that starts with `https://login.tailscale.com/`.

5. **Do:** Open that web address in a browser: right-click it and choose **Open Link**, or copy it into the browser. Sign in with the account from 3.1 (for example **Sign in with Google**) and confirm that you want to connect this device. If your Pi has no browser, you can type the address on your phone instead.

✔ **Check:** the terminal prints `Success.` [2].

6. **Do:** Check that your Pi is in your tailnet:

```
tailscale status
tailscale ip -4
```

✔ **Check:** `tailscale status` shows a line with your own Pi and a `100.x.y.z` address. `tailscale ip -4` prints that address [2].

> **After a reboot** Tailscale starts again by itself; you do not need to run `sudo tailscale up` every time. To disconnect for a while, run `sudo tailscale down`; to connect again, run `sudo tailscale up` [5].

## 3.3 Install on Windows

Tailscale needs Windows 10 or later [6].

1. **Do:** Download the Windows installer (`.exe`) from `https://tailscale.com/download` and run it.
2. **Do:** A Tailscale icon appears in the system tray (bottom right, next to the clock; select the small up arrow if you do not see it). Right-click the icon.
3. **Do:** Select **Log in**. A browser window opens. Sign in with the account from 3.1 [6].

✔ **Check:** right-click the tray icon again: it shows your account and that Tailscale is connected.

## 3.4 Install on macOS

Tailscale needs macOS 12 (Monterey) or later [7].

1. **Do:** Download Tailscale from `https://tailscale.com/download` (or from the Mac App Store) and install it.
2. **Do:** Open Tailscale and follow the steps on screen. Allow the **VPN configuration** when the Mac asks.
3. **Do:** Sign in with the account from 3.1 [7].

✔ **Check:** the Tailscale icon in the menu bar at the top of the screen shows that you are connected.

## 3.5 Install on Android

Tailscale needs Android 8.0 or later [8].

1. **Do:** Install **Tailscale** from the Google Play Store.
2. **Do:** Open the app and tap **Get Started**. Accept the request to add a **VPN configuration** and allow notifications [8].
3. **Do:** Tap **Sign in with Google**, or **Sign in with other** for a Microsoft, Apple or GitHub account [8]. Use the account from 3.1.

✔ **Check:** the app shows that you are connected, and a list of your devices.

## 3.6 Install on iPhone or iPad

Tailscale needs iOS 15 or later [9].

1. **Do:** Install **Tailscale** from the App Store.
2. **Do:** Open the app and tap **Get Started**. Accept the request to add a **VPN configuration** and allow notifications [9].
3. **Do:** Tap **Log in** and sign in with the account from 3.1 [9].

✔ **Check:** the app shows that you are connected and lists your devices.

> **Phones and tablets allow only one VPN at a time.** If you use another VPN app, switch it off while you use Tailscale.

# 4. Accepting the share invite

Koen sends you an invite (Part A). It comes as an **email from Tailscale**, or as a **link** in a message from Koen.

1. **Do:** Open the invite link (in the email, or the link Koen sent you) in a web browser.
2. **Do:** If Tailscale asks you to sign in, sign in with **the same account that you use on your devices** (3.1). The invite does not have to match the email address it was sent to: it is added to whichever Tailscale account accepts it [1].
3. **Do:** Read the invitation and accept it.

✔ **Check:** wizardly-hugle now appears in your list of machines: on the **Machines** page of your own admin console (`https://login.tailscale.com/admin/machines`) and in the Tailscale app on your devices [1]. It is listed with the address `100.115.60.6` and the name **idea** (the name it has in Koen's tailnet), shown as shared with you.

> **Each invite works once.** An invite sent by email, or a single-use link, can be accepted only once and expires after 30 days if it is not used [1]. If you accepted it with the wrong account, or it has expired, ask Koen for a new invite.

# 5. Checking that it works

## 5.1 On your Ubuntu Pi (terminal)

1. **Do:** Run:

```
tailscale status
```

✔ **Check:** there is a line with `100.115.60.6`, the name `idea.tail2d60.ts.net` and Koen's account as the owner [1]. If the line ends in `offline`, wizardly-hugle is switched off or has no internet (see 7.5).

2. **Do:** Test the connection:

```
tailscale ping 100.115.60.6
```

✔ **Check:** you see lines that start with `pong from`. The first ones may say `via DERP(...)`; that is normal while Tailscale looks for the fastest route [10]. Press **Ctrl + C** to stop if it keeps going.

The normal `ping 100.115.60.6` also works; it shows lines with `time=... ms`. Press **Ctrl + C** to stop it.

## 5.2 On a phone, tablet, Windows PC or Mac

1. **Do:** Open the Tailscale app and look at the list of machines.

✔ **Check:** wizardly-hugle (listed as **idea**, address `100.115.60.6`) is in the list. Then go straight to section 6: if the IDEA Console opens, everything works.

> **Use the number `100.115.60.6`.** In rare cases, Tailscale gives a shared machine a different `100.x.y.z` address in your tailnet, because your tailnet already uses that number [1]. If the address shown for wizardly-hugle (idea) in your Tailscale app is not `100.115.60.6`, use the address shown in the app everywhere in this guide, and tell Koen.

# 6. Opening the IDEA Console and the apps

## 6.1 The IDEA Console

1. **Do:** Make sure Tailscale is connected on your device (section 5).
2. **Do:** Open a web browser (Firefox, Chrome, Safari or Edge) and type exactly:

```
http://100.115.60.6:8081
```

Type `http://`, not `https://`, and do not forget `:8081`.

3. **Do:** Wait. At the top the Console first says **Connecting…**. After a few seconds (up to half a minute on a slow connection) it connects and the **Apps** page shows one card per app: **Kiwix**, **Kolibri**, **MilkWise** and **Nextcloud**.

✔ **Check:** the page title is **IDEA Console** and the app cards are visible.

4. **Do:** To open an app, click the blue **Open** button on its card. The app opens in a new browser tab, at the `100.115.60.6` address with the app's own port (for example `http://100.115.60.6:54189/...` for Kolibri).

> **Do not click Open on MilkWise.** Use only the cards **Kiwix**, **Kolibri** and **Nextcloud**. Do not use **Stop**, **Remove**, **Erase** or **Back up** on wizardly-hugle unless Koen has asked you to (section 8).

If the Console asks for a password, use the one Koen sent you.

## 6.2 Kolibri

1. **Do:** Click **Open** on the **Kolibri** card, or type `http://100.115.60.6:54189`.

✔ **Check:** the Kolibri sign-in page opens (the address ends in `/en/auth/`). Sign in with a demo account; the usernames are in the appendix of the teacher tutorial, the passwords come from Koen.

## 6.3 Nextcloud

1. **Do:** Click **Open** on the **Nextcloud** card, or type `http://100.115.60.6:50065`.

✔ **Check:** the Nextcloud sign-in page opens (the address ends in `/login`). Sign in with a demo account from Koen.

## 6.4 Kiwix (offline Wikipedia)

1. **Do:** Click **Open** on the **Kiwix** card, or type `http://100.115.60.6:61312`.

✔ **Check:** the Kiwix library opens and shows the available books, such as Wikipedia. Kiwix needs no password.

## 6.5 Bookmarks

Save these addresses as bookmarks in your browser (press **Ctrl + D**, or **⌘ + D** on a Mac), so you do not need to type them again.

| Bookmark name | Address | Sign in with |
|---|---|---|
| IDEA Console (demo) | `http://100.115.60.6:8081` | Console password from Koen, if asked |
| Kolibri (demo) | `http://100.115.60.6:54189` | Kolibri demo account, e.g. `demo_teacher1` |
| Nextcloud (demo) | `http://100.115.60.6:50065` | Nextcloud demo account, e.g. `demo-teacher1` |
| Kiwix (demo) | `http://100.115.60.6:61312` | No sign-in |

The bookmarks work only while Tailscale is connected on that device.

## 6.6 Following the teacher tutorial remotely

The teacher tutorial (`IDEA-teacher-tutorial.pdf`) was made with screenshots of wizardly-hugle, so what you see matches the tutorial.

- Where the tutorial says "go to the Console address your IDEA contact gives you", use `http://100.115.60.6:8081`.
- The tutorial tells teachers not to type ports and to use **Open** in the Console. That rule is for teachers at school. For you, working remotely, the bookmarks in 6.5 are fine.
- **Part A of the tutorial** (Kolibri, Nextcloud, Wikipedia offline) can be followed on wizardly-hugle with the demo accounts. Use only the demo accounts and demo content (names starting with `demo`).
- **Part B of the tutorial** (Files Disk, Backup Disk, operator tasks) needs USB disks plugged into the server. You cannot do that remotely. On wizardly-hugle, only look at those screens; practise the disk steps on a school server in front of you.

# 7. Troubleshooting





**Figure 3.** Check in this order: Tailscale on, signed in, share accepted, server online, right address

## 7.1 Tailscale is not connected or you are logged out

**What you see:** no page opens; the Tailscale app says you are logged out or disconnected; or `tailscale status` prints `Logged out.` or `Tailscale is stopped.` [5].

**What to do:**

1. On Ubuntu, run `sudo tailscale up`. If it shows a web address, open it and sign in again with **your** account (3.2, step 5).
2. On Windows, Mac, Android or iPhone, open the Tailscale app and switch it on, or select **Log in** again.

✔ **Check:** `tailscale status` lists your devices again, or the app shows that you are connected.

## 7.2 wizardly-hugle is not in your machine list

**Possible causes:** the invite was not accepted yet; it was accepted with a different Tailscale account; the invite expired (30 days); or Koen revoked the share.

**What to do:**

1. Check which account is signed in on your device (Tailscale app, or the account column in `tailscale status`). It must be the account that accepted the invite.
2. Open the invite again and accept it (section 4).
3. If the link does not work any more, ask Koen for a new invite.

## 7.3 `tailscale up` says you need sudo

**What you see:** `tailscale up` stops with a permission error and the hint `Use 'sudo tailscale up'.` [5].

**What to do:** type the command again with `sudo` in front: `sudo tailscale up`, and enter your Ubuntu password. Commands that only read, such as `tailscale status` and `tailscale ping`, work without `sudo`.

## 7.4 The page does not load

**What you see:** the browser waits for a long time, or says that the site cannot be reached.

**What to do, in this order:**

1. Is Tailscale connected on **this** device? (7.1)
2. Check the address: `http://` (not `https://`), `100.115.60.6`, a colon, and the right port (`8081`, `54189`, `50065` or `61312`).
3. On a phone: is another VPN app switched on? Switch it off.
4. Test the connection with `tailscale ping 100.115.60.6` (5.1). If you get `pong from`, the connection works; reload the page, or try the Console instead of the app.
5. If the Console stays on **Connecting…** for more than a minute, reload the page (**F5**, or **Ctrl + R**).
6. If the ping works but no page loads at all, tell Koen: he may need to check the access rules (2.4).

## 7.5 wizardly-hugle is switched off, asleep or offline

**What you see:** `tailscale status` shows `offline` on the line of wizardly-hugle (`100.115.60.6`), or `tailscale ping` gets no `pong`; the Tailscale app shows the machine as offline.

**What to do:** there is nothing you can fix from your side. The Pi in Belgium may be switched off, restarting, or Koen's home internet may be down. Send Koen a message and try again later. Remember the time difference: until 25 October 2026 (Belgian summer time) Belgium and Zimbabwe have the same time; after that, Belgium is one hour behind Zimbabwe until the end of March.

## 7.6 Everything is very slow

**Why:** when Tailscale cannot make a direct connection between your device and wizardly-hugle, it sends the traffic through one of its relay servers (called **DERP**). This is common on Starlink, mobile data and hotel Wi-Fi. The connection is still encrypted, but it is slower [10].

**How to see it:** `tailscale status` shows `relay` on the line of wizardly-hugle (for example `relay "ams"`), and `tailscale ping 100.115.60.6` keeps saying `via DERP(...)`. When it says `direct`, or `via` followed by an address, the connection is direct [10].

**What to do:**

1. Wait a minute: Tailscale keeps trying to switch to a direct connection [10].
2. Try another network if you can (for example mobile data instead of hotel Wi-Fi).
3. For demos, prefer light pages (Kiwix articles, Kolibri exercises) over large videos.

# 8. Do's and don'ts, and privacy

## 8.1 Do's and don'ts

| Do | Don't |
|---|---|
| Use the IDEA Console, Kolibri, Nextcloud and Kiwix for demos and for the tutorial. | Never open, stop or remove **MilkWise**. It is a real app that Koen's family uses. |
| Use only the demo accounts and demo content (names starting with `demo`). | Never stop or remove an app that you did not install yourself. |
| Ask Koen before you change settings, install an app or use any button that changes the server. | Do not use **Erase**, **Back up** or **Restore** on wizardly-hugle unless Koen asks you to. |
| Keep the passwords from Koen private. | Do not write the passwords in this guide, on a school wall or in a shared chat. |
| Tell Koen at once if a device with Tailscale is lost or stolen, so he can revoke the share. | Do not forward the invite link to anyone else. |
| Switch Tailscale off on a shared or school computer when you are done (`sudo tailscale down` on Ubuntu). | Do not sign in to your Tailscale account on a computer that students use. |

## 8.2 Privacy: what each side can see





**Figure 4.** Justice sees only wizardly-hugle; Koen's other machines stay hidden; wizardly-hugle cannot start connections to Justice's devices

- **You see only wizardly-hugle.** Koen shares this one machine. You cannot see or reach Koen's other devices [1].
- **wizardly-hugle cannot reach your devices.** A shared machine is quarantined: it can answer your connections, but it cannot start a connection to your devices [1].
- **What Koen sees about you.** When you accept the invite, Koen sees your email address and profile picture, so that he knows who accepted [1].
- **Your own tailnet stays yours.** Your own devices are in your own tailnet. Koen cannot see them or reach them.
- **Koen can stop the share at any time** (Part A, 2.3). If that happens, wizardly-hugle disappears from your list; ask Koen if you need access again.

# Appendix A. Quick reference

| Task | How |
|---|---|
| Install on Ubuntu | `curl -fsSL https://tailscale.com/install.sh \| sh` |
| Connect (Ubuntu) | `sudo tailscale up` |
| Disconnect (Ubuntu) | `sudo tailscale down` |
| Is wizardly-hugle visible and online? | `tailscale status` (line with `100.115.60.6`) |
| Test the connection | `tailscale ping 100.115.60.6` |
| IDEA Console | `http://100.115.60.6:8081` |
| Kolibri | `http://100.115.60.6:54189` |
| Nextcloud | `http://100.115.60.6:50065` |
| Kiwix (offline Wikipedia) | `http://100.115.60.6:61312` |
| Passwords | From Koen, sent separately |
| Problems | Section 7; then message Koen |

# Appendix B. Sources (read on 13 October 2026)

1. Tailscale, "Share your machines with other users", `https://tailscale.com/kb/1084/sharing`
2. Tailscale, "Install Tailscale on Linux", `https://tailscale.com/kb/1031/install-linux`
3. Tailscale, "Supported SSO identity providers", `https://tailscale.com/kb/1013/sso-providers`
4. Tailscale, "Pricing" (Personal plan, FAQ), `https://tailscale.com/pricing`
5. Tailscale, "Tailscale CLI", `https://tailscale.com/kb/1080/cli`, and the Tailscale client source code (`cmd/tailscale/cli`) on GitHub for the exact messages
6. Tailscale, "Install Tailscale on Windows", `https://tailscale.com/kb/1022/install-windows`
7. Tailscale, "Install Tailscale on macOS", `https://tailscale.com/kb/1016/install-mac`
8. Tailscale, "Install Tailscale on Android", `https://tailscale.com/kb/1079/install-android`
9. Tailscale, "Install Tailscale on iOS", `https://tailscale.com/kb/1020/install-ios`
10. Tailscale, "Connection types", `https://tailscale.com/kb/1257/connection-types`

The addresses, ports, app names and the Console's **Connecting…** and **Open** behaviour were checked on wizardly-hugle itself on 13 October 2026.