

Retrieve Falcon Cloud Security Component Images from the CrowdStrike Registry

Last updated: Oct. 8, 2025

Overview

Some FCS client side components and utilities are stored in our image registry. To simplify authentication and requests to download images from our registry, we've created the FCS pull script.

Access and authenticate to the CrowdStrike registry to retrieve security images for protecting containerized workloads, Kubernetes environments, and cloud infrastructure in your deployment environment.

- **Falcon sensor for Linux:** Provides comprehensive protection for Linux hosts deployed as a DaemonSet
- **Falcon Container sensor for Linux:** Secures containerized workloads with runtime protection
- **Kubernetes Admission Controller:** Prevents vulnerable or malicious containers from being deployed
- **Image Assessment tools:** Scan container images for vulnerabilities and malware
- **Cloud Security tools:** Help secure cloud infrastructure and configurations

This guide walks you through the process of authenticating to the CrowdStrike registry, retrieving the appropriate images, and preparing them for deployment in your environment. Once you've completed these steps, you'll be ready to deploy CrowdStrike's security solutions using Helm charts, Kubernetes operators, or your preferred deployment method.

Prerequisites

Before retrieving Falcon Cloud Security images, ensure you have an active CrowdStrike subscription and the required command-line utilities installed in your environment.

The following items are required to retrieve Falcon Cloud Security product images:

- An active CrowdStrike subscription with appropriate entitlements
- Command-line utilities:
 - `jq`
 - `curl` (version 7.55.0 or later recommended for security)
 - **One of:** Docker, Podman, or Skopeo (Docker must be running locally if used)

How to use the FCS pull script

CrowdStrike provides a pull script that simplifies accessing images from the CrowdStrike registry.

The FCS pull script has several use cases but the one highlighted here is to fetch an image from the CrowdStrike registry. Once you've completed the steps, you'll be ready to deploy CrowdStrike's security solutions using Helm charts, Kubernetes operators, or your preferred deployment method.

Image types reference

This reference lists the available CrowdStrike security images and their corresponding API permission requirements for retrieval from the registry.

Image Description	Image Type	Required API Permissions
Falcon sensor for Linux (DaemonSet deployment)	falcon-sensor	- Falcon Images Download (read) - Sensor Download (read)
Falcon Container sensor for Linux	falcon-container	- Falcon Images Download (read) - Sensor Download (read)
Falcon Kubernetes Admission Controller	falcon-kac	- Falcon Images Download (read) - Sensor Download (read)
Falcon Snapshot scanner	falcon-snapshot	- Falcon Images Download (read) - Snapshot Scanner Image Download (read) - Sensor Download (read)
Falcon Image Assessment at Runtime (Image Analyzer)	falcon-imageanalyzer	- Falcon Images Download (read) - Sensor Download (read)
Falcon Kubernetes Protection Agent Important: End of Support [https://support/release-notes/tech-alert-30-day-notice-falcon-kubernetes-protection-agent-end-of-support-and-transition-to-falcon-kubernetes-admission-controller]	kpagent	- Falcon Images Download (read) - Sensor Download (read) - Kubernetes Protection (read)
Falcon Cloud Security CLI tool	fcs	- Falcon Images Download (read) - Infrastructure as Code (read) - Sensor Download (read)
Falcon Self Hosted Registry Assessment (2 images) Jobs Controller	falcon-jobcontroller	Falcon Images Download (read)

Image Description	Image Type	Required API Permissions
• Executor	• falcon-registryassessmentexecutor	• Sensor Download (read)

Important: Falcon sensor images are assessed for vulnerabilities and malware before they are released, and they are continuously monitored afterwards.

Image naming conventions

Understanding CrowdStrike's image naming patterns helps identify architecture-specific images and multi-architecture manifest lists when working with container images.

Some images are architecture-specific and some are architecture agnostic. Use the image naming convention to verify the image architecture.

Type	Format	Example
Architecture-Specific	<image-type>:<version>-<build>-<baseImage>.falcon-linux.<arch>.Release.<cloud>	falcon-sensor:7.14.0-15300-1.falcon-linux.x86_64.Release.US-1
Multi-Architecture	<image-type>:<version>-<build>-<baseImage>.falcon-linux.Release.<cloud>	falcon-sensor:7.15.0-15501-1.falcon-linux.Release.US-1

Multi-architecture images lack architecture identifiers (like x86_64 or aarch64) in the tag.

Important: When pulling multi-architecture images locally, you must specify a platform with the `-p` flag (`-p x86_64` or `-p aarch64`). This is because container runtimes like Docker can only store one architecture variant per tag locally. Without specifying a platform, attempting to pull a multi-architecture image will fail or result in only one architecture being stored. If you need to preserve the multi-architecture functionality, use the `--copy` option with `--runtime skopeo` to transfer the complete multi-architecture image to another registry.

Latest image versions

These are the latest Falcon image versions available from the CrowdStrike image registry. To access images from the registry, see [Retrieve Falcon Cloud Security Component Images from the CrowdStrike Registry \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry\]](#)

Falcon component name	Image name	Latest tag	Architecture
Falcon sensor for Linux DaemonSet	falcon-sensor	7.29.0-18202-1.falcon-linux.Release.US-1	multi-architecture
Falcon Container sensor for Linux	falcon-container	7.30.0-6901.container.Release.US-1	multi-architecture
Falcon Kubernetes Admission Controller	falcon-kac	7.30.0-2801.Release.US-1	multi-architecture
Falcon Kubernetes Protection Agent	kpagent (deprecated)	0.2462.0	x86_64
Falcon Image Assessment at Runtime	falcon-imageanalyzer	1.0.20	x86_64
Falcon Cloud Security CLI image	fcs	2.1.0	x86_64
Falcon Snapshot	cs-snapshotscanner	0.21.0	x86_64
Falcon Self-Hosted Registry Assessment executor	falcon-registryassessmentexecutor	1.5.0	x86_64

Falcon component name	Image name	Latest tag	Architecture
Falcon Self-Hosted Registry Assessment job controller	falcon-jobcontroller	1.5.0	x86_64

Step 1: Create an API client key

Create an API client in the Falcon console to obtain the credentials required for authenticating to the CrowdStrike registry and retrieving security images.

1. In the Falcon console, go to [Support and resources > Resources and tools > API clients and keys \[/api-clients-and-keys\]](#).
2. Click **Add new API client**.
3. Enter a client name and description.
4. Select the required API scopes based on the image type. To check which API scopes you need, see [Image types reference \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#zccd8f5c\]](#).
5. Click **Add**.
6. Copy the client ID and secret to a secure location.
7. Set environment variables:

```
export FALCON_CLIENT_ID=<YOUR_FALCON_CLIENT_ID>
export FALCON_CLIENT_SECRET=<YOUR_FALCON_CLIENT_SECRET>
```

Step 2: Get your CID with checksum

Obtain your Customer ID (CID) with checksum from the Falcon console.

Tip: The FCS pull script can automatically discover your CID through your CrowdStrike API credentials when the sensor download (read) scope is enabled. This means that you don't need to manually pass your CID to the pull script unless you haven't assigned the required scope. However, when you deploy the image with Helm, you need to pass the CID when running `helm install`.

Step 3: Download the pull script

Download the CrowdStrike pull script that simplifies accessing images from the registry to your local environment. The script is available on GitHub at [CrowdStrike/falcon-scripts \[https://github.com/CrowdStrike/falcon-scripts\]](#).

- Download the latest version of the pull script:

```
curl -sSL -o falcon-container-sensor-pull.sh "https://raw.githubusercontent.com/CrowdStrike/falcon-scripts/main/bash/containers/falcon-container-sensor-pull/falcon-container-sensor-pull.sh"
chmod +x falcon-container-sensor-pull.sh
```

Step 4: Basic script usage

Choose between two approaches for retrieving images from the CrowdStrike registry based on your deployment needs.

[Option 1: Pull an image and copy it to your private registry \(recommended\) \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-](#)

- [images-from-the-crowdstrike-registry#t810f7ba\]](#)

[Option 2: Pull the image directly from the CrowdStrike registry \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-](#)

- [crowdstrike-registry#h05ee697\]](#)

Option 1: Pull an image and copy it to your private registry (recommended)

Pull images from the CrowdStrike registry and copy them to your private registry to remove dependencies on external sources. This is the recommended method to maintain security best practices and limit dependencies on systems or environments that you can't control.

These instructions include some Docker CLI commands. If you're using an alternative container runtime, such as Podman, containerd/nerdctl, or CRI-O, you'll need to adjust the commands accordingly while maintaining the same workflow. The core concepts of pulling, tagging, and pushing images apply across container runtimes, but command syntax may differ. Also, if your runtime is not Docker, make sure to set the runtime platform with the `--runtime` flag.

Tip: When you set your variables in

Step 1: Create an API client key [\[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#g7e71eb8\]](#)

and

Step 2: Get your CID with checksum [\[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#r71c821f\]](#)

, the script can access them without having to specify them. They are shown in examples for completeness, but after setting them it's not required to pass them with the `--client-id` and `--client-secret` switches. Also, the Customer ID (CID) is derived from the client credentials even when the variable is not set. For more details setting environment variables, see

[Pull script options \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#pe0a4002\]](#).

Important: CrowdStrike cloud region auto-discover is only available for US-1, US-2, and EU-1. If you are in another CrowdStrike cloud region, you must set the region with the `region` flag. For info, see

[Pull script options \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#pe0a4002\]](#).

1. Copy the image to your private registry:

Tip: To see the full list of `<image-types>`, see

[Image types reference \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#zccd8f5c\]](#)

.

```
./falcon-container-sensor-pull.sh \
--client-id ${FALCON_CLIENT_ID} \
--client-secret ${FALCON_CLIENT_SECRET} \
--type <image-type> \
-c <myregistry.com/repository/image-name>
```

2. Verify the image is available in your registry. For example:

```
docker images | grep <image-name>
```

Note: For most registries, you can `curl` to query the registry's API. For example `curl https://myregistry.com/repository/image-name/tags/list`.

3. Set variables for deployment. The copied image name will be `<myregistry.com/repository/image-name>:<image-tag>`:

```
FALCON_IMAGE_REPO="<myregistry.com/repository/image-name>"
FALCON_IMAGE_TAG="<image-tag>"
```

4. Get a pull token for your registry. This allows Kubernetes or other container orchestration platforms to pull the container image from your private registry. You'll add the pull token to your Helm chart, Kubernetes manifest, or other deployment config file.

a. Set your registry credentials. For example:

```
DOCKER_USERNAME="<your Docker username>"
DOCKER_PASSWORD="<your Docker password>"
DOCKER_SERVER="<your-Docker-registry.com>"
```

b. Log into your Docker registry:

```
docker login -u ${DOCKER_USERNAME} -p ${DOCKER_PASSWORD} ${DOCKER_SERVER}
```

c. Fetch the base64 encoded pull secret:

```
FALCON_IMAGE_PULL_TOKEN=$(cat ~/.docker/config.json | base64 -w 0)
```

Note: If you are deploying Falcon Self-Hosted Registry Assessment (SHRA), you'll have to repeat these steps for each image required. For details, see [Step 4: Copy the SHRA images to your registry \[documentation/page/ad2d4792/shra-deploy-via-helm-chart#y03b7e0c\]](#).

Option 2: Pull the image directly from the CrowdStrike registry

Obtain the necessary authentication token and image information to pull directly from the CrowdStrike registry during deployment.

Tip: When you set your variables in

Step 1: Create an API client key [\[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#g7e71eb8\]](#)

and

Step 2: Get your CID with checksum [\[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#r71c821f\]](#)

, the script can access them without having to specify them. They are shown in examples for completeness, but after setting them it's not required to pass them with the `--client-id` and `--client-secret` switches. Also, the Customer ID (CID) is derived from the client credentials even when the variable is not set. For more details setting environment variables, see

[Pull script options \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#pe0a4002\]](#).

Important: CrowdStrike region auto-discover is only available for US-1, US-2, and EU-1. If you are in another CrowdStrike cloud region, you must set the region with the region flag. For info, see

[Pull script options \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#pe0a4002\]](#).

1. Get the pull token for the CrowdStrike registry:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--get-pull-token
```

2. Set the pull token variable:

```
export FALCON_IMAGE_PULL_TOKEN="<pull-token>"
```

3. Get image information:

Tip: To see the full list of `<image-types>`, see

[Image types reference \[documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#zccd8f5c\]](#)

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--get-image-path
```

4. The scripts returns the image path in this format:

```
registry.crowdstrike.com/falcon-sensor/us-1/release/falcon-sensor:7.26.0-17905-1.falcon-  
linux.Release.US-1
```

Note: This example shows the Falcon sensor image.

5. Set the image path as 2 variables; 1 for the image repository and 1 for the image tag:

```
export FALCON_IMAGE_REPO="registry.crowdstrike.com/falcon-sensor/us-1/release/falcon-sensor"  
export FALCON_IMAGE_TAG="7.26.0-17905-1.falcon-linux.Release.US-1"
```

Note: The pull token for the CrowdStrike registry does not expire.

Deployment variables

After retrieving CrowdStrike registry images, these environment variables will be available for configuring your deployment tools and scripts.

Variable Name	Description
FALCON_IMAGE_TAG	The image tag for deployment
FALCON_IMAGE_REPO	The image repository location
FALCON_IMAGE_PULL_TOKEN	The required pull token for deployment

Variable Name	Description
FALCON_CLIENT_ID	The CrowdStrike API client ID
FALCON_CLIENT_SECRET	The CrowdStrike API client secret

These variables can be used with deployment tools, like Helm charts or Kubernetes operators, to deploy CrowdStrike products in your environment.

Common usage examples

Explore practical examples of using the pull script for various operations when working with CrowdStrike security images.

- [Download the latest image \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#ha64b3cc\]](#)
- [Get image path information \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#wd8afde1\]](#)
- [Copy image to private registry \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#mbd98347\]](#)
- [Generate Kubernetes pull token \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#cc30733e\]](#)
- [Retrieve CID for deployment \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#s0ecd977\]](#)
- [Display registry credentials \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#h6e5f9f1\]](#)
- [Copy multi-architecture image to registry \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#wee8d7f9\]](#)
- [Use custom destination path \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#l0fa44c9\]](#)
- [Apply custom tag \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#c48632c6\]](#)
- [Pull specific architecture \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#t4d10fbb\]](#)

Download the latest image

Retrieve the most recent version of a specific image type from the CrowdStrike registry.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type>
```
- Important:** Although the default mode for our pull script is to retrieve the most recent version of an image, the images are not tagged "latest". Instead, this script looks at the list of available versions for the image you've identified and selects the most recent.

Example result for the Falcon Container sensor for Linux:

```
Digest: sha256:582f4c9095203bfd2ffac1a7335df21de65c169db73f61e0033763ae02338709  
Status: Downloaded newer image for registry.crowdstrike.com/falcon-container/us-1/release/falcon-  
sensor:7.24.0-6302.container.x86_64.Release.US-1  
registry.crowdstrike.com/falcon-container/us-1/release/falcon-sensor:7.24.0-  
6302.container.x86_64.Release.US-1
```

Get image path information

Obtain the full image repository path with the latest tag without actually downloading the image.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  

```

-



- 

1

1

1

1

1

11

11

1

- 1



5

Display registry credentials

Print registry credentials in a format that can be used with other container tools.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--dump-credentials
```

Example result:

```
Using the following settings:  
Falcon Region:  api.crowdstrike.com  
Falcon Registry: registry.crowdstrike.com  
CS Registry Username: fc-fake12345abc67890def12345f67890abc  
CS Registry Password: cmVmdGtu0jAx0kZBS0VUT0tFTjEyMzQ1Njc4OTpBQkNERUZHSElKS0xNTk9QUVJTVFVWV1hZWjEyMzQ=
```

Copy multi-architecture image to registry

Transfer a complete multi-architecture image to your registry using Skopeo, preserving all architecture variants.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--copy <my-registry> \  
--runtime skopeo
```

Example result for the Falcon Kubernetes Admission Controller:

```
myregistry.com/mynamespace/falcon-kac:7.23.0-2103.container.x86_64.Release.US-1
```

Use custom destination path

Copy an image to a specific destination path without automatically appending the original image name.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--copy <my-registry-my-image-name> \  
--copy-omit-image-name \  
--runtime skopeo
```

Tip: When you use `--copy-omit-image-name`, the image name from the CrowdStrike registry is not copied. This allows you to set the name in the copy path.

Example result:

```
myregistry.com/mynamespace/my-image-name:<tag>
```

Apply custom tag

Copy an image to your registry and apply a custom tag.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--runtime skopeo
```

```
--copy <my-registry> \  
--copy-custom-tag <my-custom-tag> \  
--runtime docker
```

Example result for Falcon Image Assessment at Runtime:

```
myregistry.com/mynamespace/falcon-imageanalyzer:v1.2.3-custom
```

Pull specific architecture

Pull only a specific architecture variant of a multi-architecture image.

- Execute the following command:

```
./falcon-container-sensor-pull.sh \  
--client-id ${FALCON_CLIENT_ID} \  
--client-secret ${FALCON_CLIENT_SECRET} \  
--type <image-type> \  
--platform x86_64
```

Example result for the Falcon Container sensor for Linux:

```
registry.crowdstrike.com/falcon-container/us-1/release/falcon-sensor:7.24.0-  
6302.container.x86_64.Release.US-1
```

Pull script options

Reference for all available command-line flags and environment variables supported by the CrowdStrike image pull script.

Note: These settings can be passed to the script with CLI flags or environment variables. For example, you can set an environment variable for platform `export SENSOR_PLATFORM=aarch64`, and then when you run the pull script it can pick up that setting without having to add it with the CLI flag `-p` or `--platform`.

Flag	Environment Variable	Description
-u, --client-id	FALCON_CLIENT_ID	Required: CrowdStrike API OAuth client ID
-s, --client-secret	FALCON_CLIENT_SECRET	Required: CrowdStrike API OAuth client secret
-f, --cid	FALCON_CID	Falcon Customer ID (if not set, derived from client credentials)
-r, --region	FALCON_CLOUD	CrowdStrike cloud region (Default: us-1, auto-discovery available for us-1, us-2, eu-1)
-c, --copy	COPY	Registry to copy the image to
-v, --version	SENSOR_VERSION	Image version to pull (latest if not specified)
-p, --platform	SENSOR_PLATFORM	Image architecture (e.g., x86_64, aarch64)
-t, --type	SENSOR_TYPE	The specific image type to pull (Default: falcon-container)
--runtime	CONTAINER_TOOL	Container runtime to use (Default: docker)
--dump-credentials	CREDS	Print registry credentials to stdout
--get-image-path		Get the full image path including registry, repository, and latest tag
--copy-omit-image-name		Omit the image name from the destination path when copying
--copy-custom-tag		Use custom tag when copying image
--get-pull-token		Get the CrowdStrike registry pull token for Kubernetes

Flag	Environment Variable	Description
--get-cid		Get the CID assigned to the API credentials
--list-tags	LISTTAGS	List all available tags for the selected image type
--allow-legacy-curl	ALLOW_LEGACY_CURL	Allow the script to run with older versions of curl

Tip: To see the full list of <image-types>, see [Image types reference \[/documentation/page/vc320402/retrieve-falcon-cloud-security-product-images-from-the-crowdstrike-registry#zccd8f5c\]](#).

What's next

After retrieving CrowdStrike security images, proceed to deploying them in your cloud environment using your preferred method.

- [Falcon Operator for Kubernetes \[/documentation/category/ef3a99a0/cloud-security/set-up-fcs/operator\]](#)
- [Deploy Falcon sensor for Linux with a Helm chart \[/documentation/page/d0c66bb8/deploy-falcon-sensor-for-linux-with-a-helm-chart\]](#)
- [Deploy Falcon Container sensor for Linux with a Helm chart \[/documentation/page/ebc28f99/deploy-falcon-container-sensor-for-linux-with-a-helm-chart\]](#)
- [Deploy Falcon Sensor for Linux on ECS EC2 Clusters with AWS CloudFormation \[/documentation/page/m89e4d3d/deploy-falcon-sensor-for-linux-on-ecs-ec2-clusters-with-aws-cloudformation\]](#)
- [Deploy Falcon Kubernetes Admission Controller with a Helm Chart \[/documentation/page/d0a3095c/deploy-falcon-kubernetes-admission-controller-with-a-helm-chart\]](#)
- [Deploy Image Assessment at Runtime with Helm \[/documentation/page/a0cf9976/deploy-image-assessment-at-runtime-with-a-helm-chart\]](#)
- [Deploy Image Assessment at Runtime on a Standalone Host \[/documentation/page/iac7ddc1/deploy-image-assessment-at-runtime-iar-on-a-host\]](#)
- [Deploy Self-hosted Registry Assessment using Helm Chart \[/documentation/page/ad2d4792/shra-deploy-via-helm-chart\]](#)
- [Enable Snapshot Management \[/documentation/page/c8b31ee8/enable-snapshot-management\]](#)

