

Lecture 6

Session Fixation and Command Injection

- Course: Web Application Vulnerability Lab
- Theme: Understanding session-management flaws and the danger of OS command execution
- Goal: Explain the principles, dangerous implementations, and basic defenses of session fixation and command injection

Learning Goals for Today

- Explain what session fixation is
- Explain why session handling at login is important
- Explain what command injection is
- Explain why string concatenation and `shell=True` are dangerous
- Compare safe and vulnerable behavior on `/ping`

Topics for Today

1. Review of the previous class
2. Session fixation
3. Handling session IDs
4. Command injection
5. Comparison in the teaching app
6. Exercises

Review of Last Time

- XSS is a script-execution problem caused by dangerous output
- CSRF abuses a logged-in browser for unintended requests
- Safe output and request validation are important

Today's focus:

- How sessions are created
- How OS commands are executed

What Is Session Fixation?

Session fixation:

- A problem where the victim is made to use a session ID already known or chosen by an attacker

Dangerous flow:

1. The attacker prepares a session ID
2. The victim logs in while still using that ID
3. The attacker reuses the same ID to act as the victim

Image of Session Fixation

```
sequenceDiagram
    participant A as Attacker
    participant V as Victim
    participant S as Server

    A->>V: make the victim use a fixed session_id
    V->>S: access with that session_id
    V->>S: log in
    S-->>V: keep the same session_id as authenticated
    A->>S: access with the same session_id
```

Why Is It Dangerous?

- The pre-login state and post-login state are tied to the same identifier
- Anyone who knows that session ID may abuse the authenticated state

Basic defense:

- Generate a new session ID at login

Session Fixation and This Teaching App

In server-session mode:

```
def login(self, user):  
    session.clear()  
    server_session_id = create_server_session(user.id)  
    return server_session_id
```

Key points:

- A new `server_session_id` is generated at login
- This is closer to the safer direction

Session ID Generation in the Code

```
def create_server_session(user_id):  
    session_id = secrets.token_hex(16)  
    ...  
    conn.execute(  
        "INSERT INTO server_sessions (session_id, user_id, created_at) VALUES (?, ?, ?)",  
        (session_id, user_id, created_at),  
    )
```

Key points:

- The ID is random
- An existing ID is not reused

Idea for Preventing Session Fixation

flowchart TD

A["Pre-login session"] --> B["Login succeeds"]

B --> C["Generate a new session_id"]

C --> D["Authenticated state is bound to the new ID"]

What Is Command Injection?

Command injection:

- A problem where user input is interpreted as part of an OS command

Typical causes:

- Building a command through string concatenation
- Executing it with `shell=True`

Image of Command Injection

flowchart LR

A["User input"] --> B["Directly concatenated into a command string"]

B --> C["Interpreted by the OS shell"]

C --> D["Unexpected command execution"]

Pages Used in This Teaching App

- `/ping`
 - Takes a host name and runs `ping`
- `lab-settings`
 - Command injection mode
 - `safe`
 - `vulnerable`

Safe Implementation

```
def safe_ping(host):  
    if not host or not HOST_PATTERN.fullmatch(host):  
        return False, "Invalid host."  
  
    result = subprocess.run(  
        ["ping", "-c", "1", host],  
        capture_output=True,  
        text=True,  
        timeout=5,  
        check=False,  
    )
```

Key points:

- Input is validated
- The command is passed as a list
- `shell=True` is not used

Vulnerable Implementation

```
def unsafe_ping(host):  
    command = f"ping -c 1 {host}"  
    result = subprocess.run(  
        command,  
        capture_output=True,  
        text=True,  
        timeout=5,  
        shell=True,  
        check=False,  
    )
```

Key points:

- Input is concatenated directly
- `shell=True` is used

Why Is It Dangerous?

flowchart TD

A["Enter host"] --> B["Build command by string concatenation"]

B --> C["Execute with shell=True"]

C --> D["Input affects shell interpretation"]

What `/ping` Shows

On `/ping`, students can observe:

- Execution mode
- The input host
- Command output
- Executed command in vulnerable mode

Purpose:

- To see how input enters the command string

Comparison of Safe and Vulnerable Modes

Viewpoint	safe	vulnerable
Input validation	Yes	No
Execution style	List arguments	String concatenation
<code>shell=True</code>	No	Yes
Risk	Lower	Higher

Code Explanation 1

Switching in `/ping`

```
if command_injection_enabled():  
    success, output, executed_command = unsafe_ping(host)  
else:  
    success, output = safe_ping(host)
```

Key points:

- `lab-settings` switches the implementation
- The same page can be used for comparison

Code Explanation 2

ping.html

```
{% if executed_command %}  
<p>Executed command:</p>  
<pre>{{ executed_command }}</pre>  
{% endif %}
```

Key points:

- Vulnerable mode shows the executed command string
- Students can observe how input is concatenated

Difference Between Session Fixation and Command Injection

Viewpoint	Session Fixation	Command Injection
Main problem	Reusing a session ID	Polluting an OS command string
Main area	Authentication / session management	Server-side input handling
Basic defense	Regenerate ID at login	Validate input and avoid <code>shell=True</code>

Hands-On 1

Check `/ping` in Safe Mode

1. Open `Lab Settings`
2. Set `Command injection mode` to `safe`
3. Open `/ping`
4. Enter a host name and run it

Check:

- The output
- Input restrictions
- Whether `Executed command` appears

Moodle answer instructions:

- Response type: No submission required
- If the instructor collects it: Write one sentence about the main feature of safe mode

Hands-On 2

Check `/ping` in Vulnerable Mode

1. Open `Lab Settings`
2. Set `Command injection mode` to `vulnerable`
3. Open `/ping`
4. Observe how it differs from safe mode

Check:

- Whether `Executed command` is displayed
- Whether you can explain why it is dangerous

Moodle answer instructions:

- Response type: No submission required
- If the instructor collects it: Write one sentence about the main feature of vulnerable mode

Hands-On 3

Try an Actual Command Injection

1. Set `Command injection mode` to `vulnerable`
2. Open `/ping`
3. First, enter `127.0.0.1` and run it
4. Next, enter one of the following depending on your environment
5. Compare the `Executed command` and the result
6. Try the same input again in `safe` mode

Example input:

- macOS / Linux: `127.0.0.1; whoami`
- Windows: `127.0.0.1 & whoami`

Moodle answer instructions:

- Response type: Essay

Hands-On 4

Think About Session Fixation

Think about the following.

1. What is dangerous about reusing the same session ID after login?
2. Why should a new ID be created at login?
3. Which side is the current app closer to?

Moodle answer instructions:

- Response type: No submission required
- If the instructor collects it: Write only your answer to Question 3 in one sentence

Exercise 1

Read `unsafe_ping()`

Answer:

1. Where is the command string built?
2. Why is `shell=True` dangerous?
3. How does it differ from the safe version?

Moodle answer instructions:

- Response type: Essay
- Suggested length: 3 numbered lines
- Required items: Answer all 3 questions with numbers

Exercise 2

Read `safe_ping()`

Answer:

1. Where is the input validated?
2. Why is the command passed as a list?
3. Why does that reduce risk?

Moodle answer instructions:

- Response type: Essay
- Suggested length: 3 numbered lines
- Required items: Answer all 3 questions with numbers

Exercise 3

Read the Server-Session Implementation

Answer:

1. What does `create_server_session()` do?
2. Why is a random session ID necessary?
3. What is important to prevent session fixation?

Moodle answer instructions:

- Response type: Essay
- Suggested length: 3-5 short lines
- Required items: Answer all 3 questions with numbers

Exercise 4

Explain in Your Own Words

Answer:

1. What is the core problem in session fixation?
2. What is the core problem in command injection?
3. How are these two problems different?

Moodle answer instructions:

- Response type: Essay
- Suggested length: 4-6 short lines
- Required items: Answer all 3 questions with numbers

Summary

- Session fixation is a problem in how authenticated state is tied to a session ID
- A new session ID should be generated at login
- Command injection happens when input affects the structure of an OS command
- String concatenation and `shell=True` are dangerous
- The differences can be observed through `/ping` and the server-session code

Next Time

- Broken authorization
- Final integrated exercises
- Organizing everything learned so far

Homework

1. Write three differences between `safe_ping` and `unsafe_ping`
2. Write what is needed to prevent session fixation
3. Explain in writing why `shell=True` is dangerous

Moodle answer instructions:

- Response type: Essay
- Suggested length: 6-8 short lines
- Required items: 3 points for Question 1, and at least 2 sentences for Questions 2 and 3

Instructor Notes

- Session fixation is abstract, so use diagrams carefully
- It helps to show that the current implementation is relatively on the safer side
- Command injection is easy to demonstrate through the `/ping` difference
- Connect this lecture to the final integrated exercises by organizing input handling and session management