



US 20240237468A1

(19) **United States**

(12) **Patent Application Publication**
Yoon et al.

(10) **Pub. No.: US 2024/0237468 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **DISPLAY APPARATUS**

H10K 59/126 (2006.01)

H10K 59/60 (2006.01)

(71) Applicant: **Samsung Display Co., Ltd.**, Yongin-Si (KR)

(52) **U.S. Cl.**

CPC **H10K 59/38** (2023.02); **H10K 59/122** (2023.02); **H10K 59/126** (2023.02); **H10K 59/60** (2023.02)

(72) Inventors: **Seokgyu Yoon**, Yongin-si (KR);
Sujeong Kim, Yongin-si (KR); **Jinsoo Jung**, Yongin-si (KR); **Sunghan Kim**, Yongin-si (KR)

(57)

ABSTRACT

(21) Appl. No.: **18/406,227**

(22) Filed: **Jan. 8, 2024**

(30) **Foreign Application Priority Data**

Jan. 9, 2023 (KR) 10-2023-0003045

Publication Classification

(51) **Int. Cl.**

H10K 59/38 (2006.01)

H10K 59/122 (2006.01)

A display apparatus includes a substrate, a first organic light-emitting diode corresponding to the first emission area, a first photodetector corresponding to the first sensing area, a light-blocking layer including a first light-blocking layer opening overlapping the first emission area and a second light-blocking layer opening overlapping the first sensing area, a low reflection layer under the light-blocking layer, a first color filter filling the first light-blocking layer opening, and a second color filter filling the second light-blocking layer opening, wherein the light-blocking layer and the low reflection layer overlap each other.

