



US 20240237430A1

(19) **United States**

(12) **Patent Application Publication**
Jinta

(10) **Pub. No.: US 2024/0237430 A1**

(43) **Pub. Date: Jul. 11, 2024**

(54) **IMAGE DISPLAY DEVICE AND
ELECTRONIC DEVICE**

(71) Applicant: **Sony Semiconductor Solutions
Corporation, Kanagawa (JP)**

(72) Inventor: **Seiichiro Jinta, Kanagawa (JP)**

(21) Appl. No.: **18/558,614**

(22) PCT Filed: **Mar. 30, 2022**

(86) PCT No.: **PCT/JP2022/015937**

§ 371 (c)(1),

(2) Date: **Nov. 2, 2023**

(30) **Foreign Application Priority Data**

Jun. 14, 2021 (JP) 2021-099012

Publication Classification

(51) **Int. Cl.**

H10K 59/126 (2006.01)

H10K 59/121 (2006.01)

H10K 59/131 (2006.01)

H10K 59/65 (2006.01)

(52) **U.S. Cl.**

CPC **H10K 59/126** (2023.02); **H10K 59/1213**

(2023.02); **H10K 59/131** (2023.02); **H10K**

59/65 (2023.02)

(57)

ABSTRACT

An object is to block natural light and light source light from being incident on a transistor in a pixel even in a case where a transmission portion is provided.

An image display device includes a plurality of pixels arranged two-dimensionally. The plurality of pixels includes a first pixel region including a pixel that includes a first region configured to emit light and a second region configured to transmit visible light, a second pixel region arranged around the first pixel region, the second pixel region including a pixel configured to emit light with an area larger than a light-emitting area of the pixel in the first pixel region, and a light shielding layer configured to shield a transistor arranged in the second region from light.

