



US 20230231136A1

(19) **United States**(12) **Patent Application Publication****MITSUI et al.**(10) **Pub. No.: US 2023/0231136 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **ELECTRODE LAYER AND ALL-SOLID
STATE BATTERY****Publication Classification**(71) Applicants: **TOYOTA JIDOSHA KABUSHIKI
KAISHA**, Toyota-shi (JP); **Panasonic
Holdings Corporation**, Osaka (JP)(51) **Int. Cl.**
H01M 4/62 (2006.01)
H01M 10/0525 (2006.01)
H01M 10/0585 (2006.01)
H01M 10/0562 (2006.01)(72) Inventors: **Akio MITSUI**, Anjo-shi (JP); **Yasunari
SUGITA**, Osaka-shi (JP); **Yasutaka
TSUTSUI**, Osaka-shi (JP)(52) **U.S. Cl.**
CPC *H01M 4/62* (2013.01); *H01M 10/0525*
(2013.01); *H01M 10/0562* (2013.01); *H01M*
10/0585 (2013.01); *H01M 2220/20* (2013.01);
H01M 2300/0068 (2013.01)(73) Assignees: **TOYOTA JIDOSHA KABUSHIKI
KAISHA**, Toyota-shi (JP); **Panasonic
Holdings Corporation**, Osaka (JP)(21) Appl. No.: **17/979,092**(57) **ABSTRACT**(22) Filed: **Nov. 2, 2022**(30) **Foreign Application Priority Data**

Jan. 5, 2022 (JP) 2022-000470

An electrode layer for an all-solid state battery contains an electrode active material, a sulfide solid electrolyte, and a residual liquid, where the residual liquid has a δ_p of less than 2.9 MPa^{1/2} in a Hansen solubility parameter and a boiling point of 190° C. or higher.

