



US 20240179938A1

(19) **United States**

(12) **Patent Application Publication**  
**OKAZAKI et al.**

(10) **Pub. No.: US 2024/0179938 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAY DEVICE**

**Publication Classification**

(71) Applicant: **Semiconductor Energy Laboratory Co., Ltd.**, Kanagawa-ken (JP)

(72) Inventors: **Kenichi OKAZAKI**, Tochigi (JP); **Shingo EGUCHI**, Atsugi (JP); **Hiroki ADACHI**, Tochigi (JP)

(73) Assignee: **Semiconductor Energy Laboratory Co., Ltd.**, Kanagawa-ken (JP)

(21) Appl. No.: **18/404,122**

(22) Filed: **Jan. 4, 2024**

**Related U.S. Application Data**

(63) Continuation of application No. 17/581,064, filed on Jan. 21, 2022, now Pat. No. 11,871,600.

**Foreign Application Priority Data**

Jan. 27, 2021 (JP) ..... 2021-011450

(51) **Int. Cl.**

**H10K 50/822** (2006.01)

**H10K 50/13** (2006.01)

**H10K 102/00** (2006.01)

(52) **U.S. Cl.**

CPC ..... **H10K 50/822** (2023.02); **H10K 50/13** (2023.02); **H10K 2102/341** (2023.02)

(57)

**ABSTRACT**

A display device with high display quality is provided. The display device includes a first lower electrode, a first EL layer over the first lower electrode, a second lower electrode, a second EL layer over the second lower electrode, an upper electrode over the first EL layer and the second EL layer, a first region not provided with the first lower electrode below the first EL layer, and a second region not provided with the second lower electrode below the second EL layer. In the first region, the upper electrode is positioned not to be in contact with the first lower electrode. In the second region, the upper electrode is positioned not to be in contact with the second lower electrode.

