



US 20240224451A1

(19) **United States**

(12) **Patent Application Publication**
Yew et al.

(10) **Pub. No.: US 2024/0224451 A1**

(43) **Pub. Date: Jul. 4, 2024**

(54) **BATTERY CHARGER HANDLE**

(71) Applicant: **Enatel**, Christchurch (NZ)

(72) Inventors: **Chuan Cheong Yew**, Christchurch (NZ); **Ryan Cameron Taylor**, Christchurch (NZ)

(21) Appl. No.: **18/554,699**

(22) PCT Filed: **Oct. 19, 2021**

(86) PCT No.: **PCT/NZ2021/050178**

§ 371 (c)(1),

(2) Date: **Oct. 10, 2023**

Related U.S. Application Data

(60) Provisional application No. 63/182,461, filed on Apr. 30, 2021.

Publication Classification

(51) **Int. Cl.**
H05K 5/02 (2006.01)
H02J 7/00 (2006.01)

(52) **U.S. Cl.**

CPC **H05K 5/023** (2013.01); **H02J 7/0042** (2013.01); **H05K 5/0213** (2013.01)

(57) **ABSTRACT**

A handle for a battery charger includes a first coupling portion, the first coupling portion comprising a contact portion configured to be coupled to the battery charger, and a cover portion, the cover portion having a first width, wherein a depth from the contact portion to the cover portion is 45 mm or more so as to enforce a minimum spacing between adjacent battery chargers in a multi-charger system to permit airflow. The handle further includes a second coupling portion configured to be coupled to the battery charger body, the second coupling portion having a second width, and a grip portion disposed between the first coupling portion and the second coupling portion, the grip portion having a third width that is less than the first width and the second width. The cover portion may substantially cover a vent on the battery charger to prevent debris from entering the vent.

