



US 20240251619A1

(19) **United States**

(12) **Patent Application Publication**
LONG et al.

(10) **Pub. No.: US 2024/0251619 A1**

(43) **Pub. Date: Jul. 25, 2024**

(54) **DISPLAY SUBSTRATE AND DISPLAY DEVICE**

application No. PCT/CN2019/098938 on Aug. 1, 2019.

(71) Applicants: **CHENGDU BOE OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Chengdu (CN); **BOE TECHNOLOGY GROUP CO., LTD.**, Beijing (CN)

Publication Classification

(51) **Int. Cl.**
H10K 59/131 (2006.01)
H10K 50/844 (2006.01)
H10K 59/121 (2006.01)

(72) Inventors: **YUE LONG**, Beijing (CN); **Weiyun Huang**, Beijing (CN); **Chao Zeng**, Beijing (CN); **Meng Li**, Beijing (CN); **Yao Huang**, Beijing (CN)

(52) **U.S. Cl.**
CPC **H10K 59/131** (2023.02); **H10K 50/844** (2023.02); **H10K 59/121** (2023.02)

(21) Appl. No.: **18/619,330**

(22) Filed: **Mar. 28, 2024**

Related U.S. Application Data

(63) Continuation of application No. 17/255,888, filed on Dec. 23, 2020, now Pat. No. 11,991,905, filed as

(57) **ABSTRACT**

Provided is a display substrate including a base substrate, a plurality of pixel units, at least one first power line, a blocking structure, an auxiliary connection structure, a cathode layer, and a first organic pattern. A distance between a first connection position closer to a first portion of the at least one first power line and the blocking structure is arranged to be larger.

