



US 20230231519A1

(19) **United States**(12) **Patent Application Publication**  
SATO et al.(10) **Pub. No.: US 2023/0231519 A1**(43) **Pub. Date: Jul. 20, 2023**(54) **OSCILLATOR CIRCUIT AND  
TEMPERATURE COMPENSATION METHOD  
FOR OSCILLATOR CIRCUIT****G01K 1/02** (2006.01)**G05D 23/19** (2006.01)(52) **U.S. Cl.**CPC ..... **H03B 5/04** (2013.01); **H03B 5/362**  
(2013.01); **G01K 1/026** (2013.01); **G05D**  
**23/1931** (2013.01)(71) Applicant: **Asahi Kasei Microdevices**  
**Corporation, Tokyo (JP)**(72) Inventors: **TAKAYUKI SATO, Tokyo (JP);**  
**TAKESHI HAMADA, Tokyo (JP)**(73) Assignee: **Asahi Kasei Microdevices**  
**Corporation, Tokyo (JP)**(21) Appl. No.: **18/088,608**(22) Filed: **Dec. 25, 2022**(30) **Foreign Application Priority Data**

Jan. 14, 2022 (JP) ..... 2022-004683

**Publication Classification**(51) **Int. Cl.**  
**H03B 5/04** (2006.01)  
**H03B 5/36** (2006.01)

(57)

**ABSTRACT**

An oscillator circuit includes: a first temperature detector, detecting an internal temperature of the oscillator circuit; a current generator, generating a heater current so that the internal temperature matches a target temperature; a first and second heater, heating the resonator and the integrated circuit, respectively, based on the heater current; a second temperature detector, detecting a temperature of the integrated circuit; a first compensation voltage generation circuit, generating a first compensation voltage for compensating for a frequency variation due to a temperature change in the integrated circuit, based on a detection result of the second temperature detector; a second compensation voltage generation circuit, generating a second compensation voltage for compensating for a frequency variation due to a temperature change in the resonator, based on a detection result of the first temperature detector; and an oscillator, generating an oscillation signal based on the first and second compensation voltages.

