



US 20240180000A1

(19) **United States**

(12) **Patent Application Publication**
HE et al.

(10) **Pub. No.: US 2024/0180000 A1**

(43) **Pub. Date: May 30, 2024**

(54) **DISPLAY SUBSTRATE AND DISPLAY DEVICE**

Publication Classification

(71) Applicants: **Chengdu BOE Optoelectronics Technology Co., Ltd.**,
Chengdu, Sichuan (CN); **BOE Technology Group Co., Ltd.**, Beijing (CN)

(51) **Int. Cl.**
H10K 59/80 (2006.01)
H10K 102/00 (2006.01)
(52) **U.S. Cl.**
CPC **H10K 59/873** (2023.02); **H10K 2102/311** (2023.02)

(72) Inventors: **Qing HE**, Beijing (CN); **Zhiliang JIANG**, Beijing (CN); **Zaiyong LONG**, Beijing (CN); **Min CHEN**, Beijing (CN); **Ge WANG**, Beijing (CN); **Xiaomin YUAN**, Beijing (CN); **Qingqing YAN**, Beijing (CN); **Xiangnan PAN**, Beijing (CN)

(57) **ABSTRACT**

The display substrate comprises: a display area and a peripheral area located on the periphery of the display area, and a blocking dam and at least one blocking column are provided in the peripheral area. The display substrate comprises a base substrate, and a light-emitting structure layer and an encapsulation structure layer provided above the base substrate, the encapsulation structure layer is located on the side of the light-emitting structure layer away from the base substrate, the light-emitting structure layer comprises a cathode, and the encapsulation structure layer comprises an organic encapsulation layer. The at least one blocking column is located between the cathode and the blocking dam, and the orthographic projection of the at least one blocking column on the base substrate is located within the range of the orthographic projection of the organic encapsulation layer on the base substrate.

(21) Appl. No.: **18/283,460**

(22) PCT Filed: **Jan. 18, 2023**

(86) PCT No.: **PCT/CN2023/072919**

§ 371 (c)(1),

(2) Date: **Sep. 22, 2023**

(30) **Foreign Application Priority Data**

Jan. 28, 2022 (CN) 202210108262.4

